

Test report No:
NIE: 75755RAN.002A2

Assessment report

RF EXPOSURE REPORT ACCORDING TO FCC 47 CFR Part 2.1091

(*) Identification of item under evaluation	nRF91
(*) Trademark	nRF91
(*) Model and /or type reference	nRF9161
(*) Other identification of the product	IMEI TAC: 35829984 FCC ID: 2ANPO00NRF9161 IC ID: 24529-NRF9161 HW version: nRF9161 LACA A0A SW version: mfw_nrf91x1_2.0.0-77.beta
(*) Features	LTE Cat-M1, LTE NB1&NB2
(*) Manufacturer	NORDIC SEMICONDUCTOR ASA Otto Nielsens Veg 12 7052, Trondheim, NORWAY
Test method requested, standard	FCC 47 CFR Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices.
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Miguel Lacave Antennas Lab Manager
Date of issue	2023-11-07
Report template No	FAN36_01 (*) "Data provided by the client"

Index

Competences and guarantees3

General conditions3

Data provided by the client.....3

Identification of the client.....3

Document history4

Appendix A: FCC RF Exposure assessment result5

 General description of the equipment under evaluation6

 Maximum Antenna Gain determination for RF Exposure compliance7

Appendix B: FCC RF Exposure information10

 FCC RF Exposure evaluation11

 FCC MPE Evaluation.....12

 FCC Cellular bands limits12

Competences and guarantees

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification, S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification, S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification, S.A.U. at the time of performance of the test.

DEKRA Testing and Certification, S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Assessment Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification, S.A.U.

General conditions

1. This report is only referred to the item that has undergone the assessment.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification, S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification, S.A.U. and the Accreditation Bodies

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item under evaluation", "Trademark", "Model and/or type reference", "General description of the device", "Other identification of the product").
2. Maximum output power and request for evaluation under mobile exposure conditions.
3. The device under evaluation consists of an nRF91 module. The nRF9131 reference design is capable of LTE Cat-M1 and Cat-NB1 & NB2. The board includes nRF9131 IoT Chipset SoC. RF connectors are included in the board for cellular and GPS. DEKRA Testing and Certification, S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

Identification of the client

NORDIC SEMICONDUCTOR ASA
Otto Nielsens Veg 12
7052, Trondheim, NORWAY

Document history

Report number	Date	Description
75755RAN.002	2023-10-04	First release
75755RAN.002A1	2023-11-03	Second release: The device has been evaluated as a module instead a complete device with defined antenna. This modification test report cancels and replaces the test report 75755RAN.002.
75755RAN.002A2	2023-11-07	Third release: Band 26 has been deleted and band 8 has been included by customer request. This modification test report cancels and replaces the test report 75755RAN.002A1.

Appendix A: FCC RF Exposure assessment result

General description of the equipment under evaluation

Table 1 shows information used for the RF Evaluation, taking into account the following declared specifications for the device:

Description and technologies: the device under evaluation consists of an nRF91 module. The nRF9131 reference design is capable of LTE Cat-M1 and Cat-NB1 & NB2. The board includes nRF9131 IoT Chipset SoC. RF connectors are included in the board for cellular and GPS.

Evaluation Distance: As the equipment under evaluation is a module, a conservative evaluation distance of 20 cm has been used to perform the assessment.

Maximum output power:

- Values corresponding to maximum output power have been declared by the device manufacturer (maximum output power values stated in module manufacturer's Tune-up procedure document).
- Values corresponding to antenna gain have been declared by the device manufacturer (maximum peak gain stated in antenna manufacturer's datasheet).

Technology / Mode	Operating Band	Frequency under evaluation (MHz)	Maximum Conducted Output Power (Incl. Tune-Up) (dBm)	Antenna peak gain (dBi)
LTE Cat-M1	2	1850 - 1910	24.00	3.00
LTE Cat-M1	4	1710 - 1755	24.00	3.00
LTE Cat-M1	5	824 - 849	24.00	2.70
LTE Cat-M1	8	880 - 915	24.00	2.70
LTE Cat-M1	12	699 - 716	24.00	1.56
LTE Cat-M1	13	777 - 787	24.00	1.56
LTE Cat-M1	25	1850 - 1915	24.00	3.00
LTE Cat-M1	66	1710 - 1780	24.00	3.00
LTE Cat-M1	71	663 - 698	24.00	1.56
LTE Cat-M1	85	698 - 716	24.00	1.56
LTE NB-IoT	2	1850 - 1910	24.00	3.00
LTE NB-IoT	4	1710 - 1755	24.00	3.00
LTE NB-IoT	5	824 - 849	24.00	2.70
LTE NB-IoT	8	880 - 915	24.00	2.70
LTE NB-IoT	12	699 - 716	24.00	1.56
LTE NB-IoT	13	777 - 787	24.00	1.56
LTE NB-IoT	17	704 - 716	24.00	1.56
LTE NB-IoT	25	1850 - 1915	24.00	3.00
LTE NB-IoT	65	1920 - 2010	24.00	3.00
LTE NB-IoT	66	1710 - 1780	24.00	3.00
LTE NB-IoT	71	663 - 698	24.00	1.56
LTE NB-IoT	85	698 - 716	24.00	1.56

Table 1: Equipment specifications

Maximum Antenna Gain determination for RF Exposure compliance

Summary of maximum antenna gain values:

Maximum antenna gain for mobile operation to comply with MPE and EIRP limits (see Appendix B) shall not exceed the following values:

Technology / Mode	Operating Band	Frequency under evaluation (MHz)	Max Gain to comply with RF Exp Limits (dBi)	Max Gain to comply with EIRP Limits (dBi)	Maximum allowed Gain (worst case) (dBi)
LTE Cat-M1	2	1850 - 1910	13.01	9.00	9.00
LTE Cat-M1	4	1710 - 1755	13.01	6.00	6.00
LTE Cat-M1	5	824 - 849	10.41	16.60	10.41
LTE Cat-M1	8	880 - 915	10.70	12.92	10.70
LTE Cat-M1	12	699 - 716	9.70	12.92	9.70
LTE Cat-M1	13	777 - 787	10.16	12.92	10.16
LTE Cat-M1	25	1850 - 1915	13.01	9.00	9.00
LTE Cat-M1	66	1710 - 1780	13.01	6.00	6.00
LTE Cat-M1	71	663 - 698	9.47	12.92	9.47
LTE Cat-M1	85	698 - 716	9.69	12.92	9.69
LTE NB-IoT	2	1850 - 1910	13.01	9.00	9.00
LTE NB-IoT	4	1710 - 1755	13.01	6.00	6.00
LTE NB-IoT	5	824 - 849	10.41	16.60	10.41
LTE NB-IoT	8	880 - 915	10.70	12.92	10.70
LTE NB-IoT	12	699 - 716	9.70	12.92	9.70
LTE NB-IoT	13	777 - 787	10.16	12.92	10.16
LTE NB-IoT	17	704 - 716	9.73	12.92	9.73
LTE NB-IoT	25	1850 - 1915	13.01	9.00	9.00
LTE NB-IoT	65	1920 - 2010	13.01	-	13.01
LTE NB-IoT	66	1710 - 1780	13.01	6.00	6.00
LTE NB-IoT	71	663 - 698	9.47	12.92	9.47
LTE NB-IoT	85	698 - 716	9.69	12.92	9.69

Table 2: Maximum Antenna Gain values

Maximum Gain to meet FCC Radiofrequency radiation exposure limits:

Technology / Mode	Operating Band	Frequency under evaluation (MHz)	Distance (cm)	Power density for Gain = 0 dBi (mW/cm ²)	FCC General Population Limit (mW/cm ²)	Maximum Gain to comply with RF Exposure Limits (dBi)
LTE Cat-M1	2	1850 - 1910	20.00	0.05	1.00	13.01
LTE Cat-M1	4	1710 - 1755	20.00	0.05	1.00	13.01
LTE Cat-M1	5	824 - 849	20.00	0.05	0.55	10.41
LTE Cat-M1	8	880 - 915	20.00	0.05	0.59	10.70
LTE Cat-M1	12	699 - 716	20.00	0.05	0.47	9.70
LTE Cat-M1	13	777 - 787	20.00	0.05	0.52	10.16
LTE Cat-M1	25	1850 - 1915	20.00	0.05	1.00	13.01
LTE Cat-M1	66	1710 - 1780	20.00	0.05	1.00	13.01
LTE Cat-M1	71	663 - 698	20.00	0.05	0.44	9.47
LTE Cat-M1	85	698 - 716	20.00	0.05	0.47	9.69
LTE NB-IoT	2	1850 - 1910	20.00	0.05	1.00	13.01
LTE NB-IoT	4	1710 - 1755	20.00	0.05	1.00	13.01
LTE NB-IoT	5	824 - 849	20.00	0.05	0.55	10.41
LTE NB-IoT	8	880 - 915	20.00	0.05	0.59	10.70
LTE NB-IoT	12	699 - 716	20.00	0.05	0.47	9.70
LTE NB-IoT	13	777 - 787	20.00	0.05	0.52	10.16
LTE NB-IoT	17	704 - 716	20.00	0.05	0.47	9.73
LTE NB-IoT	25	1850 - 1915	20.00	0.05	1.00	13.01
LTE NB-IoT	65	1920 - 2010	20.00	0.05	1.00	13.01
LTE NB-IoT	66	1710 - 1780	20.00	0.05	1.00	13.01
LTE NB-IoT	71	663 - 698	20.00	0.05	0.44	9.47
LTE NB-IoT	85	698 - 716	20.00	0.05	0.47	9.69

Table 3: Maximum Antenna Gain values based on FCC MPE limits

Maximum Gain to meet FCC EIRP limits

Technology / Mode	Operating Band	Frequency under evaluation (MHz)	Maximum Output power (dBm)	EIRP Limits (dBm)	Maximum Gain to meet EIRP Limits (dBi)
LTE Cat-M1	2	1850 - 1910	24.00	33.00	9.00
LTE Cat-M1	4	1710 - 1755	24.00	30.00	6.00
LTE Cat-M1	5	824 - 849	24.00	40.60	16.60
LTE Cat-M1	8	880 - 915	24.00	36.92	12.92
LTE Cat-M1	12	699 - 716	24.00	36.92	12.92
LTE Cat-M1	13	777 - 787	24.00	36.92	12.92
LTE Cat-M1	25	1850 - 1915	24.00	33.00	9.00
LTE Cat-M1	66	1710 - 1780	24.00	30.00	6.00
LTE Cat-M1	71	663 - 698	24.00	36.92	12.92
LTE Cat-M1	85	698 - 716	24.00	36.92	12.92
LTE NB-IoT	2	1850 - 1910	24.00	33.00	9.00
LTE NB-IoT	4	1710 - 1755	24.00	30.00	6.00
LTE NB-IoT	5	824 - 849	24.00	40.60	16.60
LTE NB-IoT	8	880 - 915	24.00	36.92	12.92
LTE NB-IoT	12	699 - 716	24.00	36.92	12.92
LTE NB-IoT	13	777 - 787	24.00	36.92	12.92
LTE NB-IoT	17	704 - 716	24.00	36.92	12.92
LTE NB-IoT	25	1850 - 1915	24.00	33.00	9.00
LTE NB-IoT	65	1920 - 2010	24.00	-	-
LTE NB-IoT	66	1710 - 1780	24.00	30.00	6.00
LTE NB-IoT	71	663 - 698	24.00	36.92	12.92
LTE NB-IoT	85	698 - 716	24.00	36.92	12.92

Table 4: Maximum Antenna Gain values based on FCC EIRP limits

Appendix B: FCC RF Exposure information

FCC RF Exposure evaluation

Devices operating in standalone mobile device exposure conditions may contain a single transmitter or multiple transmitters that do not transmit simultaneously. A minimum test separation distance ≥ 20 cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be at least 20 cm and fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated. The minimum test separation distance required for a device to comply with mobile device exposure conditions must be clearly identified in the installation and operating instructions, for all installation and exposure conditions, to enable users and installers to comply with RF exposure requirements. For mobile devices that have the potential to operate in portable device exposure conditions, similar to the configurations described in § 2.1091(d)(4), a KDB inquiry is required to determine the SAR test requirements for demonstrating compliance.

When a device qualifies for the categorical exclusion provision of § 2.1091(c), the minimum test separation distance may be estimated, when applicable, by simple calculations according to plane-wave equivalent conditions, to ensure the transmitter and its antenna(s) can operate in manners that meet or exceed the estimated distance. The source-based time-averaged maximum radiated power, according to the maximum antenna gain, must be applied to calculate the field strength and power density required to establish the minimum test separation distance. When the estimated test separation distance becomes overly conservative and does not support compliance, MPE measurement or computational modeling may be used to determine the required minimum separation distance.

According to §1.1310 Radiofrequency radiation exposure limits, paragraph (e), the limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields are:

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	*100	6
3.0–30	1842/f	4.89/f	*900/f ²	6
30–300	61.4	0.163	1.0	6
300–1,500			f/300	6
1,500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*100	30
1.34–30	824/f	2.19/f	*180/f ²	30
30–300	27.5	0.073	0.2	30
300–1,500			f/1500	30
1,500–100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

FCC MPE Evaluation

Each supported transmission technology will be evaluated to determine if it is in compliance with limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields.

In order to perform the assessment, the following equations have been used for the calculations; these equations are accurate in the far-field of an antenna and will over-predict power density in the near field, where they could be used for making a "worst-case" or conservative prediction:

$$\text{Power density: } S[mW / cm^2] = \frac{P_{\max}[mW]}{4\pi R[cm]^2}$$

$$\text{Maximum gain to meet the MPE limit: } G_{\max}[dBi] = (10 * \log[S[mW / cm^2] * 4\pi R[cm]^2]) - P_{\max}[dBm]$$

S = power density

$P_{\max}$ = power input to the antenna

R = distance to the center of radiation of the antenna (evaluation distance)

$G_{\max}$ = power gain of the antenna in the direction of interest relative to an isotropic radiator

FCC Cellular bands limits

Maximum FCC EIRP limits are frequency-dependent and are stated into the FCC standards shown in the following table:

Standard	Frequency Band (MHz)	EIRP limit (W)	EIRP limit (dBm)
FCC 47 CFR §27.50 (c)	600-746	4.92	36.92
FCC 47 CFR §27.50 (b)	776-787	4.92	36.92
FCC Clause 90.542 (a) (7)	788-798	4.92	36.92
FCC 47 CFR §22.913	814-849	11.48	40.6
FCC 47 CFR §27.50 (d)	1710-1780	1.0	30.0
FCC 47 CFR §24.232	1850-1915	2.0	33.0
FCC 47 CFR §27.50 (a)	2305-2315	0.25 (average EIRP)	23.9
FCC 47 CFR §27.50 (h) (2)	2496-2690	2.0	33.0
FCC 47 CFR §96.41 (b)	3550-3700	0.2	23
FCC 47 CFR §27.5 (j)	3700-3980	1	30