



Test Graphs




11A-CDD_Ant6_5785




Date: 19.JAN.2022 16:30:11

11A-CDD_Ant7_5785




Date: 19.JAN.2022 16:31:46

11A-CDD_Ant6_5825



Date: 19.JAN.2022 16:34:11


11A-CDD_Ant7_5825



Date: 19.JAN.2022 16:35:43




11AC20-CDD_Ant6_5745




Date: 19.JAN.2022 17:36:00

11AC20-CDD_Ant7_5745



Date: 19.JAN.2022 17:37:35

11AC20-CDD_Ant6_5785



Date: 19.JAN.2022 17:39:23

11AC20-CDD_Ant7_5785




Date: 19.JAN.2022 17:40:57

11AC20-CDD_Ant6_5825



Date: 19.JAN.2022 17:42:42

11AC20-CDD_Ant7_5825




Date: 19.JAN.2022 17:44:18

11AC40-CDD_Ant6_5755



Date: 19.JAN.2022 18:08:07

11AC40-CDD_Ant7_5755



Date: 19.JAN.2022 18:09:36

11AC40-CDD_Ant6_5795



Date: 19.JAN.2022 18:13:18

11AC40-CDD_Ant7_5795



Date: 19.JAN.2022 18:14:47

11AC80-CDD_Ant6_5775



Date: 19.JAN.2022 18:29:13

11AC80-CDD_Ant7_5775




Date: 19.JAN.2022 18:30:41



Appendix B. AC Conducted Emission Test Results

Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-KS
Condition : FCC PART 15E LISN-060105-L LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.159	47.68	-17.84	65.52	37.20	0.02	10.46	QP
2	0.159	33.38	-22.14	55.52	22.90	0.02	10.46	Average
3 *	0.214	49.30	-13.75	63.05	38.90	0.05	10.35	QP
4	0.214	36.60	-16.45	53.05	26.20	0.05	10.35	Average
5	0.469	40.54	-16.00	56.54	30.20	0.10	10.24	QP
6	0.469	29.94	-16.60	46.54	19.60	0.10	10.24	Average
7	14.063	39.17	-20.83	60.00	28.49	0.29	10.39	QP
8	14.063	29.57	-20.43	50.00	18.89	0.29	10.39	Average
9	15.801	40.95	-19.05	60.00	30.21	0.33	10.41	QP
10	15.801	32.35	-17.65	50.00	21.61	0.33	10.41	Average
11	18.135	37.49	-22.51	60.00	26.61	0.42	10.46	QP
12	18.135	31.09	-18.91	50.00	20.21	0.42	10.46	Average



Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : FCC PART 15E LISN-060105-N NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.161	44.76	-20.67	65.43	34.20	0.11	10.45	QP
2	0.161	33.16	-22.27	55.43	22.60	0.11	10.45	Average
3 *	0.207	46.06	-17.26	63.32	35.60	0.10	10.36	QP
4	0.207	33.26	-20.06	53.32	22.80	0.10	10.36	Average
5	0.230	40.04	-22.40	62.44	29.60	0.10	10.34	QP
6	0.230	26.54	-25.90	52.44	16.10	0.10	10.34	Average
7	0.476	37.55	-18.86	56.41	27.20	0.11	10.24	QP
8	0.476	26.25	-20.16	46.41	15.90	0.11	10.24	Average
9	15.226	36.21	-23.79	60.00	25.49	0.32	10.40	QP
10	15.226	29.21	-20.79	50.00	18.49	0.32	10.40	Average
11	17.661	36.48	-23.52	60.00	25.60	0.43	10.45	QP
12	17.661	29.18	-20.82	50.00	18.30	0.43	10.45	Average

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



Appendix C. Radiated Spurious Emission

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
6+7		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		5625.6	55.96	-12.34	68.3	41.41	35.48	11.15	32.08	211	20	P	H
		5686.8	56.13	-39.43	95.56	41.42	35.55	11.22	32.06	211	20	P	H
		5706.4	57.06	-50.03	107.09	42.27	35.6	11.23	32.04	211	20	P	H
		5723.6	56.71	-62.4	119.11	41.88	35.62	11.25	32.04	211	20	P	H
		5746	103.03	-----	-----	88.12	35.65	11.27	32.01	211	20	P	H
		5746	96.4	-----	-----	81.49	35.65	11.27	32.01	211	20	A	H
		5625.6	54.81	-13.49	68.3	40.26	35.48	11.15	32.08	250	351	P	V
		5690.8	56.73	-41.79	98.52	41.99	35.58	11.22	32.06	250	351	P	V
		5718.8	55.8	-54.76	110.56	40.99	35.6	11.25	32.04	250	351	P	V
		5724.4	57.11	-63.82	120.93	42.28	35.62	11.25	32.04	250	351	P	V
		5746	98.93	-----	-----	84.02	35.65	11.27	32.01	250	351	P	V
		5746	93.86	-----	-----	78.95	35.65	11.27	32.01	250	351	A	V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 165 5825MHz		5853.2	57.11	-57.89	115	41.88	35.8	11.36	31.93	267	22	P	H
		5857.2	57.85	-52.43	110.28	42.6	35.8	11.38	31.93	267	22	P	H
		5922.8	56.61	-13.31	69.92	41.38	35.78	11.44	31.99	267	22	P	H
		5928	57.2	-11.1	68.3	41.98	35.77	11.44	31.99	267	22	P	H
		5824	102.55	-----	-----	87.4	35.75	11.35	31.95	267	22	P	H
		5824	95.43	-----	-----	80.28	35.75	11.35	31.95	267	22	A	H
		5852.4	57.08	-59.75	116.83	41.85	35.8	11.36	31.93	244	353	P	V
		5863.2	56.81	-51.79	108.6	41.59	35.79	11.38	31.95	244	353	P	V
		5893.2	57.09	-34.71	91.8	41.87	35.78	11.41	31.97	244	353	P	V
		5930.8	57.35	-10.95	68.3	42.13	35.77	11.44	31.99	244	353	P	V
		5824	100.5	-----	-----	85.35	35.75	11.35	31.95	244	353	P	V
		5824	93.69	-----	-----	78.54	35.75	11.35	31.95	244	353	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												


Band 4 5725~5850MHz
WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11488	47.09	-26.91	74	52.52	38.69	16.31	60.43	300	0	P	H
		11488	47.46	-26.54	74	52.89	38.69	16.31	60.43	100	0	P	V
802.11a CH 157 5785MHz		11565	46.79	-27.21	74	52.1	38.71	16.37	60.39	300	0	P	H
		11565	46.41	-27.59	74	51.72	38.71	16.37	60.39	100	0	P	V
802.11a CH 165 5825MHz		11653	46.82	-27.18	74	51.94	38.73	16.47	60.32	300	0	P	H
		11653	46.97	-27.03	74	52.09	38.73	16.47	60.32	100	0	P	V
Remark		1. No other spurious found. 2. All results are PASS against Peak and Average limit line.											



Band 4 5725~5850MHz

WIFI 802.11ac VHT40 (Band Edge @ 3m)

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40 CH 151 5755MHz		5641.2	55.84	-12.46	68.3	41.28	35.5	11.16	32.1	205	37	P	H
		5684.8	56.78	-37.31	94.09	42.07	35.55	11.22	32.06	205	37	P	H
		5711.2	57.3	-51.14	108.44	42.51	35.6	11.23	32.04	205	37	P	H
		5723.6	56.15	-62.96	119.11	41.32	35.62	11.25	32.04	205	37	P	H
		5851.2	56.36	-63.2	119.56	41.13	35.8	11.36	31.93	205	37	P	H
		5855.2	56.49	-54.35	110.84	41.24	35.8	11.38	31.93	205	37	P	H
		5892.8	56.67	-35.42	92.09	41.44	35.79	11.41	31.97	205	37	P	H
		5951.6	57.15	-11.15	68.3	41.95	35.76	11.45	32.01	205	37	P	H
		5752	101.72	-----	-----	86.79	35.65	11.29	32.01	205	37	P	H
		5752	94.78	-----	-----	79.85	35.65	11.29	32.01	205	37	A	H
		5641.2	55.37	-12.93	68.3	40.81	35.5	11.16	32.1	252	349	P	V
		5658.4	56.42	-18.12	74.54	41.79	35.53	11.18	32.08	252	349	P	V
		5716.8	57.05	-52.96	110.01	42.26	35.6	11.23	32.04	252	349	P	V
		5722.4	55.74	-60.63	116.37	40.93	35.6	11.25	32.04	252	349	P	V
		5854.8	55.47	-55.89	111.36	40.22	35.8	11.38	31.93	252	349	P	V
		5868.8	56.48	-50.55	107.03	41.26	35.79	11.38	31.95	252	349	P	V
		5906	57.34	-24.98	82.32	42.1	35.78	11.43	31.97	252	349	P	V
		5944	56.18	-12.12	68.3	40.97	35.77	11.45	32.01	252	349	P	V
		5758	98.31	-----	-----	83.34	35.67	11.29	31.99	252	349	P	V
		5758	91.29	-----	-----	76.32	35.67	11.29	31.99	252	349	A	V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40 CH 159 5795MHz		5610	55.98	-12.32	68.3	41.46	35.47	11.13	32.08	180	18	P	H
		5692.8	56.95	-43.04	99.99	42.21	35.58	11.22	32.06	180	18	P	H
		5707.6	57.45	-49.98	107.43	42.66	35.6	11.23	32.04	180	18	P	H
		5722.8	55.8	-61.48	117.28	40.97	35.62	11.25	32.04	180	18	P	H
		5850	57.8	-64.5	122.3	42.57	35.8	11.36	31.93	180	18	P	H
		5871.2	57.31	-49.05	106.36	42.08	35.79	11.39	31.95	180	18	P	H
		5885.6	56.92	-40.51	97.43	41.71	35.79	11.39	31.97	180	18	P	H
		5928.8	55.93	-12.37	68.3	40.71	35.77	11.44	31.99	180	18	P	H
		5794	101.9	-----	-----	86.83	35.72	11.32	31.97	180	18	P	H
		5794	93.71	-----	-----	78.64	35.72	11.32	31.97	180	18	A	H
		5610.8	56.27	-12.03	68.3	41.75	35.47	11.13	32.08	400	360	P	V
		5687.2	56.95	-38.91	95.86	42.24	35.55	11.22	32.06	400	360	P	V
		5715.6	55.9	-53.77	109.67	41.11	35.6	11.23	32.04	400	360	P	V
		5722.8	55.55	-61.73	117.28	40.72	35.62	11.25	32.04	400	360	P	V
		5852.8	56.32	-59.6	115.92	41.09	35.8	11.36	31.93	400	360	P	V
		5856.4	56.33	-54.18	110.51	41.08	35.8	11.38	31.93	400	360	P	V
		5877.6	56.87	-46.5	103.37	41.64	35.79	11.39	31.95	400	360	P	V
		5959.6	56.82	-11.48	68.3	41.6	35.76	11.47	32.01	400	360	P	V
		5800	99.34	-----	-----	84.27	35.72	11.32	31.97	400	360	P	V
		5800	91.03	-----	-----	75.96	35.72	11.32	31.97	400	360	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**Band 4 5725~5850MHz****WIFI 802.11ac VHT40 (Harmonic @ 3m)**

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40		11510	46.56	-27.44	74	51.97	38.7	16.32	60.43	300	0	P	H
CH 151 5755MHz		11510	47.22	-26.78	74	52.63	38.7	16.32	60.43	100	0	P	V
802.11ac VHT40		11587	46.33	-27.67	74	51.57	38.72	16.41	60.37	300	0	P	H
CH 159 5795MHz		11587	47.08	-26.92	74	52.32	38.72	16.41	60.37	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**Band 4 5725~5850MHz****WIFI 802.11ac VHT20 (Band Edge @ 3m)**

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT20 CH 149 5745MHz		5647.6	55.09	-13.21	68.3	40.53	35.5	11.16	32.1	302	39	P	H
		5696.8	57.3	-45.64	102.94	42.56	35.58	11.22	32.06	302	39	P	H
		5713.2	56.6	-52.4	109	41.81	35.6	11.23	32.04	302	39	P	H
		5724.8	60.24	-61.6	121.84	45.41	35.62	11.25	32.04	302	39	P	H
		5746	102.13	-----	-----	87.22	35.65	11.27	32.01	302	39	P	H
		5746	96.13	-----	-----	81.22	35.65	11.27	32.01	302	39	A	H
		5640	57.32	-10.98	68.3	42.76	35.5	11.16	32.1	130	360	P	V
		5673.6	56.17	-29.63	85.8	41.5	35.55	11.2	32.08	130	360	P	V
		5706.4	57.74	-49.35	107.09	42.95	35.6	11.23	32.04	130	360	P	V
		5720	57.07	-53.83	110.9	42.26	35.6	11.25	32.04	130	360	P	V
		5740	99.92	-----	-----	85.01	35.65	11.27	32.01	130	360	P	V
		5740	94.07	-----	-----	79.16	35.65	11.27	32.01	130	360	A	V



WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT20 CH 165 5825MHz		5850.4	56.67	-64.72	121.39	41.44	35.8	11.36	31.93	256	41	P	H
		5858.8	56.68	-53.15	109.83	41.45	35.8	11.38	31.95	256	41	P	H
		5896	56.73	-32.99	89.72	41.51	35.78	11.41	31.97	256	41	P	H
		5926.8	57.23	-11.07	68.3	42	35.78	11.44	31.99	256	41	P	H
		5824	102.94	-----	-----	87.79	35.75	11.35	31.95	256	41	P	H
		5824	94.98	-----	-----	79.83	35.75	11.35	31.95	256	41	A	H
		5852	56.47	-61.27	117.74	41.24	35.8	11.36	31.93	113	360	P	V
		5863.6	57.07	-51.42	108.49	41.85	35.79	11.38	31.95	113	360	P	V
		5921.6	57.05	-13.76	70.81	41.82	35.78	11.44	31.99	113	360	P	V
		5995.2	56.89	-11.41	68.3	41.69	35.75	11.5	32.05	113	360	P	V
		5824	99.01	-----	-----	83.86	35.75	11.35	31.95	113	360	P	V
		5824	91.44	-----	-----	76.29	35.75	11.35	31.95	113	360	A	V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT20 (Harmonic @ 3m)

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT20		11488	46.71	-27.29	74	52.14	38.69	16.31	60.43	300	0	P	H
CH 149 5745MHz		11488	46.99	-27.01	74	52.42	38.69	16.31	60.43	100	0	P	V
802.11ac VHT20		11565	47.5	-26.5	74	52.81	38.71	16.37	60.39	300	0	P	H
CH 157 5785MHz		11565	47.61	-26.39	74	52.92	38.71	16.37	60.39	100	0	P	V
802.11ac VHT20		11653	47.26	-26.74	74	52.38	38.73	16.47	60.32	300	0	P	H
CH 165 5825MHz		11653	47.22	-26.78	74	52.34	38.73	16.47	60.32	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz		5600.4	56.03	-12.27	68.3	41.52	35.45	11.13	32.07	213	39	P	H
		5696.8	57.41	-45.53	102.94	42.67	35.58	11.22	32.06	213	39	P	H
		5718.8	58.82	-51.74	110.56	44.01	35.6	11.25	32.04	213	39	P	H
		5722.4	57.81	-58.56	116.37	43	35.6	11.25	32.04	213	39	P	H
		5854.8	56.23	-55.13	111.36	40.98	35.8	11.38	31.93	213	39	P	H
		5865.6	56.59	-51.34	107.93	41.37	35.79	11.38	31.95	213	39	P	H
		5909.2	57.17	-22.79	79.96	41.95	35.78	11.43	31.99	213	39	P	H
		5944.4	57.03	-11.27	68.3	41.83	35.76	11.45	32.01	213	39	P	H
		5782	98.54	-----	-----	83.51	35.7	11.3	31.97	213	39	P	H
		5782	90.86	-----	-----	75.83	35.7	11.3	31.97	213	39	A	H
		5615.2	55.51	-12.79	68.3	40.99	35.47	11.13	32.08	251	350	P	V
		5672.8	55.8	-29.41	85.21	41.13	35.55	11.2	32.08	251	350	P	V
		5706	56.24	-50.74	106.98	41.45	35.6	11.23	32.04	251	350	P	V
		5722	55.42	-60.04	115.46	40.61	35.6	11.25	32.04	251	350	P	V
		5853.6	57.06	-57.03	114.09	41.81	35.8	11.38	31.93	251	350	P	V
		5866.8	56.54	-51.05	107.59	41.32	35.79	11.38	31.95	251	350	P	V
		5899.2	56.3	-31.05	87.35	41.08	35.78	11.41	31.97	251	350	P	V
		5943.6	56.65	-11.65	68.3	41.44	35.77	11.45	32.01	251	350	P	V
		5764	95.73	-----	-----	80.76	35.67	11.29	31.99	251	350	P	V
		5764	87.71	-----	-----	72.74	35.67	11.29	31.99	251	350	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**Band 4 5725~5850MHz****WIFI 802.11ac VHT80 (Harmonic @ 3m)**

WIFI Ant. 6+7	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80		11554	47.3	-26.7	74	52.61	38.71	16.37	60.39	300	0	P	H
CH 155 5775MHz		11554	46.15	-27.85	74	51.46	38.71	16.37	60.39	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

WIFI 802.11a (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
6+7		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a LF		30	21.07	-18.93	40	27.12	24.6	0.58	31.23	-----	-----	P	H
		160.95	19	-24.5	43.5	32.31	15.97	2.04	31.32	-----	-----	P	H
		291.9	26.17	-19.83	46	35.66	19.34	2.77	31.6	-----	-----	P	H
		323.91	26.26	-19.74	46	35.18	19.8	2.92	31.64	-----	-----	P	H
		620.73	25.73	-20.27	46	28.09	24.86	4.06	31.28	-----	-----	P	H
		892.33	28.38	-17.62	46	28.04	26.65	4.87	31.18	-----	-----	P	H
		30.97	26.98	-13.02	40	33.6	24.04	0.59	31.25	-----	-----	P	V
		191.02	17.6	-25.9	43.5	31.66	15.04	2.24	31.34	-----	-----	P	V
		280.26	21.34	-24.66	46	30.76	19.4	2.71	31.53	-----	-----	P	V
		518.88	22.86	-23.14	46	26.6	24	3.7	31.44	-----	-----	P	V
		751.68	27.73	-18.27	46	28.68	25.7	4.46	31.11	-----	-----	P	V
		896.21	28.32	-17.68	46	27.92	26.68	4.88	31.16	-----	-----	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

**Note symbol**

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
 = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
 = 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
 = 55.45 (dBμV/m)
2. Over Limit(dB)
 = Level(dBμV/m) – Limit Line(dBμV/m)
 = 55.45(dBμV/m) – 74(dBμV/m)
 = -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
 = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
 = 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
 = 43.54 (dBμV/m)
2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)
 = 43.54(dBμV/m) – 54(dBμV/m)
 = -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.





Appendix D. Radiated Spurious Emission Plots

Note symbol



-L	Low channel location
-R	High channel location





Band 4 - 5725~5850MHz
WIFI 802.11a (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
6+7	Horizontal	Fundamental
Peak	 Site : 802.11a-45 Condition : SG BAND4 3m 3117 SN 00218642 HORIZONTAL Project : RBW:1000.0000Hz VBW:3000.0000Hz SMT:Auto Mode : (FBI)20010 Plane : V ZNEI : Single-directivity PowerSetting : 18 Over Limit Read CableAntenna Preamp A/Pos T/Pos Freq Level Limit Line Level Loss Factor Factor Remark MHz dBuV/m dB dBuV/m dB dB/m dB cm deg 1 5625.00 55.96 -12.34 66.30 41.41 11.25 35.60 32.80 211 20 Peak 2 5680.00 56.13 -30.43 95.56 41.42 11.22 35.52 32.80 211 20 Peak 3 5700.00 57.96 -50.83 187.89 42.27 11.23 35.60 32.84 211 20 Peak 4 5723.00 56.72 -62.40 139.11 41.68 11.25 35.62 32.84 211 20 Peak	 Site : 802.11a-45 Condition : SG BAND4 3m 3117 SN 00218642 HORIZONTAL Project : RBW:1000.0000Hz VBW:3000.0000Hz SMT:Auto Mode : (FBI)20010 Plane : V ZNEI : Single-directivity PowerSetting : 18 Over Limit Read CableAntenna Preamp A/Pos T/Pos Freq Level Limit Line Level Loss Factor Factor Remark MHz dBuV/m dB dBuV/m dB dB/m dB cm deg 1 5745.00 103.80 -19.27 122.30 88.32 11.27 35.65 32.81 211 20 Peak 2 5746.00 96.40 81.40 11.27 35.65 32.81 211 20 Average








WIFI	Band 4 5725~5850MHz Band Edge @ 3m																																																																																																
ANT	802.11a CH149 5745MHz																																																																																																
6+7	Vertical	Fundamental																																																																																															
Peak	 No. 1002, Pengci North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China Tel: +86-512-75989958 Fax: +86-512-75989958 http://www.sjporton.com.cn Site : 802.086-K5 Condition : SG BAND4 3m 3117 SN 00218642 VERTICAL Project : RBU:1000.0000Hz VBU:3000.0000Hz SW:Auto Mode : 30 Plane : V Polar : Single-directivity Polarization : 80 PowerSetting : 10 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Read</th><th>CableAntenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5625.00</td><td>54.81</td><td>-13.49</td><td>60.30</td><td>40.26</td><td>11.55</td><td>35.48</td><td>32.80</td><td>351 Peak</td></tr><tr><td>2</td><td>5698.00</td><td>56.73</td><td>-61.79</td><td>95.52</td><td>41.99</td><td>11.22</td><td>35.50</td><td>32.80</td><td>351 Peak</td></tr><tr><td>3</td><td>5728.00</td><td>55.80</td><td>-54.70</td><td>110.56</td><td>40.99</td><td>11.25</td><td>35.60</td><td>32.84</td><td>351 Peak</td></tr><tr><td>4</td><td>5745.00</td><td>57.11</td><td>-63.82</td><td>120.93</td><td>42.18</td><td>11.25</td><td>35.62</td><td>32.84</td><td>351 Peak</td></tr></table>  No. 1002, Pengci North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China Tel: +86-512-75989958 Fax: +86-512-75989958 http://www.sjporton.com.cn Site : 802.086-K5 Condition : SG BAND4 3m 3117 SN 00218642 VERTICAL Project : RBU:1000.0000Hz VBU:3000.0000Hz SW:Auto Mode : 30 Plane : V Polar : Single-directivity Polarization : 80 PowerSetting : 10 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Read</th><th>CableAntenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5746.00</td><td>98.93</td><td>-23.37</td><td>122.30</td><td>84.02</td><td>11.27</td><td>35.65</td><td>32.81</td><td>351 Peak</td></tr><tr><td>2</td><td>5746.00</td><td>93.06</td><td>-----</td><td>79.95</td><td>11.27</td><td>35.65</td><td>32.81</td><td>250</td><td>351 Average</td></tr></table>	Freq	Level	Limit	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg	1	5625.00	54.81	-13.49	60.30	40.26	11.55	35.48	32.80	351 Peak	2	5698.00	56.73	-61.79	95.52	41.99	11.22	35.50	32.80	351 Peak	3	5728.00	55.80	-54.70	110.56	40.99	11.25	35.60	32.84	351 Peak	4	5745.00	57.11	-63.82	120.93	42.18	11.25	35.62	32.84	351 Peak	Freq	Level	Limit	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg	1	5746.00	98.93	-23.37	122.30	84.02	11.27	35.65	32.81	351 Peak	2	5746.00	93.06	-----	79.95	11.27	35.65	32.81	250	351 Average
Freq	Level	Limit	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark																																																																																									
MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg																																																																																									
1	5625.00	54.81	-13.49	60.30	40.26	11.55	35.48	32.80	351 Peak																																																																																								
2	5698.00	56.73	-61.79	95.52	41.99	11.22	35.50	32.80	351 Peak																																																																																								
3	5728.00	55.80	-54.70	110.56	40.99	11.25	35.60	32.84	351 Peak																																																																																								
4	5745.00	57.11	-63.82	120.93	42.18	11.25	35.62	32.84	351 Peak																																																																																								
Freq	Level	Limit	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark																																																																																									
MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg																																																																																									
1	5746.00	98.93	-23.37	122.30	84.02	11.27	35.65	32.81	351 Peak																																																																																								
2	5746.00	93.06	-----	79.95	11.27	35.65	32.81	250	351 Average																																																																																								



WIFI	Band 4 5725~5850MHz Band Edge @ 3m																																																																																																					
ANT	802.11a CH165 5825MHz																																																																																																					
6+7	Horizontal	Fundamental																																																																																																				
Peak	 No. 1899, Fengqi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China Tel: +86-512-57900158 Fax: +86-512-57900958 http://www.sporton.com.cn Date: 1  Site : 80CH06-15 Condition : 5G BAND4 3m 3117 SN 08218642 HORIZONTAL Project : R&D:1000~8000Hz VSW:3000~8000Hz SW:Auto Mode : FPL100210 Plane : Y ZNEI : Single-directivity Powersetting : 18 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Read</th><th>Cable</th><th>Antenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5853.20</td><td>57.11</td><td>57.89</td><td>115.00</td><td>41.88</td><td>11.36</td><td>35.80</td><td>31.93</td><td>22 Peak</td></tr><tr><td>2</td><td>5857.20</td><td>57.89</td><td>52.43</td><td>119.28</td><td>42.60</td><td>11.38</td><td>35.80</td><td>31.93</td><td>22 Peak</td></tr><tr><td>3</td><td>5922.00</td><td>56.83</td><td>53.31</td><td>69.92</td><td>41.38</td><td>11.44</td><td>35.79</td><td>31.99</td><td>22 Peak</td></tr><tr><td>4</td><td>5928.00</td><td>57.20</td><td>53.10</td><td>66.50</td><td>41.98</td><td>11.44</td><td>35.77</td><td>31.99</td><td>22 Peak</td></tr></table>	Freq	Level	Limit	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg		1	5853.20	57.11	57.89	115.00	41.88	11.36	35.80	31.93	22 Peak	2	5857.20	57.89	52.43	119.28	42.60	11.38	35.80	31.93	22 Peak	3	5922.00	56.83	53.31	69.92	41.38	11.44	35.79	31.99	22 Peak	4	5928.00	57.20	53.10	66.50	41.98	11.44	35.77	31.99	22 Peak	 No. 1899, Fengqi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China Tel: +86-512-57900158 Fax: +86-512-57900958 http://www.sporton.com.cn Date: 2  Site : 80CH06-15 Condition : 5G BAND4 3m 3117 SN 08218642 HORIZONTAL Project : R&D:1000~8000Hz VSW:3000~8000Hz SW:Auto Mode : FPL100210 Plane : Y ZNEI : Single-directivity Powersetting : 18 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Read</th><th>Cable</th><th>Antenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5824.00</td><td>182.55</td><td>-19.75</td><td>122.30</td><td>87.40</td><td>11.35</td><td>35.75</td><td>31.95</td><td>22 Peak</td></tr><tr><td>2</td><td>5824.00</td><td>195.43</td><td>.....</td><td>80.28</td><td>11.35</td><td>35.75</td><td>31.95</td><td>207</td><td>22 Average</td></tr></table>	Freq	Level	Limit	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg		1	5824.00	182.55	-19.75	122.30	87.40	11.35	35.75	31.95	22 Peak	2	5824.00	195.43		80.28	11.35	35.75	31.95	207	22 Average
Freq	Level	Limit	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark																																																																																													
MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg																																																																																														
1	5853.20	57.11	57.89	115.00	41.88	11.36	35.80	31.93	22 Peak																																																																																													
2	5857.20	57.89	52.43	119.28	42.60	11.38	35.80	31.93	22 Peak																																																																																													
3	5922.00	56.83	53.31	69.92	41.38	11.44	35.79	31.99	22 Peak																																																																																													
4	5928.00	57.20	53.10	66.50	41.98	11.44	35.77	31.99	22 Peak																																																																																													
Freq	Level	Limit	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark																																																																																													
MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg																																																																																														
1	5824.00	182.55	-19.75	122.30	87.40	11.35	35.75	31.95	22 Peak																																																																																													
2	5824.00	195.43		80.28	11.35	35.75	31.95	207	22 Average																																																																																													





WIFI	Band 4 5725~5850MHz Band Edge @ 3m																																																																																																					
ANT	802.11a CH165 5825MHz																																																																																																					
6+7	Vertical	Fundamental																																																																																																				
Peak	 No. 1899, Fengqi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Date: 3  Site : 802.11a-15 Condition : SG BAND4 3m 3117 SN 08218642 VERTICAL Project : R&D:1000~8000Hz VSW:3000~8000Hz SW:Auto Mode : S2 Plane : V ZNEI : Single-directivity Powersetting : 18 <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Read</th><th>Cable/Antenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBm/Vm</th><th>dB</th><th>dBm/Vm</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5825.40</td><td>57.80</td><td>-59.79</td><td>116.63</td><td>41.65</td><td>11.36</td><td>35.80</td><td>31.93</td><td>244</td><td>353 Peak</td></tr><tr><td>2</td><td>5803.20</td><td>56.81</td><td>-51.79</td><td>106.00</td><td>41.59</td><td>11.38</td><td>35.75</td><td>31.95</td><td>244</td><td>353 Peak</td></tr><tr><td>3</td><td>5893.20</td><td>57.89</td><td>-34.71</td><td>91.80</td><td>41.87</td><td>11.41</td><td>35.79</td><td>31.97</td><td>244</td><td>353 Peak</td></tr><tr><td>4</td><td>5930.80</td><td>57.35</td><td>-38.95</td><td>66.30</td><td>42.13</td><td>11.44</td><td>35.77</td><td>31.99</td><td>244</td><td>353 Peak</td></tr></tbody></table>  No. 1899, Fengqi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China tel: +86-512-57900158 fax: +86-512-57900958 http://www.sporton.com.cn Date: 4  Site : 802.11a-15 Condition : SG BAND4 3m 3117 SN 08218642 VERTICAL Project : R&D:1000~8000Hz VSW:3000~8000Hz SW:Auto Mode : S2 Plane : V ZNEI : Single-directivity Powersetting : 18 <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Read</th><th>Cable/Antenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBm/Vm</th><th>dB</th><th>dBm/Vm</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5824.00</td><td>100.50</td><td>-21.80</td><td>122.30</td><td>85.35</td><td>11.35</td><td>35.75</td><td>31.95</td><td>244</td><td>353 Peak</td></tr><tr><td>2</td><td>5824.00</td><td>93.09</td><td>.....</td><td>79.54</td><td>11.35</td><td>35.75</td><td>31.95</td><td>244</td><td>353 Average</td></tr></tbody></table>	Freq	Level	Limit	Read	Cable/Antenna	Preamp	A/Pos	T/Pos	Remark	MHz	dBm/Vm	dB	dBm/Vm	dB	dB/m	dB	cm	deg	1	5825.40	57.80	-59.79	116.63	41.65	11.36	35.80	31.93	244	353 Peak	2	5803.20	56.81	-51.79	106.00	41.59	11.38	35.75	31.95	244	353 Peak	3	5893.20	57.89	-34.71	91.80	41.87	11.41	35.79	31.97	244	353 Peak	4	5930.80	57.35	-38.95	66.30	42.13	11.44	35.77	31.99	244	353 Peak	Freq	Level	Limit	Read	Cable/Antenna	Preamp	A/Pos	T/Pos	Remark	MHz	dBm/Vm	dB	dBm/Vm	dB	dB/m	dB	cm	deg	1	5824.00	100.50	-21.80	122.30	85.35	11.35	35.75	31.95	244	353 Peak	2	5824.00	93.09		79.54	11.35	35.75	31.95	244	353 Average
Freq	Level	Limit	Read	Cable/Antenna	Preamp	A/Pos	T/Pos	Remark																																																																																														
MHz	dBm/Vm	dB	dBm/Vm	dB	dB/m	dB	cm	deg																																																																																														
1	5825.40	57.80	-59.79	116.63	41.65	11.36	35.80	31.93	244	353 Peak																																																																																												
2	5803.20	56.81	-51.79	106.00	41.59	11.38	35.75	31.95	244	353 Peak																																																																																												
3	5893.20	57.89	-34.71	91.80	41.87	11.41	35.79	31.97	244	353 Peak																																																																																												
4	5930.80	57.35	-38.95	66.30	42.13	11.44	35.77	31.99	244	353 Peak																																																																																												
Freq	Level	Limit	Read	Cable/Antenna	Preamp	A/Pos	T/Pos	Remark																																																																																														
MHz	dBm/Vm	dB	dBm/Vm	dB	dB/m	dB	cm	deg																																																																																														
1	5824.00	100.50	-21.80	122.30	85.35	11.35	35.75	31.95	244	353 Peak																																																																																												
2	5824.00	93.09		79.54	11.35	35.75	31.95	244	353 Average																																																																																													





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT40 CH159 5795MHz	
6+7	Horizontal	Fundamental
Peak	Site : 83086-KS Condition : SG BAND4 3m 3117 SN 08218642 HORIZONTAL Project : RBU:1000.000KHz VBU:3000.000KHz SW:Auto Mode : FPL100310 Plane : Y ZNEI : Single-directivity PowerSetting : 18  1560.00 55.98 -12.32 68.38 41.46 11.33 35.47 32.88 180 18 Peak 2 5925.00 56.95 -41.88 99.99 42.21 11.22 35.58 32.88 180 18 Peak 3 5787.00 57.45 -49.88 187.43 42.66 11.23 35.68 32.84 180 18 Peak 4 5722.00 55.89 -61.48 117.28 49.97 11.25 35.62 32.84 180 18 Peak	Site : 83086-KS Condition : SG BAND4 3m 3117 SN 08218642 HORIZONTAL Project : RBU:1000.000KHz VBU:3000.000KHz SW:Auto Mode : FPL100310 Plane : Y ZNEI : Single-directivity PowerSetting : 18  1 5794.00 181.99 -20.48 122.38 86.83 11.32 35.72 31.97 180 18 Peak 2 5794.00 181.71 78.64 11.32 35.72 31.97 180 18 Average
Peak	Site : 83086-KS Condition : SG BAND4 3m 3117 SN 08218642 HORIZONTAL Project : RBU:1000.000KHz VBU:3000.000KHz SW:Auto Mode : FPL100310 Plane : Y ZNEI : Single-directivity PowerSetting : 18  1 5858.00 57.88 -64.58 122.38 42.57 11.36 35.88 31.93 180 18 Peak 2 5871.28 57.31 -49.88 186.36 42.88 11.39 35.79 31.95 180 18 Peak 3 5825.00 56.92 -48.51 97.43 41.71 11.39 35.79 31.97 180 18 Peak 4 5928.00 55.95 -12.37 68.38 49.71 11.44 35.77 31.99 180 18 Peak	Left blank





Band 4 5725~5850MHz
WIFI 802.11ac VHT20 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m																																																																																																															
ANT	802.11ac VHT20 CH149 5745MHz																																																																																																															
6+7	Horizontal	Fundamental																																																																																																														
Peak	 No. 3899, Pengji North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China Tel: +86-512-7700010 Fax: +86-512-7700010 http://www.sporton.com.cn Site : 83CH06-K5 Condition : 5G BAND4 3m 3117 SW 00218042 HORIZONTAL Project : 802.11ac VHT20 CH149 5745MHz SUT Auto Model : (F)100310 Plane : 13 Plane : V Single-directivity DNEI : 10 PowerSetting : 10 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Band</th><th>CableLoss</th><th>Antenna</th><th>Pramp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5647.68</td><td>55.89</td><td>-13.21</td><td>68.38</td><td>40.53</td><td>11.16</td><td>35.58</td><td>32.18</td><td>302</td><td>39 Peak</td></tr><tr><td>2</td><td>5696.88</td><td>57.38</td><td>-45.64</td><td>102.94</td><td>42.56</td><td>11.22</td><td>35.58</td><td>32.80</td><td>302</td><td>39 Peak</td></tr><tr><td>3</td><td>5713.28</td><td>56.68</td><td>-42.48</td><td>100.80</td><td>41.81</td><td>11.23</td><td>35.68</td><td>32.84</td><td>302</td><td>39 Peak</td></tr><tr><td>4</td><td>5724.88</td><td>68.24</td><td>-41.68</td><td>121.64</td><td>45.41</td><td>11.25</td><td>35.62</td><td>32.84</td><td>302</td><td>39 Peak</td></tr></table>		Freq	Level	Limit	Band	CableLoss	Antenna	Pramp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dB	dB	dB	cm	deg		1	5647.68	55.89	-13.21	68.38	40.53	11.16	35.58	32.18	302	39 Peak	2	5696.88	57.38	-45.64	102.94	42.56	11.22	35.58	32.80	302	39 Peak	3	5713.28	56.68	-42.48	100.80	41.81	11.23	35.68	32.84	302	39 Peak	4	5724.88	68.24	-41.68	121.64	45.41	11.25	35.62	32.84	302	39 Peak	 No. 3899, Pengji North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China Tel: +86-512-7700010 Fax: +86-512-7700010 http://www.sporton.com.cn Site : 83CH06-K5 Condition : 5G BAND4 3m 3117 SW 00218042 HORIZONTAL Project : 802.11ac VHT20 CH149 5745MHz SUT Auto Model : (F)100310 Plane : 13 Plane : V Single-directivity DNEI : 10 PowerSetting : 10 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Band</th><th>CableLoss</th><th>Antenna</th><th>Pramp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5746.00</td><td>182.13</td><td>-20.17</td><td>122.38</td><td>87.22</td><td>11.27</td><td>35.65</td><td>32.81</td><td>302</td><td>39 Peak</td></tr><tr><td>2</td><td>5746.00</td><td>96.13</td><td>-----</td><td>81.22</td><td>11.27</td><td>35.65</td><td>32.81</td><td>302</td><td>39</td><td>Average</td></tr></table>		Freq	Level	Limit	Band	CableLoss	Antenna	Pramp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dB	dB	dB	cm	deg		1	5746.00	182.13	-20.17	122.38	87.22	11.27	35.65	32.81	302	39 Peak	2	5746.00	96.13	-----	81.22	11.27	35.65	32.81	302	39	Average
	Freq	Level	Limit	Band	CableLoss	Antenna	Pramp	A/Pos	T/Pos	Remark																																																																																																						
	MHz	dBuV/m	dB	dBuV/m	dB	dB	dB	cm	deg																																																																																																							
1	5647.68	55.89	-13.21	68.38	40.53	11.16	35.58	32.18	302	39 Peak																																																																																																						
2	5696.88	57.38	-45.64	102.94	42.56	11.22	35.58	32.80	302	39 Peak																																																																																																						
3	5713.28	56.68	-42.48	100.80	41.81	11.23	35.68	32.84	302	39 Peak																																																																																																						
4	5724.88	68.24	-41.68	121.64	45.41	11.25	35.62	32.84	302	39 Peak																																																																																																						
	Freq	Level	Limit	Band	CableLoss	Antenna	Pramp	A/Pos	T/Pos	Remark																																																																																																						
	MHz	dBuV/m	dB	dBuV/m	dB	dB	dB	cm	deg																																																																																																							
1	5746.00	182.13	-20.17	122.38	87.22	11.27	35.65	32.81	302	39 Peak																																																																																																						
2	5746.00	96.13	-----	81.22	11.27	35.65	32.81	302	39	Average																																																																																																						





WIFI	Band 4 5725~5850MHz Band Edge @ 3m																																																																																																																																																																																																																												
ANT	802.11ac VHT20 CH149 5745MHz																																																																																																																																																																																																																												
6+7	Vertical	Fundamental																																																																																																																																																																																																																											
Peak Avg.	 Site : 802.11ac-VS Condition : SG BAND4 3m 3117 SN 00218642 VERTICAL Project : RBU:1000.0000Hz VBU:3000.0000Hz SWF:Auto Model : 33 Plane : V ZNEI : Single-directivity Powersetting : 18  Level (dBV/m) Frequency (MHz) <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>Read</th><th>Cable</th><th>Antenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr></thead><tbody><tr><td>1</td><td>5640.00</td><td>57.32</td><td>-18.90</td><td>60.30</td><td>42.76</td><td>11.36</td><td>35.50</td><td>32.10</td><td>130</td><td>360 Peak</td></tr><tr><td>2</td><td>5673.00</td><td>56.37</td><td>-20.63</td><td>65.00</td><td>41.50</td><td>11.30</td><td>35.35</td><td>32.00</td><td>130</td><td>360 Peak</td></tr><tr><td>3</td><td>5700.00</td><td>57.74</td><td>-49.35</td><td>187.09</td><td>42.95</td><td>11.23</td><td>35.60</td><td>32.04</td><td>130</td><td>360 Peak</td></tr><tr><td>4</td><td>5720.00</td><td>57.07</td><td>-53.83</td><td>130.00</td><td>42.26</td><td>11.25</td><td>35.60</td><td>32.04</td><td>130</td><td>360 Peak</td></tr></tbody></table>  Site : 802.11ac-VS Condition : SG BAND4 3m 3117 SN 00218642 VERTICAL Project : RBU:1000.0000Hz VBU:3000.0000Hz SWF:Auto Model : 33 Plane : V ZNEI : Single-directivity Powersetting : 18  Level (dBV/m) Frequency (MHz) <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>Read</th><th>Cable</th><th>Antenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr></thead><tbody><tr><td>1</td><td>5640.00</td><td>57.32</td><td>-18.90</td><td>60.30</td><td>42.76</td><td>11.36</td><td>35.50</td><td>32.10</td><td>130</td><td>360 Peak</td></tr><tr><td>2</td><td>5673.00</td><td>56.37</td><td>-20.63</td><td>65.00</td><td>41.50</td><td>11.30</td><td>35.35</td><td>32.00</td><td>130</td><td>360 Peak</td></tr><tr><td>3</td><td>5700.00</td><td>57.74</td><td>-49.35</td><td>187.09</td><td>42.95</td><td>11.23</td><td>35.60</td><td>32.04</td><td>130</td><td>360 Peak</td></tr><tr><td>4</td><td>5720.00</td><td>57.07</td><td>-53.83</td><td>130.00</td><td>42.26</td><td>11.25</td><td>35.60</td><td>32.04</td><td>130</td><td>360 Peak</td></tr></tbody></table>  Site : 802.11ac-VS Condition : SG BAND4 3m 3117 SN 00218642 VERTICAL Project : RBU:1000.0000Hz VBU:3000.0000Hz SWF:Auto Model : 33 Plane : V ZNEI : Single-directivity Powersetting : 18  Level (dBV/m) Frequency (MHz) <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>Read</th><th>Cable</th><th>Antenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr></thead><tbody><tr><td>1</td><td>5740.00</td><td>99.92</td><td>-22.38</td><td>122.30</td><td>85.01</td><td>11.27</td><td>35.65</td><td>32.01</td><td>130</td><td>360 Peak</td></tr><tr><td>2</td><td>5740.00</td><td>84.07</td><td>.....</td><td>79.16</td><td>11.27</td><td>35.65</td><td>32.01</td><td>130</td><td>360 Average</td><td></td></tr></tbody></table>  Site : 802.11ac-VS Condition : SG BAND4 3m 3117 SN 00218642 VERTICAL Project : RBU:1000.0000Hz VBU:3000.0000Hz SWF:Auto Model : 33 Plane : V ZNEI : Single-directivity Powersetting : 18  Level (dBV/m) Frequency (MHz) <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>Read</th><th>Cable</th><th>Antenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr></thead><tbody><tr><td>1</td><td>5740.00</td><td>99.92</td><td>-22.38</td><td>122.30</td><td>85.01</td><td>11.27</td><td>35.65</td><td>32.01</td><td>130</td><td>360 Peak</td></tr><tr><td>2</td><td>5740.00</td><td>84.07</td><td>.....</td><td>79.16</td><td>11.27</td><td>35.65</td><td>32.01</td><td>130</td><td>360 Average</td><td></td></tr></tbody></table>	Freq	Level	Over	Limit	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg			1	5640.00	57.32	-18.90	60.30	42.76	11.36	35.50	32.10	130	360 Peak	2	5673.00	56.37	-20.63	65.00	41.50	11.30	35.35	32.00	130	360 Peak	3	5700.00	57.74	-49.35	187.09	42.95	11.23	35.60	32.04	130	360 Peak	4	5720.00	57.07	-53.83	130.00	42.26	11.25	35.60	32.04	130	360 Peak	Freq	Level	Over	Limit	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg			1	5640.00	57.32	-18.90	60.30	42.76	11.36	35.50	32.10	130	360 Peak	2	5673.00	56.37	-20.63	65.00	41.50	11.30	35.35	32.00	130	360 Peak	3	5700.00	57.74	-49.35	187.09	42.95	11.23	35.60	32.04	130	360 Peak	4	5720.00	57.07	-53.83	130.00	42.26	11.25	35.60	32.04	130	360 Peak	Freq	Level	Over	Limit	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg			1	5740.00	99.92	-22.38	122.30	85.01	11.27	35.65	32.01	130	360 Peak	2	5740.00	84.07		79.16	11.27	35.65	32.01	130	360 Average		Freq	Level	Over	Limit	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg			1	5740.00	99.92	-22.38	122.30	85.01	11.27	35.65	32.01	130	360 Peak	2	5740.00	84.07		79.16	11.27	35.65	32.01	130	360 Average	
	Freq	Level	Over	Limit	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																																																																		
MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg																																																																																																																																																																																																																					
1	5640.00	57.32	-18.90	60.30	42.76	11.36	35.50	32.10	130	360 Peak																																																																																																																																																																																																																			
2	5673.00	56.37	-20.63	65.00	41.50	11.30	35.35	32.00	130	360 Peak																																																																																																																																																																																																																			
3	5700.00	57.74	-49.35	187.09	42.95	11.23	35.60	32.04	130	360 Peak																																																																																																																																																																																																																			
4	5720.00	57.07	-53.83	130.00	42.26	11.25	35.60	32.04	130	360 Peak																																																																																																																																																																																																																			
Freq	Level	Over	Limit	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																																																																			
MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg																																																																																																																																																																																																																					
1	5640.00	57.32	-18.90	60.30	42.76	11.36	35.50	32.10	130	360 Peak																																																																																																																																																																																																																			
2	5673.00	56.37	-20.63	65.00	41.50	11.30	35.35	32.00	130	360 Peak																																																																																																																																																																																																																			
3	5700.00	57.74	-49.35	187.09	42.95	11.23	35.60	32.04	130	360 Peak																																																																																																																																																																																																																			
4	5720.00	57.07	-53.83	130.00	42.26	11.25	35.60	32.04	130	360 Peak																																																																																																																																																																																																																			
Freq	Level	Over	Limit	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																																																																			
MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg																																																																																																																																																																																																																					
1	5740.00	99.92	-22.38	122.30	85.01	11.27	35.65	32.01	130	360 Peak																																																																																																																																																																																																																			
2	5740.00	84.07		79.16	11.27	35.65	32.01	130	360 Average																																																																																																																																																																																																																				
Freq	Level	Over	Limit	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																																																																			
MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg																																																																																																																																																																																																																					
1	5740.00	99.92	-22.38	122.30	85.01	11.27	35.65	32.01	130	360 Peak																																																																																																																																																																																																																			
2	5740.00	84.07		79.16	11.27	35.65	32.01	130	360 Average																																																																																																																																																																																																																				





WIFI	Band 4 5725~5850MHz Band Edge @ 3m																																																																																																					
ANT	802.11ac VHT20 CH165 5825MHz																																																																																																					
6+7	Horizontal	Fundamental																																																																																																				
Peak	 No. 1899, Fengqi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China Tel: +86-512-57900158 Fax: +86-512-57900958 http://www.sporton.com.cn Date: 1  Site : 83CH06-15 Condition : 5G BAND4 3m 3117 SN 08218642 HORIZONTAL Project : RRU:1000.0000Hz VDU:3000.0000Hz SW:Auto Mode : 35 Plane : Y ZNEI : Single-directivity Powersetting : 18 <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Read</th><th>Cable/Antenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5808.40</td><td>56.67</td><td>-64.72</td><td>121.39</td><td>41.44</td><td>11.36</td><td>35.80</td><td>31.93</td><td>256 41 Peak</td></tr><tr><td>2</td><td>5805.00</td><td>56.68</td><td>-51.13</td><td>100.83</td><td>41.45</td><td>11.38</td><td>35.80</td><td>31.95</td><td>256 41 Peak</td></tr><tr><td>3</td><td>5806.00</td><td>56.73</td><td>-32.89</td><td>89.72</td><td>41.51</td><td>11.41</td><td>35.78</td><td>31.97</td><td>256 41 Peak</td></tr><tr><td>4</td><td>5805.00</td><td>57.23</td><td>-11.87</td><td>66.10</td><td>42.00</td><td>11.44</td><td>35.78</td><td>31.99</td><td>256 41 Peak</td></tr></tbody></table>		Freq	Level	Limit	Read	Cable/Antenna	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg	1	5808.40	56.67	-64.72	121.39	41.44	11.36	35.80	31.93	256 41 Peak	2	5805.00	56.68	-51.13	100.83	41.45	11.38	35.80	31.95	256 41 Peak	3	5806.00	56.73	-32.89	89.72	41.51	11.41	35.78	31.97	256 41 Peak	4	5805.00	57.23	-11.87	66.10	42.00	11.44	35.78	31.99	256 41 Peak	 No. 1899, Fengqi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China Tel: +86-512-57900158 Fax: +86-512-57900958 http://www.sporton.com.cn Date: 2  Site : 83CH06-15 Condition : 5G BAND4 3m 3117 SN 08218642 HORIZONTAL Project : RRU:1000.0000Hz VDU:3000.0000Hz SW:Auto Mode : 35 Plane : Y ZNEI : Single-directivity Powersetting : 18 <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Read</th><th>Cable/Antenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5824.00</td><td>102.94</td><td>-19.36</td><td>122.30</td><td>87.79</td><td>11.35</td><td>35.75</td><td>31.95</td><td>256 41 Peak</td></tr><tr><td>2</td><td>5824.00</td><td>94.98</td><td>-----</td><td>79.87</td><td>11.35</td><td>35.75</td><td>31.95</td><td></td><td>256 41 Average</td></tr></tbody></table>		Freq	Level	Limit	Read	Cable/Antenna	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg	1	5824.00	102.94	-19.36	122.30	87.79	11.35	35.75	31.95	256 41 Peak	2	5824.00	94.98	-----	79.87	11.35	35.75	31.95		256 41 Average
	Freq	Level	Limit	Read	Cable/Antenna	Preamp	A/Pos	T/Pos	Remark																																																																																													
	MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg																																																																																													
1	5808.40	56.67	-64.72	121.39	41.44	11.36	35.80	31.93	256 41 Peak																																																																																													
2	5805.00	56.68	-51.13	100.83	41.45	11.38	35.80	31.95	256 41 Peak																																																																																													
3	5806.00	56.73	-32.89	89.72	41.51	11.41	35.78	31.97	256 41 Peak																																																																																													
4	5805.00	57.23	-11.87	66.10	42.00	11.44	35.78	31.99	256 41 Peak																																																																																													
	Freq	Level	Limit	Read	Cable/Antenna	Preamp	A/Pos	T/Pos	Remark																																																																																													
	MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg																																																																																													
1	5824.00	102.94	-19.36	122.30	87.79	11.35	35.75	31.95	256 41 Peak																																																																																													
2	5824.00	94.98	-----	79.87	11.35	35.75	31.95		256 41 Average																																																																																													



WIFI	Band 4 5725~5850MHz Band Edge @ 3m																																																																																																												
ANT	802.11ac VHT20 CH165 5825MHz																																																																																																												
6+7	Vertical	Fundamental																																																																																																											
Peak	The plot shows the frequency spectrum for the vertical polarization. The x-axis represents frequency from 5600 to 6000 MHz, and the y-axis represents level in dBm/Vm from 15.3 to 130. A red line indicates the 5G BAND4 limit, and a blue line shows the measured signal. A sharp peak is visible at 5825 MHz. Site : 802.11ac-15 Condition : 5G BAND4 3m 3117 SN 08218642 VERTICAL Project : R&D:1000-0000Hz VDU:3000-0000Hz SW:Auto Model : F91200150 Plane : V Polar : Single-directivity Polarization : 86 PowerSetting : 18 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Read</th><th>Cable/Antenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBm/Vm</th><th>dB</th><th>dBm/Vm</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5825.00</td><td>56.47</td><td>-61.27</td><td>117.74</td><td>41.24</td><td>11.36</td><td>35.80</td><td>31.93</td><td>113</td><td>360</td><td>Peak</td></tr><tr><td>2</td><td>5803.00</td><td>57.87</td><td>-51.42</td><td>100.49</td><td>41.85</td><td>11.38</td><td>35.75</td><td>31.95</td><td>113</td><td>360</td><td>Peak</td></tr><tr><td>3</td><td>5921.00</td><td>57.85</td><td>-51.76</td><td>79.61</td><td>41.82</td><td>11.44</td><td>35.78</td><td>31.99</td><td>113</td><td>360</td><td>Peak</td></tr><tr><td>4</td><td>5995.00</td><td>56.89</td><td>-51.42</td><td>60.50</td><td>41.69</td><td>11.50</td><td>35.75</td><td>32.05</td><td>113</td><td>360</td><td>Peak</td></tr></table>	Freq	Level	Limit	Read	Cable/Antenna	Preamp	A/Pos	T/Pos	Remark	MHz	dBm/Vm	dB	dBm/Vm	dB	dB/m	dB	cm	deg	1	5825.00	56.47	-61.27	117.74	41.24	11.36	35.80	31.93	113	360	Peak	2	5803.00	57.87	-51.42	100.49	41.85	11.38	35.75	31.95	113	360	Peak	3	5921.00	57.85	-51.76	79.61	41.82	11.44	35.78	31.99	113	360	Peak	4	5995.00	56.89	-51.42	60.50	41.69	11.50	35.75	32.05	113	360	Peak	The plot shows the frequency spectrum for the fundamental polarization. The x-axis represents frequency from 5600 to 7000 MHz, and the y-axis represents level in dBm/Vm from 15.3 to 130. A red line indicates the 5G BAND4 limit, and a blue line shows the measured signal. A sharp peak is visible at 5825 MHz. Site : 802.11ac-15 Condition : 5G BAND4 3m 3117 SN 08218642 VERTICAL Project : R&D:1000-0000Hz VDU:3000-0000Hz SW:Auto Model : F91200150 Plane : V Polar : Single-directivity Polarization : 86 PowerSetting : 18 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Read</th><th>Cable/Antenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBm/Vm</th><th>dB</th><th>dBm/Vm</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5824.00</td><td>99.81</td><td>-23.29</td><td>122.38</td><td>83.86</td><td>11.35</td><td>35.75</td><td>31.95</td><td>113</td><td>360</td><td>Peak</td></tr><tr><td>2</td><td>5824.00</td><td>91.44</td><td>.....</td><td>76.29</td><td>11.35</td><td>35.75</td><td>31.95</td><td>113</td><td>360</td><td>Average</td></tr></table>	Freq	Level	Limit	Read	Cable/Antenna	Preamp	A/Pos	T/Pos	Remark	MHz	dBm/Vm	dB	dBm/Vm	dB	dB/m	dB	cm	deg	1	5824.00	99.81	-23.29	122.38	83.86	11.35	35.75	31.95	113	360	Peak	2	5824.00	91.44		76.29	11.35	35.75	31.95	113	360	Average
Freq	Level	Limit	Read	Cable/Antenna	Preamp	A/Pos	T/Pos	Remark																																																																																																					
MHz	dBm/Vm	dB	dBm/Vm	dB	dB/m	dB	cm	deg																																																																																																					
1	5825.00	56.47	-61.27	117.74	41.24	11.36	35.80	31.93	113	360	Peak																																																																																																		
2	5803.00	57.87	-51.42	100.49	41.85	11.38	35.75	31.95	113	360	Peak																																																																																																		
3	5921.00	57.85	-51.76	79.61	41.82	11.44	35.78	31.99	113	360	Peak																																																																																																		
4	5995.00	56.89	-51.42	60.50	41.69	11.50	35.75	32.05	113	360	Peak																																																																																																		
Freq	Level	Limit	Read	Cable/Antenna	Preamp	A/Pos	T/Pos	Remark																																																																																																					
MHz	dBm/Vm	dB	dBm/Vm	dB	dB/m	dB	cm	deg																																																																																																					
1	5824.00	99.81	-23.29	122.38	83.86	11.35	35.75	31.95	113	360	Peak																																																																																																		
2	5824.00	91.44		76.29	11.35	35.75	31.95	113	360	Average																																																																																																			

Band 4 - 5725~5850MHz





WIFI 802.11a (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m																																																													
ANT	802.11a CH149 5745MHz																																																													
6+7	Horizontal	Vertical																																																												
Peak Avg.	 Site : 83CH06-KS Condition : SG BAND4 3m 3117 SN 00218642 HORIZONTAL Project : RW:1000.000000Hz VBW:3000.000000Hz SMT:Auto Model : (F8)120010 Plane : Y Polar : Single-directivity Polarization : 45 PowerSetting : 18 Over Limit : 18 <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Read</th><th>Cable</th><th>Antenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1 11488.00</td><td>47.89</td><td>-26.91</td><td>74.80</td><td>52.52</td><td>16.31</td><td>38.69</td><td>60.43</td><td>300</td><td>0 Peak</td></tr></tbody></table>	Freq	Level	Limit	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg		1 11488.00	47.89	-26.91	74.80	52.52	16.31	38.69	60.43	300	0 Peak	 Site : 83CH06-KS Condition : SG BAND4 3m 3117 SN 00218642 VERTICAL Project : RW:1000.000000Hz VBW:3000.000000Hz SMT:Auto Model : (F8)120010 Plane : Y Polar : Single-directivity Polarization : 45 PowerSetting : 18 Over Limit : 18 <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Read</th><th>Cable</th><th>Antenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1 11488.00</td><td>47.46</td><td>-26.54</td><td>74.00</td><td>52.89</td><td>16.31</td><td>38.69</td><td>60.43</td><td>100</td><td>0 Peak</td></tr></tbody></table>	Freq	Level	Limit	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg		1 11488.00	47.46	-26.54	74.00	52.89	16.31	38.69	60.43	100	0 Peak
	Freq	Level	Limit	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark																																																				
MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg																																																						
1 11488.00	47.89	-26.91	74.80	52.52	16.31	38.69	60.43	300	0 Peak																																																					
Freq	Level	Limit	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark																																																					
MHz	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm	deg																																																						
1 11488.00	47.46	-26.54	74.00	52.89	16.31	38.69	60.43	100	0 Peak																																																					





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH157 5785MHz	
6+7	Horizontal	Vertical
Peak Avg.	Site : 803080-KS Condition : SG BAND4 3m 3117 SN 08218642 HORIZONTAL Project : RF1200158 Mode : 31 Plane : V Polar : Single-directivity PowerSetting : 18 Over Limit Read CableAntenna Preamp A/Pos T/Pos Freq Level Limit Line Level Loss Factor Factor cm deg 1 11565.00 46.79 -27.21 74.00 52.10 16.37 38.71 60.39 300 0 Peak	Site : 803080-KS Condition : SG BAND4 3m 3117 SN 08218642 HORIZONTAL Project : RF1200158 Mode : 31 Plane : V Polar : Single-directivity PowerSetting : 18 Over Limit Read CableAntenna Preamp A/Pos T/Pos Freq Level Limit Line Level Loss Factor Factor cm deg 1 11565.00 46.79 -27.21 74.00 52.10 16.37 38.71 60.39 300 0 Peak
	Site : 803080-KS Condition : SG BAND4 3m 3117 SN 08218642 HORIZONTAL Project : RF1200158 Mode : 31 Plane : V Polar : Single-directivity PowerSetting : 18 Over Limit Read CableAntenna Preamp A/Pos T/Pos Freq Level Limit Line Level Loss Factor Factor cm deg 1 11565.00 46.79 -27.21 74.00 52.10 16.37 38.71 60.39 300 0 Peak	Site : 803080-KS Condition : SG BAND4 3m 3117 SN 08218642 HORIZONTAL Project : RF1200158 Mode : 31 Plane : V Polar : Single-directivity PowerSetting : 18 Over Limit Read CableAntenna Preamp A/Pos T/Pos Freq Level Limit Line Level Loss Factor Factor cm deg 1 11565.00 46.79 -27.21 74.00 52.10 16.37 38.71 60.39 300 0 Peak







WIFI	Band 4 5725~5850MHz Harmonic @ 3m																																																																																																																																	
ANT	802.11a CH165 5825MHz																																																																																																																																	
6+7	Horizontal	Vertical																																																																																																																																
Peak Avg.	 No. 1895, Mengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China Tel: +86-512-57980518 Fax: +86-512-57980503 http://www.sporton.com.cn Date: 5  Site Condition : 802.11a-KS : SG BAND4 3m 3117 SN 08218642 HORIZONTAL Project : FR1D0310 Mode : 32 Plane : V Polarization : Single-directivity PowerSetting : 18 <table><thead><tr><th>Over</th><th>Limit</th><th>Read</th><th>CableAntenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>11653.00</td><td>46.82</td><td>-27.18</td><td>74.00</td><td>51.94</td><td>16.47</td><td>38.73 68.32 300 0 Peak</td></tr></tbody></table>  No. 1895, Mengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China Tel: +86-512-57980518 Fax: +86-512-57980503 http://www.sporton.com.cn Date: 5  Site Condition : 802.11a-KS : SG BAND4 3m 3117 SN 08218642 HORIZONTAL Project : FR1D0310 Mode : 32 Plane : V Polarization : Single-directivity PowerSetting : 18 <table><thead><tr><th>Over</th><th>Limit</th><th>Read</th><th>CableAntenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>11653.00</td><td>46.82</td><td>-27.18</td><td>74.00</td><td>51.94</td><td>16.47</td><td>38.73 68.32 300 0 Peak</td></tr></tbody></table>	Over	Limit	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Freq	Level	Limit	Line	Loss	Factor	Factor			dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm deg	1	11653.00	46.82	-27.18	74.00	51.94	16.47	38.73 68.32 300 0 Peak	Over	Limit	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Freq	Level	Limit	Line	Loss	Factor	Factor			dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm deg	1	11653.00	46.82	-27.18	74.00	51.94	16.47	38.73 68.32 300 0 Peak	 No. 1895, Mengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China Tel: +86-512-57980518 Fax: +86-512-57980503 http://www.sporton.com.cn Date: 6  Site Condition : 802.11a-KS : SG BAND4 3m 3117 SN 08218642 VERTICAL Project : FR1D0310 Mode : 32 Plane : V Polarization : Single-directivity PowerSetting : 18 <table><thead><tr><th>Over</th><th>Limit</th><th>Read</th><th>CableAntenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>11653.00</td><td>46.97</td><td>-27.03</td><td>74.00</td><td>52.09</td><td>16.47</td><td>38.73 68.32 100 0 Peak</td></tr></tbody></table>  No. 1895, Mengzi North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China Tel: +86-512-57980518 Fax: +86-512-57980503 http://www.sporton.com.cn Date: 6  Site Condition : 802.11a-KS : SG BAND4 3m 3117 SN 08218642 VERTICAL Project : FR1D0310 Mode : 32 Plane : V Polarization : Single-directivity PowerSetting : 18 <table><thead><tr><th>Over</th><th>Limit</th><th>Read</th><th>CableAntenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>11653.00</td><td>46.97</td><td>-27.03</td><td>74.00</td><td>52.09</td><td>16.47</td><td>38.73 68.32 100 0 Peak</td></tr></tbody></table>	Over	Limit	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Freq	Level	Limit	Line	Loss	Factor	Factor			dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm deg	1	11653.00	46.97	-27.03	74.00	52.09	16.47	38.73 68.32 100 0 Peak	Over	Limit	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Freq	Level	Limit	Line	Loss	Factor	Factor			dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm deg	1	11653.00	46.97	-27.03	74.00	52.09	16.47	38.73 68.32 100 0 Peak
	Over	Limit	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark																																																																																																																										
Freq	Level	Limit	Line	Loss	Factor	Factor																																																																																																																												
	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm deg																																																																																																																											
1	11653.00	46.82	-27.18	74.00	51.94	16.47	38.73 68.32 300 0 Peak																																																																																																																											
Over	Limit	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark																																																																																																																											
Freq	Level	Limit	Line	Loss	Factor	Factor																																																																																																																												
	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm deg																																																																																																																											
1	11653.00	46.82	-27.18	74.00	51.94	16.47	38.73 68.32 300 0 Peak																																																																																																																											
Over	Limit	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark																																																																																																																											
Freq	Level	Limit	Line	Loss	Factor	Factor																																																																																																																												
	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm deg																																																																																																																											
1	11653.00	46.97	-27.03	74.00	52.09	16.47	38.73 68.32 100 0 Peak																																																																																																																											
Over	Limit	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark																																																																																																																											
Freq	Level	Limit	Line	Loss	Factor	Factor																																																																																																																												
	dBuV/m	dB	dBuV/m	dB	dB/m	dB	cm deg																																																																																																																											
1	11653.00	46.97	-27.03	74.00	52.09	16.47	38.73 68.32 100 0 Peak																																																																																																																											



Band 4 5725~5850MHz
WIFI 802. 11ac VHT 40 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m																																																																
ANT	802.11n VHT 40 CH151 5755MHz																																																																
6+7	Horizontal	Vertical																																																															
Peak Avg.	 No. 1889, Pengji North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China Tel: +86-512-57988518 Fax: +86-512-57988505 http://www.sporton.com.cn SPORTON LAB Data: 7  Site Condition : 83CH06-K5 : 5G BAND4 3m 3117 SW 00218062 HORIZONTAL Project : 802.11ac VHT 40 CH151 5755MHz Mode : 10 Plane : Y Single-directivity : Y PowerSetting : 10 <table><tr><th>Over</th><th>Line</th><th>Band</th><th>CableLoss</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBm/100kHz</th><th>dB</th><th>dBm/100kHz</th><th>dB</th><th>dBm/100kHz</th><th>cm</th><th>deg</th></tr><tr><td>1 11510.00</td><td>46.56</td><td>-27.44</td><td>74.00</td><td>51.97</td><td>16.32</td><td>38.70</td><td>60.43 300 0 Peak</td></tr></table>  No. 1889, Pengji North Road, Kunshan Economic & Technical Development Zone, Jiangsu, China Tel: +86-512-57988518 Fax: +86-512-57988505 http://www.sporton.com.cn SPORTON LAB Data: 8  Site Condition : 83CH06-K5 : 5G BAND4 3m 3117 SW 00218062 VERTICAL Project : 802.11ac VHT 40 CH151 5755MHz Mode : 10 Plane : Y Single-directivity : Y PowerSetting : 10 <table><tr><th>Over</th><th>Line</th><th>Band</th><th>CableLoss</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBm/100kHz</th><th>dB</th><th>dBm/100kHz</th><th>dB</th><th>dBm/100kHz</th><th>cm</th><th>deg</th></tr><tr><td>1 11510.00</td><td>47.22</td><td>-26.78</td><td>74.00</td><td>52.63</td><td>16.32</td><td>38.70</td><td>60.43 100 0 Peak</td></tr></table>	Over	Line	Band	CableLoss	Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Loss	Factor	Factor			MHz	dBm/100kHz	dB	dBm/100kHz	dB	dBm/100kHz	cm	deg	1 11510.00	46.56	-27.44	74.00	51.97	16.32	38.70	60.43 300 0 Peak	Over	Line	Band	CableLoss	Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Loss	Factor	Factor			MHz	dBm/100kHz	dB	dBm/100kHz	dB	dBm/100kHz	cm	deg	1 11510.00	47.22	-26.78	74.00	52.63	16.32	38.70	60.43 100 0 Peak
	Over	Line	Band	CableLoss	Preamp	A/Pos	T/Pos	Remark																																																									
Freq	Level	Line	Loss	Factor	Factor																																																												
MHz	dBm/100kHz	dB	dBm/100kHz	dB	dBm/100kHz	cm	deg																																																										
1 11510.00	46.56	-27.44	74.00	51.97	16.32	38.70	60.43 300 0 Peak																																																										
Over	Line	Band	CableLoss	Preamp	A/Pos	T/Pos	Remark																																																										
Freq	Level	Line	Loss	Factor	Factor																																																												
MHz	dBm/100kHz	dB	dBm/100kHz	dB	dBm/100kHz	cm	deg																																																										
1 11510.00	47.22	-26.78	74.00	52.63	16.32	38.70	60.43 100 0 Peak																																																										





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT40 CH159 5795MHz	
6+7	Horizontal	Vertical
Peak Avg.	 Site : 80CH00-KS Condition : SG BAND4 3m 3117 SN 00218642 HORIZONTAL Project : RBU:1000.0000Hz VBU:3000.0000Hz SW:Auto Model : FPL100210 Plane : V Polar : Single-directivity PowerSetting : 10 Over Limit Read CableAntenna Preamp A/Pos T/Pos Freq Level Limit Line Level Loss Factor Factor cm deg 1 11587.00 46.33 -27.67 74.00 51.57 16.41 38.72 68.37 300 0 Peak	 Site : 80CH00-KS Condition : SG BAND4 3m 3117 SN 00218642 VERTICAL Project : RBU:1000.0000Hz VBU:3000.0000Hz SW:Auto Model : FPL100210 Plane : V Polar : Single-directivity PowerSetting : 10 Over Limit Read CableAntenna Preamp A/Pos T/Pos Freq Level Limit Line Level Loss Factor Factor cm deg 1 11587.00 47.00 -26.92 74.00 52.32 16.41 38.72 68.37 100 0 Peak
	 Site : 80CH00-KS Condition : SG BAND4 3m 3117 SN 00218642 HORIZONTAL Project : RBU:1000.0000Hz VBU:3000.0000Hz SW:Auto Model : FPL100210 Plane : V Polar : Single-directivity PowerSetting : 10 Over Limit Read CableAntenna Preamp A/Pos T/Pos Freq Level Limit Line Level Loss Factor Factor cm deg 1 11587.00 46.33 -27.67 74.00 51.57 16.41 38.72 68.37 300 0 Peak	 Site : 80CH00-KS Condition : SG BAND4 3m 3117 SN 00218642 VERTICAL Project : RBU:1000.0000Hz VBU:3000.0000Hz SW:Auto Model : FPL100210 Plane : V Polar : Single-directivity PowerSetting : 10 Over Limit Read CableAntenna Preamp A/Pos T/Pos Freq Level Limit Line Level Loss Factor Factor cm deg 1 11587.00 47.00 -26.92 74.00 52.32 16.41 38.72 68.37 100 0 Peak







WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT20 CH157 5785MHz	
6+7	Horizontal	Vertical
Peak Avg.	Site : 80CH00-KS Condition : SG BAND4 3m 3117 SN 08218642 HORIZONTAL Project : RBU:1000.0000Hz VBU:3000.0000Hz SW:Auto Mode : FPL1200150 Plane : 34 Polar : V Polar : Single-directivity Polar : 80 PowerSetting : 10 Over Limit Read CableAntenna Preamp A/Pos T/Pos Freq Level Limit Line Level Loss Factor Factor Remark MHz dBuV/m dB dBuV/m dB dB/m dB cm deg 1 11565.00 47.50 -26.50 74.00 52.81 16.37 38.71 60.39 300 0 Peak	Site : 80CH00-KS Condition : SG BAND4 3m 3117 SN 08218642 HORIZONTAL Project : RBU:1000.0000Hz VBU:3000.0000Hz SW:Auto Mode : FPL1200150 Plane : 34 Polar : V Polar : Single-directivity Polar : 80 PowerSetting : 10 Over Limit Read CableAntenna Preamp A/Pos T/Pos Freq Level Limit Line Level Loss Factor Factor Remark MHz dBuV/m dB dBuV/m dB dB/m dB cm deg 1 11565.00 47.50 -26.50 74.00 52.81 16.37 38.71 60.39 300 0 Peak
	Site : 80CH00-KS Condition : SG BAND4 3m 3117 SN 08218642 HORIZONTAL Project : RBU:1000.0000Hz VBU:3000.0000Hz SW:Auto Mode : FPL1200150 Plane : 34 Polar : V Polar : Single-directivity Polar : 80 PowerSetting : 10 Over Limit Read CableAntenna Preamp A/Pos T/Pos Freq Level Limit Line Level Loss Factor Factor Remark MHz dBuV/m dB dBuV/m dB dB/m dB cm deg 1 11565.00 47.50 -26.50 74.00 52.81 16.37 38.71 60.39 300 0 Peak	Site : 80CH00-KS Condition : SG BAND4 3m 3117 SN 08218642 HORIZONTAL Project : RBU:1000.0000Hz VBU:3000.0000Hz SW:Auto Mode : FPL1200150 Plane : 34 Polar : V Polar : Single-directivity Polar : 80 PowerSetting : 10 Over Limit Read CableAntenna Preamp A/Pos T/Pos Freq Level Limit Line Level Loss Factor Factor Remark MHz dBuV/m dB dBuV/m dB dB/m dB cm deg 1 11565.00 47.50 -26.50 74.00 52.81 16.37 38.71 60.39 300 0 Peak



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT20 CH165 5825MHz	
6+7	Horizontal	Vertical
Peak Avg.	 Site : 803080-KS Condition : SG BAND4 3m 3117 SN 08218642 HORIZONTAL Project : RF1200158 Mode : 35 Plane : V Polarization : Single-directivity PowerSetting : 18 Over Limit Read CableAntenna Preamp A/Pos T/Pos Freq Level Limit Line Level Loss Factor Factor Remark MHz dBuV/m dB dBuV/m dB dB/m dB cm deg 1 11653.00 47.26 -26.74 74.00 52.38 16.47 38.73 60.32 300 0 Peak	 Site : 803080-KS Condition : SG BAND4 3m 3117 SN 08218642 VERTICAL Project : RF1200158 Mode : 35 Plane : V Polarization : Single-directivity PowerSetting : 18 Over Limit Read CableAntenna Preamp A/Pos T/Pos Freq Level Limit Line Level Loss Factor Factor Remark MHz dBuV/m dB dBuV/m dB dB/m dB cm deg 1 11653.00 47.22 -26.78 74.00 52.34 16.47 38.73 60.32 100 0 Peak





Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m																																																																																																																																																													
ANT	802.11ac VHT80 CH155 5775MHz																																																																																																																																																													
6+7	Horizontal					Vertical																																																																																																																																																								
Peak Avg.	 Site : 83CH06-K5 Condition : 5G BAND4 3m 3117 SW 00218062 HORIZONTAL Project : 802.11ac VHT80 CH155 5775MHz SUT-Auto Mode : 18 Plane : Y Single-directivity PowerSetting : 18 <table><thead><tr><th>Over</th><th>Line</th><th>Band</th><th>CableLoss</th><th>Antenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBm</th><th>dB</th><th>dBm</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>11554.00</td><td>47.30</td><td>-26.78</td><td>74.00</td><td>52.61</td><td>16.37</td><td>38.71</td><td>60.39</td><td>300 0 Peak</td></tr></tbody></table>  Site : 83CH06-K5 Condition : 5G BAND4 3m 3117 SW 00218062 HORIZONTAL Project : 802.11ac VHT80 CH155 5775MHz SUT-Auto Mode : 18 Plane : Y Single-directivity PowerSetting : 18 <table><thead><tr><th>Over</th><th>Line</th><th>Band</th><th>CableLoss</th><th>Antenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBm</th><th>dB</th><th>dBm</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>11554.00</td><td>47.30</td><td>-26.78</td><td>74.00</td><td>52.61</td><td>16.37</td><td>38.71</td><td>60.39</td><td>300 0 Peak</td></tr></tbody></table>					Over	Line	Band	CableLoss	Antenna	Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Level	Loss	Factor	Factor			MHz	dBm	dB	dBm	dB	dB/m	dB	cm	deg	1	11554.00	47.30	-26.78	74.00	52.61	16.37	38.71	60.39	300 0 Peak	Over	Line	Band	CableLoss	Antenna	Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Level	Loss	Factor	Factor			MHz	dBm	dB	dBm	dB	dB/m	dB	cm	deg	1	11554.00	47.30	-26.78	74.00	52.61	16.37	38.71	60.39	300 0 Peak	 Site : 83CH06-K5 Condition : 5G BAND4 3m 3117 SW 00218062 VERTICAL Project : 802.11ac VHT80 CH155 5775MHz SUT-Auto Mode : 18 Plane : Y Single-directivity PowerSetting : 18 <table><thead><tr><th>Over</th><th>Line</th><th>Band</th><th>CableLoss</th><th>Antenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBm</th><th>dB</th><th>dBm</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>11554.00</td><td>46.15</td><td>-27.85</td><td>74.00</td><td>51.46</td><td>16.37</td><td>38.71</td><td>60.39</td><td>100 0 Peak</td></tr></tbody></table>  Site : 83CH06-K5 Condition : 5G BAND4 3m 3117 SW 00218062 VERTICAL Project : 802.11ac VHT80 CH155 5775MHz SUT-Auto Mode : 18 Plane : Y Single-directivity PowerSetting : 18 <table><thead><tr><th>Over</th><th>Line</th><th>Band</th><th>CableLoss</th><th>Antenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBm</th><th>dB</th><th>dBm</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>11554.00</td><td>46.15</td><td>-27.85</td><td>74.00</td><td>51.46</td><td>16.37</td><td>38.71</td><td>60.39</td><td>100 0 Peak</td></tr></tbody></table>					Over	Line	Band	CableLoss	Antenna	Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Level	Loss	Factor	Factor			MHz	dBm	dB	dBm	dB	dB/m	dB	cm	deg	1	11554.00	46.15	-27.85	74.00	51.46	16.37	38.71	60.39	100 0 Peak	Over	Line	Band	CableLoss	Antenna	Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Level	Loss	Factor	Factor			MHz	dBm	dB	dBm	dB	dB/m	dB	cm	deg	1	11554.00	46.15	-27.85	74.00	51.46	16.37	38.71	60.39	100 0 Peak
	Over	Line	Band	CableLoss	Antenna	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																					
Freq	Level	Line	Level	Loss	Factor	Factor																																																																																																																																																								
MHz	dBm	dB	dBm	dB	dB/m	dB	cm	deg																																																																																																																																																						
1	11554.00	47.30	-26.78	74.00	52.61	16.37	38.71	60.39	300 0 Peak																																																																																																																																																					
Over	Line	Band	CableLoss	Antenna	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																						
Freq	Level	Line	Level	Loss	Factor	Factor																																																																																																																																																								
MHz	dBm	dB	dBm	dB	dB/m	dB	cm	deg																																																																																																																																																						
1	11554.00	47.30	-26.78	74.00	52.61	16.37	38.71	60.39	300 0 Peak																																																																																																																																																					
Over	Line	Band	CableLoss	Antenna	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																						
Freq	Level	Line	Level	Loss	Factor	Factor																																																																																																																																																								
MHz	dBm	dB	dBm	dB	dB/m	dB	cm	deg																																																																																																																																																						
1	11554.00	46.15	-27.85	74.00	51.46	16.37	38.71	60.39	100 0 Peak																																																																																																																																																					
Over	Line	Band	CableLoss	Antenna	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																						
Freq	Level	Line	Level	Loss	Factor	Factor																																																																																																																																																								
MHz	dBm	dB	dBm	dB	dB/m	dB	cm	deg																																																																																																																																																						
1	11554.00	46.15	-27.85	74.00	51.46	16.37	38.71	60.39	100 0 Peak																																																																																																																																																					




Emission below 1GHz
5GHz WIFI 802.11a (LF)


WIFI	5GHz WIFI																																																																																																																																																																
ANT	802.11a LF																																																																																																																																																																
1	Horizontal	Vertical																																																																																																																																																															
QP / Peak	 Site : 802.11a US Condition : 5G BAND4 3m CBL61120 SNA3182 HORIZONTAL Project : NMI-100-000000 V001-300-000000 SHT:Auto Node : (FR)1D0310F Node : 33 <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>Read</th><th>CableAntenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>38.00</td><td>21.07</td><td>-18.53</td><td>46.00</td><td>27.12</td><td>0.58</td><td>24.68</td><td>31.23</td><td>--- Peak</td></tr><tr><td>2</td><td>100.95</td><td>18.00</td><td>-15.50</td><td>45.50</td><td>32.31</td><td>2.04</td><td>15.97</td><td>31.32</td><td>--- Peak</td></tr><tr><td>3</td><td>291.98</td><td>26.17</td><td>-19.83</td><td>46.00</td><td>35.66</td><td>2.77</td><td>19.34</td><td>31.68</td><td>--- Peak</td></tr><tr><td>4</td><td>323.91</td><td>26.26</td><td>-19.74</td><td>46.00</td><td>35.18</td><td>2.92</td><td>19.88</td><td>31.64</td><td>--- Peak</td></tr><tr><td>5</td><td>628.73</td><td>25.73</td><td>-20.27</td><td>46.00</td><td>28.89</td><td>4.06</td><td>24.86</td><td>31.28</td><td>--- Peak</td></tr><tr><td>6</td><td>802.13</td><td>28.38</td><td>-17.62</td><td>46.00</td><td>28.84</td><td>4.07</td><td>26.05</td><td>31.18</td><td>--- Peak</td></tr></tbody></table>  Site : 802.11a US Condition : 5G BAND4 3m CBL61120 SNA3182 VERTICAL Project : NMI-100-000000 V001-300-000000 SHT:Auto Node : (FR)1D0310F Node : 33 <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>Read</th><th>CableAntenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>38.07</td><td>26.90</td><td>-15.02</td><td>46.00</td><td>33.68</td><td>0.59</td><td>24.04</td><td>31.25</td><td>--- Peak</td></tr><tr><td>2</td><td>332.82</td><td>17.68</td><td>-25.98</td><td>43.58</td><td>31.66</td><td>2.26</td><td>15.04</td><td>31.34</td><td>--- Peak</td></tr><tr><td>3</td><td>289.26</td><td>21.34</td><td>-24.66</td><td>46.00</td><td>38.76</td><td>2.73</td><td>19.48</td><td>31.53</td><td>--- Peak</td></tr><tr><td>4</td><td>338.88</td><td>22.86</td><td>-23.14</td><td>46.00</td><td>26.98</td><td>3.78</td><td>24.00</td><td>31.44</td><td>--- Peak</td></tr><tr><td>5</td><td>751.08</td><td>27.73</td><td>-19.27</td><td>46.00</td><td>28.68</td><td>4.46</td><td>25.79</td><td>31.11</td><td>--- Peak</td></tr><tr><td>6</td><td>896.21</td><td>28.36</td><td>-17.64</td><td>46.00</td><td>27.92</td><td>4.08</td><td>26.08</td><td>31.16</td><td>--- Peak</td></tr></tbody></table>	Freq	Level	Over	Limit	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB/m	dB	cm	deg	1	38.00	21.07	-18.53	46.00	27.12	0.58	24.68	31.23	--- Peak	2	100.95	18.00	-15.50	45.50	32.31	2.04	15.97	31.32	--- Peak	3	291.98	26.17	-19.83	46.00	35.66	2.77	19.34	31.68	--- Peak	4	323.91	26.26	-19.74	46.00	35.18	2.92	19.88	31.64	--- Peak	5	628.73	25.73	-20.27	46.00	28.89	4.06	24.86	31.28	--- Peak	6	802.13	28.38	-17.62	46.00	28.84	4.07	26.05	31.18	--- Peak	Freq	Level	Over	Limit	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB/m	dB	cm	deg	1	38.07	26.90	-15.02	46.00	33.68	0.59	24.04	31.25	--- Peak	2	332.82	17.68	-25.98	43.58	31.66	2.26	15.04	31.34	--- Peak	3	289.26	21.34	-24.66	46.00	38.76	2.73	19.48	31.53	--- Peak	4	338.88	22.86	-23.14	46.00	26.98	3.78	24.00	31.44	--- Peak	5	751.08	27.73	-19.27	46.00	28.68	4.46	25.79	31.11	--- Peak	6	896.21	28.36	-17.64	46.00	27.92	4.08	26.08	31.16	--- Peak
	Freq	Level	Over	Limit	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																							
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB/m	dB	cm	deg																																																																																																																																																								
1	38.00	21.07	-18.53	46.00	27.12	0.58	24.68	31.23	--- Peak																																																																																																																																																								
2	100.95	18.00	-15.50	45.50	32.31	2.04	15.97	31.32	--- Peak																																																																																																																																																								
3	291.98	26.17	-19.83	46.00	35.66	2.77	19.34	31.68	--- Peak																																																																																																																																																								
4	323.91	26.26	-19.74	46.00	35.18	2.92	19.88	31.64	--- Peak																																																																																																																																																								
5	628.73	25.73	-20.27	46.00	28.89	4.06	24.86	31.28	--- Peak																																																																																																																																																								
6	802.13	28.38	-17.62	46.00	28.84	4.07	26.05	31.18	--- Peak																																																																																																																																																								
Freq	Level	Over	Limit	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																								
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB/m	dB	cm	deg																																																																																																																																																								
1	38.07	26.90	-15.02	46.00	33.68	0.59	24.04	31.25	--- Peak																																																																																																																																																								
2	332.82	17.68	-25.98	43.58	31.66	2.26	15.04	31.34	--- Peak																																																																																																																																																								
3	289.26	21.34	-24.66	46.00	38.76	2.73	19.48	31.53	--- Peak																																																																																																																																																								
4	338.88	22.86	-23.14	46.00	26.98	3.78	24.00	31.44	--- Peak																																																																																																																																																								
5	751.08	27.73	-19.27	46.00	28.68	4.46	25.79	31.11	--- Peak																																																																																																																																																								
6	896.21	28.36	-17.64	46.00	27.92	4.08	26.08	31.16	--- Peak																																																																																																																																																								



Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting	Duty Factor
802.11a	98.62	-	-	10Hz	-
5GHz 802.11n/ac HT20/VHT20	98.16	-	-	10Hz	-
5GHz 802.11n/ac HT40/VHT40	96.32	0.949	1.053	1.1KHz	0.16
5GHz 802.11ac VHT80	93.02	0.464	2.156	2.2KHz	0.31





————THE END————