


**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

*FCC PART 15, SUBPART B CLASS B  
and  
FCC PART 15, SUBPART C  
TEST REPORT*

*for*


*the*

**RF KEYBOARD**

**MODEL: RT7N00**

Prepared for

LOGITECH, INC.  
6505 KAISER DRIVE  
FREMONT, CALIFORNIA 94555-3615

Prepared by:   
DOUG MOON

Approved by:   
KEVIN BOTHMANN

ELECTRO MAGNETIC TEST, INC.  
1547 PLYMOUTH STREET  
MOUNTAIN VIEW , CALIFORNIA 94043  
(650) 965-4000

DATE: AUGUST 28, 2001

	REPORT BODY	APPENDICES			TOTAL
		<i>A</i>	<i>B</i>	<i>C</i>	
PAGES	16	15	4	4	<b>39</b>

This report shall not be reproduced except in full, without the written approval of Electro Magnetic Test, Inc.



# ***ELECTRO MAGNETIC TEST, INC.***

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

## **TABLE OF CONTENTS**

<b>SECTION</b>	<b>TITLE</b>	<b>PAGE</b>
	GENERAL REPORT SUMMARY	04
	SUMMARY OF TEST RESULTS	05
1.	PURPOSE	06
2.	ADMINISTRATIVE DATA	07
2.1	Location of Testing	07
2.2	Traceability Statement	07
2.3	Cognizant Personnel	07
2.4	Date Test Sample was Received	07
2.5	Disposition of the Test Sample	07
2.6	Abbreviations and Acronyms	07
3.	APPLICABLE DOCUMENTS	08
4.	DESCRIPTION OF TEST CONFIGURATIONS	09
4.1	Description of Test Configuration - EMI	09
4.1.1	Cable Construction and Termination	10
5.	LIST OF EUT, ACCESSORIES AND TEST EQUIPMENT	11
5.1	EUT and Accessory List	11
5.2	EMI Test Equipment	12
6.	TEST SITE DESCRIPTION	13
6.1	Test Facility Description	13
6.2	EUT Mounting, Bonding and Grounding	13
7.	TEST PROCEDURES	14
7.1	RF Emissions	14
7.1.1	Conducted Emissions Test	14
7.1.2	Radiated Emissions Test	15
8.	CONCLUSIONS	16

***ELECTRO MAGNETIC TEST, INC.***1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

---

**LIST OF APPENDICES**

<b>APPENDIX</b>	<b>TITLE</b>
A	Radiated and Conducted Emissions Data Sheets
B	Test Setup Diagrams
C	Antenna and Effective Gain Factors

**LIST OF FIGURES**

<b>FIGURE</b>	<b>TITLE</b>
1	Conducted Emissions Test Setup
2	Plot Map And Layout of Test Site


**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

**GENERAL REPORT SUMMARY**

This electromagnetic emission test report is generated by Electro Magnetic Test Inc., which is an independent testing and consulting firm. The test report is based on testing performed by Electro Magnetic Test personnel according to the measurement procedure described in the test specification given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced in any form unless done so in full.

Associated with the data in this report is a  $\pm 2$ dB measurement uncertainty.

This report must not be used to claim product endorsement by NVLAP or any other agency of the U.S. Government.

Electro Magnetic Test, Inc. is approved to perform EMI/EMC testing by the following agencies:

COUNTRY	AGENCY	LAB APPROVAL #
USA	Federal Communications Commission (FCC)	*
USA	National Voluntary Lab Accreditation Program (NVLAP)	200147-0
Canada	Industry Canada	IC 2804
Japan	Voluntary Control Council For Interference (VCCI)	See Below
	Open Field Test Site Registration Number	R-589
	Conducted Emissions Test Site Registration Number	C-604
Taiwan	Bureau Of Standards, Metrology and Inspection (BSMI)	SL2-IN-E-1024
Australia / New Zealand	Australian Communications Authority (AUSTEL)	*
European Community	TUV Rheinland (EMC for the European Community)	*

\*These agencies do not issue a lab approval number to test labs.

**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

**GENERAL REPORT SUMMARY (CONTINUED)**

Device Tested: RF Keyboard  
Model: RT7N00  
S/N: N/A

Product Description: The EUT is a wireless keyboard to be used with a personal computer. The EUT consists of a transmitter inside a keyboard which communicates with a receiver that connects to the USB port on a personal computer.

Modifications: The EUT was not modified during the testing.

Manufacturer: Logitech, Inc.  
6505 Kaiser Drive  
Fremont, California 94555-3615

Test Date(s): August 14 and 15, 2001

Test Specifications: EMI requirements  
FCC Title 47, Part 15 Subpart B, Class B  
FCC Title 47, Part 15 Subpart C  
Test Procedure: ANSI C63.4: 1992.

Test Deviations: The test procedure was not deviated from during the testing.

**SUMMARY OF TEST RESULTS**

TEST	DESCRIPTION	RESULTS
1	Conducted RF Emissions, 450 kHz - 30 MHz.	Complies with the <b>Class B</b> limits of FCC Title 47, Part 15 Subpart B.
2	Radiated RF Emissions, 26.96 MHz - 27.28 MHz.	Complies with the limits of FCC Title 47, Part 15 Subpart C. (Section 15.227)
3	Radiated RF Emissions, 30 MHz - 1000 MHz.	Complies with the <b>Class B</b> limits of FCC Title 47, Part 15 Subpart B.

***ELECTRO MAGNETIC TEST, INC.***1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

---

1. **PURPOSE**

This document is a qualification test report based on the Electromagnetic Interference (EMI) tests performed on the RF Keyboard Model: RT7N00. The EMI measurements were performed according to the measurement procedure described in ANSI C63.4: 1992. The tests were performed in order to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT hereafter, are within the **Class B** specification limits defined in FCC Title 47, Part 15, Subpart B. The EUT was also tested to determine if the electromagnetic emissions were within the limits defined in FCC Title 47, Subpart C, Section 15.227.

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

---

**2. ADMINISTRATIVE DATA****2.1 Location of Testing**

The EMI tests described herein were performed at the test facility of Electro Magnetic Test, 1547 Plymouth Street, Mountain View, California 94043.

**2.2 Traceability Statement**

The calibration certificates of all test equipment used during the test are on file at the location of the test. The measurement results in this report and the calibration of the test equipment are traceable to the National Institute of Standards and Technology (NIST).

**2.3 Cognizant Personnel**Logitech, Inc.

Bharat Shah                      Agency/Reliability Engineer

Electro Magnetic Test, Inc.

Michael Fennell	Test Technician
Doug Moon	Test Technician
Kevin Bothmann	Lab Manager

**2.4 Date Test Sample was Received**

The test sample was received on August 13, 2001

**2.5 Disposition of the Test Sample**

The test sample has not been returned at this time.

**2.6 Abbreviations and Acronyms**

The following abbreviations and acronyms may be used in this document.

RF	Radio Frequency
EMI	Electromagnetic Interference
EUT	Equipment Under Test
P/N	Part Number
S/N	Serial Number
HP	Hewlett Packard
ITE	Information Technology Equipment
CML	Corrected Meter Limit
LISN	Line Impedance Stabilization Network
CISPR	International Special Committee On Radio Interference
FCC	Federal Communications Commission

***ELECTRO MAGNETIC TEST, INC.***1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

---

### 3. **APPLICABLE DOCUMENTS**

The following documents are referenced or used in the preparation of this EMI Test Report.

<b>SPEC</b>	<b>TITLE</b>
FCC Title 47, Part 15, Subpart B.	FCC Rules - Radio frequency devices (including digital devices).
FCC Title 47, Part 15, Subpart C.	FCC Rules – Radio frequency devices (intentional radiators) (Section 15.227)
ANSI C63.4 1992	Methods of measurement of radio-noise emissions from low-voltage electrical and electronic equipment in the range of 9 kHz to 40 GHz.



***ELECTRO MAGNETIC TEST, INC.***1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

---

#### 4. **DESCRIPTION OF TEST CONFIGURATION**

##### 4.1 **Description of Test Configuration - EMI**

The host computer was connected to the receiver, mouse, monitor, external modem, and printer via its USB, mouse, video, serial, and parallel ports, respectively. The printer was connected to its AC power adapter via its power input port. During the testing process, the EUT was communicating with the receiver. The EUT was continuously sending "H" characters to the receiver, and the characters were displayed on the monitor.

The EUT is battery powered, but the conducted emissions test was performed on the host computer with the receiver connected to insure that communication with the EUT will not cause the computer to be out of compliance.

It was determined that the emissions were at their highest level when the EUT was operating in the above configuration. The cables were moved to maximize the emissions. The final conducted as well as radiated data was taken in this mode of operation. All initial investigations were performed with the EMI receiver in manual mode scanning the frequency range continuously. The cables were bundled and routed as shown in the photographs in Appendix A.

***ELECTRO MAGNETIC TEST, INC.***1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

---

**4.1.1 Cable Construction and Termination**Cable #1

This is a 4 foot braid and foil shielded cable connecting the computer to the receiver. It has a USB metallic connector at the computer end, and is hardwired into the receiver. The shield of the cable was grounded to the chassis via the connector.

Cable #2

This is a 6 foot foil shielded cable connecting the computer to the mouse. It has a 6 pin mini DIN metallic connector at the computer end, and is hardwired into the mouse. The shield of the cable was grounded to the chassis via the connector.

Cable #3

This is a 6 foot braid and foil shielded cable connecting the computer to the monitor. It has a high density DB-15 pin metallic connector with a factory installed ferrite bead at the computer end, and is hardwired into the monitor. The cable was bundled to a length of 4 feet. The shield of the cable was grounded to the chassis via the connector.

Cable #4

This is a 6 foot foil shielded cable connecting the computer to the external modem. It has a DB-9 pin metallic connector at the computer end, and has a DB-25 pin metallic connector at the external modem end. The cable was bundled to a length of 4 feet. The shield of the cable was grounded to the chassis via the connectors.

Cable #5

This is a 6 foot foil shielded cable connecting the computer to the printer. It has a DB-25 pin metallic connector at the computer end, and has a 36 pin Centronics metallic connector at the printer end. The shield of the cable was grounded to the chassis via the connectors.

Cable #6

This is a 6 foot unshielded cable connecting the printer to its AC power adapter. It has a 1/4 inch round metallic connector at the printer end, and is hardwired into the power adapter. The cable was bundled to a length of 4 feet.


**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

**5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT**
**5.1 EUT and Accessory List**

EQUIPMENT TYPE	MANU-FACTURER	MODEL	SERIAL NUMBER	FCC ID
RF KEYBOARD (EUT)	LOGITECH, INC.	RT7N00	N/A	DZL127640
RECEIVER	LOGITECH, INC.	C-UA3-DUAL	N/A	DoC
COMPUTER	HEWLETT PACKARD	8180	US73553464	DoC
MOUSE	COMPAQ	M-S34	N/A	DZL211029
MONITOR	DELL	P780	9289215	DoC
EXTERNAL MODEM	US ROBOTICS	28,800 FAX/MODEM	0008390160602136	CJE-0340
PRINTER	HEWLETT PACKARD	C4582A	CN798120CZ	B94C2164X
PRINTER POWER SUPPLY	HEWLETT PACKARD	C2175A	9100-5124	N/A


**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

**5.2 EMI Test Equipment**

EQUIPMENT TYPE	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. CYCLE
Spectrum Analyzer	Hewlett Packard	8566B	3013A07296	August 2, 2001	1 Year
RF Preselector	Hewlett Packard	85685A	3010A01157	August 2, 2001	1 Year
Quasi-Peak Adapter	Hewlett Packard	85650	2521A00584	August 2, 2001	1 Year
Preamplifier	Com Power	PA-102	1482	March 1, 2001	1 Year
RF Attenuator	Mini-Circuits	CAT-10	Asset #1000	December 6, 2000	1 Year
LISN	Com Power	LI-200	12012	April 24, 2001	1 Year
LISN	Com Power	LI-200	12214	April 24, 2001	1 Year
LISN	Com Power	LI-200	1767	April 24, 2001	1 Year
LISN	Com Power	LI-200	1768	April 24, 2001	1 Year
Loop Antenna	Com Power	AL-130	25308	March 21, 2001	1 Year
Biconical Antenna	Com Power	AB-100	01557	November 11, 2000	1 Year
Log Periodic Antenna	Com Power	AL-100	16037	November 11, 2000	1 Year
Antenna Mast	Com Power	AM-400	N/A	N/A	N/A
Turntable	Com Power	TT-100	N/A	N/A	N/A
Computer	Compaq	Series 3284	X637BBS20212	N/A	N/A
Printer	Epson	P930A	3HR1398903	N/A	N/A
Plotter	Hewlett Packard	7470A	2308A96499	N/A	N/A



***ELECTRO MAGNETIC TEST, INC.***

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

---

6. **TEST SITE DESCRIPTION**

6.1 **Test Facility Description**

Please refer to section 7.1.1 and 7.1.2 of this report for EMI test location.

6.2 **EUT Mounting, Bonding and Grounding**

The EUT was mounted on a 1.0 by 1.5 meter non-conductive table 0.8 meters above the ground plane.

The EUT was not grounded.

***ELECTRO MAGNETIC TEST, INC.***1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

---

**7. TEST PROCEDURES**

The following sections describe the test methods and the specifications for the tests.

**7.1 RF Emissions****7.1.1 Conducted Emissions Test**

The HP 8566B spectrum analyzer was used as a measuring meter along with the HP 85650A quasi-peak adapter. The data was collected with the spectrum analyzer in the peak detect mode with the "Max Hold" feature activated. The quasi-peak detector was used only where indicated in the data sheets. A 10 dB attenuation pad was used for the protection of the spectrum analyzer input stage, and the spectrum analyzer offset was adjusted accordingly to read the actual data measured. The LISN output was read by the HP 8566B spectrum analyzer. The output of the second LISN was terminated by a 50 ohm termination. The effective measurement bandwidth used for the conducted emissions test was 9 kHz.

Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The EUT was powered through the LISN, which was bonded to the ground plane. The LISN power was filtered and the filter was bonded to the ground plane. The EUT was set up with the minimum distances from any conductive surfaces as specified in ANSI C63.4: 1992. The excess power cord was wrapped in a figure eight pattern to form a bundle not exceeding 0.4 meters in length.

The initial test data was taken in manual mode while scanning the frequency ranges of 0.45 MHz to 1.6 MHz, 1.6 MHz to 5 MHz and 5 MHz to 30 MHz. The conducted emissions from the EUT were maximized for operating mode as well as cable and peripheral placement. Once a predominant frequency (within 12 dB of the limit) was found, it was more closely examined with the spectrum analyzer span adjusted to 1 MHz.

The final data was collected under program control by the HP 85869PC software in several overlapping sweeps by running the spectrum analyzer at a minimum scan rate of 10 seconds per octave.

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

---

### 7.1.2 Radiated Emissions Test

The HP 8566B spectrum analyzer was used as a measuring meter along with the HP 85650A quasi-peak adapter. The Com Power Preamplifier PA-102 was used to increase the sensitivity of the instrument. The spectrum analyzer was used in the peak detect mode with the "Max Hold" feature activated. In this mode, the spectrum analyzer records the highest measured reading over all the sweeps. The HP 85650A quasi-peak adapter was used only for those readings which are marked accordingly on the data sheets. The effective measurement bandwidth used for the radiated emissions test was 10 kHz from 26.96 MHz to 27.28 MHz and 120 kHz from 30 MHz to 1000 MHz.

Broadband loop, biconical and log periodic antennas were used as transducers during the measurement. The loop antenna was used from 26.96 MHz to 27.28 MHz, the biconical antenna was used from 30 MHz to 300 MHz, and the log periodic antenna was used from 300 MHz to 1 GHz. The frequency spans were wide (30 MHz to 88 MHz, 88 MHz to 216 MHz, 216 to 300 MHz and 300 MHz to 1 GHz) during preliminary investigations. The final data was taken with a frequency span of 1 MHz. Furthermore, the frequency span was reduced during the preliminary investigations as deemed necessary.

The open field test site of Electro Magnetic Test, Inc. was used for radiated emission testing. This test site is set up according to ANSI C63.4: 1992. Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The turntable supporting the EUT is remote controlled using a motor. The turntable permits EUT rotation of 360 degrees in order to maximize emissions. Also, the antenna mast allows height variation of the antenna from 1 meter to 4 meters. Data was collected in the worst case (highest emission) configuration of the EUT. At each reading, the EUT was rotated 360 degrees and the antenna height was varied from 1 to 4 meters (for E field radiated field strength).

The presence of ambient signals was verified by turning the EUT off. In case an ambient signal was detected, the measurement bandwidth was reduced temporarily and verification was made that an additional adjacent peak did not exist. This ensures that the ambient signal does not hide any emissions from the EUT. The EUT was tested at a 3 meter test distance to obtain final test data.

Calculation Of Radiated Emission Test Data:

Amplitude - Gain + Antenna Factor + Cable Loss = Corrected Amplitude

Corrected Amplitude - Limit = Margin



***ELECTRO MAGNETIC TEST, INC.***

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

---

8.

## **CONCLUSIONS**

The RF Keyboard Model: RT7N00 meets all of the **Class B** requirements of the FCC Title 47, Part 15, Subpart B and FCC Title 47, Subpart C, Section 15.227.



**EMT**

***ELECTRO MAGNETIC TEST, INC.***

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

---

**APPENDIX A**

***RADIATED AND CONDUCTED EMISSIONS  
DATA SHEETS***

**EMT**

***ELECTRO MAGNETIC TEST, INC.***

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

---

***RADIATED AND CONDUCTED EMISSIONS  
DATA SHEETS***

Electro Magnetic Test, Inc.  
1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

## Radiated Emissions Test Data

Purpose of Test: ☒ QUALIFICATION ☐ ENGINEERING ☐ MANUFACTURING AUDIT  
FCC Class B Test Date: 08-15-01  
Company Name: LOGITECH, INC.  
EUT Model Number: RT7N00  
EUT Serial Number: N/A  
EUT Description: RF KEYBOARD

## Test Setup Configuration

EUT Clock Speeds:

EUT Power Cords: ☐ SHIELDED ☒ NOT SHIELDED  
EUT tested at: ☐ LOW SPEED ☐ HIGH SPEED  
EUT is: ☒ IN COMPLIANCE ☐ OUT OF COMPLIANCE with FCC Class B.

EUT Modifications during this test:  
☐ MODIFIED ☒ NOT MODIFIED

Modifications: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

NOTE: A formal report on passing data will be generated when required.  
Design, debug and consultation services are available at all times.

Test Engineer: MICHAEL FENNELL

Electro Magnetic Test, Inc.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

FCC Class B                      Test Date: 08-15-01  
 Company Name:                  LOGITECH, INC.  
 EUT Model Number:            RT7N00  
 EUT Description:               RF KEYBOARD

## RADIATED EMISSION TEST RESULTS

Freq MHz	Ampl dBuV	M	P	A	Ht m	Dist m	Ori deg	Gain dB	ACor dBuV/m	CCor dB	DCor dB	CorAmp dBuV/m	Limit dBuV/m	Margin dB	Flags FH---
=====	=====	=	=	=	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====

THE FOLLOWING READINGS ARE FOR THE TRANSMITTER PORTION OF THE EUT (FCC PART 15.227)  
 (FIELD STRENGTH OF FUNDAMENTAL EMISSIONS)

## VERTICAL POLARIZATION

## -FUNDAMENTAL-

27.144	49.0	P	V	M	1.0	3.0	45	0.0	5.5	0.9	0.0	55.4	80.0	-24.6	-----
--------	------	---	---	---	-----	-----	----	-----	-----	-----	-----	------	------	-------	-------

## HORIZONTAL POLARIZATION

## -FUNDAMENTAL-

27.144	45.7	P	H	M	1.0	3.0	135	0.0	5.5	0.9	0.0	52.1	80.0	-27.9	-----
--------	------	---	---	---	-----	-----	-----	-----	-----	-----	-----	------	------	-------	-------

THE FOLLOWING READINGS ARE FOR THE TRANSMITTER PORTION OF THE EUT (FCC PART 15.209)  
 (FIELD STRENGTH OF HARMONICS AND SPURIOUS EMISSIONS)

## VERTICAL POLARIZATION

## -2nd HARMONIC-

54.288	41.5	P	V	B	1.0	3.0	45	21.8	10.7	1.3	0.0	31.7	40.0	-8.3	-----
--------	------	---	---	---	-----	-----	----	------	------	-----	-----	------	------	------	-------

## -3rd HARMONIC-

81.434	40.3	P	V	B	1.0	3.0	225	21.8	9.3	1.7	0.0	29.5	40.0	-10.5	-----
--------	------	---	---	---	-----	-----	-----	------	-----	-----	-----	------	------	-------	-------

## -4th HARMONIC-

108.578	34.6	P	V	B	1.0	3.0	225	21.7	10.1	1.9	0.0	24.9	43.5	-18.6	-----
---------	------	---	---	---	-----	-----	-----	------	------	-----	-----	------	------	-------	-------

## -5th HARMONIC-

135.723	28.4	P	V	B	1.0	3.0	90	21.7	11.7	2.0	0.0	20.4	43.5	-23.1	-----
---------	------	---	---	---	-----	-----	----	------	------	-----	-----	------	------	-------	-------

## -6th HARMONIC-

162.862	30.1	P	V	B	1.5	3.0	135	21.8	13.6	2.2	0.0	24.1	43.5	-19.4	-----
---------	------	---	---	---	-----	-----	-----	------	------	-----	-----	------	------	-------	-------

## -7th HARMONIC-

190.010	34.0	P	V	B	1.0	3.0	315	21.7	15.4	2.4	0.0	30.1	43.5	-13.4	-----
---------	------	---	---	---	-----	-----	-----	------	------	-----	-----	------	------	-------	-------

## -8th HARMONIC-

217.153	32.6	P	V	B	1.0	3.0	180	21.7	16.7	2.6	0.0	30.2	46.0	-15.8	-----
---------	------	---	---	---	-----	-----	-----	------	------	-----	-----	------	------	-------	-------

## -9th HARMONIC-

244.298	27.4	P	V	B	1.5	3.0	315	21.6	18.1	2.7	0.0	26.6	46.0	-19.4	-----
---------	------	---	---	---	-----	-----	-----	------	------	-----	-----	------	------	-------	-------

## -10th HARMONIC-

271.442	29.0	P	V	B	2.0	3.0	45	21.5	20.3	2.8	0.0	30.6	46.0	-15.4	-----
---------	------	---	---	---	-----	-----	----	------	------	-----	-----	------	------	-------	-------

## HORIZONTAL POLARIZATION

## -2nd HARMONIC-

54.288	39.7	P	H	B	1.0	3.0	225	21.8	10.7	1.3	0.0	29.9	40.0	-10.1	-----
--------	------	---	---	---	-----	-----	-----	------	------	-----	-----	------	------	-------	-------

## -3rd HARMONIC-

81.434	35.0	P	H	B	1.5	3.0	45	21.8	9.3	1.7	0.0	24.2	40.0	-15.8	-----
--------	------	---	---	---	-----	-----	----	------	-----	-----	-----	------	------	-------	-------

## -4th HARMONIC-

108.576	33.9	P	H	B	2.0	3.0	135	21.7	10.1	1.9	0.0	24.2	43.5	-19.3	-----
---------	------	---	---	---	-----	-----	-----	------	------	-----	-----	------	------	-------	-------

## -5th HARMONIC-

135.720	29.0	P	H	B	2.0	3.0	315	21.7	11.7	2.0	0.0	21.0	43.5	-22.5	-----
---------	------	---	---	---	-----	-----	-----	------	------	-----	-----	------	------	-------	-------

## -6th HARMONIC-

162.864	28.5	P	H	B	1.5	3.0	45	21.8	13.6	2.2	0.0	22.5	43.5	-21.0	-----
---------	------	---	---	---	-----	-----	----	------	------	-----	-----	------	------	-------	-------

-7th HARMONIC-  
 190.009 36.1 P H B 2.0 3.0 270 21.7 15.4 2.4 0.0 32.2 43.5 -11.3 -----  
 -8th HARMONIC-  
 217.154 34.2 P H B 1.5 3.0 270 21.7 16.7 2.6 0.0 31.8 46.0 -14.2 -----  
 -9th HARMONIC-  
 244.296 27.1 P H B 1.5 3.0 0 21.6 18.1 2.7 0.0 26.3 46.0 -19.7 -----  
 -10th HARMONIC-  
 271.442 31.2 P H B 1.5 3.0 270 21.5 20.3 2.8 0.0 32.8 46.0 -13.2 -----

## THE FOLLOWING ARE SPURIOUS EMISSIONS (30-1000MHz)

## VERTICAL POLARIZATION

315.767 32.6 P V L 2.5 3.0 180 21.7 15.3 3.0 0.0 29.2 46.0 -16.8 -----  
 352.262 28.4 P V L 2.0 3.0 135 21.8 14.6 3.2 0.0 24.4 46.0 -21.6 -----  
 482.082 28.9 P V L 2.0 3.0 135 21.5 17.5 3.8 0.0 28.7 46.0 -17.3 -----

## HORIZONTAL POLARIZATION

315.767 32.7 P H L 1.5 3.0 45 21.7 15.3 3.0 0.0 29.3 46.0 -16.7 -----  
 352.286 31.2 P H L 1.5 3.0 0 21.8 14.6 3.2 0.0 27.2 46.0 -18.8 -----  
 482.079 31.1 P H L 2.0 3.0 0 21.5 17.5 3.8 0.0 30.9 46.0 -15.1 -----


THE FOLLOWING READINGS ARE FOR THE DIGITAL DEVICE PORTION OF THE EUT  
FCC PART 15.109 (30-1000MHz)

## VERTICAL POLARIZATION

166.210 37.3 P V B 1.5 3.0 0 21.8 13.8 2.2 0.0 31.5 43.5 -12.0 -----  
 217.593 40.9 P V B 2.0 3.0 225 21.7 16.7 2.6 0.0 38.5 46.0 -7.5 -----  
 299.170 40.0 P V B 1.0 3.0 180 21.7 22.3 2.9 0.0 43.5 46.0 -2.5 -----  
 299.170 38.6 Q V B 1.0 3.0 180 21.7 22.3 2.9 0.0 42.1 46.0 -3.9 -----  
 332.407 42.4 P V L 2.0 3.0 315 21.8 14.9 3.1 0.0 38.6 46.0 -7.4 -----  
 332.378 43.4 P V L 2.0 3.0 315 21.8 14.9 3.1 0.0 39.6 46.0 -6.4 -----  
 398.844 43.7 P V L 1.5 3.0 225 21.4 15.7 3.5 0.0 41.5 46.0 -4.5 -----  
 432.104 38.7 P V L 1.5 3.0 315 21.4 17.0 3.6 0.0 37.9 46.0 -8.1 -----  
 465.360 42.8 P V L 2.5 3.0 315 21.4 17.6 3.7 0.0 42.7 46.0 -3.3 -----  
 598.281 36.1 P V L 2.0 3.0 135 21.1 20.4 4.3 0.0 39.7 46.0 -6.3 -----  
 687.271 38.8 P V L 2.0 3.0 135 20.9 20.2 4.7 0.0 42.8 46.0 -3.2 -----  
 691.739 33.9 P V L 1.0 3.0 90 20.9 20.2 4.8 0.0 38.0 46.0 -8.0 -----  
 797.745 32.1 P V L 1.5 3.0 315 20.3 20.8 5.1 0.0 37.7 46.0 -8.3 -----  
 997.205 31.1 P V L 1.5 3.0 180 19.6 24.3 6.0 0.0 41.8 54.0 -12.2 -----

## HORIZONTAL POLARIZATION

166.190 36.9 P H B 1.5 3.0 270 21.8 13.8 2.2 0.0 31.1 43.5 -12.4 -----  
 217.578 29.9 P H B 2.0 3.0 180 21.7 16.7 2.6 0.0 27.5 46.0 -18.5 -----  
 299.155 43.4 P H B 2.0 3.0 180 21.7 22.3 2.9 0.0 46.9 46.0 0.9 -----  
 299.155 41.4 Q H B 2.0 3.0 180 21.7 22.3 2.9 0.0 44.9 46.0 -1.1 -----  
 332.407 42.0 P H L 2.0 3.0 135 21.8 14.9 3.1 0.0 38.2 46.0 -7.8 -----  
 398.844 40.6 P H L 2.0 3.0 135 21.4 15.7 3.5 0.0 38.4 46.0 -7.6 -----  
 432.104 40.0 P H L 2.0 3.0 180 21.4 17.0 3.6 0.0 39.2 46.0 -6.8 -----  
 465.360 42.8 P H L 2.0 3.0 225 21.4 17.6 3.7 0.0 42.7 46.0 -3.3 -----  
 598.281 35.9 P H L 2.0 3.0 45 21.1 20.4 4.3 0.0 39.5 46.0 -6.5 -----  
 687.271 37.9 P H L 2.0 3.0 315 20.9 20.2 4.7 0.0 41.9 46.0 -4.1 -----  
 691.739 37.1 P H L 2.0 3.0 90 20.9 20.2 4.8 0.0 41.2 46.0 -4.8 -----  
 797.745 30.8 P H L 2.0 3.0 225 20.3 20.8 5.1 0.0 36.4 46.0 -9.6 -----  
 997.205 27.8 P H L 2.0 3.0 45 19.6 24.3 6.0 0.0 38.5 54.0 -15.5 -----



PLOT SHOWING BANDWIDTH OF FUNDAMENTAL FREQUENCY

**EMT**

***ELECTRO MAGNETIC TEST, INC.***

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

---



**FRONT VIEW**

LOGITECH, INC.

RF KEYBOARD

MODEL: RT7N00

FCC CLASS B - RADIATED EMISSIONS - 8-14-01 & 8-15-01


**PHOTOGRAPH SHOWING THE EUT CONFIGURATION  
FOR MAXIMUM EMISSIONS**

**EMT**

***ELECTRO MAGNETIC TEST, INC.***

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

---




**REAR VIEW**

LOGITECH, INC.  
RF KEYBOARD  
MODEL: RT7N00

**FCC CLASS B - RADIATED EMISSIONS - 8-14-01 & 8-15-01**

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION  
FOR MAXIMUM EMISSIONS**





=====

ELECTRO MAGNETIC TEST, INC. 15 Aug 2001 14:59:27

=====

1. CONDUCTED WITH PRESELECTOR


1.1 FCC Part 15 - CONDUCTED

=====

45 highest Peaks above -50 dB of Limit Line #2

peak criteria = .1 dB

PEAK#	FREQ (MHz)	(dBuV)	DELTA
1	.4792	41.7	-6.3
2	26.67	41	-7.0
3	.555	40.4	-7.6
4	18.36	39.4	-8.6
5	.7139	39.3	-8.7
6	.7995	38.8	-9.2
7	.8131	38.7	-9.3
8	.6374	38.5	-9.5
9	27.24	38.1	-9.9
10	17.61	37.5	-10.5
11	18.75	37.5	-10.5
12	17.39	37.3	-10.7
13	17.83	37.2	-10.8
14	19.15	37.1	-10.9
15	1.694	36.8	-11.2
16	18.06	36.7	-11.3
17	.9536	36.6	-11.4
18	1.033	36.6	-11.4
19	.5212	36.5	-11.5
20	.7383	36.3	-11.7
21	.5886	36.2	-11.8
22	19.47	36.1	-11.9
23	25.47	36.1	-11.9
24	18.91	36	-12.0
25	.4998	35.9	-12.1
26	.8768	35.9	-12.1
27	.6846	35.8	-12.2
28	.926	35.8	-12.2
29	1.285	35.7	-12.3
30	1.659	35.7	-12.3
31	17.24	35.7	-12.3
32	1.513	35.6	-12.4
33	1.632	35.5	-12.5
34	19.89	35.5	-12.5
35	24.43	35.4	-12.6
36	.8479	35.3	-12.7
37	1.072	35.3	-12.7
38	1.206	35.3	-12.7
39	1.745	35.3	-12.7
40	2.451	35.3	-12.7
41	3.487	35.3	-12.7
42	15.99	35.3	-12.7
43	20.05	35.3	-12.7
44	.702	35.2	-12.8
45	4.677	35.2	-12.8



=====

ELECTRO MAGNETIC TEST, INC. 15 Aug 2001 14:44:52

=====

1. CONDUCTED WITH PRESELECTOR

1.1 FCC Part 15 - CONDUCTED

=====

45 highest Peaks above -50 dB of Limit Line #2

peak criteria = .1 dB

PEAK#	FREQ (MHz)	(dBuV)	DELTA
1	28.77	46.3	-1.7
2	28.29	43.2	-4.8
3	.4772	42.1	-5.9
4	.4732	41.5	-6.5
5	26.56	41.4	-6.6
6	10.55	40.7	-7.3
7	18.36	40.4	-7.6
8	.5597	40.3	-7.7
9	.8165	39.7	-8.3
10	.7929	39.5	-8.5
11	18.06	39.4	-8.6
12	.7169	39.2	-8.8
13	18.52	38.1	-9.9
14	19.47	38.1	-9.9
15	18.75	37.9	-10.1
16	.6348	37.7	-10.3
17	18.99	37.4	-10.6
18	19.15	37.4	-10.6
19	9.786	37.2	-10.8
20	.6846	36.6	-11.4
21	17.76	36.6	-11.4
22	19.89	36.6	-11.4
23	6.851	36.4	-11.6
24	.8732	36.3	-11.7
25	11.33	36.2	-11.8
26	17.24	36.2	-11.8
27	1.028	36.1	-11.9
28	.9496	36	-12.0
29	.5936	35.8	-12.2
30	3.246	35.8	-12.2
31	20.31	35.7	-12.3
32	1.374	35.6	-12.4
33	1.752	35.6	-12.4
34	5.866	35.6	-12.4
35	.9338	35.5	-12.5
36	19.72	35.5	-12.5
37	.726	35.4	-12.6
38	6.247	35.4	-12.6
39	17.61	35.4	-12.6
40	1.317	35.3	-12.7
41	21	35.3	-12.7
42	.9616	35.2	-12.8
43	12.22	35.2	-12.8
44	17.1	35.2	-12.8
45	.5458	35.1	-12.9

```
=====
ELECTRO MAGNETIC TEST, INC.      15 Aug 2001  14:44:52
=====
```

```
1. CONDUCTED WITH PRESELECTOR
```

```
1.1 FCC Part 15 - CONDUCTED
```

```
=====
Quasi-Peaks above -50 dB of Limit Line #2
```

```
peak criteria = .1 dB
```

PEAK#	FREQ (MHz)	(dBuV)	DELTA
1	28.17	26.5	-21.5
2	28.89	26.4	-21.6
3	29.25	26.3	-21.7

**EMT**

***ELECTRO MAGNETIC TEST, INC.***

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

---



**FRONT VIEW**

LOGITECH, INC.

RF KEYBOARD

MODEL: RT7N00

**FCC CLASS B - CONDUCTED EMISSIONS - 8-15-01**

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION  
FOR MAXIMUM EMISSIONS**



***ELECTRO MAGNETIC TEST, INC.***

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

---



**REAR VIEW**

LOGITECH, INC.

RF KEYBOARD

MODEL: RT7N00

**FCC CLASS B - CONDUCTED EMISSIONS - 8-15-01**

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION  
FOR MAXIMUM EMISSIONS**

**EMT**

***ELECTRO MAGNETIC TEST, INC.***

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

---


## **APPENDIX B**

### ***TEST SETUP DIAGRAMS***




**EMT****ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

**FIGURE 1 - CONDUCTED EMISSIONS TEST SETUP SITE A**


**EMT****ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

**FIGURE 2: PLOT MAP AND LAYOUT OF TEST SITE "A"**

**EMT****ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000



Wooden Test Table ↗

A. Printer	E. Receiver
B. Printer AC Power Adapter	F. External Modem
C. Monitor	G. EUT
D. Computer	H. Mouse

**FIGURE 3: EQUIPMENT CONFIGURATION BLOCK DIAGRAM**

**EMT**

***ELECTRO MAGNETIC TEST, INC.***

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

---

## **APPENDIX C**

### ***ANTENNA FACTORS AND EFFECTIVE GAIN FACTORS***


**ELECTRO MAGNETIC TEST, INC.**



1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

**LAB "A" EFFECTIVE: 3/21/01**
**COM-POWER LOOP ANTENNA MODEL: AL-130, S/N: 25308**

FREQUENCY MHz	MAGNETIC dB/m	ELECTRIC dB/m
0.09	-21.0	30.5
0.01	-23.6	27.9
0.02	-33.1	18.4
0.05	-39.7	11.8
0.075	-41.0	10.5
0.1	-41.1	10.4
0.15	-41.2	10.3
0.25	-41.4	10.1
0.5	-41.4	10.1
0.75	-41.4	10.1
1	-41.0	10.5
2	-40.8	10.7
3	-41.0	10.5
4	-40.8	10.7
5	-40.9	10.6
10	-42.0	9.5
15	-43.9	7.6
20	-44.4	7.1
25	-45.8	5.7
30	-46.2	5.3


***ELECTRO MAGNETIC TEST, INC.***1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

---

***EFFECTIVE 11-11-00******LAB "A" BICONICAL ANTENNA******AB-100 S/N: 1557******EFFECTIVE 11-11-00******LAB "A" LOG PERIODIC ANTENNA******AL-100 S/N: 16037***

**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

**LAB "A" EFFECTIVE 3-1-01****PREAMPLIFIER M/N: PA-102 S/N: 1482****EFFECTIVE GAIN AT 3 METERS****PREAMPLIFIER M/N: PA-102 S/N: 1482****EFFECTIVE GAIN AT 10 METERS**