


## TEST REPORT

**Application No.:** SZCR2104020539AT  
**Applicant:** UBTECH ROBOTICS CORP LTD  
**Address of Applicant:** 16th and 22nd Floor, Block C1, Nanshan I Park, No.1001 Xueyuan Road, Nanshan District, Shenzhen City, China  
**Manufacturer:** UBTECH ROBOTICS CORP LTD  
**Address of Manufacturer:** 16th and 22ND Floor, block C1 Nanshan I Park, NO.1001 Xueyuan Road, Nanshan District, Shenzhen City, 518055, P.R.CHINA  
**Factory:** UBTECH ROBOTICS CORP LTD BAOAN BRANCH  
**Address of Factory:** 1-2Floor, Block B, Huilongda Industry Park, Shilongzai, Shiyan Street, Baoan District, Shenzhen City, P.R.CHINA  
**Equipment Under Test (EUT):**  
**EUT Name:** ADIBOT-A  
**Model No.:** ADAA201  
**Trade Mark:** UBTECH  
**FCC ID:** 2AHJX-ADAA201  
**Standard(s) :** 47 CFR Part 15, Subpart C 15.247  
**Date of Receipt:** 2021-04-16  
**Date of Test:** 2021-04-18 to 2021-06-05  
**Date of Issue:** 2021-06-10

<b>Test Result:</b>	<b>Pass*</b>
---------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu  
EMC Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
**Attention:** To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn  
 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2021-06-10		Original

Authorized for issue by:				
		Leo Li		
		Leo Li/Project Engineer		
		Eric Fu		
		Eric Fu/Reviewer		

## 2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2013) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2013) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass

Emission Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass



### 3 Contents

	Page
1 COVER PAGE .....	1
2 TEST SUMMARY .....	3
3 CONTENTS .....	4
4 GENERAL INFORMATION .....	6
4.1 DETAILS OF E.U.T. ....	6
4.2 DESCRIPTION OF SUPPORT UNITS .....	6
4.3 MEASUREMENT UNCERTAINTY .....	7
4.4 TEST LOCATION .....	8
4.5 TEST FACILITY .....	8
4.6 DEVIATION FROM STANDARDS .....	8
4.7 ABNORMALITIES FROM STANDARD CONDITIONS .....	8
5 EQUIPMENT LIST .....	9
6 RADIO SPECTRUM TECHNICAL REQUIREMENT .....	13
6.1 ANTENNA REQUIREMENT .....	13
6.1.1 Test Requirement: .....	13
6.1.2 Conclusion .....	13
7 RADIO SPECTRUM MATTER TEST RESULTS .....	14
7.1 CONDUCTED PEAK OUTPUT POWER .....	14
7.1.1 E.U.T. Operation .....	14
7.1.2 Test Mode Description .....	14
7.1.3 Test Setup Diagram .....	15
7.1.4 Measurement Procedure and Data .....	15
7.2 MINIMUM 6dB BANDWIDTH .....	16
7.2.1 E.U.T. Operation .....	16
7.2.2 Test Mode Description .....	16
7.2.3 Test Setup Diagram .....	16
7.2.4 Measurement Procedure and Data .....	16
7.3 POWER SPECTRUM DENSITY .....	17
7.3.1 E.U.T. Operation .....	17
7.3.2 Test Mode Description .....	17
7.3.3 Test Setup Diagram .....	17
7.3.4 Measurement Procedure and Data .....	17
7.4 CONDUCTED BAND EDGES MEASUREMENT .....	18
7.4.1 E.U.T. Operation .....	18
7.4.2 Test Mode Description .....	18
7.4.3 Test Setup Diagram .....	19
7.4.4 Measurement Procedure and Data .....	19
7.5 CONDUCTED SPURIOUS EMISSIONS .....	20
7.5.1 E.U.T. Operation .....	20
7.5.2 Test Mode Description .....	20
7.5.3 Test Setup Diagram .....	21



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

7.5.4	Measurement Procedure and Data.....	21
7.6	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS.....	22
7.6.1	E.U.T. Operation.....	22
7.6.2	Test Mode Description.....	22
7.6.3	Test Setup Diagram.....	23
7.6.4	Measurement Procedure and Data.....	23
7.7	RADIATED SPURIOUS EMISSIONS BELOW 1GHZ.....	40
7.7.1	E.U.T. Operation.....	40
7.7.2	Test Mode Description.....	40
7.7.3	Test Setup Diagram.....	41
7.7.4	Measurement Procedure and Data.....	41
7.8	RADIATED SPURIOUS EMISSIONS ABOVE 1GHZ.....	50
7.8.1	E.U.T. Operation.....	50
7.8.2	Test Mode Description.....	50
7.8.3	Test Setup Diagram.....	51
7.8.4	Measurement Procedure and Data.....	52
8	EMISSION TEST RESULTS.....	77
8.1	CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz).....	77
8.1.1	E.U.T. Operation.....	77
8.1.2	Test Mode Description.....	77
8.1.3	Test Setup Diagram.....	78
8.1.4	Measurement Procedure and Data.....	78
9	TEST SETUP PHOTO.....	87
10	EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS).....	87
11	APPENDIX.....	88



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



## 4 General Information

### 4.1 Details of E.U.T.

Power supply:	DC 29V from adapter input AC 120V/60Hz Lithium Ion Battery: 25.6V 100Ah rechargeable battery which charged by adapter
Cable(s):	AC cable: 145cm unshielded DC cable: 90cm shielded
Bluetooth Version:	V5.0 LE (LB-LINK module)
Data Rate:	1Mb/s & 2Mb/s
Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	GFSK
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	Dipole Antenna(ANT2)
Antenna Gain:	2dBi
Bluetooth Version:	V5.1 LE (ABLU module)
Data Rate:	1Mb/s & 2Mb/s
Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	GFSK
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	FPC Antenna
Antenna Gain:	5.1dBi

### 4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--
The EUT has been tested as an independent unit.			

#### 4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	$\pm 3.0\text{dB}$ (150kHz to 30MHz)
Conducted Peak Output Power	$\pm 0.75\text{dB}$
Minimum 6dB Bandwidth	$\pm 3\%$
Power Spectrum Density	$\pm 2.84\text{dB}$
Conducted Band Edges Measurement	$\pm 0.75\text{dB}$
Conducted Spurious Emissions	$\pm 0.75\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 4.5\text{dB}$ (Below 1GHz); $\pm 4.8\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions Below 1GHz	$\pm 4.5\text{dB}$
Radiated Spurious Emissions Above 1GHz	$\pm 4.8\text{dB}$

**Remark:**

The  $U_{\text{lab}}$  (lab Uncertainty) is less than  $U_{\text{CISPR}}$  (CISPR Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



#### 4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

#### 4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• **VCCI (Member No. 1937)**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

• **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

#### 4.6 Deviation from Standards

None

#### 4.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
**Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com**

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



## 5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2019-06-13	2022-06-12
EMI Test Receiver	Rohde&Schwarz	ESCI	SEM004-02	2021-03-24	2022-03-23
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2020-07-10	2021-07-09
LISN	Rohde&Schwarz	ENV216	SEM007-01	2020-09-23	2021-09-22
LISN	ETS-LINDGREN	3816/2	SEM007-02	2021-03-24	2022-03-25

Conducted Peak Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2021-03-23	2022-03-22
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2021-03-24	2022-03-23
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2021-04-08	2022-04-07

Minimum 6dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2021-03-23	2022-03-22
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2021-03-24	2022-03-23
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2021-04-08	2022-04-07

Power Spectrum Density					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2021-03-23	2022-03-22
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2021-03-24	2022-03-23
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2021-04-08	2022-04-07

Conducted Band Edges Measurement					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2021-03-23	2022-03-22
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2021-03-24	2022-03-23
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2021-04-08	2022-04-07

Conducted Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2021-03-23	2022-03-22
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2021-03-24	2022-03-23
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2021-04-08	2022-04-07



Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2021-03-26	2024-03-25
EXA Signal Analyzer	Agilent Technologies Inc	N9010A	SEM004-12	2021-02-01	2022-01-31
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2021-04-14	2024-04-13
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2020-09-23	2021-09-22
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2020-07-10	2021-07-09
Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2020-11-14	2023-11-13
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2021-03-24	2022-03-23

Radiated Spurious Emissions Below 1GHz					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2020-07-19	2023-07-18
MXE EMI Receiver	Agilent Technologies	N9038A	SEM004-15	2020-11-02	2021-11-01
BiConiLog Antenna	ETS-LINDGREN	3142C	SEM003-02	2019-05-24	2022-05-23
Pre-Amplifier	Agilent Technologies	8447D	SEM005-01	2021-03-24	2022-03-23
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2020-07-10	2021-07-09

Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2021-03-26	2024-03-25
EXA Signal Analyzer	Agilent Technologies Inc	N9010A	SEM004-12	2021-02-01	2022-01-31
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2021-04-14	2024-04-13
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2020-09-23	2021-09-22
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2020-07-10	2021-07-09



General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2020-09-15	2021-09-14
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2020-09-15	2021-09-14
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2021-03-30	2022-03-29





## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

#### 6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

The use of a permanently attached antenna or of an antenna that use an unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

This requirement does not apply to carrier current devices or to devices operated under the provisions of §§ 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site.

However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 5.1dBi for ABLUE module and 2dBi for LB-LINK module.

Antenna location: Refer to page 9, page 10 and page 11 of the internal photos and page 9 of the external photos.





## 7 Radio Spectrum Matter Test Results

### 7.1 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)  
Test Method: ANSI C63.10 (2013) Section 11.9.1

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for $\geq 50$ hopping channels
	0.25 for $25 \leq$ hopping channels $< 50$
	1 for digital modulation
2400-2483.5	1 for $\geq 75$ non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

#### 7.1.1 E.U.T. Operation

Operating Environment:


Temperature: 20.7 °C Humidity: 51.6 % RH Atmospheric Pressure: 1010 mbar

#### 7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	01	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.(LB-LINK)
Final test	02	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation.(LB-LINK)
Pre-scan	03	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.(ABLU)
Pre-scan	04	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.(ABLU)
Final test	05	Charge + TX mode(1Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation.(ABLU)
Final test	06	Charge + TX mode(2Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation.(ABLU)



### 7.1.3 Test Setup Diagram



### 7.1.4 Measurement Procedure and Data

Please Refer to Appendix for Details



### 7.2 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)  
Test Method: ANSI C63.10 (2013) Section 11.8.1  
Limit:  $\geq 500$  kHz

#### 7.2.1 E.U.T. Operation


Operating Environment:

Temperature: 20.5 °C Humidity: 53.4 % RH Atmospheric Pressure: 1010 mbar

#### 7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.(LB-LINK)
Final test	03	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.(ABLU)
Final test	04	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.(ABLU)

#### 7.2.3 Test Setup Diagram



#### 7.2.4 Measurement Procedure and Data

Please Refer to Appendix for Details

### 7.3 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)  
Test Method: ANSI C63.10 (2013) Section 11.10.2  
Limit: ≤8dBm in any 3 kHz band during any time interval of continuous transmission


#### 7.3.1 E.U.T. Operation

Operating Environment:  
Temperature: 20.5 °C Humidity: 53.3 % RH Atmospheric Pressure: 1010 mbar

#### 7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.(LB-LINK)
Final test	03	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.(ABLUÉ)
Final test	04	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.(ABLUÉ)

#### 7.3.3 Test Setup Diagram



#### 7.3.4 Measurement Procedure and Data

Please Refer to Appendix for Details



## 7.4 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)  
Test Method: ANSI C63.10 (2013) Section 11.13.3.2

### Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 7.4.1 E.U.T. Operation

Operating Environment:


Temperature: 20.5 °C Humidity: 52.7 % RH Atmospheric Pressure: 1010 mbar

### 7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.(LB-LINK)
Final test	03	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.(ABLUÉ)
Final test	04	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.(ABLUÉ)



### 7.4.3 Test Setup Diagram



### 7.4.4 Measurement Procedure and Data

Please Refer to Appendix for Details



## 7.5 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 20.5 °C

Humidity: 53.1 % RH


Atmospheric Pressure: 1010 mbar

### 7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.(LB-LINK)
Final test	03	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.(ABLUÉ)
Final test	04	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.(ABLUÉ)



### 7.5.3 Test Setup Diagram



### 7.5.4 Measurement Procedure and Data

Please Refer to Appendix for Details



## 7.6 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

### 7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 21.5 °C

Humidity: 54.8 % RH

Atmospheric Pressure: 1010 mbar

### 7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	01	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.(LB-LINK)
Final test	02	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation.(LB-LINK)
Pre-scan	03	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.(ABLU)
Pre-scan	04	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.(ABLU)
Final test	05	Charge + TX mode(1Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation.(ABLU)
Final test	06	Charge + TX mode(2Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation.(ABLU)



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



### 7.6.3 Test Setup Diagram



### 7.6.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch, China, Science & Technology Park, Shenzhen, China

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



Test Mode: 02; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20539AT  
Mode : 2402 Band edge  
Note : BLE 1M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2388.445	4.34	28.87	40.42	60.47	53.26	74.00	-20.74	Peak
2	2390.000	4.34	28.88	40.42	59.01	51.81	74.00	-22.19	peak
3	2402.000	4.36	28.90	40.43	107.54	100.37	74.00	26.37	peak



Test Mode: 02; Polarity: Vertical; Modulation: GFSK; Channel: Low




Site : chamber  
Condition: 3m VERTICAL  
Job No : 20539AT  
Mode : 2402 Band edge  
Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.761	4.34	28.88	40.42	60.29	53.09	74.00	-20.91 peak
2	2390.000	4.34	28.88	40.42	60.23	53.03	74.00	-20.97 peak
3	2402.000	4.36	28.90	40.43	99.62	92.45	74.00	18.45 peak



Test Mode: 02; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20539AT  
Mode : 2480 Band edge  
Note : BLE 1M

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 . 2480.000	4.49	29.06	40.47	107.27	100.35	74.00	26.35	peak
2 2483.500	4.49	29.07	40.47	59.12	52.21	74.00	-21.79	peak
3 2484.845	4.50	29.07	40.47	59.39	52.49	74.00	-21.51	peak



Test Mode: 02; Polarity: Vertical; Modulation:GFSK; Channel:High




Site : chamber  
Condition: 3m VERTICAL  
Job No : 20539AT  
Mode : 2480 Band edge  
Note : BLE 1M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 . 2480.000		4.49	29.06	40.47	97.81	90.89	74.00	16.89	peak
2 2483.500		4.49	29.07	40.47	57.36	50.45	74.00	-23.55	peak
3 2490.070		4.50	29.08	40.47	59.02	52.13	74.00	-21.87	peak



Test Mode: 02; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20539AT  
Mode : 2402 Band edge  
Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2388.951	4.34	28.88	40.42	60.41	53.21	74.00	-20.79 Peak
2	2390.000	4.34	28.88	40.42	57.76	50.56	74.00	-23.44 peak
3	2402.000	4.36	28.90	40.43	107.57	100.40	74.00	26.40 peak





Test Mode: 02; Polarity: Vertical; Modulation: GFSK; Channel: Low




Site : chamber  
Condition: 3m VERTICAL  
Job No : 20539AT  
Mode : 2402 Band edge  
Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.356	4.34	28.88	40.42	60.81	53.61	74.00	-20.39 Peak
2	2390.000	4.34	28.88	40.42	60.56	53.36	74.00	-20.64 peak
3	2402.000	4.36	28.90	40.43	99.88	92.71	74.00	18.71 peak



Test Mode: 02; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20539AT  
Mode : 2480 Band edge  
Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 . 2480.000		4.49	29.06	40.47	107.27	100.35	74.00	26.35 peak
2 2483.500		4.49	29.07	40.47	60.13	53.22	74.00	-20.78 peak
3 2484.271		4.50	29.07	40.47	59.60	52.70	74.00	-21.30 peak



Test Mode: 02; Polarity: Vertical; Modulation:GFSK; Channel:High




Site : chamber  
Condition: 3m VERTICAL  
Job No : 20539AT  
Mode : 2480 Band edge  
Note : BLE 2M

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 . 2480.000	4.49	29.06	40.47	97.44	90.52	74.00	16.52 peak
2 2483.500	4.49	29.07	40.47	56.66	49.75	74.00	-24.25 peak
3 2490.571	4.51	29.08	40.47	59.14	52.26	74.00	-21.74 peak



Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20539AT  
Mode : 2402 Band edge  
Note : BLE 1M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2349.890	4.28	28.79	40.40	58.89	51.56	74.00	-22.44	peak
2	2390.000	4.34	28.88	40.42	56.96	49.76	74.00	-24.24	peak
3	2402.000	4.36	28.90	40.43	99.44	92.27	74.00	18.27	peak





Test Mode: 05; Polarity: Vertical; Modulation:GFSK; Channel:Low




Site : chamber  
Condition: 3m VERTICAL  
Job No : 20539AT  
Mode : 2402 Band edge  
Note : BLE 1M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2358.771	4.29	28.81	40.40	58.60	51.30	74.00	-22.70	peak
2	2390.000	4.34	28.88	40.42	56.84	49.64	74.00	-24.36	peak
3	2402.000	4.36	28.90	40.43	98.07	90.90	74.00	16.90	peak



Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20539AT  
Mode : 2480 Band edge  
Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 . 2480.000		4.49	29.06	40.47	98.90	91.98	74.00	17.98 peak
2 2483.500		4.49	29.07	40.47	59.35	52.44	74.00	-21.56 peak
3 2485.444		4.50	29.07	40.47	58.76	51.86	74.00	-22.14 peak



Test Mode: 05; Polarity: Vertical; Modulation:GFSK; Channel:High




Site : chamber  
Condition: 3m VERTICAL  
Job No : 20539AT  
Mode : 2480 Band edge  
Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1 . 2480.000		4.49	29.06	40.47	97.67	90.75	74.00	16.75 peak
2 2483.500		4.49	29.07	40.47	57.89	50.98	74.00	-23.02 peak
3 2489.570		4.50	29.08	40.47	58.52	51.63	74.00	-22.37 peak



Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20539AT  
Mode : 2402 Band edge  
Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2375.423	4.32	28.85	40.41	58.69	51.45	74.00	-22.55 peak
2	2390.000	4.34	28.88	40.42	57.66	50.46	74.00	-23.54 peak
3	2402.000	4.36	28.90	40.43	99.41	92.24	74.00	18.24 peak





Test Mode: 06; Polarity: Vertical; Modulation: GFSK; Channel: Low




Site : chamber  
Condition: 3m VERTICAL  
Job No : 20539AT  
Mode : 2402 Band edge  
Note : BLE 2M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2364.275	4.30	28.82	40.41	58.56	51.27	74.00	-22.73	peak
2	2390.000	4.34	28.88	40.42	57.23	50.03	74.00	-23.97	peak
3	2402.000	4.36	28.90	40.43	97.94	90.77	74.00	16.77	peak



Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20539AT  
Mode : 2480 Band edge  
Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 . 2480.000		4.49	29.06	40.47	98.80	91.88	74.00	17.88 peak
2 2483.500		4.49	29.07	40.47	58.10	51.19	74.00	-22.81 peak
3 2496.460		4.51	29.09	40.47	58.91	52.04	74.00	-21.96 peak



Test Mode: 06; Polarity: Vertical; Modulation:GFSK; Channel:High



Site : chamber  
Condition: 3m VERTICAL  
Job No : 20539AT  
Mode : 2480 Band edge  
Note : BLE 2M

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 . 2480.000	4.49	29.06	40.47	97.45	90.53	74.00	16.53	peak
2 2483.500	4.49	29.07	40.47	57.74	50.83	74.00	-23.17	peak
3 2487.769	4.50	29.08	40.47	58.99	52.10	74.00	-21.90	peak



## 7.7 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

### 7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 25.2 °C

Humidity: 50.3 % RH


Atmospheric Pressure: 1010 mbar

### 7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	01	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.(LB-LINK)
Final test	02	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation.(LB-LINK)
Pre-scan	03	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.(ABLU)
Pre-scan	04	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.(ABLU)
Final test	05	Charge + TX mode(1Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation.(ABLU)
Final test	06	Charge + TX mode(2Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation.(ABLU)



### 7.7.3 Test Setup Diagram



### 7.7.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch, China Standards EMC Laboratory.

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgs.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 05; Polarity: Horizontal




Site : chamber  
Condition: 3m HORIZONTAL  
Job No. : 20539AT  
Test Mode: 05

		Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	43.51	37.27	16.49	0.70	27.70	26.76	40.00	-13.24	QP
2	72.85	40.78	12.46	0.92	27.64	26.52	40.00	-13.48	QP
3	157.01	42.32	15.20	1.17	27.31	31.38	43.50	-12.12	QP
4	475.50	40.76	23.99	2.45	27.71	39.49	46.00	-6.51	QP
5 q	625.08	40.30	26.60	2.75	28.07	41.58	46.00	-4.42	QP
6	706.70	36.15	27.24	2.93	27.90	38.42	46.00	-7.58	QP



Test Mode: 05; Polarity: Vertical




Site : chamber  
Condition: 3m VERTICAL  
Job No. : 20539AT  
Test Mode: 05

		Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	q	44.74	49.96	15.97	0.70	27.69	38.94	40.00	-1.06 QP
2		73.10	52.41	12.44	0.93	27.64	38.14	40.00	-1.86 QP
3		157.01	49.91	15.20	1.17	27.31	38.97	43.50	-4.53 QP
4		282.99	43.34	18.37	1.88	26.91	36.68	46.00	-9.32 QP
5		472.18	41.25	23.75	2.45	27.69	39.76	46.00	-6.24 QP
6		706.70	38.65	27.24	2.93	27.90	40.92	46.00	-5.08 QP



Test Mode: 06; Polarity: Horizontal




Site : chamber  
Condition: 3m HORIZONTAL  
Job No. : 20539AT  
Test Mode: 06

	Ant	Cable	Preamp	Read		Limit	Over	
Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	36.64	19.54	0.67	27.49	33.69	26.41	40.00	-13.59 QP
2	70.09	12.69	0.80	27.43	44.98	31.04	40.00	-8.96 QP
3 q	140.34	13.45	1.15	27.18	47.30	34.72	43.50	-8.78 QP
4	259.23	18.11	1.71	26.79	39.69	32.72	46.00	-13.28 QP
5	562.66	25.00	2.63	27.79	34.47	34.31	46.00	-11.69 QP
6	804.60	27.77	3.31	27.47	30.75	34.36	46.00	-11.64 QP





Test Mode: 06; Polarity: Vertical




Site : chamber  
Condition: 3m VERTICAL  
Job No. : 20539AT  
Test Mode: 06

	Ant	Cable	Preamp	Read	Limit	Over	
Freq	Factor	Loss	Factor	Level	Level	Line	Limit Remark
MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB
1	44.59	16.02	0.70	27.47	47.28	36.53	40.00 -3.47 QP
2	76.51	12.37	1.07	27.42	44.73	30.75	40.00 -9.25 QP
3 q	145.86	14.17	1.15	27.16	53.47	41.63	43.50 -1.87 QP
4	252.95	18.17	1.66	26.81	41.99	35.01	46.00 -10.99 QP
5	499.42	24.11	2.50	27.58	40.36	39.39	46.00 -6.61 QP
6	813.11	27.90	3.33	27.43	34.22	38.02	46.00 -7.98 QP



Test Mode: 02; Polarity: Horizontal




Site : chamber  
Condition: 3m HORIZONTAL  
Job No. : 20539AT  
Test Mode: 02  
: 1M

	Ant Freq	Cable Factor	Preamp Loss	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB
1	35.75	19.85	0.66	27.49	35.58	28.60	40.00	-11.40 QP
2	43.51	16.49	0.70	27.47	40.04	29.76	40.00	-10.24 QP
3	70.09	12.69	0.80	27.43	44.88	30.94	40.00	-9.06 QP
4	159.23	15.35	1.17	27.10	40.03	29.45	43.50	-14.05 QP
5	348.03	20.88	2.15	26.96	41.14	37.21	46.00	-8.79 QP
6 q	734.49	27.86	3.04	27.62	34.83	38.11	46.00	-7.89 QP



Test Mode: 02; Polarity: Vertical




Site : chamber  
Condition: 3m VERTICAL  
Job No. : 20539AT  
Test Mode: 02  
: 1M

	Ant Freq	Cable Factor	Preamp Loss	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	42.30	17.22	0.70	27.47	48.12	38.57	40.00	-1.43 QP
2	70.34	12.67	0.81	27.43	51.09	37.14	40.00	-2.86 QP
3	103.08	13.90	1.10	27.38	47.94	35.56	43.50	-7.94 QP
4	152.13	14.85	1.16	27.13	51.94	40.82	43.50	-2.68 QP
5	260.14	18.11	1.72	26.79	45.89	38.93	46.00	-7.07 QP
6	407.51	21.62	2.32	27.23	45.97	42.68	46.00	-3.32 QP



Test Mode: 02; Polarity: Horizontal




Site : chamber  
Condition: 3m HORIZONTAL  
Job No. : 20539AT  
Test Mode: 02  
: 2M

	Ant Freq	Cable Factor	Preamp Loss	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	35.75	19.85	0.66	27.49	37.58	30.60	40.00	-9.40 QP
2	43.51	16.49	0.70	27.47	39.04	28.76	40.00	-11.24 QP
3	71.08	12.59	0.85	27.43	45.27	31.28	40.00	-8.72 QP
4	162.04	15.44	1.17	27.09	42.68	32.20	43.50	-11.30 QP
5 q	330.19	20.20	2.10	26.87	44.88	40.31	46.00	-5.69 QP
6	625.08	26.60	2.75	27.84	34.07	35.58	46.00	-10.42 QP





Test Mode: 02; Polarity: Vertical



Site : chamber  
Condition: 3m VERTICAL  
Job No. : 20539AT  
Test Mode: 02  
: 2M

	Ant Freq	Cable Factor	Preamp Loss	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	40.70	17.79	0.70	27.48	47.44	38.45	40.00	-1.55 QP
2	73.88	12.41	0.96	27.43	51.98	37.92	40.00	-2.08 QP
3	148.96	14.57	1.16	27.15	52.67	41.25	43.50	-2.25 QP
4	253.84	18.16	1.67	26.81	48.63	41.65	46.00	-4.35 QP
5	308.91	19.37	2.03	26.75	42.79	37.44	46.00	-8.56 QP
6	672.84	27.13	2.85	27.74	33.34	35.58	46.00	-10.42 QP



## 7.8 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.6

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

### 7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 21.5 °C

Humidity: 54.9 % RH


Atmospheric Pressure: 1010 mbar

### 7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	01	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.(LB-LINK)
Final test	02	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation.(LB-LINK)
Pre-scan	03	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.(ABLU)
Pre-scan	04	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.(ABLU)
Final test	05	Charge + TX mode(1Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation.(ABLU)
Final test	06	Charge + TX mode(2Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation.(ABLU)



### 7.8.3 Test Setup Diagram



#### 7.8.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.


Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.





Test Mode: 02; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20539AT  
Mode : 2402 TX RSE  
Note : BLE 1M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1196.264	2.76	25.09	39.76	54.27	42.36	74.00	-31.64	peak
2	4405.090	6.67	32.93	41.79	48.37	46.18	74.00	-27.82	peak
3	4804.000	7.10	33.62	42.14	48.52	47.10	74.00	-26.90	peak
4	6954.852	8.52	35.42	41.73	47.79	50.00	74.00	-24.00	peak
5	7206.000	8.74	35.67	41.50	47.21	50.12	74.00	-23.88	peak
6	9608.000	10.81	37.34	37.76	43.20	53.59	74.00	-20.41	peak



Test Mode: 02; Polarity: Vertical; Modulation: GFSK; Channel: Low




Site : chamber  
Condition: 3m VERTICAL  
Job No : 20539AT  
Mode : 2402 TX RSE  
Note : BLE 1M

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1485.841	3.24	25.67	39.94	50.81	39.78	74.00	-34.22	peak
2	4193.872	6.47	32.76	41.59	48.36	46.00	74.00	-28.00	peak
3	4804.000	7.10	33.62	42.14	48.41	46.99	74.00	-27.01	peak
4	6995.172	8.54	35.49	41.70	47.73	50.06	74.00	-23.94	peak
5	7206.000	8.74	35.67	41.50	46.89	49.80	74.00	-24.20	peak
6	9608.000	10.81	37.34	37.76	43.12	53.51	74.00	-20.49	peak



Test Mode: 02; Polarity: Horizontal; Modulation:GFSK; Channel:middle




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20539AT  
Mode : 2440 TX RSE  
Note : BLE 1M

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1597.181	3.35	26.20	40.01	49.00	38.54	74.00	-35.46	peak
2	4379.699	6.65	32.91	41.77	48.42	46.21	74.00	-27.79	peak
3	4880.000	7.18	33.77	42.20	47.29	46.04	74.00	-27.96	peak
4	6036.421	8.26	34.60	42.37	49.30	49.79	74.00	-24.21	peak
5	7320.000	8.84	35.76	41.40	47.52	50.72	74.00	-23.28	peak
6	9760.000	10.76	37.41	37.50	42.60	53.27	74.00	-20.73	peak



Test Mode: 02; Polarity: Vertical; Modulation: GFSK; Channel: middle




Site : chamber  
Condition: 3m VERTICAL  
Job No : 20539AT  
Mode : 2440 TX RSE  
Note : BLE 1M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1199.726	2.76	25.09	39.76	50.81	38.90	74.00	-35.10	peak
2	4329.354	6.60	32.87	41.72	48.28	46.03	74.00	-27.97	peak
3	4880.000	7.18	33.77	42.20	47.89	46.64	74.00	-27.36	peak
4	6395.654	8.28	34.60	42.11	48.45	49.22	74.00	-24.78	peak
5	7320.000	8.84	35.76	41.40	47.39	50.59	74.00	-23.41	peak
6	9760.000	10.76	37.41	37.50	42.97	53.64	74.00	-20.36	peak





Test Mode: 02; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20539AT  
Mode : 2480 TX RSE  
Note : BLE 1M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1485.841	3.24	25.67	39.94	49.42	38.39	74.00	-35.61	peak
2	4341.886	6.61	32.88	41.73	49.23	46.99	74.00	-27.01	peak
3	4960.000	7.26	33.92	42.27	48.02	46.93	74.00	-27.07	peak
4	6142.019	8.27	34.60	42.29	48.92	49.50	74.00	-24.50	peak
5	7440.000	8.96	35.85	41.29	47.81	51.33	74.00	-22.67	peak
6	9920.000	10.71	37.47	37.23	42.90	53.85	74.00	-20.15	peak



Test Mode: 02; Polarity: Vertical; Modulation:GFSK; Channel:High



Site : chamber  
Condition: 3m VERTICAL  
Job No : 20539AT  
Mode : 2480 TX SE  
Note : BLE 1M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1199.726	2.76	25.09	39.76	50.80	38.89	74.00	-35.11	peak
2	4417.841	6.68	32.94	41.80	49.06	46.88	74.00	-27.12	peak
3	4960.000	7.26	33.92	42.27	48.37	47.28	74.00	-26.72	peak
4	6855.063	8.47	35.25	41.80	48.11	50.03	74.00	-23.97	peak
5	7440.000	8.96	35.85	41.29	47.68	51.20	74.00	-22.80	peak
6	9920.000	10.71	37.47	37.23	42.40	53.35	74.00	-20.65	peak




SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 02; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20539AT  
Mode : 2402 TX RSE  
Note : BLE 2M

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1485.841	3.24	25.67	39.94	52.15	41.12	74.00	-32.88	peak
2	4456.315	6.72	32.97	41.84	49.05	46.90	74.00	-27.10	peak
3	4804.000	7.10	33.62	42.14	48.51	47.09	74.00	-26.91	peak
4	6974.982	8.53	35.46	41.72	47.83	50.10	74.00	-23.90	peak
5	7206.000	8.74	35.67	41.50	47.19	50.10	74.00	-23.90	peak
6	9608.000	10.81	37.34	37.76	42.71	53.10	74.00	-20.90	peak



Test Mode: 02; Polarity: Vertical; Modulation: GFSK; Channel: Low




Site : chamber  
Condition: 3m VERTICAL  
Job No : 20539AT  
Mode : 2402 TX RSE  
Note : BLE 2M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1677.621	3.41	26.59	40.05	50.27	40.22	74.00	-33.78	peak
2	4291.977	6.57	32.84	41.68	47.88	45.61	74.00	-28.39	peak
3	4804.000	7.10	33.62	42.14	47.61	46.19	74.00	-27.81	peak
4	5813.812	8.23	34.46	42.38	49.75	50.06	74.00	-23.94	peak
5	7206.000	8.74	35.67	41.50	47.59	50.50	74.00	-23.50	peak
6	9608.000	10.81	37.34	37.76	43.24	53.63	74.00	-20.37	peak





Test Mode: 02; Polarity: Horizontal; Modulation: GFSK; Channel: middle




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20539AT  
Mode : 2440 TX RSE  
Note : BLE 2M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1199.726	2.76	25.09	39.76	59.22	47.31	74.00	-26.69	peak
2	4145.664	6.43	32.72	41.54	48.24	45.85	74.00	-28.15	peak
3	4880.000	7.18	33.77	42.20	47.33	46.08	74.00	-27.92	peak
4	6756.708	8.42	35.07	41.86	48.69	50.32	74.00	-23.68	peak
5	7320.000	8.84	35.76	41.40	46.78	49.98	74.00	-24.02	peak
6	9760.000	10.76	37.41	37.50	42.80	53.47	74.00	-20.53	peak



Test Mode: 02; Polarity: Vertical; Modulation: GFSK; Channel: middle




Site : chamber  
Condition: 3m VERTICAL  
Job No : 20539AT  
Mode : 2440 TX RSE  
Note : BLE 2M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1199.726	2.76	25.09	39.76	51.37	39.46	74.00	-34.54	peak
2	4379.699	6.65	32.91	41.77	48.51	46.30	74.00	-27.70	peak
3	4880.000	7.18	33.77	42.20	47.50	46.25	74.00	-27.75	peak
4	6954.852	8.52	35.42	41.73	47.24	49.45	74.00	-24.55	peak
5	7320.000	8.84	35.76	41.40	49.64	52.84	74.00	-21.16	peak
6	9760.000	10.76	37.41	37.50	42.33	53.00	74.00	-21.00	peak



Test Mode: 02; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20539AT  
Mode : 2480 TX RSE  
Note : BLE 2M

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1196.264	2.76	25.09	39.76	56.08	44.17	74.00	-29.83	peak
2	4291.977	6.57	32.84	41.68	49.18	46.91	74.00	-27.09	peak
3	4960.000	7.26	33.92	42.27	47.75	46.66	74.00	-27.34	peak
4	6995.172	8.54	35.49	41.70	48.20	50.53	74.00	-23.47	peak
5	7440.000	8.96	35.85	41.29	48.24	51.76	74.00	-22.24	peak
6	9920.000	10.71	37.47	37.23	42.00	52.95	74.00	-21.05	peak



Test Mode: 02; Polarity: Vertical; Modulation:GFSK; Channel:High



Site : chamber  
Condition: 3m VERTICAL  
Job No : 20539AT  
Mode : 2480 TX RSE  
Note : BLE 2M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1196.264	2.76	25.09	39.76	50.86	38.95	74.00	-35.05	peak
2	4405.090	6.67	32.93	41.79	48.17	45.98	74.00	-28.02	peak
3	4960.000	7.26	33.92	42.27	47.45	46.36	74.00	-27.64	peak
4	6835.278	8.46	35.21	41.81	48.33	50.19	74.00	-23.81	peak
5	7440.000	8.96	35.85	41.29	48.24	51.76	74.00	-22.24	peak
6	9920.000	10.71	37.47	37.23	42.38	53.33	74.00	-20.67	peak




SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20539AT  
Mode : 2402 TX SE  
Note : BLE 1M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1597.181	3.35	26.20	40.01	50.72	40.26	74.00	-33.74	peak
2	4443.453	6.71	32.96	41.82	49.00	46.85	74.00	-27.15	peak
3	4804.000	7.10	33.62	42.14	48.65	47.23	74.00	-26.77	peak
4	6835.278	8.46	35.21	41.81	49.20	51.06	74.00	-22.94	peak
5	7206.000	8.74	35.67	41.50	50.92	53.83	74.00	-20.17	peak
6	8688.480	10.18	36.63	39.43	44.95	52.33	74.00	-21.67	Peak



Test Mode: 05; Polarity: Vertical; Modulation: GFSK; Channel: Low




Site : chamber  
Condition: 3m VERTICAL  
Job No : 20539AT  
Mode : 2402 TX SE  
Note : BLE 1M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1597.181	3.35	26.20	40.01	49.72	39.26	74.00	-34.74	peak
2	4405.090	6.67	32.93	41.79	48.65	46.46	74.00	-27.54	peak
3	4804.000	7.10	33.62	42.14	48.56	47.14	74.00	-26.86	peak
4	5780.300	8.23	34.43	42.38	48.88	49.16	74.00	-24.84	Peak
5	6874.906	8.48	35.28	41.78	48.83	50.81	74.00	-23.19	peak
6	7206.000	8.74	35.67	41.50	49.59	52.50	74.00	-21.50	peak



Test Mode: 05; Polarity: Horizontal; Modulation: GFSK; Channel: middle




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20539AT  
Mode : 2440 TX SE  
Note : BLE 1M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1597.181	3.35	26.20	40.01	51.67	41.21	74.00	-32.79	peak
2	4354.454	6.63	32.89	41.74	49.92	47.70	74.00	-26.30	peak
3	4880.000	7.18	33.77	42.20	48.78	47.53	74.00	-26.47	peak
4	5864.443	8.24	34.49	42.39	50.19	50.53	74.00	-23.47	peak
5	7320.000	8.85	35.76	41.39	46.77	49.99	54.00	-4.01	Average
6	7320.000	8.84	35.76	41.40	52.30	55.50	74.00	-18.50	peak
7	8638.399	10.16	36.57	39.53	44.91	52.11	74.00	-21.89	Peak



Test Mode: 05; Polarity: Vertical; Modulation:GFSK; Channel:middle




Site : chamber  
Condition: 3m VERTICAL  
Job No : 20539AT  
Mode : 2440 TX SE  
Note : BLE 1M

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1597.181	3.35	26.20	40.01	51.38	40.92	74.00	-33.08	peak
2	4242.641	6.52	32.80	41.64	49.52	47.20	74.00	-26.80	peak
3	4880.000	7.18	33.77	42.20	47.73	46.48	74.00	-27.52	peak
4	6894.806	8.49	35.32	41.77	48.51	50.55	74.00	-23.45	peak
5	7320.000	8.84	35.76	41.40	49.20	52.40	74.00	-21.60	peak
6	8688.480	10.18	36.63	39.43	45.46	52.84	74.00	-21.16	Peak





Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20539AT  
Mode : 2480 TX SE  
Note : BLE 1M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1601.804	3.35	26.22	40.01	52.19	41.75	74.00	-32.25	peak
2	4417.841	6.68	32.94	41.80	48.77	46.59	74.00	-27.41	peak
3	4960.000	7.26	33.92	42.27	48.04	46.95	74.00	-27.05	peak
4	6954.852	8.52	35.42	41.73	48.50	50.71	74.00	-23.29	peak
5	7440.000	8.95	35.85	41.30	46.85	50.35	54.00	-3.65	Average
6	7440.000	8.96	35.85	41.29	53.65	57.17	74.00	-16.83	peak
7	8814.957	10.23	36.78	39.19	45.19	53.01	74.00	-20.99	Peak



Test Mode: 05; Polarity: Vertical; Modulation:GFSK; Channel:High




Site : chamber  
Condition: 3m VERTICAL  
Job No : 20539AT  
Mode : 2480 TX SE  
Note : BLE 1M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1592.571	3.34	26.18	40.00	55.36	44.88	74.00	-29.12	peak
2	4242.641	6.52	32.80	41.64	49.06	46.74	74.00	-27.26	peak
3	4960.000	7.26	33.92	42.27	48.12	47.03	74.00	-26.97	peak
4	6717.762	8.40	35.00	41.89	48.56	50.07	74.00	-23.93	peak
5	7440.000	8.96	35.85	41.29	43.51	47.03	54.00	-6.97	Average
6	7440.000	8.96	35.85	41.29	51.58	55.10	74.00	-18.90	peak
7	8613.468	10.15	36.54	39.57	45.72	52.84	74.00	-21.16	Peak



Test Mode: 06; Polarity: Horizontal; Modulation: GFSK; Channel: Low




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20539AT  
Mode : 2402 TX SE  
Note : BLE 2M

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1597.181	3.35	26.20	40.01	49.24	38.78	74.00	-35.22	peak
2	4430.628	6.70	32.95	41.81	49.49	47.33	74.00	-26.67	peak
3	4804.000	7.10	33.62	42.14	48.39	46.97	74.00	-27.03	peak
4	5471.422	8.13	34.19	42.35	50.39	50.36	74.00	-23.64	peak
5	7206.000	8.74	35.67	41.50	49.63	52.54	74.00	-21.46	peak
6	8789.516	10.22	36.75	39.24	44.55	52.28	74.00	-21.72	Peak



Test Mode: 06; Polarity: Vertical; Modulation: GFSK; Channel: Low




Site : chamber  
Condition: 3m VERTICAL  
Job No : 20539AT  
Mode : 2402 TX SE  
Note : BLE 2M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1601.804	3.35	26.22	40.01	52.86	42.42	74.00	-31.58	peak
2	4267.237	6.54	32.82	41.66	48.63	46.33	74.00	-27.67	peak
3	4804.000	7.10	33.62	42.14	48.56	47.14	74.00	-26.86	peak
4	6995.172	8.54	35.49	41.70	48.20	50.53	74.00	-23.47	peak
5	7206.000	8.74	35.67	41.50	49.03	51.94	74.00	-22.06	peak
6	8663.404	10.17	36.60	39.48	45.24	52.53	74.00	-21.47	Peak





Test Mode: 06; Polarity: Horizontal; Modulation: GFSK; Channel: middle




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20539AT  
Mode : 2440 TX SE  
Note : BLE 2M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1597.181	3.35	26.20	40.01	53.21	42.75	74.00	-31.25	peak
2	4098.010	6.38	32.68	41.50	48.79	46.35	74.00	-27.65	peak
3	4880.000	7.18	33.77	42.20	48.33	47.08	74.00	-26.92	peak
4	5984.305	8.26	34.59	42.40	49.96	50.41	74.00	-23.59	peak
5	7320.000	8.84	35.76	41.40	50.69	53.89	74.00	-20.11	peak
6	8343.918	9.89	36.31	40.10	46.77	52.87	74.00	-21.13	Peak



Test Mode: 06; Polarity: Vertical; Modulation: GFSK; Channel: middle




Site : chamber  
Condition: 3m VERTICAL  
Job No : 20539AT  
Mode : 2440 TX SE  
Note : BLE 2M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1597.181	3.35	26.20	40.01	51.29	40.83	74.00	-33.17	peak
2	3703.723	5.84	32.08	41.21	49.91	46.62	74.00	-27.38	peak
3	4880.000	7.18	33.77	42.20	47.88	46.63	74.00	-27.37	peak
4	6934.778	8.51	35.39	41.74	48.14	50.30	74.00	-23.70	peak
5	7320.000	8.84	35.76	41.40	48.27	51.47	74.00	-22.53	peak
6	8738.852	10.20	36.69	39.34	44.74	52.29	74.00	-21.71	Peak



Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; Channel:High



Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 20539AT  
Mode : 2480 TX SE  
Note : BLE 2M

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	3.35	26.20	40.01	49.81	39.35	74.00	-34.65	peak
2	6.72	32.97	41.84	49.11	46.96	74.00	-27.04	peak
3	7.26	33.92	42.27	48.26	47.17	74.00	-26.83	peak
4	8.47	35.25	41.80	49.90	51.82	74.00	-22.18	peak
5	8.95	35.85	41.30	46.49	49.99	54.00	-4.01	Average
6	8.96	35.85	41.29	53.14	56.66	74.00	-17.34	peak
7	10.38	37.05	38.71	44.04	52.76	74.00	-21.24	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch (SGS-CSTC Laboratory)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 06; Polarity: Vertical; Modulation:GFSK; Channel:High



Site : chamber  
Condition: 3m VERTICAL  
Job No : 20539AT  
Mode : 2480 TX SE  
Note : BLE 2M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1597.181	3.35	26.20	40.01	50.48	40.02	74.00	-33.98	peak
2	4354.454	6.63	32.89	41.74	48.92	46.70	74.00	-27.30	peak
3	4960.000	7.26	33.92	42.27	48.75	47.66	74.00	-26.34	peak
4	6995.172	8.54	35.49	41.70	48.82	51.15	74.00	-22.85	peak
5	7440.000	8.96	35.85	41.29	43.65	47.17	54.00	-6.83	Average
6	7440.000	8.96	35.85	41.29	51.96	55.48	74.00	-18.52	peak
7	8789.516	10.22	36.75	39.24	44.92	52.65	74.00	-21.35	Peak





## 8 Emission Test Results

### 8.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement: 47 CFR Part 15, Subpart C 15.247  
 47 CFR Part 15, Subpart C 15.207  
 Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		
Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz		


#### 8.1.1 E.U.T. Operation

Operating Environment:  
 Temperature: 24.0 °C Humidity: 59.9 % RH Atmospheric Pressure: 1010 mbar

#### 8.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation.(LB-LINK)
Final test	05	Charge + TX mode(1Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation.(ABLUE)
Final test	06	Charge + TX mode(2Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation.(ABLUE)

### 8.1.3 Test Setup Diagram




### 8.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor



Test Mode: 02; Line: Live line; Modulation:GFSK; Channel:Low




Site : Shielding Room  
Condition: Line  
Job No. : 20539AT  
Test mode: 02 1M

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1624	0.03	9.63	32.19	41.85	55.34	-13.49	Average
2	0.1624	0.03	9.63	37.91	47.57	65.34	-17.77	QP
3	0.2603	0.05	9.65	28.55	38.25	51.42	-13.17	Average
4	0.2603	0.05	9.65	34.81	44.51	61.42	-16.91	QP
5	2.7356	0.14	9.70	21.45	31.29	46.00	-14.71	Average
6	2.7356	0.14	9.70	31.65	41.49	56.00	-14.51	QP
7	3.1900	0.14	9.72	23.76	33.62	46.00	-12.38	Average
8	3.1900	0.14	9.72	33.39	43.25	56.00	-12.75	QP
9	4.6964	0.16	9.76	20.95	30.87	46.00	-15.13	Average
10	4.6964	0.16	9.76	30.50	40.42	56.00	-15.58	QP
11	26.8411	0.19	9.99	19.97	30.15	50.00	-19.85	Average
12	26.8411	0.19	9.99	29.83	40.01	60.00	-19.99	QP



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Test Mode: 02; Line: Neutral Line; Modulation: GFSK; Channel: Low




Site : Shielding Room  
Condition: Neutral  
Job No. : 20539AT  
Test mode: 02 1M

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1624	0.03	9.63	31.33	40.99	55.34	-14.35	Average
2	0.1624	0.03	9.63	36.92	46.58	65.34	-18.76	QP
3	0.2575	0.05	9.65	30.25	39.95	51.51	-11.56	Average
4	0.2575	0.05	9.65	37.21	46.91	61.51	-14.60	QP
5	1.0430	0.10	9.67	16.51	26.28	46.00	-19.72	Average
6	1.0430	0.10	9.67	24.40	34.17	56.00	-21.83	QP
7	3.2411	0.14	9.71	24.11	33.96	46.00	-12.04	Average
8	3.2411	0.14	9.71	32.12	41.97	56.00	-14.03	QP
9	6.4198	0.16	9.81	21.33	31.30	50.00	-18.70	Average
10	6.4198	0.16	9.81	28.76	38.73	60.00	-21.27	QP
11	16.1399	0.16	9.98	20.87	31.01	50.00	-18.99	Average
12	16.1399	0.16	9.98	30.94	41.08	60.00	-18.92	QP





Test Mode: 02; Line: Live line; Modulation:GFSK; Channel:Low




Site : Shielding Room  
Condition: Line  
Job No. : 20539AT  
Test mode: 02 2M

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1615	0.03	9.63	31.53	41.19	55.38	-14.19	Average
2	0.1615	0.03	9.63	38.75	48.41	65.38	-16.97	QP
3	0.2589	0.05	9.65	29.48	39.18	51.47	-12.29	Average
4	0.2589	0.05	9.65	36.32	46.02	61.47	-15.45	QP
5	0.5854	0.08	9.68	19.26	29.02	46.00	-16.98	Average
6	0.5854	0.08	9.68	24.49	34.25	56.00	-21.75	QP
7	2.7356	0.14	9.70	21.22	31.06	46.00	-14.94	Average
8	2.7356	0.14	9.70	31.91	41.75	56.00	-14.25	QP
9	3.0576	0.14	9.71	21.77	31.62	46.00	-14.38	Average
10	3.0576	0.14	9.71	33.25	43.10	56.00	-12.90	QP
11	26.9837	0.19	9.99	19.18	29.36	50.00	-20.64	Average
12	26.9837	0.19	9.99	30.46	40.64	60.00	-19.36	QP



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Test Mode: 02; Line: Neutral Line; Modulation:GFSK; Channel:Low




Site : Shielding Room  
Condition: Neutral  
Job No. : 20539AT  
Test mode: 02 2M

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1624	0.03	9.63	31.43	41.09	55.34	-14.25	Average
2	0.1624	0.03	9.63	37.62	47.28	65.34	-18.06	QP
3	0.2589	0.05	9.65	30.58	40.28	51.47	-11.19	Average
4	0.2589	0.05	9.65	37.38	47.08	61.47	-14.39	QP
5	0.5210	0.07	9.67	20.54	30.28	46.00	-15.72	Average
6	0.5210	0.07	9.67	26.20	35.94	56.00	-20.06	QP
7	2.9935	0.14	9.70	17.96	27.80	46.00	-18.20	Average
8	2.9935	0.14	9.70	29.40	39.24	56.00	-16.76	QP
9	3.2069	0.14	9.71	22.77	32.62	46.00	-13.38	Average
10	3.2069	0.14	9.71	31.34	41.19	56.00	-14.81	QP
11	16.1399	0.16	9.98	19.67	29.81	50.00	-20.19	Average
12	16.1399	0.16	9.98	30.51	40.65	60.00	-19.35	QP



Test Mode: 06; Line: Live line; Modulation: GFSK; Channel: Low




Site : Shielding Room  
Condition: Line  
Job No. : 20539AT  
Test mode: 06

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1659	0.03	9.63	31.06	40.72	55.16	-14.44	Average
2	0.1659	0.03	9.63	37.16	46.82	65.16	-18.34	QP
3	0.2589	0.05	9.65	29.16	38.86	51.47	-12.61	Average
4	0.2589	0.05	9.65	34.44	44.14	61.47	-17.33	QP
5	0.5854	0.08	9.68	19.92	29.68	46.00	-16.32	Average
6	0.5854	0.08	9.68	25.56	35.32	56.00	-20.68	QP
7	3.1231	0.14	9.71	23.52	33.37	46.00	-12.63	Average
8	3.1231	0.14	9.71	32.80	42.65	56.00	-13.35	QP
9	4.5494	0.16	9.76	20.54	30.46	46.00	-15.54	Average
10	4.5494	0.16	9.76	31.72	41.64	56.00	-14.36	QP
11	26.5581	0.19	9.99	20.20	30.38	50.00	-19.62	Average
12	26.5581	0.19	9.99	31.06	41.24	60.00	-18.76	QP





Test Mode: 06; Line: Neutral Line; Modulation: GFSK; Channel: Low




Site : Shielding Room  
Condition: Neutral  
Job No. : 20539AT  
Test mode: 06

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1677	0.03	9.63	31.06	40.72	55.08	-14.36	Average
2	0.1677	0.03	9.63	35.40	45.06	65.08	-20.02	QP
3	0.2575	0.05	9.65	31.00	40.70	51.51	-10.81	Average
4	0.2575	0.05	9.65	37.56	47.26	61.51	-14.25	QP
5	1.0375	0.10	9.67	16.69	26.46	46.00	-19.54	Average
6	1.0375	0.10	9.67	26.45	36.22	56.00	-19.78	QP
7	3.2756	0.14	9.71	24.46	34.31	46.00	-11.69	Average
8	3.2756	0.14	9.71	31.79	41.64	56.00	-14.36	QP
9	6.4198	0.16	9.81	19.78	29.75	50.00	-20.25	Average
10	6.4198	0.16	9.81	29.79	39.76	60.00	-20.24	QP
11	16.1399	0.16	9.98	20.73	30.87	50.00	-19.13	Average
12	16.1399	0.16	9.98	30.14	40.28	60.00	-19.72	QP





Test Mode: 05; Line: Live line; Modulation: GFSK; Channel: Low




Site : Shielding Room  
Condition: Line  
Job No. : 20539AT  
Test mode: 05

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1659	0.03	9.63	31.62	41.28	55.16	-13.88	Average
2	0.1659	0.03	9.63	37.67	47.33	65.16	-17.83	QP
3	0.2481	0.05	9.65	30.50	40.20	51.82	-11.62	Average
4	0.2481	0.05	9.65	34.47	44.17	61.82	-17.65	QP
5	3.0901	0.14	9.71	25.00	34.85	46.00	-11.15	Average
6	3.0901	0.14	9.71	31.85	41.70	56.00	-14.30	QP
7	4.4305	0.16	9.75	21.31	31.22	46.00	-14.78	Average
8	4.4305	0.16	9.75	31.02	40.93	56.00	-15.07	QP
9	6.1209	0.16	9.81	22.20	32.17	50.00	-17.83	Average
10	6.1209	0.16	9.81	31.42	41.39	60.00	-18.61	QP
11	26.1393	0.19	9.99	20.68	30.86	50.00	-19.14	Average
12	26.1393	0.19	9.99	31.42	41.60	60.00	-18.40	QP



Test Mode: 05; Line: Neutral Line; Modulation: GFSK; Channel: Low



Site : Shielding Room  
Condition: Neutral  
Job No. : 20539AT  
Test mode: 05

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1650	0.03	9.63	31.62	41.28	55.21	-13.93	Average
2	0.1650	0.03	9.63	36.66	46.32	65.21	-18.89	QP
3	0.2575	0.05	9.65	30.09	39.79	51.51	-11.72	Average
4	0.2575	0.05	9.65	35.02	44.72	61.51	-16.79	QP
5	2.5945	0.14	9.69	20.84	30.67	46.00	-15.33	Average
6	2.5945	0.14	9.69	28.52	38.35	56.00	-17.65	QP
7	3.2411	0.14	9.71	24.15	34.00	46.00	-12.00	Average
8	3.2411	0.14	9.71	31.10	40.95	56.00	-15.05	QP
9	6.4198	0.16	9.81	19.47	29.44	50.00	-20.56	Average
10	6.4198	0.16	9.81	29.19	39.16	60.00	-20.84	QP
11	16.1399	0.16	9.98	20.55	30.69	50.00	-19.31	Average
12	16.1399	0.16	9.98	30.71	40.85	60.00	-19.15	QP



## 9 Test Setup Photo

Refer to Setup Photos

## 10 EUT Constructional Details (EUT Photos)

Refer to EUT external and internal photos



## 11 Appendix

### LB-LINK Module


### Appendix for 15.247

#### 1. Duty Cycle



##### 1.1 Test Result



Test Mode	Channel Frequency (MHz)	TX Type	ANT No.	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)
1M	2402	SISO	1	2.137	2.501	85.45	0.68
	2440	SISO	1	2.137	2.501	85.45	0.68
	2480	SISO	1	2.138	2.499	85.55	0.68
2M	2402	SISO	1	1.080	1.874	57.63	2.39
	2440	SISO	1	1.060	1.841	57.58	2.40
	2480	SISO	1	1.080	1.876	57.57	2.40


##### 1.2 Test Graph











## 2. Bandwidth



### 2.1 Test Result



Test Mode	Frequency (MHz)	TX Type	ANT No.	6dB Bandwidth	Verdict
				Test Result (MHz)	
1M	2402	SISO	1	0.663	PASS
	2440	SISO	1	0.661	PASS
	2480	SISO	1	0.663	PASS
2M	2402	SISO	1	1.128	PASS
	2440	SISO	1	1.139	PASS
	2480	SISO	1	1.129	PASS



Test Mode	Frequency (MHz)	TX Type	ANT No.	99% Occupied Bandwidth	
				Test Result (MHz)	
1M	2402	SISO	1	1.025	Only for Report Use
	2440	SISO	1	1.028	Only for Report Use
	2480	SISO	1	1.028	Only for Report Use
2M	2402	SISO	1	2.054	Only for Report Use
	2440	SISO	1	2.051	Only for Report Use
	2480	SISO	1	2.049	Only for Report Use





### 2.2 Test Graph - 6dB Bandwidth











### 2.3 Test Graph - 99% Occupied Bandwidth












### 3. Maximum Conducted Output Power

#### 3.1 Test Result



Test Mode	Frequency (MHz)	Tx Type	Measured Peak Output Power (dBm)	Limits (dBm)	Verdict
			Ant 1		
1M	2402	SISO	5.62	30	PASS
	2440	SISO	5.35	30	PASS
	2480	SISO	5.69	30	PASS
2M	2402	SISO	5.60	30	PASS
	2440	SISO	5.42	30	PASS
	2480	SISO	5.74	30	PASS


#### 3.2 Test Graph














### 4. Maximum Power Spectral Density (PSD)

#### 4.1 Test Result



Test Mode	Frequency (MHz)	Tx Type	Maximum Power Spectral Density (dBm/3KHz)	Limits (dBm/3KHz)	Verdict
			Ant 1		
1M	2402	SISO	-10.80	≤8	PASS
	2440	SISO	-10.42	≤8	PASS
	2480	SISO	-9.76	≤8	PASS
2M	2402	SISO	-12.74	≤8	PASS
	2440	SISO	-12.79	≤8	PASS
	2480	SISO	-12.27	≤8	PASS


#### 4.2 Test Graph














### 5. Unwanted Emissions in Non-restricted Frequency Bands

#### 5.1 Test Result



Test Mode	Frequency (MHz)	TX Type	ANT No.	Spurious Conducted Emission (dBm)	Limits (dBm)	Verdict
1M	2402	SISO	1	Refer to test graph	-14.37	PASS
	2440	SISO	1	Refer to test graph	-14.37	PASS
	2480	SISO	1	Refer to test graph	-14.37	PASS
2M	2402	SISO	1	Refer to test graph	-14.43	PASS
	2440	SISO	1	Refer to test graph	-14.43	PASS
	2480	SISO	1	Refer to test graph	-14.43	PASS



#### 5.2 Test Graph
























### Appendix for 15.247


#### ABLU Module



#### 1. Duty Cycle



##### 1.1 Test Result

Test Mode	Channel Frequency (MHz)	TX Type	ANT No.	T <sub>on</sub> (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)
1M	2402	SISO	1	0.392	0.625	62.72	2.03
	2440	SISO	1	0.392	0.625	62.72	2.03
	2480	SISO	1	0.392	0.625	62.72	2.03
2M	2402	SISO	1	0.206	0.625	32.96	4.82
	2440	SISO	1	0.206	0.625	32.96	4.82
	2480	SISO	1	0.207	0.626	33.07	4.81


##### 1.2 Test Graph











## 2. Bandwidth

### 2.1 Test Result

Test Mode	Frequency (MHz)	TX Type	ANT No.	6dB Bandwidth	Verdict
				Test Result (MHz)	
1M	2402	SISO	1	0.690	PASS
	2440	SISO	1	0.688	PASS
	2480	SISO	1	0.690	PASS
2M	2402	SISO	1	1.136	PASS
	2440	SISO	1	1.136	PASS
	2480	SISO	1	1.127	PASS

Test Mode	Frequency (MHz)	TX Type	ANT No.	99% Occupied Bandwidth	
				Test Result (MHz)	
1M	2402	SISO	1	1.049	Only for Report Use
	2440	SISO	1	1.048	Only for Report Use
	2480	SISO	1	1.049	Only for Report Use
2M	2402	SISO	1	2.036	Only for Report Use
	2440	SISO	1	2.038	Only for Report Use
	2480	SISO	1	2.037	Only for Report Use





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)



SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch, China, CSTC Laboratory.

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

### 2.2 Test Graph - 6dB Bandwidth















### 2.3 Test Graph - 99% Occupied Bandwidth








### 3. Maximum Conducted Output Power



#### 3.1 Test Result



Test Mode	Frequency (MHz)	Tx Type	Measured Peak Output Power (dBm)	Limits (dBm)	Verdict
			Ant 1		
1M	2402	SISO	4.32	30	PASS
	2440	SISO	3.28	30	PASS
	2480	SISO	3.67	30	PASS
2M	2402	SISO	4.31	30	PASS
	2440	SISO	3.30	30	PASS
	2480	SISO	3.70	30	PASS


#### 3.2 Test Graph












### 4. Maximum Power Spectral Density (PSD)



#### 4.1 Test Result



Test Mode	Frequency (MHz)	Tx Type	Maximum Power Spectral Density (dBm/3KHz)	Limits (dBm/3KHz)	Verdict
			Ant 1		
1M	2402	SISO	-10.39	≤8	PASS
	2440	SISO	-11.57	≤8	PASS
	2480	SISO	-11.41	≤8	PASS
2M	2402	SISO	-12.96	≤8	PASS
	2440	SISO	-14.17	≤8	PASS
	2480	SISO	-13.85	≤8	PASS


#### 4.2 Test Graph












### 5. Unwanted Emissions in Non-restricted Frequency Bands



#### 5.1 Test Result



Test Mode	Frequency (MHz)	TX Type	ANT No.	Spurious Conducted Emission (dBm)	Limits (dBm)	Verdict
1M	2402	SISO	1	Refer to test graph	-15.78	PASS
	2440	SISO	1	Refer to test graph	-15.78	PASS
	2480	SISO	1	Refer to test graph	-15.78	PASS
2M	2402	SISO	1	Refer to test graph	-15.80	PASS
	2440	SISO	1	Refer to test graph	-15.80	PASS
	2480	SISO	1	Refer to test graph	-15.80	PASS



#### 5.2 Test Graph


















Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)







- End of the Report -

