


## RF Exposure Evaluation Report

**Client:** Toro Company

**Address:** 8111 Lyndale Ave S,  
Bloomington Minnesota, USA

**Model:** Nova Gen. 2

**Test Report No.:** RFE20241011-73-M1A

**Approved By:**   
Fox Lane,  
EMC Test Engineer

**Date:** February 5, 2025

**Total Pages:** 8

*The Nebraska Center for Excellence in Electronics (NCEE) authorizes the above-named company to reproduce this report provided it is reproduced in its entirety for use by the company's employees only. Any use that a third party makes of this report, or any reliance on or decisions made based on it, are the responsibility of such third parties. NCEE accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.*

# Revision Page

Rev. No.	Date	Description
Original	3 February 2025	Issued by FLane Prepared by FLane
A	5 February 2025	Updated Company Name Added multi-transmitter evaluation – FL

# 1 Regulatory Requirements:

FCC Part 1.1310, 2.1091, 2.1093  
KDB 447498 D01  
RSS-102, Issue 6

## **Summary:**

The purpose of this report is to evaluate the EUT's transmitter for exemption from routine SAR testing.

## **EUT:**

Model:	<b>Nova Gen. 2</b>
FCC ID:	<b>OF7-NVG2</b>
IC:	<b>3575A-NVG2</b>
HVIN:	<b>NVG2</b>

MPE Lab	Nebraska Center for Excellence in Electronics
MPE Labs FCC Cab Designation:	US1060
MPE Labs ISED Cab Designation:	US0177

## 2 FCC

### FCC Limits, Part 1.1310

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

Occupational/Controlled	<input type="checkbox"/>
General Population/uncontrolled	<input checked="" type="checkbox"/>

FCC Power Density Calculations								
Freq.	Conducted Power	Antenna Gain	Peak Power EIRP	Peak Power EIRP +10% for Tolerance	Power Density	Limit at specified distance	% of limit	Result
MHz	mW	numerical	mW	mW	mW/cm^2	mW/cm^2	%	
663.00	316.228	2.09	660.92	727.01	0.145	0.44	32.723	PASS
669.00	316.228	2.09	660.92	727.01	0.145	0.45	32.429	PASS
777.00	316.228	2.09	660.92	727.01	0.145	0.52	27.922	PASS
788.00	316.228	2.09	660.92	727.01	0.145	0.53	27.532	PASS
826.40	316.228	2.09	660.92	727.01	0.145	0.55	26.252	PASS
824.00	316.228	2.09	660.92	727.01	0.145	0.55	26.329	PASS
1710.00	316.228	1.95	616.64	678.31	0.135	1.14	11.837	PASS
1710.00	316.228	1.95	616.64	678.31	0.135	1.14	11.837	PASS
1710.00	316.228	1.95	616.64	678.31	0.135	1.14	11.837	PASS
1850.00	316.228	1.95	616.64	678.31	0.135	1.23	10.942	PASS
1850.00	316.228	1.95	616.64	678.31	0.135	1.23	10.942	PASS
2412.00	16.010	0.95	15.21	16.73	0.003	11.20	0.030	PASS
5240.00	14.550	1.48	21.53	23.69	0.005	12.20	0.039	PASS

Distance (d)	20	cm
--------------	----	----

$S = (P \times G)/(4 \times \pi \times d^2)$  – used to calculate exposure at "d" cm

$EIRP = P \times G$ , measured as field strength

$d = \sqrt{(S/(P \times G) \times 4 \times \pi)}$  – used to calculate minimum distance to meet limits

S = power density (mW/cm<sup>2</sup>)

P = transmitter conducted power (in mW)

G = antenna numeric gain (Numerical)

d = distance to radiation center (cm)

**Total % of Limit = 32.723 + 0.03 + 0.039 = 32.792%**

This shows compliance.

**Results:**  
**Complies**

**Note:**

The user's manual will stipulate that a 20cm distance from the user is to be maintained.

EIRP values in mW were multiplied by 1.1 to account for a 10% tolerance.

Conducted Power values were taken from Module manufacturer RF exposure report

Antenna Gain values were taken from antenna document, peak gain was used.

### 3 ISED

#### RSS 102, Issue 6, Section 6.4 (for distances less than 20cm)

Devices operating at or below the applicable output power levels (adjusted for tune-up tolerance) specified in table 11, based on the separation distance, are exempt from SAR evaluation. The separation distance, defined as the distance between the user and/or bystander and the antenna and/or radiating element of the device or the outer surface of the device, shall be less than or equal to 20 cm for these exemption limits to apply.

Table 11: Power limits for exemption from routine SAR evaluation based on the separation distance

Frequency (MHz)	≤ 5 mm(mW)	10 mm (mW)	15 mm(mW)	20 mm(mW)	25 mm(mW)	30 mm(mW)	35 mm(mW)	40 mm(mW)	45 mm(mW)	> 50 mm(mW)
≤ 300	45	116	139	163	189	216	246	280	319	362
450	32	71	87	104	124	147	175	208	248	296
835	21	32	41	54	72	96	129	172	228	298
1900	6	10	18	33	57	92	138	194	257	323
2450	3	7	16	32	56	89	128	170	209	245
3500	2	6	15	29	50	72	94	114	134	158
5800	1	5	13	23	32	41	54	74	102	128

The exemption limits in table 11 are based on measurements and simulations of half-wave dipole antennas at separation distances of 5 mm to 50 mm from a flat phantom, which provides a SAR value of approximately 0.4 W/kg for 1 g of tissue.

For limb-worn devices where the 10 gram of tissue applies, the exemption limits for routine evaluation in table 11 are multiplied by a factor of 2.5.

For controlled-use devices where the 8 W/kg for 1 gram of tissue applies, the exemption limits for routine evaluation in table 11 are multiplied by a factor of 5.

When the operating frequency of the device is between two frequencies located in table 11, linear interpolation shall be applied for the applicable separation distance. If the separation distance of the device is between two distances located in table 11, linear interpolation may be applied for the applicable frequency. Alternatively, the limit corresponding to the smaller distance may be employed. For example, in case of a 7 mm separation distance, either use the exception value for a 5 mm separation distance or interpolate between the limits corresponding to 5 mm and 10 mm separation distances.

For implanted medical devices, the exemption limit for routine SAR evaluation is set at an output power of 1 mW, regardless of frequency.

The SAR levels from exempted transmitters shall be included in the compliance assessment and the determination of the TER. Detailed guidance is included in sections 7.1.8 and 8.2.2.1.

### **RSS 102, Issue 6, Section 6.6 (for distances 20cm or greater)**

Field reference level (FRL) exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm (i.e. mobile devices), except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 1 W (adjusted for tune-up tolerance)
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than  $4.49/f^{0.5} W$  (adjusted for tune-up tolerance), where  $f$  is in MHz
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance)
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834} W$  (adjusted for tune-up tolerance), where  $f$  is in MHz
- at or above 6 GHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 5 W (adjusted for tune-up tolerance)

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the EIRP was derived.

Occupational/Controlled			<input type="checkbox"/>			
General Population/uncontrolled			<input checked="" type="checkbox"/>			
ISED Power Density Calculations						
Frequency	Cond. Power	Antenna Gain	Peak Power EIRP	Peak Power EIRP +10% for Tolerance	Exemption Limit	Result
MHz	mW	numerical	mW	mW	mW	
663.00	316.228	2.09	660.92	727.01	1110.44	PASS
669.00	316.228	2.09	660.92	727.01	1117.29	PASS
777.00	316.228	2.09	660.92	727.01	1237.61	PASS
788.00	316.228	2.09	660.92	727.01	1249.56	PASS
826.40	316.228	2.09	660.92	727.01	1290.86	PASS
824.00	316.228	2.09	660.92	727.01	1288.30	PASS
1710.00	316.228	1.95	616.64	678.31	2121.78	PASS
1710.00	316.228	1.95	616.64	678.31	2121.78	PASS
1710.00	316.228	1.95	616.64	678.31	2121.78	PASS
1850.00	316.228	1.95	616.64	678.31	2239.01	PASS
1850.00	316.228	1.95	616.64	678.31	2239.01	PASS
2412.00	16.010	0.95	15.21	16.73	2684.03	PASS
5240.00	14.550	1.48	21.53	23.69	4561.02	PASS

Distance (d)	20	cm
--------------	----	----

**$S = (P \times G)/(4 \times \pi \times d^2)$  – used to calculate exposure at "d" cm**

**$EIRP = P \times G$ , measured as field strength**

**$d = \sqrt{(S/(P \times G) \times 4 \times \pi)}$  – used to calculate minimum distance to meet limits**

S = power density (mW/cm<sup>2</sup>)

P = transmitter conducted power (in mW)

G = antenna numeric gain (Numerical)

d = distance to radiation center (cm)

### Result:

The EUT was found to be exempt from routine SAR testing and **COMPLIANT** with FCC and ISED RF exposure requirements.

## REPORT END