


RF Test Report

For

Globe Electric Company Inc.

Test Standards:	Part 15C Subpart C §15.247 RSS 247 Issue 2
Product Name:	Smart 70.90" LED Torchiere
Tested Model:	50404
Brand Name:	Globe
FCC ID:	2AQUOGL50404
IC:	8290A-GL50404
Classification	(DTS) Digital Transmission System
Report No.:	EC2104015RF01
Tested Date:	2021-04-16 to 2021-05-20
Issued Date:	2021-05-20
Prepared By:	 Jack Liu / Engineer
Approved By:	 Tiny Yang / RF Manager

Hunan Ecloud Testing Technology Co., Ltd.
Building A1, Changsha E Center, No. 18 Xiangtai Avenue, Liuyang Economic and
Technological Development Zone, Hunan, P.R.C
Tel.: +86-731-89634887 Fax.: +86-731-89634887
www.hn-ecloud.com

Note: The test results in this report apply exclusively to the tested model / sample. Without written approval of

Hunan Ecloud Testing Technology Co., Ltd., the test report shall not be reproduced except in full.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	2021.05.20	Valid	Original Report

TABLE OF CONTENTS

1	TEST LABORATORY	5
1.1	Test facility	5
2	GENERAL DESCRIPTION.....	6
2.1	Applicant	6
2.2	Manufacturer	6
2.3	General Description Of EUT	6
2.4	Modification of EUT	7
2.5	Applicable Standards.....	7
3	TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	8
3.1	Descriptions of Test Mode	8
3.2	Test Mode	8
3.3	Support Equipment	9
3.4	Test Setup	10
3.5	Measurement Results Explanation Example.....	14
4	TEST RESULT	15
4.1	DTS and Occupied Channel Bandwidth Measurement.....	15
4.2	Maximum Conducted Output Power Measurement	16
4.3	Maximum Power Spectral Density Measurement	17
4.4	Band Edges and Spurious Emission Measurement	18
4.5	Radiated Band Edges and Spurious Emission Measurement	19
4.6	AC Conducted Emission Measurement.....	103
4.7	Antenna Requirements.....	106
5	LIST OF MEASURING EQUIPMENT.....	107
6	UNCERTAINTY OF EVALUATION.....	109
	Appendix A: DTS Bandwidth.....	110
	Appendix B: Occupied Channel Bandwidth	117
	Appendix C: Maximum conducted output power	124
	Appendix D: Duty Cycle.....	131
	Appendix E: Maximum power spectral density.....	138
	Appendix F: Band edge measurements.....	145
	Appendix G: Conducted Spurious Emission	150
	Appendix H: Setup Photographs	170

Summary Of Test Result

FCC Rule	IC Rule	Description	Limit	Result	Remark
15.247(a)(2)	RSS-247 5.2(a)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
-	RSS-Gen 6.7	99% Bandwidth	-	Pass	-
15.247(b)(3)	RSS-247 A5.4(d)	Output Power	$\leq 30\text{dBm}$	Pass	-
15.247(e)	RSS-247 5.2(b)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
15.247(d)	RSS-247 5.5	Conducted Band Edges and Spurious Emission	$\leq 30\text{dBc}$	Pass	-
15.247(d)	RSS-247 5.5	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 1.57 dB at 4924 MHz
15.207	RSS-GEN 8.8	AC Conducted Emission	15.207(a)	Pass	Under limit 1.20 dB at 0.880 MHz
15.203 & 15.247(b)	RSS-GEN 6.8	Antenna Requirement	15.203 & 15.247(b) RSS-GEN 6.8	Pass	-

1 Test Laboratory

1.1 Test facility

CNAS (accreditation number: L11138)

Hunan Ecloud Testing Technology Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

FCC (Designation number: CN1244 , Test Firm Registration Number: 793308)

Hunan Ecloud Testing Technology Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

ISED(CAB identifier: CN0012, ISED# :24347)

Hunan Ecloud Testing Technology Co., Ltd. has been listed on the Wireless Device Testing Laboratories list of innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements.

A2LA (Certificate Code : 4895.01)

Hunan Ecloud Testing Technology Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

2 General Description

2.1 Applicant

Globe Electric Company Inc.
150, Oneida, Montreal, Quebec, Canada, H9R 1A8

2.2 Manufacturer

Globe Electric Company Inc.
150, Oneida, Montreal, Quebec, Canada, H9R 1A8

2.3 General Description Of EUT

Product	Smart 70.90" LED Torchiere
Model No.	50404
Brand Name	Globe
Additional No.	N/A
Difference Description	N/A
FCC ID	2AQUQGL50404
IC	8290A-GL50404
Power Supply*	120Vac
Modulation Technology	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Type	802.11b : DSSS 802.11g/n : OFDM
Operating Frequency	2412-2462MHz
Number Of Channel	11
Max. Output Power	802.11b : 15.43 dBm (0.0349 W) 802.11g : 14.16 dBm (0.0261 W) 802.11n HT20 : 13.98 dBm (0.0250 W) 802.11n HT40 : 13.44 dBm (0.0221 W)
Max. e.i.r.p.	18.43 dBm (0.0697W)
Antenna Type	PCB Antenna type with 3dBi gain
HW Version	V1.0
SW Version	0019
I/O Ports	Refer to user's manual

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the

user's manual.

2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

2.4 Modification of EUT

No modifications are made to the EUT during all test items.

2.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2013
- ♦ IC RSS-247 Issue 2
- ♦ IC RSS-Gen Issue 5
- ♦ KDB 558074 D01 15.247 Meas Guidance v05r02

Remark:

1. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B&ICES-005, recorded in a separate test report.

3 Test Configuration of Equipment Under Test

3.1 Descriptions of Test Mode

11 channels are provided for 802.11b, 802.11g and 802.11n(HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n(HT40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
		7	2442 MHz
		8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz		
5	2432 MHz		
6	2437 MHz		

The transmitter has a maximum conducted output power as follows:

Frequency Range(MHz)	Mode	Rate	Output Power(dBm)
2412~2462	802.11b	1Mbps	15.43
2412~2462	802.11g	6Mbps	14.16
2412~2462	802.11n HT20	MCS0	13.98
2422~2452	802.11n HT40	MCS0	13.44

- a. Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

3.2 Test Mode

3.2.1 Antenna Port Conducted Measurement

Summary table of Test Cases				
Test Item	Modulation			
	802.11 b	802.11 g	802.11n HT20	802.11n HT40
Conducted	Mode 1: CH01	Mode 1: CH01	Mode 1: CH01	Mode 1: CH03

Test Cases	Mode 2: CH06 Mode 3: CH011	Mode 2: CH06 Mode 3: CH011	Mode 2: CH06 Mode 3: CH011	Mode 2: CH06 Mode 3: CH09
-------------------	-------------------------------	-------------------------------	-------------------------------	------------------------------

3.2.2 Radiated Emission Test (Below 1GHz)

Radiated Test Cases	802.11 b Mode 1: CH01
----------------------------	---------------------------------

- Note : 1. Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type. Z orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Z orientation.
2. Following channel(s) was (were) selected for the final test as listed above

3.2.3 Radiated Emission Test (Above 1GHz)

Test Item	Modulation			
	802.11 b	802.11 g	802.11n HT20	802.11n HT40
Radiated Test Cases	Mode 1: CH01 Mode 2: CH06 Mode 3: CH11	Mode 1: CH01 Mode 2: CH06 Mode 3: CH11	Mode 1: CH01 Mode 2: CH06 Mode 3: CH11	Mode 1: CH03 Mode 2: CH06 Mode 3: CH09

- Note : 1. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that Z orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Z orientation.
2. Following channel(s) was (were) selected for the final test as listed above
3. For frequency above 18GHz, the measured value is much lower than the limit, therefore, it is not reflected in the report.

3.2.4 Power Line Conducted Emission Test:

AC Conducted Emission	Mode 1 : WLAN Linking + Lighting
------------------------------	----------------------------------

3.3 Support Equipment

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	NETGEAR	R7800	PY315100319	N/A	shielded, 1.8 m
2.	Notebook	Lenovo	E470C	FCC sDoC	N/A	shielded cable DC O/P 1.8 m unshielded AC


						I/P cable1.2 m
--	--	--	--	--	--	----------------

3.4 Test Setup


The EUT is continuously communicating to the WIFI tester during the tests.

EUT was set in the Hidden menu mode to enable WIFI communications.


The following picture is a screenshot of the test software




Setup diagram for Conducted Test




Setup diagram for Raidation(9KHz~30MHz) Test




Setup diagram for Radiation(Below 1G) Test



Setup diagram for Radiation (Above 1G) Test



Setup diagram for AC Conducted Emission Test



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.5 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 5 + 10 = 15 \text{ (dB)}\end{aligned}$$

For all radiated test items:

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

Over Limit (dB μ V/m) = Level(dB μ V/m) - Limit Level (dB μ V/m)

4 Test Result

4.1 DTS and Occupied Channel Bandwidth Measurement

4.1.1 Limit of 6dB Bandwidth

FCC §15.247 (a) (2)

IC RSS-247 5.2(a)

The minimum 6 dB bandwidth shall be at least 500 kHz.

4.1.2 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v05r02.
2. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
3. Turn on the EUT and connect it to measurement instrument.
4. Set to the maximum power setting and enable Transmitting the EUT transmit continuously
5. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
6. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) setting should be 1%-5% of OBW, please revise and set the Video bandwidth (VBW) $\geq 3 \times$ RBW.

4.1.3 Test Result of 6dB Bandwidth

Refer to Appendix A of this test report.

4.1.4 Test Result of 99% Bandwidth

Refer to Appendix B of this test report.

4.2 Maximum Conducted Output Power Measurement

4.2.1 Limit of Output Power

FCC §15.247 (b)(3)

For systems using digital modulation in the 2400-2483.5 MHz bands: 30dBm.

IC RSS-247 A5.4(d)

For DTSs employing digital modulation techniques operating in the bands 902-928MHz and 2400-2483.5MHz, the maximum peak conducted output power shall not exceed 1 W.

The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e)

4.2.2 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 section 11.9.2.2.4 Measurement using a spectrum analyzer.
2. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
3. Turn on the EUT and connect it to spectrum analyzer.
4. Set to the maximum power setting and enable Transmitting the EUT transmit continuously
5. Measure the duty cycle, x, of the transmitter output signal as described in below:
 - a. Set the center frequency of the instrument to the center frequency of the transmission.
 - b. Set RBW to the largest available Transmitting value.
 - c. Set detector = peak
6. Set span to at least 1.5*OBW. Set RBW=510KHz, VBW=2MHz, Number of points in sweep $\geq 2/3$ * span, Sweep time = auto. Detector = RMS
7. Allow the sweep to "free run". Trace average 100 traces in RMS mode
8. Compute power by integrating the spectrum across the OBW of the signal using the instrument's Channel power measurement function with band limits set equal to the OBW band edges.
9. Add $10 \log (1/x)$, where x is the duty cycle. The duty cycle factor has been compensated to the "offset" of the spectrum analyser.

4.2.3 Test Result of Output Power

Refer to Appendix C of this test report.

4.2.4 Test Result of Duty Cycle

Refer to Appendix D of this test report.

4.3 Maximum Power Spectral Density Measurement

4.3.1 Limits of Power Spectral Density

FCC§15.247(e)

IC RSS-247 5.2(b)

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

4.3.2 Test Procedure

1. The testing follows Measurement Procedure 8.4 DTS maximum power spectral density level in the fundamental emission of ANSI C63.10-2013 section 11.9.2.2.4
2. Turn on the EUT and connect it to measurement instrument.
3. Measure the duty cycle, x , of the transmitter output signal as described in below:
 - a. Set the center frequency of the instrument to the center frequency of the transmission.
 - b. Set RBW to the largest available Transmitting value.
 - c. Set detector = peak
4. Set span to at least $1.5 \times \text{OBW}$. Set RBW= 30 KHz, VBW=100 KHz, Number of points in sweep $\geq 2/3 \times \text{span}$, Sweep time = auto.
5. Detector = power averaging (rms), Sweep time = auto couple, Trace mode = averaging (rms) mode over a minimum of 100 traces. Use the peak marker function to determine the maximum power level.
6. Add $10 \log(1/x)$, where x is the duty cycle.
7. Measure and record the results in the test report.
8. The Measured power density (dBm)/ 100kHz is a reference level and used as 30dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.
9. Add $10 \log(1/x)$, where x is the duty cycle. The duty cycle factor has been compensated to the 'offset' of the spectrum analyser.

4.3.3 Test Result of Power Spectral Density

Refer to Appendix E of this test report.

4.4 Band Edges and Spurious Emission Measurement

4.4.1 Limit of Conducted Band Edges and Spurious Emission

FCC §15.247 (d)

IC RSS-247 5.5

Maximum conducted (average) output power was used to determine compliance, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).

4.4.2 Test Procedures

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument.
3. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
4. Measure and record the results in the test report.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

4.4.3 Test Result of Conducted Band Edges

Refer to Appendix F of this test report.

4.4.4 Test Result of Conducted Spurious Emission

Refer to Appendix G of this test report.

4.5 Radiated Band Edges and Spurious Emission Measurement

4.5.1 Limit of Radiated Band Edges and Spurious Emission

FCC §15.247 (d)

IC RSS-247 5.5


In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 30 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3


4.5.2 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The measurement distance is 3 meter.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1\text{ GHz}$, RBW=1MHz for $f > 1\text{ GHz}$; VBW RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement:
VBW = 10 Hz, when duty cycle is no less than 98 percent.
VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	100.00	-	-	10Hz
802.11g	100.00	-	-	10Hz
802.11n HT20	100.00	-	-	10Hz
802.11n HT40	100.00	-	-	10Hz




802.11b



802.11g



802.11n HT20



6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


4.5.3 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

4.5.4 Test Result of Radiated Spurious at Band Edges

Test Mode :	802.11b CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Horizontal

Test Site : 3m Chamber	Temp/Humi : 24℃/62%
Tested by : Jack	Pol/Phase : HORIZONTAL
Test Mode : 802.11b CH01(2412MHz)	Power rating: 120VAC




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	43.22	27.38	4.08	35.68	39.00	74.00	-35.00	Peak
2390.000	46.24	27.56	4.16	35.88	42.08	74.00	-31.92	Peak
2410.875	101.64	27.60	4.17	35.93	97.48	74.00	23.48	Peak

Test Mode :	802.11b CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b CH01(2412MHz)	Power rating	: 120Wac


Data: 485



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	30.96	27.38	4.08	35.68	26.74	54.00	-27.26	Average
2385.500	35.54	27.55	4.16	35.86	31.39	54.00	-22.61	Average
2390.000	34.43	27.56	4.16	35.88	30.27	54.00	-23.73	Average
2411.250	98.01	27.60	4.17	35.93	93.85	54.00	39.85	Average

Test Mode :	802.11b CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH01(2412MHz)	Power rating	: 120Vac




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	41.43	27.38	4.08	35.68	37.21	74.00	-36.79	Peak
2340.625	45.81	27.45	4.11	35.75	41.62	74.00	-32.38	Peak
2390.000	41.71	27.56	4.16	35.88	37.55	74.00	-36.45	Peak
2410.875	95.46	27.60	4.17	35.93	91.30	74.00	17.30	Peak

Test Mode :	802.11b CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH01(2412MHz)	Power rating	: 120VAc


Data: 482



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	28.42	27.38	4.08	35.68	24.20	54.00	-29.80	Average
2390.000	29.50	27.56	4.16	35.88	25.34	54.00	-28.66	Average
2411.250	91.86	27.60	4.17	35.93	87.70	54.00	33.70	Average

Test Mode :	802.11b CH11 (2462 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Horizontal


Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b CH11(2462MHz)	Power rating:	120Vac



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2463.140	101.93	27.72	4.19	36.06	97.78	74.00	23.78	Peak
2483.500	50.24	27.76	4.19	36.11	46.08	74.00	-27.92	Peak
2500.000	50.85	27.80	4.19	36.15	46.69	74.00	-27.31	Peak


Test Mode :	802.11b CH11 (2462 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b CH11(2462MHz)	Power rating:	120VAc



Test Mode :	802.11b CH11 (2462 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH11(2462MHz)	Power rating:	120Vac



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2463.380	93.77	27.72	4.19	36.06	89.62	74.00	15.62	Peak
2483.500	44.59	27.76	4.19	36.11	40.43	74.00	-33.57	Peak
2487.980	46.18	27.77	4.19	36.12	42.02	74.00	-31.98	Peak
2500.000	44.94	27.80	4.19	36.15	40.78	74.00	-33.22	Peak

Test Mode :	802.11b CH11 (2462 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH11(2462MHz)	Power rating:	120Vac



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2462.720	90.03	27.72	4.19	36.06	85.88	54.00	31.88	Average
2483.500	31.31	27.76	4.19	36.11	27.15	54.00	-26.85	Average
2488.280	32.62	27.77	4.19	36.12	28.46	54.00	-25.54	Average
2500.000	32.08	27.80	4.19	36.15	27.92	54.00	-26.08	Average


Test Mode :	802.11g CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Horizontal

Test Site : 3m Chamber
 Temp/Humi : 24℃/62%
 Tested by : Jack
 Pol/Phase : HORIZONTAL
 Test Mode : 802.11g CH01(2412MHz)
 Power rating: 120VAc




Test Mode :	802.11g CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g CH01(2412MHz)	Power rating:	120VAc



Test Mode :	802.11g CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11g CH01(2412MHz)	Power rating	: 120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	40.14	27.38	4.08	35.68	35.92	74.00	-38.08	Peak
2390.000	45.09	27.56	4.16	35.88	40.93	74.00	-33.07	Peak
2412.875	96.12	27.61	4.17	35.93	91.97	74.00	17.97	Peak


Test Mode :	802.11g CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11g CH01(2412MHz)	Power rating	: 120VAc



Test Mode :	802.11g CH11 (2462 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Horizontal


Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g CH11(2462MHz)	Power rating:	120Vac



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2462.840	103.91	27.72	4.19	36.06	99.76	74.00	25.76	Peak
2483.500	56.54	27.76	4.19	36.11	52.38	74.00	-21.62	Peak
2500.000	50.65	27.80	4.19	36.15	46.49	74.00	-27.51	Peak

Test Mode :	802.11g CH11 (2462 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Horizontal


Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g CH11(2462MHz)	Power rating:	120Vac



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2467.220	93.09	27.73	4.19	36.07	88.94	54.00	34.94	Average
2483.500	44.25	27.76	4.19	36.11	40.09	54.00	-13.91	Average
2500.000	37.56	27.80	4.19	36.15	33.40	54.00	-20.60	Average

Test Mode :	802.11g CH11 (2462 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11g CH11(2462MHz)	Power rating:	120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2462.900	97.03	27.72	4.19	36.06	92.88	74.00	18.88	Peak
2483.500	48.76	27.76	4.19	36.11	44.60	74.00	-29.40	Peak
2500.000	44.36	27.80	4.19	36.15	40.20	74.00	-33.80	Peak


Test Mode :	802.11g CH11 (2462 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11g CH11(2462MHz)	Power rating:	120Vac



Test Mode :	802.11n HT20 CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Horizontal


Test Site : 3m Chamber
 Temp/Humi : 24℃/62%
 Tested by : Jack
 Pol/Phase : HORIZONTAL
 Test Mode : 802.11N HT20 CH01(2412MHz)
 Power rating: 120Vac



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	45.79	27.38	4.08	35.68	41.57	74.00	-32.43	Peak
2389.125	55.04	27.56	4.16	35.87	50.89	74.00	-23.11	Peak
2390.000	54.27	27.56	4.16	35.88	50.11	74.00	-23.89	Peak
2416.750	103.56	27.62	4.17	35.94	99.41	74.00	25.41	Peak


Test Mode :	802.11n HT20 CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Horizontal

Test Site : 3m Chamber
 Temp/Humi : 24℃/62%
 Tested by : Jack
 Pol/Phase : HORIZONTAL
 Test Mode : 802.11N HT20 CH01(2412MHz)
 Power rating: 120VAc



Test Mode :	802.11n HT20 CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11N HT20 CH01(2412MHz)	Power rating:	120VAc




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamplifier factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	39.87	27.38	4.08	35.68	35.65	74.00	-38.35	Peak
2390.000	48.14	27.56	4.16	35.88	43.98	74.00	-30.02	Peak
2416.750	95.12	27.62	4.17	35.94	90.97	74.00	16.97	Peak

Test Mode :	802.11n HT20 CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Vertical

Test Site : 3m Chamber
 Temp/Humi : 24℃/62%
 Tested by : Jack
 Pol/Phase : VERTICAL
 Test Mode : 802.11N HT20 CH01(2412MHz)
 Power rating: 120VAc


Data: 510



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	28.13	27.38	4.08	35.68	23.91	54.00	-30.09	Average
2390.000	34.04	27.56	4.16	35.88	29.88	54.00	-24.12	Average
2406.750	83.85	27.59	4.17	35.92	79.69	54.00	25.69	Average

Test Mode :	802.11n HT20 CH11 (2462 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT20 CH11(2462MHz)	Power rating:	120Vac




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2466.620	103.68	27.73	4.19	36.07	99.53	74.00	25.53	Peak
2483.500	58.39	27.76	4.19	36.11	54.23	74.00	-19.77	Peak
2500.000	51.10	27.80	4.19	36.15	46.94	74.00	-27.06	Peak

Test Mode :	802.11n HT20 CH11 (2462 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Horizontal

Test Site : 3m Chamber
 Temp/Humi : 24℃/62%
 Tested by : Jack
 Pol/Phase : HORIZONTAL
 Test Mode : 802.11N HT20 CH11(2462MHz)
 Power rating: 120Vac


Data: 521



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2467.160	92.07	27.73	4.19	36.07	87.92	54.00	33.92	Average
2483.500	42.57	27.76	4.19	36.11	38.41	54.00	-15.59	Average
2500.000	37.24	27.80	4.19	36.15	33.08	54.00	-20.92	Average

Test Mode :	802.11n HT20 CH11 (2462 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11N HT20 CH11(2462MHz)	Power rating:	120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2466.620	96.21	27.73	4.19	36.07	92.06	74.00	18.06	Peak
2483.500	51.88	27.76	4.19	36.11	47.72	74.00	-26.28	Peak
2500.000	45.14	27.80	4.19	36.15	40.98	74.00	-33.02	Peak


Test Mode :	802.11n HT20 CH11 (2462 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11N HT20 CH11(2462MHz)	Power rating:	120Vac



Test Mode :	802.11n HT40 CH03 (2422 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.45GHz	Polarization :	Horizontal

Test Site : 3m Chamber
 Temp/Humi : 24℃/62%
 Tested by : Jack
 Pol/Phase : HORIZONTAL
 Test Mode : 802.11N HT40 CH03(2422MHz)
 Power rating: 120Vac




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	43.58	27.38	4.08	35.68	39.36	74.00	-34.64	Peak
2389.250	54.51	27.56	4.16	35.87	50.36	74.00	-23.64	Peak
2390.000	53.82	27.56	4.16	35.88	49.66	74.00	-24.34	Peak
2430.950	101.04	27.65	4.18	35.98	96.89	74.00	22.89	Peak

Test Mode :	802.11n HT40 CH03 (2422 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.45GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT40 CH03(2422MHz)	Power rating:	120VAc

Data: 524




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	31.21	27.38	4.08	35.68	26.99	54.00	-27.01	Average
2390.000	41.65	27.56	4.16	35.88	37.49	54.00	-16.51	Average
2431.250	89.77	27.65	4.18	35.98	85.62	54.00	31.62	Average

Test Mode :	802.11n HT40 CH03 (2422 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.45GHz	Polarization :	Vertical

Test Site : 3m Chamber
 Temp/Humi : 24℃/62%
 Tested by : Jack
 Pol/Phase : VERTICAL
 Test Mode : 802.11N HT40 CH03(2422MHz)
 Power rating: 120VAc

Data: 526




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	39.78	27.38	4.08	35.68	35.56	74.00	-38.44	Peak
2390.000	46.29	27.56	4.16	35.88	42.13	74.00	-31.87	Peak
2418.650	93.75	27.62	4.17	35.95	89.59	74.00	15.59	Peak

Test Mode :	802.11n HT40 CH03 (2422 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.45GHz	Polarization :	Vertical

Test Site : 3m Chamber
 Temp/Humi : 24℃/62%
 Tested by : Jack
 Pol/Phase : VERTICAL
 Test Mode : 802.11N HT40 CH03(2422MHz)
 Power rating: 120VAc


Data: 527



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	28.35	27.38	4.08	35.68	24.13	54.00	-29.87	Average
2390.000	34.81	27.56	4.16	35.88	30.65	54.00	-23.35	Average
2420.600	82.74	27.63	4.18	35.95	78.60	54.00	24.60	Average

Test Mode :	802.11n HT40 CH09 (2452 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.425GHz~2.51GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT40 CH09(2452MHz)	Power rating:	120Vac




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2460.700	101.52	27.71	4.19	36.05	97.37	74.00	23.37	Peak
2483.500	58.54	27.76	4.19	36.11	54.38	74.00	-19.62	Peak
2484.330	59.66	27.77	4.19	36.11	55.51	74.00	-18.49	Peak
2500.000	51.27	27.80	4.19	36.15	47.11	74.00	-26.89	Peak

Test Mode :	802.11n HT40 CH09 (2452 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.425GHz~2.51GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT40 CH09(2452MHz)	Power rating:	120VAc


Data: 535



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2461.125	89.91	27.71	4.19	36.05	85.76	54.00	31.76	Average
2483.500	46.36	27.76	4.19	36.11	42.20	54.00	-11.80	Average
2500.000	38.65	27.80	4.19	36.15	34.49	54.00	-19.51	Average

Test Mode :	802.11n HT40 CH09 (2452 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.425GHz~2.51GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11N HT40 CH09(2452MHz)	Power rating:	120VAc




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2460.955	94.64	27.71	4.19	36.05	90.49	74.00	16.49	Peak
2483.500	49.65	27.76	4.19	36.11	45.49	74.00	-28.51	Peak
2500.000	45.75	27.80	4.19	36.15	41.59	74.00	-32.41	Peak

Test Mode :	802.11n HT40 CH09 (2452 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.425GHz~2.51GHz	Polarization :	Vertical

Test Site : 3m Chamber
 Temp/Humi : 24℃/62%
 Tested by : Jack
 Pol/Phase : VERTICAL
 Test Mode : 802.11N HT40 CH09(2452MHz)
 Power rating: 120VAc

Data: 532




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2461.125	82.90	27.71	4.19	36.05	78.75	54.00	24.75	Average
2483.500	36.42	27.76	4.19	36.11	32.26	54.00	-21.74	Average
2500.000	31.41	27.80	4.19	36.15	27.25	54.00	-26.75	Average

4.5.1 Test Result of Radiated Spurious Emission (1GHz ~ 10th Harmonic)

Test Mode :	802.11b CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal


Test Site : 3m Chamber	Temp/Humi : 24℃/62%
Tested by : Jack	Pol/Phase : HORIZONTAL
Test Mode : 802.11b CH01(2412MHz)	Power rating: 120VAC



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2412.000	101.62	27.61	4.17	35.93	97.47	74.00	23.47	Peak


Test Mode :	802.11b CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b CH01(2412MHz)	Power rating:	120VAc



Test Mode :	802.11b CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH01(2412MHz)	Power rating:	120VAc




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2412.000	95.43	27.61	4.17	35.93	91.28	74.00	17.28	Peak

Test Mode :	802.11b CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH01(2412MHz)	Power rating:	: 120VAc

Data: 592




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4824.000	48.85	30.95	6.59	34.09	52.30	54.00	-1.70	Average
4824.000	50.14	30.95	6.59	34.09	53.59	74.00	-20.41	Peak
7236.000	25.37	35.47	8.71	34.41	35.14	54.00	-18.86	Average
7236.000	39.59	35.47	8.71	34.41	49.36	74.00	-24.64	Peak
9648.000	26.42	38.42	11.55	34.16	42.23	54.00	-11.77	Average
9648.000	39.93	38.42	11.55	34.16	55.74	74.00	-18.26	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11b CH06 (2437MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b CH06(2437MHz)	Power rating:	120VAc




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2437.000	101.87	27.66	4.18	35.99	97.72	74.00	23.72	Peak

Test Mode :	802.11b CH06 (2437MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b CH06(2437MHz)	Power rating	: 120VAc

Data: 596




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4874.000	48.11	31.02	6.97	34.04	52.06	54.00	-1.94	Average
4874.000	55.44	31.02	6.97	34.04	59.39	74.00	-14.61	Peak
7311.000	25.76	35.65	8.95	34.48	35.88	54.00	-18.12	Average
7311.000	38.81	35.65	8.95	34.48	48.93	74.00	-25.07	Peak
9748.000	26.26	38.50	11.20	34.20	41.76	54.00	-12.24	Average
9748.000	39.03	38.50	11.20	34.20	54.53	74.00	-19.47	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11b CH06 (2437MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH06(2437MHz)	Power rating	: 120VAc




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2437.000	93.26	27.66	4.18	35.99	89.11	74.00	15.11	Peak

Test Mode :	802.11b CH06 (2437MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH06(2437MHz)	Power rating:	: 120VAc

Data: 594




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4874.000	48.39	31.02	6.97	34.04	52.34	54.00	-1.66	Average
4874.000	51.21	31.02	6.97	34.04	55.16	74.00	-18.84	Peak
7311.000	25.57	35.65	8.95	34.48	35.69	54.00	-18.31	Average
7311.000	39.43	35.65	8.95	34.48	49.55	74.00	-24.45	Peak
9748.000	26.31	38.50	11.20	34.20	41.81	54.00	-12.19	Average
9748.000	40.10	38.50	11.20	34.20	55.60	74.00	-18.40	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11b CH11 (2462MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal


Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b CH11(2462MHz)	Power rating:	: 120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2462.000	101.90	27.72	4.19	36.06	97.75	74.00	23.75	Peak

Test Mode :	802.11b CH11 (2462MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal


Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b CH11(2462MHz)	Power rating:	: 120VAc



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11b CH11 (2462MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH11(2462MHz)	Power rating:	: 120VAC



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2462.000	93.72	27.72	4.19	36.06	89.57	74.00	15.57	Peak

Test Mode :	802.11b CH11 (2462MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH11(2462MHz)	Power rating:	: 120VAc



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11g CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g CH01(2412MHz)	Power rating:	: 120VAc




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2412.000	102.80	27.61	4.17	35.93	98.65	74.00	24.65	Peak

Test Mode :	802.11g CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g CH01(2412MHz)	Power rating:	: 120VAc

Data: 604




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4824.000	39.40	30.95	6.59	34.09	42.85	54.00	-11.15	Average
4824.000	51.82	30.95	6.59	34.09	55.27	74.00	-18.73	Peak
7236.000	25.62	35.47	8.71	34.41	35.39	54.00	-18.61	Average
7236.000	38.85	35.47	8.71	34.41	48.62	74.00	-25.38	Peak
9648.000	26.91	38.42	11.55	34.16	42.72	54.00	-11.28	Average
9648.000	39.62	38.42	11.55	34.16	55.43	74.00	-18.57	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11g CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11g CH01(2412MHz)	Power rating:	120VAc




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2412.000	95.72	27.61	4.17	35.93	91.57	74.00	17.57	Peak

Test Mode :	802.11g CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11g CH01(2412MHz)	Power rating:	: 120VAc

Data: 602




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4824.000	32.41	30.95	6.59	34.09	35.86	54.00	-18.14	Average
4824.000	45.38	30.95	6.59	34.09	48.83	74.00	-25.17	Peak
7236.000	25.61	35.47	8.71	34.41	35.38	54.00	-18.62	Average
7236.000	39.07	35.47	8.71	34.41	48.84	74.00	-25.16	Peak
9648.000	26.90	38.42	11.55	34.16	42.71	54.00	-11.29	Average
9648.000	39.64	38.42	11.55	34.16	55.45	74.00	-18.55	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11g CH06 (2437MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g CH06(2437MHz)	Power rating:	: 120VAc




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2437.000	103.31	27.66	4.18	35.99	99.16	74.00	25.16	Peak

Test Mode :	802.11g CH06 (2437MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site : 3m Chamber	Temp/Humi : 24℃/62%
Tested by : Jack	Pol/Phase : HORIZONTAL
Test Mode : 802.11g CH06(2437MHz)	Power rating: 120VAc

Data: 606




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4874.000	39.26	31.02	6.97	34.04	43.21	54.00	-10.79	Average
4874.000	50.51	31.02	6.97	34.04	54.46	74.00	-19.54	Peak
7311.000	25.48	35.65	8.95	34.48	35.60	54.00	-18.40	Average
7311.000	38.88	35.65	8.95	34.48	49.00	74.00	-25.00	Peak
9748.000	26.13	38.50	11.20	34.20	41.63	54.00	-12.37	Average
9748.000	39.25	38.50	11.20	34.20	54.75	74.00	-19.25	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11g CH06 (2437MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11g CH06(2437MHz)	Power rating	: 120VAc




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2437.000	94.77	27.66	4.18	35.99	90.62	74.00	16.62	Peak

Test Mode :	802.11g CH06 (2437MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11g CH06(2437MHz)	Power rating:	120VAc

Data: 608




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4874.000	34.80	31.02	6.97	34.04	38.75	54.00	-15.25	Average
4874.000	46.55	31.02	6.97	34.04	50.50	74.00	-23.50	Peak
7311.000	25.58	35.65	8.95	34.48	35.70	54.00	-18.30	Average
7311.000	44.05	35.65	8.95	34.48	54.17	74.00	-19.83	Peak
9748.000	26.12	38.50	11.20	34.20	41.62	54.00	-12.38	Average
9748.000	39.31	38.50	11.20	34.20	54.81	74.00	-19.19	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11g CH11 (2462MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g CH11(2462MHz)	Power rating:	120VAc




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2462.000	103.37	27.72	4.19	36.06	99.22	74.00	25.22	Peak

Test Mode :	802.11g CH11 (2462MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g CH11(2462MHz)	Power rating:	: 120VAc

Data: 612




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4924.000	30.34	31.09	7.35	33.98	34.80	54.00	-19.20	Average
4924.000	50.33	31.09	7.35	33.98	54.79	74.00	-19.21	Peak
7386.000	25.07	35.83	9.19	34.55	35.54	54.00	-18.46	Average
7386.000	38.46	35.83	9.19	34.55	48.93	74.00	-25.07	Peak
9848.000	26.03	38.58	11.49	34.24	41.86	54.00	-12.14	Average
9848.000	39.75	38.58	11.49	34.24	55.58	74.00	-18.42	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11g CH11 (2462MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11g CH11(2462MHz)	Power rating:	: 120VAC



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2462.000	96.55	27.72	4.19	36.06	92.40	74.00	18.40	Peak

Test Mode :	802.11g CH11 (2462MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site : 3m Chamber	Temp/Humi : 24℃/62%
Tested by : Jack	Pol/Phase : VERTICAL
Test Mode : 802.11g CH11(2462MHz)	Power rating: 120VAc




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4924.000	35.54	31.09	7.35	33.98	40.00	54.00	-14.00	Average
4924.000	48.14	31.09	7.35	33.98	52.60	74.00	-21.40	Peak
7386.000	25.09	35.83	9.19	34.55	35.56	54.00	-18.44	Average
7386.000	38.31	35.83	9.19	34.55	48.78	74.00	-25.22	Peak
9848.000	26.02	38.58	11.49	34.24	41.85	54.00	-12.15	Average
9848.000	39.06	38.58	11.49	34.24	54.89	74.00	-19.11	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11n HT20 CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT20 CH01(2412MHz)	Power rating:	120VAc




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2412.000	102.21	27.61	4.17	35.93	98.06	74.00	24.06	Peak

Test Mode :	802.11n HT20 CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site : 3m Chamber
 Temp/Humi : 24℃/62%
 Tested by : Jack
 Pol/Phase : HORIZONTAL
 Test Mode : 802.11N HT20 CH01(2412MHz)
 Power rating: 120VAC

Data: 614




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4824.000	38.98	30.95	6.59	34.09	42.43	54.00	-11.57	Average
4824.000	52.48	30.95	6.59	34.09	55.93	74.00	-18.07	Peak
7236.000	25.61	35.47	8.71	34.41	35.38	54.00	-18.62	Average
7236.000	39.43	35.47	8.71	34.41	49.20	74.00	-24.80	Peak
9648.000	26.89	38.42	11.55	34.16	42.70	54.00	-11.30	Average
9648.000	39.82	38.42	11.55	34.16	55.63	74.00	-18.37	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11n HT20 CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11N HT20 CH01(2412MHz)	Power rating:	120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2412.000	94.55	27.61	4.17	35.93	90.40	74.00	16.40	Peak

Test Mode :	802.11n HT20 CH01 (2412 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site : 3m Chamber
 Temp/Humi : 24℃/62%
 Tested by : Jack
 Pol/Phase : VERTICAL
 Test Mode : 802.11N HT20 CH01(2412MHz)
 Power rating: 120VAC




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4824.000	34.36	30.95	6.59	34.09	37.81	54.00	-16.19	Average
4824.000	46.41	30.95	6.59	34.09	49.86	74.00	-24.14	Peak
7236.000	25.64	35.47	8.71	34.41	35.41	54.00	-18.59	Average
7236.000	39.03	35.47	8.71	34.41	48.80	74.00	-25.20	Peak
9648.000	26.87	38.42	11.55	34.16	42.68	54.00	-11.32	Average
9648.000	40.14	38.42	11.55	34.16	55.95	74.00	-18.05	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11n HT20 CH06 (2437MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT20 CH06(2437MHz)	Power rating:	120VAC




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2437.000	102.77	27.66	4.18	35.99	98.62	74.00	24.62	Peak

Test Mode :	802.11n HT20 CH06 (2437MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site : 3m Chamber Temp/Humi : 24℃/62%
Tested by : Jack Pol/Phase : HORIZONTAL
Test Mode : 802.11n HT20 CH06(2437MHz) Power rating: 120VAC

Data: 620




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4874.000	39.01	31.02	6.97	34.04	42.96	54.00	-11.04	Average
4874.000	50.93	31.02	6.97	34.04	54.88	74.00	-19.12	Peak
7311.000	25.47	35.65	8.95	34.48	35.59	54.00	-18.41	Average
7311.000	39.04	35.65	8.95	34.48	49.16	74.00	-24.84	Peak
9748.000	26.05	38.50	11.20	34.20	41.55	54.00	-12.45	Average
9748.000	39.39	38.50	11.20	34.20	54.89	74.00	-19.11	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11n HT20 CH06 (2437MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11N HT20 CH06(2437MHz)	Power rating	: 120VAc




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2437.000	95.16	27.66	4.18	35.99	91.01	74.00	17.01	Peak

Test Mode :	802.11n HT20 CH06 (2437MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site : 3m Chamber
Temp/Humi : 24℃/62%
Tested by : Jack
Pol/Phase : VERTICAL
Test Mode : 802.11n HT20 CH06(2437MHz)
Power rating: 120VAc

Data: 618




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4874.000	34.83	31.02	6.97	34.04	38.78	54.00	-15.22	Average
4874.000	46.51	31.02	6.97	34.04	50.46	74.00	-23.54	Peak
7311.000	25.50	35.65	8.95	34.48	35.62	54.00	-18.38	Average
7311.000	39.03	35.65	8.95	34.48	49.15	74.00	-24.85	Peak
9748.000	26.22	38.50	11.20	34.20	41.72	54.00	-12.28	Average
9748.000	39.73	38.50	11.20	34.20	55.23	74.00	-18.77	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11n HT20 CH11 (2462 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT20 CH11(2462MHz)	Power rating:	120VAC




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2462.000	103.22	27.72	4.19	36.06	99.07	74.00	25.07	Peak

Test Mode :	802.11n HT20 CH11 (2462 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT20 CH11(2462MHz)	Power rating:	120VAC


Data: 622



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4924.000	38.50	31.09	7.35	33.98	42.96	54.00	-11.04	Average
4924.000	50.38	31.09	7.35	33.98	54.84	74.00	-19.16	Peak
7386.000	25.05	35.83	9.19	34.55	35.52	54.00	-18.48	Average
7386.000	47.91	35.83	9.19	34.55	58.38	74.00	-15.62	Peak
9848.000	26.20	38.58	11.49	34.24	42.03	54.00	-11.97	Average
9848.000	39.97	38.58	11.49	34.24	55.80	74.00	-18.20	Peak

Test Mode :	802.11n HT20 CH11 (2462 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11N HT20 CH11(2462MHz)	Power rating:	120VAC



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2462.000	96.24	27.72	4.19	36.06	92.09	74.00	18.09	Peak

Test Mode :	802.11n HT20 CH11 (2462 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical


Test Site : 3m Chamber
 Temp/Humi : 24℃/62%
 Tested by : Jack
 Pol/Phase : VERTICAL
 Test Mode : 802.11N HT20 CH11(2462MHz)
 Power rating: 120VAc



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11n HT40 CH03 (2422 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT40 CH03(2422MHz)	Power rating:	120VAc




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2422.000	100.90	27.63	4.18	35.96	96.75	74.00	22.75	Peak

Test Mode :	802.11n HT40 CH03 (2422 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site : 3m Chamber
 Temp/Humi : 24℃/62%
 Tested by : Jack
 Pol/Phase : HORIZONTAL
 Test Mode : 802.11N HT40 CH03(2422MHz)
 Power rating: 120VAC

Data: 628




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4844.000	37.58	30.98	6.74	34.07	41.23	54.00	-12.77	Average
4844.000	47.88	30.98	6.74	34.07	51.53	74.00	-22.47	Peak
7266.000	25.57	35.54	8.80	34.44	35.47	54.00	-18.53	Average
7266.000	40.19	35.54	8.80	34.44	50.09	74.00	-23.91	Peak
9688.000	26.56	38.45	11.41	34.18	42.24	54.00	-11.76	Average
9688.000	40.27	38.45	11.41	34.18	55.95	74.00	-18.05	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11n HT40 CH03 (2422 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11N HT40 CH03(2422MHz)	Power rating:	120VAc




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2422.000	93.92	27.63	4.18	35.96	89.77	74.00	15.77	Peak

Test Mode :	802.11n HT40 CH03 (2422 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site : 3m Chamber Temp/Humi : 24℃/62%
Tested by : Jack Pol/Phase : VERTICAL
Test Mode : 802.11N HT40 CH03(2422MHz) Power rating: 120VAC

Data: 626




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4844.000	33.66	30.98	6.74	34.07	37.31	54.00	-16.69	Average
4844.000	45.53	30.98	6.74	34.07	49.18	74.00	-24.82	Peak
7266.000	25.79	35.54	8.80	34.44	35.69	54.00	-18.31	Average
7266.000	38.90	35.54	8.80	34.44	48.80	74.00	-25.20	Peak
9688.000	26.68	38.45	11.41	34.18	42.36	54.00	-11.64	Average
9688.000	40.46	38.45	11.41	34.18	56.14	74.00	-17.86	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11n HT40 CH06 (2437MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal


Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT40 CH06(2437MHz)	Power rating:	120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2437.000	99.99	27.66	4.18	35.99	95.84	74.00	21.84	Peak

Test Mode :	802.11n HT40 CH06 (2437MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site : 3m Chamber
 Temp/Humi : 24℃/62%
 Tested by : Jack
 Pol/Phase : HORIZONTAL
 Test Mode : 802.11N HT40 CH06(2437MHz)
 Power rating: 120VAC




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4874.000	37.22	31.02	6.97	34.04	41.17	54.00	-12.83	Average
4874.000	48.55	31.02	6.97	34.04	52.50	74.00	-21.50	Peak
7311.000	25.51	35.65	8.95	34.48	35.63	54.00	-18.37	Average
7311.000	38.49	35.65	8.95	34.48	48.61	74.00	-25.39	Peak
9748.000	26.20	38.50	11.20	34.20	41.70	54.00	-12.30	Average
9748.000	39.22	38.50	11.20	34.20	54.72	74.00	-19.28	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11n HT40 CH06 (2437MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11N HT40 CH06(2437MHz)	Power rating:	120VAC




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2437.000	92.69	27.66	4.18	35.99	88.54	74.00	14.54	Peak

Test Mode :	802.11n HT40 CH06 (2437MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site : 3m Chamber
 Temp/Humi : 24℃/62%
 Tested by : Jack
 Pol/Phase : VERTICAL
 Test Mode : 802.11N HT40 CH06(2437MHz)
 Power rating: 120VAc

Data: 632




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4874.000	33.46	31.02	6.97	34.04	37.41	54.00	-16.59	Average
4874.000	44.86	31.02	6.97	34.04	48.81	74.00	-25.19	Peak
7311.000	25.46	35.65	8.95	34.48	35.58	54.00	-18.42	Average
7311.000	45.08	35.65	8.95	34.48	55.20	74.00	-18.80	Peak
9748.000	26.19	38.50	11.20	34.20	41.69	54.00	-12.31	Average
9748.000	39.15	38.50	11.20	34.20	54.65	74.00	-19.35	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11n HT40 CH09(2452 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT40 CH09(2452MHz)	Power rating:	120VAC




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2452.000	101.04	27.69	4.18	36.03	96.88	74.00	22.88	Peak

Test Mode :	802.11n HT40 CH09(2452 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site : 3m Chamber	Temp/Humi : 24℃/62%
Tested by : Jack	Pol/Phase : HORIZONTAL
Test Mode : 802.11n HT40 CH09(2452MHz)	Power rating: 120VAC

Data: 634




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4904.000	36.35	31.07	7.20	34.01	40.61	54.00	-13.39	Average
4904.000	47.08	31.07	7.20	34.01	51.34	74.00	-22.66	Peak
7356.000	25.14	35.75	9.09	34.52	35.46	54.00	-18.54	Average
7356.000	38.35	35.75	9.09	34.52	48.67	74.00	-25.33	Peak
9808.000	26.04	38.55	11.10	34.22	41.47	54.00	-12.53	Average
9808.000	39.30	38.55	11.10	34.22	54.73	74.00	-19.27	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11n HT40 CH09(2452 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 24℃/62%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11N HT40 CH09(2452MHz)	Power rating:	120VAC



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2452.000	94.34	27.69	4.18	36.03	90.18	74.00	16.18	Peak

Test Mode :	802.11n HT40 CH09(2452 MHz)	Temperature :	22~24℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site : 3m Chamber
 Temp/Humi : 24℃/62%
 Tested by : Jack
 Pol/Phase : VERTICAL
 Test Mode : 802.11N HT40 CH09(2452MHz)
 Power rating: 120VAc




Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

4.5.2 Test Result of Radiated Spurious Emission (30MHz ~ 1GHz)


Test Mode :	802.11b CH01 (2412 MHz)	Temperature :	21~25℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	30MHz~1GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b CH01(2412MHz)	Power rating:	120VAc



Test Mode :	802.11b CH01 (2412 MHz)	Temperature :	21~25℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	30MHz~1GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 25℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH01(2412MHz)	Power rating:	120VAc



4.6 AC Conducted Emission Measurement

4.6.1 Limit of AC Conducted Emission

FCC §15.207

IC RSS-GEN 8.8

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50


*Decreases with the logarithm of the frequency.

4.6.2 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

4.6.3 Test Result of AC Conducted Emission


Test Mode :	Mode 1	Temperature :	20°C
Test Engineer :	Jack Liu	Relative Humidity :	64%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WLAN Linking + Lighting		



Freq MHz	Reading level dBuV	LISN/ISN factor dB	Cable loss dB	Result level dBuV	Limit level dBuV	Over limit dB	Remark
0.486	44.60	9.58	0.01	54.19	56.23	-2.04	QP
0.486	29.40	9.58	0.01	38.99	46.23	-7.24	Average
0.513	42.70	9.58	0.01	52.29	56.00	-3.71	QP
0.513	23.80	9.58	0.01	33.39	46.00	-12.61	Average
0.555	39.90	9.58	0.01	49.49	56.00	-6.51	QP
0.555	24.30	9.58	0.01	33.89	46.00	-12.11	Average
0.658	43.40	9.58	0.02	53.00	56.00	-3.00	QP
0.658	24.60	9.58	0.02	34.20	46.00	-11.80	Average
3.025	41.20	9.61	0.04	50.85	56.00	-5.15	QP
3.025	29.10	9.61	0.04	38.75	46.00	-7.25	Average
10.072	45.60	9.81	0.09	55.50	60.00	-4.50	QP
10.072	35.40	9.81	0.09	45.30	50.00	-4.70	Average

Result Level= Reading Level + LISN Factor + Cable Loss

Test Mode :	Mode 1	Temperature :	20°C
Test Engineer :	Jack Liu	Relative Humidity :	64%
Test Voltage :	120Vac / 60Hz	Phase :	NEUTRAL
Function Type :	WLAN Linking + Lighting		



Freq MHz	Reading level dBuV	LISN/ISN factor dB	Cable loss dB	Result level dBuV	Limit level dBuV	Over limit dB	Remark
0.456	45.20	9.57	0.01	54.78	56.76	-1.98	QP
0.456	32.30	9.57	0.01	41.88	46.76	-4.88	Average
0.880	45.20	9.58	0.02	54.80	56.00	-1.20	QP
0.880	29.90	9.58	0.02	39.50	46.00	-6.50	Average
1.032	43.50	9.59	0.02	53.11	56.00	-2.89	QP
1.032	28.30	9.59	0.02	37.91	46.00	-8.09	Average
3.207	45.10	9.62	0.04	54.76	56.00	-1.24	QP
3.207	33.80	9.62	0.04	43.46	46.00	-2.54	Average
12.852	46.51	9.92	0.09	56.52	60.00	-3.48	QP
12.852	38.71	9.92	0.09	48.72	50.00	-1.28	Average
13.479	45.71	9.94	0.09	55.74	60.00	-4.26	QP
13.479	37.81	9.94	0.09	47.84	50.00	-2.16	Average

Result Level= Reading Level + LISN Factor + Cable Loss

4.7 Antenna Requirements

4.7.1 Standard Applicable

According to antenna requirement of §15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded..

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 Antenna Connected Construction

An PCB antenna design is used.

4.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date	Remark
Spectrum Analyzer	Keysight	N9010A	MY56070788	2021-01-05	2022-01-04	Conducted
Power Sensor	Keysight	U2021XA	MY56510025	2021-01-05	2022-01-04	Conducted
Power Sensor	Keysight	U2021XA	MY57030005	2021-01-05	2022-01-04	Conducted
Power Sensor	Keysight	U2021XA	MY56510018	2021-01-05	2022-01-04	Conducted
Power Sensor	Keysight	U2021XA	MY56480002	2021-01-05	2022-01-04	Conducted
Thermal Chamber	Howkin	UHL-34	19111801	2021-04-21	2022-04-20	Conducted
Base Station	R&S	CMW 270	101231	2021-01-05	2022-01-04	Conducted
Signal Generator (Interferer)	Keysight	N5182B	MY56200384	2021-01-05	2022-01-04	Conducted
Signal Generator (Blocker)	Keysight	N5171B	MY56200661	2021-01-05	2022-01-04	Conducted

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV 40	101433	2021-01-05	2022-01-04	Radiation
Amplifier	Sonoma	310	363917	2021-01-06	2022-01-05	Radiation
Amplifier	Schwarzbeck	BBV 9718	327	2021-01-06	2022-01-05	Radiation
Amplifier	Narda	TTA1840-35-HG	2034380	2020-11-28	2021-11-27	Radiation
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-051	2020-02-14	2023-02-13	Radiation
Broadband Antenna	Schwarzbeck	VULB 9168	9168-757	2020-09-27	2023-09-26	Radiation
Horn Antenna	Schwarzbeck	BBHA 9120 D	1677	2020-02-14	2023-02-13	Radiation
Horn Antenna	COM-POWER	AH-1840	101117	2018-06-20	2021-06-19	Radiation
Test Software	Audix	E3	6.111221a	N/A	N/A	Radiation
Filter	Micro-Tronics	BRM 50702	G266	N/A	N/A	Radiation

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date	Remark
LISN	R&S	ENV216	102125	2021-01-05	2022-01-04	Conducted
LISN	R&S	ENV432	101327	2021-01-06	2022-01-05	Conducted
EMI Test Receiver	R&S	ESR3	102143	2021-01-06	2022-01-05	Conducted
EMI Test Software	Audix	E3	N/A	N/A	N/A	Conducted

N/A: No Calibration Required

6 Uncertainty of Evaluation

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.42dB
Radiated emission	30MHz ~ 1GMHz	2.50dB
	1GHz ~ 18GHz	3.51dB
	18GHz ~ 40GHz	3.96dB

MEASUREMENT	UNCERTAINTY
Occupied Channel Bandwidth	±196.4Hz
RF output power, conducted	±2.31dB
Power density, conducted	±2.31dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Appendix A: DTS Bandwidth

Test Result


TestMode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	8.640	2407.880	2416.520	≥ 0.5	PASS
		2437	9.640	2432.400	2442.040	≥ 0.5	PASS
		2462	9.160	2457.400	2466.560	≥ 0.5	PASS
11G	Ant1	2412	16.440	2403.760	2420.200	≥ 0.5	PASS
		2437	16.440	2428.760	2445.200	≥ 0.5	PASS
		2462	16.440	2453.760	2470.200	≥ 0.5	PASS
11N20SISO	Ant1	2412	17.120	2403.400	2420.520	≥ 0.5	PASS
		2437	17.040	2428.480	2445.520	≥ 0.5	PASS
		2462	17.120	2453.440	2470.560	≥ 0.5	PASS
11N40SISO	Ant1	2422	32.880	2405.440	2438.320	≥ 0.5	PASS
		2437	33.440	2420.280	2453.720	≥ 0.5	PASS
		2452	32.480	2435.840	2468.320	≥ 0.5	PASS

Test Graphs






11B_Ant1_2462



11G_Ant1_2412




11G_Ant1_2437




11G_Ant1_2462




11N20SISO_Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462



11N40SISO_Ant1_2422



11N40SISO_Ant1_2437




11N40SISO_Ant1_2452


Appendix B: Occupied Channel Bandwidth

Test Result


TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	13.134	2405.436	2418.570	---	PASS
		2437	13.148	2430.413	2443.561	---	PASS
		2462	13.130	2455.433	2468.563	---	PASS
11G	Ant1	2412	16.587	2403.726	2420.313	---	PASS
		2437	16.545	2428.723	2445.268	---	PASS
		2462	16.594	2453.720	2470.314	---	PASS
11N20SISO	Ant1	2412	17.337	2403.331	2420.668	---	PASS
		2437	17.354	2428.309	2445.663	---	PASS
		2462	17.336	2453.327	2470.663	---	PASS
11N40SISO	Ant1	2422	34.517	2404.821	2439.338	---	PASS
		2437	34.539	2419.804	2454.343	---	PASS
		2452	34.548	2434.828	2469.376	---	PASS

Test Graphs







11B_Ant1_2462




11G_Ant1_2412




11G_Ant1_2437



11G_Ant1_2462



11N20SISO_Ant1_2412



11N20SISO_Ant1_2437