



中认信通

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: Shenzhen Xin Yuan Electronic Technology Co., Ltd.

Address: Room 801-803, Yousuowei Building, No.2000, JiaXian Road, Bantian Street,
Longgang District, Shenzhen, Guangdong, China

FCC ID: 2ASYE-T4-S3-241

Product Name: T4-S3-2.41

Standard(s): 47 CFR Part 15, Subpart C(15.247)
ANSI C63.10-2013
KDB 558074 D01 15.247 Meas Guidance v05r02

The above device has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR231167841-00B

Date Of Issue: 2024/1/3

Reviewed By: Calvin Chen

Title: RF Engineer

Approved By: Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,
Guangdong, China
Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

DOCUMENT REVISION HISTORY	5
1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	6
1.2 DESCRIPTION OF TEST CONFIGURATION.....	7
1.2.1 EUT Operation Condition:.....	7
1.2.2 Support Equipment List and Details	7
1.2.3 Support Cable List and Details	7
1.2.4 Block Diagram of Test Setup.....	8
1.3 MEASUREMENT UNCERTAINTY	9
2. SUMMARY OF TEST RESULTS	10
3. REQUIREMENTS AND TEST PROCEDURES	11
3.1 AC LINE CONDUCTED EMISSIONS.....	11
3.1.1 Applicable Standard.....	11
3.1.2 EUT Setup.....	12
3.1.3 EMI Test Receiver Setup	12
3.1.4 Test Procedure	13
3.1.5 Corrected Amplitude & Margin Calculation.....	13
3.2 RADIATION SPURIOUS EMISSIONS.....	14
3.2.1 Applicable Standard.....	14
3.2.2 EUT Setup.....	14
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup	15
3.2.4 Test Procedure	16
3.2.5 Corrected Amplitude & Margin Calculation.....	16
3.3 MINIMUM 6 dB EMISSION BANDWIDTH	17
3.3.1 Applicable Standard.....	17
3.3.2 EUT Setup.....	17
3.3.3 Test Procedure	17
3.4 99% OCCUPIED BANDWIDTH.....	18
3.4.1 EUT Setup.....	18
3.4.2 Test Procedure	18
3.5 MAXIMUM CONDUCTED OUTPUT POWER.....	19
3.5.1 Applicable Standard.....	19
3.5.2 EUT Setup.....	19
3.5.3 Test Procedure	19
3.6 MAXIMUM POWER SPECTRAL DENSITY	20
3.6.1 Applicable Standard.....	20
3.6.2 EUT Setup.....	20
3.6.3 Test Procedure	20
3.7 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE.....	21
3.7.1 Applicable Standard.....	21
3.7.2 EUT Setup.....	21
3.7.3 Test Procedure	21

3.8 DUTY CYCLE	22
3.8.1 EUT Setup.....	22
3.8.2 Test Procedure	22
3.9 ANTENNA REQUIREMENT.....	22
3.9.1 Applicable Standard.....	22
3.9.2 Judgment.....	22
4. Test DATA AND RESULTS.....	23
4.1 AC LINE CONDUCTED EMISSIONS.....	23
4.2 RADIATION SPURIOUS EMISSIONS	26
4.3 MINIMUM 6 dB EMISSION BANDWIDTH	44
4.4 99% OCCUPIED BANDWIDTH.....	49
4.5 MAXIMUM CONDUCTED OUTPUT POWER.....	54
4.6 MAXIMUM POWER SPECTRAL DENSITY	55
4.7 100 KHz BANDWIDTH OF FREQUENCY BAND EDGE:	60
4.8 DUTY CYCLE:.....	65
5. RF EXPOSURE EVALUATION	68
5.1 MPE-BASED EXEMPTION.....	68
5.1.1 Applicable Standard.....	68
5.1.2 Measurement Result.....	68
6. EUT PHOTOGRAPHS	69
7. TEST SETUP PHOTOGRAPHS	70

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR231167841-00B	Original Report	2024/1/3

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	T4-S3-2.41
EUT Model:	T4-S3-2.41
Trade Name:	LILYGO
Operation Frequency:	2412-2462 MHz(802.11b/g/n ht20) 2422-2452 MHz(802.11n ht40)
Maximum Peak Output Power (Conducted):	14.84 dBm
Modulation Type:	802.11b:DSSS-DBPSK, DQPSK, CCK 802.11g/n:OFDM-BPSK, QPSK, 16QAM, 64QAM
Rated Input Voltage:	DC 5V from USB Port
Serial Number:	CE&RE: 2DSO-2 RF: 2DSO-1
EUT Received Date:	2023/11/16
EUT Received Status:	Good

Operation Frequency Detail:

For 802.11b/g/n ht20:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

Per section 15.31(m), the below frequencies were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	2412
Middle	2437
Highest	2462

For 802.11n ht40:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	7	2442
4	2427	8	2447
5	2432	9	2452
6	2437	/	/

Per section 15.31(m), the below frequencies were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	2422
Middle	2437
Highest	2452

Antenna Information Detail▲:

Antenna Type	input impedance (Ohm)	Frequency Range (MHz)	Antenna Gain (dBi)
Stamped Metal Antenna	50	2400~2500	4.9
The Method of §15.203 Compliance: ☒ Antenna was permanently attached to the unit. ☐ Antenna use a unique type of connector to attach to the EUT. ☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.			

Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
/	/	/	/

1.2 Description of Test Configuration**1.2.1 EUT Operation Condition:**

For 802.11b/g/n:

EUT Operation Mode:		The system was configured for testing in Engineering Mode, which was provided by the manufacturer.		
Equipment Modifications:		No		
EUT Exercise Software:		EspRFTTestTool_v3.6_Manual.exe		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:				
Test Modes	Data Rate	Power Level Setting		
		Lowest Channel	Middle Channel	Highest Channel
802.11b	1Mbps	68	68	68
802.11g	6Mbps	58	58	58
802.11n ht20	MCS0	45	45	45
802.11n ht40	MCS0	35	35	35
The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.				

1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	PC	E6410	GYXJ3 A00 JSD2
DELL	Adapter	HA65NM130	CN-OFPC2Y-CH200-14M-061U-A07

1.2.3 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
AC cable	No	No	1.2	LISN	Adapter
DC cable	No	Yes	1.5	PC	Adapter
USB cable	No	Yes	1.0	PC	EUT
USB cable	No	No	0.1	PC	EUT

1.2.4 Block Diagram of Test Setup

AC line conducted emissions:



Spurious Emissions:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	$\pm 5\%$
RF output power, conducted	$\pm 0.61\text{ dB}$
Power Spectral Density, conducted	$\pm 0.61\text{ dB}$
Unwanted Emissions, radiated	9kHz-30MHz: 4.12dB, 30M~200MHz: 4.15 dB, 200M~1GHz: 5.61 dB, 1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	$\pm 1.26\text{ dB}$
Temperature	$\pm 1^\circ\text{C}$
Humidity	$\pm 5\%$
DC and low frequency voltages	$\pm 0.4\%$
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	Minimum 6 dB Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.203	Antenna Requirement	Compliant
§15.247 (i) & §1.1307	RF Exposure Evaluation	Compliant

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

3.1.2 EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiation Spurious Emissions


3.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


3.2.2 EUT Setup

9 kHz-30MHz:



30MHz-1GHz:



Above 1GHz:

The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9 kHz-1000MHz:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	/	/	200 Hz	QP
	300 Hz	1 kHz	/	PK
150 kHz – 30 MHz	/	/	9 kHz	QP
	10 kHz	30 kHz	/	PK
30 MHz – 1000 MHz	/	/	120 kHz	QP
	100 kHz	300 kHz	/	PK

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	$\geq 1/T$

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss - Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


3.3 Minimum 6 dB Emission Bandwidth

3.3.1 Applicable Standard

FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

3.3.2 EUT Setup




3.3.3 Test Procedure

According to ANSI C63.10-2013 Section 11.8

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.4 99% Occupied Bandwidth

3.4.1 EUT Setup



3.4.2 Test Procedure

According to ANSI C63.10-2013 Section 6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.
- Step a) through step c) might require iteration to adjust within the specified range.
- Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).


3.5 Maximum Conducted Output Power

3.5.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

3.5.2 EUT Setup



3.5.3 Test Procedure

For Peak Power

According to ANSI C63.10-2013 Section 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

For Average Power

According to ANSI C63.10-2013 Section 11.9.2.3.2

Method AVGPM-G is a measurement using a gated RF average power meter.

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.


3.6 Maximum Power Spectral Density

3.6.1 Applicable Standard

FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.6.2 EUT Setup



3.6.3 Test Procedure

According to ANSI C63.10-2013 Section 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance:

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.


3.7 100 kHz Bandwidth of Frequency Band Edge

3.7.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.7.2 EUT Setup



3.7.3 Test Procedure


According to ANSI C63.10-2013 Section 11.11

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

3.8 Duty Cycle

3.8.1 EUT Setup



3.8.2 Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

3.9 Antenna Requirement

3.9.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.9.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.

4. Test DATA AND RESULTS

4.1 AC Line Conducted Emissions

Serial Number:	2DSO-2	Test Date:	2023/12/29
Test Site:	CE	Test Mode:	Transmitting(Maximum Conducted Output Power Mode, 802.11n ht40 High Channel)
Tester:	David Huang	Test Result:	Pass

Environmental Conditions:


Temperature: (°C)	23.8	Relative Humidity: (%)	45	ATM Pressure: (kPa)	101.5
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101134	2023/3/31	2024/3/30
R&S	EMI Test Receiver	ESR3	102726	2023/3/31	2024/3/30
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2023/8/6	2024/8/5
Audix	Test Software	E3	190306 (V9)	N/A	N/A


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Project No.: CR231167841-RF
 Tester: David Huang
 Port: Line
 Note: Transmitting(2.4G WIFI)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.154	46.76	9.61	56.37	65.77	9.40	QP
2	0.154	22.81	9.61	32.42	55.77	23.35	Average
3	0.199	37.65	9.61	47.26	63.63	16.37	QP
4	0.199	11.12	9.61	20.73	53.63	32.90	Average
5	0.432	24.09	9.61	33.70	57.22	23.52	QP
6	0.432	11.57	9.61	21.18	47.22	26.04	Average
7	1.178	25.11	9.62	34.73	56.00	21.27	QP
8	1.178	17.66	9.62	27.28	46.00	18.72	Average
9	3.049	20.68	9.65	30.33	56.00	25.67	QP
10	3.049	11.66	9.65	21.31	46.00	24.69	Average
11	4.593	20.49	9.66	30.15	56.00	25.85	QP
12	4.593	12.36	9.66	22.02	46.00	23.98	Average

Project No.: CR231167841-RF
 Tester: David Huang
 Port: neutral
 Note: Transmitting(2.4G WIFI)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.153	47.53	9.61	57.14	65.85	8.71	QP
2	0.153	27.93	9.61	37.54	55.85	18.31	Average
3	0.249	32.18	9.61	41.79	61.79	20.00	QP
4	0.249	10.22	9.61	19.83	51.79	31.96	Average
5	0.427	26.14	9.61	35.75	57.32	21.57	QP
6	0.427	9.52	9.61	19.13	47.32	28.19	Average
7	1.204	24.83	9.62	34.45	56.00	21.55	QP
8	1.204	18.48	9.62	28.10	46.00	17.90	Average
9	2.892	22.28	9.65	31.93	56.00	24.07	QP
10	2.892	12.42	9.65	22.07	46.00	23.93	Average
11	4.562	20.49	9.66	30.15	56.00	25.85	QP
12	4.562	11.21	9.66	20.87	46.00	25.13	Average

4.2 Radiation Spurious Emissions

Serial Number:	2DSO-2	Test Date:	Below 1GHz: 2023/12/27 Above 1GHz: 2023/12/19
Test Site:	966-1, 966-2	Test Mode:	Transmitting
Tester:	Jeff Luo, Tao Zhu	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	24.2~26	Relative Humidity: (%)	44~54	ATM Pressure: (kPa)	101.7~101.9

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Below 1GHz					
Sunol Sciences	Antenna	JB6	A082520-6	2023/9/18	2026/9/17
BACL	Loop Antenna	1313-1P	3092721	2023/10/20	2026/10/19
R&S	EMI Test Receiver	ESR3	102724	2023/3/31	2024/3/30
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2023/7/16	2024/7/15
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2023/7/16	2024/7/15
Sonoma	Amplifier	310N	186165	2023/7/16	2024/7/15
Audix	Test Software	E3	201021 (V9)	N/A	N/A
Above 1GHz					
AH	Double Ridge Guide Horn Antenna	SAS-571	1394	2023/2/22	2026/2/21
R&S	Spectrum Analyzer	FSV40	101591	2023/3/31	2024/3/30
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2023/8/6	2024/8/5
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2023/8/6	2024/8/5
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2023/11/8	2024/11/7
Audix	Test Software	E3	201021 (V9)	N/A	N/A
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021/2/5	2024/2/4
Quinstar	Preamplifier	QLW-18405536-JO	15964001005	2023/9/15	2024/9/14
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2023/8/6	2024/8/5
E-Microwave	Band Rejection Filter	2400-2483.5MHz	OE01902424	2023/8/6	2024/8/5
Mini Circuits	High Pass Filter	VHF-6010+	31119	2023/8/6	2024/8/5

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below table and plots.


After pre-scan in the X, Y and Z axes of orientation, the worst case is below:

For 9kHz-30MHz, The amplitude of spurious emissions attenuated more than 20 dB below the limit was not be recorded.

1) 30MHz-1GHz Transmitting (Maximum Conducted Output Power Mode, 802.11n ht40)


Low channel

Project No.: CR231167841-RF
Tester: Jeff Luo
Polarization: horizontal
Note: Transmitting(2.4G WIFI 802.11n ht40 Mode)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.317	28.04	-4.36	23.68	40.00	16.32	Peak
2	75.446	44.32	-17.39	26.93	40.00	13.07	Peak
3	183.201	43.35	-13.84	29.51	43.50	13.99	Peak
4	232.532	42.52	-13.37	29.15	46.00	16.85	Peak
5	333.687	47.08	-10.56	36.52	46.00	9.48	Peak
6	719.200	38.06	-3.65	34.41	46.00	11.59	Peak


Project No.: CR231167841-RF
Tester: Jeff Luo
Polarization: vertical
Note: Transmitting(2.4G WIFI 802.11n ht40 Mode)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.211	27.81	-4.28	23.53	40.00	16.47	Peak
2	75.182	40.96	-17.37	23.59	40.00	16.41	Peak
3	194.453	36.89	-13.28	23.61	43.50	19.89	Peak
4	332.519	42.98	-10.55	32.43	46.00	13.57	Peak
5	530.101	37.51	-6.21	31.30	46.00	14.70	Peak
6	801.786	31.52	-2.39	29.13	46.00	16.87	Peak


Middle channel

Project No.: CR231167841-RF
Tester: Jeff Luo
Polarization: horizontal
Note: Transmitting(2.4G WIFI 802.11n ht40 Mode)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.745	28.57	-4.69	23.88	40.00	16.12	Peak
2	75.446	45.51	-17.39	28.12	40.00	11.88	Peak
3	184.490	42.14	-13.82	28.32	43.50	15.18	Peak
4	230.099	40.95	-13.31	27.64	46.00	18.36	Peak
5	332.519	45.98	-10.55	35.43	46.00	10.57	Peak
6	455.906	35.66	-7.11	28.55	46.00	17.45	Peak


Project No.: CR231167841-RF
Tester: Jeff Luo
Polarization: vertical
Note: Transmitting(2.4G WIFI 802.11n ht40 Mode)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.000	27.70	-4.12	23.58	40.00	16.42	Peak
2	74.919	44.58	-17.34	27.24	40.00	12.76	Peak
3	173.814	37.51	-13.43	24.08	43.50	19.42	Peak
4	306.754	39.53	-10.95	28.58	46.00	17.42	Peak
5	334.859	41.45	-10.56	30.89	46.00	15.11	Peak
6	506.479	41.17	-6.33	34.84	46.00	11.16	Peak


High channel

Project No.: CR231167841-RF
Tester: Jeff Luo
Polarization: horizontal
Note: Transmitting(2.4G WIFI 802.11n ht40 Mode)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	31.620	28.70	-5.35	23.35	40.00	16.65	Peak
2	74.657	46.05	-17.34	28.71	40.00	11.29	Peak
3	185.138	44.36	-13.83	30.53	43.50	12.97	Peak
4	249.425	41.26	-13.60	27.66	46.00	18.34	Peak
5	332.519	49.20	-10.55	38.65	46.00	7.35	Peak
6	447.982	36.59	-7.33	29.26	46.00	16.74	Peak

Project No.: CR231167841-RF
Tester: Jeff Luo
Polarization: vertical
Note: Transmitting(2.4G WIFI 802.11n ht40 Mode)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.853	28.18	-4.78	23.40	40.00	16.60	Peak
2	74.919	40.77	-17.34	23.43	40.00	16.57	Peak
3	196.510	37.27	-13.00	24.27	43.50	19.23	Peak
4	332.519	46.63	-10.55	36.08	46.00	9.92	Peak
5	420.580	36.20	-8.32	27.88	46.00	18.12	Peak
6	531.964	38.77	-6.23	32.54	46.00	13.46	Peak

2) 1-25GHz:**802.11b Mode**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2412 MHz							
2390.000	29.19	PK	H	31.71	60.90	74.00	13.10
2390.000	16.43	AV	H	31.71	48.14	54.00	5.86
2390.000	27.77	PK	V	31.71	59.48	74.00	14.52
2390.000	15.37	AV	V	31.71	47.08	54.00	6.92
4824.000	45.68	PK	H	11.26	56.94	74.00	17.06
4824.000	38.88	AV	H	11.26	50.14	54.00	3.86
4824.000	44.77	PK	V	11.26	56.03	74.00	17.97
4824.000	38.05	AV	V	11.26	49.31	54.00	4.69
Middle Channel: 2437 MHz							
4874.000	45.48	PK	H	11.45	56.93	74.00	17.07
4874.000	37.59	AV	H	11.45	49.04	54.00	4.96
4874.000	43.81	PK	V	11.45	55.26	74.00	18.74
4874.000	37.19	AV	V	11.45	48.64	54.00	5.36
High Channel: 2462 MHz							
2483.500	29.87	PK	H	32.19	62.06	74.00	11.94
2483.500	16.72	AV	H	32.19	48.91	54.00	5.09
2483.500	29.04	PK	V	32.19	61.23	74.00	12.77
2483.500	15.96	AV	V	32.19	48.15	54.00	5.85
4924.000	45.40	PK	H	11.67	57.07	74.00	16.93
4924.000	38.49	AV	H	11.67	50.16	54.00	3.84
4924.000	44.45	PK	V	11.67	56.12	74.00	17.88
4924.000	38.24	AV	V	11.67	49.91	54.00	4.09

802.11g Mode

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2412 MHz							
2390.000	29.02	PK	H	31.71	60.73	74.00	13.27
2390.000	16.51	AV	H	31.71	48.22	54.00	5.78
2390.000	27.95	PK	V	31.71	59.66	74.00	14.34
2390.000	15.83	AV	V	31.71	47.54	54.00	6.46
4824.000	54.44	PK	H	11.26	65.70	74.00	8.30
4824.000	38.56	AV	H	11.26	49.82	54.00	4.18
4824.000	53.65	PK	V	11.26	64.91	74.00	9.09
4824.000	38.08	AV	V	11.26	49.34	54.00	4.66
Middle Channel: 2437 MHz							
4874.000	53.85	PK	H	11.45	65.30	74.00	8.70
4874.000	38.66	AV	H	11.45	50.11	54.00	3.89
4874.000	52.46	PK	V	11.45	63.91	74.00	10.09
4874.000	37.47	AV	V	11.45	48.92	54.00	5.08
High Channel: 2462 MHz							
2483.500	28.48	PK	H	32.19	60.67	74.00	13.33
2483.500	16.08	AV	H	32.19	48.27	54.00	5.73
2483.500	27.37	PK	V	32.19	59.56	74.00	14.44
2483.500	15.60	AV	V	32.19	47.79	54.00	6.21
4924.000	53.65	PK	H	11.67	65.32	74.00	8.68
4924.000	38.42	AV	H	11.67	50.09	54.00	3.91
4924.000	52.56	PK	V	11.67	64.23	74.00	9.77
4924.000	37.43	AV	V	11.67	49.10	54.00	4.90

802.11n ht20 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2412 MHz							
2390.000	28.92	PK	H	31.71	60.63	74.00	13.37
2390.000	16.54	AV	H	31.71	48.25	54.00	5.75
2390.000	27.50	PK	V	31.71	59.21	74.00	14.79
2390.000	16.21	AV	V	31.71	47.92	54.00	6.08
4824.000	53.49	PK	H	11.26	64.75	74.00	9.25
4824.000	38.56	AV	H	11.26	49.82	54.00	4.18
4824.000	52.90	PK	V	11.26	64.16	74.00	9.84
4824.000	38.66	AV	V	11.26	49.92	54.00	4.08
Middle Channel: 2437 MHz							
4874.000	53.11	PK	H	11.45	64.56	74.00	9.44
4874.000	36.87	AV	H	11.45	48.32	54.00	5.68
4874.000	51.23	PK	V	11.45	62.68	74.00	11.32
4874.000	36.56	AV	V	11.45	48.01	54.00	5.99
High Channel: 2462 MHz							
2483.500	28.67	PK	H	32.19	60.86	74.00	13.14
2483.500	16.16	AV	H	32.19	48.35	54.00	5.65
2483.500	27.16	PK	V	32.19	59.35	74.00	14.65
2483.500	15.32	AV	V	32.19	47.51	54.00	6.49
4924.000	50.36	PK	H	11.67	62.03	74.00	11.97
4924.000	35.70	AV	H	11.67	47.37	54.00	6.63
4924.000	49.45	PK	V	11.67	61.12	74.00	12.88
4924.000	35.26	AV	V	11.67	46.93	54.00	7.07


802.11n ht40 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2422 MHz							
2390.000	29.30	PK	H	31.71	61.01	74.00	12.99
2390.000	16.55	AV	H	31.71	48.26	54.00	5.74
2390.000	28.13	PK	V	31.71	59.84	74.00	14.16
2390.000	15.99	AV	V	31.71	47.70	54.00	6.30
4844.000	53.02	PK	H	11.31	64.33	74.00	9.67
4844.000	38.51	AV	H	11.31	49.82	54.00	4.18
4844.000	52.20	PK	V	11.31	63.51	74.00	10.49
4844.000	38.08	AV	V	11.31	49.39	54.00	4.61
Middle Channel: 2437 MHz							
4874.000	52.11	PK	H	11.45	63.56	74.00	10.44
4874.000	37.57	AV	H	11.45	49.02	54.00	4.98
4874.000	50.68	PK	V	11.45	62.13	74.00	11.87
4874.000	37.12	AV	V	11.45	48.57	54.00	5.43
High Channel: 2452 MHz							
2483.500	28.73	PK	H	32.19	60.92	74.00	13.08
2483.500	16.16	AV	H	32.19	48.35	54.00	5.65
2483.500	27.96	PK	V	32.19	60.15	74.00	13.85
2483.500	15.82	AV	V	32.19	48.01	54.00	5.99
4904.000	52.24	PK	H	11.58	63.82	74.00	10.18
4904.000	38.01	AV	H	11.58	49.59	54.00	4.41
4904.000	51.87	PK	V	11.58	63.45	74.00	10.55
4904.000	36.30	AV	V	11.58	47.88	54.00	6.12

**Listed with the worst harmonic margin test plots (802.11b Mode High Channel)
1-6GHz (Horizontal):**

Project No.: CR231167841-RF
Tester: Tao Zhu
Polarization: horizontal
Note:

Date: 2023-12-19




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4924.000	38.49	11.67	50.16	54.00	3.84	Average
2	4924.000	45.40	11.67	57.07	74.00	16.93	Peak

Vertical:

Project No.: CR231167841-RF
Tester: Tao Zhu
Polarization: vertical
Note:


Date: 2023-12-19



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4924.000	38.24	11.67	49.91	54.00	4.09	Average
2	4924.000	44.45	11.67	56.12	74.00	17.88	Peak

6-18GHz (Horizontal):


Project No.: CR231167841-RF
Tester: Tao Zhu
Polarization: horizontal
Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	17887.180	15.47	32.11	47.58	54.00	6.42	Average
2	17887.180	28.73	32.11	60.84	74.00	13.16	Peak

Vertical:


Project No.: CR231167841-RF
Tester: Tao Zhu
Polarization: vertical
Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	17030.210	19.41	28.22	47.63	54.00	6.37	Average
2	17030.210	32.66	28.22	60.88	74.00	13.12	Peak

18-25GHz (Horizontal):


Project No.: CR231167841-RF
Tester: Tao Zhu
Polarization: Horizontal
Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	23433.090	38.29	5.40	43.69	54.00	10.31	Average
2	23433.090	51.15	5.40	56.55	74.00	17.45	Peak

Vertical:

Project No.: CR231167841-RF
Tester: Tao Zhu
Polarization: Vertical
Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	23560.510	39.39	5.19	44.58	54.00	9.42	Average
2	23560.510	52.06	5.19	57.25	74.00	16.75	Peak

4.3 Minimum 6 dB Emission Bandwidth

Serial Number:	2DSO-1	Test Date:	2023/12/13
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rod Luo	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.6	Relative Humidity: (%)	46	ATM Pressure: (kPa)	101
----------------------	------	------------------------------	----	------------------------	-----


Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200120	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).




Test Data:

Test Modes	Test Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	2412	9.60	0.5
	2437	9.63	0.5
	2462	9.63	0.5
802.11g	2412	16.38	0.5
	2437	16.35	0.5
	2462	16.38	0.5
802.11n ht20	2412	16.59	0.5
	2437	16.59	0.5
	2462	16.59	0.5
802.11n ht40	2422	35.22	0.5
	2437	35.22	0.5
	2452	33.90	0.5








6dB Emission Bandwidth

802.11n ht20
Lowest ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 10:34:06802.11n ht20
Middle ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 10:45:02802.11n ht20
Highest ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 10:49:36

6dB Emission Bandwidth

802.11n ht40
Lowest ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 10:54:36802.11n ht40
Middle ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 11:01:37802.11n ht40
Highest ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 11:07:56

4.4 99% Occupied Bandwidth

Serial Number:	2DSO-1	Test Date:	2023/12/13
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rod Luo	Test Result:	N/A

Environmental Conditions:

Temperature: (°C)	26.6	Relative Humidity: (%)	46	ATM Pressure: (kPa)	101
----------------------	------	------------------------------	----	------------------------	-----

Test Equipment List and Details:




Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200120	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*




Test Data:


Test Modes	Test Channel	Test Frequency (MHz)	99% Occupied Bandwidth (MHz)
802.11b	Lowest	2412	13.08
	Middle	2437	13.08
	Highest	2462	13.08
802.11g	Lowest	2412	16.56
	Middle	2437	16.56
	Highest	2462	16.56
802.11n ht20	Lowest	2412	17.40
	Middle	2437	17.40
	Highest	2462	17.40
802.11n ht40	Lowest	2422	35.76
	Middle	2437	35.76
	Highest	2452	35.76

99% Occupied Bandwidth

802.11b
Lowest ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 09:11:45802.11b
Middle ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 09:18:44802.11b
Highest ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 09:22:12

99% Occupied Bandwidth

802.11g
Lowest ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 10:00:13802.11g
Middle ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 10:21:43802.11g
Highest ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 10:25:17

99% Occupied Bandwidth802.11n ht20
Lowest Channel

4.5 Maximum Conducted Output Power

Serial Number:	2DSO-1	Test Date:	2023/12/13
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rod Luo	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.6	Relative Humidity: (%)	46	ATM Pressure: (kPa)	101
----------------------	------	------------------------------	----	------------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Anritsu	Power Meter	ML2495A	1106009	2023/08/04	2024/08/03
Anritsu	Pulse Power Sensor	MA2411A	10780	2023/08/04	2024/08/03

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Modes	Test Frequency (MHz)	Maximum Conducted Peak Output Power (dBm)	Limit (dBm)
802.11b	2412	5.65	30
	2437	5.05	30
	2462	5.12	30
802.11g	2412	9.92	30
	2437	10.02	30
	2462	10.01	30
802.11n ht20	2412	12.52	30
	2437	12.49	30
	2462	12.56	30
802.11n ht40	2422	14.80	30
	2437	14.76	30
	2452	14.84	30

4.6 Maximum Power Spectral Density

Serial Number:	2DSO-1	Test Date:	2023/12/13
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rod Luo	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.6	Relative Humidity: (%)	46	ATM Pressure: (kPa)	101
----------------------	------	------------------------------	----	------------------------	-----

Test Equipment List and Details:




Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200120	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Test Mode	Test Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	2412	-24.13	8.00
	2437	-22.57	8.00
	2462	-24.46	8.00
802.11g	2412	-23.61	8.00
	2437	-24.15	8.00
	2462	-24.62	8.00
802.11n ht20	2412	-20.66	8.00
	2437	-21.38	8.00
	2462	-20.67	8.00
802.11n ht40	2422	-21.56	8.00
	2437	-20.86	8.00
	2452	-21.11	8.00

Maximum power spectral density

802.11b
Lowest ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 09:12:47802.11b
Middle ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 09:19:58802.11b
Highest ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 09:23:24


Maximum power spectral density

802.11g
Lowest Channel




ProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 10:01:09

802.11g
Middle Channel






ProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 10:22:52

802.11g
Highest Channel






ProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 10:26:12

Maximum power spectral density

802.11n ht20
Lowest ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 10:34:38802.11n ht20
Middle ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 10:45:35802.11n ht20
Highest ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 10:50:05

Maximum power spectral density

802.11n ht40
Lowest ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 10:55:25802.11n ht40
Middle ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 11:02:22802.11n ht40
Highest ChannelProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 11:08:41

4.7 100 kHz Bandwidth of Frequency Band Edge:

Serial Number:	2DSO-1	Test Date:	2023/12/13
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rod Luo	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.6	Relative Humidity: (%)	46	ATM Pressure: (kPa)	101
----------------------	------	------------------------------	----	------------------------	-----

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200120	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:


100 kHz Bandwidth of Frequency Band Edge

802.11b
Lowest Band edge



ProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 09:14:37


802.11b
Highest Band edge




ProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 09:25:09

100 kHz Bandwidth of Frequency Band Edge

802.11g
Lowest Band edge




802.11g
Highest Band edge




100 kHz Bandwidth of Frequency Band Edge

802.11n ht20
Lowest Band edge



ProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 10:42:17


802.11n ht20
Highest Band edge



ProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 10:51:29


100 kHz Bandwidth of Frequency Band Edge

802.11n ht40
Lowest Band edge



ProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 10:58:50

802.11n ht40
Highest Band edge



ProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 11:11:53

4.8 Duty Cycle:

Serial Number:	2DSO-1	Test Date:	2023/12/13
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rod Luo	Test Result:	N/A

Environmental Conditions:

Temperature: (°C)	26.6	Relative Humidity: (%)	46	ATM Pressure: (kPa)	101
----------------------	------	------------------------------	----	------------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200120	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A


** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:


Test Modes	Ton (ms)	Ton+off (ms)	Duty cycle (%)	1/T (Hz)	VBW setting (Hz)
802.11b	33.18	33.20	99.94	/	10
802.11g	5.49	5.54	99.10	/	10
802.11n ht20	5.08	5.11	99.41	/	10
802.11n ht40	2.47	2.49	99.20	/	10

Duty Cycle


802.11b

ProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 09:17:15


802.11g

ProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 10:20:14

802.11n ht20

ProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 10:42:54

802.11n ht40



ProjectNo.:CR231167841-RF Tester:Rod Luo
Date: 13.DEC.2023 10:59:44

5. RF EXPOSURE EVALUATION

5.1 MPE-Based Exemption

5.1.1 Applicable Standard

According to §1.1307(b)(3)(i)

(C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

5.1.2 Measurement Result

Radio	Frequency (MHz)	$\lambda/2\pi$ (mm)	Distance (mm)	Exemption ERP (mW)	Maximum Conducted Power including Tune-up Tolerance (dBm)	Antenna Gain (dBi)	ERP	
							dBm	mW
BLE	2402-2480	19.88	200	768	2.5	4.9	5.25	3.35
2.4G WLAN	2412-2462	19.80	200	768	15.0	4.9	17.75	59.57

Note:

The Maximum Conducted Power including Tune-up Tolerance was declared by manufacturer.
The 2.4G WLAN and BLE cannot transmit simultaneously.

Result: The device compliant the MPE-Based Exemption at 20cm distances.

6. EUT PHOTOGRAPHS

Please refer to the attachment CR231167841-EXP EUT EXTERNAL PHOTOGRAPHS and CR231167841-INP EUT INTERNAL PHOTOGRAPHS

7. TEST SETUP PHOTOGRAPHS

Please refer to the attachment CR231167841-00B-TSP TEST SETUP PHOTOGRAPHS.

===== END OF REPORT =====