

1

TEST REPORT				
Report Number:	90454-23-72-23-PP002			
Date of issue:	June 29.2023			
Tested by (+signature):	Duke Chen	Ruke Chen		
Approved by (+signature):	Jason Gao	Jason gao		
Testing Laboratory name:	SLG-CPC Testlaboratory Co., Ltd.			
Address	No. 11, Wu Song Road, Dongcheng Di Province, China 523117	strict, Dongguan, Guangdong		
Applicant's name:	Lightcomm Technology Co., Ltd.			
Address	UNIT 1306 13/F ARION COMMERCIAL CENTRE,2-12 QUEEN'S ROAD WEST,SHEUNG WAN HK			
Manufacturer's name:	Lightcomm Technology Co., Ltd.			
Address	UNIT 1306 13/F ARION COMMERCIAL CENTRE,2-12 QUEEN'S ROAD WEST,SHEUNG WAN HK			
Factory's name	Huizhou Hengdu Electronics Co.,Ltd.			
Address	No.8 Huitai Road,Huinan High-tech Industrial Park,Huiao Avenue,Huizhou,Guangdong,China			
Standard(s):	FCC 47 CFR Part 15, Subpart C			
Test item description:	Car Multimedia System			
Model/Type reference:	DMCPA8W			
Series models	DMCPA80FL, DCPA813, DCPA81W, DMCPA10W, AVM2310W, J1CA10FL, CAR1013, CAR813, J1CA8FL, CVS8489W-SD, CVS1515W- SD, XDCPA73W, DCPA723W, DCA73W, DMCPA703W, CAR723W, J3CA7W, CVS7482W-SD			
FCC ID	XMF-DMCPA8W			
Date of receipt of test item:	tem: June 01.2023			
Date (s) of performance of test:	st: June 02.2023 to June 15.2023			
Summary of Test Results:	Pass			
The Summary of Test Results base	ed on a technical opinion belongs to the	standard(s).		

#### General disclaimer:

This report shall not be reproduced except in full, without the written approval of SLG-CPC Testlaboratory Co., Ltd. The test results in the report only apply to the tested sample.



## TABLE OF CONTENTS

1	EUT TECHNICAL DESCRIPTION	
2	SUMMARY OF TEST RESULT	4
3	TEST METHODOLOGY	5
3.1	GENERAL DESCRIPTION OF APPLIED STANDARDS	5
3.2	MEASUREMENT EQUIPMENT USED	5
3.3	DESCRIPTION OF TEST MODES	6
4	FACILITIES AND ACCREDITATIONS	7
4.1	FACILITIES	7
4.2	LABORATORY ACCREDITATIONS AND LISTINGS	7
5	TEST SYSTEM UNCERTAINTY	8
6	SETUP OF EQUIPMENT UNDER TEST	9
6.1	RADIO FREQUENCY TEST SETUP 1	9
6.2	RADIO FREQUENCY TEST SETUP 2	9
6.3	CONDUCTED EMISSION TEST SETUP	11
6.4	BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM	
6.5	SUPPORT EQUIPMENT	
7	TEST REQUIREMENTS	
7.1	DTS (6DB) BANDWIDTH	
7.2	MAXIMUM CONDUCTED OUTPUT POWER	
7.3	MAXIMUM POWER SPECTRAL DENSITY	
7.4	UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS	
7.5	RADIATED SPURIOUS EMISSION	
7.6	ANTENNA APPLICATION	
7.7	TEST PHOTO	
7.8	EUT PHOTO	



## **1 EUT TECHNICAL DESCRIPTION**

Characteristics	Description
Product:	Car Multimedia System
Model Number:	DMCPA8W
Model Differences:	DMCPA80FL, DCPA813, DCPA81W, DMCPA10W, AVM2310W, J1CA10FL, CAR1013, CAR813, J1CA8FL, CVS8489W-SD, CVS1515W- SD, XDCPA73W, DCPA723W, DCA73W, DMCPA703W, CAR723W, J3CA7W, CVS7482W-SD
IEEE 802.11 WLAN Mode Supported :	⊠802.11b ⊠802.11g ⊠802.11n(20MHz channel bandwidth)
Modulation :	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Operating Frequency Range :	2412-2462MHz for 802.11b/g/n(HT20);
Number of Channels :	⊠11 channels for 802.11b/g/n(HT20);
Antenna Type :	External antenna
Antenna Gain : 1.59dBi	
Power Supply:	DC 12V
rower Suppry.	Adapter supply:

Note: for more details, please refer to the User's manual of the EUT.



## 2 SUMMARY OF TEST RESULT

FCC Part Clause	Test Parameter	Verdict	Remark			
15.247(a)(2)	DTS (6dB) Bandwidth	PASS				
15.247(b)(3)	Maximum Peak Conducted Output Power	PASS				
15.247(e)	Maximum Power Spectral Density Level	PASS				
15.247(d)	Unwanted Emission Into Non-Restricted Frequency Bands	PASS				
15.247(d) 15.209	Unwanted Emission Into Restricted Frequency Bands (conducted)	PASS				
15.247(d) 15.209	Radiated Spurious Emission	PASS				
15.207	Conducted Emission Test	N/A				
15.247(b)	15.247(b) Antenna Application PASS					
NOTE1:N/A (Not A	pplicable)					
NOTE2: According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.						

15.207 only signals conducted onto the AC power lines are required to be measured. The equipment is only DC power supply, so "Power Line Conducted Emissions" is not required.

#### RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: XMF-DMCPA8W filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.



## **3 TEST METHODOLOGY**

#### 3.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards: FCC 47 CFR Part 15, Subpart C

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

#### 3.2 MEASUREMENT EQUIPMENT USED

Equipment	Model	Manufacturer	S/N	Last Cal.	DUE Cal.			
RF Connected Test								
Vector Signal Generater	Rohde & Schwarz	SMBV100B(6G)	101166	2022/06/29	1 year			
Analog Signal Generator	Rohde & Schwarz	SMB100A(40G)	181333	2022/06/29	1 year			
Signal Analyzer	Rohde & Schwarz	FSV40	101527	2023/03/29	1 year			
Power Analyzer	Rohde & Schwarz	OSP-B157W8	N/A	2022/06/29	1 year			
Wideband Radio Communication Tester	R&S	CMW270	101985	2022/07/05	1 year			
Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	166898	2022/07/14	1 year			
Spectrum Analyzer	Agilent	E4408B	MY44211139	2022/11/07	1 year			
Temperature&Humidity test chamber	ESPEC	VC 4018	/	2023/03/29	1 year			
	Radia	ated Emission Tes	st					
EMI Test Receiver	KEYSIGHT	N9010A	MY56070465	2022/12/07	1 year			
EMI Test Receiver	Rohde & Schwarz	FSV40	101511	2023/03/29	1 year			
Bilog Antenna	Schwarzbeck	VULB 9163	01335	2023/04/21	3 year			
Power Amplifier	EMEC	EM330	060676	2022/12/07	3 year			
Cable	Tuyue	F4309	L-400-NmNm- 12000	2022/12/07	1 year			
Horn Antenna	Schwarzbeck	BBHA9120D	1779	2022/04/21	3 year			
Horn Antenna	Schwarzbeck	BBHA9170	00954	2022/09/13	3 year			
Power Amplifier	Rohde & Schwarz	SCU-18F	180118	2022/04/21	3 year			
Active Loop Antenna	ETS LINDGREN	6512	41623	2022/04/23	3 year			
Test Software	Farad	EZ-EMC	Ver.CPC-3A1	/	/			
Conducted Emission Test								
LISN	Schwarzbeck	NSLK 8127	8127-892	2023/03/21	1 year			
EMI Test Receiver	R&S	ESR3	102124	2022/12/07	1 year			
Pulse Limiter	R&S	ESH3-Z2	357.8810.52	2022/12/07	1 year			
Test Software	Farad	EZ-EMC	Ver.CPC-3A1	/	/			



#### **3.3 DESCRIPTION OF TEST MODES**

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates ( $\boxtimes$ 802.11b:1 Mbps;  $\boxtimes$ 802.11g: 6 Mbps;  $\boxtimes$ 802.11n(HT20): MCS0;  $\square$ 802.11n(HT40): MCS0) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel	Frequency	ency Iz) Channel	Frequency	Channel	Frequency
	(MHz)		(MHz)		(MHz)
1	2412	6	2437	11	2462
2	2417	7	2442		
3	2422	8	2447		
4	2427	9	2452		
5	2432	10	2457		

Frequency and Channel list for 802.11b/g/n (HT20):

Test Frequency and Channel for 802.11b/g/n (HT20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462



## **4** FACILITIES AND ACCREDITATIONS

#### 4.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

No. 11, Wu Song Road, Dongcheng District, Dongguan, Guangdong Province, China 523117 The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

#### 4.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description		
EMC Lab.	:	Accredited by A2LA The Certificate Number is 6325.01.
Name of Firm Site Location	:	SLG-CPC Testlaboratory Co., Ltd. No. 11, Wu Song Road, Dongcheng District, Dongguan, Guangdong Province, China 523117



## **5 TEST SYSTEM UNCERTAINTY**

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	±1x10^-5
Maximum Peak Output Power Test	±1.0dB
Conducted Emissions Test	±2.0dB
Radiated Emission Test	±2.0dB
Power Density	±2.0dB
Occupied Bandwidth Test	±1.0dB
Band Edge Test	±3dB
All emission, radiated	±3dB
Antenna Port Emission	±3dB
Temperature	±0.5°C
Humidity	±3%

Measurement Uncertainty for a level of Confidence of 95%



## **6 SETUP OF EQUIPMENT UNDER TEST**

#### 6.1 RADIO FREQUENCY TEST SETUP 1

The WLAN component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



#### 6.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

#### Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT androtated about its vertical axis formaximum response at each azimuth about the EUT. The center of the loopshall be 1 m above the ground.For certain applications, the loop antennaplane may also need to be positioned horizontally at the specified distance from the EUT.

#### 30MHz-1GHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

#### Above 1GHz:

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

(a) Radiated Emission Test Set-Up, Frequency Below 30MHz







#### (b) Radiated Emission Test Set-Up, Frequency Below 1000MHz

#### (c) Radiated Emission Test Set-Up, Frequency above 1000MHz





#### 6.3 CONDUCTED EMISSION TEST SETUP

The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN. Ground connections, where required for safety purposes, shall be connected to the reference ground point

of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m. According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.





#### 6.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



#### 6.5 SUPPORT EQUIPMENT

EUT Cable List and Details					
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite		
DC cable	1.0	Unshielded	Without Ferrite		

Auxiliary Cable List and Details					
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite		
/	/	/	/		

Auxiliary Equipment List and Details					
Description	Manufacturer	Model	Serial Number		
Notebook	Lenovo	MPNXB1505007	MP1XHYV7		

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.

2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

3. Unless otherwise denoted as EUT in *[Remark]* column , device(s) used in tested system is a support equipment



## 7 TEST REQUIREMENTS

#### 7.1 DTS (6DB) BANDWIDTH

#### 7.1.1 Applicable Standard

According to FCC Part15.247 (a)(2) and KDB 558074 D01 15.247 Meas Guidance v05r02

#### 7.1.2 Conformance Limit

The minimum -6 dB bandwidth shall be at least 500 kHz.

#### 7.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

#### 7.1.4 Test Procedure

The EUT was operating in IEEE 802.11b/g/n mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 100 kHz.

Set the video bandwidth (VBW) =300kHz.

Set Span=2 times OBW

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. Measure and record the results in the test report.

7.1.5 Test Results

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Operation Mode	Channel Number	Channel Frequency (MHz) Measurement Bandwidth (MH		Limit (kHz)	Verdict
	1	2412	9.117	>500	PASS
802.11b	6	2437	9.122	>500	PASS
	11	2462	9.517	>500	PASS
802.11g	1	2412	16.400	>500	PASS
	6	2437	16.090	>500	PASS
	11	2462	16.380	>500	PASS
802.11n (HT20)	1	2412	16.330	>500	PASS
	6	2437	16.490	>500	PASS
	11	2462	16.530	>500	PASS

Page 14 of 48





#### **Test Model**

#### DTS (6dB) Bandwidth 802.11b Channel 6: 2437MHz







#### DTS (6dB) Bandwidth 802.11g Channel 1: 2412MHz







#### DTS (6dB) Bandwidth 802.11g Channel 11: 2462MHz







#### DTS (6dB) Bandwidth 802.11n (HT20) Channel 6: 2437MHz



#### 90454-23-72-23-PP002

Page 18 of 48



#### Test Model

#### DTS (6dB) Bandwidth 802.11n (HT20) Channel 11: 2462MHz

Agilent Spectrum Analyzer - Occupied BW				
	SENSE:INT	ALIGNAUTO 02:19:5	PM Apr 27, 2022	Frequency
Center Freq 2.462000000 GHz	Trig: Free Run	Avg Hold:>10/10	u. Hone	
#IFGain:	Low #Atten: 22 dB	Radio D	evice: BTS	
10 dB/div Ref 20.00 dBm				
				Contor From
				2 462000000 GHz
10.0				2.402000000 GH2
20.0	and a start and a start a start of the start	wwwwww		
20.0				
		<u>Ъ</u> а и .		
-40.0		multin	A A	
		4 Met 10	w w low	
-60.0				
-70.0				
Center 2.462 GHz		Sp	an 40 MHz	05.044
#Res BW 100 kHz	#VBW 300 kH	z Si	veep 5 m s	4 000000 MHz
On surveying of Damaker is 14h	Total Bay	vor 10.7 dBm		<u>Auto</u> Man
Occupied Bandwidth				
16.903	3 MHz			Freq Offset
Transmit Freg Error -42	615 kHz OBW Pov	wer 99.00 %		0 Hz
		00.00 /ID		
x dB Bandwidth 16	5.53 MHZ X dB	-6.00 dB		
MSG		STATUS		



#### 7.2 MAXIMUM CONDUCTED OUTPUT POWER

#### 7.2.1 Applicable Standard

According to FCC Part15.247 (b)(3) and KDB 558074 D01 15.247 Meas Guidance v05r02

#### 7.2.2 Conformance Limit

The maximum conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm).

#### 7.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

#### 7.2.4 Test Procedure

a) Set span to at least 1.5 times the OBW.

b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.

c) Set VBW  $\ge$  3 x RBW.

d) Number of points in sweep  $\ge$  2  $\times$  span / RBW. (This gives bin-to-bin spacing  $\le$  RBW/2, so that narrowband signals are not lost between frequency bins.)

e) Sweep time = auto.

f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.

g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle  $\ge$  98 %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".

h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.

i) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

#### 7.2.5 Test Results

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm)	Limit (dBm)	Verdict
	1	2412	15.23	30	PASS
802.11b	6	2437	14.68	30	PASS
	11	2462	14.91	30	PASS
	1	2412	16.43	30	PASS
802.11g	6	2437	16.09	30	PASS
	11	2462	17.15	30	PASS
902 11 m	1	2412	17.48	30	PASS
002.1111 (HT20)	6	2437	17.52	30	PASS
(1120)	11	2462	17.89	30	PASS



#### 7.3 MAXIMUM POWER SPECTRAL DENSITY

#### 7.3.1 Applicable Standard

According to FCC Part15.247(e) and KDB 558074 D01 15.247 Meas Guidance v05r02

#### 7.3.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### 7.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

#### 7.3.4 Test Procedure

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance

The transmitter output (antenna port) was connected to the spectrum analyzer Set analyzer center frequency to DTS channel center frequency. Set the span to 1.5 times the DTS bandwidth. Set the RBW to: 3 kHz Set the VBW to:10 kHz. Set Detector = peak. Set Sweep time = auto couple. Set Trace mode = max hold. Allow trace to fully stabilize. Use the peak marker function to determine the maximum amplitude level within the RBW. Note: If antenna Gain exceeds 6 dBi, then PSD Limit=8-(Gain- 6)

#### 7.3.5 Test Results

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Operation Mode	Channel Number	Channel Frequency (MHz)	Channel Frequency (MHz) Measurement Level (dBm/3kHz)		Verdict
	1	2412	-15.794	8	PASS
802.11b	6	2437	-14.897	8	PASS
	11	2462	-15.620	8	PASS
	1	2412	-22.495	8	PASS
802.11g	6	2437	-21.406	8	PASS
	11	2462	-22.825	8	PASS
802.11n	1	2412	-22.081	8	PASS
	6	2437	-21.590	8	PASS
(1120)	11	2462	-22.457	8	PASS





#### Power Spectral Density 802.11b Channel 6: 2437MHz







#### Power Spectral Density 802.11g Channel 1: 2412MHz







#### Power Spectral Density 802.11g Channel 11: 2462MHz







#### Power Spectral Density 802.11n (HT20) Channel 6: 2437MHz











#### 7.4 UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS

#### 7.4.1 Applicable Standard

According to FCC Part15.247(d) and KDB 558074 D01 15.247 Meas Guidance v05r02

#### 7.4.2 Conformance Limit

#### According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

7.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

7.4.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

#### Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to  $\geq$  1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW  $\geq$  3 x RBW.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

#### Emission level measurement

Set the center frequency and span to encompass frequency range to be measured.

Set the RBW = 100 kHz.

Set the VBW =300 kHz.

Set Detector = peak

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements. Report the three highest emissions relative to the limit.

7.4.5 Test Results



All the antennas and modulation modes were tested, and the worst data for is shown in the table below. Unwanted Emissions in non-restricted frequency bands

⊠802.11b ⊡802.11g ⊠Channel 1: 2412MHz

802.11n(HT20)



 Mkr1 2.483 50 GHz
 Next Pk Right

 10 dB/div
 Ref 10.00 dBm
 -55.399 dBm

 000
 -55.399 dBm
 Next Pk Right

 100
 -000
 -000

 100
 -000
 -000

 200
 -000
 -000

 200
 -000
 -000

 200
 -000
 -000

 400
 -000
 -000

 400
 -000
 -000

 400
 -000
 -000

 400
 -000
 -000

 600
 -000
 -000

 700
 -000
 -000

 700
 -000
 -000

 700
 -000
 -000

 700
 -000
 -000

 700
 -000
 -000

 700
 -000
 -000

 700
 -000
 -000

 700
 -000
 -000

 700
 -000
 -000

 700
 -000
 -000

 700
 -000
 -000













#### 7.5 RADIATED SPURIOUS EMISSION

#### 7.5.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 Meas Guidance v05r02

#### 7.5.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). According to FCC Part15.205, Restricted bands

0			
MHz	MHz	MHz	GHz
0.090-0.110	0.110 16.42-16.423 399.9-410		4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted	Field Strength (µV/m)	eld Strength ( $\mu$ V/m) Field Strength (dB $\mu$ V/m)	
Frequency(MHz)			Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	24000/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

#### 7.5.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

#### 7.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for f  $\ge$  1 GHz(1GHz to 25GHz), 100 kHz for f < 1 GHz(30MHz to 1GHz), 200Hz for f<150KHz(9KHz to 150KHz), 9KHz for f<30MHz(150KHz to 30KHz)

 $VBW \geq RBW$ 

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this

Address:No.11,WuSongRoad, DongchengDistrict,Dongguan, GuangdongProvince,China523117



test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from 20log(dwell time/100 ms), in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

#### 7.5.5 Test Results

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

#### Spurious Emission below 30MHz(9KHz to 30MHz)

Freq.	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
	H/V	PK	ÂV	PK	AV	PK	AV

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =40log(Specific distance/ test distance)( dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor



- Spurious Emission Above 1GHz(1GHz to 25GHz)
- All modes 2.4G 802.11b/g/n have been tested, and the worst result recorded was report as below:

#### Antenna 1:

Test mode:	802.11 b		Frequency:		Channel 1: 2412MHz		z
Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
	H/V	PK	AV	PK	AV	PK	AV
3068.45	V	56.81	43.58	74	54	-17.19	-10.42
7173.30	V	53.88	39.83	74	54	-20.12	-14.17
14792.42	V	50.84	37.37	74	54	-23.16	-16.63
3048.56	Н	57.64	40.90	74	54	-16.36	-13.10
7098.02	Н	54.02	41.20	74	54	-19.98	-12.80
14741.21	Н	48.08	37.50	74	54	-25.92	-16.50

Test mode:	802.11 b		Frequency:		Channel 11: 2462MHz		
Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
	H/V	PK	AV	PK	AV	PK	AV
2965.14	V	57.91	43.06	74	54	-16.09	-10.94
5676.81	V	53.94	39.77	74	54	-20.06	-14.23
10732.58	V	49.76	36.30	74	54	-24.24	-17.70
3041.96	Н	59.73	44.38	74	54	-14.27	-9.62
7694.13	Н	55.02	40.60	74	54	-18.98	-13.40
11894.03	Н	48.30	36.46	74	54	-25.70	-17.54

Note: (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).

(2) Emission Level= Reading Level+Correct Factor.

(3) Correct Factor= Ant\_F + Cab\_L - Preamp

(4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

All modes 2.4G 802.11b/g/n have been tested, and the worst result recorded was report as below:

Antenna 1:

Test mode:	802.11 b	Frequency:		Channel 1: 2412MHz		
Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)	
2389.99	Н	62.72	74	41.10	54	
2389.63	V	56.34	74	37.30	54	
Test mode:	802.11 b	Frequ	ency: (	Channel 11: 2462MF	łz	
Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)	
2483.56	Н	70.79	74	50.43	54	
2484.25	V	63.35	74	45.60	54	

Note: (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).

(2) Emission Level= Reading Level+Correct Factor.

 (3) Correct Factor= Ant\_F + Cab\_L - Preamp
(4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



- Spurious Emission below 1GHz (30MHz to 1GHz)
- All antenna modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11g recorded was report as below:









#### 7.6 ANTENNA APPLICATION

#### 7.6.1 Antenna Requirement

Standard	Requirement				
FCC CRF Part15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217,§15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.				

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

#### 7.6.2 Result

PASS.

The EUT has 1 antennas:a Integral Antenna for Wifi model, the gain is 2.5 dBi Note:

Antenna uses a permanently attached antenna which is not replaceable.

Not using a standard antenna jack or electrical connector for antenna replacement

The antenna has to be professionally installed (please provide method of installation)

Which in accordance to section 15.203, please refer to the internal photos.



### **7.7 TEST PHOTO**





#### **7.8 EUT PHOTO**

External photo M/N: DMCPA8W, DMCPA80FL, DCPA813, DCPA81W, CAR1013, CAR813, J1CA8FL, CVS8489W-SD, XDCPA73W, DCPA723W, DCA73W, DMCPA703W, CAR723W, J3CA7W, CVS7482W-SD





Page 39 of 48



#### External photo

M/N: DMCPA8W, DMCPA80FL, DCPA813, DCPA81W, CAR1013, CAR813, J1CA8FL, CVS8489W-SD, XDCPA73W, DCPA723W, DCA73W, DMCPA703W, CAR723W, J3CA7W, CVS7482W-SD







#### External photo

# M/N: DMCPA8W, DMCPA80FL, DCPA813, DCPA81W, CAR1013, CAR813, J1CA8FL, CVS8489W-SD, XDCPA73W, DCPA723W, DCA73W, DMCPA703W, CAR723W, J3CA7W, CVS7482W-SD







#### External photo

# M/N: DMCPA8W, DMCPA80FL, DCPA813, DCPA81W, CAR1013, CAR813, J1CA8FL, CVS8489W-SD, XDCPA73W, DCPA723W, DCA73W, DMCPA703W, CAR723W, J3CA7W, CVS7482W-SD







## External photo M/N: DMCPA10W, AVM2310W, J1CA10FL, CAR1013, CVS1515W-SD







External photo M/N: DMCPA10W, VM2310W, J1CA10FL, CAR1013, CVS1515W-SD







## External photo M/N: DMCPA10W, AVM2310W, J1CA10FL, CAR1013, CVS1515W-SD







Internal photo





Page 46 of 48



Internal photo









## Internal photo







Internal photo





----- END OF REPORT ------