



Microtest
微 测 检 测

Test Report

Report No.: MTi230509012-16E2

Date of issue: 2023-06-29

Applicant: ShenZhen ZhiHaiHe Tech Co., Ltd.

Product name: VARMILO Mechanical Keyboard

Model(s): VXT81, VXT82

FCC ID: 2AF8O-VXT81

Shenzhen Microtest Co., Ltd.
<http://www.mtitest.com>



Instructions

1. The report shall not be partially reproduced without the written consent of the laboratory;
2. The test results of this report are only responsible for the samples submitted;
3. This report is invalid without the seal and signature of the laboratory;
4. This report is invalid if transferred, altered or tampered with in any form without authorization;
5. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	FEATURE OF EQUIPMENT UNDER TEST (EUT).....	5
1.2	OPERATION CHANNEL LIST	5
1.3	TEST FREQUENCY CHANNEL	5
1.4	EUT OPERATION MODE	6
1.5	ANCILLARY EQUIPMENT LIST.....	6
2	SUMMARY OF TEST RESULT.....	6
3	TEST FACILITIES AND ACCREDITATIONS	7
3.1	TEST LABORATORY	7
3.2	ENVIRONMENTAL CONDITIONS	7
3.3	MEASUREMENT UNCERTAINTY.....	7
3.4	TEST SOFTWARE	7
4	LIST OF TEST EQUIPMENT.....	8
5	TEST RESULT	9
5.1	ANTENNA REQUIREMENT	9
5.1.1	Standard requirement.....	9
5.1.2	EUT Antenna	9
5.2	AC POWER LINE CONDUCTED EMISSION	10
5.2.1	Limits.....	10
5.2.2	Test setup	10
5.2.3	Test procedure.....	11
5.2.4	Test results	11
5.3	RADIATED SPURIOUS EMISSION	14
5.3.1	Limit	14
5.3.2	Test method.....	14
5.3.3	Test Result	15
5.3.4	Band edge-Field strength of fundamental	20
5.3.5	Band edge-radiated	21
5.4	20dB AND 99% BANDWIDTH	22
5.4.1	Limits.....	22
5.4.2	Test method.....	22
5.4.3	Test result.....	23
	PHOTOGRAPHS OF THE TEST SETUP	25
	PHOTOGRAPHS OF THE EUT	26



TEST RESULT CERTIFICATION	
Applicant:	ShenZhen ZhiHaiHe Tech Co., Ltd.
Address:	Unit B,2nd Floor, Block 3,10th Industrial Zone, Tian Liao Community, Gong Ming Area, Guang Ming New District, Shen Zhen, China
Manufacturer:	ShenZhen ZhiHaiHe Tech Co., Ltd.
Address:	Unit B,2nd Floor, Block 3,10th Industrial Zone, Tian Liao Community, Gong Ming Area, Guang Ming New District, Shen Zhen, China
Factory:	ShenZhen ZhiHaiHe Tech Co., Ltd.
Address:	Unit B,2nd Floor, Block 3,10th Industrial Zone, Tian Liao Community, Gong Ming Area, Guang Ming New District, Shen Zhen, China
Product description	
Product name	VARMILO Mechanical Keyboard
Trademark	VARMILO
Model Name	VXT81
Series Model.....	VXT82
Standards	FCC Part 15.249
Test procedure.....	ANSI C63.10-2013
Date of Test	
Date (s) of performance of tests	2023-05-16 ~ 2023-06-29
Test Result.....	Pass

Note: All two models have been tested, and the report only shows the VXT81 with the worst data.

Testing Engineer

:

Letter Lan.

(Letter Lan)

Technical Manager

:

Leon Chen

(Leon Chen)

Authorized Signatory

:

Tom Xue

(Tom Xue)

1 General description

1.1 Feature of equipment under test (EUT)

Equipment:	VARMILO Mechanical Keyboard
Model Name:	VXT81
Serial Model:	VXT82
Model Difference:	All the models are the same circuit and module, except the model name, color and appearance.
Operation Frequency:	2410 - 2468 MHz
Modulation Type:	GFSK
Antenna Type:	PCB antenna
Antenna Gain:	0.11dBi
Max. Field Strength:	88.45dBuV/m
Power Source:	Input: DC 5V/0.5A Battery: DC 3.7V 3400mAh
Accessories:	Cable: USB-A to USB-C cable 1.8m
Hardware version:	VXT82-V1.0(G)
Software version:	ZHH-MINILO-K81_2-MA08559-230512-1.00-0004-53C0
Test sample(s) number:	MTi230509012-16S001(model: VXT81) MTi230509012-16S002(model: VXT82)

1.2 Operation channel list

Channel	Frequency(MHz)	Channel	Frequency(MHz)	Channel	Frequency(MHz)	Channel	Frequency(MHz)
CH01	2410	CH09	2426	CH17	2442	CH25	2458
CH02	2412	CH10	2428	CH18	2444	CH26	2460
CH03	2414	CH11	2430	CH19	2446	CH27	2462
CH04	2416	CH12	2432	CH20	2448	CH28	2464
CH05	2418	CH13	2434	CH21	2450	CH29	2466
CH06	2420	CH14	2436	CH22	2452	CH30	2468
CH07	2422	CH15	2438	CH23	2454		
CH08	2424	CH16	2440	CH24	2456		

1.3 Test Frequency Channel

Channel	Frequency(MHz)
Low	2410
Middle	2440
High	2468

1.4 EUT operation mode

During testing, RF test program provided by the manufacture to control the Tx operation followed the test requirement.

Mode	Test Software	ET Dual Keyboard Test Tool Ver 1.0.4.11		
	Channel	2410MHz	2440MHz	2468MHz
2.4G SRD	Power setting	DEF	DEF	DEF

1.5 Ancillary equipment list

Equipment	Model	S/N	Manufacturer
Adapter	HW-090200CH0	/	Huizhou BYD Electronics Co., Ltd.
Mobile phone	S9+	R28C34V79NT	SAMSUNG

2 Summary of Test Result

Test procedures according to the technical standards:

Item	FCC Part No.	Description of Test	Result
1	FCC Part15.203	Antenna Requirement	Pass
2	FCC Part15.207	AC power line conducted emission	Pass
5	FCC Part15.249(d)	Radiated spurious emission	Pass
4	FCC Part 15.215	20dB and 99% Bandwidth	Pass

3 Test Facilities and Accreditations

3.1 Test laboratory

Test Laboratory	Shenzhen Microtest Co., Ltd
Location	101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China.
FCC Registration No.	448573

3.2 Environmental conditions

Temperature:	15°C~35°C
Humidity	20%~75%
Atmospheric pressure	98kPa~101kPa

3.3 Measurement uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %

RF frequency	1×10^{-7}
RF power, conducted	± 1 dB
Conducted emission(150kHz~30MHz)	± 2.5 dB
Radiated emission (9 kHz ~ 30 MHz)	± 4.0 dB
Radiated emission(30MHz~1GHz)	± 4.2 dB
Radiated emission (above 1GHz)	± 4.3 dB
Temperature	± 1 degree
Humidity	± 5 %

3.4 Test software

Software Name	Manufacturer	Model	Version
Bluetooth and WiFi Test System	Shenzhen JS tonscond co.,ltd	JS1120-3	2.5.77.0418

4 List of test equipment

Equipment No.	Equipment Name	Manufacturer	Model	Serial No.	Calibration date	Due date
MTI-E043	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2023/04/26	2024/04/25
MTI-E044	TRILOG Broadband Antenna	schwarzbeck	VULB 9163	9163-1338	2021/05/30	2024/05/29
MTI-E047	Amplifier	Hewlett-Packard	8447F	3113A06150	2023/04/26	2024/04/25
MTI-E089	ESG Vector Signal Generator	Agilent	N5182A	MY49060455	2023/04/26	2024/04/25
MTI-E058	ESG Series Analog Signal Generator	Agilent	E4421B	GB40051240	2023/04/26	2024/04/25
MTI-E062	PXA Signal Analyzer	Agilent	N9030A	MY51350296	2023/04/26	2024/04/25
MTI-E066	MXA Signal Analyzer	Agilent	N9020A	MY50143483	2023/04/26	2024/04/25
MTI-E078	Synthesized Sweeper	Agilent	83752A	3610A01957	2023/04/26	2024/04/25
MTI-E079	DC Power Supply	Agilent	E3632A	MY40027695	2023/04/26	2024/04/25
MTI-E045	Double Ridged Broadband Horn Antenna	schwarzbeck	BBHA 9120D	9120D-2278	2021/05/30	2024/05/29
MTI-E022	Pulse Limiter	Schwarzbeck	VSTD 9561-F	00679	2022/08/24	2023/08/23
MTI-E023	Artificial mains network	Schwarzbeck	NSLK 8127	NSLK 8127 #841	2023/05/05	2024/05/04
MTI-E046	Active Loop Antenna	Schwarzbeck	FMZB 1519B	00044	2021/05/30	2024/05/29
MTI-E048	Amplifier	Agilent	8449B	3008A02400	2023/05/05	2024/05/04
MTI-E072	Thermometer Clock Humidity Monitor	-	HTC-1	/	2023/05/05	2024/05/04
Note: the calibration interval of the above test instruments is 12 or 24 months and the calibrations are traceable to international system unit (SI).						

5 Test Result

5.1 Antenna requirement

5.1.1 Standard requirement

FCC PART 15.203;

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

5.1.2 EUT Antenna

The antenna is a PCB antenna, which was permanently affixed to the device and un-replaced, complies with 15.203. In addition, the maximum antenna gain is 0.11dBi.



5.2 AC power line conducted emission

5.2.1 Limits

FCC §15.207;


For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 ^{note2}	56 - 46 ^{note2}
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note1: The tighter limit applies at the band edges.

Note2: The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

5.2.2 Test setup



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

5.2.3 Test procedure

a. EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b. The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


- c. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment's powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- d. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- e. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- f. LISN at least 80 cm from nearest part of EUT chassis.

For the actual test configuration, please refer to the related Item –EUT Test Photos.

5.2.4 Test results




EUT:	VARMiLO Mechanical Keyboard	Model Name :	VXT81
Pressure:	101kPa	Polarization:	N
Test voltage:	Power by AC/DC adapter AC 120V/60Hz	Test mode:	Mode 1



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	*	0.5180	31.39	11.36	42.75	56.00	-13.25	QP
2		0.5220	18.43	11.37	29.80	46.00	-16.20	AVG
3		0.8500	25.89	12.06	37.95	56.00	-18.05	QP
4		0.8580	13.47	12.08	25.55	46.00	-20.45	AVG
5		1.4180	9.95	13.23	23.18	46.00	-22.82	AVG
6		1.6220	21.59	13.66	35.25	56.00	-20.75	QP
7		4.8260	30.97	10.27	41.24	56.00	-14.76	QP
8		4.9660	14.28	10.27	24.55	46.00	-21.45	AVG
9		11.8979	22.65	10.38	33.03	50.00	-16.97	AVG
10		14.3700	34.83	10.46	45.29	60.00	-14.71	QP
11		20.8300	29.21	10.71	39.92	60.00	-20.08	QP
12		21.5700	16.85	10.72	27.57	50.00	-22.43	AVG



EUT:	VARMiLO Mechanical Keyboard	Model Name :	VXT81
Pressure:	101kPa	Polarization:	L
Test voltage:	Power by AC/DC adapter AC 120V/60Hz	Test mode:	Mode 1



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1	*	0.5140	21.54	11.34	32.88	46.00	-13.12	AVG
2		0.5180	30.60	11.36	41.96	56.00	-14.04	QP
3		0.8420	13.31	12.07	25.38	46.00	-20.62	AVG
4		0.8500	24.21	12.09	36.30	56.00	-19.70	QP
5		1.3460	8.55	12.97	21.52	46.00	-24.48	AVG
6		1.4540	19.33	13.12	32.45	56.00	-23.55	QP
7		2.3020	20.58	10.08	30.66	56.00	-25.34	QP
8		2.3100	10.02	10.08	20.10	46.00	-25.90	AVG
9		11.6620	21.50	10.45	31.95	50.00	-18.05	AVG
10		12.0140	32.82	10.45	43.27	60.00	-16.73	QP
11		20.3420	13.59	10.66	24.25	50.00	-25.75	AVG
12		21.4020	24.72	10.69	35.41	60.00	-24.59	QP

5.3 Radiated spurious emission

5.3.1 Limit

FCC PART 15.249(a);

Except as provided in paragraph (a) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Frequency (MHz)	Field Strength of Fundamental (mV/m)	Field Strength of Harmonics ($\mu\text{V/m}$)
902-928	50	500
2400-2483.5	50	500
5725-5875	50	500

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	$2400/F(\text{kHz})$	300
0.490 - 1.705	$24000/F(\text{kHz})$	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

5.3.2 Test method

- The EUT is placed on a turntable, which is 0.8m above ground plane for test frequency range below 1GHz, and 1.5m above ground plane for test frequency range above 1GHz.
- EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- Use the following spectrum analyser settings:
 - Span = wide enough to fully capture the emission being measured
 - RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$
 - VBW $\geq$ RBW, Sweep = auto
 - Detector function = peak
 - Trace = max hold
- Follow the guidelines in ANSI C63.4-2014 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.



- e) The peak level, once corrected, must comply with the limit specified in Section 15.209. Set the RBW = 1MHz, VBW = 10Hz, Detector = PK for AV value, while maintaining all of the other instrument settings.

5.3.3 Test Result

Below 30MHz

EUT:	VARMILO Mechanical Keyboard	Model name. :	VXT81
Pressure:	1010 hPa	Test voltage:	Power by AC/DC adapter AC 120V/60Hz
Test mode:	Charging+TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	Pass
--	--	--	--	Pass


Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);
3. Limit line = specific limits (dBuV) + distance extrapolation factor.



30MHz-1GHz


EUT:	VARMILO Mechanical Keyboard	Model Name:	VXT81
Pressure:	101kPa	Polarization:	Horizontal
Test voltage:	Power by AC/DC adapter AC 120V/60Hz	Test Mode:	TX-2468MHz



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	42.0066	42.29	-7.04	35.25	40.00	-4.75	QP
2		71.8320	43.48	-10.04	33.44	40.00	-6.56	QP
3		96.0986	42.48	-8.13	34.35	43.50	-9.15	QP
4	!	125.8864	49.09	-10.57	38.52	43.50	-4.98	QP
5		143.8295	46.13	-10.71	35.42	43.50	-8.08	QP
6		336.0352	43.70	-5.00	38.70	46.00	-7.30	QP



EUT:	VARMiLO Mechanical Keyboard	Model Name:	VXT81
Pressure:	101kPa	Polarization:	Vertical
Test voltage:	Power by AC/DC adapter AC 120V/60Hz	Test Mode:	TX-2468MHz



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	!	35.8746	42.20	-7.57	34.63	40.00	-5.37	QP
2	*	39.7146	42.83	-7.61	35.22	40.00	-4.78	QP
3		84.1100	43.13	-10.66	32.47	40.00	-7.53	QP
4		96.0986	41.26	-8.13	33.13	43.50	-10.37	QP
5		131.7577	46.73	-10.83	35.90	43.50	-7.60	QP
6		276.1235	40.12	-5.92	34.20	46.00	-11.80	QP

Note:

1. Emission Level = Meter Reading + Factor, Margin= Emission Level- Limit, Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. The three modulated high, medium and low channels have been tested. The report only shows the worst mode. The worst mode is CH30.



1GHz-26.5GHz:

Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector	Polarization
(MHz)	(dBμV)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)	Peak/AVG	H/V
GFSK - 2410 MHz TX mode							
4820.000	43.08	0.80	43.88	74.00	-30.12	Peak	V
4820.000	36.85	0.80	37.65	54.00	-16.35	AVG	V
7230.000	44.47	6.01	50.48	74.00	-23.52	Peak	V
7230.000	38.22	6.01	44.23	54.00	-9.77	AVG	V
9640.000	42.35	6.12	48.47	74.00	-25.53	Peak	V
9640.000	36.05	6.12	42.17	54.00	-11.83	AVG	V
4820.000	45.56	0.80	46.36	74.00	-27.64	Peak	H
4820.000	39.32	0.80	40.12	54.00	-13.88	AVG	H
7230.000	44.73	6.01	50.74	74.00	-23.26	Peak	H
7230.000	39.20	6.01	45.21	54.00	-8.79	AVG	H
9640.000	41.46	6.12	47.58	74.00	-26.42	Peak	H
9640.000	35.11	6.12	41.23	54.00	-12.77	AVG	H
GFSK - 2440 MHz TX mode							
4880.000	40.63	1.04	41.67	74.00	-32.33	Peak	V
4880.000	34.17	1.04	35.21	54.00	-18.79	AVG	V
7320.000	45.20	5.93	51.13	74.00	-22.87	Peak	V
7320.000	39.58	5.93	45.51	54.00	-8.49	AVG	V
9760.000	40.60	6.55	47.15	74.00	-26.85	Peak	V
9760.000	34.68	6.55	41.23	54.00	-12.77	AVG	V
4880.000	41.52	1.04	42.56	74.00	-31.44	Peak	H
4880.000	35.50	1.04	36.54	54.00	-17.46	AVG	H
7320.000	47.11	5.93	53.04	74.00	-20.96	Peak	H
7320.000	40.61	5.93	46.54	54.00	-7.46	AVG	H
9760.000	41.12	6.55	47.67	74.00	-26.33	Peak	H
9760.000	34.81	6.55	41.36	54.00	-12.64	AVG	H



Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector	Polarization
(MHz)	(dBμV)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)	Peak/AVG	H/V
GFSK - 2468 MHz TX mode							
4936.000	41.43	1.34	42.77	74.00	-31.23	Peak	V
4936.000	34.90	1.34	36.24	54.00	-17.76	AVG	V
7404.000	42.46	5.83	48.29	74.00	-25.71	Peak	V
7404.000	36.12	5.83	41.95	54.00	-12.05	AVG	V
9872.000	41.29	6.20	47.49	74.00	-26.51	Peak	V
9872.000	35.05	6.20	41.25	54.00	-12.75	AVG	V
4936.000	43.04	1.34	44.38	74.00	-29.62	Peak	H
4936.000	36.87	1.34	38.21	54.00	-15.79	AVG	H
7404.000	42.16	5.83	47.99	74.00	-26.01	Peak	H
7404.000	35.40	5.83	41.23	54.00	-12.77	AVG	H
9872.000	41.18	6.20	47.38	74.00	-26.62	Peak	H
9872.000	35.58	6.20	41.78	54.00	-12.22	AVG	H

Note:

1. All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
2. Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor
3. All the modulation modes have been tested, and the worst results are reflected in the report.



5.3.4 Band edge-Field strength of fundamental

Frequency	Ant. Polarization	Emission level	Limits	Detector	Result
(MHz)	H / V	dB μ V/m	dB μ V/m		
2410	H	88.45	114	PK	PASS
2410	H	87.08	94	AV	PASS
2410	V	81.90	114	PK	PASS
2410	V	80.38	94	AV	PASS

Frequency	Ant. Polarization	Emission level	Limits	Detector	Result
(MHz)	H / V	dB μ V/m	dB μ V/m		
2440	H	87.52	114	PK	PASS
2440	H	86.62	94	AV	PASS
2440	V	80.20	114	PK	PASS
2440	V	78.76	94	AV	PASS

Frequency	Ant. Polarization	Emission level	Limits	Detector	Result
(MHz)	H / V	dB μ V/m	dB μ V/m		
2468	H	87.24	114	PK	PASS
2468	H	86.01	94	AV	PASS
2468	V	79.15	114	PK	PASS
2468	V	77.90	94	AV	PASS



5.3.5 Band edge-radiated

Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector	Polarization
(MHz)	(dBμV)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)	Peak/AVG	H/V
GFSK – Low band-edge							
(MHz)	(dBμV)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)	Peak/AVG	H/V
2310.000	47.71	-8.08	39.63	74.00	-34.37	Peak	V
2310.000	37.44	-8.08	29.36	54.00	-24.64	AVG	V
2390.000	49.58	-7.71	41.87	74.00	-32.13	Peak	V
2390.000	39.07	-7.71	31.36	54.00	-22.64	AVG	V
2400.000	51.21	-7.66	43.55	74.00	-30.45	Peak	V
2400.000	40.13	-7.66	32.47	54.00	-21.53	AVG	V
2310.000	45.60	-8.08	37.52	74.00	-36.48	Peak	H
2310.000	37.12	-8.08	29.04	54.00	-24.96	AVG	H
2390.000	51.39	-7.71	43.68	74.00	-30.32	Peak	H
2390.000	41.83	-7.71	34.12	54.00	-19.88	AVG	H
2400.000	54.66	-7.66	47.00	74.00	-27.00	Peak	H
2400.000	43.68	-7.66	36.02	54.00	-17.98	AVG	H
GFSK – High band-edge							
2483.500	49.43	-7.24	42.19	74.00	-31.81	Peak	V
2483.500	38.35	-7.24	31.11	54.00	-22.89	AVG	V
2500.000	46.98	-7.17	39.81	74.00	-34.19	Peak	V
2500.000	38.03	-7.17	30.86	54.00	-23.14	AVG	V
2483.500	50.03	-7.24	42.79	74.00	-31.21	Peak	H
2483.500	40.77	-7.24	33.53	54.00	-20.47	AVG	H
2500.000	48.04	-7.17	40.87	74.00	-33.13	Peak	H
2500.000	38.89	-7.17	31.72	54.00	-22.28	AVG	H

5.4 20dB and 99% bandwidth

5.4.1 Limits

FCC §15.215(c)

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

5.4.2 Test method

Use the following spectrum analyzer settings:

For 20 dB bandwidth

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW $\geq 1\%$ of the 20 dB bandwidth

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold


The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth and 99% occupied bandwidth of the emission



5.4.3 Test result


Frequency (MHz)	20dB bandwidth (MHz)	99% bandwidth (MHz)
2410	1.969	2.0936
2440	1.934	2.1001
2468	1.958	2.0891

Test plots






2440MHz



2468MHz





Photographs of the Test Setup

See the APPENDIX – Test setup photos.



Photographs of the EUT

See the Appendix - EUT Photos.

----END OF REPORT----