

FCC PART 15C TEST REPORT FOR CERTIFICATION
On Behalf of

Jiangmen Dascom Computer Peripherals Co., Ltd.

Portable Receipt and Label Printer

Model Number: DP-541

Additional Model: DP-541a, DP-541b, DP-541c, FP-541

FCC ID: Z7ODP5410

Prepared for:	Jiangmen Dascom Computer Peripherals Co., Ltd.
	No 399, Jin Xing Road, Jiang Hai District, Jiangmen City,
	Guang Dong Province, China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
	Tel: 86-769-83081888-808



Report Number:	ESTE-R1712012
Date of Test:	November 22~December 01, 2017
Date of Report:	December 04, 2017

TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION	3
1. GENERAL INFORMATION.....	5
1.1. Description of Device (EUT)	5
2. SUMMARY OF TEST	6
2.1. Summary of test result.....	6
2.2. Test Facilities.....	7
2.3. Measurement uncertainty	8
2.4. Assistant equipment used for test	8
2.5. Block Diagram.....	8
2.6. Test mode	9
2.7. Channel List.....	9
2.8. Test Equipment.....	10
3. MAXIMUM PEAK OUTPUT POWER.....	12
3.1. Limit	12
3.2. Test Procedure	12
3.3. Test Result	12
3.4. Test Data.....	13
4. 20 DB BANDWIDTH	17
4.1. Limit	17
4.2. Test Procedure	17
4.3. Test Result	17
4.4. Test Data.....	18
5. CARRIER FREQUENCY SEPARATION.....	22
5.1. Limit	22
5.2. Test Procedure	22
5.3. Test Result	22
5.4. Test Data.....	23
6. NUMBER OF HOPPING CHANNEL	27
6.1. Limit	27
6.2. Test Procedure	27
6.3. Test Result	27
6.4. Test Data.....	28
7. DWELL TIME.....	30
7.1. Limit	30
7.2. Test Procedure	30
7.3. Test Result	30
7.4. Test Data.....	31
8. RADIATED EMISSIONS	37
8.1. Limit	37
8.2. Block Diagram of Test setup	38
8.3. Test Procedure	39
8.4. Test Result	39
8.5. Test Data.....	40

9.	BAND EDGE COMPLIANCE	56
9.1.	Limit	56
9.2.	Block Diagram of Test setup	56
9.3.	Test Procedure	56
9.4.	Test Result	56
9.5.	Test Data.....	57
10.	POWER LINE CONDUCTED EMISSIONS	73
10.1.	Limit	73
10.2.	Test Procedure	73
11.	ANTENNA REQUIREMENTS.....	78
11.1.	Limit	78
11.2.	Result.....	78
12.	TEST SETUP PHOTO.....	79
13.	PHOTO EUT	81

EST Technology Co., Ltd.

Applicant:	Jiangmen Dascom Computer Peripherals Co., Ltd.		
Address:	No 399, Jin Xing Road, Jiang Hai District, Jiangmen City, Guang Dong Province, China		
Manufacturer:	Jiangmen Dascom Computer Peripherals Co., Ltd.		
Address:	No 399, Jin Xing Road, Jiang Hai District, Jiangmen City, Guang Dong Province, China		
E.U.T:	Portable Receipt and Label Printer		
Model Number:	DP-541		
Additional Model:	DP-541a, DP-541b, DP-541c, FP-541 (They are identical except model name only)		
Power Supply:	DC 11.1V From Battery DC 19V From Adapter Input AC 100-240V, 50/60Hz		
Test Voltage:	DC 19V From Adapter Input AC 120V/60Hz and AC 240V/60Hz		
Trade Name:	Tally/DASCOM, DASCOM, PRINTEK	Serial No.:	-----
Date of Receipt:	November 22, 2017	Date of Test:	November 22~December 01, 2017
Test Specification:	FCC Rules and Regulations Part 15 Subpart C:2017 ANSI C63.10:2013		
Test Result:	The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC Rules and Regulations Part 15 Subpart C requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.		
		Date: December 04, 2017	
Prepared by:	Reviewed by:	Approved by:	
			
Amy / Assistant	Tony / Engineer	Iceman Hu / Manager	
Other Aspects: None.			
Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested			
This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.			

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Product Name	:	Portable Receipt and Label Printer	
FCC ID	:	Z7ODP5410	
Model Number	:	DP-541	
Operation frequency	:	2402MHz~2480MHz	
Number of channel	:	79	40
Antenna	:	Internal antenna, 0.5 dBi gain	
Modulation	:	Dual-mode Bluetooth 4.0 BT BDR: GFSK BT EDR: $\pi/4$ -DQPSK BT EDR: 8-DPSK	Dual-mode Bluetooth 4.0 BLE: GFSK
Sample Type	:	Prototype production	

2. SUMMARY OF TEST

2.1. Summary of test result

Description of Test Item	Standard	Results
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) DA 00-705	PASS
20dB Bandwidth	FCC Part 15: 15.247a1 DA 00-705	PASS
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) DA 00-705	PASS
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) DA 00-705	PASS
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) DA 00-705	PASS
Radiated Emissions	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10:2013 DA 00-705	PASS
Band Edge Compliance	FCC Part 15: 15.247(d) DA 00-705	PASS
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10:201 DA 00-705	PASS
Antenna requirement	FCC Part 15: 15.203	PASS

2.2. Test Facilities

EMC Lab	:	Certificated by CNAS, CHINA Registration No.: L5288 Date of registration: November 13, 2017 Certificated by A2LA, USA Registration No.: 4366.01 Date of registration: November 07, 2017 Certificated by FCC, USA Designation Number: CN1215 Registration No.: 722932 Date of registration: November 21, 2017 Certificated by Industry Canada Registration No.: 9405A Date of registration: December 03, 2015 Certificated by VCCI, Japan Registration No.: R-13663; C-14103 Date of registration: July 25, 2017 This Certificate is valid until: July 24, 2020 Certificated by TUV Rheinland, Germany Registration No.: UA 50195514 0001 Date of registration: February 07, 2015 Certificated by TUV/PS, Shenzhen Registration No.: SCN1017 Date of registration: January 27, 2011 Certificated by Intertek ETL SEMKO Registration No.: 2011-RTL-L2-64 Date of registration: April 28, 2011 Certificated by Nemko, Hong Kong Registration No.: 175193 Date of registration: May 4, 2011
Name of Firm	:	EST Technology Co., Ltd.
Site Location	:	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China

2.3. Measurement uncertainty

Test Item	Uncertainty
Uncertainty for Conduction emission test	$\pm 3.48\text{dB}$
Uncertainty for spurious emissions test (30MHz-1GHz)	$\pm 4.60\text{ dB(Polarize: H)}$
	$\pm 4.68\text{ dB(Polarize: V)}$
Uncertainty for spurious emissions test (1GHz to 18GHz)	$\pm 4.96\text{dB}$
Uncertainty for radio frequency	7×10^{-8}
Uncertainty for conducted RF Power	0.20dB
Uncertainty for Power density test	0.26dB

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.


2.4. Assistant equipment used for test

2.4.1. Adapter

M/N	:	GS90A19-P1M
Manufacturer	:	MEAN WELL ENTERPRISES CO., LTD
Input	:	AC 100-240V, 50/60Hz, 2.0A
Output	:	DC 19V, 4.74A, 90W MAX

2.5. Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 (or 1.5) meter high above ground. EUT was beset into Bluetooth test mode by software before test.



(EUT: Portable Receipt and Label Printer)

2.6. Test mode

The test software was used to control EUT work in Continuous TX mode, and select test channel, wireless mode

Mode	Channel	Frequency
GFSK	Low	2402MHz
	Middle	2441MHz
	High	2480MHz
8-DPSK	Low	2402MHz
	Middle	2441MHz
	High	2480MHz

2.7. Channel List

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2402	2	2403	3	2404	4	2405
5	2406	6	2407	7	2408	8	2409
9	2410	10	2411	11	2412	12	2413
13	2414	14	2415	15	2416	16	2417
17	2418	18	2419	19	2420	20	2421
21	2422	22	2423	23	2424	24	2425
25	2426	26	2427	27	2428	28	2429
29	2430	30	2431	31	2432	32	2433
33	2434	34	2435	35	2436	36	2437
37	2438	38	2439	39	2440	40	2441
41	2442	42	2443	43	2444	44	2445
45	2446	46	2447	47	2448	48	2449
49	2450	50	2451	51	2452	52	2453
53	2454	54	2455	55	2456	56	2457
57	2458	58	2459	59	2460	60	2461
61	2462	62	2463	63	2464	64	2465
65	2466	66	2467	67	2468	68	2469
69	2470	70	2471	71	2472	72	2473
73	2474	74	2475	75	2476	76	2477
77	2478	78	2479	79	2480	-	-

2.8. Test Equipment

2.8.1. For conducted emission test

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESHS30	832354	CEPREI	June 17,17	1 Year
Artificial Mains Network	Rohde & Schwarz	ENV216	101260	CEPREI	June 17,17	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	101100	CEPREI	June 17,17	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

2.8.2. For radiated emission test(9 kHz-30MHz)

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	101780	CEPREI	June 17,17	1 Year
Active Loop Antenna	SCHWARZB ECK	FMZB1519	1519-038	CEPREI	October 08,17	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

2.8.3. For radiated emissions test (30-1000MHz)

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	101780	CEPREI	June 17,17	1 Year
Bilog Antenna	Teseq	CBL 6111D	27090	CEPREI	June 08,17	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

2.8.4. For radiated emission test(above 1GHz)

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Horn Antenna	SCHWARZB ECK	BBHA 9120 D	BBHA912 0D1002	CEPREI	June 08,17	1 Year
Horn Antenna	SCHWARZB ECK	BBHA9170	BBHA917 0242	CEPREI	June 08,17	1Year
Signal Amplifier	SCHWARZB ECK	BBV9718	9718-212	CEPREI	March 12,17	1 Year
Spectrum Analyzer	Rohde &Schwarz	FSV	103173	CEPREI	June 17,17	1 Year
PSA Series Spertrum Analyzer	Agilent	E4447A	MY50180 031	CEPREI	June 16,17	1Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

2.8.5. For connect EUT antenna terminal test

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Spectrum Analyzer	Rohde & Schwarz	FSV	103173	CEPREI	June 17,17	1 Year
Spectrum Analyzer	Agilent	E4408B	MY44211 139	CEPREI	June 17,17	1 Year

3. MAXIMUM PEAK OUTPUT POWER

3.1. Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W



3.2. Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer. Connect EUT antenna terminal to the spectrum analyzer with a low loss SMA cable.


3.3. Test Result

EUT: Portable Receipt and Label Printer					
M/N: DP-541					
Test date: 2017.11.23		Test site: RF site		Tested by: Seven	
Mode	Freq (MHz)	Result (dBm)	Limit		Conclusion
			dBm	W	
GFSK	2402	3.584	30.00	1	Pass
	2441	5.509	30.00	1	Pass
	2480	6.368	30.00	1	Pass
8-DPSK	2402	1.654	21.00	0.125	Pass
	2441	3.830	21.00	0.125	Pass
	2480	5.141	21.00	0.125	Pass


3.4. Test Data




GFSK 2480 MHz




8-DPSK 2402 MHz



8-DPSK 2441 MHz



8-DPSK 2480 MHz



4. 20 DB BANDWIDTH

4.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.2. Test Procedure


The transmitter output (antenna port) was connected to the spectrum analyzer. Connect EUT antenna terminal to the spectrum analyzer with a low loss SMA cable. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3. Test Result


EUT: Portable Receipt and Label Printer				
M/N: DP-541				
Test date: 2017.11.23		Test site: RF site		Tested by: Seven
Mode	Freq (MHz)	20dB Bandwidth (MHz)	Limit (kHz)	Conclusion
GFSK	2402	0.931	/	PASS
	2441	0.860	/	PASS
	2480	0.862	/	PASS
8-DPSK	2402	1.219	/	PASS
	2441	1.232	/	PASS
	2480	1.230	/	PASS

4.4. Test Data


GFSK 2402MHz




GFSK 2441MHz




GFSK 2480MHz




8-DPSK 2402MHz



8-DPSK 2441MHz



8-DPSK 2480MHz



5. CARRIER FREQUENCY SEPARATION

5.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.


5.2. Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer. Connect EUT antenna terminal to the spectrum analyzer with a low loss SMA cable. The carrier frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW.


5.3. Test Result


EUT: Portable Receipt and Label Printer				
M/N: DP-541				
Test date: 2017.11.23			Test site: RF site	Tested by: Seven
Mode	Channel	Channel separation (MHz)	Limit	Conclusion
GFSK	Low CH	1.000	0.931 MHz	PASS
	Mid CH	1.000	0.860 MHz	PASS
	High CH	1.000	0.862 MHz	PASS
8-DPSK	Low CH	1.000	> 2/3 of the 20dB Bandwidth or 25[kHz](whichever is greater)	PASS
	Mid CH	1.000		PASS
	High CH	1.000		PASS

5.4. Test Data


GFSK
Low Channel

Mid Channel







8-DPSK Low Channel



Mid Channel





6. NUMBER OF HOPPING CHANNEL

6.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

6.2. Test Procedure




The transmitter output (antenna port) was connected to the spectrum analyzer. Connect EUT antenna terminal to the spectrum analyzer with a low loss SMA cable. The number of hopping channel was measured by spectrum analyzer with 300kHz RBW and 300kHz VBW.

6.3. Test Result




EUT: Portable Receipt and Label Printer			
M/N: DP-541			
Test date: 2017.11.23		Test site: RF site	Tested by: Seven
Mode	Number of hopping channel	Limit	Conclusion
GFSK	79	>15	PASS
8-DPSK	79	>15	PASS

6.4. Test Data

GFSK



8-DPSK



7. DWELL TIME

7.1. Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.



7.2. Test Procedure

1. The transmitter output (antenna port) was connected to the spectrum analyzer. Connect EUT antenna terminal to the spectrum analyzer with a low loss SMA cable.
2. Set the EUT to proper test mode with relative test software and hardware.
3. Spectrum analyzer setting: Centered Frequency = measured channel, RBW = 1MHz, VBW= 1MHz, Frequency Span = 0 Hz.
4. Set sweep time properly to capture the entire dwell time per hopping channel.
5. Set detector type to Peak and trace mode to Max Hold and make the measurement.
6. Repeat step 3-5 until all channels measured were complete.



7.3. Test Result

EUT: Portable Receipt and Label Printer						
M/N: DP-541						
Test date: 2017.11.23		Test site: RF site		Tested by: Seven		
Mode	Hopping number	Measure time (s)	Burst on time (ms)	Dwell time (ms)	Limit	Conclusion
GFSK DH1	50	5	0.43	135.88	<400ms	PASS
GFSK DH3	25	5	1.68	265.44	<400ms	PASS
GFSK DH5	17	5	2.93	314.80	<400ms	PASS
8-DPSK 3DH1	50	5	0.45	142.20	<400ms	PASS
8-DPSK 3DH3	25	5	1.70	268.60	<400ms	PASS
8-DPSK 3DH5	17	5	2.96	318.02	<400ms	PASS
Dwell time = Hopping number/measure time *0.4*79*burst on time.						



7.4. Test Data





GFSK DH3





GSFK DH5





8-DPSK 3DH1



8-DPSK 3DH3



8-DPSK 3DH5



8. RADIATED EMISSIONS

8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

15.209 Limit

Frequency (MHz)	Field Strength(μ V/m)	Distance(m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


Remark : (1) Emission level $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$

(2) The smaller limit shall apply at the cross point between two frequency bands.


(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

8.2. Block Diagram of Test setup


9kHz~30MHz



30~1000MHz



Above 1GHz



8.3. Test Procedure

EUT was placed on a turn table, which is 0.8 meter high above ground for 9kHz~1000MHz test, and which is 1.5 meter high above ground for above 1GHz test. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

The test frequency analyzer system was set to Peak Detect (300Hz RBW in 9kHz to 150kHz and 10kHz RBW in 150kHz to 30MHz) Function and Specified Bandwidth with Maximum Hold Mode.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 1MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz

PEAK detector, 1MHz/1MHz for PAEK measurement,

PEAK detector, 1MHz/10Hz for Average measurement

The frequency range from 30MHz to 10th harmonic (25GHz) are checked.

8.4. Test Result

Pass

- Note: 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.
- 2、 The frequency 2402MHz 、 2441MHz and 2480MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.

8.5. Test Data

9 kHz – 30 MHz

Pass

Note: The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

30 MHz – 1000 MHz


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 351

File: \\Emc-966-1\test data\2017\RFID\ASCOM-RF.EM6 (448)

Date: 2017-11-23



Site no : 1# 966 Chamber Data no. : 351
 Env. / Ins. : Temp:24.2';Humi:54%;Press:101.52kPa LINE Phase : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : TX Mode

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	209.450	8.82	1.54	14.66	25.02	43.50	18.48	QP
2	296.750	13.68	2.04	11.17	26.89	46.00	19.11	QP
3	395.690	15.92	2.34	10.63	28.89	46.00	17.11	QP
4	660.500	21.10	3.43	4.11	28.64	46.00	17.36	QP
5	709.970	21.30	3.53	4.71	29.54	46.00	16.46	QP
6	792.420	22.80	3.74	2.98	29.52	46.00	16.48	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 352

File: \\Emc-966-1\test data\2017\RFID\DA5COM-RF.EM6 (448)

Date: 2017-11-23



Site no : 1# 966 Chamber Data no. : 352
 Env. / Ins. : Temp:24.2';Humi:54%;Press:101.52kPa LINE Phase : VERTICAL
 Limit : FCC PART 15 B(3M)
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : TX Mode

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.000	18.10	0.31	14.55	32.96	40.00	7.04	QP
2	395.690	15.92	2.34	7.13	25.39	46.00	20.61	QP
3	577.080	19.64	3.13	4.85	27.62	46.00	18.38	QP
4	611.030	20.42	3.24	6.71	30.37	46.00	15.63	QP
5	660.500	21.10	3.43	4.26	28.79	46.00	17.21	QP
6	709.970	21.30	3.53	3.14	27.97	46.00	18.03	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

1000-18000MHz


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 339

File: \\Emc-966-1\test data\2017\RFID\IDASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 339
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.35	3.21	27.25	88.63	91.94	74.00	-17.94	Peak
2	4804.00	32.06	4.67	26.93	34.10	43.90	74.00	30.10	Peak
3	7206.00	36.56	5.99	25.80	27.52	44.27	74.00	29.73	Peak
4	8514.00	37.22	6.90	25.31	24.36	43.17	74.00	30.83	Peak
5	10775.00	39.63	8.85	24.91	18.26	41.83	74.00	32.17	Peak
6	13274.00	40.76	9.36	24.51	17.38	42.99	74.00	31.01	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 340

File: \\Emc-966-1\\test data\\2017\\RF\\D\\DASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 340
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
Engineer : Seven
EUT : Portable Receipt and Label Printer
Power : DC 19V From Adapter Input AC 120V/60Hz
M/N : DP-541
Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.35	3.21	27.25	93.16	96.47	74.00	-22.47	Peak
2	4804.00	32.06	4.67	26.93	37.27	47.07	74.00	26.93	Peak
3	7206.00	36.56	5.99	25.80	28.65	45.40	74.00	28.60	Peak
4	8650.00	37.41	6.90	25.29	25.86	44.88	74.00	29.12	Peak
5	10180.00	39.17	9.62	25.02	21.60	45.37	74.00	28.63	Peak
6	11404.00	40.06	8.29	24.80	20.80	44.35	74.00	29.65	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 341

File: \\Emc-966-1\\test data\\2017\\RF\\D\\DASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 341
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2441MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.00	27.48	3.26	27.24	86.46	89.96	74.00	-15.96	Peak
2	4882.00	32.18	4.73	26.92	35.64	45.63	74.00	28.37	Peak
3	7323.00	36.82	6.10	25.74	28.68	45.86	74.00	28.14	Peak
4	10146.00	39.16	9.48	25.03	21.71	45.32	74.00	28.68	Peak
5	10894.00	39.78	8.65	24.89	22.93	46.47	74.00	27.53	Peak
6	14549.00	41.11	10.24	24.32	16.97	44.00	74.00	30.00	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 342

File: \\Emc-966-1\\test data\\2017\\RF\\D\\DASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 342
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2441MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.00	27.48	3.26	27.24	88.38	91.88	74.00	-17.88	Peak
2	4882.00	32.18	4.73	26.92	37.03	47.02	74.00	26.98	Peak
3	7323.00	36.82	6.10	25.74	29.01	46.19	74.00	27.81	Peak
4	8650.00	37.41	6.90	25.29	23.53	42.55	74.00	31.45	Peak
5	11115.00	39.95	8.49	24.85	18.71	42.30	74.00	31.70	Peak
6	14090.00	41.61	10.14	24.39	17.96	45.32	74.00	28.68	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 343

File: \\Emc-966-1\test data\2017\RF\ID\ASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 343
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.56	3.29	27.24	92.20	95.81	74.00	-21.81	Peak
2	4960.00	32.34	4.80	26.90	36.45	46.69	74.00	27.31	Peak
3	7440.00	37.09	6.13	25.68	27.91	45.45	74.00	28.55	Peak
4	10146.00	39.16	9.48	25.03	19.83	43.44	74.00	30.56	Peak
5	11404.00	40.06	8.29	24.80	19.72	43.27	74.00	30.73	Peak
6	13376.00	41.01	9.50	24.49	18.78	44.80	74.00	29.20	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 344

File: \\Emc-966-1\test data\2017\RF\ID\ASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 344
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2480MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.56	3.29	27.24	86.02	89.63	74.00	-15.63	Peak
2	4960.00	32.34	4.80	26.90	34.55	44.79	74.00	29.21	Peak
3	7440.00	37.09	6.13	25.68	25.31	42.85	74.00	31.15	Peak
4	9160.00	38.18	7.02	25.20	24.04	44.04	74.00	29.96	Peak
5	11030.00	39.91	8.55	24.87	20.85	44.44	74.00	29.56	Peak
6	14515.00	41.17	10.20	24.32	18.71	45.76	74.00	28.24	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Data: 345

File: \\Emc-966-1\test data\2017\RF\ID\ASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 345
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : 8-DPSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.35	3.21	27.25	89.53	92.84	74.00	-18.84	Peak
2	4804.00	32.06	4.67	26.93	35.13	44.93	74.00	29.07	Peak
3	7206.00	36.56	5.99	25.80	29.41	46.16	74.00	27.84	Peak
4	8735.00	37.53	6.90	25.27	27.39	46.55	74.00	27.45	Peak
5	11166.00	39.97	8.45	24.85	20.10	43.67	74.00	30.33	Peak
6	14515.00	41.17	10.20	24.32	18.36	45.41	74.00	28.59	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 346

File: \\Emc-966-1\\test data\\2017\\RF\\D\\DASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 346
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
Engineer : Seven
EUT : Portable Receipt and Label Printer
Power : DC 19V From Adapter Input AC 120V/60Hz
M/N : DP-541
Test Mode : 8-DPSK TX 2402MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.35	3.21	27.25	85.31	88.62	74.00	-14.62	Peak
2	4804.00	32.06	4.67	26.93	34.60	44.40	74.00	29.60	Peak
3	7206.00	36.56	5.99	25.80	27.09	43.84	74.00	30.16	Peak
4	9160.00	38.18	7.02	25.20	24.87	44.87	74.00	29.13	Peak
5	10316.00	39.23	10.20	24.99	21.03	45.47	74.00	28.53	Peak
6	11642.00	39.91	8.25	24.76	18.33	41.73	74.00	32.27	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

Data: 347

File: \\Emc-966-1\test data\2017\RF\ID\ASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 347
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : 8-DPSK TX 2441MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.00	27.48	3.26	27.24	88.72	92.22	74.00	-18.22	Peak
2	4882.00	32.18	4.73	26.92	37.61	47.60	74.00	26.40	Peak
3	7323.00	36.82	6.10	25.74	28.52	45.70	74.00	28.30	Peak
4	8684.00	37.46	6.90	25.28	25.61	44.69	74.00	29.31	Peak
5	11200.00	39.98	8.43	24.84	20.30	43.87	74.00	30.13	Peak
6	14345.00	41.36	10.18	24.35	16.46	43.65	74.00	30.35	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Data: 348

File: \\Emc-966-1\test data\2017\RF\ID\ASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 348
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : 8-DPSK TX 2441MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.00	27.48	3.26	27.24	85.55	89.05	74.00	-15.05	Peak
2	4882.00	32.18	4.73	26.92	35.16	45.15	74.00	28.85	Peak
3	7323.00	36.82	6.10	25.74	27.97	45.15	74.00	28.85	Peak
4	9160.00	38.18	7.02	25.20	23.73	43.73	74.00	30.27	Peak
5	12084.00	39.38	8.30	24.69	20.18	43.17	74.00	30.83	Peak
6	13410.00	41.09	9.55	24.49	19.18	45.33	74.00	28.67	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 349

File: \\Emc-966-1\test data\2017\RF\ID\ASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 349
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : 8-DPSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.56	3.29	27.24	84.96	88.57	74.00	-14.57	Peak
2	4960.00	32.34	4.80	26.90	33.18	43.42	74.00	30.58	Peak
3	7440.00	37.09	6.13	25.68	26.81	44.35	74.00	29.65	Peak
4	10146.00	39.16	9.48	25.03	22.42	46.03	74.00	27.97	Peak
5	11166.00	39.97	8.45	24.85	22.76	46.33	74.00	27.67	Peak
6	14090.00	41.61	10.14	24.39	17.64	45.00	74.00	29.00	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 350

File: \\Emc-966-1\\test data\\2017\\RF\\D\\DASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 350
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : 8-DPSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.56	3.29	27.24	88.52	92.13	74.00	-18.13	Peak
2	4960.00	32.34	4.80	26.90	33.59	43.83	74.00	30.17	Peak
3	7440.00	37.09	6.13	25.68	28.83	46.37	74.00	27.63	Peak
4	8684.00	37.46	6.90	25.28	27.76	46.84	74.00	27.16	Peak
5	10996.00	39.90	8.57	24.88	22.58	46.17	74.00	27.83	Peak
6	13495.00	41.30	9.66	24.47	17.21	43.70	74.00	30.30	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

18000MHz – 25000MHz

Pass


Note: The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

9. BAND EDGE COMPLIANCE

9.1. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

9.2. Block Diagram of Test setup



9.3. Test Procedure

EUT was placed on a turn table, which is 1.5 m high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of emissions

Peak : RBW = 1MHz, VBW = 1MHz, Detector=PEAK detector, Sweep time = auto.

AV : RBW = 1MHz, VBW = 10Hz, Detector=PEAK detector, Sweep time = auto.

9.4. Test Result

Pass (The testing data was attached in the next pages.)


Note: 1、For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

- 2、The frequency 2402MHz and 2480MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.

9.5. Test Data

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



Site no. : 1# 966 Chamber Data no. : 323
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6'; Humi:56%; Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2402MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.35	3.21	27.25	30.59	33.90	74.00	40.10	Peak
2	2400.00	27.35	3.21	27.25	41.50	44.81	74.00	29.19	Peak
3	2402.30	27.35	3.21	27.25	90.90	94.21	74.00	-20.21	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 324

File: \\Emc-966-1\test data\2017\RFID\DA5COM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 324
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6'; Humi:56%; Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2402MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.35	3.21	27.25	29.14	32.45	74.00	41.55	Peak
2	2400.00	27.35	3.21	27.25	34.09	37.40	74.00	36.60	Peak
3	2402.30	27.35	3.21	27.25	84.57	87.88	74.00	-13.88	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 325

File: \\Emc-966-1\test data\2017\RFID\DA5COM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 325
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6'; Humi:56%; Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2480MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.88	27.56	3.29	27.24	86.16	89.77	74.00	-15.77	Peak
2	2483.50	27.56	3.29	27.24	29.91	33.52	74.00	40.48	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 326

File: \\Emc-966-1\test data\2017\RFID\DA5COM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 326
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6'; Humi:56%; Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2480MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.88	27.56	3.29	27.24	91.15	94.76	74.00	-20.76	Peak
2	2483.50	27.56	3.29	27.24	27.88	31.49	74.00	42.51	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 327

File: \\Emc-966-1\test data\2017\RFID\DA5COM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 327
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6'; Humi:56%; Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : 8-DPSK TX 2402MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.35	3.21	27.25	29.45	32.76	74.00	41.24	Peak
2	2400.00	27.35	3.21	27.25	37.94	41.25	74.00	32.75	Peak
3	2401.75	27.35	3.21	27.25	85.02	88.33	74.00	-14.33	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 328

File: \\Emc-966-1\test data\2017\RFID\DA5COM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 328
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6'; Humi:56%; Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : 8-DPSK TX 2402MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.35	3.21	27.25	32.12	35.43	74.00	38.57	Peak
2	2400.00	27.35	3.21	27.25	41.44	44.75	74.00	29.25	Peak
3	2402.30	27.35	3.21	27.25	89.13	92.44	74.00	-18.44	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 329

File: \\Emc-966-1\test data\2017\RFID\DA5COM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 329
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6'; Humi:56%; Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : 8-DPSK TX 2480MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.88	27.56	3.29	27.24	89.78	93.39	74.00	-19.39	Peak
2	2483.50	27.56	3.29	27.24	28.04	31.65	74.00	42.35	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 330

File: \\Emc-966-1\test data\2017\RFID\DA5COM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 330
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6'; Humi:56%; Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : 8-DPSK TX 2480MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.88	27.56	3.29	27.24	83.60	87.21	74.00	-13.21	Peak
2	2483.50	27.56	3.29	27.24	28.46	32.07	74.00	41.93	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 331

File: \\Emc-966-1\test data\2017\RFID\ASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 331
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6'; Humi:56%; Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2402MHz(Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.35	3.21	27.25	28.86	32.17	74.00	41.83	Peak
2	2400.00	27.35	3.21	27.25	32.17	35.48	74.00	38.52	Peak
3	2403.95	27.39	3.23	27.25	86.91	90.28	74.00	-16.28	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 332

File: \\Emc-966-1\test data\2017\RFID\DA5COM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 332
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6'; Humi:56%; Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2402MHz(Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.35	3.21	27.25	31.57	34.88	74.00	39.12	Peak
2	2400.00	27.35	3.21	27.25	34.08	37.39	74.00	36.61	Peak
3	2403.18	27.39	3.23	27.25	92.47	95.84	74.00	-21.84	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 333

File: \\Emc-966-1\test data\2017\RFID\DA5COM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 333
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2480MHz(Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2476.20	27.56	3.29	27.24	93.74	97.35	74.00	-23.35	Peak
2	2483.50	27.56	3.29	27.24	29.47	33.08	74.00	40.92	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 334

File: \\Emc-966-1\test data\2017\RFID\DA5COM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 334
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6'; Humi:56%; Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2480MHz(Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.05	27.56	3.29	27.24	86.40	90.01	74.00	-16.01	Peak
2	2483.50	27.56	3.29	27.24	27.77	31.38	74.00	42.62	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 335

File: \\Emc-966-1\test data\2017\RFID\ASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 335
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6'; Humi:56%; Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : 8-DPSK TX 2402MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.35	3.21	27.25	29.06	32.37	74.00	41.63	Peak
2	2400.00	27.35	3.21	27.25	32.80	36.11	74.00	37.89	Peak
3	2403.95	27.39	3.23	27.25	86.30	89.67	74.00	-15.67	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 336

File: \\Emc-966-1\test data\2017\RFID\ASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 336
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6'; Humi:56%; Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : 8-DPSK TX 2402MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.35	3.21	27.25	30.09	33.40	74.00	40.60	Peak
2	2400.00	27.35	3.21	27.25	35.02	38.33	74.00	35.67	Peak
3	2402.85	27.39	3.23	27.25	92.16	95.53	74.00	-21.53	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 337

File: \\Emc-966-1\test data\2017\RFID\DA5COM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 337
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6'; Humi:56%; Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : 8-DPSK TX 2480MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.20	27.56	3.29	27.24	93.54	97.15	74.00	-23.15	Peak
2	2483.50	27.56	3.29	27.24	28.37	31.98	74.00	42.02	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 338

File: \\Emc-966-1\test data\2017\RFID\DA5COM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 338
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6'; Humi:56%; Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : 8-DPSK TX 2480MHz (Hopping On)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.88	27.56	3.29	27.24	86.15	89.76	74.00	-15.76	Peak
2	2483.50	27.56	3.29	27.24	27.92	31.53	74.00	42.47	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

10. POWER LINE CONDUCTED EMISSIONS

10.1. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

10.2. Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT was charged from PC's USB port which connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#).. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10:2013 on Conducted Emission Test.

The bandwidth of test receiver (R & S ESHS30) is set at 10kHz.

The frequency range from 150kHz to 30MHz is checked.


10.3. Test Result

PASS. (All emissions not reported below are too low against the prescribed limits.)

10.4. Test data

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV)	Limits (dBUV)	Margin (dB)	Remark
1	0.15	9.61	9.81	6.66	26.08	56.00	29.92	Average
2	0.15	9.61	9.81	12.66	32.08	66.00	33.92	QP
3	1.01	9.64	9.83	7.72	27.19	46.00	18.81	Average
4	1.01	9.64	9.83	10.72	30.19	56.00	25.81	QP
5	25.86	9.68	10.03	20.32	40.03	50.00	9.97	Average
6	25.86	9.68	10.03	25.32	45.03	60.00	14.97	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 134

File: \\Emc-ce-2\Test Data\2017\RFID\IDASCOM.EM6 (146)

Date: 2017-11-30



Trace: 133

Site no. : 2# Conduction Shield Room Data no. : 134
 Dis. / Ant. : Temp:25.8'C Humi:54.8% Press:101.50kPa Ant. pol. : NEUTRAL
 Limit : FCC PART 15B QP
 Env. / Ins. : Temp:25.8'C Humi:54.8% Press:101.50kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 240V/60Hz
 M/N : DP-541
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.15	9.46	9.81	7.95	27.22	55.91	28.69	Average
2	0.15	9.46	9.81	12.95	32.22	65.91	33.69	QP
3	0.95	9.61	9.82	4.93	24.36	46.00	21.64	Average
4	0.95	9.61	9.82	8.93	28.36	56.00	27.64	QP
5	25.86	9.81	10.03	19.39	39.23	50.00	10.77	Average
6	25.86	9.81	10.03	26.39	46.23	60.00	13.77	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 136

File: \\Emc-ce-2\Test Data\2017\RF\ID\ASCOM.EM6 (146)

Date: 2017-11-30



Trace: 135

Site no. : 2# Conduction Shield Room Data no. : 136
 Dis. / Ant. : Temp:25.8'C Humi:54.8% Press:101.50kPa Ant. pol. : NEUTRAL
 Limit : FCC PART 15B QP
 Env. / Ins. : Temp:25.8'C Humi:54.8% Press:101.50kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.15	9.46	9.81	2.64	21.91	55.96	34.05	Average
2	0.15	9.46	9.81	11.64	30.91	65.96	35.05	QP
3	0.96	9.61	9.82	1.39	20.82	46.00	25.18	Average
4	0.96	9.61	9.82	2.39	21.82	56.00	34.18	QP
5	26.00	9.81	10.04	12.04	31.89	50.00	18.11	Average
6	26.00	9.81	10.04	20.04	39.89	60.00	20.11	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 138

File: \\Emc-ce-2\Test Data\2017\RF\ID\ASCOM.EM6 (146)

Date: 2017-11-30



Trace: 137

Site no. : 2# Conduction Shield Room Data no. : 138
 Dis. / Ant. : Temp:25.8'C Humi:54.8% Press:101.50kPa Ant. pol. : LINE
 Limit : FCC PART 15B QP
 Env. / Ins. : Temp:25.8'C Humi:54.8% Press:101.50kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.15	9.61	9.81	3.96	23.38	56.00	32.62	Average
2	0.15	9.61	9.81	13.96	33.38	66.00	32.62	QP
3	0.93	9.63	9.82	0.41	19.86	46.00	26.14	Average
4	0.93	9.63	9.82	3.41	22.86	56.00	33.14	QP
5	25.86	9.68	10.03	12.34	32.05	50.00	17.95	Average
6	25.86	9.68	10.03	21.34	41.05	60.00	18.95	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.

11. ANTENNA REQUIREMENTS

11.1. Limit


For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2. Result


The antennas used for this product are Internal antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 0.5 dBi.

12. TEST SETUP PHOTO

Conducted Test



Radiated Test (30-1000 MHz)



Radiated Test (Above 1GHz)




13. PHOTO EUT

External Photos

M/N: DP-541



External Photos
M/N: DP-541



External Photos
M/N: DP-541



External Photos
M/N: DP-541



External Photos Adapter



Internal Photos
M/N: DP-541





Internal Photos
M/N: DP-541





Internal Photos
M/N: DP-541



Internal Photos
M/N: DP-541





Internal Photos
M/N: DP-541



Bluetooth
Antenna

Internal Photos
M/N: DP-541



Internal Photos
M/N: DP-541

