

**FCC PART 15 SUBPART B & C
TEST REPORT**

for

**LIFE SHIELD 4 BUTTON KEY FOB
Model: SKF2**

Prepared for

LINEAR, LLC.
1950 CAMINO VIDA ROBLE, SUITE 150
CARLSBAD, CA 92008

Prepared by: _____

MATT HARRISON

Approved by: _____

JEFF KLINGER

COMPATIBLE ELECTRONICS INC.
20621 PASCAL WAY
LAKE FOREST, CALIFORNIA 92630
(949) 587-0400

DATE: MAY 14, 2014

	REPORT BODY	APPENDICES					TOTAL
		A	B	C	D	E	
PAGES	18	2	2	2	12	18	54

This report shall not be reproduced except in full, without the written approval of Compatible Electronics.



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

TABLE OF CONTENTS

Section / Title	PAGE
GENERAL REPORT SUMMARY	4
SUMMARY OF TEST RESULTS	5
1. PURPOSE	6
2. ADMINISTRATIVE DATA	7
2.1 Location of Testing	7
2.2 Traceability Statement	7
2.3 Cognizant Personnel	7
2.4 Date Test Sample was Received	7
2.5 Disposition of the Test Sample	7
2.6 Abbreviations and Acronyms	7
3. APPLICABLE DOCUMENTS	8
4. DESCRIPTION OF TEST CONFIGURATION	9
4.1 Description of Test Configuration	9
4.1.1 Photograph Test Configuration	9
4.1.2 Cable Construction and Termination	10
5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT	11
5.1 EUT and Accessory List	11
5.2 EMI Test Equipment	12
6. TEST SITE DESCRIPTION	13
6.1 Test Facility Description	13
6.2 EUT Mounting, Bonding and Grounding	13
6.3 Facility Environmental Characteristics	13
7. CHARACTERISTICS OF THE TRANSMITTER	14
7.1 Channel Number and Frequencies	14
7.2 Antenna	14
8. TEST PROCEDURES	15
8.1 RF Emissions	15
8.1.1 Conducted Emissions Test	15
8.1.2 Radiated Emissions (Spurious and Harmonics) Test	16
8.1.3 Fundamental Field Strength	17
8.1.4 Occupied Bandwidth	17
8.1.5 Transmit Time Out	17
8.1.6 Duty Cycle	17
9. TEST PROCEDURE DEVIATIONS	18
10. CONCLUSIONS	18



LIST OF APPENDICES

APPENDIX	TITLE
A	Laboratory Accreditations and Recognitions
B	Modifications to the EUT
C	Additional Models Covered Under This Report
D	Diagrams, Charts, and Photos • Test Setup Diagrams • Antenna and Amplifier Factors • Radiated Emissions Photos
E	Radiated Emissions Data Sheets

LIST OF FIGURES

FIGURE	TITLE
1	Plot Map And Layout of Test Site Below 1GHz
2	Plot Map And Layout of Test Site Above 1GHz



GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Compatible Electronics Inc., which is an independent testing and consulting firm. The test report is based on testing performed by Compatible Electronics personnel according to the measurement procedures described in the test specifications given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced in any form unless done so in full with the written permission of Compatible Electronics.

This report must not be used to claim product endorsement by NVLAP, NIST, or any other agency of the U.S. Government or other governments.

Device Tested: Life Shield 4 Button Key Fob
Model: SKF2
S/N: N/A

Product Description: The Life Shield Key Fob is a 4 button key fob for arming and disarming a home security system.

Modifications: The EUT was not modified during testing.

Manufacturer: Linear, LLC.
1950 Camino Vida Roble, Suite 150
Carlsbad, CA 92008

Test Date: May 1st, 2nd, and 14th, 2014

Test Specifications: EMI requirements
CFR Title 47, Part 15 Subpart B Sections 15.109
CFR Title 47, Part 15 Subpart C Sections 15.205, 15.209 and 15.231

Test Procedure: ANSI C63.4
ANSI C63.10



SUMMARY OF TEST RESULTS

TEST	DESCRIPTION	RESULTS
1	Conducted RF Emissions, 150 kHz - 30 MHz.	The EUT is battery powered; therefore this test was not performed.
2	Radiated RF Emissions & Harmonics, 9 kHz – 4 GHz.	Complies with the limits of CFR Title 47 Part 15 Subpart B Section 15.109 and Part 15 Subpart C Section 15.205, 15.209, and 15.231.

SIX HIGHEST RADIATED EMISSIONS READINGS

	Reading Type (PK / QP / AV)	Polarization (Vert / Horz)	Frequency (MHz)	Level (dBµV/m)	Limit (dBµV/m)	Delta (dB)	Test Distance
1	AV	V	2415.00	52.84	57.26	-4.42	3-Meters
2	AV	H	345.00	72.31	77.26	-4.95	3-Meters
3	AV	H	2070.00	47.68	57.26	-9.58	3-Meters
4	AV	H	2415.00	47.54	57.26	-9.72	3-Meters
5	AV	V	2070.00	45.75	57.26	-11.51	3-Meters
6	AV	V	3105.00	41.08	57.26	-13.54	3-Meters



1. PURPOSE

This document is a qualification test report based on the Electromagnetic Interference (EMI) tests performed on the Life Shield 4 Button Key Fob Model: SKF2. The EMI measurements were performed according to the measurement procedure described in ANSI C63.4 and ANSI C63.10. The tests were performed in order to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT (equipment under test) hereafter, are within the specification limits defined by the Code of Federal Regulations Title 47, Part 15 Subpart B sections 15.109 and Part 15 Subpart C sections 15.205, 15.209 and 15.231.



2. ADMINISTRATIVE DATA

2.1 Location of Testing

The tests described herein were performed at the test facility of Compatible Electronics, 20621 Pascal Way Lake Forest, California 92630.

2.2 Traceability Statement

The calibration certificates of all test equipment used during the test are on file at the location of the test. The calibration is traceable to the National Institute of Standards and Technology (NIST).

2.3 Cognizant Personnel

Linear, LLC.

Josh Hansen Regulatory Engineer

Compatible Electronics, Inc.

Matt Harrison Test Technician

Jeff Klinger Director of Engineering

2.4 Date Test Sample was Received

The test sample was received on May ^{1st}, 2014.

2.5 Disposition of the Test Sample

The test sample remains at Compatible Electronics, Inc. as of the date of this test report.

2.6 Abbreviations and Acronyms

The following abbreviations and acronyms may be used in this document.

RF	Radio Frequency
EMI	Electromagnetic Interference
EUT	Equipment Under Test
P/N	Part Number
S/N	Serial Number
HP	Hewlett Packard
ITE	Information Technology Equipment
CML	Corrected Meter Limit
LISN	Line Impedance Stabilization Network
NVLAP	National Voluntary Laboratory Accreditation Program
CFR	Code of Federal Regulations
PCB	Printed Circuit Board
TX	Transmit
RX	Receive



3. APPLICABLE DOCUMENTS

The following documents are referenced or used in the preparation of this Test Report.

SPEC	TITLE
CFR Title 47, Part 15	FCC Rules – Radio frequency devices (including digital devices)
ANSI C63.4 2009	Methods of measurement of radio-noise emissions from low-voltage electrical and electronic equipment in the range of 9 kHz to 40 GHz.
ANSI C63.10: 2009	American National Standard for Testing Unlicensed Wireless Devices



4. DESCRIPTION OF TEST CONFIGURATION

4.1 Description of Test Configuration

The Life Shield 4 Button Key Fob Model: SKF2 (EUT) was setup in a tabletop configuration. The EUT was powered by 1-CR2450 battery. The EUT was continuously transmitting a control signal during transmitter tests and continuously receiving during receiver tests. The EUT was checked in the X, Y, and Z axis, X axis was found to be worst case.

The CR2450 battery was replaced with a new CR2450 battery; the transmitting signal amplitude and frequency did not vary.

It was determined that the emissions were at their highest level when the EUT was transmitting in the configuration described above for Radiated Emissions. The final radiated data was taken in the above configuration. Please see Appendix E for the test data.

4.1.1 Photograph Test Configuration



4.1.2 Cable Construction and Termination

Cable 1

There were no interconnecting cables.



5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT**5.1 EUT and Accessory List**

#	EQUIPMENT TYPE	MANU-FACTURER	MODEL	SERIAL NUMBER	FCC ID
1	Life Shield 4 Button Key Fob (EUT)	LINEAR, LLC.	SKF2	N/A	EF400119
2	BATTERY	PANASONIC	CR2450	N/A	N/A



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

5.2 EMI Test Equipment

EQUIPMENT TYPE	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. DUE DATE
Computer	Compatible Electronics	NONE	NONE	N/A	N/A
EMI Receiver	Rohde & Schwarz	ESIB40	100219	9/19/2013	9/19/2014
Antenna, Loop	Com Power	AL-130	121049	12/6/2013	12/6/2015
Antenna, CombiLog	Com Power	AC-220	25857	5/25/2013	5/25/2014
Antenna, Horn 1-18GHz	Com Power	AH-118	071250	7/3/2012	7/3/2014
Pre-Amp, 1-18GHz	Com Power	PAM-118A	551034	2/6/2014	2/6/2015
Pre-Amp, 1-18GHz	Com Power	PAM-118	443011	4/16/2014	4/16/2015
Notch Filter	Microwave Circuits	N0309153	3709-01 DC0415	5/9/2013	5/9/2014
Mast, Antenna Positioner	Sunol Science Corporation	TWR 95-4	081309-3	N/A	N/A
Antenna Mast	Sunol Science Corporation	TWR 95-4	081309-3	N/A	N/A
Turntable	Sunol Science Corporation	FM2011VS	N/A	N/A	N/A
Mast and Turntable Controller	Sunol Science Corporation	SC104V	020808-1	N/A	N/A



6. TEST SITE DESCRIPTION**6.1 Test Facility Description**

Please refer to section 2.1 and the figures in Appendix D of this report for test location.

6.2 EUT Mounting, Bonding and Grounding

The EUT was mounted on a 1.0 by 1.5 by 0.8 meter high non-conductive table, which was placed on the ground plane.

The EUT was not grounded.

6.3 Facility Environmental Characteristics

When applicable refer to the data sheets in Appendix E for the relative humidity, air temperature, and barometric pressure.



7. CHARACTERISTICS OF THE TRANSMITTER

7.1 Channel Number and Frequencies

There is 1 operating channel.

1 == 345 MHz

7.2 Antenna

The antenna is made up of an integrated PCB antenna which is located on the PCB.



8. TEST PROCEDURES

The following sections describe the test methods and the specifications for the tests. Test results are also included in this section.

8.1 RF Emissions

8.1.1 Conducted Emissions Test

(This test was not performed)

The EMI receiver was used as a measuring meter. A quasi-peak and/or average reading was taken only where indicated in the data sheets. The LISN output was measured using the EMI receiver. The output of the second LISN was terminated by a 50-ohm termination. The effective measurement bandwidth used for this test was 9 kHz.

Please see section 6.2 of this report for mounting, bonding, and grounding of the EUT. The EUT received its power through the LISN, which was bonded to the ground plane. The EUT was set up with the minimum distances from any conductive surfaces as specified in ANSI 63.4. The excess power cord was wrapped in a figure eight pattern to form a bundle not exceeding 0.4 meters in length.

The conducted emissions from the EUT were maximized for operating mode as well as cable placement. The final data was collected under program control by the computer software. The final qualification data is located in Appendix E.

Test Results:

The EUT is battery powered; therefore this test was not performed.



8.1.2 Radiated Emissions (Spurious and Harmonics) Test

The EMI receiver was used as a measuring meter. The receiver was used in the peak detect mode with the "Max Hold" feature activated. In this mode, the receiver records the highest measured reading over all the sweeps. Amplifiers were used to increase the sensitivity of the instrument. There was one Microwave Preamplifier used for frequencies above 1 GHz.

For spurious emissions the quasi-peak detector was used for frequencies below 1GHz and the average detector was used for frequencies above 1 GHz.

For the Fundamental and Harmonic emissions a duty cycle correction factor was used.

The measurement bandwidths and transducers used for the radiated emissions test were:

FREQUENCY RANGE (MHz)	TRANSDUCER	EFFECTIVE MEASUREMENT BANDWIDTH
.009 to .150	Active Loop Antenna	200 Hz
.150 to 30	Active Loop Antenna	9 kHz
30 to 1000	Combilog Antenna	100 kHz
1000 to 10000	Horn Antenna	1 MHz

The TDK FAC-3 shielded test chamber of Compatible Electronics, Inc. was used for radiated emissions testing. This test site is in full compliance with ANSI C63.4, EN 50147-2, and CISPR 22. Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The turntable supporting the EUT is remote controlled using a motor. The turntable permits EUT rotation of 360 degrees in order to maximize emissions. Also, the antenna mast allows height variation of the antenna from 1 meter to 4 meters. Data was collected in the worst case (highest emission) configuration of the EUT. At each reading, the EUT was rotated 360 degrees and the antenna height was varied from 1 to 4 meters in both vertical and horizontal polarizations (for E field radiated field strength).

Test Results:

The EUT complies with the limits of CFR Title 47 Part 15 Subpart B sections 15.109 and CFR Title 47 Part 15 Subpart C sections 15.205, 15.209 and 15.231.



8.1.3 Fundamental Field Strength

The Peak Transmit Radiated Field Strength was measured at a 3-meter test distance using the EMI Receiver to obtain the final test data. The final qualification data sheets are located in Appendix E.

Test Results:

The EUT complies with Part 15 Subpart C, Section 15.231.

8.1.4 Occupied Bandwidth

The Occupied Bandwidth measurement was made using the EMI Receiver to obtain the final test data. The final qualification data sheets are located in Appendix E.

Test Results:

The EUT complies with Part 15 Subpart C, Section 15.231.

8.1.5 Transmit Time Out

The Transmit Time Out measurement was made using the EMI Receiver to obtain the final test data. The final qualification data sheets are located in Appendix E.

Test Results:

The EUT complies with Part 15 Subpart C, Section 15.231.

8.1.6 Duty Cycle

Duty Cycle Correction Factor = -15.66dB

$$\delta(\text{dB}) = 20 \log \left[\sum (nt_1 + mt_2 + \dots + \xi t_x) / T \right]$$

where

n is the number of pulses of duration t_1

m is the number of pulses of duration t_2

ξ is the number of pulses of duration t_x

T is the period of the pulse train or 100 ms if the pulse train length is greater than 100 ms

Pulse Type 1: $150.301\mu\text{s} * 68 = 10.22 \text{ mS}$; Pulse Type 2: $284.369\mu\text{s} * 22 = 6.256\text{mS}$

$10.22\text{ms} + 6.256\text{mS} = 16.476 \text{ mS} / 100\text{ms} = 0.16476$

$20 \log (0.16476) = -15.66 \text{ dB}$



9. TEST PROCEDURE DEVIATIONS

The test procedures were not deviated from throughout all tests.

10. CONCLUSIONS

The Life Shield 4 Button Key Fob Model: SKF2 meets all of the relevant specification requirements defined in the Code of Federal Regulations Title 47, Part 15 Subpart B sections 15.109 and Code of Federal Regulations Title 47, Part 15 Subpart C sections 15.205, 15.209 and 15.231.



APPENDIX A***LABORATORY ACCREDITATIONS AND
RECOGNITIONS***

Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

LABORATORY ACCREDITATIONS AND RECOGNITIONS



NVLAP LAB CODES 200063-0,
200528-0, 200527-0

For US, Canada, Australia/New Zealand, Taiwan and the European Union, Compatible Electronics is currently accredited by NVLAP to ISO/IEC 17025 an ISO 9002 equivalent. Please follow the link to the NIST site for each of our facilities NVLAP certificate and scope of accreditation.

NVLAP listing links

Agoura Division - <http://ts.nist.gov/Standards/scopes/2000630.htm>

Brea Division - <http://ts.nist.gov/Standards/scopes/2005280.htm>

Silverado/Lake Forest Division - <http://ts.nist.gov/Standards/scopes/2005270.htm>



ANSI listing

[CETCB](http://www.ansica.org/wwwversion2/outside/ALLdirectoryDetails.asp?menuID=1&prgID=3&orgID=123&status=4)

<https://www.ansica.org/wwwversion2/outside/ALLdirectoryDetails.asp?menuID=1&prgID=3&orgID=123&status=4>



Compatible Electronics has been nominated as a Conformity Assessment Body (CAB) for EMC under the US/EU Mutual Recognition Agreement (MRA).



Compatible Electronics has been nominated as a Conformity Assessment Body (CAB) for Taiwan/BSMI under the US/APEC (Asia-Pacific Economic Cooperation) Mutual Recognition Agreement (MRA).

We are also certified/listed for IT products by the following country/agency:



VCCI Listing, from VCCI site

[Enter "Compatible" in search form](http://www.vcci.or.jp/vcci_e/activity/registration/setsubi.html) http://www.vcci.or.jp/vcci_e/activity/registration/setsubi.html



FCC Listing, from FCC OET site

[FCC test lab search](https://fjallfoss.fcc.gov/oetcf/eas/reports/TestFirmSearch.cfm) <https://fjallfoss.fcc.gov/oetcf/eas/reports/TestFirmSearch.cfm>



Compatible Electronics IC listing can be found at:

<http://www.ic.gc.ca/eic/site/ic1.nsf/eng/home>



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

APPENDIX B

MODIFICATIONS TO THE EUT



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

MODIFICATIONS TO THE EUT

There were no modifications made to the EUT during testing.



APPENDIX C***ADDITIONAL MODELS COVERED
UNDER THIS REPORT***

Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

ADDITIONAL MODELS COVERED UNDER THIS REPORT

USED FOR THE PRIMARY TEST

Life Shield 4 Button Key Fob
Model: SKF2
S/N: None

No additional models were tested.



APPENDIX D***DIAGRAMS, CHARTS, AND PHOTOS***

FIGURE 1: PLOT MAP AND LAYOUT OF TEST SITE BELOW 1GHZ





FIGURE 2: PLOT MAP AND LAYOUT OF TEST SITE ABOVE 1GHZ



COM-POWER AL-130**LOOP ANTENNA****S/N: 121049****CALIBRATION DUE: DECEMBER 6, 2015**

FREQUENCY (MHz)	MAGNETIC (dB/m)	ELECTRIC (dB/m)	FREQUENCY (MHz)	MAGNETIC (dB/m)	ELECTRIC (dB/m)
0.009	-34.64	16.86	0.8	-36.32	15.18
0.01	-34.78	16.72	0.9	-36.22	15.28
0.02	-35.91	15.59	1.0	-36.22	15.28
0.03	-35.48	16.02	2.0	-35.91	15.59
0.04	-35.82	15.68	3.0	-35.91	15.59
0.05	-36.49	15.01	4.0	-36.01	15.49
0.06	-36.30	15.20	5.0	-35.80	15.70
0.07	-36.43	15.07	6.0	-36.00	15.50
0.08	-36.30	15.20	7.0	-35.90	15.60
0.09	-36.39	15.11	8.0	-35.70	15.80
0.1	-36.41	15.09	9.0	-35.70	15.80
0.2	-36.61	14.89	10.0	-35.60	15.90
0.3	-36.63	14.87	15.0	-36.52	14.98
0.4	-36.52	14.99	20.0	-35.75	15.75
0.5	-36.63	14.87	25.0	-37.78	13.72
0.6	-36.62	14.88	30.0	-38.62	12.88
0.7	-36.53	14.97			



COM-POWER AC-220**LAB R - COMBILOG ANTENNA****S/N: 25857****CALIBRATION DUE: MAY 25, 2014**

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
30	17.8	160	8.3
35	18.4	180	9.4
40	19.2	200	9.0
45	17.2	250	12.0
50	17.2	300	13.4
60	13.5	400	15.0
70	8.9	500	17.3
80	6.0	600	17.8
90	7.1	700	20.0
100	8.0	800	20.5
120	9.2	900	20.8
140	7.5	1000	22.4



COM-POWER AH-118**HORN ANTENNA****S/N: 071250****CALIBRATION DUE: JULY 3, 2014**

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
1000	26.5	9500	40.4
1500	27.2	10000	40.3
2000	31.5	10500	41.7
2500	31.9	11000	42.1
3000	32.7	11500	42.3
3500	34.0	12000	42.6
4000	33.5	12500	41.4
4500	34.9	13000	42.7
5000	36.2	13500	43.6
5500	36.6	14000	42.4
6000	36.8	14500	42.7
6500	37.4	15000	45.4
7000	39.4	15500	45.1
7500	39.6	16000	42.9
8000	42.4	16500	44.0
8500	40.3	17000	46.8
9000	39.6	17500	47.5
		18000	46.6



COM-POWER PAM-118A**1-18GHz - PREAMPLIFIER****S/N: 551034****CALIBRATION DUE: FEBRUARY 6, 2015**

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
500	36.77	5500	39.82
1000	38.63	6000	38.74
1100	38.72	6500	39.60
1200	38.97	7000	35.52
1300	38.59	7500	36.61
1400	39.18	8000	36.92
1500	38.71	8500	37.13
1600	39.28	9000	36.50
1700	39.25	9500	38.92
1800	39.06	10000	38.74
1900	40.34	11000	35.23
2000	40.07	12000	35.64
2500	39.69	13000	36.73
3000	40.94	14000	36.48
3500	40.41	15000	37.57
4000	40.44	16000	38.10
4500	41.20	17000	37.34
5000	39.35	18000	36.80



COM-POWER PAM-118**1-18GHz - PREAMPLIFIER****S/N: 443011****CALIBRATION DUE: APRIL 16, 2015**

FREQUENCY (GHz)	FACTOR (dB)	FREQUENCY (GHz)	FACTOR (dB)
0.500	27.01	7.000	23.96
1.000	25.68	7.500	24.28
1.500	26.55	8.000	24.33
2.000	26.16	8.500	24.42
2.500	27.21	9.500	25.89
3.000	26.46	10.000	27.73
3.500	26.52	11.000	28.36
4.000	27.67	12.000	27.21
4.500	26.32	13.000	27.69
5.000	26.90	14.000	25.94
5.500	26.72	15.000	24.27
6.000	26.48	16.000	27.22
6.500	27.12	17.000	26.12
		18.000	25.96





FRONT VIEW

LINEAR, LLC.

Life Shield 4 Button Key Fob

Model: SKF2

FCC SUBPART B & C - RADIATED EMISSIONS < 1GHz

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400



REAR VIEW

LINEAR, LLC.

Life Shield 4 Button Key Fob

Model: SKF2

FCC SUBPART B & C - RADIATED EMISSIONS < 1GHz

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**





FRONT VIEW

LINEAR, LLC.

Life Shield 4 Button Key Fob

Model: SKF2

FCC SUBPART B & C - RADIATED EMISSIONS > 1GHz

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400



REAR VIEW

LINEAR, LLC.

Life Shield 4 Button Key Fob

Model: SKF2

FCC SUBPART B & C - RADIATED EMISSIONS > 1GHz

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

APPENDIX E***RADIATED EMISSIONS DATA SHEETS***

Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700


Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

Title: FCC 15.209
File: Radiated Pre-Scan 30-1000Mhz.set
Operator: Matt Harrison
EUT Type: Key Fob: SKF2.
EUT Condition: Constantly Transmitting.
Comments:
Temp: 72f
Hum: 30%
Battery Powered

5/1/2014 9:55:07 AM
Sequence: Preliminary Scan

Compatible Electronics, Inc. FAC-3 (Lab R)

Electric Field Strength (dBμV/m)



There were no radiated emissions other than harmonics found below 30 MHz or above 1000MHz
There were no radiated emissions found in Receive Mode.



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

Title: FCC 15.209
File: Radiated Final 30-1000Mhz.set
Operator: Matt Harrison
EUT Type: Key Fob: SKF2.
EUT Condition: Constantly Transmitting.
Comments:
Temp: 72f
Hum: 30%
Battery Powered

5/1/2014 10:06:36 AM
Sequence: Final Measurements

Compatible Electronics, Inc. FAC-3 (Lab R)

Freq (MHz)	(QP) Margin (dB)	(QP) EMI (dBμV/m)	(PEAK) EMI (dBμV/m)	Limit (dBμV/m)	Pol	Ttbl Agl (deg)	Twr Ht (cm)	Transducer (dB)	Cable(dB)
36.00	-18.68	21.32	26.52	40.00	H	153.00	133.43	18.58	1.09
38.00	-18.19	21.81	27.19	40.00	H	87.50	224.95	18.90	1.19
39.20	-17.93	22.07	27.84	40.00	H	345.25	204.35	19.09	1.26
39.70	-17.77	22.23	28.29	40.00	V	258.00	399.94	19.15	1.28
43.00	-19.13	20.87	26.08	40.00	V	0.00	251.28	18.01	0.92
48.00	-16.07	23.93	28.08	40.00	H	39.00	399.94	17.20	0.32

*There were no radiated emissions other than harmonics found below 30 MHz or above 1000MHz
There were no radiated emissions found in Receive Mode.*



***FUNDAMENTAL & HARMONICS
DATA SHEETS***



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

FCC 15.231

Linear, LLC.

Life Shield 4 Button Key Fob

Model: SKF2

Duty Cycle Correction Factor: -15.66

Date: 5/2/2014

Lab: R

Tested By: Matt Harrison

Fundamental Field Strength

Freq. (MHz)	Level (dBμV)	Pol (v/h)	Limit (dBμV)	Margin (dB)	Peak / QP / Avg	Table Angle (deg)	Tower Height (m)	Comments
345	87.97	H	97.26	-9.29	Peak	100	234	X-Axis
345	72.31	H	77.26	-4.95	AVG	100	234	X-Axis
345	70.67	V	97.26	-26.59	Peak	131	326	X-Axis
345	55.01	V	77.26	-22.25	AVG	131	326	X-Axis

Test distance

3 meter



HARMONIC EMISSIONS HORIZONTAL

FCC 15.231

Company: Linear, LLC

EUT: Key Fob

Model: SKF2

Duty Cycle Correction Factor: -15.66

Date: 5/1/2014

Lab: R

Test ENG: M. Harrison

Compatible Electronics, Inc. FAC-3

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
690.00	47.52	H	77.26	-29.74	Peak	1.06	65	
690.00	31.86	H	57.26	-25.40	Avg	1.06	65	
1035.00	45.66	H	73.98	-28.32	Peak	1.00	65	
1035.00	30.00	H	53.98	-23.98	Avg	1.00	65	
1380.00	56.10	H	73.98	-17.88	Peak	1.00	285	
1380.00	40.44	H	53.98	-13.54	Avg	1.00	285	
1725.00	51.83	H	77.26	-25.43	Peak	1.25	240	
1725.00	36.17	H	57.26	-21.09	Avg	1.25	240	
2070.00	63.34	H	77.26	-13.92	Peak	1.00	185	
2070.00	47.68	H	57.26	-9.58	Avg	1.00	185	
2415.00	63.20	H	77.26	-14.06	Peak	1.00	340	
2415.00	47.54	H	57.26	-9.72	Avg	1.00	340	
2760.00	50.99	H	73.98	-22.99	Peak	1.00	210	
2760.00	35.33	H	53.98	-18.65	Avg	1.00	210	
3105.00	51.33	H	77.26	-25.93	Peak	1.00	172	
3105.00	35.67	H	57.26	-21.59	Avg	1.00	172	
3450.00	49.53	H	77.26	-27.73	Peak	1.00	205	
3450.00	33.87	H	57.26	-23.39	Avg	1.00	205	

Test distance

3 meter



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

HARMONIC EMISSIONS VERTICAL

FCC 15.231

Company: Linear, LLC

EUT: Key Fob

Model: SKF2

Duty Cycle Correction Factor: -15.66

Date: 5/1/2014

Lab: R

Test ENG: M. Harrison

Compatible Electronics, Inc. FAC-3

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
690.00	44.02	V	77.26	-33.24	Peak	1.00	166	
690.00	28.36	V	57.26	-28.90	Avg	1.00	166	
1035.00	45.84	V	73.98	-28.14	Peak	1.20	163	
1035.00	30.18	V	53.98	-23.80	Avg	1.20	163	
1380.00	51.34	V	73.98	-22.64	Peak	1.65	190	
1380.00	35.68	V	53.98	-18.30	Avg	1.65	190	
1725.00	54.25	V	77.26	-23.01	Peak	1.00	360	
1725.00	38.59	V	57.26	-18.67	Avg	1.00	360	
2070.00	61.41	V	77.26	-15.85	Peak	1.00	275	
2070.00	45.75	V	57.26	-11.51	Avg	1.00	275	
2415.00	68.50	V	77.26	-8.76	Peak	1.00	165	
2415.00	52.84	V	57.26	-4.42	Avg	1.00	165	
2760.00	54.02	V	73.98	-19.96	Peak	1.00	285	
2760.00	38.36	V	53.98	-15.62	Avg	1.00	285	
3105.00	56.74	V	77.26	-20.52	Peak	1.00	272	
3105.00	41.08	V	57.26	-16.18	Avg	1.00	272	
3450.00	54.81	V	77.26	-22.45	Peak	1.00	330	
3450.00	39.15	V	57.26	-18.11	Avg	1.00	330	

Test distance

3 meter



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

OCCUPIED BANDWIDTH

DATA SHEETS



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

OCCUPIED BANDWIDTH


FCC 15.231

Company: Linear, LLC
EUT: Key Fob
Model: SKF2

Date: 5/2/2014
Lab: R
Test ENG: M. Harrison

Compatible Electronics, Inc. FAC-3
FCC 20dB Occupied Bandwidth

Freq. (MHz)	Measured BW (kHz)	Limit (kHz)	Margin (kHz)	Comments
345.00	234.47	862.50	-628.03	



Title: Key Fob: KF2.
Comment A: 20dB Bandwidth.
Date: 1.MAY.2014 10:30:51



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

TRANSMITTER TIME OUT

DATA SHEETS



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

TRANSMIT TIME OUT

FCC 15.231


Company: Linear, LLC
EUT: Key Fob
Model: SKF2

Date: 5/14/2014
Lab: R
Test ENG: M. Harrison

Compatible Electronics, Inc. FAC-3

Freq. (MHz)	Measured Time (S)	Limit (S)	Margin (S)	Comments
345	2.61	5.00	-2.39	


Delta 1 [T1] RBW 1 MHz RF Att 10 dB
Ref Lvl 8.75 dB VBW 300 kHz
87 dBµV 2.605210 s SWT 5 s Unit dBµV



Title: SKF2.
Comment A: Max Transmit Time.
Date: 14.MAY.2014 16:00:20



DUTY CYCLE

DATA SHEETS




Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700


Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

DUTY CYCLE TRAIN

Ref Lvl
87 dBμVRBW 100 kHz RF Att 10 dB
VBW 300 kHz
SWT 105 ms Unit dBμVTitle: SKF2.
Comment A: Duty Cycle
Date: 19.MAY.2014 13:01:23**Brea Division**
114 Olinda Drive
Brea, CA 92823
(714) 579-0500**Agoura Division**
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600**Silverado Division**
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700**Lake Forest Division**
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

DUTY CYCLE

PULSE TYPE 1 WIDTH




```
Title:      Key Fob, KF2.
Comment A:  Pulse Type 1.
Date:      1.MAY.2014  08:26:07
```

Pulse width = 150.301 μ s



DUTY CYCLE

PULSE TYPE 2 WIDTH



Title: Key Fob, KF2.

Comment A: Pulse Type 2.

Date: 1.MAY.2014 08:28:09

Pulse width = 284.369 μ s


Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500


Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

DUTY CYCLE

PULSE TRAIN (1st 10mS of Train)




Title: Key Fob, KF2.
Comment A: Duty Cycle 1st 10uS of Train.
Date: 1.MAY.2014 08:15:36



DUTY CYCLE

PULSE TRAIN (2nd 10mS of Train)



Title: Key Fob, KF2.
Comment A: Duty Cycle 2nd 10uS of Train.
Date: 1.MAY.2014 08:18:59



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500


Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

DUTY CYCLE

PULSE TRAIN (Last 10mS of Train)



Title: Key Fob, KF2.
Comment A: Duty Cycle 3rd 10uS of Train.
Date: 1.MAY.2014 08:19:58

Number of Pulses in 100ms = Pulse Type 1: 68; Pulse Type 2: 22
Total Pulse On-Time Within 100ms period = 16.476ms
Duty Cycle = 16.476ms / 100ms = 0.16476
Correction Factor = 20 * log 0.16476 = -15.66 dB



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400