

Report Number: F690501-RF-RTL000159

Page:

74

TEST REPORT

of

FCC Part 15 Subpart C §15.247 RSS-247 Issue 2, RSS-Gen Issue 5

FCC ID: TQ8-ADC400AAN IC Certification: 5074A-ADC400AKN

Equipment Under Test

DISPLAY CAR SYSTEM

FCC Model Name

ADC400AAN

IC Model Name

ADC400AKN

FCC Variant Model Name

ADC401VAN

IC Variant Model Name

ADC401VKN

Applicant

Hyundai Mobis Co., Ltd.

Manufacturer

Hyundai Mobis Co., Ltd.

Date of Receipt

2019.11.12

Date of Test(s)

2019.11.28 ~ 2019.12.26

Date of Issue

2019.12.31

In the configuration tested, the EUT complied with the standards specified above.

Murphy Kim

Jungmin Yang

Tested By:

Date:

2019.12.31

Technical

Manager:

Date:

2019.12.31



Report Number: F690501-RF-RTL000159 Page: of 74 2

INDEX

Table of Contents

1. General Information	3
2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission	10
3. 6 dB Bandwidth & 99% Bandwidth	52
4. Maximum Peak Conducted Output Power	64
5. Power Spectral Density	67
6. Antenna Requirement	74



Report Number: F690501-RF-RTL000159 Page: 3 of 74

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.

Phone No. : +82 31 688 0901 Fax No. : +82 31 688 0921

1.2. Details of Applicant

Applicant : Hyundai Mobis Co., Ltd.

Address : 203, Teheran-ro, Gangnam-gu, Seoul, South Korea, 135-977

Contact Person : Choe, Seung-hoon Phone No. : +82 31 260 0098

1.3. Details of Manufacturer

Company : Same as applicant Address : Same as applicant

1.4. Description of EUT

Kind of Product	DISPLAY CAR SYSTEM	
FCC Model Name	ADC400AAN	
IC Model Name	ADC400AKN	
FCC Variant Model Name	ADC401VAN	
IC Variant Model Name	ADC401VKN	
Power Supply	DC 14.4 V	
Frequency Range 2 412 № ~ 2 462 № (11b/g/n_HT20)		
Modulation Technique DSSS, OFDM		
Number of Channels	11 channels (11b/g/n_HT20)	
Antenna Type	Pattern antenna	
Antenna Gain	-0.01 dBi	



Report Number: F690501-RF-RTL000159 Page: 4 of 74

1.5. Test Equipment List

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Interval	Cal. Due
Signal Generator	R&S	SMR40	100272	Jun. 07, 2019	Annual	Jun. 07, 2020
Signal Generator	R&S	SMBV100A	255834	Jun. 10, 2019	Annual	Jun. 10, 2020
Spectrum Analyzer	R&S	FSV30	103102	Jun. 05, 2019	Annual	Jun. 05, 2020
Spectrum Analyzer	Agilent	N9030A	US51350132	Sep. 11, 2019	Annual	Sep. 11, 2020
Attenuator	AEROFLEX / INMET	40AH2W-10	40G-3	Jun. 20, 2019	Annual	Jun. 20, 2020
High Pass Filter	Wainwright Instrument GmbH	WHK3.0/18G-10SS	344	May 21, 2019	Annual	May 21, 2020
High Pass Filter	Wainwright Instrument GmbH	WHNX7.5/26.5G-6SS	15	Jun. 05, 2019	Annual	Jun. 05, 2020
Low Pass Filter	Mini-Circuits	NLP-1200+	V 8979400903-2	Feb. 19, 2019	Annual	Feb. 19, 2020
Power Sensor	R&S	NRP-Z81	100748	Jun. 05, 2019	Annual	Jun. 05, 2020
DC Power Supply	R&S	HMP2020	020089489	May 21, 2019	Annual	May 21, 2020
Preamplifier	H.P.	8447F	2944A03909	Aug. 07, 2019	Annual	Aug. 07, 2020
Signal Conditioning Unit	R&S	SCU-18	10117	Jun. 12, 2019	Annual	Jun. 12, 2020
Preamplifier	MITEQ Inc.	JS44-18004000-35-8P	1546891	May 13, 2019	Annual	May 13, 2020
Loop Antenna	Schwarzbeck Mess-Elektronik	FMZB 1519	1519-039	Aug. 22, 2019	Biennial	Aug. 22, 2021
Bilog Antenna	Schwarzbeck Mess-Elektronik	VULB 9163	396	Mar. 21, 2019	Biennial	Mar. 21, 2021
Horn Antenna	R&S	HF906	100326	Feb. 14, 2018	Biennial	Feb. 14, 2020
Horn Antenna	Schwarzbeck Mess-Elektronik	BBHA 9170	BBHA9170431	Sep. 10, 2018	Biennial	Sep. 10, 2020
Test Receiver	R&S	ESU26	100109	Jan. 31, 2019	Annual	Jan. 31, 2020
Turn Table	Innco systems GmbH	DS 1200 S	N/A	N.C.R.	N/A	N.C.R.
Controller	Innco systems GmbH	CONTROLLER CO3000-4P	CO3000/963/383 30516/L	N.C.R.	N/A	N.C.R.
Antenna Mast	Innco systems GmbH	MA4640-XP-ET	MA4640/536/383 30516/L	N.C.R.	N/A	N.C.R.
Anechoic Chamber	SY Corporation	L × W × H (9.6 m × 6.4 m × 6.6 m)	N/A	N.C.R.	N/A	N.C.R.
Coaxial Cable	SUCOFLEX	104 (3 m)	MY3258414	Jul. 20, 2019	Semi- annual	Jan. 20, 2020
Coaxial Cable	SUCOFLEX	104 (10 m)	MY3145814	Jul. 20, 2019	Semi- annual	Jan. 20, 2020
Coaxial Cable	Rosenberger	LA1-C006-1500	131014 01/20	Aug. 23, 2019	Semi- annual	Feb. 23, 2020



Report Number: F690501-RF-RTL000159 Page: 5 of 74

1.6. Summary of Test Results

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part15 Subpart C, RSS-247 Issue 2, RSS-Gen Issue 5					
Section in FCC	Section in IC	Test Item(s)	Result		
15.205(a) 15.209 15.247(d)	RSS-247 Issue 2 5.5 RSS-Gen Issue 5 8.9	Transmitter Radiated Spurious Emissions and Conducted Spurious Emission	Complied		
15.247(a)(2)	RSS-247 Issue 2 5.2(a) RSS-Gen Issue 5 6.7	6 dB Bandwidth & 99 % Bandwidth	Complied		
15.247(b)(3)	RSS-247 Issue 2 5.4(d)	Maximum Peak Conducted Output Power	Complied		
15.247(e)	RSS-247 Issue 2 5.2(b)	Power Spectral Density	Complied		
15.207	RSS-Gen Issue 5 8.8	AC Power Line Conducted Emission	N/A ¹⁾		

Note;

1) The AC power line test was not performed because the EUT use battery power for operation and which do not operate from the AC power lines.



Report Number: F690501-RF-RTL000159 Page: 6 of 74

1.7. Information of Variant Models

					De	scripti	on				
	Model	Names	BT/WIFI	FM/AM Code	INTERNAL /EXTERNAL	USB	RDS	DAB	SXM	HD	RHD/LHD
Basic	FCC	ADC400AAN	BT/WIFI/LTE	A2	EXTERNAL	0	0	Х	0	0	LHD
Model	IC	ADC400AKN	BT/WIFI/LTE	A2	EXTERNAL	0	0	Х	0	0	LHD
Variant	FCC	ADC401VAN	BT/WIFI/LTE	A2	EXTERNAL	0	0	Х	0	0	LHD
Model	IC	ADC401VKN	BT/WIFI/LTE	A2	EXTERNAL	0	0	Х	0	0	LHD

CODE	BAND	FREQUENCY RANGE	STEP	LOCAL
A. 2	FM	87.5-107.9 Mb	200 kHz	NA/CENI
A2	AM	530-1710 kHz	10 kHz	NA/GEN

1.8. Test Procedure(s)

The measurement procedures described in the American National Standard of Procedure for Compliance Testing of unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 558074 D01 15.247 Meas Guidance v05r02 were used in the measurement of the DUT.

1.9. Sample Calculation

Where relevant, the following sample calculation is provided:

1.9.1. Conducted Test

Offset value (dB) = Attenuator (dB) + Cable loss (dB)

1.9.2. Radiation Test

Field strength level ($dB\mu V/m$) = Measured level ($dB\mu V$) + Antenna factor (dB) + Cable loss (dB) - Amplifier gain (dB)



Report Number: F690501-RF-RTL000159 Page: 7 of 74

1.10. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
RF Output Power	± 0.52 dB
Occupied Bandwidth	± 9.66 kHz
Power Spectral Density	± 0.41 dB
Conducted Spurious Emission	± 0.76 dB
Radiated Emission, 9 klb to 30 Mb	± 3.59 dB
Radiated Emission, below 1 @	± 5.88 dB
Radiated Emission, above 1 @	± 5.94 dB

Uncertainty figures are valid to a confidence level of 95 %.

1.11. Test Report Revision

Revision	Report Number	Date of Issue	Description
0	F690501-RF-RTL000159	2019.12.31	Initial



Report Number: F690501-RF-RTL000159 Page: of 74

1.12. Duty Cycle of EUT

Regarding to KDB 558074 D01 15.247 Meas Guidance v05r02, 6, the maximum duty cycles of all modes were investigated and set the spectrum analyzer as below;

Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100.


Mode	Data Rate (Mbps)	Duty Cycle (%)	Correction Factor (dB)
11b	11	92.69	0.33
11g	6	94.95	0.23
11n_HT20	MCS0	95.05	0.22

Remark;

- As measured duty cycles of EUT, all of mode and data rate keeps constant period and are converted
 - log scale (power averaging) to compensate correction factor to result of average test items.
- Duty Cycle (%) = $(Tx \text{ on time } / Tx \text{ on + off time}) \times 100$
- Correction Factor (dB) = 10 log (1 / Duty Cycle)

- Test plots


802.11b






Report Number: F690501-RF-RTL000159 Page: 9 of 74

802.11g



802.11n_HT20






Report Number: F690501-RF-RTL000159 Page: 10 of 74

2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission


2.1. Test Setup

2.1.1. Transmitter Radiated Spurious Emissions

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 $\,\mathrm{kll}$ to 30 $\,\mathrm{ml}$ emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 \(\mathref{M} \) to 1 \(\mathref{M} \) emissions.




The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 http://www.sgsgroup.kr



F690501-RF-RTL000159 74 Report Number: Page: 11 of

The diagram below shows the test setup that is utilized to make the measurements for emission .The or 40 GHz, whichever is lower.





Report Number: F690501-RF-RTL000159 Page: 12 of 74

2.1.2. Conducted Spurious Emission



2.2. Limit

2.2.1. FCC

According to \$15.247(d), in any 100 klb bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emission which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (쌘)	Field Strength (᠘V/m)	Measurement Distance (Meters)
0.009-0.490	2 400/F(kHz)	300
0.490-1.705	24 000/F(kllz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

^{**} Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 Mb, 76-88 Mb, 174-216 Mb or 470-806 Mb. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.



Report Number: F690501-RF-RTL000159 Page: 13 of 74

2.2.2. IC

According to RSS-247 Issue 2, 5.5, in any 100 \(\text{klz} \) bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 \(\text{dB} \) below that in the 100 \(\text{klz} \) bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 \(\text{dB} \) instead of 20 \(\text{dB} \). Attenuation below the general field strength limits specified in RSS-Gen is not required.

According to RSS-Gen Issue 5, 8.9, except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

Table 5 – General Field Strength Limits at frequencies above 30 胍

Frequency (Mb)	Field Strength (μ̄V/m at 3 m)
30-88	100
88-216	150
216-960	200
Above 960	500

Table 6 – General Field Strength Limits at frequencies below 30 №

Frequency	Magnetic Field Strength (H-Field) (μλ/m)	Measurement Distance (meters)
9-490 kHz ¹	6.37/F (F in 세z)	300
490-1 705 kHz	63.7/F (F in klb)	30
1.705-30 Mb	0.08	30

Note¹: The emission limits for the ranges 9-90 klb and 110-490 klb are based on measurements employing a linear average detector.



Report Number: F690501-RF-RTL000159 Page: 14 of 74

2.3. Test Procedures

Radiated emissions from the EUT were measured according to the dictates in section 11.11 & 11.12 of ANSI C63.10-2013.

2.3.1. Test Procedures for emission below 30 Mb

- 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
- 3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum Hold Mode.

2.3.2. Test Procedures for emission from above 30 Mb

- 2. During performing radiated emission below 1 (), the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 (), the EUT was set 3 meter away from the interference-receiving antenna.
- 3. The antenna is a bi-log antenna, a horn antenna and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.



Report Number: F690501-RF-RTL000159 Page: 15 of 74

Note;

All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

- 1. Unwanted Emissions into Non-Restricted Frequency Bands
- The Reference Level Measurement refer to section 11.11.2 Set analyzer center frequency to DTS channel center frequency, SPAN \geq 1.5 times the DTS bandwidth, the RBW = 100 kHz and VBW \geq 3 x RBW, Detector = Peak, Sweep time = Auto couple, Trace = Max hold.
- Unwanted Emissions Level Measurement refer to section 11.11.3 Set the center frequency and span to encompass frequency range to be measured, the RBW = 100 $\,\mathrm{kl}$ and $\,\mathrm{VBW} \ge 3 \,\mathrm{x} \,\mathrm{RBW}$, Detector = Peak, Sweep time = Auto couple, Trace = Max hold.
- 2. Unwanted Emissions into Restricted Frequency Bands
- Peak Power measurement procedure refer to section 11.12.2.4 Set RBW = as specified in Table 9, VBW ≥ 3 x RBW, Detector = Peak, Sweep time = auto, Trace = Max hold.

Table 9 – RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1 000 MHz	100 kHz to 120 kHz
> 1 000 MHz	1 MHz

If the peak – detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

- Average Power measurements procedure refer to section 11.12.2.5.2 The EUT shall be configured to operate at the maximum achievable duty cycle. Measure the duty cycle D of the transmitter output signal as described in section 11.6. Set RBW = 1 Mb, VBW \geq 3 x RBW, Detector = RMS, if span / (# of points in sweep) \leq (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied then the detector mode shall be set to peak.

Averaging type = power (i.e., RMS).

As an alternative the detector and averaging type may be set for linear voltage averaging.

Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used. Sweep time = auto, Perform a trace average of at least 100 traces.

A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:

- 1) If power averaging (rms) mode was used in step f), then the applicable correction factor is [10 log(1 / D)], where D is the duty cycle.
- 3. Definition of DUT Axis.

Definition of the test orthogonal plan for EUT was described in the test setup photo. The test orthogonal plan of EUT is X - axis during radiation test.



Report Number: F690501-RF-RTL000159 Page: 16 of 74

2.3.3. Test Procedures for Conducted Spurious Emissions

All data rates and modes were investigated for conducted spurious emissions.

Per the guidance of ANSI C63.10-2013, section 11.11.1 & 11.11.2 & 11.11.3, the reference level for out of band emissions is established from the plots of this section since the band edge emissions are measured with a RBW of 100 kHz. This reference level is then used as the limit in subsequent plots for out of band spurious emissions shown in section 2.4.3. The limit for out of band spurious emission at the band edge is 20 dB below the fundamental emission level measured in a 100 kHz bandwidth.

1. Conducted Emissions at Band Edge

- The Measurement refer to section 11.11.2

Set the center frequency and span to encompass frequency range to be measured, the RBW = 100 ຟz

and VBW ≥ 3 x RBW, Detector = Peak, Sweep time = Auto couple, Trace mode = Max hold, The trace was allowed to stabilize.

2. Conducted Spurious Emissions

- The Measurement refer to section 11.11.3

Start frequency was set to 9 № and stop frequency was set to 25 № (separated into two plots per channel), RBW = 1 №, VBW ≥ 3 x RBW, Detector = Peak, Sweep time = Auto couple, Trace = Max hold, The trace was allowed to stabilize.

3. TDF function

- For plots showing conducted spurious emissions from 9 椪 to 25 吨, all path loss of wide frequency range was investigated and compensated to spectrum analyzer as TDF function. So, the reading values shown in plots were final result.



Report Number: F690501-RF-RTL000159 Page: 17 of 74

2.4. Test Results

Ambient temperature : **(23** ± **1)** ℃ Relative humidity : 47 % R.H.

2.4.1. Radiated Spurious Emission below 1 000 Mb


The frequency spectrum from 9 kHz to 1 000 kHz was investigated. All reading values are peak values.

Radia	ated Emissio	ns	Ant	Correctio	n Factors	Total	Lim	t
Frequency (脈)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP + CL (dB)	Actual (dΒμV/m)	Limit (dBµV/m)	Margin (dB)
30.16	34.60	Peak	V	15.22	-27.17	22.65	40.00	17.35
114.27	35.30	Peak	V	16.17	-25.51	25.96	43.50	17.54
228.57	34.70	Peak	V	17.67	-25.46	26.91	46.00	19.09
457.16	38.60	Peak	Н	21.94	-25.09	35.45	46.00	10.55
685.72	35.90	Peak	Н	25.41	-23.50	37.81	46.00	8.19
933.03	35.20	Peak	Н	28.14	-22.71	40.63	46.00	5.37

Remark;

- 1. Spurious emissions for all channels were investigated and almost the same below 1 @lz.
- Reported spurious emissions are in 11n HT20 / MCS0 / Low channel as worst case among other modes.
- Radiated spurious emission measurement as below. (Actual = Reading + AF + AMP + CL)
- 4. According to §15.31(o), emission levels are not report much lower than the limits by over 20 dB.

- Test plot





Report Number: F690501-RF-RTL000159 Page: 18 of 74

2.4.2. Radiated Spurious Emission above 1 000 Mb

The frequency spectrum above 1 000 Mb was investigated. All reading values are peak and average values.

DSSS: 802.11b (11 Mbps)

Low Channel (2 412 眦)

Radi	ated Emissic	ons	Ant.	Corr	ection Fact	tors	Total	Limit	
Frequency (畑)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 310.00	19.27	Peak	V	27.82	8.07	-	55.16	74.00	18.84
*2 310.00	10.02	Average	V	27.82	8.07	0.33	46.24	54.00	7.76
*2 368.40	21.54	Peak	V	27.94	8.20	-	57.68	74.00	16.32
*2 350.16	11.00	Average	V	27.90	8.13	0.33	47.36	54.00	6.64
*2 390.00	21.15	Peak	V	27.98	8.22	-	57.35	74.00	16.65
*2 390.00	10.44	Average	V	27.98	8.22	0.33	46.97	54.00	7.03

Radiated Emissions		Ant.	Corr	ection Fact	ors	Total	Limit		
Frequency (Mb)	Reading ($dB\mu V$)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dΒμV/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

Middle Channel (2 437 眦)

Radiated Emissions		Ant.	Correction Factors			Total	Limit		
Frequency (Mb)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dB <i>µ</i> V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501-RF-RTL000159 Page: 19 of 74

High Channel (2 462 眦)

Radi	ated Emissic	ons	Ant.	Corr	ection Fac	tors	Total	Limit	
Frequency (脈)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 483.50	19.22	Peak	V	28.00	8.37	-	55.59	74.00	18.41
*2 483.50	10.44	Average	V	28.00	8.37	0.33	47.14	54.00	6.86
*2 497.64	21.73	Peak	V	28.00	8.38	-	58.11	74.00	15.89
*2 499.71	11.25	Average	V	28.00	8.38	0.33	47.96	54.00	6.04
*2 500.00	19.91	Peak	V	28.00	8.38	-	56.29	74.00	17.71
*2 500.00	10.53	Average	V	28.00	8.38	0.33	47.24	54.00	6.76

Radiated Emissions		Ant.	Corr	ection Fact	ors	Total	Limit		
Frequency (Mb)	Reading ($dB\mu V$)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dB <i>µ</i> V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501-RF-RTL000159 Page: 20 of 74

OFDM: 802.11g (6 Mbps)

Low Channel (2 412 Mb)

Radi	ated Emissic	ons	Ant.	Correction Factors			Total	Limit	
Frequency (Mb)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 310.00	19.17	Peak	V	27.82	8.07	-	55.06	74.00	18.94
*2 310.00	10.67	Average	V	27.82	8.07	0.23	46.79	54.00	7.21
*2 360.24	22.25	Peak	V	27.92	8.17	-	58.34	74.00	15.66
*2 365.16	10.79	Average	V	27.93	8.18	0.23	47.13	54.00	6.87
*2 390.00	20.47	Peak	V	27.98	8.22	-	56.67	74.00	17.33
*2 390.00	10.41	Average	V	27.98	8.22	0.23	46.84	54.00	7.16

Radiated Emissions		Ant.	Corr	ection Fact	ors	Total	Limit		
Frequency (Mb)	Reading ($dB\mu V$)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dB <i>µ</i> V/m)	Margin (dB)
Above 1 000.00	Not detected	-	-	-	-	-	-	-	-

Middle Channel (2 437 Mb)

Radi	Radiated Emissions		Ant.	Corr	ection Fact	ors	Total	Limi	it
Frequency (雕)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dΒμV/m)	Margin (dB)
*7 312.60	54.35	Peak	V	35.85	-30.35	-	59.85	74.00	14.15
*7 313.10	36.44	Average	V	35.85	-30.35	0.23	42.17	54.00	11.83
Above 7 400.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501-RF-RTL000159 Page: 21 of 74

High Channel (2 462 眦)

Radi	ated Emissio	ons	Ant.	Corr	ection Fac	tors	Total	Lim	it
Frequency (雕)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 483.50	19.66	Peak	V	28.00	8.37	-	56.03	74.00	17.97
*2 483.50	10.41	Average	V	28.00	8.37	0.23	47.01	54.00	6.99
*2 488.60	21.75	Peak	V	28.00	8.38	-	58.13	74.00	15.87
*2 499.12	11.01	Average	V	28.00	8.38	0.23	47.62	54.00	6.38
*2 500.00	19.97	Peak	V	28.00	8.38	-	56.35	74.00	17.65
*2 500.00	10.29	Average	V	28.00	8.38	0.23	46.90	54.00	7.10

Radi	Radiated Emissions		Ant.	Corr	ection Fact	ors	Total	Limi	it
Frequency (Mb)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*7 379.20	51.04	Peak	V	36.06	-30.57	-	56.53	74.00	17.47
*7 384.35	32.61	Average	V	36.07	-30.60	0.23	38.31	54.00	15.69
Above 7 400.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501-RF-RTL000159 Page: 22 of 74

OFDM: 802.11n_HT20 (MCS0)

Low Channel (2 412 Mb)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (脈)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dBµV/m)	Margin (dB)
*2 310.00	19.52	Peak	V	27.82	8.07	-	55.41	74.00	18.59
*2 310.00	9.83	Average	V	27.82	8.07	0.22	45.94	54.00	8.06
*2 356.76	21.79	Peak	V	27.91	8.15	-	57.85	74.00	16.15
*2 371.88	11.02	Average	V	27.94	8.21	0.22	47.39	54.00	6.61
*2 390.00	20.64	Peak	V	27.98	8.22	-	56.84	74.00	17.16
*2 390.00	11.51	Average	V	27.98	8.22	0.22	47.93	54.00	6.07

Radiated Emissions		Ant.	Correction Factors			Total	Limit		
Frequency (Mb)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dΒμV/m)	Margin (dB)
Above 1 000.00	Not detected	ı	-	ı	-	-	-	-	-

Middle Channel (2 437 Mb)

Radiated Emissions			Ant.	Corr	ection Fact	ors	Total	Limit	
Frequency (脈)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dB <i>µ</i> V/m)	Margin (dB)
*7 305.45	56.75	Peak	V	35.82	-30.33	-	62.24	74.00	11.76
*7 312.95	33.79	Average	V	35.85	-30.35	0.22	39.51	54.00	14.49
Above 7 400.00	Not detected	-	-	-	-	-	-	-	-



Report Number: F690501-RF-RTL000159 Page: 23 of 74

High Channel (2 462 账)

Radiated Emissions			Ant.	Correction Factors			Total	al Limit	
Frequency (脈)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dB <i>µ</i> V/m)	Margin (dB)
*2 483.50	20.33	Peak	V	28.00	8.37	-	56.70	74.00	17.30
*2 483.50	9.87	Average	٧	28.00	8.37	0.22	46.46	54.00	7.54
*2 485.52	22.45	Peak	V	28.00	8.37	-	58.82	74.00	15.18
*2 494.84	11.24	Average	V	28.00	8.38	0.22	47.84	54.00	6.16
*2 500.00	19.56	Peak	V	28.00	8.38	-	55.94	74.00	18.06
*2 500.00	9.98	Average	V	28.00	8.38	0.22	46.58	54.00	7.42

Radiated Emissions			Ant.	Corr	ection Fact	ors	Total	Limit	
Frequency (畑)	Reading (dBµV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBµV/m)	Limit (dB <i>µ</i> V/m)	Margin (dB)
*7 381.25	53.24	Peak	V	36.06	-30.58	-	58.72	74.00	15.28
*7 384.50	32.06	Average	V	36.07	-30.60	0.22	37.75	54.00	16.25
Above 7 400.00	Not detected	-	-	-	-	-	-	-	-

Remarks;

- 1. "*" means the restricted band.
- 3. Radiated emissions measured in frequency above 1 000 Mb were made with an instrument using peak/average detector mode.
- 4. Actual = Reading + AF + CL + (DF) or Reading + AF + AMP + CL + (DF).
- 5. According to § 15.31(o), emission levels are not reported much lower than the limits by over 20 dB.
- 6. The maximized peak measured value complies with the average limit, to perform an average measurement is unnecessary.



Report Number: F690501-RF-RTL000159 Page: 24 of 74

- Test plots

DSSS: 802.11b (11 Mbps)

Low channel Band edge (Peak)




Low channel Band edge (Average)





Report Number: F690501-RF-RTL000159 Page: 25 of 74

High channel Band edge (Peak)



High channel Band edge (Average)






Report Number: F690501-RF-RTL000159 Page: 26 74 of

OFDM: 802.11g (6 Mbps)

Low channel Band edge (Peak)



Low channel Band edge (Average)





Report Number: F690501-RF-RTL000159 Page: 27 of 74

High channel Band edge (Peak)



High channel Band edge (Average)



The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 http://www.sgsgroup.kr



Report Number: F690501-RF-RTL000159 Page: 28 of 74

OFDM: 802.11n_HT20 (MCS0)

Low channel Band edge (Peak)



Low channel Band edge (Average)





Report Number: F690501-RF-RTL000159 Page: 29 of 74

High channel Band edge (Peak)



High channel Band edge (Average)






Report Number: F690501-RF-RTL000159 Page: 30 of 74

OFDM: 802.11g (6 Mbps)

Middle channel 3rd harmonic (Peak)




Middle channel 3rd harmonic (Average)





Report Number: F690501-RF-RTL000159 Page: 31 of 74

High channel 3rd harmonic (Peak)



High channel 3rd harmonic (Average)



The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.


SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 http://www.sgsgroup.kr



Report Number: F690501-RF-RTL000159 Page: 32 of 74

OFDM: 802.11n_HT20 (MCS0)

Middle channel 3rd harmonic (Peak)




Middle channel 3rd harmonic (Average)





Report Number: F690501-RF-RTL000159 Page: 33 of 74

High channel 3rd harmonic (Peak)



High channel 3rd harmonic (Average)



The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 http://www.sgsgroup.kr




Report Number: F690501-RF-RTL000159 Page: 34 of 74

2.4.3. Plot of Conducted Spurious Emissions


DSSS: 802.11b (11 Mbps)

Low Channel






Report Number: F690501-RF-RTL000159 Page: 35 of 74






Report Number: F690501-RF-RTL000159 Page: 36 of 74

Middle Channel






Report Number: F690501-RF-RTL000159 Page: 37 of 74






Report Number: F690501-RF-RTL000159 Page: 38 of 74

High Channel





Report Number: F690501-RF-RTL000159 Page: 39 of 74






Report Number: F690501-RF-RTL000159 Page: 40 of 74


OFDM: 802.11g (6 Mbps)

Low Channel






Report Number: F690501-RF-RTL000159 Page: 41 of 74






Report Number: F690501-RF-RTL000159 Page: 42 of 74

Middle Channel






Report Number: F690501-RF-RTL000159 Page: 43 of 74






Report Number: F690501-RF-RTL000159 Page: 44 of 74

High Channel





Report Number: F690501-RF-RTL000159 Page: 45 of 74






Report Number: F690501-RF-RTL000159 Page: 46 of 74


OFDM: 802.11n_HT20 (MCS0)

Low Channel






Report Number: F690501-RF-RTL000159 Page: 47 of 74






Report Number: F690501-RF-RTL000159 Page: 48 of 74

Middle Channel






Report Number: F690501-RF-RTL000159 Page: 49 of 74





Report Number: F690501-RF-RTL000159 Page: 50 of 74

High Channel





Report Number: F690501-RF-RTL000159 Page: 51 of 74

