

RF Exposure Requirements

Product Description: OontZ Angle 3 Pro Soundbar

Model No.: OontZ Angle 3 Pro Soundbar

FCC ID: 2AGA6-OZSBAR

According to the KDB 447498 D01 v06 section 4.3.1, for 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz

- Power and distance are rounded to the nearest mW and mm before calculation¹⁷

- The result is rounded to one decimal place for comparison

Calculation Result:

Bluetooth 1: V5.0 (BR/EDR/LE mode)

Tx frequency range: 2402-2480MHz

Min. test separation distance: 5mm

Maximum Conducted Output Power: 1.20dBm

Tune-Up output power: 2dBm

RF channel transmit frequency: 2480MHz

Result: 0.5

Limit: 3.0

Exclusion thresholds is $0.5 < 3$

Bluetooth 2: V5.0 (Only BLE mode)

Tx frequency range: 2402-2480MHz

Min. test separation distance: 5mm

Maximum Conducted Output Power: 0.97dBm

Tune-Up output power: 1dBm

RF channel transmit frequency: 2480MHz

Result: 0.4

Limit: 3.0

Exclusion thresholds is $0.4 < 3$

So the transmitter complies with the RF exposure requirements and the SAR is not required.