



# FCC RF Test Report

**APPLICANT** : ZTE CORPORATION  
**EQUIPMENT** : LTE/CDMA/GSM Multi-Mode Digital Mobile Phone  
**BRAND NAME** : ZTE  
**MODEL NAME** : Z3351S  
**FCC ID** : SRQ-Z3351S  
**STANDARD** : FCC Part 15 Subpart C §15.247  
**CLASSIFICATION** : (DSS) Spread Spectrum Transmitter

The product was received on Feb. 21, 2019 and testing was completed on Mar. 19, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.



---

Approved by: James Huang / Manager

***Sporton International (Kunshan) Inc.***  
***No. 1098, Pengxi North Road, Kunshan Economic Development Zone,***  
***Jiangsu Province 215335, China***



## TABLE OF CONTENTS

<b>REVISION HISTORY.....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION.....</b>	<b>5</b>
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT .....	6
1.6 Testing Location .....	7
1.7 Applicable Standards.....	7
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....</b>	<b>8</b>
2.1 Carrier Frequency Channel .....	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system .....	10
2.5 EUT Operation Test Setup .....	11
2.6 Measurement Results Explanation Example.....	11
<b>3 TEST RESULT .....</b>	<b>12</b>
3.1 Number of Channel Measurement .....	12
3.2 Hopping Channel Separation Measurement .....	14
3.3 Dwell Time Measurement.....	21
3.4 20dB Bandwidth Measurement .....	23
3.5 Output Power Measurement.....	30
3.6 Conducted Band Edges Measurement.....	32
3.7 Conducted Spurious Emission Measurement .....	39
3.8 Radiated Band Edges and Spurious Emission Measurement .....	49
3.9 AC Conducted Emission Measurement.....	53
3.10 Antenna Requirements.....	55
<b>4 LIST OF MEASURING EQUIPMENT.....</b>	<b>56</b>
<b>5 UNCERTAINTY OF EVALUATION.....</b>	<b>57</b>
<b>APPENDIX A. AC CONDUCTED EMISSION TEST RESULT</b>	
<b>APPENDIX B. RADIATED SPURIOUS EMISSION</b>	
<b>APPENDIX C. DUTY CYCLE PLOTS</b>	
<b>APPENDIX D. SETUP PHOTOGRAPHS</b>	



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR922103A	Rev. 01	Initial issue of report	Apr. 04, 2019

## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	NA	Pass	-
3.5	15.247(b)(1)	Peak Output Power	$\leq 125\text{ mW}$	Pass	-
3.6	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 19.60 dB at 30.000 MHz
3.9	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 4.00 dB at 2.794 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



# 1 General Description

## 1.1 Applicant

**ZTE CORPORATION**

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

## 1.2 Manufacturer

**ZTE CORPORATION**

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	LTE/CDMA/GSM Multi-Mode Digital Mobile Phone
Brand Name	ZTE
Model Name	Z3351S
FCC ID	SRQ-Z3351S
EUT supports Radios application	CDMA/EVDO/GSM/GPRS/EGPRS/LTE WLAN 2.4GHz 802.11b/g/n HT20 Bluetooth BR/EDR/LE GNSS/FM
IMEI Code	Conducted: 990010440004274 Conduction: 990010440004589 Radiation: 990010440004225
HW Version	Z3351SHW1.0
SW Version	Z3351SV1.0.0B01
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 7.15 dBm (0.0052 W) Bluetooth EDR (2Mbps) : 6.55 dBm (0.0045 W) Bluetooth EDR (3Mbps) : 6.72 dBm (0.0047 W)
Antenna Type / Gain	IFA Antenna with gain -2.80 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.



## 1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0).

<b>Test Site</b>	Sporton International (Kunshan) Inc.		
<b>Test Site Location</b>	No. 1098, Pengxi North Road, Kunshan Economic Development Zone, Jiangsu Province 215335, China TEL : 86-512-57900158 FAX : 86-512-57900958		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC designation No.</b>	<b>FCC Test Firm Registration No.</b>
	TH01-KS CO01-KS 03CH02-KS	CN5013	630927

## 1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r01
- ♦ ANSI C63.10-2013

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-




## 2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth BR 1Mbps GFSK		
	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz		
AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN Link (2.4G) + USB Cable (Charging from Adapter 2) + Earphone		
Remark:			
1. For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.			
2. For Radiated Test Cases, The tests were performed with Adapter 1, Earphone and USB Cable.			

## 2.3 Connection Diagram of Test System



## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	BT Base Station	R&S	CBT	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	LINKSYS	WRT600N	Q87-WRT600NV11	N/A	Unshielded, 1.8 m
4.	Notebook	Lenovo	G480	PRC4	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
5.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
6.	Earphone	Lenovo	LH102	N/A	N/A	Unshielded, 1.2m

## 2.5 EUT Operation Test Setup

For Bluetooth function, the engineering test program was provided and enabled to make EUT connect with Bluetooth base station to continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

*Offset = RF cable loss.*

Following shows an offset computation example with cable loss 5.8 dB.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} . \\ &= 5.8 \text{ (dB)}\end{aligned}$$

### 3 Test Result

#### 3.1 Number of Channel Measurement

##### 3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation;  
RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

##### 3.1.4 Test Setup




##### 3.1.5 Test Result of Number of Hopping Frequency


<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	21~24°C
<b>Test Engineer :</b>	Lion Ran	<b>Relative Humidity :</b>	49~51%
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass



Number of Hopping Channel Plot on Channel 00 - 78



Date: 9.MAR.2019 20:10:43



Date: 9.MAR.2019 20:11:03

## 3.2 Hopping Channel Separation Measurement

### 3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels;  
RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

### 3.2.4 Test Setup






## 3.2.5 Test Result of Hopping Channel Separation

Test Mode :	1Mbps	Temperature :	21~24℃
Test Engineer :	Lion Ran	Relative Humidity :	49~51%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	0.9899	0.6136	Pass
39	2441	0.9585	0.6291	Pass
78	2480	0.9769	0.6291	Pass


Channel Separation Plot on Channel 00 - 01



Date: 9.MAR.2019 20:54:42




### Channel Separation Plot on Channel 39 - 40



Date: 9.MAR.2019 21:03:28

### Channel Separation Plot on Channel 77 - 78




Date: 9.MAR.2019 20:53:49





Test Mode :	2Mbps	Temperature :	21~24°C
Test Engineer :	Lion Ran	Relative Humidity :	49~51%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.3155	0.8539	Pass
39	2441	0.9986	0.8393	Pass
78	2480	1.0072	0.8567	Pass

**Channel Separation Plot on Channel 00 - 01**

Date: 9.MAR.2019 20:56:20




Channel Separation Plot on Channel 39 - 40



Date: 9.MAR.2019 21:02:05

Channel Separation Plot on Channel 77 - 78




Date: 9.MAR.2019 20:52:54



Test Mode :	3Mbps	Temperature :	21~24°C
Test Engineer :	Lion Ran	Relative Humidity :	49~51%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	0.9986	0.8220	Pass
39	2441	0.9986	0.8191	Pass
78	2480	1.2634	0.8220	Pass

**Channel Separation Plot on Channel 00 - 01**

Date: 9.MAR.2019 20:57:26




Channel Separation Plot on Channel 39 - 40



Date: 9.MAR.2019 21:01:01

Channel Separation Plot on Channel 77 - 78



Date: 9.MAR.2019 21:06:08

### 3.3 Dwell Time Measurement

#### 3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW  $\geq$  RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

#### 3.3.4 Test Setup




### 3.3.5 Test Result of Dwell Time

<b>Test Mode :</b>	DH5	<b>Temperature :</b>	21~24℃
<b>Test Engineer :</b>	Lion Ran	<b>Relative Humidity :</b>	49~51%

Mode	Hopping Channel Number	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	2.8783	0.31	0.4	Pass
AFH	20	53.34	2.8783	0.15	0.4	Pass

**Package Transfer Time Plot**



**Remark:**

- In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.  
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),  
Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
- In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.  
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),  
Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
- Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

### 3.4 20dB Bandwidth Measurement

#### 3.4.1 Limit of 20dB Bandwidth

Reporting only


#### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.  
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;  
RBW  $\geq$  1% of the 20 dB bandwidth; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
5. Measure and record the results in the test report.


#### 3.4.4 Test Setup



**3.4.5 Test Result of 20dB Bandwidth**

Test Mode :	1Mbps	Temperature :	21~24℃
Test Engineer :	Lion Ran	Relative Humidity :	49~51%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.039
39	2441	1.039
78	2480	1.004


**20 dB Bandwidth Plot on Channel 00**

Date: 10.MAR.2019 06:44:40






### 20 dB Bandwidth Plot on Channel 39



Date: 10.MAR.2019 06:57:19

### 20 dB Bandwidth Plot on Channel 78




Date: 10.MAR.2019 06:54:34



Test Mode :	2Mbps	Temperature :	21~24°C
Test Engineer :	Lion Ran	Relative Humidity :	49~51%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.276
39	2441	1.276
78	2480	1.255

**20 dB Bandwidth Plot on Channel 00**

Date: 10.MAR.2019 06:46:16




### 20 dB Bandwidth Plot on Channel 39



Date: 10.MAR.2019 07:00:39

### 20 dB Bandwidth Plot on Channel 78




Date: 10.MAR.2019 06:52:16



Test Mode :	3Mbps	Temperature :	21~24℃
Test Engineer :	Lion Ran	Relative Humidity :	49~51%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.242
39	2441	1.246
78	2480	1.242

**20 dB Bandwidth Plot on Channel 00**

Date: 10.MAR.2019 06:48:05




### 20 dB Bandwidth Plot on Channel 39



Date: 10.MAR.2019 07:03:39

### 20 dB Bandwidth Plot on Channel 78



Date: 10.MAR.2019 06:50:14

## 3.5 Output Power Measurement

### 3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:

(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.


### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

### 3.5.4 Test Setup



### 3.5.5 Test Result of Peak Output Power

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	21~24℃
<b>Test Engineer :</b>	Lion Ran	<b>Relative Humidity :</b>	49~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	5.34	20.97	Pass
39	2441	7.15	20.97	Pass
78	2480	7.14	20.97	Pass

<b>Test Mode :</b>	2Mbps	<b>Temperature :</b>	21~24℃
<b>Test Engineer :</b>	Lion Ran	<b>Relative Humidity :</b>	49~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		$\pi/4$ -DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	4.81	20.97	Pass
39	2441	6.55	20.97	Pass
78	2480	6.45	20.97	Pass

<b>Test Mode :</b>	3Mbps	<b>Temperature :</b>	21~24℃
<b>Test Engineer :</b>	Lion Ran	<b>Relative Humidity :</b>	49~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	4.95	20.97	Pass
39	2441	6.72	20.97	Pass
78	2480	6.59	20.97	Pass

## 3.6 Conducted Band Edges Measurement

### 3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

### 3.6.4 Test Setup








## 3.6.5 Test Result of Conducted Band Edges


Test Mode :	1Mbps	Temperature :	21~24℃
Test Channel :	00 and 78	Relative Humidity :	49~51%
		Test Engineer :	Lion Ran

Low Band Edge Plot on Channel 00



Date: 9.MAR.2019 20:19:43


High Band Edge Plot on Channel 78




Date: 9.MAR.2019 20:20:11



Test Mode :	2Mbps	Temperature :	21~24°C
Test Channel :	00 and 78	Relative Humidity :	49~51%
		Test Engineer :	Lion Ran

**Low Band Edge Plot on Channel 00**


Date: 9.MAR.2019 20:18:14

**High Band Edge Plot on Channel 78**


Date: 9.MAR.2019 20:18:41



Test Mode :	3Mbps	Temperature :	21~24°C
Test Channel :	00 and 78	Relative Humidity :	49~51%
		Test Engineer :	Lion Ran

**Low Band Edge Plot on Channel 00**

Date: 9.MAR.2019 20:17:13

**High Band Edge Plot on Channel 78**


Date: 9.MAR.2019 20:16:30



## 3.6.6 Test Result of Conducted Hopping Mode Band Edges


Test Mode :	1Mbps	Temperature :	21~24℃
Test Engineer :	Lion Ran	Relative Humidity :	49~51%

Hopping Mode Low Band Edge Plot



Date: 9.MAR.2019 20:11:26


Hopping Mode High Band Edge Plot




Date: 9.MAR.2019 20:11:54



Test Mode :	2Mbps	Temperature :	21~24°C
Test Engineer :	Lion Ran	Relative Humidity :	49~51%

**Hopping Mode Low Band Edge Plot**


Date: 9.MAR.2019 20:13:46

**Hopping Mode High Band Edge Plot**


Date: 9.MAR.2019 20:12:42



Test Mode :	3Mbps	Temperature :	21~24°C
Test Engineer :	Lion Ran	Relative Humidity :	49~51%

**Hopping Mode Low Band Edge Plot**

Date: 9.MAR.2019 20:14:37

**Hopping Mode High Band Edge Plot**

Date: 9.MAR.2019 20:15:34

## 3.7 Conducted Spurious Emission Measurement

### 3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


### 3.7.4 Test Setup



### 3.7.5 Test Result of Conducted Spurious Emission


Test Mode :	1Mbps	Temperature :	21~24℃
Test Channel :	00	Relative Humidity :	49~51%
		Test Engineer :	Lion Ran

**CSE Plot on Ch 00 between 30MHz ~ 3 GHz**



Date: 9.MAR.2019 20:35:26

**1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz**




Date: 9.MAR.2019 20:35:54






CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 9.MAR.2019 20:32:54


CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 9.MAR.2019 20:33:21




CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 9.MAR.2019 20:48:52


CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 9.MAR.2019 20:49:19



Test Mode :	2Mbps	Temperature :	21~24°C
Test Channel :	00	Relative Humidity :	49~51%
		Test Engineer :	Lion Ran

**CSE Plot on Ch 00 between 30MHz ~ 3 GHz**


Date: 9.MAR.2019 20:41:30

**CSE Plot on Ch 00 between 2 GHz ~ 25 GHz**

Date: 9.MAR.2019 20:41:57




CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 9.MAR.2019 20:31:44


CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 9.MAR.2019 20:32:11




CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 9.MAR.2019 20:46:09


CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 9.MAR.2019 20:47:51



Test Mode :	3Mbps	Temperature :	21~24°C
Test Channel :	00	Relative Humidity :	49~51%
		Test Engineer :	Lion Ran

**CSE Plot on Ch 00 between 30MHz ~ 3 GHz**


Date: 9.MAR.2019 20:42:48

**CSE Plot on Ch 00 between 2 GHz ~ 25 GHz**

Date: 9.MAR.2019 20:43:16




CSE Plot on Ch 39 between 30MHz ~ 3 GHz




Date: 9.MAR.2019 20:28:15


CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 9.MAR.2019 20:28:43

**CSE Plot on Ch 78 between 30MHz ~ 3 GHz**


Date: 9.MAR.2019 20:43:56

**CSE Plot on Ch 78 between 2 GHz ~ 25 GHz**


Date: 9.MAR.2019 20:44:25



### 3.8 Radiated Band Edges and Spurious Emission Measurement

#### 3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


### 3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz, RBW=1MHz for  $f > 1$ GHz ; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
  - (3) For average measurement: use duty cycle correction factor method per 15.35(c).  
Duty cycle = On time/100 milliseconds  
On time =  $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$   
Where  $N_1$  is number of type 1 pulses,  $L_1$  is length of type 1 pulses, etc.  
Average Emission Level = Peak Emission Level +  $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from  $20 \log(\text{dwell time}/100\text{ms})$ . This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

### 3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





### **3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

### **3.8.6 Test Result of Radiated Spurious at Band Edges**

Please refer to Appendix B.

### **3.8.7 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)**

Please refer to Appendix B.

### **3.8.8 Duty cycle correction factor for average measurement**

Please refer to Appendix C.

### 3.9 AC Conducted Emission Measurement

#### 3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.9.4 Test Setup



### 3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix A.



## **3.10 Antenna Requirements**

### **3.10.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.10.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.10.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 07, 2018	Mar. 03, 2019~ Mar. 10, 2019	Aug. 06, 2019	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 14, 2019	Mar. 03, 2019~ Mar. 10, 2019	Jan. 13, 2020	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 14, 2019	Mar. 03, 2019~ Mar. 10, 2019	Jan. 13, 2020	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz; MAX x 30dBm	Aug. 06, 2018	Mar. 19, 2019	Aug. 05, 2019	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz~44G, MAX 30dB	Apr. 17, 2018	Mar. 19, 2019	Apr. 16, 2019	Radiation (03CH02-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 19, 2018	Mar. 19, 2019	Oct. 18, 2019	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	30MHz~2GHz	Dec. 29, 2018	Mar. 19, 2019	Dec. 28, 2019	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 27, 2019	Mar. 19, 2019	Jan. 26, 2020	Radiation (03CH02-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2025788	100MHz~18GHz	Apr. 17, 2018	Mar. 19, 2019	Apr. 16, 2019	Radiation (03CH02-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2019	Mar. 19, 2019	Jan. 04, 2020	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9KHz~1GHz	Aug. 06, 2018	Mar. 19, 2019	Aug. 05, 2019	Radiation (03CH02-KS)
Amplifier	Keysight	83017A	MY53270203	500MHz~26.5GHz	Apr. 18, 2018	Mar. 19, 2019	Apr. 17, 2019	Radiation (03CH02-KS)
Amplifier	MITEQ	TTA1840-35-HG	1887435	18~40GHz	Jan. 14, 2019	Mar. 19, 2019	Jan. 13, 2020	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Mar. 19, 2019	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Mar. 19, 2019	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Mar. 19, 2019	NCR	Radiation (03CH02-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 19, 2018	Mar. 01, 2019	Apr. 18, 2019	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 12, 2018	Mar. 01, 2019	Oct. 11, 2019	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Nov. 19, 2018	Mar. 01, 2019	Nov. 18, 2019	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2018	Mar. 01, 2019	Oct. 11, 2019	Conduction (CO01-KS)

NCR: No Calibration Required



## 5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage  $K=2$  to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.9dB
-------------------------------------------------------------------------	-------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.8dB
-------------------------------------------------------------------------	-------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)


Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.2dB
-------------------------------------------------------------------------	-------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.0dB
-------------------------------------------------------------------------	-------




## Appendix A. AC Conducted Emission Test Results





Test Engineer :	Amos Zhang	Temperature :	23.6~24.2℃
		Relative Humidity :	31~33%
Test Voltage :	120Vac / 60Hz	Phase :	Line




Site : CO01-KS  
Condition : FCC PART 15C LISN-L-181013-060103 LINE  
mode : Mode 1  
: 990010440004589 #10

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
18	1.772	34.08	-11.92	46.00	23.59	0.26	10.23	Average
19	2.033	45.39	-10.61	56.00	34.90	0.26	10.23	QP
20	2.033	37.09	-8.91	46.00	26.60	0.26	10.23	Average
21	2.309	47.99	-8.01	56.00	37.50	0.26	10.23	QP
22	2.309	38.69	-7.31	46.00	28.20	0.26	10.23	Average
23	2.540	50.10	-5.90	56.00	39.60	0.26	10.24	QP
24	2.540	41.00	-5.00	46.00	30.50	0.26	10.24	Average
25	2.794	51.30	-4.70	56.00	40.80	0.26	10.24	QP
26 *	2.794	42.00	-4.00	46.00	31.50	0.26	10.24	Average
27	3.041	48.01	-7.99	56.00	37.51	0.26	10.24	QP
28	3.041	39.01	-6.99	46.00	28.51	0.26	10.24	Average
29	3.381	45.31	-10.69	56.00	34.79	0.27	10.25	QP
30	3.381	36.71	-9.29	46.00	26.19	0.27	10.25	Average
31	3.681	44.02	-11.98	56.00	33.50	0.27	10.25	QP
32	3.681	35.02	-10.98	46.00	24.50	0.27	10.25	Average
33	4.049	41.32	-14.68	56.00	30.80	0.27	10.25	QP
34	4.049	31.72	-14.28	46.00	21.20	0.27	10.25	Average
35	11.438	43.54	-16.46	60.00	32.90	0.28	10.36	QP
36	11.438	31.94	-18.06	50.00	21.30	0.28	10.36	Average
37	17.661	41.19	-18.81	60.00	30.30	0.44	10.45	QP
38	17.661	26.09	-23.91	50.00	15.20	0.44	10.45	Average



Test Engineer :	Amos Zhang	Temperature :	23.6~24.2℃
		Relative Humidity :	31~33%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Site : CO01-KS  
Condition : FCC PART 15C LISN-N-181013-060103 NEUTRAL  
mode : Mode 1  
: 990010440004589 #10

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	2.023	40.95	-15.05	56.00	30.50	0.22	10.23	QP
2	2.023	31.95	-14.05	46.00	21.50	0.22	10.23	Average
3	2.178	41.55	-14.45	56.00	31.10	0.22	10.23	QP
4	2.178	33.25	-12.75	46.00	22.80	0.22	10.23	Average
5	2.409	42.65	-13.35	56.00	32.20	0.22	10.23	QP
6	2.409	34.95	-11.05	46.00	24.50	0.22	10.23	Average
7	2.608	44.96	-11.04	56.00	34.50	0.22	10.24	QP
8	2.608	37.06	-8.94	46.00	26.60	0.22	10.24	Average
9	2.736	45.36	-10.64	56.00	34.90	0.22	10.24	QP
10 *	2.736	37.66	-8.34	46.00	27.20	0.22	10.24	Average
11	2.946	42.66	-13.34	56.00	32.20	0.22	10.24	QP
12	2.946	34.66	-11.34	46.00	24.20	0.22	10.24	Average
13	3.190	41.56	-14.44	56.00	31.10	0.22	10.24	QP
14	3.190	33.76	-12.24	46.00	23.30	0.22	10.24	Average
15	3.603	38.77	-17.23	56.00	28.30	0.22	10.25	QP
16	3.603	30.67	-15.33	46.00	20.20	0.22	10.25	Average
17	4.598	36.08	-19.92	56.00	25.60	0.22	10.26	QP
18	4.598	24.68	-21.32	46.00	14.20	0.22	10.26	Average



## Appendix B. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BT CH00 2402MHz		2348.74	53.10	-20.90	74	50.14	32.1	5.43	34.57	153	2	P	H
	*	2348.74	28.31	-25.69	54	-	-	-	-	-	-	A	H
		2402	97.52	-	-	94.55	32	5.48	34.51	153	2	P	H
		2402	72.73	-	-	-	-	-	-	-	-	A	H
		2362.39	53.18	-20.82	74	50.25	32.07	5.43	34.57	122	125	P	V
	*	2362.39	28.39	-25.61	54	-	-	-	-	-	-	A	V
		2402	98.81	-	-	95.84	32	5.48	34.51	122	125	P	V
		2402	74.02	-	-	-	-	-	-	-	-	A	V
BT CH 78 2480MHz	*	2480	98.23	-	-	94.73	32.27	5.55	34.32	148	360	P	H
		2480	73.44	-	-	-	-	-	-	-	-	A	H
		2484.25	53.89	-20.11	74	50.39	32.27	5.55	34.32	148	360	P	H
		2484.25	29.10	-24.90	54	-	-	-	-	-	-	A	H
	*	2480	98.61	-	-	95.11	32.27	5.55	34.32	114	113	P	V
		2480	73.82	-	-	-	-	-	-	-	-	A	V
		2498.32	54.30	-19.70	74	50.8	32.2	5.55	34.25	114	113	P	V
		2498.32	29.51	-24.49	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



## 2.4GHz 2400~2483.5MHz

## BT (Harmonic @ 3m)

BT	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
BT CH 00 2402MHz		4806	41.18	-32.82	74	61.01	34.2	8.1	62.13	150	360	P	H
		4806	40.1	-33.9	74	59.93	34.2	8.1	62.13	150	0	P	V
BT CH 39 2441MHz		4884	38.69	-35.31	74	58.6	34.13	8.07	62.11	150	360	P	H
		7323	43.33	-30.67	74	59.75	36.6	9.75	62.77	150	360	P	H
		4882	38.54	-35.46	74	58.45	34.13	8.07	62.11	150	17	P	V
		7323	42.36	-31.64	74	58.78	36.6	9.75	62.77	150	17	P	V
BT CH 78 2480MHz		4962	39.27	-34.73	74	59.2	34.1	8.05	62.08	150	360	P	H
		7440	40.84	-33.16	74	57.38	36.4	9.84	62.78	150	360	P	H
		4960	40.02	-33.98	74	59.95	34.1	8.05	62.08	150	0	P	V
		7440	42.43	-31.57	74	58.97	36.4	9.84	62.78	150	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## Emission below 1GHz

## 2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
2.4GHz BT LF		33.88	17.23	-22.77	40	27.2	21.28	0.71	31.96	100	0	P	H
		47.46	13.48	-26.52	40	30.11	14.5	0.81	31.94	-	-	P	H
		104.69	13.61	-29.89	43.5	27.6	16.76	1.18	31.93	-	-	P	H
		161.92	14.61	-28.89	43.5	28.9	16.14	1.5	31.93	-	-	P	H
		220.12	14.46	-31.54	46	28.18	16.47	1.73	31.92	-	-	P	H
		746.83	23.5	-22.5	46	26.78	25.85	3.13	32.26	-	-	P	H
		30	20.4	-19.6	40	28.94	22.8	0.64	31.98	100	0	P	V
		46.49	19.81	-20.19	40	36.13	14.83	0.79	31.94	-	-	P	V
		101.78	14.89	-28.61	43.5	28.88	16.78	1.16	31.93	-	-	P	V
		157.07	15.19	-28.31	43.5	29.4	16.25	1.47	31.93	-	-	P	V
		562.53	21.71	-24.29	46	26.51	24.9	2.66	32.36	-	-	P	V
		842.86	24.54	-21.46	46	26.61	26.43	3.34	31.84	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>P</b> eak or <b>A</b> verage
H/V	<b>H</b> orizontal or <b>V</b> ertical





A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)


= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)


Both peak and average measured complies with the limit line, so test result is “PASS”.

## Appendix C. Duty Cycle Plots

### DH5 on time (One Pulse) Plot on Channel 39



### DH5 on time (Count Pulses) Plot on Channel 39



#### Note:

1. Worst case Duty cycle = on time/100 milliseconds =  $2 * 2.88 / 100 = 5.76 \%$
2. Worst case Duty cycle correction factor =  $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
3. DH5 has the highest duty cycle worst case and is reported.