



RF Exposure Evaluation Declaration

Product Name : Wireless Access Point

Model No. : AP410C

FCC ID : QXO-AP410CNB

Applicant : Extreme Networks, Inc

Address : 6480 Via Del Oro, San Jose, CA 95119

Date of Receipt : Apr. 11, 2022

Test Date : Apr. 12, 2022 ~ Apr. 27, 2022

Issued Date : May. 19, 2022

Report No. : 2230991R-RF-US-P20V02

Report Version : V1.1

NOTE: The EUT used in this report and the 1992128R-RF-US-P20V02report are the same model. The difference is that the EUT used this time removes the BLE chip. The output power test results are not worse than 1992128R-RF-US-P20V02, so the test data in this report refer to the data of 1992128R-RF-US-P20V02.

The test results presented in this report relate only to the object tested.

The measurement result is considered in conformance with the requirement if it is within the prescribed limit, It is not necessary to account the uncertainty associated with the measurement result, unless the specification, standard or customer have special requirements

This report shall not be reproduced, except in full, without the written approval of the Issuing CB Testing Laboratory

This report is not used for social proof in China (or Mainland China) market.

Test Report Certification


Issued Date: May. 19, 2022

Report No.: 2230991R-RF-US-P20V02




Product Name : Wireless Access Point
Applicant : Extreme Networks, Inc
Address : 6480 Via Del Oro, San Jose, CA 95119
Manufacturer : Extreme Networks, Inc
Address : 6480 Via Del Oro, San Jose, CA 95119
Model No. : AP410C
Brand : Extreme Networks
FCC ID : QXO-AP410CNB
EUT Voltage : DC 37~57V
Applicable Standard : KDB 447498D01V06
FCC Part1.1310
Test Result : Complied
Performed Location : DEKRA Testing and Certification (Suzhou) Co., Ltd.
No.99 Hongye Rd., Suzhou Industrial Park, Suzhou,
215006, Jiangsu, China
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
FCC Designation Number: CN1199

Documented By :



(Project Engineer: Tim Cao)

Approved By :



(Engineer Supervisor: Jack Zhang)

1. RF Exposure Evaluation

1.1.Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product	:	Wireless Access Point
Test Item	:	RF Exposure Evaluation
Test Site	:	AC-6

Antenna Information:

WLAN 2.4GHz:

Antenna Model No.	N/A					
Antenna Manufacturer	N/A					
Antenna Delivery	<input checked="" type="checkbox"/>	1*TX+1*RX	<input checked="" type="checkbox"/>	2*TX+2*RX	<input type="checkbox"/>	3*TX+3*RX
Antenna Technology	<input checked="" type="checkbox"/>	SISO				
	<input checked="" type="checkbox"/>	MIMO	<input type="checkbox"/>	Basic methodology		
			<input type="checkbox"/>	Sectorized antenna systems		
			<input type="checkbox"/>	Cross-polarized antennas		
			<input type="checkbox"/>	Unequal antenna gains, with equal transmit powers		
			<input checked="" type="checkbox"/>	Spatial Multiplexing		
			<input checked="" type="checkbox"/>	Cyclic Delay Diversity (CDD)		
Antenna Type	PIFA					
Antenna Gain(Radio 1)						
Antenna Technology		Ant Gain (dBi)				
Ant 4(Radio 1)		4.00				
Antenna Gain(Radio 2)						
Antenna Technology		Ant Gain (dBi)				
<input checked="" type="checkbox"/>	SISO	<input checked="" type="checkbox"/>	Ant1 (Radio 2)	3.80		
		<input checked="" type="checkbox"/>	Ant2 (Radio 2)	3.90		
<input checked="" type="checkbox"/>	CDD		3.90dBi for Power; 6.91dBi for PSD			
<input checked="" type="checkbox"/>	Beam-forming		6.91dBi for Power; 6.91dBi for PSD			

WLAN 5GHz:

Antenna Model No.	N/A									
Antenna Manufacturer	N/A									
Antenna Delivery	<input checked="" type="checkbox"/>	1*TX+1*RX	<input checked="" type="checkbox"/>	2*TX+2*RX	<input checked="" type="checkbox"/>	3*TX+3*RX	<input checked="" type="checkbox"/>	4*TX+4*RX		
Antenna Technology	<input checked="" type="checkbox"/>	SISO								
	<input checked="" type="checkbox"/>	MIMO	<input type="checkbox"/>	Basic methodology						
			<input type="checkbox"/>	Sectorized antenna systems						
			<input type="checkbox"/>	Cross-polarized antennas						
			<input type="checkbox"/>	Unequal antenna gains, with equal transmit powers						
			<input checked="" type="checkbox"/>	Spatial Multiplexing						
			<input checked="" type="checkbox"/>	Cyclic Delay Diversity (CDD)						
Antenna Type	PIFA									
Antenna Gain(Radio 1)										
Antenna Technology	Ant Gain (dBi)									
Ant 4(Radio 1)	3.3									
Antenna Gain(Radio 2)										
Antenna Technology	Ant Gain (dBi)									
<input checked="" type="checkbox"/>	SISO	<input checked="" type="checkbox"/>	Ant1 (Radio 2)	4.5						
<input checked="" type="checkbox"/>		Ant2 (Radio 2)	4.7							
<input checked="" type="checkbox"/>	CDD			4.7dBi for Power; 7.71dBi for PSD						
<input checked="" type="checkbox"/>	Beam-forming			7.71dBi for Power; 7.71dBi for PSD						

Antenna Gain(Radio 3)				
Antenna Technology			Ant Gain (dBi)	
<input checked="" type="checkbox"/>	SISO	<input checked="" type="checkbox"/>	Ant3 (Radio 3)	4.7
		<input checked="" type="checkbox"/>	Ant5 (Radio 3)	4.6
		<input checked="" type="checkbox"/>	Ant6 (Radio 3)	4.6
		<input checked="" type="checkbox"/>	Ant7 (Radio 3)	4.7
<input checked="" type="checkbox"/>	2*2 CDD			4.7dBi for Power; 7.71dBi for PSD
<input checked="" type="checkbox"/>	2*2 Beam-forming			7.71dBi for Power; 7.71dBi for PSD
<input checked="" type="checkbox"/>	4*4 CDD			4.7dBi for Power; 10.72dBi for PSD
<input checked="" type="checkbox"/>	4*4 Beam-forming			10.72dBi for Power; 10.72dBi for PSD

Note: The device supports 3 radios, radio 1(1*1 2.4GHz & 1*1 5GHz full band); radio 2(2*2 2.4GHz & 2*2 5GHz low band); radio 3(4*4 5GHz full band), and radio 2 & 3 can works with Dual 2.4GHz & 5GHz mode and Dual 5GHz mode. As the 5GHz high band filter is different between two modes, additional Radio 3 5GHz high band mode is tested for compliance.

Dual 2.4GHz & 5GHz mode: Radio 2(2.4GHz 2*2) + Radio 3(5GHz full band 4*4)

Dual 5GHz mode: Radio 2(5GHz low band 2*2) + Radio 3(5GHz high band 4*4)

Power Density

Standalone modes:

AP410C:

Wireless Radio	Test Mode	Frequency Band (MHz)	Maximum EIRP (dBm)	Power Density at R = 20cm (mW/cm ²)	Power Density Limit at R = 20 cm (mW/cm ²)
Radio 1	802.11b/g/n/ac/ax	2400 ~ 2483.5	26.93	0.098	1.0
Radio 2	802.11b/g/n/ac/ax	2400 ~ 2483.5	31.8	0.301	1.0
Radio 1	802.11a/n/ac/ax	5150 ~ 5850	23.76	0.047	1.0
Radio 2	802.11a/n/ac/ax	5150 ~ 5350	29.63	0.183	1.0
Radio 3 Full band	802.11a/n/ac/ax	5150 ~ 5850	34.61	0.575	1.0
Radio 3 High band	802.11a/n/ac/ax	5470 ~ 5850	33.83	0.481	1.0

Simultaneous transmission:

Wireless Configure	Frequency Range (MHz)	Maximum EIRP (dBm)			Limit of Power Density S(mW/cm ²)	Power Density Rate			Total Rate	Limit
		Radio 1	Radio 2	Radio 3		Radio 1	Radio 2	Radio 3		
Radio 1 + Radio 2(2.4GHz Only) + Radio 3(5GHz Full Band)	2.4G+5G	26.93	31.8	34.61	1.0	0.098	0.301	0.575	0.974	1
Radio 1 + Radio 2(5GHz Low Band) + Radio 3(5GHz High Band)	2.4G+5G	26.93	29.63	33.83	1.0	0.098	0.183	0.481	0.761	1

The EUT support simultaneously transmit with Radio 1 + Radio 2+ Radio 3 .

The worst combination should be shown in the report. The simultaneously safety distance is 20cm for installed for Wireless Access Point without any other radio equipment.

_____ The End _____