

## MPE Calculation

|                       |  |
|-----------------------|--|
| Applicant:            | Guangdong Wangjia Intelligent Robot Co., Ltd.  |
| Address:              | 3rd Floor, No. 2 Plant, Yuxinfeng Industrial Park Phase I, Chigan Junma Road, Humen Town, Dongguan, Guangdong, China |
| Product:              | Robotic Vacuum Cleaner   |
| FCC ID:               | 2AVYJ-J300   |
| Model No.:            | J300; J300S; J300U; J300SU; J301; J301S; J301U; J301SU; J302; J302S; J302U; J302SU; J306; J306S; J306U; J306SU       |
| Reference RF report # | 68.910.20.0038.01 for Wi-Fi report   |

According to subpart 15.247(i) and subpart §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

| (B) Limits for General Population/Uncontrolled Exposure |                               |                               |                                     |                          |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| Frequency Range (MHz)                                   | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (minutes) |
| 0.3–1.34  | 614                           | 1.63                          | *(100)                              | 30                       |
| 1.34–30   | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |
| 30–300  | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300–1,500   | /                             | /                             | f/1500                              | 30                       |
| 1,500–100,000   | /                             | /                             | 1.0                                 | 30                       |

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);



## Calculated Data:

|   |       |
|---|-------|
| Maximum peak output power at antenna input terminal (dBm):                  | 12.63 |
| Maximum peak output power at antenna input terminal (mW):                   | 18.32 |
| Prediction distance (cm):   | 20    |
| Antenna Gain, typical (dBi):  | 2.0   |
| Maximum Antenna Gain (numeric):   | 1.58  |
| The worst case is power density at predication frequency at 20 cm (mW/cm2): | 0.058 |
| MPE limit for general population exposure at prediction frequency (mW/cm2): | 1.0   |
| 0.058 (mW/cm2) < 1 (mW/cm2)   |       |

Result: Compliant

TUV SUD China, Shenzhen Branch

Reviewed by:



Dawi Xu / EMC Project Manager

Date: 2021-03-26

Prepared By:



Myron Yu / EMC Project Engineer

Date: 2021-03-26