


FCC PART 15.247 TEST REPORT

For

Meizhou Guo Wei Electronics Co., Ltd

AD1 Section, Economic Development Area, Dongsheng Industrial District, Meizhou, Guangdong, China.

FCC ID: 2ARRB-F80X79BS

Report Type: Original Report	Product Type: Digital Cordless Telephone
Report Number: SZ1210209-04496E-00A	
Report Date: 2021-03-31	
Jimmy Xiao 	
Reviewed By: RF Engineer	
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 5F(B-West) ,6F,7F,the 3rd Phase of Wan Li Industrial Building D,Shihua Rd, FuTian Free Trade Zone, Shenzhen, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
SPECIAL ACCESSORIES	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
TEST EQUIPMENT LIST	9
FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	10
APPLICABLE STANDARD	10
RESULT	10
FCC §15.203 – ANTENNA REQUIREMENT	12
APPLICABLE STANDARD	12
ANTENNA CONNECTOR CONSTRUCTION	12
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	13
APPLICABLE STANDARD	13
EUT SETUP	13
EMI TEST RECEIVER SETUP	13
TEST PROCEDURE	13
CORRECTED FACTOR & MARGIN CALCULATION	14
TEST DATA	14
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS	19
APPLICABLE STANDARD	19
EUT SETUP	19
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	20
TEST PROCEDURE	20
CORRECTED AMPLITUDE & MARGIN CALCULATION	20
TEST DATA	20
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	28
APPLICABLE STANDARD	28
TEST PROCEDURE	28
TEST DATA	28
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH	29
APPLICABLE STANDARD	29
TEST PROCEDURE	29
TEST DATA	29

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	30
APPLICABLE STANDARD	30
TEST PROCEDURE	30
TEST DATA	30
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	31
APPLICABLE STANDARD	31
TEST PROCEDURE	31
TEST DATA	31
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	32
APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST DATA	32
FCC §15.247(d) - BAND EDGES TESTING	33
APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST DATA	33
APPENDIX	34
APPENDIX A: 20dB EMISSION BANDWIDTH.....	34
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	38
APPENDIX C: MAXIMUM CONDUCTED PEAK OUTPUT POWER.....	42
APPENDIX D: CARRIER FREQUENCY SEPARATION	46
APPENDIX E: TIME OF OCCUPANCY	48
APPENDIX F: NUMBER OF HOPPING CHANNELS	55
APPENDIX G: BAND EDGE MEASUREMENTS	57

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Digital Cordless Telephone
Tested Model	Motorola D871-B
Frequency Range	Bluetooth: 2402~2480MHz
Maximum conducted Peak output power	Bluetooth: 3.19dBm
Modulation Technique	Bluetooth: GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna Specification*	0dBi(provided by the applicant)
Voltage Range	DC 6.0V from adapter
Date of Test	2021-02-23 to 2021-03-24
Sample serial number	SZ1210209-04496E-RF-S1(Assigned by BACL, Shenzhen)
Received date	2021-02-09
Sample/EUT Status	Good condition
Adapter1 information	Model: BLJ05W060040P-UA Input: AC 100-240V~50/60Hz, 0.2A Output: DC 6.0V, 400mA
Adapter2 information	Model: HJ-0600400A1-US Input: AC 100-240V~50/60Hz, 0.15A Max Output: DC 6.0V, 400mA

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters. Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.73dB
RF conducted test with spectrum		±1.6dB
AC Power Lines Conducted Emissions		±1.95dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±1 °C
Humidity		±6%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) ,6F,7F,the 3rd Phase of Wan Li Industrial Building D,Shihua Rd, FuTian Free Trade Zone, Shenzhen, China

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

EUT Exercise Software

Testing in an engineering mode then controlled by the CMW500. The power level is default*.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Meizhou Guo Wei Electronics Co., Ltd.	Handset	Motorola D871-HS	Unknown
Rohde & Schwarz	Wideband Radio Communication Tester	CMW500	1201.002K50-116218-U

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-shielded Un-Detachable AC Cable	1.2	Socket	Mains
Un-shielded Un-Detachable DC Cable	1.5	Adapter	EUT

Block Diagram of Test Setup

For conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §2.1091	Maximum Permissible Exposure(MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band edges	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2020/08/04	2021/08/03
Rohde & Schwarz	LISN	ENV216	101613	2020/08/04	2021/08/03
Rohde & Schwarz	Transient Limitor	ESH3Z2	DE25985	2020/11/29	2021/11/28
Unknown	CE Cable	CE Cable	UF A210B-1-0720-504504	2020/11/29	2021/11/28
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
Radiated Emission Test					
R&S	EMI Test Receiver	ESR3	102455	2020/08/04	2021/08/03
Sonoma instrument	Pre-amplifier	310 N	186238	2020/08/04	2021/08/03
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2020/12/22	2023/12/21
Cable 2	RF Cable 2	F-03-EM197	2020/11/29	2020/11/28	2021/11/28
Cable	Chamber Cable 1	F-03-EM236	2020/11/29	2020/11/28	2021/11/28
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR
Rohde & Schwarz	Spectrum Analyzer	FSV40-N	102259	2020/08/04	2021/08/03
COM-POWER	Pre-amplifier	PA-122	181919	2020/11/29	2021/11/28
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2020/11/29	2021/11/28
Sunol Sciences	Horn Antenna	3115	9107-3694	2021/01/15	2024/01/14
Insulted Wire Inc.	RF Cable	SPS-2503-3150	02222010	2020/11/29	2021/11/28
Unknown	RF Cable	W1101-EQ1 OUT	F-19-EM005	2020/11/29	2021/11/28
SNSD	Band Reject filter	BSF2402-2480MN-0898-001	2.4G filter	2020/04/20	2021/04/20
Ducommun Technologies	Horn antenna	ARH-4223-02	1007726-021304	2020/12/06	2023/12/05
RF Conducted Test					
Tonscend Corporation	RF control Unit	JS0806-2	19D8060154	2020/08/04	2021/08/03
Rohde & Schwarz	Signal and Spectrum Analyzer	FSV40	101473	2020/08/04	2021/08/03
Unknown	RF Cable	Unknown	2301 276	2020/11/29	2021/11/28

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Frequency (MHz)	Antenna Gain		Tune up conducted power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2402-2480	0	1.0	3.5	2.24	20	0.0004	1
1921.536 - 1928.448	0	1.0	20.5	112.2	20	0.0223	1

Note: 1. The tune up conducted power was declared by the applicant
 2. The Bluetooth can transmit with DECT function at the same time.

Simultaneous transmitting consideration:

The ratio= $MPE_{\text{Bluetooth}}/\text{limit} + MPE_{\text{DECT}}/\text{limit} = 0.0004 + 0.0223 = 0.0227 < 1.0$

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Pass

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 0dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the device was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$


Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	65 %
ATM Pressure:	101.0 kPa

The testing was performed by Haiguo Li on 2021-02-23.


Test mode: Transmitting & Charging

*For Adapter1 (BLJ05W060040P-UA)***AC 120V/60 Hz, Line****Final Result 1**

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.166501	49.3	9.000	L1	19.9	15.8	65.1
0.178500	50.8	9.000	L1	19.9	13.8	64.6
0.189500	46.7	9.000	L1	19.8	17.4	64.1
0.221500	45.3	9.000	L1	19.8	17.5	62.8
0.309350	41.7	9.000	L1	19.7	18.3	60.0
0.407790	41.0	9.000	L1	19.9	16.7	57.7

Final Result 2


Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.166501	33.6	9.000	L1	19.9	21.5	55.1
0.178500	33.5	9.000	L1	19.9	21.1	54.6
0.189500	30.6	9.000	L1	19.8	23.5	54.1
0.221500	28.4	9.000	L1	19.8	24.4	52.8
0.309350	26.7	9.000	L1	19.7	23.3	50.0
0.407790	31.7	9.000	L1	19.9	16.0	47.7

AC 120V/60 Hz, Neutral**Final Result 1**

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.169500	47.5	9.000	N	19.8	17.5	65.0
0.173500	49.9	9.000	N	19.8	14.9	64.8
0.221500	43.7	9.000	N	19.8	19.1	62.8
0.309350	42.0	9.000	N	19.7	18.0	60.0
0.411730	46.4	9.000	N	19.8	11.2	57.6
28.648250	42.4	9.000	N	20.2	17.6	60.0

Final Result 2


Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.418000	35.0	9.000	N	19.8	12.5	47.5
0.450000	30.9	9.000	N	19.8	16.0	46.9
17.190000	17.7	9.000	N	20.2	32.3	50.0
21.486000	39.6	9.000	N	20.4	10.4	50.0
25.070000	36.9	9.000	N	20.3	13.1	50.0
28.650000	36.0	9.000	N	20.2	14.0	50.0

*For Adapter2 (HJ-0600400A1-US)***AC 120V/60 Hz, Line****Final Result 1**

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.837370	35.5	9.000	L1	19.8	20.5	56.0
0.951930	36.7	9.000	L1	19.8	19.3	56.0
1.049510	36.2	9.000	L1	19.9	19.8	56.0
1.164450	37.8	9.000	L1	19.8	18.2	56.0
1.381570	36.3	9.000	L1	19.8	19.7	56.0
1.582510	36.1	9.000	L1	19.8	19.9	56.0

Final Result 2

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.837370	24.3	9.000	L1	19.8	21.7	46.0
0.951930	25.1	9.000	L1	19.8	20.9	46.0
1.049510	25.8	9.000	L1	19.9	20.2	46.0
1.164450	26.7	9.000	L1	19.8	19.3	46.0
1.381570	26.5	9.000	L1	19.8	19.5	46.0
1.582510	26.0	9.000	L1	19.8	20.0	46.0

AC 120V/60 Hz, Neutral**Final Result 1**



Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
1.069770	40.4	9.000	N	19.8	15.6	56.0
1.223490	41.4	9.000	N	19.8	14.6	56.0
1.370250	40.1	9.000	N	19.8	15.9	56.0
1.440070	40.3	9.000	N	19.8	15.7	56.0
1.696590	39.7	9.000	N	19.8	16.3	56.0
1.712050	39.9	9.000	N	19.8	16.1	56.0

Final Result 2

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.902000	29.1	9.000	N	19.7	16.9	46.0
1.126000	30.4	9.000	N	19.8	15.6	46.0
9.454000	34.5	9.000	N	19.9	15.5	50.0
21.486000	41.8	9.000	N	20.4	8.2	50.0
25.066000	40.3	9.000	N	20.3	9.7	50.0
28.650000	36.1	9.000	N	20.2	13.9	50.0

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS**Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1 MHz	10 Hz	/	Average

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data

Environmental Conditions


Temperature:	23~24.8 °C
Relative Humidity:	51~58 %
ATM Pressure:	101.2~101.3 kPa

The testing was performed by Kilroy Deng on 2021-02-25 for below 1GHz and Alan He on 2021-03-22 for above 1GHz.

EUT operation mode: Transmitting


30 MHz~1 GHz: (the worst case is GFSK Mode, High channel)

For Adapter1 (BLJ05W060040P-UA)



Final Result

Frequency (MHz)	QuasiPeak (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
30.275860	21.13	40.00	18.87	171.0	V	118.0	2.2
34.780125	18.82	40.00	21.18	111.0	V	128.0	-1.1
290.745875	30.74	46.00	15.26	174.0	H	81.0	-4.3
387.069250	32.19	46.00	13.81	104.0	H	344.0	-1.7
711.812125	25.11	46.00	20.89	263.0	H	205.0	4.7
876.624875	26.95	46.00	19.05	247.0	V	355.0	6.6

For Adapter2 (HJ-0600400A1-US)

Final Result

Frequency (MHz)	QuasiPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
30.201906	20.45	40.00	19.55	368.0	H	157.0	2.3
35.873875	19.45	40.00	20.55	223.0	V	204.0	-1.9
221.203125	32.56	46.00	13.44	104.0	V	129.0	-5.4
388.854000	30.11	46.00	15.89	114.0	H	97.0	-1.7
580.614000	33.21	46.00	12.79	195.0	H	72.0	2.4
677.626375	39.94	46.00	6.06	109.0	V	0.0	4.1

1 GHz - 25 GHz: (Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK mode, the worst case is GFSK Mode)

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2402 MHz)									
2389.94	27.95	PK	282	1.5	H	31.87	59.82	74	14.18
2389.94	13.57	Ave.	282	1.5	H	31.87	45.44	54	8.56
2491.60	28.55	PK	251	2.4	H	32.13	60.68	74	13.32
2491.60	13.65	Ave.	251	2.4	H	32.13	45.78	54	8.22
4804.00	53.57	PK	350	2.2	H	6.28	59.85	74	14.15
4804.00	38.41	Ave.	350	2.2	H	6.28	44.69	54	9.31
Middle Channel (2441 MHz)									
4882.00	52.31	PK	298	1.3	H	6.76	59.07	74	14.93
4882.00	36.89	Ave.	297	2.2	H	6.76	43.65	54	10.35
High Channel (2480 MHz)									
2313.18	28.06	PK	177	1.0	H	31.64	59.70	74	14.30
2313.18	13.56	Ave.	177	1.0	H	31.64	45.20	54	8.80
2497.21	28.60	PK	157	1.3	H	32.13	60.73	74	13.27
2497.21	13.63	Ave.	157	1.3	H	32.13	45.76	54	8.24
4960.00	54.43	PK	5	1.2	H	6.80	61.23	74	12.77
4960.00	39.58	Ave.	93	1.9	H	6.80	46.38	54	7.62

Note:


Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading


Margin = Limit - Corrected. Amplitude

The other spurious emission which is 20dB to the limit was not recorded.

Pre-scan with High channel Peak Horizontal




Date: 22.MAR.2021 09:41:44




Date: 22.MAR.2021 10:30:53

Vertical




Date: 22.MAR.2021 09:30:15




Date: 22.MAR.2021 10:20:09

Average Horizontal




Date: 22.MAR.2021 09:46:37




Date: 22.MAR.2021 10:34:51

Vertical



Date: 22.MAR.2021 09:36:19



Date: 22.MAR.2021 10:25:51

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Test Procedure

1. Set the EUT in transmitting mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Bravos Zhao on 2021-03-24.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH**Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Bravos Zhao on 2021-03-24.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Bravos Zhao on 2021-03-24.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses

Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Bravos Zhao on 2021-03-24.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Bravos Zhao on 2021-03-24.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

g

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Bravos Zhao on 2021-03-24.

EUT operation mode: Transmitting


Test Result: Compliant. Please refer to the Appendix.

APPENDIX


Appendix A: 20dB Emission Bandwidth Test Result

TestMode	Antenna	Channel	20db EBW[MHz]	Limit[MHz]	Verdict
DH1	Ant1	2402	0.897	---	PASS
		2441	0.891	---	PASS
		2480	0.891	---	PASS
2DH1	Ant1	2402	1.221	---	PASS
		2441	1.221	---	PASS
		2480	1.233	---	PASS
3DH1	Ant1	2402	1.233	---	PASS
		2441	1.233	---	PASS
		2480	1.260	---	PASS

Test Graphs




2DH1_Ant1_2402




Date: 24.MAR.2021 09:54:26

2DH1_Ant1_2441




Date: 24.MAR.2021 09:54:53

2DH1_Ant1_2480




Date: 24.MAR.2021 09:55:11

3DH1_Ant1_2402



Date: 24.MAR.2021 09:55:38

3DH1_Ant1_2441



Date: 24.MAR.2021 09:56:05

3DH1_Ant1_2480





Date: 24.MAR.2021 09:56:23

**Appendix B: Occupied Channel Bandwidth
Test Result**

TestMode	Antenna	Channel	OCB [MHz]	Limit[MHz]	Verdict
DH1	Ant1	2402	0.836	---	PASS
		2441	0.833	---	PASS
		2480	0.845	---	PASS
2DH1	Ant1	2402	1.154	---	PASS
		2441	1.151	---	PASS
		2480	1.148	---	PASS
3DH1	Ant1	2402	1.151	---	PASS
		2441	1.145	---	PASS
		2480	1.154	---	PASS

Test Graphs





3DH1 Ant1 2402



3DH1 Ant1 2441




3DH1 Ant1 2480




**Appendix C: Maximum conducted Peak output power
Test Result**

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH1	Ant1	2402	2.15	<=20.97	PASS
		2441	1.49	<=20.97	PASS
		2480	3.19	<=20.97	PASS
2DH1	Ant1	2402	0.79	<=20.97	PASS
		2441	0.13	<=20.97	PASS
		2480	1.86	<=20.97	PASS
3DH1	Ant1	2402	1.35	<=20.97	PASS
		2441	0.67	<=20.97	PASS
		2480	2.43	<=20.97	PASS


Test Graphs




2DH1_Ant1_2402




2DH1_Ant1_2441




2DH1_Ant1_2480




3DH1_Ant1_2402



3DH1_Ant1_2441



3DH1_Ant1_2480




**Appendix D: Carrier frequency separation
Test Result**

TestMode	Antenna	Channel	Result[MHz]	Limit[MHz]	Verdict
DH1	Ant1	Hop	1.003	≥ 0.598	PASS
2DH1	Ant1	Hop	1.000	≥ 0.822	PASS
3DH1	Ant1	Hop	1.003	≥ 0.840	PASS

Note: the limit = $(2/3) * 20\text{dB}$ bandwidth

Test Graphs



**Appendix E: Time of occupancy
Test Result**


TestMode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.39	310	0.121	<=0.4	PASS
DH3	Ant1	Hop	1.64	140	0.229	<=0.4	PASS
DH5	Ant1	Hop	2.88	100	0.288	<=0.4	PASS
2DH1	Ant1	Hop	0.40	320	0.128	<=0.4	PASS
2DH3	Ant1	Hop	1.65	110	0.181	<=0.4	PASS
2DH5	Ant1	Hop	2.89	110	0.318	<=0.4	PASS
3DH1	Ant1	Hop	0.40	290	0.117	<=0.4	PASS
3DH3	Ant1	Hop	1.64	130	0.214	<=0.4	PASS
3DH5	Ant1	Hop	2.89	100	0.289	<=0.4	PASS


Note 1: A period time= $0.4 \times 79 = 31.6$ (S), Result=BurstWidth*Totalhops

Note 2: Totalhops=Hopping Number in $3.16\text{s} \times 10$



Note 3: Hopping Number in 3.16s=Total of highest signals in 3.16s(Second high signals were other channel)

Test Graphs







DH5_Ant1_Hop



2DH1_Ant1_Hop




Date: 24.MAR.2021 10:10:02




Date: 24.MAR.2021 10:10:07

2DH3_Ant1_Hop




Date: 24.MAR.2021 10:10:16




Date: 24.MAR.2021 10:10:22

2DH5_Ant1_Hop




Date: 24.MAR.2021 10:10:31




Date: 24.MAR.2021 10:10:36

3DH1 Ant1 Hop




Date: 24.MAR.2021 10:14:00




Date: 24.MAR.2021 10:14:05



3DH3 Ant1 Hop



Date: 24.MAR.2021 10:17:59




3DH5_Ant1_Hop




**Appendix F: Number of hopping channels
Test Result**

TestMode	Antenna	Channel	Result[Num]	Limit[Num]	Verdict
DH1	Ant1	Hop	79	≥ 15	PASS
2DH1	Ant1	Hop	79	≥ 15	PASS
3DH1	Ant1	Hop	79	≥ 15	PASS


Test Graphs



Appendix G: Band edge measurements Test Graphs




DH1 Ant1 High Hop 2480




Date: 24.MAR.2021 10:17:27

2DH1 Ant1 Low 2402




Date: 24.MAR.2021 09:54:44

2DH1 Ant1 High 2480




Date: 24.MAR.2021 09:55:29

2DH1 Ant1 Low Hop 2402




Date: 24.MAR.2021 10:08:47

2DH1 Ant1 High Hop 2480




Date: 24.MAR.2021 10:10:46

3DH1 Ant1 Low 2402




Date: 24.MAR.2021 09:55:56

3DH1 Ant1 High 2480




Date: 24.MAR.2021 09:56:42

3DH1 Ant1 Low Hop 2402



Date: 24.MAR.2021 10:17:47

3DH1 Ant1 High Hop 2480



Date: 24.MAR.2021 10:14:50

***** END OF REPORT *****