

# FCC ID PER PART 15.227 EMI MEASUREMENT AND TEST REPORT

For

**Sunrex Technology (Jiangsu) Co., Ltd.**

Fenhu Economic Development Zone  
Wujiang, China

**FCC ID: J751051**

March 10, 2003

<b>This Report Concerns:</b> <input checked="" type="checkbox"/> Original Report	<b>Equipment Type:</b> Cordless Mouse, ITE
<b>Test Engineer:</b> Steve Giron	
<b>Report No.:</b> R0301212	
<b>Test Date:</b> February 26, 2003	
<b>Reviewed By:</b> Hans Mellberg	
<b>Prepared By:</b> Bay Area Compliance Laboratory Corporation (BACL) 230 Commercial Street Sunnyvale, CA 94085 Tel: (408) 732-9162 Fax: (408) 732-9164	

**Note:** This test report is specially limited to the above client company and the product model only. It may not be duplicated without prior written consent of Bay Area Compliance Laboratory Corporation. This report **must not** be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

**TABLE OF CONTENTS**

<b>1 - GENERAL INFORMATION.....</b>	<b>3</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	3
1.2 OBJECTIVE .....	3
1.3 RELATED SUBMITTAL(S)/GRANT(S).....	3
1.4 TEST METHODOLOGY .....	3
1.5 TEST FACILITY .....	3
1.6 TEST EQUIPMENT LIST .....	4
<b>2 - SYSTEM TEST CONFIGURATION.....</b>	<b>5</b>
2.1 JUSTIFICATION .....	5
2.2 SCHEMATICS AND BLOCK DIAGRAM .....	5
2.3 EQUIPMENT MODIFICATIONS .....	5
2.4 TEST SETUP CONFIGURATION .....	5
<b>3 - SUMMARY OF TEST RESULTS.....</b>	<b>6</b>
<b>4 - RADIATED EMISSION TEST .....</b>	<b>7</b>
4.1 MEASUREMENT UNCERTAINTY .....	7
4.2 EUT SETUP .....	7
4.3 SPECTRUM ANALYZER SETUP .....	7
4.4 TEST PROCEDURE .....	8
4.5 CORRECTED AMPLITUDE & MARGIN CALCULATION .....	8
4.6 SUMMARY OF TEST RESULTS .....	8
4.7 RADIATED EMISSIONS TEST RESULT DATA .....	8

---

## 1 - GENERAL INFORMATION

---

### 1.1 Product Description for Equipment Under Test (EUT)

The *Sunrex Technology (Jiangsu) Co., Ltd.* 's product, model *KBR-1051* or the "EUT" as referred to in this report is a wireless mouse. The transmitter part measures approximately 4.75" L x 2.75" W x 1.75" H.

*\* The test data gathered is from typical production samples provided by the manufacturer.*

### 1.2 Objective

This Type approval report is prepared on behalf of *Sunrex Technology (Jiangsu) Co., Ltd.* in accordance with Part 2, Subpart J, and Part 15, Subparts A and C of the Federal Communication Commissions rules.

The objective of the manufacturer is to demonstrate compliance with FCC rules, Part 15, sec 15.209 and sec 15.227.

### 1.3 Related Submittal(s)/Grant(s)

No Related Submittals.

### 1.4 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-1992, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. All radiated and conducted emissions measurement was performed at BACL. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

### 1.5 Test Facility

The Open Area Test site used by BACL to collect radiated and conducted emission measurement data is located in the back parking lot of the building at 230 Commercial Street, Sunnyvale, California, USA.

Test site at BACL has been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports has been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997 and Article 8 of the VCCI regulations on December 25, 1997. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-1992.

The Federal Communications Commission and Voluntary Control Council for Interference has the reports on file and is listed under FCC file 31040/SIT 1300F2 and VCCI Registration No.: C-1298 and R-1234. The test site has been approved by the FCC and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, BACL is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200167-0). The scope of the accreditation covers the FCC Method - 47 CFR Part 15 - Digital Devices, CISPR 22: 1997: Electromagnetic Interference - Limits and Methods of Measurement of Information Technology Equipment test methods.

### 1.6 Test Equipment List

Manufacturer	Description	Model	Serial Number	Cal. Due Date
HP	Spectrum Analyzer	8568B	2610A02165	12/6/03
HP	Spectrum Analyzer	8593B	2919A00242	12/20/03
HP	Amplifier	8349B	2644A02662	12/20/03
HP	Quasi-Peak Adapter	85650A	917059	12/6/03
HP	Amplifier	8447E	1937A01046	12/6/03
A.H. System	Horn Antenna	SAS0200/571	261	12/27/03
Com-Power	Log Periodic Antenna	AL-100	16005	11/2/03
Com-Power	Biconical Antenna	AB-100	14012	11/2/03
Solar Electronics	LISN	8012-50-R-24-BNC	968447	12/28/03
Com-Power	LISN	LI-200	12208	12/20/03
Com-Power	LISN	LI-200	12005	12/20/03
BACL	Data Entry Software	DES1	0001	12/20/03

\* **Statement of Traceability:** BACL Corp. certifies that all calibration has been performed using suitable standards traceable to the NIST.

## **2 - SYSTEM TEST CONFIGURATION**

---

### **2.1 Justification**

The EUT was configured for testing in a typical fashion (as normally used by a typical user).

### **2.2 Schematics and Block Diagram**

Please refer to Appendix D.

### **2.3 Equipment Modifications**

No modifications were necessary for the EUT to comply.

### **2.4 Test Setup Configuration**



Mouse Transmitter

---

### 3 - SUMMARY OF TEST RESULTS

---

FCC RULES	DESCRIPTION OF TEST	RESULT
§ 15.203	Antenna requirement	Compliant
§ 15.205	Restricted Band	Compliant
§ 15.209 § 15.227	Radiated emission limit	Compliant

---

## 4 - RADIATED EMISSION TEST

---

### 4.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at BACL is  $\pm 4.0$  dB.

### 4.2 EUT Setup

The radiated emission tests were performed in the open area 3-meter test site, using the setup accordance with the ANSI C63.4-1992. The specification used was the FCC Subpart C limits.

The spacing between the peripherals was 10 cm.

External I/O cables are draped over edge of test table or bundled when necessary.

The host PC was connected to a 110Vac/60Hz power source.

### 4.3 Spectrum Analyzer Setup

According to FCC Rules, §15.33 (a) (1), the system was tested to 1000 MHz.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

<i><b>Frequency Range</b></i>	<i><b>RBW</b></i>	<i><b>Video B/W</b></i>
Below 30MHz	10kHz	10kHz
30 – 1000MHz	100kHz	100kHz
Above 1000MHz	1MHz	1MHz

#### 4.4 Test Procedure

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT is compliant with all installation combination.

All data was recorded in the peak detection mode. Quasi-peak readings performed only when an emission was found to be marginal (within -4 dB $\mu$ V of specification limitation), and are distinguished with a "QP" in the data table.

The EUT was operating at normal to represent worst case during final qualification test. Therefore, this configuration was used for final test data recorded in the table(s) listed under section 4.7 of this report.

#### 4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB $\mu$ V means the emission is 7dB $\mu$ V below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

#### 4.6 Summary of Test Results

According to the final data in section 4.7, the EUT complied with the FCC 15.227 and FCC 15.209 standards, and had the worst margin of:

-8.8 dB $\mu$ V at 81.09 MHz in the Horizontal polarization, 27-1000MHz

#### 4.7 Radiated Emissions Test Result Data

INDICATED		TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC SUBPART C		
Frequency MHz	Ampl. dB $\mu$ V/m	Angle Degree	Height Meter	Polar H/ V	Antenna dB $\mu$ V/m	Cable dB	Amp. dB	Corr. Ampl. dB $\mu$ V/m	Limit dB $\mu$ V/m	Margin dB	Mode
81.09	41.4	0	2.5	H	9.6	2.7	25.0	31.2	40	-8.8	Peak
54.06	40.9	90	1.0	V	10.5	2.0	25.0	28.4	40	-11.6	Peak
54.06	39.8	120	1.5	H	10.5	2.0	25.0	27.3	40	-12.7	Peak
81.09	43.9	0	3	V	9.6	2.0	25.0	26.4	40	-13.6	Peak
27.03	69.9	15	1.0	V	14.6	1.5	25.0	61.0	80	-19.0	Ave, Fund
27.03	60.5	0	1.2	H	14.6	1.5	25.0	51.6	80	-28.4	Ave, Fund

The mouse transmitter was placed in continuous transmit mode for all tests.

**Note:**

Fund: Fundamental