

RF Exposure Report

Report No.: SABHQC-WTW-P21100439 R1

FCC ID: 2AQ68RPQN7801

Test Model: RPQN-7801E, RPQN-7801I

Received Date: Sep. 10, 2021

Test Date: Sep. 10 ~ Sep. 16, 2021

Issued Date: Mar. 04, 2022

Applicant: Hon Lin Technology Co., Ltd.

Address: 11F, No. 32, Jihu Rd., Neihu Dist., Taipei City 114, Taiwan R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, Taiwan

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	5

Release Control Record

Issue No.	Description	Date Issued
SABHQC-WTW-P21100439	Original release	Nov. 30, 2021
SABHQC-WTW-P21100439 R1	Item 3 modified	Mar. 04, 2022

1 Certificate of Conformity

Product: 5G NR indoor O-RU S4 RPQN-7801

Brand: Foxconn

Test Model: RPQN-7801E, RPQN-7801I

Sample Status: Mass Production

Applicant: Hon Lin Technology Co., Ltd.

Test Date: Sep. 10 ~ Sep. 16, 2021

Standards: FCC Part 2 (Section 2.1091)

References Test Guidance: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Pettie Chen , **Date:** Mar. 04, 2022
Pettie Chen / Senior Specialist

Approved by : Jeremy Lin , **Date:** Mar. 04, 2022
Jeremy Lin / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 35cm away from the body of the user. So, this device is classified as fixed station and installations by professional service personnel device.

3 Calculation Result of Maximum Conducted Power

For 5G NR Band n78

100MHz: QPSK

Frequency Band (MHz)	Conducted Average Power - Per Chain (dBm)				Max Conducted Average Power - Total (dBm)	Directional Gain (dBi)	Max EIRP Power (dBm)	Max EIRP Power (W)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
	ANT0	ANT1	ANT2	ANT3							
3750	24.11	24.24	24.67	24.73	30.47	11.32	41.79	15.10	35	0.981	1

Note:

- Directional gain=5.3 dBi +Array Gain(6.02)= 11.32 dBi
- EIRP = Conducted + antenna gain (11.32dBi)
- The antenna gain was declared by client.
- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

--- END ---