



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V05

Report Template Revision Date: 2021-11-03

Test Report

Report No. : CQASZ20220500783E-02
Applicant: ORAIMO TECHNOLOGY LIMITED
Address of Applicant: FLAT 39 8/F BLOCK D WAH LOK INDUSTRIAL CENTRE 31-35 SHAN MEI STREET FOTAN NT
Equipment Under Test (EUT):
Product: Smart Watch
Model No.: boAt Wave Connect RTL, boAt Wave Connect F, boAt Wave Connect A, boAt Wave Connect Plus, boAt Wave Connect Pro, boAt Wave Connect Max , boAt Wave Connect, ID208, ID208 BT
Test Model No.: ID208 BT
Brand Name: oraimo
FCC ID: 2AXYP-ID208
Standards: 47 CFR Part 15, Subpart C
Date of Receipt: 2021-12-23
Date of Test: 2021-12-23 to 2021-12-30
Date of Issue: 2022-6-22
Test Result : **PASS***

*In the configuration tested, the EUT complied with the standards specified above.

Tested By: Lewis Zhou
(Lewis Zhou)

Reviewed By: K. Liao
(K Liao)

Approved By: Jack Ai
(Jack Ai)



Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20220500783E-02	Rev.01	Initial report	2022-6-22

Note:

This test report (Ref. No.: CQASZ20220500783E-02)

All test data comes from source test reports (Ref. No.: CQASZ20211202223E-02).

Only on the basis of the original report Change Brand Name, Applicant, Address of Applicant.

The tested samples have not been changed.

1 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 (2013)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2013)	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(1)	ANSI C63.10 (2013)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Carrier Frequencies Separation	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Hopping Channel Number	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 15.247(b)(4)&TCB Exclusion List (7 July 2002)	ANSI C63.10 (2013)	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
Radiated Spurious emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS

2 Contents

	Page
1 VERSION	2
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 CLIENT INFORMATION	5
4.2 GENERAL DESCRIPTION OF EUT	5
4.3 ADDITIONAL INSTRUCTIONS	7
4.4 TEST ENVIRONMENT	8
4.5 DESCRIPTION OF SUPPORT UNITS	8
4.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY	9
4.7 TEST LOCATION	10
4.8 TEST FACILITY	10
4.9 ABNORMALITIES FROM STANDARD CONDITIONS	10
4.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	10
4.11 EQUIPMENT LIST	11
5 TEST RESULTS AND MEASUREMENT DATA	12
5.1 ANTENNA REQUIREMENT	12
5.2 CONDUCTED EMISSIONS	13
5.3 CONDUCTED PEAK OUTPUT POWER	18
<i>Test Result</i>	19
<i>Test Graphs</i>	20
5.4 20DB OCCUPY BANDWIDTH	25
<i>Test Result</i>	25
<i>Test Graphs</i>	26
5.5 CARRIER FREQUENCIES SEPARATION	31
<i>Test Result</i>	32
<i>Test Graphs</i>	32
5.6 HOPPING CHANNEL NUMBER	34
<i>Test Result</i>	34
<i>Test Graphs</i>	35
5.7 DWELL TIME	37
<i>Test Result</i>	38
5.7.1 <i>Test Graphs</i>	39
5.8 BAND-EDGE FOR RF CONDUCTED EMISSIONS	46
<i>Test Result</i>	47
<i>Test Graphs</i>	48
5.9 SPURIOUS RF CONDUCTED EMISSIONS	54
5.9.1 <i>Test Result</i>	55
<i>Test Graphs</i>	56
5.10 OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM	70
5.11 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS	72
5.11.1 <i>Radiated Emission below 1GHz</i>	75
5.11.2 <i>Transmitter Emission above 1GHz</i>	79
6 PHOTOGRAPHS - EUT TEST SETUP	82
6.1 RADIATED EMISSION	82
6.2 CONDUCTED EMISSION	83
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	84

3 General Information

3.1 Client Information

Applicant:	ORAIMO TECHNOLOGY LIMITED
Address of Applicant:	FLAT 39 8/F BLOCK D WAH LOK INDUSTRIAL CENTRE 31-35 SHAN MEI STREET FOTAN NT
Manufacturer:	Shenzhen DO Intelligent Technology Co., Ltd
Address of Manufacturer:	11th Floor, 3# Building, Guole Tech Park, Lirong Road, Dalang, Longhua District, Shenzhen, China
Factory:	Shenzhen DO Intelligent Technology Co., Ltd
Address of Factory:	11th Floor, 3# Building, Guole Tech Park, Lirong Road, Dalang, Longhua District, Shenzhen, China

3.2 General Description of EUT

Product Name:	Smart Watch
Model No.:	boAt Wave Connect RTL, boAt Wave Connect F, boAt Wave Connect A, boAt Wave Connect Plus, boAt Wave Connect Pro, boAt Wave Connect Max , boAt Wave Connect, ID208, ID208 BT
Test Model No.:	ID208 BT
Trade Mark:	oraimo
Software Version:	V1
Hardware Version:	V1.1
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.1
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Transfer Rate:	1Mbps/2Mbps/3Mbps
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Product Type:	☐ Mobile ☒ Portable ☐ Fix Location
Test Software of EUT:	MainWindow
Antenna Type:	FPC antenna
Antenna Gain:	-0.61dBi
Power Supply:	lithium battery:DC3.8V, 300mAh, 1.140Wh, Charge by DC5.0V 280mA

Note:

Model No.:boAt Wave Connect RTL, boAt Wave Connect F, boAt Wave Connect A, boAt Wave Connect Plus, boAt Wave Connect Pro, boAt Wave Connect Max, boAt Wave Connect, ID208, ID208 BT

The model ID208 BT was tested, Their electrical circuit design, layout, components used and internal wiring are identical, Only the product model is different.

The difference between 1 # and 2 # is that the supplier of the screen differently tests the data

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
6	2408MHz	26	2428MHz	46	2448MHz	66	2468MHz
7	2409MHz	27	2429MHz	47	2449MHz	67	2469MHz
8	2410MHz	28	2430MHz	48	2450MHz	68	2470MHz
9	2411MHz	29	2431MHz	49	2451MHz	69	2471MHz
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
12	2414MHz	32	2434MHz	52	2454MHz	72	2474MHz
13	2415MHz	33	2435MHz	53	2455MHz	73	2475MHz
14	2416MHz	34	2436MHz	54	2456MHz	74	2476MHz
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2441MHz
The Highest channel	2480MHz

3.3 Additional Instructions

EUT Test Software Settings:		
Mode:	☒ Special software is used. ☐ Through engineering command into the engineering mode. engineering command: ***#3646633#**	
EUT Power level:	Class2 (Power level is built-in set parameters and cannot be changed and selected)	
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.		
Mode	Channel	Frequency(MHz)
DH1/DH3/DH5	CH0	2402
	CH39	2441
	CH78	2480
2DH1/2DH3/2DH5	CH0	2402
	CH39	2441
	CH78	2480
3DH1/3DH3/3DH5	CH0	2402
	CH39	2441
	CH78	2480

Run Software:



The screenshot shows the 'Run Software' window with the following details:

- RF 测试 (RF Test):** BLE 测试参数 (BLE Test Parameters) and BT 测试参数 (BT Test Parameters) are visible. BLE parameters include 包类型 (Package Type) set to PRBS9, 频段 (Frequency Band) set to CH78:2480, and 功率 (Power) set to 0x16. BT parameters include 包类型 (Package Type) set to DM1, 频段 (Frequency Band) set to 跳频 (Frequency Hopping), and 功率 (Power) set to 0x10.
- 单载波测试参数 (Single Carrier Test Parameters):** 频段 (Frequency Band) set to CH0:2402, 功率 (Power) set to 0x0a.
- 测试选项 (Test Options):** 模式 (Mode) set to 发送 (Transmit). Radio buttons for 测试BLE (Test BLE) and 测试BT (Test BT) are present.
- 串口 (Serial Port):** 串口 (Serial Port) set to COM24, 波特率 (Baud Rate) set to 115200. 当前状态 (Current Status) is 已经连接 (Flash). Buttons for 打开 (Open) and 关闭 (Close) are available.
- 配置 (Configuration):** Buttons for 导入DAT文件 (Import DAT File), 导出DAT文件 (Export DAT File), 导入程序补丁 (Import Program Patch), 导出程序补丁 (Export Program Patch), 导入DSF_CODE (Import DSF_CODE), and 导出DSF_CODE (Export DSF_CODE).
- 补丁大小 (Patch Size):** 补丁大小 (Patch Size) set to 0, dsp 大小 (dsp Size) set to 0.
- 烧录 (Burn):** A green progress bar is shown, along with buttons for 写入所有内容 (Write All Content) and 读取所有内容 (Read All Content).
- 版本 (Version):** CHIP: and Version: fields are present.
- 运行状态信息 (Run Status Information):** A log window at the bottom shows multiple entries of '[19:28:38]: BLE测试执行成功...' and '[19:40:28]: BLE测试执行成功...'.

3.4 Test Environment

Operating Environment:	
Temperature:	26 °C
Humidity:	59% RH
Atmospheric Pressure:	1009mbar
Test Mode:	Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.

3.5 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.	Remark	FCC certification
/	/	/	/	/

3.6 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty	Notes
1	Radiated Emission (Below 1GHz)	±5.12dB	(1)
2	Radiated Emission (Above 1GHz)	±4.60dB	(1)
3	Conducted Disturbance (0.15~30MHz)	±3.34dB	(1)
4	Radio Frequency	3×10^{-8}	(1)
5	Duty cycle	0.6 %.	(1)
6	Occupied Bandwidth	1.1%	(1)
7	RF conducted power	0.86dB	(1)
8	RF power density	0.74	(1)
9	Conducted Spurious emissions	0.86dB	(1)
10	Temperature test	0.8℃	(1)
11	Humidity test	2.0%	(1)
12	Supply voltages	0.5 %.	(1)
13	time	0.6 %.	(1)
14	Frequency Error	5.5 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

3.7 Test Location

Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

3.8 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 22984-1

The 3m Semi-anechoic chamber of Shenzhen Huaxia Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

The test facility is recognized, certified, or accredited by the following organizations:

• **CNAS (No. CNAS L5785)**

CNAS has accredited Shenzhen Huaxia Testing Technology Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

3.9 Abnormalities from Standard Conditions

None.

3.10 Other Information Requested by the Customer

None.

3.11 Equipment List

Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2021/9/10	2021/9/9
Spectrum analyzer	R&S	FSU26	CQA-038	2021/9/10	2021/9/9
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2021/9/10	2021/9/9
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2021/9/10	2021/9/9
Loop antenna	Schwarzbeck	FMZB1516	CQA-087	2021/9/16	2024/9/15
Bilog Antenna	R&S	HL562	CQA-011	2021/9/16	2024/9/15
Horn Antenna	R&S	HF906	CQA-012	2021/9/16	2024/9/15
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2021/9/16	2024/9/15
Coaxial Cable (Above 1GHz)	CQA	N/A	C019	2021/9/10	2021/9/9
Coaxial Cable (Below 1GHz)	CQA	N/A	C020	2021/9/10	2021/9/9
Antenna Connector	CQA	RFC-01	CQA-080	2021/9/10	2021/9/9
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2021/9/10	2021/9/9
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2021/9/10	2021/9/9
EMI Test Receiver	R&S	ESPI3	CQA-013	2021/9/10	2021/9/9
LISN	R&S	ENV216	CQA-003	2021/9/10	2021/9/9
Coaxial cable	CQA	N/A	CQA-C009	2021/9/10	2021/9/9

Note:


The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

4 Test results and Measurement Data

4.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
	15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
EUT Antenna:	 The antenna is FPC antenna. The best case gain of the antenna is -0.61 dBi.

4.2 Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.		
Test Setup:			

Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type at the lowest, middle, high channel.
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation at the lowest channel is the worst case. Only the worst case is recorded in the report.
Test Voltage:	AC 120V/60Hz
Test Results:	Pass

Measurement Data

1#

Live line:




	Read Freq	Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.220	21.41	9.58	30.99	52.82	-21.83	Average	Line
2	0.220	26.47	9.58	36.05	62.82	-26.77	QP	Line
3	0.320	19.93	9.52	29.45	49.71	-20.26	Average	Line
4	0.320	24.82	9.52	34.34	59.71	-25.37	QP	Line
5	0.685	18.72	9.89	28.61	46.00	-17.39	Average	Line
6	0.685	23.75	9.89	33.64	56.00	-22.36	QP	Line
7	0.940	19.19	9.74	28.93	46.00	-17.07	Average	Line
8	0.940	24.01	9.74	33.75	56.00	-22.25	QP	Line
9 PP	1.405	20.58	10.65	31.23	46.00	-14.77	Average	Line
10 QP	1.405	25.14	10.65	35.79	56.00	-20.21	QP	Line
11	1.750	19.00	11.27	30.27	46.00	-15.73	Average	Line
12	1.750	24.23	11.27	35.50	56.00	-20.50	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:




	Freq	Read	Factor	Level	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Remark	Pol/Phase
1	0.235	21.06	9.56	30.62	52.27	-21.65	Average	Neutral
2	0.235	26.35	9.56	35.91	62.27	-26.36	QP	Neutral
3	0.510	18.71	9.71	28.42	46.00	-17.58	Average	Neutral
4	0.510	23.64	9.71	33.35	56.00	-22.65	QP	Neutral
5 PP	1.080	19.43	9.70	29.13	46.00	-16.87	Average	Neutral
6 QP	1.080	24.54	9.70	34.24	56.00	-21.76	QP	Neutral
7	1.630	18.99	9.73	28.72	46.00	-17.28	Average	Neutral
8	1.630	23.93	9.73	33.66	56.00	-22.34	QP	Neutral
9	2.530	12.37	9.76	22.13	46.00	-23.87	Average	Neutral
10	2.530	17.73	9.76	27.49	56.00	-28.51	QP	Neutral
11	5.795	7.24	9.82	17.06	50.00	-32.94	Average	Neutral
12	5.795	11.89	9.82	21.71	60.00	-38.29	QP	Neutral

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

2#

Live line:




	Freq	Read		Limit	Over		
	MHz	Level	Factor	Line	Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dB		
1	0.175	21.82	9.65	31.47	54.72	-23.25 Average	Line
2	0.175	27.15	9.65	36.80	64.72	-27.92 QP	Line
3	0.550	18.96	9.75	28.71	46.00	-17.29 Average	Line
4	0.550	23.86	9.75	33.61	56.00	-22.39 QP	Line
5	0.660	18.60	9.86	28.46	46.00	-17.54 Average	Line
6	0.660	24.09	9.86	33.95	56.00	-22.05 QP	Line
7	0.920	19.16	9.75	28.91	46.00	-17.09 Average	Line
8	0.920	24.36	9.75	34.11	56.00	-21.89 QP	Line
9 PP	1.700	18.91	11.19	30.10	46.00	-15.90 Average	Line
10 QP	1.700	23.95	11.19	35.14	56.00	-20.86 QP	Line
11	14.215	11.91	9.75	21.66	50.00	-28.34 Average	Line
12	14.215	17.61	9.75	27.36	60.00	-32.64 QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:




	Freq	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.235	21.40	9.56	30.96	52.27	-21.31	Average	Neutral
2	0.235	26.62	9.56	36.18	62.27	-26.09	QP	Neutral
3	0.400	19.39	9.60	28.99	47.85	-18.86	Average	Neutral
4	0.400	24.47	9.60	34.07	57.85	-23.78	QP	Neutral
5	0.825	18.85	9.82	28.67	46.00	-17.33	Average	Neutral
6	0.825	23.81	9.82	33.63	56.00	-22.37	QP	Neutral
7 PP	1.530	20.04	9.73	29.77	46.00	-16.23	Average	Neutral
8 QP	1.530	25.15	9.73	34.88	56.00	-21.12	QP	Neutral
9	3.945	8.16	9.79	17.95	46.00	-28.05	Average	Neutral
10	3.945	13.14	9.79	22.93	56.00	-33.07	QP	Neutral
11	13.850	9.94	9.77	19.71	50.00	-30.29	Average	Neutral
12	13.850	14.49	9.77	24.26	60.00	-35.74	QP	Neutral

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

4.3 Conducted Peak Output Power


Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	21dBm
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass

Test Result

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH5	Ant1	2402	-1.55	≤ 21	PASS
		2441	0.22	≤ 21	PASS
		2480	1.41	≤ 21	PASS
2DH5	Ant1	2402	-1.86	≤ 21	PASS
		2441	-0.05	≤ 21	PASS
		2480	1.49	≤ 21	PASS
3DH5	Ant1	2402	-1.73	≤ 21	PASS
		2441	-0.06	≤ 21	PASS
		2480	1.32	≤ 21	PASS


Test Graphs

DH5_Ant1_2402




Date: 30 DEC 2021 03:18:58

DH5_Ant1_2441




Date: 30 DEC 2021 03:20:19


DH5_Ant1_2480




2DH5_Ant1_2402




2DH5_Ant1_2441




2DH5_Ant1_2480




3DH5_Ant1_2402




3DH5_Ant1_2441





4.4 20dB Occupy Bandwidth


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	NA
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass

Test Result

TestMode	Antenna	Channel	20db EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	0.990	2401.511	2402.501	---	PASS
		2441	0.975	2440.505	2441.480	---	PASS
		2480	0.969	2479.520	2480.489	---	PASS
2DH5	Ant1	2402	1.254	2401.367	2402.621	---	PASS
		2441	1.269	2440.358	2441.627	---	PASS
		2480	1.266	2479.352	2480.618	---	PASS
3DH5	Ant1	2402	1.269	2401.352	2402.621	---	PASS
		2441	1.266	2440.355	2441.621	---	PASS
		2480	1.266	2479.358	2480.624	---	PASS


Test Graphs

DH5_Ant1_2402




Date: 30 DEC 2021 02:06:15

DH5_Ant1_2441




Date: 30 DEC 2021 02:09:30

DH5_Ant1_2480




Date: 30 DEC 2021 02:12:07

2DH5_Ant1_2402




Date: 30 DEC 2021 02:14:32

2DH5_Ant1_2441




Date: 30 DEC 2021 02:17:11

2DH5_Ant1_2480




Date: 30 DEC 2021 02:18:25

3DH5_Ant1_2402




Date: 30 DEC 2021 02:25:10


3DH5_Ant1_2441



Date: 30 DEC 2021 02:26:01



4.5 Carrier Frequencies Separation


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	2/3 of the 20dB bandwidth
	Remark: the transmission power is less than 0.125W.
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass

Test Result


TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH5	Ant1	Hop	1.171	≥0.660	PASS
2DH5	Ant1	Hop	1.148	≥0.846	PASS
3DH5	Ant1	Hop	0.849	≥0.846	PASS

Test Graphs






4.6 Hopping Channel Number


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	At least 15 channels
Exploratory Test Mode:	hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass

Test Result


TestMode	Antenna	Channel	Result[Num]	Limit[Num]	Verdict
DH5	Ant1	Hop	79	≥ 15	PASS
2DH5	Ant1	Hop	79	≥ 15	PASS
3DH5	Ant1	Hop	79	≥ 15	PASS

Test Graphs





4.7 Dwell Time

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.
Limit:	0.4 Second
Test Results:	Pass

Test Result

TestMode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.41	320	0.132	≤0.4	PASS
DH3	Ant1	Hop	1.58	150	0.236	≤0.4	PASS
DH5	Ant1	Hop	2.61	100	0.261	≤0.4	PASS
2DH1	Ant1	Hop	0.42	330	0.14	≤0.4	PASS
2DH3	Ant1	Hop	1.62	160	0.259	≤0.4	PASS
2DH5	Ant1	Hop	2.61	100	0.261	≤0.4	PASS
3DH1	Ant1	Hop	0.43	320	0.138	≤0.4	PASS
3DH3	Ant1	Hop	1.41	140	0.198	≤0.4	PASS
3DH5	Ant1	Hop	2.60	130	0.338	≤0.4	PASS

Remark:


The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

DH1/2DH1/3DH1 Dwell time = Burst Width(ms)*(1600/ (2*79))*31.6


DH3/2DH3/3DH3 Dwell time = Burst Width (ms)*(1600/ (4*79))*31.6

DH5/2DH5/3DH5 Dwell time = Burst Width (ms)*(1600/ (6*79))*31.6


4.7.1 Test Graphs



DH3_Ant1_Hop




Date: 30 DEC 2021 02:37:29




Date: 30 DEC 2021 02:37:34



DH5_Ant1_Hop




Date: 30 DEC 2021 02:36:24




2DH1_Ant1_Hop



2DH3_Ant1_Hop




Date: 30 DEC 2021 02:43:47




Date: 30 DEC 2021 02:43:53



2DH5_Ant1_Hop




Date: 30 DEC 2021 12:21:44




3DH1_Ant1_Hop



3DH3_Ant1_Hop




Date: 30 DEC 2021 03:14:57




Date: 30 DEC 2021 03:15:03


3DH5_Ant1_Hop



Date: 30 DEC 2021 03:12:55



4.8 Band-edge for RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	 <i>Remark: Offset=cable loss+ attenuation factor.</i>
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass

Test Result

TestMode	Antenna	ChName	Channel	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	-1.92	-46.41	≤ -21.92	PASS
		High	2480	1.08	-47.65	≤ -18.92	PASS
		Low	Hop_2402	-2.04	-48.85	≤ -22.04	PASS
		High	Hop_2480	0.80	-47.05	≤ -19.2	PASS
2DH5	Ant1	Low	2402	-1.91	-47.06	≤ -21.91	PASS
		High	2480	0.91	-46.46	≤ -19.09	PASS
		Low	Hop_2402	-1.98	-48.44	≤ -21.98	PASS
		High	Hop_2480	1.22	-48.15	≤ -18.78	PASS
3DH5	Ant1	Low	2402	-1.96	-46.54	≤ -21.96	PASS
		High	2480	1.03	-46.26	≤ -18.97	PASS
		Low	Hop_2402	-3.93	-48.68	≤ -23.93	PASS
		High	Hop_2480	1.02	-47.08	≤ -18.98	PASS


Test Graphs

DH5_Ant1_Low_2402




Date: 30 DEC 2021 02:06:37

DH5_Ant1_High_2480




Date: 30 DEC 2021 02:12:28

DH5_Ant1_Low_Hop_2402




Date: 30 DEC 2021 02:33:38

DH5_Ant1_High_Hop_2480




Date: 30 DEC 2021 02:37:51

2DH5_Ant1_Low_2402




Date: 30 DEC 2021 02:14:53

2DH5_Ant1_High_2480




Date: 30 DEC 2021 02:18:48

2DH5_Ant1_Low_Hop_2402




Date: 30 DEC 2021 02:38:29

2DH5_Ant1_High_Hop_2480




Date: 30 DEC 2021 02:44:13

3DH5_Ant1_Low_2402




Date: 30 DEC 2021 02:23:31

3DH5_Ant1_High_2480




Date: 30 DEC 2021 02:27:42

3DH5_Ant1_Low_Hop_2402




Date: 30 DEC 2021 03:06:02

3DH5_Ant1_High_Hop_2480



Date: 30 DEC 2021 03:15:30

4.9 Spurious RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	 <i>Remark: Offset=cable loss+ attenuation factor.</i>
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.
Test Results:	Pass

4.9.1 Test Result


TestMode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	2402	Reference	-2.00	-2.00	---	PASS
			30~1000	-2.00	-54.46	≤-22	PASS
			1000~26500	-2.00	-48.11	≤-22	PASS
		2441	Reference	-0.14	-0.14	---	PASS
			30~1000	-0.14	-54.65	≤-20.14	PASS
			1000~26500	-0.14	-48.33	≤-20.14	PASS
		2480	Reference	1.03	1.03	---	PASS
			30~1000	1.03	-56.86	≤-18.97	PASS
			1000~26500	1.03	-49.08	≤-18.97	PASS
2DH5	Ant1	2402	Reference	-2.05	-2.05	---	PASS
			30~1000	-2.05	-56.91	≤-22.05	PASS
			1000~26500	-2.05	-48.83	≤-22.05	PASS
		2441	Reference	-0.14	-0.14	---	PASS
			30~1000	-0.14	-56.85	≤-20.14	PASS
			1000~26500	-0.14	-47.66	≤-20.14	PASS
		2480	Reference	0.96	0.96	---	PASS
			30~1000	0.96	-55.32	≤-19.04	PASS
			1000~26500	0.96	-48.3	≤-19.04	PASS
3DH5	Ant1	2402	Reference	-2.00	-2.00	---	PASS
			30~1000	-2.00	-57.04	≤-22	PASS
			1000~26500	-2.00	-48.6	≤-22	PASS
		2441	Reference	-0.14	-0.14	---	PASS
			30~1000	-0.14	-56.53	≤-20.14	PASS
			1000~26500	-0.14	-47.46	≤-20.14	PASS
		2480	Reference	1.04	1.04	---	PASS
			30~1000	1.04	-56.56	≤-18.96	PASS
			1000~26500	1.04	-48.11	≤-18.96	PASS

Test Graphs


DH5_Ant1_2402_Reference



DH5_Ant1_2402_30~1000




DH5_Ant1_2402_1000~26500




DH5_Ant1_2441_Reference




DH5_Ant1_2441_30~1000




DH5_Ant1_2441_1000~26500




DH5_Ant1_2480_Reference




DH5_Ant1_2480_30~1000




DH5_Ant1_2480_1000~26500




2DH5_Ant1_2402_Reference




2DH5_Ant1_2402_30~1000




2DH5_Ant1_2402_1000~26500




2DH5_Ant1_2441_Reference




2DH5_Ant1_2441_30~1000




2DH5_Ant1_2441_1000~26500




2DH5_Ant1_2480_Reference




2DH5_Ant1_2480_30~1000




2DH5_Ant1_2480_1000~26500




3DH5_Ant1_2402_Reference



3DH5_Ant1_2402_30~1000




3DH5_Ant1_2402_1000~26500




3DH5_Ant1_2441_Reference




3DH5_Ant1_2441_30~1000




3DH5_Ant1_2441_1000~26500




3DH5_Ant1_2480_Reference



3DH5_Ant1_2480_30~1000





Remark:

Pre test 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

4.10 Other requirements Frequency Hopping Spread Spectrum System

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1), (h) requirement:
	The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals. Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section. The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.
	Compliance for section 15.247(a)(1)
	According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones. • Number of shift register stages: 9 • Length of pseudo-random sequence: $2^9 - 1 = 511$ bits • Longest sequence of zeros: 8 (non-inverted signal) <i>Linear Feedback Shift Register for Generation of the PRBS sequence</i> An example of Pseudorandom Frequency Hopping Sequence as follow: Each frequency used equally on the average by each transmitter. According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.
	Compliance for section 15.247(g)
	According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

4.11 Radiated Spurious Emission & Restricted bands

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Peak	100 kHz	300kHz	Peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:


- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
Note: For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

	d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel (2402MHz), the middle channel (2441MHz), the Highest channel (2480MHz) h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type Transmitting mode
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation is the worst case. Pretest the EUT at Transmitting mode and Charge + Transmitting mode, found the Charge + Transmitting mode which it is worse case For below 1GHz part, through pre-scan, the worst case is the lowest channel. Only the worst case is recorded in the report.
Test Results:	Pass

4.11.1 Radiated Emission below 1GHz

1#

Vertical



		Read		Limit	Over		
	Freq	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Pol/Phase
1	pp	57.59	15.65	6.00	21.65	40.00	-18.35 Peak
2		83.23	11.07	9.86	20.93	40.00	-19.07 Peak
3		119.86	9.47	10.69	20.16	43.50	-23.34 Peak
4		181.92	10.11	8.27	18.38	43.50	-25.12 Peak
5		298.27	9.65	13.68	23.33	46.00	-22.67 Peak
6		331.35	10.30	14.49	24.79	46.00	-21.21 Peak

Remark:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

Horizontal



	Freq	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	98.49	9.95	10.56	20.51	43.50	-22.99	Peak	HORIZONTAL
2	128.11	9.10	10.40	19.50	43.50	-24.00	Peak	HORIZONTAL
3	239.99	9.76	11.56	21.32	46.00	-24.68	Peak	HORIZONTAL
4	304.61	10.45	13.85	24.30	46.00	-21.70	Peak	HORIZONTAL
5	440.20	11.38	16.42	27.80	46.00	-18.20	Peak	HORIZONTAL
6 pp	511.84	10.37	18.41	28.78	46.00	-17.22	Peak	HORIZONTAL

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:


Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

2#

Vertical



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1 pp	73.10	19.26	8.66	27.92	40.00	-12.08	Peak	VERTICAL
2	118.19	9.23	10.60	19.83	43.50	-23.67	Peak	VERTICAL
3	248.55	9.98	12.04	22.02	46.00	-23.98	Peak	VERTICAL
4	411.82	10.30	15.52	25.82	46.00	-20.18	Peak	VERTICAL
5	501.18	12.52	18.29	30.81	46.00	-15.19	Peak	VERTICAL
6	785.09	9.97	22.20	32.17	46.00	-13.83	Peak	VERTICAL

Remark:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

Horizontal



	Read Freq	Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	36.00	7.79	14.24	22.03	40.00	-17.97	Peak	HORIZONTAL
2	73.10	10.25	8.66	18.91	40.00	-21.09	Peak	HORIZONTAL
3	129.47	9.46	10.34	19.80	43.50	-23.70	Peak	HORIZONTAL
4	245.09	10.53	11.93	22.46	46.00	-23.54	Peak	HORIZONTAL
5 pp	530.10	10.88	18.59	29.47	46.00	-16.53	Peak	HORIZONTAL
6	1000.00	9.45	25.14	34.59	54.00	-19.41	Peak	HORIZONTAL

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

4.11.2 Transmitter Emission above 1GHz

Worse case mode:		GFSK(DH5)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2390	54.77	-9.2	45.57	74	-28.43	Peak	H
2400	56.90	-9.39	47.51	74	-26.49	Peak	H
4804	52.57	-4.33	48.24	74	-25.76	Peak	H
7206	48.73	1.01	49.74	74	-24.26	Peak	H
2390	54.23	-9.2	45.03	74	-28.97	Peak	V
2400	55.04	-9.39	45.65	74	-28.35	Peak	V
4804	53.07	-4.33	48.74	74	-25.26	Peak	V
7206	49.05	1.01	50.06	74	-23.94	Peak	V

Worse case mode:		GFSK(DH5)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4882	52.49	-4.11	48.38	74	-25.62	peak	H
7323	50.57	1.51	52.08	74	-21.92	peak	H
4882	53.64	-4.11	49.53	74	-24.47	peak	V
7323	49.87	1.51	51.38	74	-22.62	peak	V

Worse case mode:		GFSK(DH5)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2483.5	55.05	-9.29	45.76	74	-28.24	Peak	H
4960	51.74	-4.04	47.70	74	-26.30	Peak	H
7440	49.57	1.57	51.14	74	-22.86	Peak	H
2483.5	53.88	-9.29	44.59	74	-29.41	Peak	V
4960	48.31	-4.04	44.27	74	-29.73	Peak	V
7440	48.86	1.57	50.43	74	-23.57	Peak	V

Worse case mode:		$\pi/4$ DQPSK (2DH5)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
2390	56.19	-9.2	46.99	74	-27.01	Peak	H
2400	55.49	-9.39	46.10	74	-27.90	Peak	H
4804	52.13	-4.33	47.80	74	-26.20	Peak	H
7206	50.87	1.01	51.88	74	-22.12	Peak	H
2390	55.35	-9.2	46.15	74	-27.85	Peak	V
2400	54.80	-9.39	45.41	74	-28.59	Peak	V
4804	52.27	-4.33	47.94	74	-26.06	Peak	V
7206	48.53	1.01	49.54	74	-24.46	Peak	V

Worse case mode:		$\pi/4$ DQPSK (2DH5)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
4882	50.76	-4.11	46.65	74	-27.35	peak	H
7323	48.29	1.51	49.80	74	-24.20	peak	H
4882	53.46	-4.11	49.35	74	-24.65	peak	V
7323	50.00	1.51	51.51	74	-22.49	peak	V

Worse case mode:		$\pi/4$ DQPSK (2DH5)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
2483.5	57.19	-9.29	47.90	74	-26.10	Peak	H
4960	52.27	-4.04	48.23	74	-25.77	Peak	H
7440	48.38	1.57	49.95	74	-24.05	Peak	H
2483.5	54.16	-9.29	44.87	74	-29.13	Peak	V
4960	49.26	-4.04	45.22	74	-28.78	Peak	V
7440	50.52	1.57	52.09	74	-21.91	Peak	V

Worse case mode:		8DPSK (3DH5)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2390	56.14	-9.2	46.94	74	-27.06	Peak	H
2400	57.04	-9.39	47.65	74	-26.35	Peak	H
4804	51.84	-4.33	47.51	74	-26.49	Peak	H
7206	49.97	1.01	50.98	74	-23.02	Peak	H
2390	55.26	-9.2	46.06	74	-27.94	Peak	V
2400	54.68	-9.39	45.29	74	-28.71	Peak	V
4804	54.72	-4.33	50.39	74	-23.61	Peak	V
7206	49.27	1.01	50.28	74	-23.72	Peak	V

Worse case mode:		8DPSK (3DH5)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4882	51.08	-4.11	46.97	74	-27.03	peak	H
7323	49.33	1.51	50.84	74	-23.16	peak	H
4882	51.77	-4.11	47.66	74	-26.34	peak	V
7323	48.25	1.51	49.76	74	-24.24	peak	V

Worse case mode:		8DPSK (3DH5)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2483.5	55.22	-9.29	45.93	74	-28.07	Peak	H
4960	53.07	-4.04	49.03	74	-24.97	Peak	H
7440	48.28	1.57	49.85	74	-24.15	Peak	H
2483.5	54.71	-9.29	45.42	74	-28.58	Peak	V
4960	50.04	-4.04	46.00	74	-28.00	Peak	V
7440	48.96	1.57	50.53	74	-23.47	Peak	V

Remark:

- The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

5 Photographs - EUT Test Setup

5.1 Radiated Emission

9KHz~30MHz:



30MHz~1GHz:



Above 1GHz:



5.2 Conducted Emission



6 Photographs - EUT Constructional Details

Refer to Photographs - EUT Constructional Details OF EUT for CQASZ20220500783E-01.

*** END OF REPORT ***