

**47 C.F.R. Part 1, Subpart I, Section 1.1310
47 C.F.R. Part 2, Subpart J, Section 2.1091
Maximum Permissible Exposure Calculations**

For FCC ID: 2AB8I-RE4

EUT Device Category = General Population/Uncontrolled Exposure

EUT consists of two ISM band transmitters. One operating over a range of: **2402 MHz to 2480 MHz**, and one operating over a range of **910.2 MHz to 920 MHz**.

MPE Summary:

According subpart 1.1307 (b)(1) and 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

PG = EIRP

MPE and Limit are calculated for this device as follows:

2.402 GHz to 2.48 GHz Frequency Band							
BLE Transceiver							
Freq	Field Strength (dBuV/m)	Max Antenna Gain (dBi)	Max EIRP (dBm)	Max EIRP (mW)	Power Density at 20 cm (mW/cm ²)	Limit (mW)	Margin (mW)
2402	98.65	0.0	3.42	2.20	0.0004	1.000	0.9996
2440	98.72	0.0	3.49	2.23	0.0004	1.000	0.9996
2480	96.69	0.0	1.46	1.40	0.0003	1.000	0.9997

910.2 MHz to 920.0 MHz Frequency Band							
Freq	Output Power (dBm)	Max Antenna Gain (dBi)	Max EIRP (dBm)	Max EIRP (mW)	Power Density at 20 cm (mW/cm ²)	Limit (mW)	Margin (mW)
910.2	29.87	0.0	29.87	970.51	0.193	0.607	0.414
915.0	29.57	0.0	29.57	905.73	0.180	0.610	0.430
920.0	29.32	0.0	29.32	855.07	0.170	0.613	0.443

Result: There are two transceivers in the device. They will never transmit at the same time as only one radio is configured for use in each installation. The device meets FCC MPE limit at 20 cm for General Population/Uncontrolled Exposure as specified in 47 CFR §1.1310 and §2.1091.