



FCC TEST REPORT

FCC ID: 2AATL-6222B-SRC

On Behalf of

FN-LINK TECHNOLOGY LIMITED

WIFI MODULE

Model No.: 6222B-SRC

Prepared for : FN-LINK TECHNOLOGY LIMITED
Address : No.8, Litong Road, Liuyang Economic & Technical Development
Zone, Changsha, Hunan, China

Prepared By : Shenzhen Alpha Product Testing Co., Ltd.
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

Report Number : A2303077-C01-R02
Date of Receipt : March 20, 2023
Date of Test : March 20, 2023- May 8, 2023
Date of Report : May 8, 2023
Version Number : V0

TABLE OF CONTENTS

<u>Description</u>	<u>Page</u>
1. Summary of Standards And Results	6
1.1. Description of Standards and Results	6
2. General Information	7
2.1. Description of Device (EUT)	7
2.2. Accessories of Device (EUT)	8
2.3. Tested Supporting System Details	8
2.4. Block Diagram of connection between EUT and simulators	8
2.5. Test Mode Description	8
2.6. Test Conditions	9
2.7. Test Facility	9
2.8. Measurement Uncertainty	9
2.9. Test Equipment List	10
3. Maximum Peak Output power	11
3.1. Limit	11
3.2. Test Procedure	11
3.3. Test Setup	11
3.4. Test Result	11
4. Bandwidth	12
4.1. Limit	12
4.2. Test Procedure	12
4.3. Test Result	12
5. Carrier Frequency Separation	23
5.1. Limit	23
5.2. Test Procedure	23
5.3. Test Result	23
6. Number Of Hopping Channel	25
6.1. Limit	25
6.2. Test Procedure	25
6.3. Test Result	25
7. Dwell Time	27
7.1. Test limit	27
7.2. Test Procedure	27
7.3. Test Result	27
8. Radiated emissions	43
8.1. Limit	43
8.2. Block Diagram of Test setup	44
8.3. Test Procedure	45
8.4. Test Result	45
9. Band Edge Compliance	60
9.1. Block Diagram of Test Setup	60

9.2. Limit	60
9.3. Test Procedure	60
9.4. Test Result.....	60
10. Power Line Conducted Emissions.....	67
10.1. Block Diagram of Test Setup	67
10.2. Limit	67
10.3. Test Procedure	67
10.4. Test Result.....	67
11. Antenna Requirements.....	70
11.1. Limit.....	70
11.2. Result	70
12. Test setup photo	71
12.1. Photo of Radiated Emission test	71
12.2. Photo of Conducted Emission test	72

TEST REPORT DECLARATION

Applicant : FN-LINK TECHNOLOGY LIMITED

Address : No.8, Litong Road, Liuyang Economic & Technical Development Zone,
Changsha, Hunan, China

Manufacturer : FN-LINK TECHNOLOGY LIMITED

Address : No.8, Litong Road, Liuyang Economic & Technical Development Zone,
Changsha, Hunan, China

EUT Description : WIFI MODULE

(A) Model No. : 6222B-SRC

(B) Trademark :  欧智通

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247

ANSI C63.10:2013

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....: Yannis Wen
Project Engineer



Approved by (name + signature).....: Reak Yang
Project Manager



Date of issue.....: May 8, 2023

Revision History

Revision	Issue Date	Revisions	Revised By
V0	May 8, 2023	Initial released Issue	Yannis Wen

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) ANSI C63.10 :2013	P
Bandwidth	FCC Part 15: 15.215 ANSI C63.10 :2013	P
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2013	P
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2013	P
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2013	P
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10 :2013	P
Band Edge Compliance	FCC Part 15: 15.247(d) ANSI C63.10 :2013	P
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10 :2013	P
Antenna requirement	FCC Part 15: 15.203	P
Note: 1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable. 4. The conclusion of this test report is judged by actual test data without considering measurement uncertainty.		

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

Description	: WIFI MODULE
Model Number	: 6222B-SRC
Diff	: N/A
Trademark	:  欧智通
Power supply	: DC 3.3V from USB adapter board
Radio Technology	: Bluetooth V5.2 EDR
Operation frequency	: 2402-2480MHz
Channel No.	: 79 Channels
Channel spacing	: 1MHz
Modulation type	: GFSK, $\pi/4$ DQPSK, 8DPSK
Antenna Type	: FPC Antenna, max gain 2.63dBi (Antenna information is provided by applicant.)
Software version	: V1.0
Hardware version	: V1.0
Connector cable loss	: N/A
Intend use environment	: Residential, commercial and light industrial environment

2.2. Accessories of Device (EUT)

Accessories : /

Manufacturer : /


Model : /

Ratings : /

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDoC
1.	Notebook PC	Lenovo	T430	--	--

2.4. Block Diagram of connection between EUT and simulators



2.5. Test Mode Description

Tested mode, channel information		
Mode	Channel	Frequency (MHz)
GFSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480
$\pi/4$ DQPSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480
8DPSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480

2.6. Test Conditions

Items	Required	Actual
Temperature range:	15-35°C	24°C
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	980kPa

2.7. Test Facility

Shenzhen Alpha Product Testing Co., Ltd

Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission

Registration Number: 293961

September 15, 2019 Certificated by IC

Registration Number: CN0085

2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	2.74dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	2.13 dB(Polarize: V)
	2.57dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.77dB(Polarize: V)
	3.80dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	4.13dB(Polarize: H)
	4.16dB(Polarize: V)
Uncertainty for radio frequency	5.4×10^{-8}
Uncertainty for conducted RF Power	0.37dB
Uncertainty for temperature	0.2°C
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

2.9. Test Equipment List

Equipment	Manufacture	Model No.	Firmware version	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	CHENYU	9*6*6	/	N/A	2022.05.17	3Year
Spectrum analyzer	ROHDE&SCHWARZ	FSV40-N	2.3	102137	2022.08.22	1Year
Spectrum analyzer	Agilent	N9020A	A.14.16	MY499100060	2022.08.22	1Year
Receiver	ROHDE&SCHWARZ	ESR	2.28 SP1	1316.3003K03-10 2082-Wa	2022.08.22	1Year
Receiver	R&S	ESCI	4.42 SP1	101165	2022.08.22	1Year
Bilog Antenna	Schwarzbeck	VULB 9168	/	VULB 9168#627	2021.08.30	2Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	/	2106	2021.08.30	2Year
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	/	00059	2021.08.30	2Year
RF Cable	Resenberger	Cable 1	/	RE1	2022.08.22	1Year
RF Cable	Resenberger	Cable 2	/	RE2	2022.08.22	1Year
RF Cable	Resenberger	Cable 3	/	CE1	2022.08.22	1Year
Pre-amplifier	HP	HP8347A	/	2834A00455	2022.08.22	1Year
Pre-amplifier	Agilent	8449B	/	3008A02664	2022.08.22	1Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	/	8126-466	2022.08.22	1Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	/	101043	2022.08.23	1 Year
Horn Antenna	SCHWARZBECK	BBHA9170	/	00946	2021.08.30	2 Year
Preamplifier	SKET	LNPA_1840 -50	/	SK2018101801	2022.08.22	1 Year
Power Meter	Agilent	E9300A	/	MY41496628	2022.08.22	1 Year
Power Sensor	DARE	RPR3006W	/	15100041SNO91	2022.08.22	1 Year
Temp. & Humid. Chamber	Weihuang	WHTH-1000 -40-880	/	100631	2023.04.18	1 Year
Switching Mode Power Supply	JUNKE	JK12010S	/	20140927-6	2022.08.22	1 Year
Adjustable attenuator	MWRFtest	N/A	/	N/A	N/A	N/A
10dB Attenuator	Mini-Circuits	DC-6G	/	N/A	N/A	N/A

Software Information			
Test Item	Software Name	Manufacturer	Version
RE	EZ-EMC	EZ	Alpha-3A1
CE	EZ-EMC	EZ	Alpha-3A1
RF-CE	MTS 8310	MW	V2.0.0.0

3. MAXIMUM PEAK OUTPUT POWER

3.1. Limit


Please refer section 15.247.

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

3.2. Test Procedure

The transmitter output is connected to the RF Power Meter. The RF Power Meter is set to the peak power detection.

3.3. Test Setup



3.4. Test Result

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Limit (dBm)	Verdict
NVNT	1-DH1	2402	Ant1	1.542	0	21	Pass
NVNT	1-DH1	2441	Ant1	2.798	0	21	Pass
NVNT	1-DH1	2480	Ant1	2.68	0	21	Pass
NVNT	1-DH3	2441	Ant1	2.979	0	21	Pass
NVNT	1-DH5	2441	Ant1	2.885	0	21	Pass
NVNT	2-DH1	2402	Ant1	0.836	0	21	Pass
NVNT	2-DH1	2441	Ant1	1.89	0	21	Pass
NVNT	2-DH1	2480	Ant1	0.873	0	21	Pass
NVNT	2-DH3	2441	Ant1	1.663	0	21	Pass
NVNT	2-DH5	2441	Ant1	1.67	0	21	Pass
NVNT	3-DH1	2402	Ant1	0.781	0	21	Pass
NVNT	3-DH1	2441	Ant1	1.902	0	21	Pass
NVNT	3-DH1	2480	Ant1	0.919	0	21	Pass
NVNT	3-DH3	2441	Ant1	1.915	0	21	Pass
NVNT	3-DH5	2441	Ant1	2.077	0	21	Pass

4. BANDWIDTH

4.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


4.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.


4.3. Test Result

-20dB Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	-20 dB Bandwidth (MHz)	Limit -20 dB Bandwidth (MHz)	Verdict
NVNT	1-DH1	2402	Ant1	0.932	0	Pass
NVNT	1-DH1	2441	Ant1	0.834	0	Pass
NVNT	1-DH1	2480	Ant1	0.928	0	Pass
NVNT	2-DH1	2402	Ant1	1.244	0	Pass
NVNT	2-DH1	2441	Ant1	1.246	0	Pass
NVNT	2-DH1	2480	Ant1	1.25	0	Pass
NVNT	3-DH1	2402	Ant1	1.256	0	Pass
NVNT	3-DH1	2441	Ant1	1.256	0	Pass
NVNT	3-DH1	2480	Ant1	1.228	0	Pass

-20dB Bandwidth NVNT 1-DH1 2402MHz Ant1


Date: 26.APR.2023 05:04:12

-20dB Bandwidth NVNT 1-DH1 2441MHz Ant1

Date: 26.APR.2023 05:06:49


-20dB Bandwidth NVNT 1-DH1 2480MHz Ant1

Date: 26.APR.2023 05:08:30

-20dB Bandwidth NVNT 2-DH1 2402MHz Ant1


Date: 26.APR.2023 05:30:29

-20dB Bandwidth NVNT 2-DH1 2441MHz Ant1




Date: 26.APR.2023 05:32:49


-20dB Bandwidth NVNT 2-DH1 2480MHz Ant1



Date: 26.APR.2023 05:37:02


-20dB Bandwidth NVNT 3-DH1 2402MHz Ant1

Date: 26.APR.2023 06:02:32

-20dB Bandwidth NVNT 3-DH1 2441MHz Ant1

Date: 26.APR.2023 06:04:59

-20dB Bandwidth NVNT 3-DH1 2480MHz Ant1




Date: 26.APR.2023 06:06:50

Occupied Channel Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	1-DH1	2402	Ant1	0.859
NVNT	1-DH1	2441	Ant1	0.863
NVNT	1-DH1	2480	Ant1	0.849
NVNT	2-DH1	2402	Ant1	1.169
NVNT	2-DH1	2441	Ant1	1.165
NVNT	2-DH1	2480	Ant1	1.165
NVNT	3-DH1	2402	Ant1	1.171
NVNT	3-DH1	2441	Ant1	1.159
NVNT	3-DH1	2480	Ant1	1.167

OBW NVNT 1-DH1 2402MHz Ant1




Date: 26.APR.2023 05:04:04

OBW NVNT 1-DH1 2441MHz Ant1




Date: 26.APR.2023 05:06:41

OBW NVNT 1-DH1 2480MHz Ant1




Date: 26.APR.2023 05:08:22

OBW NVNT 2-DH1 2402MHz Ant1




Date: 26.APR.2023 05:30:19

OBW NVNT 2-DH1 2441MHz Ant1




Date: 26.APR.2023 05:32:38

OBW NVNT 2-DH1 2480MHz Ant1




Date: 26.APR.2023 05:36:51

OBW NVNT 3-DH1 2402MHz Ant1




Date: 26.APR.2023 06:02:18

OBW NVNT 3-DH1 2441MHz Ant1



Date: 26.APR.2023 06:04:44

OBW NVNT 3-DH1 2480MHz Ant1



Date: 26.APR.2023 06:06:36

5. CARRIER FREQUENCY SEPARATION

5.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW


5.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The carrier frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW.

5.3. Test Result


Condition	Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH1	Ant1	2440.84	2441.842	1.002	0.834	Pass
NVNT	2-DH1	Ant1	2440.84	2441.84	1	0.831	Pass
NVNT	3-DH1	Ant1	2440.838	2441.838	1	0.837	Pass

CFS NVNT 1-DH1 2441MHz Ant1




Date: 26.APR.2023 05:13:24

CFS NVNT 2-DH1 2441MHz Ant1



Date: 26.APR.2023 05:44:52

CFS NVNT 3-DH1 2441MHz Ant1



Date: 26.APR.2023 06:15:12

6. NUMBER OF HOPPING CHANNEL

6.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels


6.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The number of hopping channel was measured by spectrum analyzer with 100kHz RBW and 300KHz VBW.

6.3. Test Result


Condition	Mode	Hopping Number	Limit	Verdict
NVNT	1-DH1	79	15	Pass
NVNT	2-DH1	79	15	Pass
NVNT	3-DH1	79	15	Pass

Hopping No. NVNT 1-DH1 2441MHz Ant1




Date: 26.APR.2023 05:19:23

Hopping No. NVNT 2-DH1 2441MHz Ant1



Date: 26.APR.2023 05:48:24

Hopping No. NVNT 3-DH1 2441MHz Ant1



Date: 26.APR.2023 06:18:48

7. DWELL TIME

7.1. Test limit

Please refer section 15.247

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5

MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 seconds multiplied by the number of hopping channel employed.

7.2. Test Procedure

7.2.1. Place the EUT on the table and set it in transmitting mode.

7.2.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

7.2.3. Set center frequency of spectrum analyzer = operating frequency.

7.2.4. Set the spectrum analyzer as RBW=1MHz, VBW=1MHz, Span = 0Hz, Sweep = auto.


7.2.5. Repeat above procedures until all frequency measured were complete.

7.3. Test Result

Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH1	2402	Ant1	0.371	118.720	315	31600	400	Pass
NVNT	1-DH1	2441	Ant1	0.37	118.400	317	31600	400	Pass
NVNT	1-DH1	2480	Ant1	0.369	118.080	316	31600	400	Pass
NVNT	1-DH3	2441	Ant1	1.627	260.320	156	31600	400	Pass
NVNT	1-DH5	2441	Ant1	2.875	306.667	103	31600	400	Pass
NVNT	2-DH1	2402	Ant1	0.378	120.960	316	31600	400	Pass
NVNT	2-DH1	2441	Ant1	0.379	121.280	501	31600	400	Pass
NVNT	2-DH1	2480	Ant1	0.378	120.960	501	31600	400	Pass
NVNT	2-DH3	2441	Ant1	1.63	260.800	158	31600	400	Pass
NVNT	2-DH5	2441	Ant1	2.876	306.773	102	31600	400	Pass
NVNT	3-DH1	2402	Ant1	0.379	121.280	317	31600	400	Pass
NVNT	3-DH1	2441	Ant1	0.379	121.280	316	31600	400	Pass
NVNT	3-DH1	2480	Ant1	0.38	121.600	317	31600	400	Pass
NVNT	3-DH3	2441	Ant1	1.63	260.800	187	31600	400	Pass
NVNT	3-DH5	2441	Ant1	2.879	307.093	101	31600	400	Pass


Note: Total Dwell Time= Pulse Time* Burst Count

Dwell NVNT 1-DH1 2402MHz Ant1 One Burst




Date: 26.APR.2023 05:10:32

Dwell NVNT 1-DH1 2402MHz Ant1 Accumulated




Date: 26.APR.2023 05:11:06

Dwell NVNT 1-DH1 2441MHz Ant1 One Burst




Date: 26.APR.2023 05:19:32

Dwell NVNT 1-DH1 2441MHz Ant1 Accumulated




Date: 26.APR.2023 05:20:07

Dwell NVNT 1-DH1 2480MHz Ant1 One Burst




Date: 26.APR.2023 05:22:31

Dwell NVNT 1-DH1 2480MHz Ant1 Accumulated




Date: 26.APR.2023 05:23:06

Dwell NVNT 1-DH3 2441MHz Ant1 One Burst




Date: 26.APR.2023 05:23:44

Dwell NVNT 1-DH3 2441MHz Ant1 Accumulated




Date: 26.APR.2023 05:24:18

Dwell NVNT 1-DH5 2441MHz Ant1 One Burst




Date: 26.APR.2023 05:27:35

Dwell NVNT 1-DH5 2441MHz Ant1 Accumulated




Date: 26.APR.2023 05:28:09

Dwell NVNT 2-DH1 2402MHz Ant1 One Burst




Date: 26.APR.2023 05:39:47

Dwell NVNT 2-DH1 2402MHz Ant1 Accumulated




Date: 26.APR.2023 05:40:21

Dwell NVNT 2-DH1 2441MHz Ant1 One Burst




Date: 26.APR.2023 05:48:37

Dwell NVNT 2-DH1 2441MHz Ant1 Accumulated




Date: 26.APR.2023 05:49:11

Dwell NVNT 2-DH1 2480MHz Ant1 One Burst




Date: 26.APR.2023 05:50:55

Dwell NVNT 2-DH1 2480MHz Ant1 Accumulated




Date: 26.APR.2023 05:51:29

Dwell NVNT 2-DH3 2441MHz Ant1 One Burst




Date: 26.APR.2023 05:53:42

Dwell NVNT 2-DH3 2441MHz Ant1 Accumulated




Date: 26.APR.2023 05:54:17

Dwell NVNT 2-DH5 2441MHz Ant1 One Burst




Date: 26.APR.2023 06:00:48

Dwell NVNT 2-DH5 2441MHz Ant1 Accumulated




Date: 26.APR.2023 06:01:22

Dwell NVNT 3-DH1 2402MHz Ant1 One Burst




Date: 26.APR.2023 06:47:20

Dwell NVNT 3-DH1 2402MHz Ant1 Accumulated




Date: 26.APR.2023 06:47:55

Dwell NVNT 3-DH1 2441MHz Ant1 One Burst




Date: 26.APR.2023 06:19:06

Dwell NVNT 3-DH1 2441MHz Ant1 Accumulated




Date: 26.APR.2023 06:19:41

Dwell NVNT 3-DH1 2480MHz Ant1 One Burst




Date: 26.APR.2023 06:19:59

Dwell NVNT 3-DH1 2480MHz Ant1 Accumulated




Date: 26.APR.2023 06:20:33

Dwell NVNT 3-DH3 2441MHz Ant1 One Burst




Date: 26.APR.2023 06:52:00

Dwell NVNT 3-DH3 2441MHz Ant1 Accumulated




Date: 26.APR.2023 06:52:35

Dwell NVNT 3-DH5 2441MHz Ant1 One Burst



Date: 26.APR.2023 06:55:04

Dwell NVNT 3-DH5 2441MHz Ant1 Accumulated



Date: 26.APR.2023 06:55:38

8. RADIATED EMISSIONS

8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band


MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

15.209 Limit


FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

8.2. Block Diagram of Test setup


8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



8.2.2 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

8.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.
- (2) Setup EUT and simulator as shown in section 1.4 and 6.1
- (3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
 - (a) Change work frequency or channel of device if practicable.
 - (b) Change modulation type of device if practicable.
 - (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
- (4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated
- (5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013on Radiated Emission test.
- (6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

8.4. Test Result


We have scanned the 10th harmonic from 9KHz to the EUT's highest frequency.
Detailed information please see the following page.

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

From 30MHz to 1000MHz: Conclusion: PASS


Horizontal:



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Antenna	Table
		MHz	Level	Factor	ment			Height	Degree
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		63.4837	15.75	12.51	28.26	40.00	-11.74	peak	
2		92.1711	19.03	10.22	29.25	43.50	-14.25	peak	
3		135.2371	19.61	13.97	33.58	43.50	-9.92	peak	
4	*	159.4859	21.62	15.04	36.66	43.50	-6.84	peak	
5		292.4341	10.18	13.93	24.11	46.00	-21.89	peak	
6		840.0651	10.88	23.27	34.15	46.00	-11.85	peak	

Note: 1. *: Maximum data; x: Over limit; !: over margin.

2. Measurement = Reading Level + Correct Factor; Correct Factor = Antenna Factor + Cable Loss.

Vertical:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	36.2965	20.10	13.85	33.95	40.00	-6.05	peak		
2		59.4127	19.21	13.25	32.46	40.00	-7.54	peak		
3		63.4614	19.94	12.51	32.45	40.00	-7.55	peak		
4		102.0252	18.84	11.05	29.89	43.50	-13.61	peak		
5		157.1542	14.00	15.05	29.05	43.50	-14.45	peak		
6		281.7640	10.07	13.63	23.70	46.00	-22.30	peak		

Note: 1. *: Maximum data; x: Over limit; !: over margin.

2. Measurement = Reading Level + Correct Factor; Correct Factor = Antenna Factor + Cable Loss.

Remark: All modes have been tested, and only worst data of GFSK mode, Channel 2441MHz was listed in this report.

From 1G-25GHz

Test Mode: GFSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	47.21	V	33.95	10.18	34.26	57.08	74	-16.92	PK
4804	37.80	V	33.95	10.18	34.26	47.67	54	-6.33	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	44.78	H	33.95	10.18	34.26	54.65	74	-19.35	PK
4804	35.08	H	33.95	10.18	34.26	44.95	54	-9.05	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: GFSK TX Mid									
4882	42.15	V	33.93	10.2	34.29	51.99	74	-22.01	PK
4882	35.45	V	33.93	10.2	34.29	45.29	54	-8.71	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	45.05	H	33.93	10.2	34.29	54.89	74	-19.11	PK
4882	35.64	H	33.93	10.2	34.29	45.48	54	-8.52	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: GFSK TX High									
4960	46.37	V	33.93	10.2	34.29	56.21	74	-17.79	PK
4960	33.57	V	33.93	10.2	34.29	43.41	54	-10.59	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	42.75	H	33.93	10.2	34.29	52.59	74	-21.41	PK
4960	33.78	H	33.93	10.2	34.29	43.62	54	-10.38	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
Note:									
1, Result = Read level + Antenna factor + cable loss-Amp factor									
2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.									