

# **FCC ID: 2A5PL-STRKPRO2**

## **Portable device**

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm

and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

Transmit Frequency (GHz)	Mode	Max Conducted Power (dBm)	tune up maximum power(dBm)	Result calculation	1-g SAR
2.402	GFSK	0.60	1	0.39	3
2.441	GFSK	-1.21	-1	0.25	3
2.480	GFSK	-1.32	-1	0.25	3
2.402	Pi/4 DQPSK	0.67	1	0.39	3
2.441	Pi/4 DQPSK	-0.47	0	0.31	3
2.480	Pi/4 DQPSK	-0.64	0	0.31	3

Transmit Frequency (GHz)	Mode	Max Conducted Power (dBm)	tune up maximum power(dBm)	Result calculation	1-g SAR
2.402	GFSK 1M	-2.32	-2	0.20	3
2.440	GFSK 1M	2.20	3	0.62	3
2.480	GFSK 1M	3.33	4	0.79	3
2.402	Pi/4-DQPSK 2M	-2.69	-2	0.20	3
2.440	Pi/4-DQPSK 2M	-1.64	-1	0.25	3
2.480	Pi/4-DQPSK 2M	-0.60	0	0.31	3

Conclusion:

For the max result :  $0.79 \leq 3.0$  for 1-g SAR extremity SAR, No SAR is required.