



Maximum Permissible Exposure (MPE) & Exposure evaluation

Report identification number: 1-1068/20-02-08 MPE (FCC_ISED)

Certification numbers and labeling requirements	
FCC ID	JFZR4180DAN
ISED number	1752B-R4180DAN
HVIN (Hardware Version Identification Number)	ESW-R4180DAN
PMN (Product Marketing Name)	ESW- R4180DAN
FVIN (Firmware Version Identification Number)	-/-
HMN (Host Marketing Name)	ESW- R4180DAN

This report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:



Alexander Hnatovskiy
Lab Manager
Radio Communications & EMC



Marco Scigliano
Testing Manager
Radio Communications & EMC

EUT technologies:

Technologies:	Max. declared power [dBm]		Antenna gain max.: [dBi]
	conducted	EIRP	
UPCS 1925	20.0 (avg)	decl. 23. (avg)	3.0

Prediction of MPE limit at given distance - FCC

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

where: S = Power density

P = Power input to the antenna

G = Antenna gain

R = Distance to the center of radiation of the antenna

PG = Output Power including antenna gain

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure"

Frequency Range (MHz)	Power Density (mW/cm ²)	Averaging Time (minutes)
300 -1500	f/1500	30
1500 - 100000	1.0	30

where f = Frequency (MHz)

Prediction: worst case

	Technology	UPCS
	Frequency	1925 MHz
P	Declared max power input to the antenna	20 dBm
R	Distance	20 cm
G	Antenna gain	3 dBi
S	MPE limit for uncontrolled exposure	1.0000 mW/cm ²
	Calculated Power density:	0.0397 mW/cm ²
	Calculated percentage of limit:	3.97%

This prediction demonstrates the following:

The power density levels for FCC at a distance of 20 cm are below the maximum levels allowed by regulations.

Prediction of MPE limit at given distance - ISED

RSS-102, Issue 5, 2.5.2

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5} \text{ W}$ (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834} \text{ W}$ (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

Prediction: worst case

		UPCS	
	Frequency	1920	MHz
R	Distance	20	cm
P	Max power input to the antenna	20	dBm
G	Antenna gain	3	dBi
PG	Maximum EIRP	23	dBm
PG	Maximum EIRP	199.5	mW
	Exclusion Limit from above:	2.30	W
	Calculated percentage of Limit:	8.69%	

Conclusion: RF exposure evaluation is not required.