



No. I22Z60667-SEM01

For

HONOR Device Co., Ltd.

Smart Phone

Model Name: VNE-N41

with

Hardware Version: HN2VNEM

Software Version: 4.2.0.55(C900E55R1P1)

FCC ID: 2AYGCVNE-N41

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No. 51, Xueyuan Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: cttl_terminals@caict.ac.cn, website: www.caict.ac.cn



Picture 1: Constituents of the sample



Picture 2: Left Head Touch Cheek Position



Picture 3: Left Head Tilt 15° Position




Picture 4: Right Head Touch Cheek Position




Picture 5: Right Head Tilt 15° Position

Test positions for body:

The Body SAR is tested at the following 9 test positions all with the distance =0/10/15mm between the EUT and the phantom bottom:




Picture 6: Front 10mm



Picture 7: Rear 10mm




Picture 8: Left 10mm




Picture 9: Right 10mm




Picture 10: Top 10mm



Picture 11: Bottom 10mm



Picture 12: Front 15mm



Picture 13: Rear 15mm



Picture 14: Top 0mm