

# FCC Part 15C Measurement and Test Report

For

**Intracom Asia Co., Ltd.**

**4F., No. 77, Sec. 1, Xintai 5th Rd., Xinzhi Dist., New Taipei City 221,**

**Taiwan**

**FCC ID: 2ADQY525756**

**FCC Rule(s):** FCC Part 15C

**Product Description:** Wireless 300N Range Extender

**Tested Model:** 525756

**Report No.:** STR15048243I-1

**Tested Date:** 2015-04-29 to 2015-05-12

**Issued Date:** 2015-05-14

**Tested By:** Susan Su / Engineer

*Susan Su*

**Reviewed By:** Lahm Peng / EMC Manager

*Lahm peng*

**Approved & Authorized By:** Jandy so / PSQ Manager

*Jandyso*

**Prepared By:**

**Shenzhen SEM.Test Technology Co., Ltd.**

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,  
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

**TABLE OF CONTENTS**

|                                                             |           |
|-------------------------------------------------------------|-----------|
| <b>1. GENERAL INFORMATION.....</b>                          | <b>3</b>  |
| 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)..... | 3         |
| 1.2 TEST STANDARDS.....                                     | 4         |
| 1.3 TEST METHODOLOGY.....                                   | 4         |
| 1.4 TEST FACILITY.....                                      | 4         |
| 1.5 EUT SETUP AND TEST MODE.....                            | 5         |
| <b>2. SUMMARY OF TEST RESULTS .....</b>                     | <b>6</b>  |
| <b>3. RF EXPOSURE .....</b>                                 | <b>7</b>  |
| 3.1 STANDARD APPLICABLE.....                                | 7         |
| 3.2 TEST RESULT.....                                        | 7         |
| <b>4. ANTENNA REQUIREMENT .....</b>                         | <b>8</b>  |
| 4.1 STANDARD APPLICABLE.....                                | 8         |
| 4.2 EVALUATION INFORMATION .....                            | 8         |
| <b>5. POWER SPECTRAL DENSITY .....</b>                      | <b>9</b>  |
| 5.1 STANDARD APPLICABLE.....                                | 9         |
| 5.2 TEST EQUIPMENT LIST AND DETAILS .....                   | 9         |
| 5.3 TEST PROCEDURE.....                                     | 9         |
| 5.4 ENVIRONMENTAL CONDITIONS .....                          | 9         |
| 5.5 SUMMARY OF TEST RESULTS/PLOTS .....                     | 10        |
| <b>6. 6DB BANDWIDTH .....</b>                               | <b>23</b> |
| 6.1 STANDARD APPLICABLE.....                                | 23        |
| 6.2 TEST EQUIPMENT LIST AND DETAILS .....                   | 23        |
| 6.3 TEST PROCEDURE.....                                     | 23        |
| 6.4 ENVIRONMENTAL CONDITIONS .....                          | 23        |
| 6.5 SUMMARY OF TEST RESULTS/PLOTS .....                     | 24        |
| <b>7. RF OUTPUT POWER.....</b>                              | <b>37</b> |
| 7.1 STANDARD APPLICABLE.....                                | 37        |
| 7.2 TEST EQUIPMENT LIST AND DETAILS .....                   | 37        |
| 7.3 TEST PROCEDURE.....                                     | 37        |
| 7.4 ENVIRONMENTAL CONDITIONS .....                          | 37        |
| 7.5 SUMMARY OF TEST RESULTS/PLOTS .....                     | 38        |
| <b>8. FIELD STRENGTH OF SPURIOUS EMISSIONS .....</b>        | <b>51</b> |
| 8.1 MEASUREMENT UNCERTAINTY .....                           | 51        |
| 8.2 STANDARD APPLICABLE.....                                | 51        |
| 8.3 TEST EQUIPMENT LIST AND DETAILS .....                   | 51        |
| 8.4 TEST PROCEDURE.....                                     | 52        |
| 8.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....           | 53        |
| 8.6 ENVIRONMENTAL CONDITIONS .....                          | 53        |
| 8.7 SUMMARY OF TEST RESULTS/PLOTS .....                     | 53        |
| <b>9. OUT OF BAND EMISSIONS.....</b>                        | <b>82</b> |
| 9.1 STANDARD APPLICABLE.....                                | 82        |
| 9.2 TEST EQUIPMENT LIST AND DETAILS .....                   | 82        |
| 9.3 TEST PROCEDURE.....                                     | 82        |
| 9.4 ENVIRONMENTAL CONDITIONS .....                          | 83        |
| 9.5 SUMMARY OF TEST RESULTS/PLOTS .....                     | 83        |
| <b>10. CONDUCTED EMISSIONS .....</b>                        | <b>92</b> |
| 10.1 MEASUREMENT UNCERTAINTY .....                          | 92        |
| 10.2 TEST EQUIPMENT LIST AND DETAILS .....                  | 92        |
| 10.3 TEST PROCEDURE.....                                    | 92        |
| 10.4 BASIC TEST SETUP BLOCK DIAGRAM.....                    | 92        |
| 10.5 ENVIRONMENTAL CONDITIONS .....                         | 93        |
| 10.6 TEST RECEIVER SETUP .....                              | 93        |
| 10.7 SUMMARY OF TEST RESULTS/PLOTS .....                    | 93        |
| 10.8 CONDUCTED EMISSIONS TEST DATA.....                     | 93        |

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: Intracom Asia Co., Ltd.  
 Address of applicant: 4F., No. 77, Sec. 1, Xintai 5th Rd., Xinzhi Dist., New Taipei City 221, Taiwan  
 Manufacturer: Intracom Asia Co., Ltd.  
 Address of manufacturer: 4F., No. 77, Sec. 1, Xintai 5th Rd., Xinzhi Dist., New Taipei City 221, Taiwan

| General Description of EUT                                                             |                              |
|----------------------------------------------------------------------------------------|------------------------------|
| Product Name:                                                                          | Wireless 300N Range Extender |
| Trade Name:                                                                            | Manhattan                    |
| Model No.:                                                                             | 525756                       |
| Adding Model(s):                                                                       | /                            |
| Rated Voltage:                                                                         | AC 100-240V                  |
| Note: The test data is gathered from a production sample provided by the manufacturer. |                              |

| Technical Characteristics of EUT |                                                                      |
|----------------------------------|----------------------------------------------------------------------|
| Support Standards:               | 802.11b, 802.11g, 802.11n                                            |
| Frequency Range:                 | 2412-2462MHz for 802.11b/g/n(HT20)<br>2422-2452MHz for 802.11n(HT40) |
| RF Output Power:                 | 17.31dBm (Conducted)                                                 |
| Type of Modulation:              | CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM                                  |
| Data Rate:                       | 1-11Mbps, 6-54Mbps, up to 150Mbps                                    |
| Quantity of Channels:            | 11 for 802.11b/g/n(HT20); 7 for 802.11n(HT40)                        |
| Channel Separation:              | 5MHz                                                                 |
| Type of Antenna:                 | Integral                                                             |
| Antenna Gain:                    | 2dBi                                                                 |
| Lowest Internal Frequency        | 40MHz                                                                |

## 1.2 Test Standards

The following report is prepared on behalf of the Intracom Asia Co., Ltd. in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide KDB 558074 D01 V03r02 for digital transmission systems shall be performed also.

## 1.4 Test Facility

### **FCC – Registration No.: 934118**

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

### **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

### **CNAS Registration No.: L4062**

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2<sup>nd</sup> Road, Bao'an District, Shenzhen, P.R.C (518101).

## 1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

| Test Mode List |              |                           |
|----------------|--------------|---------------------------|
| Test Mode      | Description  | Remark                    |
| TM1            | 802.11b      | 2412MHz, 2437MHz, 2462MHz |
| TM2            | 802.11g      | 2412MHz, 2437MHz, 2462MHz |
| TM3            | 802.11n-HT20 | 2412MHz, 2437MHz, 2462MHz |
| TM4            | 802.11n-HT40 | 2422MHz, 2437MHz, 2452MHz |

| EUT Cable List and Details |            |                      |                        |
|----------------------------|------------|----------------------|------------------------|
| Cable Description          | Length (m) | Shielded/ Unshielded | With / Without Ferrite |
| RJ45                       | 1.0        | Unshielded           | Without Ferrite        |

| Special Cable List and Details |            |                     |                        |
|--------------------------------|------------|---------------------|------------------------|
| Cable Description              | Length (m) | Shielded/Unshielded | With / Without Ferrite |
|                                |            |                     |                        |

| Auxiliary Equipment List and Details |              |       |               |
|--------------------------------------|--------------|-------|---------------|
| Description                          | Manufacturer | Model | Serial Number |
|                                      |              |       |               |

## 2. SUMMARY OF TEST RESULTS

| <b>FCC Rules</b>            | <b>Description of Test Item</b>   | <b>Result</b> |
|-----------------------------|-----------------------------------|---------------|
| § 2.1093                    | RF Exposure                       | Compliant     |
| § 15.203; § 15.247(b)(4)(i) | Antenna Requirement               | Compliant     |
| § 15.207(a)                 | Conducted Emission                | Compliant     |
| § 15.247(e)                 | Power Spectral Density            | Compliant     |
| § 15.247(a)(2)              | 6 dB Bandwidth                    | Compliant     |
| § 15.247(b)(3)              | RF Output Power                   | Compliant     |
| § 15.209(a)                 | Radiated Emission                 | Compliant     |
| § 15.247(d)                 | Band Edge (Out of Band Emissions) | Compliant     |

N/A: not applicable

### **3. RF Exposure**

---

#### **3.1 Standard Applicable**

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

#### **3.2 Test Result**

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

## **4. Antenna Requirement**

---

### **4.1 Standard Applicable**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **4.2 Evaluation Information**

This product has an integral antenna, fulfill the requirement of this section.

## 5. Power Spectral Density

### 5.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 5.2 Test Equipment List and Details

| Description       | Manufacturer | Model       | Serial Number | Cal. Date  | Due. Date  |
|-------------------|--------------|-------------|---------------|------------|------------|
| Spectrum Analyzer | Agilent      | E4402B      | US41192821    | 2014-05-28 | 2015-05-27 |
| Attenuator        | ATTEN        | ATS100-4-20 | /             | 2014-05-28 | 2015-05-27 |

### 5.3 Test Procedure

According to the KDB 558074 D01 V03r02, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set VBW  $\geq 3 \times \text{RBW}$ .
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span/RBW}$ .
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

### 5.4 Environmental Conditions


|                    |           |
|--------------------|-----------|
| Temperature:       | 26° C     |
| Relative Humidity: | 54%       |
| ATM Pressure:      | 1011 mbar |

## 5.5 Summary of Test Results/Plots


| Test Mode       | Test Channel<br>MHz | PSD Ant.A<br>dBm/100kHz | PSD Ant.B<br>dBm/100kHz | Total PSD<br>dBm/100kHz | Limit<br>dBm/3kHz |
|-----------------|---------------------|-------------------------|-------------------------|-------------------------|-------------------|
| 802.11b         | 2412                | 3.622                   | 4.939                   | 7.341                   | 8                 |
|                 | 2437                | 4.99                    | 4.548                   | 7.785                   | 8                 |
|                 | 2462                | 5.478                   | 4.814                   | 7.971                   | 8                 |
| 802.11g         | 2412                | -4.145                  | -3.949                  | -1.036                  | 8                 |
|                 | 2437                | -3.053                  | -3.009                  | -0.021                  | 8                 |
|                 | 2462                | -2.835                  | -2.653                  | 0.267                   | 8                 |
| 802.11n<br>HT20 | 2412                | -4.444                  | -4.295                  | -1.359                  | 8                 |
|                 | 2437                | -3.306                  | -3.732                  | -0.503                  | 8                 |
|                 | 2462                | -3.863                  | -3.715                  | -0.778                  | 8                 |
| 802.11n<br>HT40 | 2422                | -8.388                  | -8.12                   | -5.242                  | 8                 |
|                 | 2437                | -7.467                  | -8.072                  | -4.749                  | 8                 |
|                 | 2452                | -7.262                  | -8.205                  | -4.698                  | 8                 |

Please refer to the following test plots:


For Ant.A  
802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel




802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel




802.11n-HT20-High Channel




802.11n-HT40-Low Channel




802.11n-HT40-Middle Channel




802.11n-HT40-High Channel




For Ant.B  
802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel




802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel




802.11n-HT20-High Channel




802.11n-HT40-Low Channel



802.11n-HT40-Middle Channel



802.11n-HT40-High Channel



## 6. 6dB Bandwidth

### 6.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 6.2 Test Equipment List and Details

| Description       | Manufacturer | Model       | Serial Number | Cal. Date  | Due. Date  |
|-------------------|--------------|-------------|---------------|------------|------------|
| Spectrum Analyzer | Agilent      | E4402B      | US41192821    | 2014-05-28 | 2015-05-27 |
| Attenuator        | ATTEN        | ATS100-4-20 | /             | 2014-05-28 | 2015-05-27 |

### 6.3 Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 6.4 Environmental Conditions


|                    |           |
|--------------------|-----------|
| Temperature:       | 25° C     |
| Relative Humidity: | 53%       |
| ATM Pressure:      | 1018 mbar |

## 6.5 Summary of Test Results/Plots


| Test Mode    | Test Channel<br>MHz | 6 dB BW<br>Ant.A kHz | 99% BW<br>Ant.A kHz | 6 dB BW<br>Ant.B kHz | 99% BW<br>Ant.B kHz | Limit<br>kHz |
|--------------|---------------------|----------------------|---------------------|----------------------|---------------------|--------------|
| 802.11b      | 2412                | 10038                | 14894.8             | 10086                | 14949.9             | >500         |
|              | 2437                | 10013                | 14936.8             | 10097                | 14956.4             | >500         |
|              | 2462                | 10088                | 14976.8             | 10079                | 14945.8             | >500         |
| 802.11g      | 2412                | 16551                | 16475.4             | 16551                | 16476.0             | >500         |
|              | 2437                | 16506                | 16469.0             | 16592                | 16494.7             | >500         |
|              | 2462                | 16582                | 16467.1             | 16550                | 16497.0             | >500         |
| 802.11n-HT20 | 2412                | 17780                | 17655.7             | 17822                | 17674.2             | >500         |
|              | 2437                | 17798                | 17671.5             | 17839                | 17682.5             | >500         |
|              | 2462                | 17808                | 17630.8             | 17841                | 17701.2             | >500         |
| 802.11n-HT40 | 2422                | 36466                | 35966.5             | 36530                | 36020.0             | >500         |
|              | 2437                | 36450                | 35977.2             | 36534                | 36034.3             | >500         |
|              | 2452                | 36410                | 35937.1             | 36512                | 36009.2             | >500         |

Please refer to the following test plots:


For Ant.A  
802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




## 802.11g-Middle Channel




## 802.11g-High Channel




802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel




802.11n-HT20-High Channel




802.11n-HT40-Low Channel




802.11n-HT40-Middle Channel




802.11n-HT40-High Channel




For Ant.B  
802.11b-Low Channel




802.11b-Middle Channel




802.11b-High Channel




802.11g-Low Channel




802.11g-Middle Channel




802.11g-High Channel




802.11n-HT20-Low Channel




802.11n-HT20-Middle Channel




802.11n-HT20-High Channel




802.11n-HT40-Low Channel



802.11n-HT40-Middle Channel



802.11n-HT40-High Channel



## 7. RF Output Power

### 7.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

### 7.2 Test Equipment List and Details

| Description       | Manufacturer | Model       | Serial Number | Cal. Date  | Due. Date  |
|-------------------|--------------|-------------|---------------|------------|------------|
| Spectrum Analyzer | Agilent      | E4402B      | US41192821    | 2014-05-28 | 2015-05-27 |
| Attenuator        | ATTEN        | ATS100-4-20 | /             | 2014-05-28 | 2015-05-27 |

### 7.3 Test Procedure

According to section 15.247(b)-power output of the KDB-558074 D01 V03r02, 9.2.2.2 (channel integration method) When this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW  $\geq 3 \times$  RBW.
- d) Number of points in sweep  $\geq 2 \times \text{span} / \text{RBW}$ . (This gives bin-to-bin spacing  $\leq \text{RBW}/2$ , so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle  $\geq 98$  %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run” .
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

### 7.4 Environmental Conditions


|                    |           |
|--------------------|-----------|
| Temperature:       | 26° C     |
| Relative Humidity: | 57%       |
| ATM Pressure:      | 1011 mbar |

## 7.5 Summary of Test Results/Plots


| Test Mode            | Frequency<br>MHz | Reading Ant.A<br>dBm | Reading Ant.B<br>dBm | Output Power<br>mW | Limit<br>mW |
|----------------------|------------------|----------------------|----------------------|--------------------|-------------|
| 802.11b_1Mbps        | 2412             | 12.94                | 13.31                | 16.14              | 1000        |
|                      | 2437             | 14.09                | 13.72                | 16.92              | 1000        |
|                      | 2462             | 14.35                | 14.24                | 17.31              | 1000        |
| 802.11g_6Mbps        | 2412             | 8.96                 | 9.83                 | 12.43              | 1000        |
|                      | 2437             | 10.28                | 10.02                | 13.16              | 1000        |
|                      | 2462             | 10.42                | 9.75                 | 13.11              | 1000        |
| 802.11n<br>HT20_MCS0 | 2412             | 9.22                 | 9.25                 | 12.25              | 1000        |
|                      | 2437             | 10.17                | 9.92                 | 13.06              | 1000        |
|                      | 2462             | 10.57                | 10.27                | 13.43              | 1000        |
| 802.11n<br>HT40_MCS0 | 2422             | 8.43                 | 8.45                 | 11.45              | 1000        |
|                      | 2437             | 9.03                 | 8.82                 | 11.94              | 1000        |
|                      | 2452             | 9.31                 | 9.21                 | 12.27              | 1000        |

Please refer to the following test plots:


For Ant.A  
802.11b-1Mbps-Low Channel




802.11b -1Mbps-Middle Channel




802.11b -1Mbps-High Channel




802.11g-6Mbps-Low Channel




## 802.11g-6Mbps-Middle Channel




## 802.11g-6Mbps-High Channel




802.11n-HT20-MCS0-Low Channel




802.11n-HT20-MCS0-Middle Channel




802.11n-HT20-MCS0-High Channel




802.11n-HT40-MCS0-Low Channel




802.11n-HT40-MCS0-Middle Channel




802.11n-HT40-MCS0-High Channel




For Ant.B  
802.11b-1Mbps-Low Channel




802.11b -1Mbps-Middle Channel




802.11b -1Mbps-High Channel




802.11g-6Mbps-Low Channel




802.11g-6Mbps-Middle Channel




802.11g-6Mbps-High Channel




802.11n-HT20-MCS0-Low Channel




802.11n-HT20-MCS0-Middle Channel




802.11n-HT20-MCS0-High Channel




802.11n-HT40-MCS0-Low Channel



802.11n-HT40-MCS0-Middle Channel



802.11n-HT40-MCS0-High Channel



## 8. Field Strength of Spurious Emissions

### 8.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is  $\pm 5.10$  dB.

### 8.2 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

### 8.3 Test Equipment List and Details



| Description              | Manufacturer         | Model     | Serial Number | Cal. Date  | Due. Date  |
|--------------------------|----------------------|-----------|---------------|------------|------------|
| Spectrum Analyzer        | R&S                  | FSP       | 836079/035    | 2014-05-28 | 2015-05-27 |
| EMI Test Receiver        | R&S                  | ESVB      | 825471/005    | 2014-05-28 | 2015-05-27 |
| Pre-amplifier            | Agilent              | 8447F     | 3113A06717    | 2014-05-28 | 2015-05-27 |
| Pre-amplifier            | Compliance Direction | PAP-0118  | 24002         | 2014-05-28 | 2015-05-27 |
| Trilog Broadband Antenna | SCHWARZBECK          | VULB9163  | 9163-333      | 2014-05-24 | 2015-05-23 |
| Horn Antenna             | ETS                  | 3117      | 00086197      | 2014-05-24 | 2015-05-23 |
| Horn Antenna             | ETS                  | 3116B     | 00088203      | 2014-05-24 | 2015-05-23 |
| Loop Antenna             | SCHWARZECK           | HFRA 5165 | 9365          | 2014-05-24 | 2015-05-23 |

## 8.4 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

## 8.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$


## 8.6 Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 52%       |
| ATM Pressure:      | 1012 mbar |

## 8.7 Summary of Test Results/Plots


According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:

*Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.*

**Plot of Radiated Emissions Test Data (30MHz to 1GHz)**EUT: *Wireless 300N Range Extender*Tested Model: *525756*Operating Condition: *802.11b Transmitting Low Channel-2412MHz*Comment: *AC 120V/60Hz*Test Specification: *Horizontal*

| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ° ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|-----------------|----------------|--------|
| 1   | 125.0066           | 21.54               | 3.61            | 25.15              | 43.50             | -18.35         | 114             | 100            | peak   |
| 2   | 156.4578           | 24.11               | 2.58            | 26.69              | 43.50             | -16.81         | 270             | 100            | peak   |
| 3   | 368.1116           | 33.66               | 9.23            | 42.89              | 46.00             | -3.11          | 360             | 100            | peak   |
| 4   | 440.1963           | 23.35               | 10.03           | 33.38              | 46.00             | -12.62         | 116             | 100            | peak   |

Test Specification: Vertical




| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 240.8304  | 25.45    | 6.36    | 31.81    | 46.00    | -14.19 | 178    | 100    | peak   |
| 2   | 258.3264  | 35.80    | 6.98    | 42.78    | 46.00    | -3.22  | 224    | 100    | peak   |
| 3   | 366.8231  | 33.92    | 9.22    | 43.14    | 46.00    | -2.86  | 160    | 100    | peak   |
| 4   | 524.5541  | 24.80    | 11.36   | 36.16    | 46.00    | -9.84  | 290    | 100    | peak   |

Operating Condition: 802.11b Transmitting Middle Channel-2437MHz


Comment: AC 120V/60Hz

Test Specification: Horizontal



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ° ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|-----------------|----------------|--------|
| 1   | 156.4578           | 26.73               | 2.58            | 29.31              | 43.50             | -14.19         | 256             | 100            | peak   |
| 2   | 261.9753           | 24.69               | 7.17            | 31.86              | 46.00             | -14.14         | 360             | 100            | peak   |
| 3   | 361.7139           | 35.21               | 9.24            | 44.45              | 46.00             | -1.55          | 360             | 100            | peak   |
| 4   | 441.7426           | 23.15               | 10.06           | 33.21              | 46.00             | -12.79         | 360             | 100            | peak   |

Test Specification: Vertical




| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 261.9753  | 36.22    | 7.17    | 43.39    | 46.00    | -2.61  | 176    | 100    | peak   |
| 2   | 362.9845  | 34.68    | 9.24    | 43.92    | 46.00    | -2.08  | 255    | 100    | peak   |
| 3   | 517.2480  | 26.55    | 11.30   | 37.85    | 46.00    | -8.15  | 360    | 100    | peak   |

Operating Condition: 802.11b Transmitting High Channel-2462MHz


Comment: AC 120V/60Hz

Test Specification: Horizontal




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ° ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|-----------------|----------------|--------|
| 1   | 154.8205           | 23.34               | 2.55            | 25.89              | 43.50             | -17.61         | 360             | 100            | peak   |
| 2   | 262.8955           | 21.91               | 7.23            | 29.14              | 46.00             | -16.86         | 225             | 100            | peak   |
| 3   | 368.1116           | 35.34               | 9.23            | 44.57              | 46.00             | -1.43          | 160             | 100            | peak   |
| 4   | 441.7426           | 23.74               | 10.06           | 33.80              | 46.00             | -12.20         | 310             | 100            | peak   |

Test Specification: Vertical




| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 235.8164  | 27.84    | 6.07    | 33.91    | 46.00    | -12.09 | 174    | 100    | peak   |
| 2   | 259.2338  | 35.75    | 7.01    | 42.76    | 46.00    | -3.24  | 160    | 100    | peak   |
| 3   | 361.7139  | 32.06    | 9.24    | 41.30    | 46.00    | -4.70  | 320    | 100    | peak   |
| 4   | 517.2480  | 25.80    | 11.30   | 37.10    | 46.00    | -8.90  | 360    | 100    | peak   |

**Plot of Radiated Emissions Test Data (30MHz to 1GHz)***EUT:* Wireless 300N Range Extender*Tested Model:* 525756*Operating Condition:* 802.11g Transmitting Low Channel-2412MHz*Comment:* AC 120V/60Hz*Test Specification:* Horizontal

| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ° ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|-----------------|----------------|--------|
| 1   | 262.8955           | 25.52               | 7.23            | 32.75              | 46.00             | -13.25         | 177             | 100            | peak   |
| 2   | 362.9845           | 35.00               | 9.24            | 44.24              | 46.00             | -1.76          | 90              | 100            | peak   |
| 3   | 440.1963           | 23.72               | 10.03           | 33.75              | 46.00             | -12.25         | 336             | 100            | peak   |
| 4   | 568.6127           | 19.93               | 11.98           | 31.91              | 46.00             | -14.09         | 360             | 100            | peak   |

Test Specification: Vertical




| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 261.9753  | 35.95    | 7.17    | 43.12    | 46.00    | -2.88  | 270    | 100    | peak   |
| 2   | 366.8231  | 35.48    | 9.22    | 44.70    | 46.00    | -1.30  | 164    | 100    | peak   |
| 3   | 444.8514  | 24.63    | 10.15   | 34.78    | 46.00    | -11.22 | 228    | 200    | peak   |
| 4   | 517.2480  | 25.58    | 11.30   | 36.88    | 46.00    | -9.12  | 130    | 200    | peak   |

Operating Condition: 802.11g Transmitting Middle Channel-2437MHz


Comment: AC 120V/60Hz

Test Specification: Horizontal



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>(°) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|---------------|----------------|--------|
| 1   | 261.9753           | 23.07               | 7.17            | 30.24              | 46.00             | -15.76         | 360           | 100            | peak   |
| 2   | 314.3765           | 23.11               | 9.26            | 32.37              | 46.00             | -13.63         | 255           | 100            | peak   |
| 3   | 366.8231           | 34.10               | 9.22            | 43.32              | 46.00             | -2.68          | 270           | 100            | peak   |
| 4   | 446.4141           | 22.36               | 10.19           | 32.55              | 46.00             | -13.45         | 180           | 100            | peak   |

Test Specification: Vertical




| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 258.3264  | 36.95    | 6.98    | 43.93    | 46.00    | -2.07  | 270    | 100    | peak   |
| 2   | 309.9977  | 27.35    | 9.23    | 36.58    | 46.00    | -9.42  | 51     | 200    | peak   |
| 3   | 375.9385  | 29.00    | 9.20    | 38.20    | 46.00    | -7.80  | 360    | 200    | peak   |
| 4   | 444.8514  | 24.87    | 10.15   | 35.02    | 46.00    | -10.98 | 360    | 100    | peak   |

Operating Condition: 802.11g Transmitting High Channel-2462MHz


Comment: AC 120V/60Hz

Test Specification: Horizontal




| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 240.8304  | 22.58    | 6.36    | 28.94    | 46.00    | -17.06 | 360    | 100    | peak   |
| 2   | 284.9767  | 21.31    | 8.58    | 29.89    | 46.00    | -16.11 | 180    | 100    | peak   |
| 3   | 362.9845  | 34.32    | 9.24    | 43.56    | 46.00    | -2.44  | 225    | 100    | peak   |
| 4   | 440.1963  | 24.11    | 10.03   | 34.14    | 46.00    | -11.86 | 67     | 100    | peak   |

Test Specification: Vertical




| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 262.8955  | 36.41    | 7.23    | 43.64    | 46.00    | -2.36  | 260    | 100    | peak   |
| 2   | 362.9845  | 34.29    | 9.24    | 43.53    | 46.00    | -2.47  | 131    | 200    | peak   |
| 3   | 379.9141  | 27.39    | 9.19    | 36.58    | 46.00    | -9.42  | 285    | 200    | peak   |
| 4   | 526.3967  | 22.53    | 11.35   | 33.88    | 46.00    | -12.12 | 224    | 100    | peak   |

**Plot of Radiated Emissions Test Data (30MHz to 1GHz)***EUT:* Wireless 300N Range Extender*Tested Model:* 525756*Operating Condition:* 802.11n-HT20 Transmitting Low Channel-2412MHz*Comment:* AC 120V/60Hz*Test Specification:* Horizontal

| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 156.4578  | 25.83    | 2.58    | 28.41    | 43.50    | -15.09 | 155    | 100    | peak   |
| 2   | 259.2338  | 23.90    | 7.01    | 30.91    | 46.00    | -15.09 | 197    | 100    | peak   |
| 3   | 362.9845  | 34.50    | 9.24    | 43.74    | 46.00    | -2.26  | 310    | 100    | peak   |
| 4   | 440.1963  | 24.00    | 10.03   | 34.03    | 46.00    | -11.97 | 229    | 100    | peak   |

Test Specification: Vertical




| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 250.3012  | 25.83    | 6.71    | 32.54    | 46.00    | -13.46 | 274    | 100    | peak   |
| 2   | 261.9753  | 36.24    | 7.17    | 43.41    | 46.00    | -2.59  | 116    | 100    | peak   |
| 3   | 366.8231  | 34.41    | 9.22    | 43.63    | 46.00    | -2.37  | 82     | 100    | peak   |
| 4   | 524.5541  | 23.46    | 11.36   | 34.82    | 46.00    | -11.18 | 134    | 100    | peak   |

Operating Condition: 802.11n-HT20 Transmitting Middle Channel-2437MHz


Comment: AC 120V/60Hz

Test Specification: Horizontal



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ° ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|-----------------|----------------|--------|
| 1   | 156.4578           | 24.32               | 2.58            | 26.90              | 43.50             | -16.60         | 264             | 100            | peak   |
| 2   | 229.2931           | 22.25               | 5.68            | 27.93              | 46.00             | -18.07         | 110             | 100            | peak   |
| 3   | 366.8231           | 34.64               | 9.22            | 43.86              | 46.00             | -2.14          | 136             | 100            | peak   |
| 4   | 441.7426           | 22.66               | 10.06           | 32.72              | 46.00             | -13.28         | 90              | 100            | peak   |

Test Specification: Vertical




| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 258.3264  | 36.98    | 6.98    | 43.96    | 46.00    | -2.04  | 360    | 100    | peak   |
| 2   | 315.4808  | 27.33    | 9.27    | 36.60    | 46.00    | -9.40  | 112    | 100    | peak   |
| 3   | 368.1116  | 34.23    | 9.23    | 43.46    | 46.00    | -2.54  | 180    | 200    | peak   |
| 4   | 517.2480  | 27.39    | 11.30   | 38.69    | 46.00    | -7.31  | 270    | 200    | peak   |

Operating Condition: 802.11n-HT20 Transmitting High Channel-2462MHz


Comment: AC 120V/60Hz

Test Specification: Horizontal



| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 155.3644  | 22.04    | 2.57    | 24.61    | 43.50    | -18.89 | 267    | 100    | peak   |
| 2   | 259.2338  | 25.42    | 7.01    | 32.43    | 46.00    | -13.57 | 116    | 100    | peak   |
| 3   | 361.7139  | 34.58    | 9.24    | 43.82    | 46.00    | -2.18  | 360    | 100    | peak   |
| 4   | 440.1963  | 22.99    | 10.03   | 33.02    | 46.00    | -12.98 | 228    | 100    | peak   |


Test Specification: Vertical



| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 261.9753  | 35.36    | 7.17    | 42.53    | 46.00    | -3.47  | 267    | 100    | peak   |
| 2   | 362.9845  | 33.18    | 9.24    | 42.42    | 46.00    | -3.58  | 114    | 200    | peak   |
| 3   | 517.2480  | 25.73    | 11.30   | 37.03    | 46.00    | -8.97  | 35     | 200    | peak   |


EUT: Wireless 300N Range Extender  
 Tested Model: 525756  
 Operating Condition: 802.11n-HT40 Transmitting Low Channel-2422MHz  
 Comment: AC 120V/60Hz

Test Specification: Horizontal



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ° ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|-----------------|----------------|--------|
| 1   | 235.8164           | 22.59               | 6.07            | 28.66              | 46.00             | -17.34         | 360             | 100            | peak   |
| 2   | 309.9977           | 23.74               | 9.23            | 32.97              | 46.00             | -13.03         | 258             | 100            | peak   |
| 3   | 361.7139           | 34.15               | 9.24            | 43.39              | 46.00             | -2.61          | 347             | 100            | peak   |
| 4   | 440.1963           | 22.93               | 10.03           | 32.96              | 46.00             | -13.04         | 270             | 100            | peak   |

Test Specification: Vertical




| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 262.8955  | 35.06    | 7.23    | 42.29    | 46.00    | -3.71  | 251    | 100    | peak   |
| 2   | 284.9767  | 30.35    | 8.58    | 38.93    | 46.00    | -7.07  | 167    | 100    | peak   |
| 3   | 361.7139  | 32.18    | 9.24    | 41.42    | 46.00    | -4.58  | 44     | 100    | peak   |
| 4   | 517.2480  | 24.49    | 11.30   | 35.79    | 46.00    | -10.21 | 130    | 100    | peak   |

Operating Condition: 802.11n-HT40 Transmitting Middle Channel-2437MHz


Comment: AC 120V/60Hz

Test Specification: Horizontal



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Degree<br>( ° ) | Height<br>(cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|-----------------|----------------|--------|
| 1   | 261.9753           | 24.04               | 7.17            | 31.21              | 46.00             | -14.79         | 47              | 100            | peak   |
| 2   | 311.0867           | 23.86               | 9.24            | 33.10              | 46.00             | -12.90         | 264             | 100            | peak   |
| 3   | 362.9845           | 34.96               | 9.24            | 44.20              | 46.00             | -1.80          | 225             | 100            | peak   |
| 4   | 441.7426           | 24.08               | 10.06           | 34.14              | 46.00             | -11.86         | 180             | 100            | peak   |

Test Specification: Vertical




| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 261.9753  | 36.99    | 7.17    | 44.16    | 46.00    | -1.84  | 360    | 100    | peak   |
| 2   | 315.4808  | 28.52    | 9.27    | 37.79    | 46.00    | -8.21  | 287    | 100    | peak   |
| 3   | 366.8231  | 34.69    | 9.22    | 43.91    | 46.00    | -2.09  | 168    | 100    | peak   |
| 4   | 517.2480  | 24.49    | 11.30   | 35.79    | 46.00    | -10.21 | 122    | 100    | peak   |

Operating Condition: 802.11n-HT40 Transmitting High Channel-2452MHz


Comment: AC 120V/60Hz

Test Specification: Horizontal



| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 262.8955  | 24.77    | 7.23    | 32.00    | 46.00    | -14.00 | 78     | 100    | peak   |
| 2   | 362.9845  | 34.53    | 9.24    | 43.77    | 46.00    | -2.23  | 136    | 100    | peak   |
| 3   | 440.1963  | 23.27    | 10.03   | 33.30    | 46.00    | -12.70 | 284    | 100    | peak   |
| 4   | 517.2480  | 21.15    | 11.30   | 32.45    | 46.00    | -13.55 | 60     | 100    | peak   |

Test Specification: Vertical



| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Degree | Height | Remark |
|-----|-----------|----------|---------|----------|----------|--------|--------|--------|--------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | ( ° )  | (cm)   |        |
| 1   | 259.2338  | 36.36    | 7.01    | 43.37    | 46.00    | -2.63  | 124    | 100    | peak   |
| 2   | 362.9845  | 34.51    | 9.24    | 43.75    | 46.00    | -2.25  | 36     | 100    | peak   |
| 3   | 444.8514  | 24.41    | 10.15   | 34.56    | 46.00    | -11.44 | 127    | 100    | peak   |
| 4   | 517.2480  | 24.13    | 11.30   | 35.43    | 46.00    | -10.57 | 159    | 100    | peak   |

*Spurious Emissions Above 1GHz**Test Mode: 802.11b*

| Frequency              | Reading  | Correct | Result   | Limit    | Margin | Polar | Detector |
|------------------------|----------|---------|----------|----------|--------|-------|----------|
| (MHz)                  | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | H/V   |          |
| Low Channel-2412MHz    |          |         |          |          |        |       |          |
| 4824.000               | 54.09    | -3.87   | 50.22    | 74.00    | -23.78 | H     | PK       |
| 4824.000               | 38.84    | -3.87   | 34.97    | 54.00    | -19.03 | H     | AV       |
| 7236.000               | 46.30    | 1.14    | 47.44    | 74.00    | -26.56 | H     | PK       |
| 7236.000               | 34.98    | 1.19    | 36.17    | 54.00    | -17.83 | H     | AV       |
| 4824.000               | 57.31    | -3.86   | 53.45    | 74.00    | -20.55 | V     | PK       |
| 4824.000               | 40.50    | -3.86   | 36.64    | 54.00    | -17.36 | V     | AV       |
| 7236.000               | 49.11    | 1.10    | 50.21    | 74.00    | -23.79 | V     | PK       |
| 7236.000               | 37.44    | 1.10    | 38.54    | 54.00    | -15.46 | V     | AV       |
| Middle Channel-2437MHz |          |         |          |          |        |       |          |
| 4874.000               | 54.74    | -3.74   | 51.00    | 74.00    | -23.00 | H     | PK       |
| 4874.000               | 39.99    | -3.74   | 36.25    | 54.00    | -17.75 | H     | AV       |
| 7311.000               | 47.77    | 1.47    | 49.24    | 74.00    | -24.76 | H     | PK       |
| 7311.000               | 33.10    | 1.47    | 34.57    | 54.00    | -19.43 | H     | AV       |
| 4874.000               | 53.97    | -3.74   | 50.23    | 74.00    | -23.77 | V     | PK       |
| 4874.000               | 40.89    | -3.74   | 37.15    | 54.00    | -16.85 | V     | AV       |
| 7311.000               | 47.98    | 1.47    | 49.45    | 74.00    | -24.55 | V     | PK       |
| 7311.000               | 34.08    | 1.47    | 35.55    | 54.00    | -18.45 | V     | AV       |
| High Channel-2462MHz   |          |         |          |          |        |       |          |
| 4924.000               | 55.82    | -3.59   | 52.23    | 74.00    | -21.77 | H     | PK       |
| 4924.000               | 41.76    | -3.59   | 38.17    | 54.00    | -15.83 | H     | AV       |
| 7386.000               | 46.38    | 1.79    | 48.17    | 74.00    | -25.83 | H     | PK       |
| 7386.000               | 34.83    | 1.79    | 36.62    | 54.00    | -17.38 | H     | AV       |
| 4924.000               | 54.94    | -3.59   | 51.35    | 74.00    | -22.65 | V     | PK       |
| 4924.000               | 42.04    | -3.59   | 38.45    | 54.00    | -15.55 | V     | AV       |
| 7386.000               | 47.99    | 1.79    | 49.78    | 74.00    | -24.22 | V     | PK       |
| 7386.000               | 35.18    | 1.79    | 36.97    | 54.00    | -17.03 | V     | AV       |

Test Mode: 802.11g

| Frequency              | Reading  | Correct | Result   | Limit    | Margin | Polar | Detector |
|------------------------|----------|---------|----------|----------|--------|-------|----------|
| (MHz)                  | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | H/V   |          |
| Low Channel-2412MHz    |          |         |          |          |        |       |          |
| 4824.000               | 55.50    | -3.86   | 51.64    | 74.00    | -22.36 | H     | PK       |
| 4824.000               | 42.23    | -3.86   | 38.37    | 54.00    | -15.63 | H     | AV       |
| 7236.000               | 48.42    | 1.10    | 49.52    | 74.00    | -24.48 | H     | PK       |
| 7236.000               | 34.40    | 1.10    | 35.50    | 54.00    | -18.50 | H     | AV       |
| 4824.000               | 55.99    | -3.86   | 52.13    | 74.00    | -21.87 | V     | PK       |
| 4824.000               | 42.65    | -3.86   | 38.79    | 54.00    | -15.21 | V     | AV       |
| 7236.000               | 49.22    | 1.10    | 50.32    | 74.00    | -23.68 | V     | PK       |
| 7236.000               | 35.54    | 1.10    | 36.64    | 54.00    | -17.36 | V     | AV       |
| Middle Channel-2437MHz |          |         |          |          |        |       |          |
| 4874.000               | 55.10    | -3.74   | 51.36    | 74.00    | -22.64 | H     | PK       |
| 4874.000               | 43.28    | -3.74   | 39.54    | 54.00    | -14.46 | H     | AV       |
| 7311.000               | 47.38    | 1.47    | 48.85    | 74.00    | -25.15 | H     | PK       |
| 7311.000               | 35.27    | 1.47    | 36.74    | 54.00    | -17.26 | H     | AV       |
| 4874.000               | 57.07    | -3.74   | 53.33    | 74.00    | -20.67 | V     | PK       |
| 4874.000               | 43.86    | -3.74   | 40.12    | 54.00    | -13.88 | V     | AV       |
| 7311.000               | 48.40    | 1.47    | 49.87    | 74.00    | -24.13 | V     | PK       |
| 7311.000               | 35.33    | 1.47    | 36.80    | 54.00    | -17.20 | V     | AV       |
| High Channel-2462MHz   |          |         |          |          |        |       |          |
| 4924.000               | 54.00    | -3.59   | 50.41    | 74.00    | -23.59 | H     | PK       |
| 4924.000               | 40.75    | -3.59   | 37.16    | 54.00    | -16.84 | H     | AV       |
| 7386.000               | 47.18    | 1.79    | 48.97    | 74.00    | -25.03 | H     | PK       |
| 7386.000               | 34.73    | 1.79    | 36.52    | 54.00    | -17.48 | H     | AV       |
| 4924.000               | 56.11    | -3.59   | 52.52    | 74.00    | -21.48 | V     | PK       |
| 4924.000               | 42.69    | -3.59   | 39.10    | 54.00    | -14.90 | V     | AV       |
| 7386.000               | 48.58    | 1.79    | 50.37    | 74.00    | -23.63 | V     | PK       |
| 7386.000               | 35.95    | 1.79    | 37.74    | 54.00    | -16.26 | V     | AV       |

Test Mode: 802.11n-HT20

| Frequency              | Reading  | Correct | Result   | Limit    | Margin | Polar | Detector |
|------------------------|----------|---------|----------|----------|--------|-------|----------|
| (MHz)                  | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | H/V   |          |
| Low Channel-2412MHz    |          |         |          |          |        |       |          |
| 4824.000               | 65.60    | -3.86   | 61.74    | 74.00    | -12.26 | H     | PK       |
| 4824.000               | 44.54    | -3.86   | 40.68    | 54.00    | -13.32 | H     | AV       |
| 7236.000               | 57.26    | 1.10    | 58.36    | 74.00    | -15.64 | H     | PK       |
| 7236.000               | 37.44    | 1.10    | 38.54    | 54.00    | -15.46 | H     | AV       |
| 4824.000               | 66.71    | -3.86   | 62.85    | 74.00    | -11.15 | V     | PK       |
| 4824.000               | 43.18    | -3.86   | 39.32    | 54.00    | -14.68 | V     | AV       |
| 7236.000               | 59.21    | 1.10    | 60.31    | 74.00    | -13.69 | V     | PK       |
| 7236.000               | 35.77    | 1.10    | 36.87    | 54.00    | -17.13 | V     | AV       |
| Middle Channel-2437MHz |          |         |          |          |        |       |          |
| 4874.000               | 65.16    | -3.74   | 61.42    | 74.00    | -12.58 | H     | PK       |
| 4874.000               | 43.48    | -3.74   | 39.74    | 54.00    | -14.26 | H     | AV       |
| 7311.000               | 60.74    | 1.47    | 62.21    | 74.00    | -11.79 | H     | PK       |
| 7311.000               | 33.10    | 1.47    | 34.57    | 54.00    | -19.43 | H     | AV       |
| 4874.000               | 64.92    | -3.74   | 61.18    | 74.00    | -12.82 | V     | PK       |
| 4874.000               | 42.62    | -3.74   | 38.88    | 54.00    | -15.12 | V     | AV       |
| 7311.000               | 58.49    | 1.47    | 59.96    | 74.00    | -14.04 | V     | PK       |
| 7311.000               | 35.20    | 1.47    | 36.67    | 54.00    | -17.33 | V     | AV       |
| High Channel-2462MHz   |          |         |          |          |        |       |          |
| 4924.000               | 66.90    | -3.59   | 63.31    | 74.00    | -10.69 | H     | PK       |
| 4924.000               | 46.23    | -3.59   | 43.64    | 54.00    | -10.36 | H     | AV       |
| 7386.000               | 58.31    | 1.79    | 60.10    | 74.00    | -13.90 | H     | PK       |
| 7386.000               | 36.10    | 1.79    | 37.89    | 54.00    | -16.11 | H     | AV       |
| 4924.000               | 64.70    | -3.59   | 61.11    | 74.00    | -12.89 | V     | PK       |
| 4924.000               | 41.48    | -3.59   | 37.89    | 54.00    | -16.11 | V     | AV       |
| 7386.000               | 57.55    | 1.79    | 59.34    | 74.00    | -14.66 | V     | PK       |
| 7386.000               | 35.36    | 1.79    | 37.15    | 54.00    | -16.85 | V     | AV       |

Test Mode: 802.11n-HT40

| Frequency              | Reading  | Correct | Result   | Limit    | Margin | Polar | Detector |
|------------------------|----------|---------|----------|----------|--------|-------|----------|
| (MHz)                  | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   | H/V   |          |
| Low Channel-2422MHz    |          |         |          |          |        |       |          |
| 4844.000               | 63.25    | -3.90   | 59.35    | 74.00    | -14.65 | H     | PK       |
| 4824.000               | 38.25    | -3.90   | 34.35    | 54.00    | -19.65 | H     | AV       |
| 7266.000               | 56.48    | 1.06    | 57.54    | 74.00    | -16.46 | H     | PK       |
| 7266.000               | 32.56    | 1.06    | 33.62    | 54.00    | -20.38 | H     | AV       |
| 4844.000               | 64.22    | -3.90   | 60.32    | 74.00    | -13.68 | V     | PK       |
| 4824.000               | 39.42    | -3.90   | 35.52    | 54.00    | -18.48 | V     | AV       |
| 7266.000               | 58.81    | 1.06    | 59.87    | 74.00    | -14.13 | V     | PK       |
| 7266.000               | 34.78    | 1.06    | 35.84    | 54.00    | -18.16 | V     | AV       |
| Middle Channel-2437MHz |          |         |          |          |        |       |          |
| 4874.000               | 62.53    | -3.74   | 58.79    | 74.00    | -15.21 | H     | PK       |
| 4874.000               | 37.88    | -3.74   | 34.14    | 54.00    | -19.86 | H     | AV       |
| 7311.000               | 54.88    | 1.47    | 56.35    | 74.00    | -17.65 | H     | PK       |
| 7311.000               | 32.03    | 1.47    | 33.50    | 54.00    | -20.50 | H     | AV       |
| 4874.000               | 63.74    | -3.74   | 60.00    | 74.00    | -14.00 | V     | PK       |
| 4874.000               | 39.95    | -3.74   | 36.21    | 54.00    | -17.79 | V     | AV       |
| 7311.000               | 55.78    | 1.47    | 57.25    | 74.00    | -16.75 | V     | PK       |
| 7311.000               | 34.00    | 1.47    | 35.47    | 54.00    | -18.53 | V     | AV       |
| High Channel-2452MHz   |          |         |          |          |        |       |          |
| 4904.000               | 64.65    | -3.63   | 61.02    | 74.00    | -12.98 | H     | PK       |
| 4904.000               | 39.37    | -3.63   | 35.74    | 54.00    | -18.26 | H     | AV       |
| 7356.000               | 47.63    | 1.62    | 49.25    | 74.00    | -24.75 | H     | PK       |
| 7356.000               | 30.73    | 1.62    | 32.35    | 54.00    | -21.65 | H     | AV       |
| 4904.000               | 64.84    | -3.63   | 61.21    | 74.00    | -12.79 | V     | PK       |
| 4904.000               | 40.83    | -3.63   | 37.20    | 54.00    | -16.80 | V     | AV       |
| 7356.000               | 58.18    | 1.62    | 59.80    | 74.00    | -14.20 | V     | PK       |
| 7356.000               | 35.12    | 1.62    | 36.74    | 54.00    | -17.26 | V     | AV       |

Note: Testing is carried out with frequency rang 30MHz to the tenth harmonics, which above 3<sup>th</sup> Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

## 9. Out of Band Emissions

### 9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### 9.2 Test Equipment List and Details

| Description              | Manufacturer         | Model    | Serial Number | Cal. Date  | Due. Date  |
|--------------------------|----------------------|----------|---------------|------------|------------|
| Spectrum Analyzer        | R&S                  | FSP      | 836079/035    | 2014-05-28 | 2015-05-27 |
| EMI Test Receiver        | R&S                  | ESVB     | 825471/005    | 2014-05-28 | 2015-05-27 |
| Pre-amplifier            | Agilent              | 8447F    | 3113A06717    | 2014-05-28 | 2015-05-27 |
| Pre-amplifier            | Compliance Direction | PAP-0118 | 24002         | 2014-05-28 | 2015-05-27 |
| Trilog Broadband Antenna | SCHWARZBECK          | VULB9163 | 9163-333      | 2014-05-24 | 2015-05-23 |
| Horn Antenna             | ETS                  | 3117     | 00086197      | 2014-05-24 | 2015-05-23 |

### 9.3 Test Procedure

According to the KDB 558074D01 v03r02, the band-edge radiated test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

According to the KDB 558074 D01 V03r02, the conducted spurious emissions test method as follows:

1. Set start frequency to DTS channel edge frequency.
2. Set stop frequency so as to encompass the spectrum to be examined.
3. Set RBW = 100 kHz.
4. Set VBW  $\geq$  300 kHz.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.


#### 9.4 Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 23°C      |
| Relative Humidity: | 54%       |
| ATM Pressure:      | 1011 mbar |

#### 9.5 Summary of Test Results/Plots

Please refer to the test plots as below.


802.11b-Lowest Bandedge  
Horizontal (Worst case)



| No. | Frequency | Reading  | Correct | Result   | Limit          | Margin | Remark           |
|-----|-----------|----------|---------|----------|----------------|--------|------------------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m)       | (dB)   |                  |
| 1   | 2310.000  | 41.37    | -3.76   | 37.61    | 50.00          | -12.39 | Average Detector |
|     | 2310.000  | 47.50    | -3.76   | 43.74    | 74.00          | -30.26 | Peak Detector    |
| 2   | 2385.720  | 51.46    | -3.56   | 47.90    | 50.00          | -2.10  | Average Detector |
|     | 2385.720  | 62.40    | -3.56   | 58.84    | 74.00          | -15.16 | Peak Detector    |
| 3   | 2390.000  | 45.87    | -3.55   | 42.32    | 50.00          | -7.68  | Average Detector |
|     | 2390.000  | 57.26    | -3.55   | 53.71    | 74.00          | -20.29 | Peak Detector    |
| 4   | 2400.000  | 68.29    | -3.52   | 64.77    | Delta=36.12dBc |        | Average Detector |
| 5   | 2412.840  | 104.37   | -3.48   | 100.89   |                |        | Average Detector |


## 802.11b-Highest Bandedge

Horizontal (Worst case)




| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Remark           |
|-----|-----------|----------|---------|----------|----------|--------|------------------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   |                  |
| 1   | 2461.300  | 100.75   | -3.35   | 97.40    | /        | /      | Average Detector |
| 2   | 2483.500  | 38.23    | -3.30   | 34.93    | 54.00    | -19.07 | Average Detector |
|     | 2483.500  | 51.26    | -3.30   | 47.96    | 74.00    | -26.04 | Peak Detector    |
| 3   | 2488.350  | 39.34    | -3.29   | 36.05    | 54.00    | -17.95 | Average Detector |
|     | 2488.350  | 51.78    | -3.29   | 48.49    | 74.00    | -25.51 | Peak Detector    |
| 4   | 2490.350  | 38.75    | -3.28   | 35.47    | 54.00    | -18.53 | Average Detector |
|     | 2490.350  | 51.64    | -3.28   | 48.36    | 74.00    | -25.64 | Peak Detector    |
| 5   | 2500.000  | 38.97    | -3.25   | 35.72    | 54.00    | -18.28 | Average Detector |
|     | 2500.000  | 51.08    | -3.25   | 47.83    | 74.00    | -26.17 | Peak Detector    |

802.11g-Lowest Bandedge  
Horizontal (Worst case)




| No. | Frequency | Reading  | Correct | Result   | Limit          | Margin | Remark           |
|-----|-----------|----------|---------|----------|----------------|--------|------------------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m)       | (dB)   |                  |
| 1   | 2310.000  | 33.99    | -3.76   | 30.23    | 54.00          | -23.77 | Average Detector |
|     | 2310.000  | 45.91    | -3.76   | 42.15    | 74.00          | -31.85 | Peak Detector    |
| 2   | 2390.000  | 43.88    | -3.55   | 40.33    | 54.00          | -13.67 | Average Detector |
|     | 2390.000  | 59.58    | -3.55   | 56.03    | 74.00          | -17.97 | Peak Detector    |
| 3   | 2400.000  | 53.10    | -3.52   | 49.58    | Delta=37.55dBc |        | Average Detector |
| 4   | 2413.920  | 90.61    | -3.48   | 87.13    |                |        | Average Detector |

802.11g-Highest Bandedge  
Horizontal (Worst case)




| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Remark           |
|-----|-----------|----------|---------|----------|----------|--------|------------------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   |                  |
| 1   | 2459.950  | 90.19    | -3.35   | 86.84    | /        | /      | Average Detector |
| 2   | 2483.500  | 42.40    | -3.30   | 39.10    | 54.00    | -14.90 | Average Detector |
|     | 2483.500  | 61.29    | -3.30   | 57.99    | 74.00    | -16.01 | Peak Detector    |
| 3   | 2500.000  | 37.89    | -3.25   | 34.64    | 54.00    | -19.36 | Average Detector |
|     | 2500.000  | 50.66    | -3.25   | 47.41    | 74.00    | -26.59 | Peak Detector    |

802.11n-HT20-Lowest Bandedge  
Horizontal (Worst case)




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark           |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|------------------|
| 1   | 2310.000           | 29.11               | -3.71           | 25.40              | 54.00             | -28.60         | Average Detector |
|     | 2310.000           | 38.48               | -3.71           | 34.77              | 74.00             | -39.23         | Peak Detector    |
| 2   | 2390.000           | 41.94               | -3.54           | 38.40              | 54.00             | -15.60         | Average Detector |
|     | 2390.000           | 54.59               | -3.54           | 51.05              | 74.00             | -22.95         | Peak Detector    |
| 3   | 2400.000           | 50.87               | -3.51           | 47.36              | 54.00             | -6.64          | Average Detector |
|     | 2400.000           | 61.86               | -3.51           | 58.35              | 74.00             | -15.65         | Peak Detector    |

802.11n-HT20-Highest Bandedge  
Horizontal (Worst case)




| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark           |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|------------------|
| 1   | 2460.600           | 89.03               | -3.35           | 85.68              | /                 | /              | Average Detector |
| 2   | 2483.500           | 43.65               | -3.30           | 40.35              | 54.00             | -13.65         | Average Detector |
|     | 2483.500           | 61.74               | -3.30           | 58.44              | 74.00             | -15.56         | Peak Detector    |
| 3   | 2500.000           | 38.41               | -3.25           | 35.16              | 54.00             | -18.84         | Average Detector |
|     | 2500.000           | 52.80               | -3.25           | 49.55              | 74.00             | -24.45         | Peak Detector    |

802.11n-HT40-Lowest Bandedge  
Horizontal (Worst case)



| No. | Frequency<br>(MHz) | Reading<br>(dBuV/m) | Correct<br>dB/m | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark           |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|------------------|
| 1   | 2310.000           | 29.03               | -3.71           | 25.32              | 54.00             | -28.68         | Average Detector |
|     | 2310.000           | 42.42               | -3.71           | 38.71              | 74.00             | -35.29         | Peak Detector    |
| 2   | 2390.000           | 41.17               | -3.54           | 37.63              | 54.00             | -16.37         | Average Detector |
|     | 2390.000           | 58.01               | -3.54           | 54.47              | 74.00             | -19.53         | Peak Detector    |
| 3   | 2400.000           | 45.53               | -3.51           | 42.02              | 54.00             | -11.98         | Average Detector |
|     | 2400.000           | 61.59               | -3.51           | 58.08              | 74.00             | -15.92         | Peak Detector    |

802.11n-HT40-Highest Bandedge  
Horizontal (Worst case)



| No. | Frequency | Reading  | Correct | Result   | Limit    | Margin | Remark           |
|-----|-----------|----------|---------|----------|----------|--------|------------------|
|     | (MHz)     | (dBuV/m) | dB/m    | (dBuV/m) | (dBuV/m) | (dB)   |                  |
| 1   | 2459.750  | 80.56    | -3.35   | 77.21    | /        | /      | Average Detector |
| 2   | 2483.500  | 49.23    | -3.30   | 45.93    | 54.00    | -8.07  | Average Detector |
|     | 2483.500  | 67.05    | -3.30   | 63.75    | 74.00    | -10.25 | Peak Detector    |
| 3   | 2489.780  | 47.73    | -3.28   | 44.45    | 54.00    | -9.55  | Average Detector |
|     | 2489.780  | 65.71    | -3.28   | 62.43    | 74.00    | -11.57 | Peak Detector    |
| 4   | 2500.000  | 43.74    | -3.25   | 40.49    | 54.00    | -13.51 | Average Detector |
|     | 2500.000  | 63.91    | -3.25   | 60.66    | 74.00    | -13.34 | Peak Detector    |

## 10. Conducted Emissions

### 10.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is  $\pm 2.88$  dB.

### 10.2 Test Equipment List and Details

| Description       | Manufacturer    | Model    | Serial Number | Cal. Date  | Due. Date  |
|-------------------|-----------------|----------|---------------|------------|------------|
| EMI Test Receiver | Rohde & Schwarz | ESPI     | 101611        | 2014-05-28 | 2015-05-27 |
| L.I.S.N           | Schwarz beck    | NSLK8126 | 8126-224      | 2014-05-28 | 2015-05-27 |
| Pulse Limiter     | Rohde & Schwarz | ESH3-Z2  | 100911        | 2014-05-28 | 2015-05-27 |


### 10.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

### 10.4 Basic Test Setup Block Diagram



10.5 Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 52%       |
| ATM Pressure:      | 1012 mbar |

10.6 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency ..... 150 kHz  
Stop Frequency..... 30 MHz  
Sweep Speed ..... Auto  
IF Bandwidth..... 10 kHz  
Quasi-Peak Adapter Bandwidth ..... 9 kHz  
Quasi-Peak Adapter Mode ..... Normal

10.7 Summary of Test Results/Plots

According to the data in section 9.8, the EUT complied with the FCC Part 15.207 Conducted margin for a Class B device, with the *worst* margin reading of:


**-10.58 dB at 0.4220 MHz in the Neutral mode, Peak detector, 0.15-30MHz**

10.8 Conducted Emissions Test Data

**Plot of Conducted Emissions Test Data**


EUT: Wireless 300N Range Extender  
 Tested Model: 525756  
 Operating Condition: Transmitting(Wi-Fi)  
 Comment: AC 120V/60Hz

Test Specification: Neutral



| No. | Frequency | Reading | Correct | Result | Limit  | Margin | Detector |
|-----|-----------|---------|---------|--------|--------|--------|----------|
|     | (MHz)     | (dBuV)  | (dB/m)  | (dBuV) | (dBuV) | (dB)   |          |
| 1   | 0.4180    | 31.83   | 9.50    | 41.33  | 57.49  | -16.16 | peak     |
| 2   | 0.4220    | 21.11   | 9.50    | 30.61  | 47.41  | -16.80 | AVG      |
| 3   | 1.3180    | 30.44   | 10.00   | 40.44  | 56.00  | -15.56 | peak     |
| 4   | 1.4500    | 16.21   | 10.00   | 26.21  | 46.00  | -19.79 | AVG      |
| 5   | 2.0860    | 17.02   | 10.00   | 27.02  | 46.00  | -18.98 | AVG      |
| 6*  | 2.5620    | 31.43   | 10.00   | 41.43  | 56.00  | -14.57 | peak     |

Test Specification: Line



| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB/m) | Result<br>(dBuV) | Limit<br>(dBuV) | Margin<br>(dB) | Detector |
|-----|--------------------|-------------------|-------------------|------------------|-----------------|----------------|----------|
| 1*  | 0.4220             | 37.33             | 9.50              | 46.83            | 57.41           | -10.58         | peak     |
| 2   | 0.4220             | 26.23             | 9.50              | 35.73            | 47.41           | -11.68         | AVG      |
| 3   | 0.8740             | 32.13             | 9.87              | 42.00            | 56.00           | -14.00         | peak     |
| 4   | 0.9100             | 20.07             | 9.91              | 29.98            | 46.00           | -16.02         | AVG      |
| 5   | 1.9940             | 22.21             | 10.00             | 32.21            | 46.00           | -13.79         | AVG      |
| 6   | 2.0300             | 35.10             | 10.00             | 45.10            | 56.00           | -10.90         | peak     |

\*\*\*\*\* END OF REPORT \*\*\*\*\*