

Advanced
Compliance Laboratory

6 Randolph Way
Hillsborough, NJ 08844
Tel: (908) 927 9288
Fax: (908) 927 0728

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT

of

TRANSMITTER
MODEL: TELIS1
FCC ID: DWNTELIS1

February 20, 2004

This report concerns (check one): Original grant _____ Class II change <u> X </u> Equipment type: <u>TRANSMITTER</u>	
Deferred grant requested per 47 CF 0.457(d)(1)(ii)? yes _____ no <u> x </u> If yes, defer until: _____ (date) Company agrees to notify the Commission by _____ (date) of the intended date of announcement of the product so that the grant can be issued on that date.	
Transition Rules Request per 15.37? yes _____ no <u> x </u> If no, assumed Part 15, Subpart B for unintentional radiators - the new 47 CFR [10-1-90 Edition] provision.	
Report prepared for:	SOMFY SYSTEM, INC.
Report prepared by:	Advanced Compliance Lab
Report number:	0048-040211-02



The test result in this report IS supported and covered by the NVLAP accreditation

Table of Contents

Report Cover Page.....	1
Table of Contents	2
Figures.....	3
1. GENERAL INFORMATION	4
1.1 Verification of Compliance	4
1.2 Equipment Modifications.....	5
1.3 Product Information	6
1.4 Test Methodology.....	6
1.5 Test Facility	6
1.6 Test Equipment	6
1.7 Statement of the Document Use.....	7
2. PRODUCT LABELING.....	8
3. SYSTEM TEST CONFIGURATION	9
3.1 Justification	9
3.2 Special Accessories.....	9
3.3 Configuration of Tested System	9
4. SYSTEM SCHEMATICS	12
5. RADIATED EMISSION DATA	13
5.1 Field Strength Calculation	13
5.2 Test Methods and Conditions	13
5.3 Test Data	13
5.4 Occupied Bandwidth	15
6. PHOTOS OF TESTED EUT	17

Figures

Figure 2.1 FCC ID Label.....	8
Figure 2.2 Location of Label on Back of the EUT	8
Figure 3.1 Radiated Test Setup, Position 1.....	10
Figure 3.2 Radiated Test Setup, Position 2.....	10
Figure 3.3 Radiated Test Setup, Position 3.....	11
Figure 4.1 EUT Schematics.....	12
Figure 5.1 Pulse Train Timing.....	15
Figure 5.2 Occupied Bandwidth	16
Figure 6.1 Front View.....	19
Figure 6.2 Rear View	20
Figure 6.3 Inside View, Cover Opened	21
Figure 6.4 Component Side.....	22
Figure 6.5 Foil Side	23

1. GENERAL INFORMATION


1.1 Verification of Compliance

EUT: TRANSMITTER
 Model: TELIS1
 Applicant: SOMFY SYSTEM, INC.
 Test Type: FCC Part 15C CERTIFICATION
 Result: PASS
 Tested by: ADVANCED COMPLIANCE LAB
 Test Date: February 18, 2004
 Report Number: 0048-040211-02

The above equipment was tested by Advanced Compliance Laboratory for compliance with the requirement set forth in the FCC rules and regulations Part 15, subpart C. This said equipment in the configuration described in the report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

The estimated uncertainty of the test result is given as following. The method of uncertainty calculation is provided in Advanced Compliance Lab. Doc. No. 0048-01-01.

	Prob. Dist.	Uncertainty(dB)	Uncertainty(dB)	Uncertainty(dB)
		30-1000MHz	1-6.5GHz	Conducted
Combined Std. Uncertainty u_c	norm.	± 2.36	± 2.99	± 1.83



Wei Li
 2004
 Lab Manager
 Advanced Compliance Lab

Date: February 20,

1.2 Equipment Modifications

N/A

1.3 Product Information

System Configuration

ITEM	DESCRIPTION	FCC ID	CABLE
Product	TRANSMITTER	DWNTTELIS1	
Housing	PLASTICS		
Power Supply	BATTERY		
Clock/OSC Freq.	433.5 MHz		
Device Type	Periodic Operation		

(1) EUT submitted for grant.

1.4 Test Methodology

Radiated tests were performed according to the procedures in ANSI C63.4-1992 at an antenna to EUT distance of 3 meters.

1.5 Test Facility

The open area test site and conducted measurement facility used to collect the radiated and conducted data are located at 50 Randolph Road, Somerset, New Jersey. This site has been accepted by FCC to perform measurements under Part 15 or 18 in a letter dated May 19, 1997 (Refer to: 31040/PRV 1300F2). The NVLAP Lab code for accreditation of FCC EMC Test Method is: 200101-0.

1.6 Test Equipment

Manufacture	Model	Serial No.	Description	Last Cal dd/mm/y	Cal Due dd/mm/y
Hewlett-Packard	HP8546A	3625A00341	EMI Receiver	12/01/04	12/01/05
EMCO	3115	4945	Double Ridge Guide Horn Antenna	11/08/03	11/08/04
AIL	94455	933	20-300MHz Biconical Antenna	11/03/03	11/03/04
EMCO	3146	3672	200-1000MHz Log-Periodic Antenna	11/02/03	11/02/04
Fischer Custom	LISN-2	900-4-0008	Line Impedance Stabilization Networks	11/08/03	11/08/04
Fischer Custom	LISN-2	900-4-0009	Line Impedance Stabilization Networks	25/08/03	25/08/04

All Test Equipment Used are Calibrated Traceable to NIST Standards.

1.7 Statement for the Document Use

This report shall not be reproduced except in full, without the written approval of the laboratory. And this report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

2. PRODUCT LABELING




Figure 2.1 FCC ID Label




Figure 2.2 Location of Label on Back of the EUT

3. SYSTEM TEST CONFIGURATION

3.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it). And its antenna was permanently attached to the EUT (Made on the PCB). One LED on the front appearances.

This manually operated transmitter will deactivate immediately after press “ ” button.

Testing was performed in either “UP arrow”, “ Down arrow” and “ O” button. It is the worst case.

3.2 Special Accessories

N/A

3.3 Configuration of Tested System

Figure 3.1 and Figure 3.3 illustrate this system, which is tested standing along.



Figure 3.1 Radiated Test Setup, Position 1



Figure 3.2 Radiated Test Setup, Position 2



Figure 3.3 Radiated Test Setup, Position 3

5. RADIATED EMISSION DATA

5.1 Field Strength Calculation

The corrected field strength is automatically calculated by EMI Receiver using following:

$$FS = RA - AF - CF - AG$$

where FS: Corrected Field Strength in dB μ V/m

RA: Amplitude of EMI Receiver before correction in dB μ V

AF: Antenna Factor in dB/m

CF: Cable Attenuation Factor in dB

AG: Built-in Preamplifier Gain in dB (Stored in receiver as part of the calibration data)

The pulse train timing plots are showed in Figure 5.1.

The pulse train timing plots as follows:

The total time for each pulse train is 139.62 ms, The short pulse is 0.640ms, The middle pulse is 2.5 ms, The long pulse is 4.8m

$$\text{Coeff.} = (56 \times 0.640 + 1 \times 4.8 + 4 \times 2.5 + (2.88 - 2.5)) / (71.68 + 5.44 + 22.88) = 51.02 / 100 = 0.51$$

The maximum average field strength should be 0.51 of the peak field strength measured. So we use peak value minus 5.85dB as calculated maximum average field strength.

5.2 Test Methods and Conditions

The initial step in collecting radiated data is an EMI Receiver scan of the measurement range 30MHz - 5GHz using peak detector. IF bandwidth is 120KHz and video bandwidth is 300KHz for measuring 30MHz-1GHz. Both bandwidths are 1MHz for above 1GHz measurement.

5.3 Test Data

The following data lists the significant emission frequencies, polarity and position, peak reading of the EMI Receiver, calculated average reading, the FCC limit, and the difference between the peak reading and the limit. Explanation of the correction and calculation are given in section 5.1.

Test Personnel:

Tester Signature



Typed/Printed Name: Edward Lee

Date: February 20, 2004

Radiated Test Data

Frequency (MHz)	Polarity [H or V], Position (X,Y,Z)	Height (m)	Azimuth (Degree)	Peak Reading (dBμV/m)	Calculated Average Reading (dBμV/m)	FCC 3m Limit (dBμV/m)	Difference from limit (dB)
433.5	H,X	2.5	270	83.6	77.75	80.8(3)	-3.05
867	H,X	1.0	270	60	54.15	60.8(4)	-6.65
1300.5	H,X	1.2	315	54.4	48.55	54.0(2)	-5.45
1734	H,X	1.1	45	37.7	31.85	60.8	-28.95
2167.5	H,X	1.1	150	51	45.15	60.8	-15.65
433.5	V,X	2.2	45	78.7	72.85	80.8	-7.95
867	V,X	1.0	45	50.4	44.55	54.0	-9.45
1300.5	V,X	1.2	45	63.8	57.95	60.8	-2.85
1734	V,X	1.1	180	39.7	33.85	60.8	-26.95
2167.5	V,X	1.0	45	48.1	42.25	60.8	-18.55
433.5	H,Y	2.4	270	78.7	72.85	80.8	-7.95
867	H,Y	1.5	270	58	52.15	60.8	-8.65
1300.5	H,Y	1.1	45	54.7	48.85	54.0	-5.15
1734	H,Y	1.1	315	41.1	35.25	60.8	-25.55
2167.5	H,Y	1.1	60	54.9	49.05	60.8	-11.75
433.5	V,Y	2.2	60	80.2	74.35	80.8	-6.45
867	V,Y	1.2	270	50	44.15	60.8	-16.65
1300.5	V,Y	1.4	45	54.4	48.55	54.0	-5.45
2167.5	V,Y	1.1	280	44.7	38.85	60.8	-21.95
433.5	H,Z	2.1	200	80.9	75.05	80.8	-5.75
867	H,Z	1.1	180	56.3	50.45	60.8	-10.35
1300.5	H,Z	1.3	90	56.2	50.35	54.0	-3.65
2167.5	H,Z	1.0	0	50.5	44.65	60.8	-16.15
433.5	V,Z	2.1	0	82.7	76.85	80.8	-3.95
867	V,Z	1.5	15	58.6	52.75	60.8	-8.05
1300.5	V,Z	1.1	120	55.3	49.45	54.0	-4.55
1734	V,Z	1.0	0	39.4	33.55	60.8	-27.25
2167.5	V,Z	1.2	0	52.9	47.05	60.8	-13.75

- (1) See Figure 3.1, 3.2 and 3.3 for definition of position X-1, Y-2, Z-3.
- (2) Restricted band.
- (3) Fundamental limit is 3750-12500 microvolts/meter linear interpolations.
- (4) Spurious limit is 375-1250 microvolts/meter linear interpolations.

5.4 Occupied Bandwidth

The bandwidth of the emission shall be no wider than 0.25% of the center frequency, in this case, 1.084MHz($433.5 \times 0.25\%$). Bandwidth is determined at the points 20dB down from the modulated carrier. Figure 5.2 shows the occupied bandwidth plot.




Figure 5.1 Pulse Train Timing




Figure 5.2 Occupied Bandwidth