



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : moto tag
BRAND NAME : Motorola
MODEL NAME : XT2445-1
FCC ID : IHDT6AB3
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System
TEST DATE(S) : May 01, 2024 ~ May 23, 2024

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	5
1.5 Modification of EUT	5
1.6 Specification of Accessory.....	6
1.7 Testing Location	6
1.8 Test Software.....	6
1.9 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	9
2.6 Measurement Results Explanation Example.....	10
3 TEST RESULT	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	12
3.3 Power Spectral Density Measurement	13
3.4 Conducted Band Edges and Spurious Emission Measurement	14
3.5 Radiated Band Edges and Spurious Emission Measurement	15
3.6 Antenna Requirements.....	19
4 LIST OF MEASURING EQUIPMENT.....	20
5 MEASUREMENT UNCERTAINTY.....	21
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. RADIATED SPURIOUS EMISSION AND PLOTS	
APPENDIX C. DUTY CYCLE PLOTS	
APPENDIX D. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR441117A	Rev. 01	Initial issue of report	May 28, 2024

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Report only	-
3.2	15.247(b)(3)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.42 dB at 33.88 MHz for Quasi-peak
-	15.207	AC Conducted Emission	15.207(a)	Not Applicable	2
3.6	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-
Remark: 1. Not Applicable means after assessing, the test item is not necessary to carry out. 2. The device is powered by Battery only.					

Conformity Assessment Condition: 1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account. 2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"
Disclaimer: The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	moto tag
Brand Name	Motorola
Model Name	XT2445-1
FCC ID	IHDT6AB3
SN Code	Conducted: UT0D3L1445D008C Radiation: 0014101101045B000A2
HW Version	EVT2
SW Version	1.0.9
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	BLE 1Mbps: 6.96 dBm (0.0050 W) BLE 2Mbps: 6.97 dBm (0.0050 W)
99% Occupied Bandwidth	BLE 1Mbps:1.051MHz BLE 2Mbps:2.046MHz
Antenna Type / Gain	IFA Antenna type with gain 2.00 dBi
Type of Modulation	Bluetooth LE : GFSK

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Specification of Accessory

Specification of Accessory				
Battery	Brand Name	Motorola	Model Name	CR2032

1.7 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH05-KS TH01-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH05-KS	AUDIX	E3	210616

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_BLE 2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_BLE 2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_BLE 2Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_BLE 2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_BLE 2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_BLE 2Mbps

2.3 Connection Diagram of Test System

For Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Test jig	N/A	N/A	N/A	N/A	N/A
2.	Notebook	HONOR	N/A	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For BLE function, the engineering test program was provided and enabled to make EUT continuous transmit.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 1.1 dB

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} \\ &= 1.10 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1% to 5% of the 99% OBW and the VBW is set to 3 times of the RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



**3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B

3.5.7 Duty Cycle

Please refer to Appendix C.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix B



3.6 Antenna Requirements

3.6.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.6.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 11, 2023	May 01, 2024 ~May 07, 2024	Oct. 10, 2024	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 02, 2024	May 01, 2024 ~May 07, 2024	Jan. 01, 2025	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1435004	50MHz Bandwidth	Jan. 02, 2024	May 01, 2024 ~May 07, 2024	Jan. 01, 2025	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz; Max 30dBm	Oct. 10, 2023	May 23, 2024	Oct. 09, 2024	Radiation (03CH05-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44GHz, MAX 30dB	Apr. 18, 2024	May 23, 2024	Apr. 17, 2025	Radiation (03CH05-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 10, 2023	May 23, 2024	Oct. 09, 2024	Radiation (03CH05-KS)
Bilog Antenna	TeseQ	CBL6111D	59913	30MHz~1GHz	Aug. 19, 2023	May 23, 2024	Aug. 18, 2024	Radiation (03CH05-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 23, 2023	May 23, 2024	Oct. 22, 2024	Radiation (03CH05-KS)
SHF-EHF Horn	Com-power	AH-840	101093	18GHz~40GHz	Jan. 05, 2024	May 23, 2024	Jan. 04, 2025	Radiation (03CH05-KS)
Amplifier	SONOMA	310N	380826	9KHz~1GHz	Jul. 06, 2023	May 23, 2024	Jul. 05, 2024	Radiation (03CH05-KS)
Amplifier	EM	EM18G40GA	060852	18~40GHz	Jan. 05, 2024	May 23, 2024	Jan. 04, 2025	Radiation (03CH05-KS)
high gain Amplifier	EM	EM01G18GA	060839	1Ghz~18Ghz	Oct. 10, 2023	May 23, 2024	Oct. 09, 2024	Radiation (03CH05-KS)
Amplifier	EM	EM01G18GA	060833	1Ghz~18Ghz	Jan. 03, 2024	May 23, 2024	Jan. 02, 2025	Radiation (03CH05-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	May 23, 2024	NCR	Radiation (03CH05-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	May 23, 2024	NCR	Radiation (03CH05-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	May 23, 2024	NCR	Radiation (03CH05-KS)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	±2.26 dB
Occupied Channel Bandwidth	±0.1%
Conducted Power	±0.46 dB
Conducted Power Spectral Density	±0.88 dB
Frequency	±0.4 Hz

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.30dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.02dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.22dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.34dB
---	--------

----- THE END -----



Appendix A. Conducted Test Results



Ambient Condition: 25 °C, 45 %RH

Test Date: 2024.5.1~5.7

Test Engineer: Jiang Jun


6dB Bandwidth


Test Result


TestMode	Freq(MHz)	6dB BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	2402	0.70	2401.66	2402.36	0.5	PASS
	2440	0.70	2439.66	2440.36	0.5	PASS
	2480	0.70	2479.66	2480.36	0.5	PASS
BLE_2M	2402	1.14	2401.45	2402.60	0.5	PASS
	2440	1.15	2439.45	2440.60	0.5	PASS
	2480	1.15	2479.44	2480.60	0.5	PASS



Test Graphs










Occupied Channel Bandwidth


Test Result


TestMode	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	2402	1.047	2401.4965	2402.5435	---	---
	2440	1.051	2439.4965	2440.5475	---	---
	2480	1.051	2479.4965	2480.5475	---	---
BLE_2M	2402	2.042	2401.0090	2403.0509	---	---
	2440	2.042	2439.0090	2441.0509	---	---
	2480	2.046	2479.0090	2481.0549	---	---



Test Graphs







Maximum conducted output power

Test Result Peak

TestMode	CH.	Peak Conducted Power (dBm)	Conducted Power Limit	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit	Pass/Fail
BLE1M	0	6.96	30.00	2	8.96	36.00	Pass
	19	6.93	30.00	2	8.93	36.00	Pass
	39	6.81	30.00	2	8.81	36.00	Pass
BLE2M	0	6.97	30.00	2	8.97	36.00	Pass
	19	6.93	30.00	2	8.93	36.00	Pass
	39	6.79	30.00	2	8.79	36.00	Pass

Test Result Average

TestMode	CH.	Duty Factor (dB)	Average Conducted Power (dBm)
BLE1M	0	2.04	6.72
	19	2.04	6.69
	39	2.04	6.63
BLE2M	0	4.83	6.66
	19	4.83	6.80
	39	4.83	6.57




Maximum power spectral density


Test Result


TestMode	Freq(MHz)	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	2402	-9.09	≤8.00	PASS
	2440	-9.10	≤8.00	PASS
	2480	-8.93	≤8.00	PASS
BLE_2M	2402	-11.60	≤8.00	PASS
	2440	-11.49	≤8.00	PASS
	2480	-11.43	≤8.00	PASS



Test Graphs










Reference level measurement

Test Result


TestMode	Freq(MHz)	Max.Point[MHz]	Result[dBm/100KHz]
BLE_1M	2402	2402.02	4.87
	2440	2440.02	5.11
	2480	2480.02	5.31
BLE_2M	2402	2402.02	4.86
	2440	2440.02	5.10
	2480	2480.03	5.30



Test Graphs










Band edge measurements


Test Result

TestMode	ChName	Freq(MHz)	RefLevel[dBm /100KHz]	Result[dBm /100KHz]	Limit[dBm /100KHz]	Verdict
BLE_1M	Low	2402	4.87	-44.24	≤-15.13	PASS
	High	2480	5.31	-43.12	≤-14.69	PASS
BLE_2M	Low	2402	4.86	-28.37	≤-15.14	PASS
	High	2480	5.30	-43.78	≤-14.7	PASS



Test Graphs








Conducted Spurious Emission


Test Result


TestMode	Freq(MHz)	FreqRange [MHz]	RefLevel [dBm/100KHz]	Result [dBm/100KHz]	Limit [dBm/100KHz]	Verdict
BLE_1M	2402	30~1000	4.87	-45.69	≤-15.13	PASS
		1000~26500	4.87	-35.32	≤-15.13	PASS
	2440	30~1000	5.11	-46.38	≤-14.89	PASS
		1000~26500	5.11	-36.95	≤-14.89	PASS
	2480	30~1000	5.31	-45.18	≤-14.69	PASS
		1000~26500	5.31	-36.45	≤-14.69	PASS
BLE_2M	2402	30~1000	4.86	-46.47	≤-15.14	PASS
		1000~26500	4.86	-35.3	≤-15.14	PASS
	2440	30~1000	5.10	-46.04	≤-14.9	PASS
		1000~26500	5.10	-37.16	≤-14.9	PASS
	2480	30~1000	5.30	-45.89	≤-14.7	PASS
		1000~26500	5.30	-36.28	≤-14.7	PASS





Test Graphs
















Appendix B. Radiated Spurious Emission Test Data

Test Engineer :	Levi Zhuo	Relative Humidity :	22~23
		Temperature :	42~43

Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	Bluetooth-LE_GSFK	0	2402	1Mbps	-	-
Mode 2	2400-2483.5	Bluetooth-LE_GSFK	19	2440	1Mbps	-	-
Mode 3	2400-2483.5	Bluetooth-LE_GSFK	39	2480	1Mbps	-	-
Mode 4	2400-2483.5	Bluetooth-LE_GSFK	0	2402	2Mbps	-	-
Mode 5	2400-2483.5	Bluetooth-LE_GSFK	19	2440	2Mbps	-	-
Mode 6	2400-2483.5	Bluetooth-LE_GSFK	39	2480	2Mbps	-	-

Co-location Test Mode





Mode	Band (MHz)	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 7	2400-2483.5	Bluetooth-LE_GSFK	39	2480	2Mbps	-	-
	UWB CH9_cidx-10_sts-1_packet length-67						

**Summary of each worse mode**





Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	Bluetooth-LE_GSKF	0	2378.12	46.79	54.00	-7.21	H	AVERAGE	Pass	Band Edge
1	Bluetooth-LE_GSKF	0	7206.00	50.38	78.11	-27.73	V	PEAK	Pass	Harmonic
2	Bluetooth-LE_GSKF	19	-	-	-	-	-	-	-	Band Edge
2	Bluetooth-LE_GSKF	19	7320.00	46.81	54.00	-7.19	H	AVERAGE	Pass	Harmonic
3	Bluetooth-LE_GSKF	39	2488.00	49.45	54.00	-4.55	H	AVERAGE	Pass	Band Edge
3	Bluetooth-LE_GSKF	39	4960.00	48.06	54.00	-5.94	H	AVERAGE	Pass	Harmonic
4	Bluetooth-LE_GSKF	0	2377.86	46.13	54.00	-7.87	H	AVERAGE	Pass	Band Edge
4	Bluetooth-LE_GSKF	0	4804.00	42.94	74.00	-31.06	H	Peak	Pass	Harmonic
5	Bluetooth-LE_GSKF	19	-	-	-	-	-	-	-	Band Edge
5	Bluetooth-LE_GSKF	19	7320.00	45.83	54.00	-8.17	H	AVERAGE	Pass	Harmonic
6	Bluetooth-LE_GSKF	39	2483.50	49.41	54.00	-4.59	H	AVERAGE	Pass	Band Edge
6	Bluetooth-LE_GSKF	39	4960.00	46.68	54.00	-7.32	H	AVERAGE	Pass	Harmonic
7	Bluetooth-LE_GSKF	39	2488.00	50.96	54.00	-3.04	H	AVERAGE	Pass	Band Edge
7	Bluetooth-LE_GSKF	39	4960.00	50.33	54.00	-3.67	H	AVERAGE	Pass	Harmonic

Mode	Modulation	Ch.	Freq. (MHz)	E-field (dBuV/m)	Limit (dBm)	Limit (dBuV/m)	Margin (dB)	Result
7	UWB CH9_cidx-10_ sts-1_packet length-67		7987	50.53	-41.3	53.93	-3.4	Pass





		1																																																				
Mode		Band Edge																																																				
		2400-2483.5_Bluetooth-LE_GSKF_CH0_2402MHz																																																				
Pol.		Horizontal					Fundamental																																															
Peak																																																						
		<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2377.73</td><td>53.21</td><td>74.00</td><td>-20.79</td><td>45.09</td><td>32.08</td><td>7.09</td><td>37.05</td><td>6.00</td><td>384</td><td>80</td><td>PEAK</td></tr></table>											Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2377.73	53.21	74.00	-20.79	45.09	32.08	7.09	37.05	6.00	384	80
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2377.73	53.21	74.00	-20.79	45.09	32.08	7.09	37.05	6.00	384	80	PEAK																																										
Avg																																																						
		<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2378.12</td><td>46.79</td><td>54.00</td><td>-7.21</td><td>38.67</td><td>32.08</td><td>7.09</td><td>37.05</td><td>6.00</td><td>384</td><td>80</td><td>AVERAGE</td></tr></table>											Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2378.12	46.79	54.00	-7.21	38.67	32.08	7.09	37.05	6.00	384	80
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2378.12	46.79	54.00	-7.21	38.67	32.08	7.09	37.05	6.00	384	80	AVERAGE																																										
																																																						
		<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>106.18</td><td>-----</td><td>-----</td><td>97.80</td><td>32.30</td><td>7.12</td><td>37.04</td><td>6.00</td><td>384</td><td>80</td><td>PEAK</td></tr></table>											Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	106.18	-----	-----	97.80	32.30	7.12	37.04	6.00	384	80
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2402.00	106.18	-----	-----	97.80	32.30	7.12	37.04	6.00	384	80	PEAK																																										
																																																						
		<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>105.23</td><td>-----</td><td>-----</td><td>96.85</td><td>32.30</td><td>7.12</td><td>37.04</td><td>6.00</td><td>384</td><td>80</td><td>AVERAGE</td></tr></table>											Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	105.23	-----	-----	96.85	32.30	7.12	37.04	6.00	384	80
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2402.00	105.23	-----	-----	96.85	32.30	7.12	37.04	6.00	384	80	AVERAGE																																										





		1																																																				
Mode		Band Edge																																																				
		2400-2483.5_Bluetooth-LE_GSKF_CH0_2402MHz																																																				
Pol.		Vertical					Fundamental																																															
Peak																																																						
		<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2386.18</td><td>49.59</td><td>74.00</td><td>-24.41</td><td>41.38</td><td>32.16</td><td>7.10</td><td>37.05</td><td>6.00</td><td>100</td><td>358</td><td>PEAK</td></tr></table>											Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2386.18	49.59	74.00	-24.41	41.38	32.16	7.10	37.05	6.00	100	358
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																														
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2386.18	49.59	74.00	-24.41	41.38	32.16	7.10	37.05	6.00	100	358	PEAK																																										
Fundamental																																																						
		<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>96.81</td><td>-----</td><td>-----</td><td>88.43</td><td>32.30</td><td>7.12</td><td>37.04</td><td>6.00</td><td>100</td><td>358</td><td>PEAK</td></tr></table>											Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	96.81	-----	-----	88.43	32.30	7.12	37.04	6.00	100	358
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																														
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2402.00	96.81	-----	-----	88.43	32.30	7.12	37.04	6.00	100	358	PEAK																																										
Avg																																																						
		<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2386.05</td><td>41.05</td><td>54.00</td><td>-12.95</td><td>32.84</td><td>32.16</td><td>7.10</td><td>37.05</td><td>6.00</td><td>100</td><td>358</td><td>AVERAGE</td></tr></table>											Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2386.05	41.05	54.00	-12.95	32.84	32.16	7.10	37.05	6.00	100	358
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																														
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2386.05	41.05	54.00	-12.95	32.84	32.16	7.10	37.05	6.00	100	358	AVERAGE																																										
Fundamental																																																						
		<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>95.79</td><td>-----</td><td>-----</td><td>87.41</td><td>32.30</td><td>7.12</td><td>37.04</td><td>6.00</td><td>100</td><td>358</td><td>AVERAGE</td></tr></table>											Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	95.79	-----	-----	87.41	32.30	7.12	37.04	6.00	100	358
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																														
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																												
1	2402.00	95.79	-----	-----	87.41	32.30	7.12	37.04	6.00	100	358	AVERAGE																																										







Mode	1																																																																																																		
	Harmonic																																																																																																		
	2400-2483.5_Bluetooth-LE_GSKF_CH0_2402MHz																																																																																																		
Pol.	Horizontal						Vertical																																																																																												
Peak Avg																																																																																																			
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>104.03</td><td>-----</td><td>-----</td><td>95.65</td><td>32.30</td><td>7.12</td><td>37.04</td><td>6.00</td><td>300</td><td>333</td><td>PEAK</td></tr></table> <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>98.11</td><td>-----</td><td>-----</td><td>89.73</td><td>32.30</td><td>7.12</td><td>37.04</td><td>6.00</td><td>300</td><td>67</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	104.03	-----	-----	95.65	32.30	7.12	37.04	6.00	300	333	PEAK		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	98.11	-----	-----	89.73	32.30	7.12	37.04	6.00	300	67
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2402.00	104.03	-----	-----	95.65	32.30	7.12	37.04	6.00	300	333	PEAK																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2402.00	98.11	-----	-----	89.73	32.30	7.12	37.04	6.00	300	67	PEAK																																																																																							



Mode	2																																																																																																																																																						
	Harmonic																																																																																																																																																						
	2400-2483.5_Bluetooth-LE_GSKF_CH19_2440MHz																																																																																																																																																						
Pol.	Horizontal						Vertical																																																																																																																																																
Peak Avg																																																																																																																																																							
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>42.80</td><td>74.00</td><td>-31.20</td><td>63.88</td><td>34.15</td><td>10.30</td><td>65.53</td><td>0.00</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>7320.00</td><td>51.47</td><td>74.00</td><td>-22.53</td><td>69.33</td><td>35.74</td><td>12.72</td><td>66.32</td><td>0.00</td><td>100</td><td>117</td><td>PEAK</td></tr><tr><td>3</td><td>7320.00</td><td>46.81</td><td>54.00</td><td>-7.19</td><td>64.67</td><td>35.74</td><td>12.72</td><td>66.32</td><td>0.00</td><td>100</td><td>117</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4880.00	42.80	74.00	-31.20	63.88	34.15	10.30	65.53	0.00	--	--	PEAK	2	7320.00	51.47	74.00	-22.53	69.33	35.74	12.72	66.32	0.00	100	117	PEAK	3	7320.00	46.81	54.00	-7.19	64.67	35.74	12.72	66.32	0.00	100	117	AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>41.69</td><td>74.00</td><td>-32.31</td><td>62.77</td><td>34.15</td><td>10.30</td><td>65.53</td><td>0.00</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>7320.00</td><td>50.95</td><td>74.00</td><td>-23.05</td><td>68.81</td><td>35.74</td><td>12.72</td><td>66.32</td><td>0.00</td><td>106</td><td>337</td><td>PEAK</td></tr><tr><td>3</td><td>7320.00</td><td>46.24</td><td>54.00</td><td>-7.76</td><td>64.10</td><td>35.74</td><td>12.72</td><td>66.32</td><td>0.00</td><td>106</td><td>337</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4880.00	41.69	74.00	-32.31	62.77	34.15	10.30	65.53	0.00	--	--	PEAK	2	7320.00	50.95	74.00	-23.05	68.81	35.74	12.72	66.32	0.00	106	337	PEAK	3	7320.00	46.24	54.00	-7.76	64.10	35.74	12.72	66.32	0.00	106	337
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																													
1	4880.00	42.80	74.00	-31.20	63.88	34.15	10.30	65.53	0.00	--	--	PEAK																																																																																																																																											
2	7320.00	51.47	74.00	-22.53	69.33	35.74	12.72	66.32	0.00	100	117	PEAK																																																																																																																																											
3	7320.00	46.81	54.00	-7.19	64.67	35.74	12.72	66.32	0.00	100	117	AVERAGE																																																																																																																																											
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																													
1	4880.00	41.69	74.00	-32.31	62.77	34.15	10.30	65.53	0.00	--	--	PEAK																																																																																																																																											
2	7320.00	50.95	74.00	-23.05	68.81	35.74	12.72	66.32	0.00	106	337	PEAK																																																																																																																																											
3	7320.00	46.24	54.00	-7.76	64.10	35.74	12.72	66.32	0.00	106	337	AVERAGE																																																																																																																																											



		3																																																																																																											
Mode		Band Edge																																																																																																											
		2400-2483.5 Bluetooth-LE_GSKF_CH39_2480MHz																																																																																																											
Pol.	Horizontal											Fundamental																																																																																																	
Peak																																																																																																													
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.50</td><td>61.33</td><td>74.00</td><td>-12.67</td><td>52.45</td><td>32.47</td><td>7.26</td><td>36.85</td><td>6.00</td><td>121 118 PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.50	61.33	74.00	-12.67	52.45	32.47	7.26	36.85	6.00	121 118 PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>103.87</td><td>-----</td><td>-----</td><td>95.02</td><td>32.46</td><td>7.25</td><td>36.86</td><td>6.00</td><td>121 118 PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	103.87	-----	-----	95.02	32.46	7.25	36.86	6.00
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																			
1	2483.50	61.33	74.00	-12.67	52.45	32.47	7.26	36.85	6.00	121 118 PEAK																																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																			
1	2480.00	103.87	-----	-----	95.02	32.46	7.25	36.86	6.00	121 118 PEAK																																																																																																			
Avg																																																																																																													
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>49.45</td><td>54.00</td><td>-4.55</td><td>40.55</td><td>32.48</td><td>7.26</td><td>36.84</td><td>6.00</td><td>121 118 AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	49.45	54.00	-4.55	40.55	32.48	7.26	36.84	6.00	121 118 AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>102.95</td><td>-----</td><td>-----</td><td>94.10</td><td>32.46</td><td>7.25</td><td>36.86</td><td>6.00</td><td>121 118 AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	102.95	-----	-----	94.10	32.46	7.25	36.86	6.00
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																			
1	2480.00	49.45	54.00	-4.55	40.55	32.48	7.26	36.84	6.00	121 118 AVERAGE																																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																			
1	2480.00	102.95	-----	-----	94.10	32.46	7.25	36.86	6.00	121 118 AVERAGE																																																																																																			



3

Mode

Band Edge


2400-2483.5 Bluetooth-LE_GSKF_CH39_2480MHz

Pol.


Vertical

Fundamental

Peak




Freq	Level	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
		Line Margin								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg
1 2483.74	55.44	74.00	-18.56	46.56	32.47	7.26	36.85	6.00	300	263 PEAK




Freq	Level	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
		Line Margin								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg
1 2480.00	97.12	-----	88.27	32.46	7.25	36.86	6.00	300	263	PEAK

Avg



Freq	Level	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
		Line Margin								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg
1 2480.00	43.28	54.00	-10.72	34.38	32.48	7.26	36.84	6.00	300	263 AVERAGE



Freq	Level	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
		Line Margin								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg
1 2480.00	96.13	-----	87.28	32.46	7.25	36.86	6.00	300	263	AVERAGE



Mode	3																																																																																													
	Harmonic																																																																																													
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																													
Pol.	Horizontal																																																																																													
Peak Avg																																																																																														
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4960.00</td><td>51.33</td><td>74.00</td><td>-22.67</td><td>72.30</td><td>34.22</td><td>10.40</td><td>65.59</td><td>0.00</td><td>100</td><td>32</td><td>PEAK</td></tr><tr><td>2</td><td>4960.00</td><td>48.06</td><td>54.00</td><td>-5.94</td><td>69.03</td><td>34.22</td><td>10.40</td><td>65.59</td><td>0.00</td><td>100</td><td>32</td><td>AVERAGE</td></tr><tr><td>3</td><td>7440.00</td><td>50.00</td><td>74.00</td><td>-24.00</td><td>68.05</td><td>35.00</td><td>12.78</td><td>66.63</td><td>0.00</td><td>100</td><td>91</td><td>PEAK</td></tr><tr><td>4</td><td>7440.00</td><td>45.36</td><td>54.00</td><td>-8.64</td><td>63.41</td><td>35.00</td><td>12.78</td><td>66.63</td><td>0.00</td><td>100</td><td>91</td><td>AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4960.00	51.33	74.00	-22.67	72.30	34.22	10.40	65.59	0.00	100	32	PEAK	2	4960.00	48.06	54.00	-5.94	69.03	34.22	10.40	65.59	0.00	100	32	AVERAGE	3	7440.00	50.00	74.00	-24.00	68.05	35.00	12.78	66.63	0.00	100	91	PEAK	4	7440.00	45.36	54.00	-8.64	63.41	35.00	12.78	66.63	0.00	100	91	AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																					
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																				
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																			
1	4960.00	51.33	74.00	-22.67	72.30	34.22	10.40	65.59	0.00	100	32	PEAK																																																																																		
2	4960.00	48.06	54.00	-5.94	69.03	34.22	10.40	65.59	0.00	100	32	AVERAGE																																																																																		
3	7440.00	50.00	74.00	-24.00	68.05	35.00	12.78	66.63	0.00	100	91	PEAK																																																																																		
4	7440.00	45.36	54.00	-8.64	63.41	35.00	12.78	66.63	0.00	100	91	AVERAGE																																																																																		
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4960.00</td><td>51.33</td><td>74.00</td><td>-22.67</td><td>72.30</td><td>34.22</td><td>10.40</td><td>65.59</td><td>0.00</td><td>100</td><td>32</td><td>PEAK</td></tr><tr><td>2</td><td>4960.00</td><td>48.06</td><td>54.00</td><td>-5.94</td><td>69.03</td><td>34.22</td><td>10.40</td><td>65.59</td><td>0.00</td><td>100</td><td>32</td><td>AVERAGE</td></tr><tr><td>3</td><td>7440.00</td><td>50.00</td><td>74.00</td><td>-24.00</td><td>68.05</td><td>35.00</td><td>12.78</td><td>66.63</td><td>0.00</td><td>100</td><td>91</td><td>PEAK</td></tr><tr><td>4</td><td>7440.00</td><td>45.36</td><td>54.00</td><td>-8.64</td><td>63.41</td><td>35.00</td><td>12.78</td><td>66.63</td><td>0.00</td><td>100</td><td>91</td><td>AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4960.00	51.33	74.00	-22.67	72.30	34.22	10.40	65.59	0.00	100	32	PEAK	2	4960.00	48.06	54.00	-5.94	69.03	34.22	10.40	65.59	0.00	100	32	AVERAGE	3	7440.00	50.00	74.00	-24.00	68.05	35.00	12.78	66.63	0.00	100	91	PEAK	4	7440.00	45.36	54.00	-8.64	63.41	35.00	12.78	66.63	0.00	100	91	AVERAGE	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																				
1	4960.00	51.33	74.00	-22.67	72.30	34.22	10.40	65.59	0.00	100	32	PEAK																																																																																		
2	4960.00	48.06	54.00	-5.94	69.03	34.22	10.40	65.59	0.00	100	32	AVERAGE																																																																																		
3	7440.00	50.00	74.00	-24.00	68.05	35.00	12.78	66.63	0.00	100	91	PEAK																																																																																		
4	7440.00	45.36	54.00	-8.64	63.41	35.00	12.78	66.63	0.00	100	91	AVERAGE																																																																																		
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4960.00</td><td>44.20</td><td>74.00</td><td>-29.80</td><td>65.17</td><td>34.22</td><td>10.40</td><td>65.59</td><td>0.00</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>7440.00</td><td>51.28</td><td>74.00</td><td>-22.72</td><td>69.33</td><td>35.00</td><td>12.78</td><td>66.63</td><td>0.00</td><td>100</td><td>333</td><td>PEAK</td></tr><tr><td>3</td><td>7440.00</td><td>46.93</td><td>54.00</td><td>-7.07</td><td>64.98</td><td>35.00</td><td>12.78</td><td>66.63</td><td>0.00</td><td>100</td><td>333</td><td>AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4960.00	44.20	74.00	-29.80	65.17	34.22	10.40	65.59	0.00	--	--	PEAK	2	7440.00	51.28	74.00	-22.72	69.33	35.00	12.78	66.63	0.00	100	333	PEAK	3	7440.00	46.93	54.00	-7.07	64.98	35.00	12.78	66.63	0.00	100	333	AVERAGE														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																				
1	4960.00	44.20	74.00	-29.80	65.17	34.22	10.40	65.59	0.00	--	--	PEAK																																																																																		
2	7440.00	51.28	74.00	-22.72	69.33	35.00	12.78	66.63	0.00	100	333	PEAK																																																																																		
3	7440.00	46.93	54.00	-7.07	64.98	35.00	12.78	66.63	0.00	100	333	AVERAGE																																																																																		



4

Mode

Band Edge


2400-2483.5 Bluetooth-LE_GSKF_CH0_2402MHz

Pol.


Horizontal

Fundamental

Peak




Freq	Level	Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
		Line	Margin	Level	Factor	Loss	Factor	Factor			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1 2378.51	53.38	74.00	-20.62	45.25	32.09	7.09	37.05	6.00	385	82	PEAK




Freq	Level	Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
		Line	Margin	Level	Factor	Loss	Factor	Factor			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1 2402.00	106.15	-----	-----	97.77	32.30	7.12	37.04	6.00	385	82	PEAK

Avg







Freq	Level	Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
		Line	Margin	Level	Factor	Loss	Factor	Factor			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1 2377.86	46.13	54.00	-7.87	38.01	32.08	7.09	37.05	6.00	385	82	AVERAGE





Freq	Level	Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
		Line	Margin	Level	Factor	Loss	Factor	Factor			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1 2402.00	104.05	-----	-----	95.67	32.30	7.12	37.04	6.00	385	82	AVERAGE





		4																																																																																							
Mode		Band Edge																																																																																							
		2400-2483.5_Bluetooth-LE_GSKF_CH0_2402MHz																																																																																							
Pol.	Vertical					Fundamental																																																																																			
Peak																																																																																									
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 2385.79	49.72	74.00	-24.28	41.51	32.16	7.10	37.05	6.00	100 358 PEAK	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 2402.00</td><td>96.67</td><td>-----</td><td>-----</td><td>88.29</td><td>32.30</td><td>7.12</td><td>37.04</td><td>6.00</td><td>100 358 PEAK</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 2402.00	96.67	-----	-----	88.29	32.30	7.12	37.04	6.00	100 358 PEAK				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1 2385.79	49.72	74.00	-24.28	41.51	32.16	7.10	37.05	6.00	100 358 PEAK																																																																																
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1 2402.00	96.67	-----	-----	88.29	32.30	7.12	37.04	6.00	100 358 PEAK																																																																																
Avg																																																																																									
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 2377.99</td><td>40.75</td><td>54.00</td><td>-13.25</td><td>32.63</td><td>32.08</td><td>7.09</td><td>37.05</td><td>6.00</td><td>100 358 AVERAGE</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 2377.99	40.75	54.00	-13.25	32.63	32.08	7.09	37.05	6.00	100 358 AVERAGE	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 2402.00</td><td>94.51</td><td>-----</td><td>-----</td><td>86.13</td><td>32.30</td><td>7.12</td><td>37.04</td><td>6.00</td><td>100 358 AVERAGE</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 2402.00	94.51	-----	-----	86.13	32.30	7.12	37.04	6.00
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1 2377.99	40.75	54.00	-13.25	32.63	32.08	7.09	37.05	6.00	100 358 AVERAGE																																																																																
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1 2402.00	94.51	-----	-----	86.13	32.30	7.12	37.04	6.00	100 358 AVERAGE																																																																																



Mode	4																																																								
	Harmonic																																																								
	2400-2483.5_Bluetooth-LE_GSKF_CH0_2402MHz																																																								
Pol.	Horizontal						Vertical																																																		
Peak Avg																																																									
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>101.14</td><td>-----</td><td>-----</td><td>92.76</td><td>32.30</td><td>7.12</td><td>37.04</td><td>6.00</td><td>300</td><td>335</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	2402.00	101.14	-----	-----	92.76	32.30	7.12	37.04	6.00	300	335	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																														
1	2402.00	101.14	-----	-----	92.76	32.30	7.12	37.04	6.00	300	335	PEAK																																													
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>103.74</td><td>-----</td><td>-----</td><td>95.36</td><td>32.30</td><td>7.12</td><td>37.04</td><td>6.00</td><td>100</td><td>264</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	2402.00	103.74	-----	-----	95.36	32.30	7.12	37.04	6.00	100	264	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																														
1	2402.00	103.74	-----	-----	95.36	32.30	7.12	37.04	6.00	100	264	PEAK																																													



		5																																																																					
Mode		Harmonic																																																																					
		2400-2483.5_Bluetooth-LE_GSKF_CH19_2440MHz																																																																					
Pol.		Horizontal																																																																					
Peak		Vertical																																																																					
Avg		Vertical																																																																					
																																																																							
																																																																							
		<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th></tr><tr><td>1 4880.00</td><td>42.25</td><td>74.00</td><td>-31.75</td><td>63.33</td><td>34.15</td><td>10.30</td><td>65.53</td><td>0.00</td></tr><tr><td>2 7320.00</td><td>50.69</td><td>74.00</td><td>-23.31</td><td>68.55</td><td>35.74</td><td>12.72</td><td>66.32</td><td>0.00</td></tr><tr><td>3 7320.00</td><td>45.83</td><td>54.00</td><td>-8.17</td><td>63.68</td><td>35.74</td><td>12.72</td><td>66.31</td><td>0.00</td></tr></table>																	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	1 4880.00	42.25	74.00	-31.75	63.33	34.15	10.30	65.53	0.00	2 7320.00	50.69	74.00	-23.31	68.55	35.74	12.72	66.32	0.00	3 7320.00	45.83	54.00	-8.17	63.68	35.74	12.72	66.31	0.00
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB																																																															
1 4880.00	42.25	74.00	-31.75	63.33	34.15	10.30	65.53	0.00																																																															
2 7320.00	50.69	74.00	-23.31	68.55	35.74	12.72	66.32	0.00																																																															
3 7320.00	45.83	54.00	-8.17	63.68	35.74	12.72	66.31	0.00																																																															
		<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th></tr><tr><td>1 4880.00</td><td>41.22</td><td>74.00</td><td>-32.78</td><td>62.30</td><td>34.15</td><td>10.30</td><td>65.53</td><td>0.00</td></tr><tr><td>2 7320.00</td><td>46.60</td><td>74.00</td><td>-27.40</td><td>64.46</td><td>35.74</td><td>12.72</td><td>66.32</td><td>0.00</td></tr></table>																	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	1 4880.00	41.22	74.00	-32.78	62.30	34.15	10.30	65.53	0.00	2 7320.00	46.60	74.00	-27.40	64.46	35.74	12.72	66.32	0.00									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB																																																															
1 4880.00	41.22	74.00	-32.78	62.30	34.15	10.30	65.53	0.00																																																															
2 7320.00	46.60	74.00	-27.40	64.46	35.74	12.72	66.32	0.00																																																															



6

Mode

Band Edge



2400-2483.5 Bluetooth-LE_GSKF_CH39_2480MHz

Pol.



Horizontal

Fundamental





Peak



Avg







Mode	6																																																																																																		
	Band Edge																																																																																																		
	2400-2483.5 Bluetooth-LE_GSKF_CH39_2480MHz																																																																																																		
Pol.	Vertical						Fundamental																																																																																												
Peak																																																																																																			
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2483.68</td><td>55.30</td><td>74.00</td><td>-18.70</td><td>46.42</td><td>32.47</td><td>7.26</td><td>36.85</td><td>6.00</td><td>297</td><td>264</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.68	55.30	74.00	-18.70	46.42	32.47	7.26	36.85	6.00	297	264	PEAK	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>97.31</td><td>-----</td><td>-----</td><td>88.46</td><td>32.46</td><td>7.25</td><td>36.86</td><td>6.00</td><td>297</td><td>264</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	97.31	-----	-----	88.46	32.46	7.25	36.86	6.00	297	264
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2483.68	55.30	74.00	-18.70	46.42	32.47	7.26	36.85	6.00	297	264	PEAK																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2480.00	97.31	-----	-----	88.46	32.46	7.25	36.86	6.00	297	264	PEAK																																																																																							
Avg																																																																																																			
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2483.50</td><td>43.45</td><td>54.00</td><td>-10.55</td><td>34.57</td><td>32.47</td><td>7.26</td><td>36.85</td><td>6.00</td><td>297</td><td>264</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.50	43.45	54.00	-10.55	34.57	32.47	7.26	36.85	6.00	297	264	AVERAGE	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>95.10</td><td>-----</td><td>-----</td><td>86.25</td><td>32.46</td><td>7.25</td><td>36.86</td><td>6.00</td><td>297</td><td>264</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	95.10	-----	-----	86.25	32.46	7.25	36.86	6.00	297	264
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2483.50	43.45	54.00	-10.55	34.57	32.47	7.26	36.85	6.00	297	264	AVERAGE																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2480.00	95.10	-----	-----	86.25	32.46	7.25	36.86	6.00	297	264	AVERAGE																																																																																							



Mode	6																																																																																																				
	Harmonic																																																																																																				
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																																				
Pol.	Horizontal																																																																																																				
Peak Avg																																																																																																					
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4960.00</td><td>50.93</td><td>74.00</td><td>-23.07</td><td>71.90</td><td>34.22</td><td>10.40</td><td>65.59</td><td>0.00</td><td>100</td><td>30</td><td>PEAK</td></tr><tr><td>2</td><td>4960.00</td><td>46.68</td><td>54.00</td><td>-7.32</td><td>67.65</td><td>34.22</td><td>10.40</td><td>65.59</td><td>0.00</td><td>100</td><td>30</td><td>AVERAGE</td></tr><tr><td>3</td><td>7440.00</td><td>49.46</td><td>74.00</td><td>-24.54</td><td>67.51</td><td>35.00</td><td>12.78</td><td>66.63</td><td>0.00</td><td>100</td><td>93</td><td>PEAK</td></tr><tr><td>4</td><td>7440.00</td><td>43.99</td><td>54.00</td><td>-10.01</td><td>62.04</td><td>35.00</td><td>12.78</td><td>66.63</td><td>0.00</td><td>100</td><td>93</td><td>AVERAGE</td></tr></table>													Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4960.00	50.93	74.00	-23.07	71.90	34.22	10.40	65.59	0.00	100	30	PEAK	2	4960.00	46.68	54.00	-7.32	67.65	34.22	10.40	65.59	0.00	100	30	AVERAGE	3	7440.00	49.46	74.00	-24.54	67.51	35.00	12.78	66.63	0.00	100	93	PEAK	4	7440.00	43.99	54.00	-10.01	62.04	35.00	12.78	66.63	0.00	100	93	AVERAGE
			Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																									
1	4960.00	50.93	74.00	-23.07	71.90	34.22	10.40	65.59	0.00	100	30	PEAK																																																																																									
2	4960.00	46.68	54.00	-7.32	67.65	34.22	10.40	65.59	0.00	100	30	AVERAGE																																																																																									
3	7440.00	49.46	74.00	-24.54	67.51	35.00	12.78	66.63	0.00	100	93	PEAK																																																																																									
4	7440.00	43.99	54.00	-10.01	62.04	35.00	12.78	66.63	0.00	100	93	AVERAGE																																																																																									
<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4960.00</td><td>44.11</td><td>74.00</td><td>-29.89</td><td>65.00</td><td>34.22</td><td>10.40</td><td>65.59</td><td>0.00</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>7440.00</td><td>50.02</td><td>74.00</td><td>-23.98</td><td>68.07</td><td>35.00</td><td>12.78</td><td>66.63</td><td>0.00</td><td>300</td><td>303</td><td>PEAK</td></tr><tr><td>3</td><td>7440.00</td><td>44.59</td><td>54.00</td><td>-9.41</td><td>62.64</td><td>35.00</td><td>12.78</td><td>66.63</td><td>0.00</td><td>300</td><td>303</td><td>AVERAGE</td></tr></table>													Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4960.00	44.11	74.00	-29.89	65.00	34.22	10.40	65.59	0.00	--	--	PEAK	2	7440.00	50.02	74.00	-23.98	68.07	35.00	12.78	66.63	0.00	300	303	PEAK	3	7440.00	44.59	54.00	-9.41	62.64	35.00	12.78	66.63	0.00	300	303	AVERAGE														
		Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																										
1	4960.00	44.11	74.00	-29.89	65.00	34.22	10.40	65.59	0.00	--	--	PEAK																																																																																									
2	7440.00	50.02	74.00	-23.98	68.07	35.00	12.78	66.63	0.00	300	303	PEAK																																																																																									
3	7440.00	44.59	54.00	-9.41	62.64	35.00	12.78	66.63	0.00	300	303	AVERAGE																																																																																									







Mode	6	
	18G-25G	
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz	
Pol.	Horizontal	Vertical
Peak Avg		



Mode	6																																																																																																						
	30-1G																																																																																																						
	2400-2483.5_Bluetooth-LE_GSKF_CH39_2480MHz																																																																																																						
Pol.	Horizontal																																																																																																						
QP/Peak																																																																																																							
	<table><tr><th>Freq</th><th>Level</th><th>Over Limit</th><th>Limit Line</th><th>Read Level</th><th>CableAntenna Loss</th><th>Preamp Factor</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>57.16</td><td>19.86</td><td>-20.14</td><td>40.00</td><td>38.55</td><td>1.12</td><td>13.10</td><td>32.91</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>167.74</td><td>33.55</td><td>-9.95</td><td>43.50</td><td>48.36</td><td>1.96</td><td>16.06</td><td>32.83</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>180.35</td><td>34.85</td><td>-8.65</td><td>43.50</td><td>49.04</td><td>2.03</td><td>15.81</td><td>32.83</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>263.77</td><td>25.39</td><td>-20.61</td><td>46.00</td><td>37.02</td><td>2.48</td><td>18.67</td><td>32.78</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>408.30</td><td>30.13</td><td>-15.87</td><td>46.00</td><td>38.10</td><td>3.08</td><td>21.82</td><td>32.87</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>6</td><td>735.19</td><td>30.40</td><td>-15.60</td><td>46.00</td><td>33.48</td><td>4.15</td><td>25.65</td><td>32.88</td><td>---</td><td>---</td><td>Peak</td></tr></table>											Freq	Level	Over Limit	Limit Line	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB/m	dB	cm	deg	1	57.16	19.86	-20.14	40.00	38.55	1.12	13.10	32.91	---	---	Peak	2	167.74	33.55	-9.95	43.50	48.36	1.96	16.06	32.83	---	---	Peak	3	180.35	34.85	-8.65	43.50	49.04	2.03	15.81	32.83	---	---	Peak	4	263.77	25.39	-20.61	46.00	37.02	2.48	18.67	32.78	---	---	Peak	5	408.30	30.13	-15.87	46.00	38.10	3.08	21.82	32.87	---	---	Peak	6	735.19	30.40	-15.60	46.00	33.48	4.15	25.65	32.88	---	---	Peak
	Freq	Level	Over Limit	Limit Line	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Remark																																																																																													
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB/m	dB	cm	deg																																																																																													
	1	57.16	19.86	-20.14	40.00	38.55	1.12	13.10	32.91	---	---	Peak																																																																																											
	2	167.74	33.55	-9.95	43.50	48.36	1.96	16.06	32.83	---	---	Peak																																																																																											
	3	180.35	34.85	-8.65	43.50	49.04	2.03	15.81	32.83	---	---	Peak																																																																																											
	4	263.77	25.39	-20.61	46.00	37.02	2.48	18.67	32.78	---	---	Peak																																																																																											
	5	408.30	30.13	-15.87	46.00	38.10	3.08	21.82	32.87	---	---	Peak																																																																																											
	6	735.19	30.40	-15.60	46.00	33.48	4.15	25.65	32.88	---	---	Peak																																																																																											
<table><tr><th>Freq</th><th>Level</th><th>Over Limit</th><th>Limit Line</th><th>Read Level</th><th>CableAntenna Loss</th><th>Preamp Factor</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>33.88</td><td>35.58</td><td>-4.42</td><td>40.00</td><td>45.16</td><td>0.78</td><td>22.56</td><td>32.92</td><td>100</td><td>174</td><td>QP</td></tr><tr><td>2</td><td>45.52</td><td>31.19</td><td>-8.81</td><td>40.00</td><td>47.07</td><td>0.98</td><td>16.11</td><td>32.97</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>156.10</td><td>32.90</td><td>-10.52</td><td>43.50</td><td>47.61</td><td>1.89</td><td>16.30</td><td>32.82</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>203.63</td><td>31.03</td><td>-12.47</td><td>43.50</td><td>46.05</td><td>2.17</td><td>15.64</td><td>32.83</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>551.06</td><td>27.22</td><td>-18.78</td><td>46.00</td><td>31.64</td><td>3.59</td><td>25.10</td><td>33.11</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>6</td><td>833.16</td><td>32.10</td><td>-13.90</td><td>46.00</td><td>33.71</td><td>4.41</td><td>26.48</td><td>32.50</td><td>---</td><td>---</td><td>Peak</td></tr></table>											Freq	Level	Over Limit	Limit Line	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB/m	dB	cm	deg	1	33.88	35.58	-4.42	40.00	45.16	0.78	22.56	32.92	100	174	QP	2	45.52	31.19	-8.81	40.00	47.07	0.98	16.11	32.97	---	---	Peak	3	156.10	32.90	-10.52	43.50	47.61	1.89	16.30	32.82	---	---	Peak	4	203.63	31.03	-12.47	43.50	46.05	2.17	15.64	32.83	---	---	Peak	5	551.06	27.22	-18.78	46.00	31.64	3.59	25.10	33.11	---	---	Peak	6	833.16	32.10	-13.90	46.00	33.71	4.41	26.48	32.50	---	---	Peak	
Freq	Level	Over Limit	Limit Line	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Remark																																																																																														
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB/m	dB	cm	deg																																																																																														
1	33.88	35.58	-4.42	40.00	45.16	0.78	22.56	32.92	100	174	QP																																																																																												
2	45.52	31.19	-8.81	40.00	47.07	0.98	16.11	32.97	---	---	Peak																																																																																												
3	156.10	32.90	-10.52	43.50	47.61	1.89	16.30	32.82	---	---	Peak																																																																																												
4	203.63	31.03	-12.47	43.50	46.05	2.17	15.64	32.83	---	---	Peak																																																																																												
5	551.06	27.22	-18.78	46.00	31.64	3.59	25.10	33.11	---	---	Peak																																																																																												
6	833.16	32.10	-13.90	46.00	33.71	4.41	26.48	32.50	---	---	Peak																																																																																												



		7																																																																																								
Mode		Band Edge																																																																																								
		Bluetooth-LE_GSKF_CH39_2480MHz																																																																																								
Pol.	Horizontal										Fundamental																																																																															
Peak																																																																																										
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.68	61.62	74.00	-12.38	49.15	31.97	6.73	32.23	6.00	100	297 PEAK	<table><thead><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>103.56</td><td>-----</td><td>-----</td><td>91.10</td><td>31.96</td><td>6.73</td><td>32.23</td><td>6.00</td><td>100</td><td>297 PEAK</td></tr></tbody></table>		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	103.56	-----	-----	91.10	31.96	6.73	32.23	6.00	100
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																	
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2483.68	61.62	74.00	-12.38	49.15	31.97	6.73	32.23	6.00	100	297 PEAK																																																																															
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																	
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2480.00	103.56	-----	-----	91.10	31.96	6.73	32.23	6.00	100	297 PEAK																																																																															
Avg																																																																																										
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2488.00	50.96	54.00	-3.04	38.48	31.98	6.74	32.24	6.00	100	297 AVERAGE	<table><thead><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>101.35</td><td>-----</td><td>-----</td><td>88.89</td><td>31.96</td><td>6.73</td><td>32.23</td><td>6.00</td><td>100</td><td>297 AVERAGE</td></tr></tbody></table>		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	101.35	-----	-----	88.89	31.96	6.73	32.23	6.00	100
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																	
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2488.00	50.96	54.00	-3.04	38.48	31.98	6.74	32.24	6.00	100	297 AVERAGE																																																																															
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																	
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2480.00	101.35	-----	-----	88.89	31.96	6.73	32.23	6.00	100	297 AVERAGE																																																																															



Mode	7																																																							
	Band Edge																																																							
	Bluetooth-LE_GSKF_CH39_2480MHz																																																							
Pol.	Vertical																																																							
Peak	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.68</td><td>62.19</td><td>74.00</td><td>-11.81</td><td>49.72</td><td>31.97</td><td>6.73</td><td>32.23</td><td>6.00</td><td>286</td><td>311 PEAK</td></tr></table>												Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.68	62.19	74.00	-11.81	49.72	31.97	6.73	32.23	6.00	286	311 PEAK
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																														
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																														
1	2483.68	62.19	74.00	-11.81	49.72	31.97	6.73	32.23	6.00	286	311 PEAK																																													
Fundamental	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>102.20</td><td>-----</td><td>-----</td><td>89.74</td><td>31.96</td><td>6.73</td><td>32.23</td><td>6.00</td><td>286</td><td>311 PEAK</td></tr></table>												Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	102.20	-----	-----	89.74	31.96	6.73	32.23	6.00	286	311 PEAK
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																														
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																														
1	2480.00	102.20	-----	-----	89.74	31.96	6.73	32.23	6.00	286	311 PEAK																																													
Avg	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.50</td><td>49.19</td><td>54.00</td><td>-4.81</td><td>36.72</td><td>31.97</td><td>6.73</td><td>32.23</td><td>6.00</td><td>286</td><td>311 AVERAGE</td></tr></table>												Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.50	49.19	54.00	-4.81	36.72	31.97	6.73	32.23	6.00	286	311 AVERAGE
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																														
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																														
1	2483.50	49.19	54.00	-4.81	36.72	31.97	6.73	32.23	6.00	286	311 AVERAGE																																													
Fundamental	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>100.12</td><td>-----</td><td>-----</td><td>87.66</td><td>31.96</td><td>6.73</td><td>32.23</td><td>6.00</td><td>286</td><td>311 AVERAGE</td></tr></table>												Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	100.12	-----	-----	87.66	31.96	6.73	32.23	6.00	286	311 AVERAGE
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																														
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																														
1	2480.00	100.12	-----	-----	87.66	31.96	6.73	32.23	6.00	286	311 AVERAGE																																													



7

Mode

Harmonic

Bluetooth-LE_GSKF_CH39_2480MHz


Pol.

Horizontal


Vertical

Peak

Avg



	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		
1	4960.00	54.20	74.00	-19.80	71.49	34.26	9.61	61.16	0.00	100	338	PEAK
2	4960.00	50.33	54.00	-3.67	67.62	34.26	9.61	61.16	0.00	100	338	AVERAGE
3	7440.00	53.49	74.00	-20.51	67.12	35.62	11.77	61.02	0.00	100	352	PEAK
4	7440.00	48.58	54.00	-5.42	62.20	35.62	11.77	61.01	0.00	100	352	AVERAGE



	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		
1	4960.00	49.21	74.00	-24.79	66.50	34.26	9.61	61.16	0.00	111	0	PEAK
2	4960.00	44.31	54.00	-9.69	61.60	34.26	9.61	61.16	0.00	111	0	AVERAGE
3	7440.00	52.85	74.00	-21.15	66.48	35.62	11.77	61.02	0.00	100	240	PEAK
4	7440.00	47.68	54.00	-6.32	61.30	35.62	11.77	61.01	0.00	100	240	AVERAGE




Mode	7																																							
	-																																							
	UWB CH9																																							
Pol.	Horizontal																																							
Avg	Level (dBuV/m) Frequency (MHz) <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th><th>Pol/Phase</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr></thead><tbody><tr><td>1 7987.00</td><td>50.53</td><td>-----</td><td>-----</td><td>62.42</td><td>35.90</td><td>12.41</td><td>60.20</td><td>0.00</td><td>---</td><td>---</td><td>Average</td><td>Horizontal</td></tr></tbody></table>	Freq	Level	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Pol/Phase	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg			1 7987.00	50.53	-----	-----	62.42	35.90	12.41	60.20	0.00	---	---	Average	Horizontal
Freq	Level	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Pol/Phase																												
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																														
1 7987.00	50.53	-----	-----	62.42	35.90	12.41	60.20	0.00	---	---	Average	Horizontal																												

Appendix C. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
Bluetooth LE 1Mbps	62.50	0.391	2.556	2.7KHz
Bluetooth LE 2Mbps	32.87	0.206	4.859	5.1KHz

Bluetooth LE 1Mbps





Bluetooth LE 2Mbps

