

FCC §15.247 (i) & §1.1307 (b) (3) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2f$.
1,500-100,000	$19.2R^2$.

R is the minimum separation distance in meters

f = frequency in MHz

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Result

Mode	Frequency (MHz)	Tune up conducted power	Antenna Gain		ERP		Evaluation Distance (m)	ERP Limit (W)
		(dBm)	(dBi)	(dBd)	(dBm)	(W)		
BT	2402-2480	12.0	3	0.85	12.85	0.019	0.2	0.768
BLE	2402-2480	12.0	3	0.85	12.85	0.019	0.2	0.768
Wi-Fi	2412-2462	18.5	3	0.85	19.35	0.086	0.2	0.768
	5150-5850	15.5	3	0.85	16.35	0.043	0.2	0.768
DECT	1921.536 - 1928.448	20.4	3	0.85	21.25	0.133	0.2	0.768

Note: 1. The tune up conducted power and antenna gain was declared by the applicant.
 2. EUT contain a BT/Wi-Fi module YL430132, FCC ID: T2C-YL430132
 3. 0dBd=2.15dBi
 4. the Wi-Fi can transmit at the same time with the DECT function, the BT/BLE cannot transmit simultaneously with DECT/Wi-Fi, the 2.4GHz Wi-Fi and 5GHz Wi-Fi cannot transmit simultaneously.

Simultaneous transmitting consideration (worst case):

The ratio= $ERP_{Wi-Fi}/limit + ERP_{DECT}/limit = 0.086/0.768 + 0.133/0.768 = 0.285 < 1.0$, so simultaneous exposure is compliant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.