

## Indoor Antennas OMNI-6

### OMNI-6, Indoor Omni-directional Antenna

The OMNI-6, 6 dBi, omnidirectional antenna can be used with the [BreezeNET PRO.11 D Model Bridges](#) and [DS.11 Outdoor Bridges](#) for long range indoor applications.

The OMNI-6 antenna attaches to the female connector on the PRO.11 D Model Bridges and the DS.11 Outdoor Bridges and provides 360 degree horizontal/20 degree vertical transmission. Click [here](#) to view BreezeNET PRO.11 Range Table. Click [here](#) to view the BreezeNET DS.11 Range Table.



SPECIFICATIONS	
<b>Antenna:</b>	
Antenna Gain*	6 dBi
Kit Gain!	5 dBi
Frequency Range	2.4 – 2.5 GHz
Impedance	50 Ohms
Dispersion	360° horizontal/20° vertical
Polarization	Vertical
VSWR	1.5:1 Max
Dimensions	10.5" x 0.75"; 38 x 18mm tubular
Operating temperature range	-86° to 158° F; -30° to 70° C
Weight	4 oz; 100 g
Mounting	Wall, standard
<b>Cable:</b>	
Type	RG-58
Impedance	50 Ohms
Attenuation	0.2 dB (ft.);
Length	4'
Connector	N type

\* Antenna gain is the gain of the antenna without the cable.

! Kit gain is the actual gain of the antenna kit as it is shipped from BreezeCOM.

**Back to [Antennas & Accessories](#)**

|| [Home](#) || [About BreezeCOM](#) || [Products](#) || [Applications](#) || [News and Events](#) ||  
|| [Ordering and Tracking](#) || [Technical Support](#) || [Partners](#) || [Site Map](#) || [Contact Us](#) ||

©Copyrighted BreezeCOM®  
All Rights Reserved