

FCC TEST REPORT

REPORT NO.: RF931018L03A

MODEL NO.: WLG-2206

OEM MODEL NO.: IS35744-M1
(refer to page 6 for other models)

RECEIVED: NA

TESTED: Oct. 07 ~ Oct. 13, 2004

ISSUED: Apr. 22, 2005

APPLICANT: CAMEO COMMUNICATIONS, INC.

ADDRESS: 2F, No 44, Park Ave 2 Science-Based
Industrial Park, Taiwan, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan,
R.O.C.

This test report consists of 62 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.



Table of Contents

1	CERTIFICATION	4
2	SUMMARY OF TEST RESULTS	5
2.1	GENERAL DESCRIPTION OF EUT	5
3	GENERAL INFORMATION.....	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	7
3.2.1	CONFIGURATION OF SYSTEM UNDER TEST	7
3.2.2	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	8
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	10
3.4	DESCRIPTION OF SUPPORT UNITS	10
4	TEST TYPES AND RESULTS	11
4.1	CONDUCTED EMISSION MEASUREMENT	11
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	11
4.1.2	TEST INSTRUMENTS.....	11
4.1.3	TEST PROCEDURES	12
4.1.4	DEVIATION FROM TEST STANDARD	12
4.1.5	TEST SETUP	13
4.1.6	EUT OPERATING CONDITIONS	13
4.1.7	TEST RESULTS	14
4.2	RADIATED EMISSION MEASUREMENT	20
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	20
4.2.2	TEST INSTRUMENTS.....	21
4.2.3	TEST PROCEDURES	22
4.2.4	DEVIATION FROM TEST STANDARD	22
4.2.5	TEST SETUP.....	23
4.2.6	EUT OPERATING CONDITIONS	23
4.2.7	TEST RESULTS	24
4.3	6dB BANDWIDTH MEASUREMENT.....	31
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	31
4.3.2	TEST INSTRUMENTS.....	31
4.3.3	TEST PROCEDURE.....	32
4.3.4	DEVIATION FROM TEST STANDARD	32
4.3.5	TEST SETUP.....	32
4.3.6	EUT OPERATING CONDITIONS	32
4.3.7	TEST RESULTS	33
4.4	MAXIMUM PEAK OUTPUT POWER	39
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	39
4.4.2	TEST INSTRUMENTS.....	39
4.4.3	TEST PROCEDURES	40
4.4.4	DEVIATION FROM TEST STANDARD	40
4.4.5	TEST SETUP.....	40
4.4.6	EUT OPERATING CONDITIONS	40
4.4.7	TEST RESULTS	41



4.5	POWER SPECTRAL DENSITY MEASUREMENT	42
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	42
4.5.2	TEST INSTRUMENTS.....	42
4.5.3	TEST PROCEDURE.....	43
4.5.4	DEVIATION FROM TEST STANDARD	43
4.5.5	TEST SETUP.....	43
4.5.6	EUT OPERATING CONDITIONS	43
4.5.7	TEST RESULTS	44
4.6	BAND EDGES MEASUREMENT	50
4.6.1	LIMITS OF BAND EDGES MEASUREMENT.....	50
4.6.2	TEST INSTRUMENTS.....	50
4.6.3	TEST PROCEDURE.....	50
4.6.4	DEVIATION FROM TEST STANDARD	50
4.6.5	EUT OPERATING CONDITION	50
4.6.6	TEST RESULTS	51
4.7	ANTENNA REQUIREMENT	59
4.7.1	STANDARD APPLICABLE	59
4.7.2	ANTENNA CONNECTED CONSTRUCTION.....	59
5	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	60
6	INFORMATION ON THE TESTING LABORATORIES	62



1 CERTIFICATION

PRODUCT : 802.11g Wireless Broadband Router

MODEL NO. : WLG-2206

OEM MODEL NO.: IS35744-M1 (refer to page 6 for other models)

BRAND NAME : CAMEO

OEM BRAND NAME : ISINE (refer to page 6 for other brands)

APPLICANT : CAMEO COMMUNICATIONS, INC.

TEST SAMPLE : ENGINEERING SAMPLE

STANDARDS : FCC Part 15, Subpart C (Section 15.247),
ANSI C63.4-2003

The above equipment (model no.: WLG-2206) is identical to model no. DI-524, which has been tested by **Advance Data Technology Corporation** from Oct. 07 ~ Oct. 13, 2004, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Andrea Hsia , **DATE:** Apr. 22, 2005
(Andrea Hsia)

TECHNICAL

ACCEPTANCE : Gary Chang , **DATE:** Apr. 22, 2005
Responsible for RF (Gary Chang)

APPROVED BY : Cody Chang , **DATE:** Apr. 22, 2005
(Cody Chang, Deputy Manager)

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -13.51dB at 2.547MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -1.28dB at 2390.00MHz
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.

2.1 GENERAL DESCRIPTION OF EUT

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9k~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.73 dB
	200MHz ~1000MHz	3.74 dB
	1GHz ~ 18GHz	2.20 dB
	18GHz ~ 40GHz	1.88 dB

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	802.11g Wireless Broadband Router
MODEL NO.	WLG-2206
POWER SUPPLY	5.0Vdc from AC adapter
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
RADIO TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11
OUTPUT POWER	56.49mW
ANTENNA TYPE	Dipole antenna with 2dBi gain
DATA CABLE	NA
I/O PORTS	RJ45
ASSOCIATED DEVICES	NA

NOTE:

1. This is a duplicate report of RF931018L03, the difference are changing the product name, brand name, model name, Applicant, appearance and adding OEM due to marketing requirement.
2. The models as below are identical to each other expect for their models due to marketing requirement.

Model Name	Brand	Remark
ISINE	IS35744-M1	OEM
WR 100	Crypto	OEM
BR6004W-G	Dynamode	OEM
LSA-900R	lenovonetworks	OEM
LWG5410R	LG	OEM
WL-G54MAR	LINKPRO	OEM
KWG-401	KTI	OEM
ENHWI-RG	ENCORE	OEM
WLG-R4II	BONA	OEM
TEW-432BRP	TRENDnet	OEM
ALL0266	ALLNET GmbH	OEM
WL RT 2454 NM2	GST	OEM
WLR4G	Amertek	OEM

3. The EUT was tested with the following adapter:

BRAND:	D-Link
MODEL :	JTA0302B
INPUT :	100-240Vac~0.5S, 50-60Hz
OUTPUT :	5.0Vdc, 2.5A
POWER LINE:	DC 1.8m non-shielded cable without core


4. The EUT operates in the 2.4GHz frequency spectrum with throughput of up to 54Mbps.
5. The EUT complies with IEEE 802.11g standards and backwards compatible with IEEE 802.11b products.
6. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST



3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT configure mode	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
-	X	X	X	X	-

Where PLC: Power Line Conducted Emission

RE<1G RE: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

Radiated Emission Test (Below 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11g	1 to 11	11	OFDM	BPSK	6

Radiated Emission Test (Above 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

**Bandedge Measurement:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 11	DSSS	CCK	11
802.11g	1 to 11	1, 11	OFDM	BPSK	6

Antenna Port Conducted Measurement:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a 802.11g Wireless Broadband Router. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

ANSI C63.4- 2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP05L	12130898320	E2K24CLNS
1	NOTEBOOK COMPUTER	DELL	PP05L	12130898320	E2K24CLNS
2	PRINTER	EPSON	LQ-300+	DCGY047265	FCC DoC Approved
3	MODEM	ACEEX	1414V/3	0401008248	IFAXDM1414

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	NA
3	1.2m shielded cable without core.
4	1.2m shielded cable without core.

NOTE:

1. All power cords of the above support units are non shielded (1.8m).
2. Item 2 act as a communication partner to transfer data.

4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Dec. 11, 2004
RF signal cable Woken	5D-FB	Cable-HyC02-01	Mar. 07, 2005
LISN ROHDE & SCHWARZ	ESH2-Z5	100100	Mar. 10, 2005
LISN ROHDE & SCHWARZ	ESH3-Z5	100311	Mar. 04, 2005
Software ADT	ADT_Cond_V3	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 2.
 3. The VCCI Site Registration No. is C-2047.




4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels (Limit -20dB) was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

- a. Placed the EUT on the testing table.
- b. Prepared another Notebook system to act as a communication partner and placed it outside of testing area.
- c. The communication partner run a test program (provided by manufacturer) to enable EUT under transmission/receiving condition continuously at specific channel frequency via an RJ45 cable.
- d. The communication partner sent data to EUT by command "PING".

4.1.7 TEST RESULTS

Conducted Worst-Case Data

EUT	802.11g Wireless Broadband Router	MEASUREMENT DETAIL	
MODEL	WLG-2206	PHASE	Line 1
CHANNEL	Channel 1	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
ENVIRONMENTAL CONDITIONS	21 deg. C, 61% RH, 991 hPa	INPUT POWER (SYSTEM)	120 Vac, 60 Hz
TESTED BY	Long Chen		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.176	0.11	48.57	-	48.68	-	64.70	54.70	-16.01	-
2	0.232	0.12	42.37	-	42.49	-	62.37	52.37	-19.88	-
3	0.470	0.13	33.01	-	33.14	-	56.51	46.51	-23.37	-
4	2.515	0.17	40.78	-	40.95	-	56.00	46.00	-15.05	-
5	2.750	0.18	38.85	-	39.03	-	56.00	46.00	-16.97	-
6	23.066	1.11	30.69	-	31.80	-	60.00	50.00	-28.20	-

*(The test data is in accordance with ADT Report No.: RF931018L03.)

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.


2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.

3. The emission levels of other frequencies were very low against the limit.

4. Margin value = Emission level - Limit value

5. Correction factor = Insertion loss + Cable loss

6. Emission Level = Correction Factor + Reading Value.




EUT	802.11g Wireless Broadband Router	MEASUREMENT DETAIL	
MODEL	WLG-2206	PHASE	Line 2
CHANNEL	Channel 1	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
ENVIRONMENTAL CONDITIONS	21 deg. C, 61% RH, 991 hPa	INPUT POWER (SYSTEM)	120 Vac, 60 Hz
TESTED BY	Long Chen		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.175	0.11	46.12	-	46.23	-	64.70	54.70	-18.48	-
2	0.468	0.12	30.80	-	30.92	-	56.56	46.56	-25.64	-
3	1.878	0.16	33.19	-	33.35	-	56.00	46.00	-22.65	-
4	2.583	0.17	42.07	-	42.24	-	56.00	46.00	-13.76	-
5	6.166	0.25	25.49	-	25.74	-	60.00	50.00	-34.26	-
6	23.012	0.69	32.72	-	33.41	-	60.00	50.00	-26.59	-

*(The test data is in accordance with ADT Report No.: RF931018L03.)

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.




EUT	802.11g Wireless Broadband Router	MEASUREMENT DETAIL	
MODEL	WLG-2206	PHASE	Line 1
CHANNEL	Channel 6	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
ENVIRONMENTAL CONDITIONS	21 deg. C, 61% RH, 991 hPa	INPUT POWER (SYSTEM)	120 Vac, 60 Hz
TESTED BY	Long Chen		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.11	47.58	-	47.69	-	64.65	54.65	-16.96	-
2	0.237	0.12	41.38	-	41.50	-	62.19	52.19	-20.69	-
3	0.472	0.13	32.97	-	33.10	-	56.49	46.49	-23.39	-
4	2.589	0.17	41.90	-	42.07	-	56.00	46.00	-13.93	-
5	2.826	0.18	37.95	-	38.13	-	56.00	46.00	-17.87	-
6	22.144	1.08	30.19	-	31.27	-	60.00	50.00	-28.73	-

*(The test data is in accordance with ADT Report No.: RF931018L03.)

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.




EUT	802.11g Wireless Broadband Router	MEASUREMENT DETAIL	
MODEL	WLG-2206	PHASE	Line 2
CHANNEL	Channel 6	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
ENVIRONMENTAL CONDITIONS	21 deg. C, 61% RH, 991 hPa	INPUT POWER (SYSTEM)	120 Vac, 60 Hz
TESTED BY	Long Chen		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.11	45.25	-	45.36	-	64.64	54.64	-19.29	-
2	0.236	0.11	38.43	-	38.54	-	62.24	52.24	-23.70	-
3	1.711	0.16	32.83	-	32.99	-	56.00	46.00	-23.01	-
4	2.535	0.17	41.54	-	41.71	-	56.00	46.00	-14.29	-
5	5.305	0.23	20.66	-	20.89	-	60.00	50.00	-39.11	-
6	22.156	0.69	20.74	-	21.43	-	60.00	50.00	-38.57	-

*(The test data is in accordance with ADT Report No.: RF931018L03.)

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.




EUT	802.11g Wireless Broadband Router	MEASUREMENT DETAIL	
MODEL	WLG-2206	PHASE	Line 1
CHANNEL	Channel 11	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
ENVIRONMENTAL CONDITIONS	21 deg. C, 61% RH, 991 hPa	INPUT POWER (SYSTEM)	120 Vac, 60 Hz
TESTED BY	Long Chen		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.11	47.60	-	47.71	-	64.61	54.61	-16.90	-
2	0.237	0.12	40.82	-	40.94	-	62.21	52.21	-21.27	-
3	0.473	0.13	32.89	-	33.02	-	56.47	46.47	-23.45	-
4	1.953	0.16	34.74	-	34.90	-	56.00	46.00	-21.10	-
5	2.545	0.17	42.04	-	42.21	-	56.00	46.00	-13.79	-
6	22.456	1.09	29.70	-	30.79	-	60.00	50.00	-29.21	-

*(The test data is in accordance with ADT Report No.: RF931018L03.)

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	802.11g Wireless Broadband Router	MEASUREMENT DETAIL	
MODEL	WLG-2206	PHASE	Line 2
CHANNEL	Channel 11	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
ENVIRONMENTAL CONDITIONS	21 deg. C, 61% RH, 991 hPa	INPUT POWER (SYSTEM)	120 Vac, 60 Hz
TESTED BY	Long Chen		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.179	0.11	45.27	-	45.38	-	64.55	54.55	-19.18	-
2	0.474	0.12	30.04	-	30.16	-	56.44	46.44	-26.28	-
3	1.898	0.16	33.57	-	33.73	-	56.00	46.00	-22.27	-
4	2.547	0.17	42.32	-	42.49	-	56.00	46.00	-13.51	-
5	6.874	0.27	24.39	-	24.66	-	60.00	50.00	-35.34	-
6	21.926	0.69	32.67	-	33.36	-	60.00	50.00	-26.64	-

*(The test data is in accordance with ADT Report No.: RF931018L03.)

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.


2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.

3. The emission levels of other frequencies were very low against the limit.

4. Margin value = Emission level - Limit value

5. Correction factor = Insertion loss + Cable loss

6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESIB7	100188	Jan. 13, 2005
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Dec. 15, 2004
BILOG Antenna SCHWARZBECK	VULB9168	9168-157	Feb. 03, 2005
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-407	Feb. 03, 2005
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA 9170241	Feb. 23, 2005
Preamplifier Agilent	8449B	3008A01961	Jan. 22, 2005
Preamplifier Agilent	8447D	2944A10629	Jan. 14, 2005
RF signal cable HUBER+SUHNER	SUCOFLEX 104	218182/4	Mar. 04, 2005
RF signal cable HUBER+SUHNER	SUCOFLEX 104	218194/4	Mar. 04, 2005
Software ADT.	ADT_Radiated_V5.14	NA	NA
Antenna Tower ADT.	AT100	AT93021702	NA
Turn Table ADT.	TT100.	TT93021702	NA
Controller ADT.	SC100.	SC93021702	NA

- NOTE:** 1.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
- 2.The test was performed in HwaYa Chamber 1.
- 3.The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 4.The IC Site Registration No. is IC4924-2.

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

Below 1GHz Worst-Case Data

EUT	802.11g Wireless Broadband Router	MEASUREMENT DETAIL	
MODEL	WLG-2206	FREQUENCY RANGE	Below 1000MHz
CHANNEL	Channel 11	DETECTOR FUNCTION	Quasi-Peak
MODULATION TYPE	BPSK	INPUT POWER (SYSTEM)	120 Vac, 60Hz
ENVIRONMENTAL CONDITIONS	25 deg. C, 61% RH, 991 hPa	TESTED BY	Gary Chang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	249.66	42.74 QP	46.00	-3.26	1.00 H	331	29.32	13.41
2	300.20	34.58 QP	46.00	-11.42	1.00 H	262	19.77	14.81
3	319.64	34.37 QP	46.00	-11.63	1.00 H	232	19.15	15.22
4	374.07	34.63 QP	46.00	-11.37	1.00 H	229	18.24	16.39
5	500.42	35.26 QP	46.00	-10.74	1.50 H	67	16.54	18.72
6	640.38	34.69 QP	46.00	-11.31	2.50 H	214	12.89	21.81
7	799.78	37.21 QP	46.00	-8.79	2.00 H	214	13.44	23.77
8	961.12	38.34 QP	54.00	-15.66	1.50 H	163	12.47	25.87

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	199.12	31.48 QP	43.50	-12.02	1.00 V	310	19.95	11.53
2	249.66	37.77 QP	46.00	-8.23	1.00 V	1	24.36	13.41
3	319.64	32.67 QP	46.00	-13.33	1.50 V	343	17.45	15.22
4	348.80	31.37 QP	46.00	-14.63	1.50 V	352	15.54	15.83
5	449.88	30.86 QP	46.00	-15.14	1.00 V	349	12.75	18.11
6	479.04	35.16 QP	46.00	-10.84	1.00 V	310	16.70	18.46
7	640.38	33.31 QP	46.00	-12.69	1.50 V	307	11.51	21.81
8	799.78	37.18 QP	46.00	-8.82	1.00 V	7	13.41	23.77

*(The test data is in accordance with ADT Report No.: RF931018L03.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

802.11b DSSS modulation

EUT	802.11g Wireless Broadband Router	MEASUREMENT DETAIL	
MODEL	WLG-2206	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 1	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	CCK	INPUT POWER (SYSTEM)	120 Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1120.00	50.01 PK	74.00	-23.99	1.19 H	313	23.25	26.76
1	1120.00	48.09 AV	54.00	-5.91	1.19 H	313	21.33	26.76
2	2360.00	51.60 PK	74.00	-22.40	1.00 H	305	19.89	31.71
2	2360.00	43.34 AV	54.00	-10.66	1.00 H	305	11.63	31.71
3	2390.00	52.39 PK	74.00	-21.61	1.00 H	314	20.59	31.80
3	2390.00	44.65 AV	54.00	-9.35	1.00 H	314	12.85	31.80
4	*2412.00	108.15 PK			1.00 H	314	76.28	31.87
4	*2412.00	100.04 AV			1.00 H	314	68.17	31.87
5	4824.00	60.59 PK	74.00	-13.41	1.00 H	149	22.48	38.11
5	4824.00	48.91 AV	54.00	-5.09	1.00 H	149	10.80	38.11

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1600.00	50.06 PK	74.00	-23.94	1.11 V	340	21.43	28.63
1	16000.00	47.55 AV	54.00	-6.45	1.11 V	340	18.92	28.63
2	1920.00	49.90 PK	74.00	-24.10	1.22 V	336	19.75	30.15
2	1920.00	46.97 AV	54.00	-7.03	1.22 V	336	16.82	30.15
3	2360.00	53.02 PK	74.00	-20.98	1.08 V	250	21.31	31.71
3	2360.00	44.82 AV	54.00	-9.18	1.08 V	250	13.11	31.71
4	2390.00	55.71 PK	74.00	-18.29	1.08 V	193	23.91	31.80
4	2390.00	46.00 AV	54.00	-8.00	1.08 V	193	14.20	31.80
5	*2412.00	111.10 PK			1.08 V	193	79.23	31.87
5	*2412.00	103.43 AV			1.08 V	193	71.56	31.87
6	4824.00	63.21 PK	74.00	-10.79	1.06 V	309	25.10	38.11
6	4824.00	51.34 AV	54.00	-2.66	1.06 V	309	13.23	38.11

*(The test data is in accordance with ADT Report No.: RF931018L03.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT	802.11g Wireless Broadband Router	MEASUREMENT DETAIL	
MODEL	WLG-2206	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 6	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	CCK	INPUT POWER (SYSTEM)	120 Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1120.00	48.62 PK	74.00	-25.38	1.18 H	25	21.86	26.76
1	1120.00	46.75 AV	54.00	-7.25	1.18 H	25	19.99	26.76
2	2360.00	52.97 PK	74.00	-21.03	1.00 H	299	21.26	31.71
2	2360.00	43.93 AV	54.00	-10.07	1.00 H	299	12.22	31.71
3	*2437.00	107.80 PK			1.04 H	185	75.85	31.95
3	*2437.00	99.80 AV			1.04 H	185	67.85	31.95
4	4874.00	60.64 PK	74.00	-13.36	1.00 H	160	22.36	38.28
4	4874.00	48.56 AV	54.00	-5.44	1.00 H	160	10.28	38.28

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1120.00	48.54 PK	74.00	-25.46	1.25 V	334	21.78	26.76
1	1120.00	46.32 AV	54.00	-7.68	1.25 V	334	19.56	26.76
2	1920.00	48.64 PK	74.00	-25.36	1.16 V	7	18.49	30.15
2	1920.00	45.64 AV	54.00	-8.36	1.16 V	7	15.49	30.15
3	2360.00	53.53 PK	74.00	-20.47	1.05 V	277	21.82	31.71
3	2360.00	45.15 AV	54.00	-8.85	1.05 V	277	13.44	31.71
4	*2437.00	112.70 PK			1.08 V	249	80.75	31.95
4	*2437.00	104.80 AV			1.08 V	249	72.85	31.95
5	4874.00	64.17 PK	74.00	-9.83	1.28 V	360	25.89	38.28
5	4874.00	52.43 AV	54.00	-1.57	1.28 V	360	14.15	38.28

*(The test data is in accordance with ADT Report No.: RF931018L03.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT	802.11g Wireless Broadband Router	MEASUREMENT DETAIL	
MODEL	WLG-2206	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 11	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	CCK	INPUT POWER (SYSTEM)	120 Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1120.00	49.88 PK	74.00	-24.12	1.21 H	314	23.12	26.76
1	1120.00	48.28 AV	54.00	-5.72	1.21 H	314	21.52	26.76
2	2360.00	53.07 PK	74.00	-20.93	1.00 H	304	21.36	31.71
2	2360.00	43.77 AV	54.00	-10.23	1.00 H	304	12.06	31.71
3	*2462.00	107.10 PK			1.28 H	58	75.08	32.02
3	*2462.00	99.40 AV			1.28 H	58	67.38	32.02
4	2483.50	50.77 PK	74.00	-23.23	1.28 H	58	18.68	32.09
4	2483.50	43.07 AV	54.00	-10.93	1.28 H	58	10.98	32.09
5	4924.00	56.41 PK	74.00	-17.59	1.08 H	61	17.92	38.49
5	4924.00	43.87 AV	54.00	-10.13	1.08 H	61	5.38	38.49

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1600.00	49.90 PK	74.00	-24.10	1.07 V	313	21.27	28.63
1	1600.00	47.34 AV	54.00	-6.66	1.07 V	313	18.71	28.63
2	1920.00	49.48 PK	74.00	-24.52	1.22 V	8	19.33	30.15
2	1920.00	46.83 AV	54.00	-7.17	1.22 V	8	16.68	30.15
3	2360.00	52.63 PK	74.00	-21.37	1.24 V	360	20.92	31.71
3	2360.00	44.36 AV	54.00	-9.64	1.24 V	360	12.65	31.71
4	*2462.00	112.46 PK			1.04 V	47	80.44	32.02
4	*2462.00	104.62 AV			1.04 V	47	72.60	32.02
5	2483.50	56.13 PK	74.00	-17.87	1.04 V	47	24.04	32.09
5	2483.50	46.49 AV	54.00	-7.51	1.04 V	47	14.40	32.09
6	4924.00	59.86 PK	74.00	-14.14	1.13 V	262	21.37	38.49
6	4924.00	48.34 AV	54.00	-5.66	1.13 V	262	9.85	38.49

*(The test data is in accordance with ADT Report No.: RF931018L03.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

802.11b OFDM modulation

EUT	802.11g Wireless Broadband Router	MEASUREMENT DETAIL	
MODEL	WLG-2206	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 1	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	BPSK	INPUT POWER (SYSTEM)	120 Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1120.00	50.25 PK	74.00	-23.75	1.08 H	250	23.49	26.76
1	1120.00	48.20 AV	54.00	-5.80	1.08 H	250	21.44	26.76
2	2360.00	54.21 PK	74.00	-19.79	1.00 H	305	22.50	31.71
2	2360.00	45.16 AV	54.00	-8.84	1.00 H	305	13.45	31.71
3	2390.00	58.09 PK	74.00	-15.91	1.00 H	315	26.29	31.80
3	2390.00	48.74 AV	54.00	-5.26	1.00 H	315	16.94	31.80
4	*2412.00	104.71 PK			1.00 H	315	72.84	31.87
4	*2412.00	95.36 AV			1.00 H	315	63.49	31.87
5	4824.00	58.84 PK	74.00	-15.16	1.08 H	250	20.73	38.11
5	4824.00	44.19 AV	54.00	-9.81	1.08 H	250	6.08	38.11

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1600.00	50.75 PK	74.00	-23.25	1.00 V	13	22.12	28.63
1	1600.00	48.66 AV	54.00	-5.34	1.00 V	13	20.03	28.63
2	1920.00	48.86 PK	74.00	-25.14	1.21 V	335	18.71	30.15
1	1920.00	45.75 AV	54.00	-8.25	1.21 V	335	15.60	30.15
3	2360.00	54.85 PK	74.00	-19.15	1.13 V	178	23.14	31.71
3	2360.00	47.03 AV	54.00	-6.97	1.13 V	178	15.32	31.71
4	2390.00	62.02 PK	74.00	-11.98	1.16 V	344	30.22	31.80
4	2390.00	52.72 AV	54.00	-1.28	1.16 V	344	20.92	31.80
5	*2412.00	108.64 PK			1.16 V	344	76.77	31.87
5	*2412.00	99.34 AV			1.16 V	344	67.47	31.87
6	4824.00	61.37 PK	74.00	-12.63	1.06 V	43	23.26	38.11
6	4824.00	49.14 AV	54.00	-4.86	1.06 V	43	11.03	38.11

*(The test data is in accordance with ADT Report No.: RF931018L03.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

5. “ * “ : Fundamental frequency

EUT	802.11g Wireless Broadband Router	MEASUREMENT DETAIL	
MODEL	WLG-2206	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 6	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	BPSK	INPUT POWER (SYSTEM)	120 Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1120.00	49.45 PK	74.00	-24.55	1.18 H	24	22.69	26.76
1	1120.00	47.45 AV	54.00	-6.55	1.18 H	24	20.69	26.76
2	2360.00	53.43 PK	74.00	-20.57	1.00 H	296	21.72	31.71
2	2360.00	45.21 AV	54.00	-8.79	1.00 H	296	13.50	31.71
3	*2437.00	104.55 PK			1.25 H	298	72.60	31.95
3	*2437.00	95.12 AV			1.25 H	298	63.17	31.95
4	4874.00	58.99 PK	74.00	-15.01	1.24 H	157	20.71	38.28
4	4874.00	45.94 AV	54.00	-8.06	1.24 H	157	7.66	38.28

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1600.00	50.37 PK	74.00	-23.63	1.08 V	357	21.74	28.63
1	1600.00	48.12 AV	54.00	-5.88	1.08 V	357	19.49	28.63
2	1920.00	48.65 PK	74.00	-25.35	1.15 V	6	18.50	30.15
2	1920.00	45.56 AV	54.00	-8.44	1.15 V	6	15.41	30.15
3	2360.00	54.25 PK	74.00	-19.75	1.06 V	276	22.54	31.71
3	2360.00	46.59 AV	54.00	-7.41	1.06 V	276	14.88	31.71
4	*2437.00	109.72 PK			1.06 V	248	77.77	31.95
4	*2437.00	99.82 AV			1.06 V	248	67.87	31.95
5	2520.00	55.83 PK	74.00	-18.17	1.00 V	246	23.62	32.21
5	2520.00	50.66 AV	54.00	-3.34	1.00 V	246	18.45	32.21
6	4874.00	61.76 PK	74.00	-12.24	1.03 V	37	23.48	38.28
6	4874.00	48.91 AV	54.00	-5.09	1.03 V	37	10.63	38.28

*(The test data is in accordance with ADT Report No.: RF931018L03.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency

EUT	802.11g Wireless Broadband Router	MEASUREMENT DETAIL	
MODEL	WLG-2206	FREQUENCY RANGE	1~25 GHz
CHANNEL	Channel 11	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	BPSK	INPUT POWER (SYSTEM)	120 Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1120.00	50.07 PK	74.00	-23.93	1.18 H	313	23.31	26.76
1	1120.00	48.03 AV	54.00	-5.97	1.18 H	313	21.27	26.76
2	2360.00	52.83 PK	74.00	-21.17	1.00 H	306	21.12	31.71
2	2360.00	44.72 AV	54.00	-9.28	1.00 H	306	13.01	31.71
3	*2462.00	103.09 PK			1.01 H	21	71.07	32.02
3	*2462.00	93.75 AV			1.01 H	21	61.73	32.02
4	2483.50	55.39 PK	74.00	-18.61	1.01 H	21	23.30	32.09
4	2483.50	46.05 AV	54.00	-7.95	1.01 H	21	13.96	32.09
5	4924.00	55.04 PK	74.00	-18.96	1.06 H	68	16.55	38.49
5	4924.00	41.62 AV	54.00	-12.38	1.06 H	68	3.13	38.49

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1600.00	51.11 PK	74.00	-22.89	1.01 V	11	22.48	28.63
1	1600.00	48.87 AV	54.00	-5.13	1.01 V	11	20.24	28.63
2	1920.00	49.33 PK	74.00	-24.67	1.21 V	346	19.18	30.15
2	1920.00	46.14 AV	54.00	-7.86	1.21 V	346	15.99	30.15
3	2360.00	53.90 PK	74.00	-20.10	1.28 V	348	22.19	31.71
3	2360.00	45.63 AV	54.00	-8.37	1.28 V	348	13.92	31.71
4	*2462.00	109.77 PK			1.06 V	202	77.75	32.02
4	*2462.00	100.33 AV			1.06 V	202	68.31	32.02
5	2483.50	62.07 PK	74.00	-11.93	1.06 V	202	29.98	32.09
5	2483.50	52.63 AV	54.00	-1.37	1.06 V	202	20.54	32.09
6	4924.00	56.76 PK	74.00	-17.24	1.04 V	334	18.27	38.49
6	4924.00	43.79 AV	54.00	-10.21	1.04 V	334	5.30	38.49

*(The test data is in accordance with ADT Report No.: RF931018L03.)

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

5. “ * “ : Fundamental frequency

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS


802.11b DSSS modulation

EUT	802.11g Wireless Broadband Router	MODEL	WLG-2206
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23 deg. C, 67% RH, 991 hPa
TESTED BY	Leo Hung		


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	9.58	0.5	PASS
6	2437	9.93	0.5	PASS
11	2462	9.86	0.5	PASS

*(The test data is in accordance with ADT Report No.: RF931018L03.)


CH1



CH6



CH11





**802.11g OFDM modulation**


EUT	802.11g Wireless Broadband Router	MODEL	WLG-2206
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23 deg. C, 67% RH, 991 hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	16.59	0.5	PASS
6	2437	16.55	0.5	PASS
11	2462	16.59	0.5	PASS

*(The test data is in accordance with ADT Report No.: RF931018L03.)

CH1**CH6**

CH11



4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005
AGILENT SIGNAL GENERATOR	E8257C	MY43320668	Dec. 31, 2004
TEKTRONIX OSCILLOSCOPE	TDS 220	C019167	Feb. 1, 2005
NARDA DETECTOR	4503A	FSCM99899	NA

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G. was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same reading on oscilloscope. Record the power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

4.4.7 TEST RESULTS

802.11b DSSS modulation

EUT	802.11g Wireless Broadband Router	MODEL	WLG-2206
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23 deg. C, 67% RH, 991 hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	56.23	17.50	30	PASS
6	2437	56.49	17.52	30	PASS
11	2462	56.36	17.51	30	PASS

*(The test data is in accordance with ADT Report No.: RF931018L03.)

802.11g OFDM modulation

EUT	802.11g Wireless Broadband Router	MODEL	WLG-2206
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23 deg. C, 67% RH, 991 hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	40.74	16.10	30	PASS
6	2437	39.81	16.00	30	PASS
11	2462	35.48	15.50	30	PASS

*(The test data is in accordance with ADT Report No.: RF931018L03.)

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITIONS

Same as 4.3.6

4.5.7 TEST RESULTS


802.11b DSSS modulation

EUT	802.11g Wireless Broadband Router	MODEL	WLG-2206
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23 deg. C, 67% RH, 991 hPa
TESTED BY	Leo Hung		


CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-9.01	8	PASS
6	2437	-9.18	8	PASS
11	2462	-9.01	8	PASS

*(The test data is in accordance with ADT Report No.: RF931018L03.)


CH1



CH6



CH11




802.11g OFDM modulation

EUT	802.11g Wireless Broadband Router	MODEL	WLG-2206
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23 deg. C, 67% RH, 991 hPa
TESTED BY	Leo Hung		


CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-16.96	8	PASS
6	2437	-16.72	8	PASS
11	2462	-17.11	8	PASS

*(The test data is in accordance with ADT Report No.: RF931018L03.)


CH1



CH6



CH11



4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span including 100MHz bandwidth from band edge. The band edges was measured and recorded. The spectrum plots (Peak RBW=VBW=100kHz; Average RBW=1MHz, VBW=10Hz) are attached on the following pages.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.6 TEST RESULTS

The spectrum plots are attached on the following 8 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

802.11b DSSS modulation

NOTE 1: The band edge emission plot of DSSS technique on page 53 shows 56.03dBc between carrier maximum power and local maximum emission in restrict band (2.3599GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 111.10dBuV/m (Peak), so the maximum field strength in restrict band is $111.10 - 56.03 = 55.07$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of DSSS technique on page 53 shows 57.86dBc between carrier maximum power and local maximum emission in restrict band (2.3601GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 103.43dBuV/m (Average), so the maximum field strength in restrict band is $103.43 - 57.86 = 45.57$ dBuV/m which is under 54dBuV/m limit.

*(The test data is in accordance with ADT Report No.: RF931018L03.)

NOTE 2: The band edge emission plot of DSSS technique on page 54 shows 56.22dBc between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 112.46dBuV/m (Peak), so the maximum field strength in restrict band is $112.46 - 56.22 = 56.24$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of DSSS technique on page 55 shows 58.56dBc between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 104.62dBuV/m (Average), so the maximum field strength in restrict band is $104.62 - 58.56 = 46.06$ dBuV/m which is under 54dBuV/m limit.

*(The test data is in accordance with ADT Report No.: RF931018L03.)

802.11g OFDM modulation

NOTE 1: The band edge emission plot of OFDM technique on page 56 shows 41.90dBc between carrier maximum power and local maximum emission in restrict band (2.3889GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 108.64dBuV/m (Peak), so the maximum field strength in restrict band is $108.64 - 41.90 = 66.74$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of OFDM technique on page 56 shows 49.05dBc between carrier maximum power and local maximum emission in restrict band (2.3898GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 99.34dBuV/m (Average), so the maximum field strength in restrict band is $99.34 - 49.05 = 50.29$ dBuV/m which is under 54dBuV/m limit.



*(The test data is in accordance with ADT Report No.: RF931018L03.)







NOTE 2: The band edge emission plot of OFDM technique on page 57 shows 43.03dBc between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 109.77dBuV/m (Peak), so the maximum field strength in restrict band is $109.77 - 43.03 = 66.74$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot of OFDM technique on page 58 shows 48.99dBc between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 100.33dBuV/m (Average), so the maximum field strength in restrict band is $100.33 - 48.99 = 51.33$ dBuV/m which is under 54dBuV/m limit.



*(The test data is in accordance with ADT Report No.: RF931018L03.)



802.11b DSSS modulation





802.11g OFDM modulation







4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION



The antenna used in this product is Dipole antenna with RSMA connector. And the maximum Gain of this antenna is 2dBi.

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST



RADIATED EMISSION TEST



6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

USA	FCC, NVLAP, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180
Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232
Fax: 886-3-3185050

Linko RF Lab.

Tel: 886-3-3270910
Fax: 886-3-3270892

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.