
TEST REPORT

Report No.: SRTC2020-9003(F)-0004
Product Name: Smartphone
Model Name: HLTE229E
Marketing Name: Hisense E40
Applicant: Hisense International Co., Ltd.
Manufacturer: Hisense Communications Co., Ltd.
Specification: FCC Part15B (Certification)
(2020 edition)
FCC ID: 2ADOBHLTE229E

The State Radio_monitoring_center Testing Center (SRTC)
15th Building, No.30 Shixing Street, Shijingshan District,
Beijing, China

Tel: 86-10-57996183 Fax: 86-10-57996388

CONTENTS

1. General information	3
1.1 Notes of the test report	3
1.2 Information about the testing laboratory	3
1.3 Applicant's details	3
1.4 Manufacturer's details	3
1.5 Application details	4
1.6 Reference specification	4
1.7 Information of EUT	4
1.7.1 General information	4
1.7.2 EUT details	5
1.7.3 Auxiliary equipment details	5
2. Test information	6
2.1 Summary of the test results	7
2.2 Test result	8
2.2.1 Conducted Emissions-FCC Part15.107	8
2.2.2 Radiated Emissions-FCC Part15.109	13
2.3. List of test equipments	21

1. General information

1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio_monitoring_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested.

1.2 Information about the testing laboratory

Company: The State Radio_monitoring_center Testing Center (SRTC)
Address: 15th Building, No.30 Shixing Street, Shijingshan District
Testing location: No.80, Zhaojiachang, BeizangCun, Daxing District, Beijing, China.
City: Beijing
Country or Region: China
Contacted person: Liu Jia
Tel: +86 10 57996183
Fax: +86 10 57996388
Email: liujiaf@srtc.org.cn

1.3 Applicant's details

Company: Hisense International Co., Ltd.
Address: Floor 22, Hisense Tower, 17 Donghai Xi Road, Qingdao, 266071, China
City: Qingdao
Country or Region: China
Contacted person: Geng Ruifeng
Tel: +86-532-80877742
Email: gengruifeng@hisense.com

1.4 Manufacturer's details

Company: Hisense Communications Co., Ltd.
Address: No.218 Qianwangang Road, Economic & Technological Development Zone, Qingdao, China
City: Qingdao
Country or Region: China
Contacted person: Deng Tingting
Tel: +86-532-55753708
Email: dengtingting@hisense.com

1.5 Application details

Date of reception of test sample: 2nd Mar. 2020

Date of test: 2nd Mar. 2020 to 20th Mar. 2020

1.6 Reference specification

FCC Part 15B, 2020 (Certification)

1.7 Information of EUT

1.7.1 General information

Name of EUT	Smartphone
Model Name	HLTE229E
FCC ID	2ADOBHLTE229E
Frequency Range	GSM: GSM850/PCS1900 WCDMA: FDD II / FDD IV / FDD V LTE:FDD 2/ FDD 4/ FDD 5/ FDD 7/FDD 12 Bluetooth: 2.4~2.4835GHz WiFi: 2.4~2.4835GHz
Equipment Class	Class B
Power Supply	Battery or Charger
Rated Power Supply Voltage	3.8V
Extreme Temperature	Lowest: 0°C Highest: +55°C
Extreme Voltage	Minimum: 3.5V Maximum: 4.35V
HW Version	V0.1
SW Version	Hisense_HLTE229E_10_S02_03

1.7.2EUT details

Product Name	Model Name	IMEI
Smartphone	HLTE229E	867400020316612

1.7.3 Auxiliary equipment details

AE (Auxiliary Equipment) 1#: Laptop

Manufacturer	Lenovo
Model Number	E40-70
S/N	MP06WE9U
Input Voltage	100V-240V AC

AE (Auxiliary Equipment) 2#: USB Cable

Manufacturer	kelinDongguan Keling Electronic Technology Co., Ltd
Model Number	KS230B

AE (Auxiliary Equipment)3#: Battery1

Type	Li-Lon
Manufacturer	ShenzhenAerospaceElectronicCo.,Ltd
Model Number	LPN385400A
Capacity	4000mAh
Nominal Voltage	3.85V

AE (Auxiliary Equipment) 4#: Battery2

Type	Li-Lon
Manufacturer	Shenzhen Tianjin New Energy Technology Co., Ltd.
Model Number	LPN385400A
Capacity	4000mAh
Nominal Voltage	3.85V

AE (Auxiliary Equipment) 5#: Charger

Manufacturer	SHENZHENTIANYIN ELECTRONICS CO., LTD.
Model Number	TPA-46050200UU
S/N	/

Input Voltage	100V-240VAC 0.3A
Output Voltage	5.0VDC 2000mA

AE (Auxiliary Equipment) 6#: Headset



Manufacturer	kelinDongguan Keling Electronic Technology Co., Ltd
Model Number	KS230B

Note1: As the information described in these above tables, the relevant tests have been performed in order to verify in which supply would have the worst features. When the EUT exercised with 2# USB Cable, 3# Battery, 5# Charger, 6# Headset, is the worst feature, and record the results in the test report.

2. Test information

2.1 Summary of the test results

No.	Test case	FCC reference	Verdict
1	Conducted emissions	15.107	Pass
2	Radiated emissions	15.109	Pass

Approved By:Mr. Liu Wei Director of the test department 	Checked By:Mr. Guo Yu Vice director of the test department 
Tested by: Mr. Liu Jian Test engineer 	Issued date: 2020.03.18

2.2 Test result

2.2.1 Conducted Emissions-FCC Part15.107

Ambient condition:

Temperature	Relative humidity	Pressure
24.4°C	38.9%	100.8kPa

Test Setup with laptop:




Figure 1

Test Procedure:

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The accessories of the EUT are connected with the EUT such as headset etc. The EUT was connected with a laptop via the USB cable and transferred the data by copying large files from laptop to the EUT. The laptop's LAN port is connected with another laptop via cable. And the data transferring between two laptops is maintained.

The AC main power supply of the laptop is connected to LISN and LISN is connected to the reference ground. The test set-up and the test methods are performed according to ANSI C63.4:2014.

Then start the test software EMC32. Sweep the whole frequency band through the range from 150 KHz to 30 MHz with RBW 9kHz, VBW 30kHz. The measurement should be done for both L line and N line. During pre-test, the receiver uses both peak detector and average detector. And the final test, the receiver uses both average detector and Quasi-peak detector.

The data of cable loss has been calibrated in full testing frequency range before the testing.

Test Setup with charger:




Figure 2

Test Procedure:

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The EUT is connected with LISN via the charger. The LISN is connected to the reference ground. The accessories of the EUT are connected with the EUT such as headset etc. Open the following functions of EUT: Camera, flash lamp, FM, GPS and video.

The test set-up and the test methods are performed according to ANSI C63.4:2014. Then start the test software EMC32. Sweep the whole frequency band through the range from 150 KHz to 30 MHz with RBW 9kHz, VBW 30kHz. The measurement should be done for both L line and N line. During pre-test, the receiver uses both peak detector and average detector. And the final test, the receiver uses both average detector and Quasi-peak detector.

The data of cable loss has been calibrated in full testing frequency range before the testing.

A "reference path loss" Corr.(dB) is established and the $L_{\text{cable}} + \text{ATT} + \text{VDF}$ is the attenuation of "reference path loss", and including the cable loss, the attenuation of the attenuator, the voltage division factor of AMN.

The measurement results are obtained as described below:

$$P_{\text{result}} = P_{\text{mea}} + \text{Corr.}(\text{dB})$$

Sample calculation: $(30.77\text{dB}\mu\text{V}) = (1.07\text{dB}\mu\text{V}) + (29.7\text{dB})$, the corresponding frequency is 0.188379MHz.


Limit:

Frequency of Emission(MHz)	Limits(dBμV)	
	Quasi-peak	Average
0.15~0.5	66 to 56*	56 to 46*
0.5~5	56	46
5~30	60	50

Note: * Decreases with the logarithm of the frequency


Test result:

Noise Level of the Measuring Instrument



Pic1. Conducted emission L and N Line


EUT + Charger:



Pic2. Conducted emission L&N Line

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dB μV)	Margin (dB)	Line	Corr. (dB)	Pmea QuasiPeak (dBμV)	Pmea Average (dBμV)
0.18837	---	30.77	54.1	23.34	L1	29.7	---	1.07
0.24807	50.52	---	61.8	11.30	L1	29.7	20.82	---
0.28645	---	27.87	50.6	22.76	L1	29.7	---	-1.83
0.28645	48.20	---	60.6	12.43	L1	29.7	18.5	---
0.44850	37.00	---	56.9	19.91	N	29.7	7.3	---
0.60627	---	23.84	46.0	22.16	L1	29.7	---	-5.86
0.86640	---	23.71	46.0	22.29	L1	29.7	---	-5.99
13.7274	31.67	---	60.0	28.33	N	29.9	1.77	---

EUT + Laptop:



Pic3. Conducted emission L&N Line

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)	Pme a Quas	Pme a Aver
0.171321	37.48	---	64.90	27.42	L1	29.7	7.78	---
0.563636	---	25.94	46.00	20.06	L1	29.7	---	-3.76
4.772486	---	24.89	46.00	21.11	L1	29.8	---	-4.91
4.772486	25.96	---	56.00	30.04	N	29.8	-3.84	---
14.337279	---	34.89	50.00	15.11	L1	29.9	---	4.99
17.092007	32.03	---	60.00	27.97	L1	30.0	2.03	---
18.430993	---	39.96	50.00	10.04	L1	30.0	---	9.96
23.646214	36.03	---	60.00	23.97	L1	29.9	6.13	---

2.2.2 Radiated Emissions-FCC Part15.109

Ambient condition:

Temperature	Relative humidity	Pressure
24.4°C	38.9%	100.8kPa

Test Setup:




Figure 3

Test Procedure:

EUT+Laptop:

The EUT should be placed on a non-metallic table 80cm above the ground plane. The receive antennas shall be moved from 1 to 4 meters. The distance between EUT and receive antenna should be 3 meters.

The accessories of the EUT are connected with the EUT such as headset etc. The EUT was connected with a laptop via the USB cable and transferred the data by copying large files from laptop to the EUT. The test set-up and the test methods are performed according to ANSI C63.4:2014

Then start the test software EMC32. Sweep the whole frequency band through the range from 30MHz to 1GHz, using receive log period antenna VULB 9163.

During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with orthogonal polarization of the test antenna. The EUT is laid in two modes as follow:
1. put the EUT in horizontal direction; 2. put the EUT in vertical direction.

The data of cable loss and antenna factor have been calibrated in full testing frequency range before the testing.

EUT + Charger:

The EUT should be placed on a non-metallic table 80cm above the ground plane. The receive antennas shall be moved from 1 to 4 meters. The distance between EUT and receive antenna should be 3 meters.

The EUT should work in idle mode. The accessories of the EUT are connected with the EUT such as headset etc. Open the following functions of EUT: Camera, flash lamp, FM, GPS and video. The test set-up and the test methods are performed according to ANSI C63.4:2014.

Then start the test software EMC32. Sweep the whole frequency band through the range from 30MHz to 1GHz, using receive log period antenna VULB 9163.

During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with orthogonal polarization of the test antenna. The EUT is laid in two modes as follow: 1. put the EUT in horizontal direction; 2. put the EUT in vertical direction.

The data of cable loss and antenna factor have been calibrated in full testing frequency range before the testing. All test results are performed with max hold at the horizontal and vertical polarity.

RBW=120kHz, VBW=300kHz, when the test frequency: 30MHz<f<1GHz

RBW=1MHz, VBW=3MHz, when the test frequency: f>1GHz

A “reference path loss” is established and the A_{Rpl} is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{mea}} + A_{Rpl}$$

Limit:

Frequency of Emission(MHz)	Limits	
	Detector	Unit (dBμV/m)
30~88	Quasi-peak	40
88~216	Quasi-peak	43.5
216~960	Quasi-peak	46
960~1000	Quasi-peak	54
1000~5th harmonic of the highest frequency or 40GHz, whichever is lower	Average	54
	Peak	74

Test result:

Sample calculation: $(12.2\text{dB}\mu\text{V/m}) = (30.4\text{dB}\mu\text{V/m}) + (-18.2\text{dB})$, the corresponding frequency is 58.3725MHz.

EUT + Laptop:


Frequency(MHz)	Result(dB μ V/m)	Limit (dB μ V/m)	ARpl (dB)	Pmea (dB μ V/m)	Polarity
58.3725	12.2	40.00	-18.2	30.4	V
168.128	15.61	43.50	-20.8	36.41	V
197.1795	17.34	43.50	-18.5	35.84	V
295.9255	17.6	46.00	-15.2	32.8	V
396.3205	25.92	46.00	-11.9	37.82	V
799.4525	26.03	46.00	-3.4	29.43	V

EUT + Charger:

Frequency(MHz)	Result(dB μ V/m)	Limit (dB μ V/m)	ARpl (dB)	Pmea (dB μ V/m)	Polarity
32.048500	15.26	40.00	-20.6	35.86	V
84.192000	20.98	40.00	-22.5	43.48	V
109.996500	16.53	43.50	-19.6	36.13	V
306.687000	9.31	46.00	-14.9	24.21	V
439.990500	16.67	46.00	-10.7	27.37	V
945.563000	20.98	46.00	-0.9	21.88	V

EUT + Laptop: refer to Pic4, Pic5, Pic6, Pic7


Full Spectrum



Pic4. Radiated emission(30MHz – 1GHz)


Note : The test data in the graph includes two polarizations: horizontal and vertical

Full Spectrum




Pic5. Radiated emission (1GHz –6GHz)

Note : The test data in the graph includes two polarizations: horizontal and vertical.



Pic6. Radiated emission (6GHz –18GHz)

Note : The test data in the graph includes two polarizations: horizontal and vertical.




Pic7. Radiated emission (18GHz – 26GHz)

Note : The test data in the graph includes two polarizations: horizontal and vertical.

EUT + Charger: refer to Pic8, Pic9, Pic10, Pic11


Full Spectrum



Pic8. Radiated emission(30MHz – 1GHz)


Note : The test data in the graph includes two polarizations: horizontal and vertical

Full Spectrum




Pic9. Radiated emission (1GHz –6GHz)

Note : The test data in the graph includes two polarizations: horizontal and vertical.



Pic10. Radiated emission (6GHz –18GHz)

Note : The test data in the graph includes two polarizations: horizontal and vertical.



Pic11. Radiated emission (18GHz – 26GHz)

Note : The test data in the graph includes two polarizations: horizontal and vertical.

2.3. List of test equipments

No.	Name/Model	Manufacturer	S/N	Calibration Due Date	Calibration Date
1	23.18m×16.88m×9.60mS emi-AnechoicChamber	FRANKONIA	-----	5th Sep. 2021	6th Sep. 2016
2	ESW EMI test receiver	R&S	101574	20th Aug. 2020	20th Aug. 2019
3	9.080m×5.255m×3.525m Shielding room	FRANKONIA	-----	5th Sep. 2021	6th Sep. 2016
4	ESR3EMI test receiver	R&S	102361	20th Aug. 2020	20th Aug. 2019
5	VULB 9163 Ultra log test antenna	Schwarzbeck	867	20th Aug. 2020	20th Aug. 2019
6	ENV216 AMN	R&S	3560.6550. 12	20th Aug. 2020	20th Aug. 2019
7	HF 907 Double-Ridged Waveguide Horn Antenna	R&S	100512	20th Aug. 2020	20th Aug. 2019
8	PS2000 Turn Table	FRANKONIA	-----	-----	-----
9	MA260 Antenna Master	FRANKONIA	-----	-----	-----
10	EMC32EMI test software	R&S	-----	-----	-----