

AD-302N

Antenna Approval Sheet

Part Number	R3410110221
Product Number	AD-302N
Description	3dBi/2dBi 2.4G/5GHz Dipole RP-SMA
DOC NO.	AS-1809001

Ver 1.6

Revised History

Version	Purpose	Date	Editor
V1.0	Initial	09/18/2018	Aaron
V1.1	Revised Page6 Pic and Page 8 Gain table	02/15/2019	Kamoro
V1.2	Replaced Page 6 picture	08/16/2019	Kamoro
V1.3	Added Packing Info.	01/03/2020	Kamoro
V1.4	Added Packing Info.	03/19/2020	Kamoro
V1.5	Revised Packing Info.	06/05/2020	Kamoro
V1.6	Revised Specification / Frequency (Page 3)	08/28/2020	Kamoro

SparkLAN		Customer
Sales	PM	Approved by
	Aaron	

Index


1. Features.....	3
2. Specification	3
3. Mechanical Dimensions	3
4. Antenna Testing System	4
5. Antenna under testing	5
6. Antenna Placement.....	6
7. ANT S-Parameter, VSWR & Smith Chart	7
8. Gain Table	8
9. Ant 2.4G 2D&3D Gain pattern.....	9
10. Ant 5G 2D&3D Gain pattern	11
11. Packing information	13

Features


- Dual band IEEE 802.11 a/b/g/n/ac standard
- High efficiency
- Quick integration

Specification

Frequency (MHz)	2400 - 2483	5150 - 5825
Peak Gain (dBi)	3.0 ± 0.5	2.0 ± 1
VSWR	≤ 2.0	≤ 2.0
Power (Watts)	1	1
Impedance (Ohms)	50	50
Dimension (mm)	109 x $\varnothing 7.9$	
Weight (g)	9.5 ± 2 g	
Connector	SMA Male RP	
Polarization	Liner ; Vertical	
Operating Temp (°C)	$-20^{\circ}\text{C} \sim +60^{\circ}\text{C}$	




2.45GHz




5GHz

Mechanical Dimensions



Antenna Testing System




Antenna under testing



Antenna Placement




Ant S-Parameter, VSWR & Smith Chart




Gain Table

Ant												
Frequency (MHz)	2400	2450	2500	5150	5250	5350	5450	5550	5650	5725	5775	5825
Efficiency (dB)	-1.66	-1.24	-1.22	-1.86	-1.52	-1.51	-1.63	-2.13	-2.14	-2.08	-2.17	-2.19
Peak Gain (dBi)	2.89	3.14	2.95	2.5	2.74	2.67	2.87	2.73	2.56	2.35	2.27	1.63
Efficiency (%)	68.24	75.09	75.56	65.16	70.48	70.68	68.67	61.21	61.07	61.9	60.64	60.41


Ant 2.4G 3D Gain pattern




Ant 2.4G 2D Gain pattern



X-Y




X-Z




Y-Z


Ant 5G 3D Gain pattern




Ant 5G 2D Gain pattern



X-Y



X-Z



Y-Z

包裝規範書

產品名稱	AD-302N	客戶名稱		產品名稱	
產品料號	R3410110221	客戶料號		製作日期	2020/5/27

產品包裝說明:

單個產品




內袋包裝說明:

1. PE袋厚 0.1mm, 每PE袋裝入30pcs產品.
2. 每袋需貼1pc內袋標籤(PE袋正中間)以及1pcRoHS標籤, RoHS標籤需粘貼在內袋標籤的正下方位置.

PE 袋單邊厚度 0.1 ±0.02

內袋包裝



標籤說明:

1. Company : SparkLAN Communications, Inc.
2. Model Name : AD-302
3. Description : Dipole Antenna, 3dBi/2dBi 2.4G/5GHz, RP-SMA(M) connector
4. Part NO : R3410110221
5. Q'TY : 30 PCS

Company	SparkLAN Communications, Inc.
Model Name	AD-302
Description	Dipole Antenna, 3dBi/2dBi 2.4G/5GHz, RP-SMA(M) connector
Part NO	R3410110221
Q'TY	30 PCS

內袋標籤


Pack full: 30pcs/ Bag



底層與頂層需放各1PCS平卡

四個角需各放1pc護角紙

外箱包裝



RoHS 標籤

Dipole Antenna, 3dBi/2dBi 2.4G/5GHz, RP-SMA(M) connector
Part Number: R3410110221
Model No.: AD-302N
QTY: 30 PCS
N.W: 0.3 KGS
G.W: 0.3 KGS
CARTON Q'NO: 01 / 01
RP, No. 287, Sec. 2, Tainan Road, Taichung District, Taipei 11403, Taiwan
Made in Taiwan

外箱標籤

外箱包裝說明:

1. 紙箱底層與頂層需各放1pc平卡, 紙箱四個角需各放1pc護角紙.
2. 外箱需貼1pc外箱標籤(規格尺寸面) 右上角位置.
3. RoHS標籤需外箱標籤右下角外置.
4. 紙箱尺寸: 長350mm*寬300mm*高200mm.
5. 每箱裝34袋產品, 共計裝1020pcs產品.
6. 箱內若有空隙需用填充材填實, 避免晃動.
7. 實際包裝會依出貨數量進行調整.