

Report Seal

Report No.: EED32Q80116703 Page 1 of 7

RF Exposure Evaluation Report

Product : UWB Kbeacon

Trade mark : Kbeacon

Model/Type reference : K4W,K5W,K7W,K9W

Serial Number : N/A

Report Number : EED32Q80116703

FCC ID : 2AXZL-K4W

Date of Issue : Mar. 21, 2024

Test Standards : 47 CFR Part 1.1307

47 CFR Part 1.1310 47 CFR Part 2.1091 47 CFR Part 2.1093

KDB 447498 D04 Interim General RF

Exposure Guidance v01

Test result : PASS

Prepared for:

KKM Company Limited

3CDE, Building6, Baoneng Science&Technology Park, Qingxiang Rd, Longhua Street, Longhua District,Shenzhen City,Guangdong Province, China

Prepared by:

Centre Testing International Group Co., Ltd. Hongwei Industrial Zone, Bao'an 70 District, Shenzhen, Guangdong, China

TEL: +86-755-3368 3668 FAX: +86-755-3368 3385

Compiled by:

Mark Chen

Mark Chen

Approved by:

Approved by:

Aaron Ma

Reviewed by:

Frazer Li

Mar. 21, 2024

Check No.: 5128240124









Page 2 of 7

Report No.: EED32Q80116703

2 Version

Version No.	Date	Description	
00	Mar. 21, 2024	Original	
		(6)	(0)











































































Report No.: EED32Q80116703

Page 3 of 7

Contents

								Page
1 COVE	R PAGE.		•••••	••••••	••••••••••••		••••••	••••••
2 VERS	ION		••••••		••••••		•••••	
3 CONT	ENTS		•••••		•••••		•••••	
4 GENE	RAL INFO	ORMATION	••••••	•••••	••••••	•••••	•••••	
4.2 G1 4.3 PR 4.4 TE 4.5 D1 4.6 A1	ENERAL DE RODUCT SP EST LOCATE EVIATION F BNORMALI	SCRIPTION OF ECIFICATION SI ON ROM STANDAR TIES FROM STA	EUT JBJECTIVE TO LDS NDARD CONDI	THIS STANDARE)			
	F Exposur 1.1 Limits			VT				
5. 1 5. 1	1.2 Test Pi	ocedure						
5.7	1.5 LOT IX	r Exposure E	valuation				(4)	



Report No.: EED32Q80116703 Page 4 of 7

4 General Information

4.1 Client Information

Applicant:	KKM Company Limited				
Address of Applicant:	3CDE, Building6, Baoneng Science&Technology Park, Qingxiang Rd, Longhua Street, Longhua District,Shenzhen City,Guangdong Province, China				
Manufacturer:	KKM Company Limited				
Address of Manufacturer:	3CDE, Building6, Baoneng Science&Technology Park, Qingxiang Rd, Longhua Street, Longhua District,Shenzhen City,Guangdong Province, China				
Factory:	KKM Company Limited				
Address of Factory:	3CDE, Building6, Baoneng Science&Technology Park, Qingxiang Rd, Longhua Street, Longhua District,Shenzhen City,Guangdong Province, China				

4.2 General Description of EUT

Product Name:	UWB Kbeacon		
Model No.:	K4W,K5W,K7W,K9W	(6,1)	(6,2)
Test Model No.:	K4W		
Trade Mark:	Kbeacon		

4.3 Product Specification subjective to this standard

Frequency Range:	Bluetooth LE:2402MHz~2480MHz, UWB:6489.6MHz		
Modulation Type:	Bluetooth LE:GFSK UWB:BPM		
Test Power Grade:	Default	(6,)	(0,)
Test Software of EUT:	Bluetooth LE:Direct Test Mode Tool, UWB:RF test		
Antenna Type:	Bluetooth LE:Chip Antenna, UWB:Chip Antenna		
Antenna Gain:	Bluetooth LE:0.5 dBi, UWB:4.16dBi		
Power Supply:	Battery DC 3V		
Sample Received Date:	Jan. 24, 2024		(3)
Sample tested Date:	Jan. 24, 2024 to Mar. 14, 2024	(0,)	(0,)

Remark

Company Name and Address shown on Report, the sample(s) and sample Information was/ were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.

Model No.:K4W,K5W,K7W,K9W

Only the model K4W was tested, their electrical circuit design,layout,components used and internal wiring are identical.Only the case design is different.
















4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax:+86 (0) 755 33683385

No tests were sub-contracted. FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer





Report No.: EED32Q80116703 Page 6 of 7

5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

0.3 GHz to 6 GHz (inclusive). Pth is given by Formula

5.1.1 Limits

For Bluetooth LE:

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold Pth (mW). This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from

$$P_{\text{th}} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \le 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \le 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20\,\mathrm{cm}}\sqrt{f}}\right)$$

and f is in GHz, d is the separation distance (cm), and ERP20cm is per Formula (B.1).

$$P_{\text{th}} (\text{mW}) = ERP_{20 \text{ cm}} (\text{mW}) = \begin{cases} 2040f & 0.3 \text{ GHz} \le f < 1.5 \text{ GHz} \\ \\ 3060 & 1.5 \text{ GHz} \le f \le 6 \text{ GHz} \end{cases}$$
(B. 1)

For UWB:

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.





Report No.: EED32Q80116703 Page 7 of 7

5.1.3 EUT RF Exposure Evaluation

For Stand alone:

For Bluetooth LE:

	Frequency	Max. Conducted	Antenna Gain	ERP	ERP	ERP	Limit	MPE	Result
3	(MHz)	Output power	(dBi)	(dBm)	(dBm)	(mW)	(mW)	Ratio1	3
-		(dBm)							
	2402	1.39	0.5	1.89	-0.26	0.942	≤3060	0.0003	PASS

For UWB:

Frequency	Field strength of the	EIRP	EIRP	Limit	MPE	Result
(MHz)	fundamental signal	(dBm)	(mW)	(mW)	Ratio2	
	(dBuV/m@3m)					
6489.6	77.58	-17.65	0.0172	1.00	0.0172	PASS

Note:

- ①EIRP=conducted power+antenna gain;
- ②ERP=EIRP-2.15;
- ③EIRP(dBm) = Field strength of the fundamental signal(dBuV/m@3m) 95.23;
- $4ERP(mW) = 10^{(ERP (dBm)/10)};$
- ⑤The estimation distance is 20cm;
- The test data please refer to the report of EED32Q80116701 and EED32Q80116702, and only the worst case data was recorded in the report.

For co-launch:

Simultaneous launch is not supported.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

*** End of Report