SPARK Go 2023

User Manual




Explosion diagram specification



| 3 UPHOUSING | 1 | SP FILM 2 LAYERS | 2 | TP+LCM |
|---|----|-------------------|----|--------------------|
| 7 | 3 | UPHOUSING | 4 | BATTERY |
| 9 | 5 | LOW MYLAR | 6 | SIDEKEY FPC |
| 11 | 7 | PS RUBBER | 8 | MAIN PCB |
| 13 CON FOAM CAM | 9 | FCAM RUBBER RNM | 10 | BACK CAM AF |
| 15 | 11 | FRONT CAM FF | 12 | BACK CAM AI |
| 17 REC FPC UPPER 18 BACK FLASH LED HD 19 RECEIVER 20 RUBBER PI 21 RUBBER BAT 22 CAM 8W RUBBER 23 FINGER SHORT 24 SIM CARD 25 SHIELD COP FOIL 3 26 LOWHOUSING 27 FINGERPRINT HD 28 FINGERPRINT RUBBER 29 BATTERY COVER ASM 30 R CAM DECO LEN 31 MAIN CAM LENS 32 SUB CAM LENS 33 SPK FRAME ASM 34 FINGER FRAME 35 EARLACK RUBBER 36 RUBBER FRAME 37 USB RUBBER 38 RF CABLE 39 STIG SCREW 35 40 SUB PCBA 41 STIG SCREW 25 42 MYLAR SPEAKER 43 SPEAKER FPC 44 SHELD COP FOIL 2 | 13 | CON FOAM CAM | 14 | AF CAM ED FAB |
| 19 RECEIVER 20 RUBBER PI | 15 | REC ED FAB | 16 | FOAM CON FINGER |
| 21 RUBBER BAT 22 CAM SW RUBBER 23 FINGER SHORT 24 SIM CARD 25 SHIELD COP FOIL 3 26 LOWHOUSING 27 FINGERPRINT HD 28 FINGERPRINT RUBBER 29 BATTERY COVER ASM 30 R CAM DECO LEN 31 MAIN CAM LENS 32 SUB CAM LENS 33 SPK FRAME ASM 34 FINGER FRAME 35 EARIACK RUBBER 36 RUBBER P 37 USB RUBBER 38 RF CABLE 39 STIG SCREW 35 40 SUB PCBA 41 STIG SCREW 25 42 MYLAR SPEAKER 43 SPEAKER FPC 44 SPEAKER 45 SPHE C FAB 46 SHIELD COP FOIL 2 | 17 | REC FPC UPPER | 18 | BACK FLASH LED HD |
| 23 | 19 | RECEIVER | 20 | RUBBER PI |
| 25 | 21 | RUBBER BAT | 22 | CAM 8W RUBBER |
| 27 FINGERPRINT HD 28 FINGERPRINT RUBBER 29 BATTERY COVER ASM 30 R CAM DECO LEN 31 MAIN CAM LENS 32 SUB CAM LENS 33 SPK FRAME ASM 34 FINGER FRAME 35 EARJACK RUBBER 36 RUBBER P 37 USB RUBBER 38 RF CABLE 39 STI6 SCREW 35 40 SUB PCBA 41 STI6 SCREW 25 42 MYLAR SPEAKER 43 SPEAKER FPC 44 SPEAKER 45 SPE CD FAB 46 SHIELD COP FOIL 2 | 23 | FINGER SHORT | 24 | SIM CARD |
| 29 BATTERY COVER ASM 30 R CAM DECO LEN | 25 | SHIELD COP FOIL 3 | 26 | LOWHOUSING |
| 31 MAIN CAM LENS 32 SUB CAM LENS 33 SPK FRAME ASM 34 FINGER FRAME 35 EARJACK RUBBER 36 RUBBER P 37 USB RUBBER 38 RF CABLE 39 STIG SCREW 35 40 SUB PCBA 41 STIG SCREW 25 42 MYLAR SPEAKER 43 SPEAKER PCC 444 SPEAKER 445 SPEKER PCC 446 SHIELD COP FOIL 2 | 27 | FINGERPRINT HD | 28 | FINGERPRINT RUBBER |
| 33 SPK FRAME ASM 34 FINGER FRAME 35 EARJACK RUBBER 36 RUBBER P 37 USB RUBBER 38 RF CABLE 39 STI6 SCREW 35 40 SUB PCBA 41 STI6 SCREW 25 42 MYLAR SPEAKER 43 SPEAKER FPC 44 SPEAKER 45 SPEAKER DFAB 46 SHIELD COP FOIL 2 | 29 | BATTERY COVER ASM | 30 | R CAM DECO LEN |
| 35 EARJACK RUBBER 36 RUBBER P 37 USB RUBBER 38 RF CABLE 39 STI6 SCREW 35 40 SUB PCBA 41 STI6 SCREW 25 42 MYLAR SPEAKER 43 SPEAKER FPC 44 SPEAKER 45 SPK ED FAB 46 SHIELD COP FOIL 2 | 31 | MAIN CAM LENS | 32 | SUB CAM LENS |
| 37 USB RUBBER 38 RF CABLE 39 STI6 SCREW 35 40 SUB PCBA 41 STI6 SCREW 25 42 MYLAR SPEAKER 43 SPEAKER FPC 44 SPEAKER 45 SPK ED FAB 46 SHIELD COP FOIL 2 | 33 | SPK FRAME ASM | 34 | FINGER FRAME |
| 39 STI6 SCREW 35 40 SUB PCBA 41 STI6 SCREW 25 42 MYLAR SPEAKER 43 SPEAKER PFC 44 SPEAKER 45 SPEAKER 46 SHIELD COP FOIL 2 | 35 | EARJACK RUBBER | 36 | RUBBER P |
| 41 STI6 SCREW 25 42 MYLAR SPEAKER 43 SPEAKER FPC 44 SPEAKER 45 SPK ED FAB 46 SHIELD COP FOIL 2 | 37 | USB RUBBER | 38 | RF CABLE |
| 43 SPEAKER FPC 44 SPEAKER 45 SPK ED FAB 46 SHIELD COP FOIL 2 | 39 | STI6 SCREW 35 | 40 | SUB PCBA |
| 45 SPK ED FAB 46 SHIELD COP FOIL 2 | 41 | STI6 SCREW 25 | 42 | MYLAR SPEAKER |
| | 43 | SPEAKER FPC | 44 | SPEAKER |
| 47 SHIELD COP FOIL 4 48 SHIELD COP FOIL 1 | 45 | SPK ED FAB | 46 | SHIELD COP FOIL 2 |
| | 47 | SHIELD COP FOIL 4 | 48 | SHIELD COP FOIL 1 |

Know your phone



- 1. Front camera
- 2. Volume + key
- 3. Volume key
- 4. Power key

SIM/SD card installation

- 1. Power off mobile.
- 2. Refer to the following picture for SIM / SD card installation.



Charging the phone

You can charge your device using a charger or by connecting it to the computer using a USB cable (comes with the phone).

Use only TECNO charger and cables. Other chargers or cables may damage the device. This will invalidate your phone warranty.



FCC Caution

Labelling requirements.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference.
- (2) This device must accept any interference received, including interference that may cause undesired operation.

Information to user.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Information to the user.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- -Increase the separation between the equipment and receiver.
- -Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- -Consult the dealer or an experienced radio/TV technician for help.

Specific Absorption Rate (SAR) information:

This mobile phone meets the government's requirements for

exposure to radio waves. The guidelines are based on standards that were developed by independent scientific organizations through periodic and thorough evaluation of scientific studies. The standards include a substantial safety margin designed to assure the safety of all persons regardless of age or health.

include a substantial safety margin designed to assure the safety of all persons regardless of age or health.

FCC RF Exposure Information and Statement The SAR limit of USA (FCC) is 1.6 W/kg averaged over one gram of tissue. Device types: BF7 (FCC ID: 2ADY-BF7) has also been tested against this SAR limit. The highest SAR value reported under this standard during product certification for use at the ear is 1.189W/kg and when properly worn on the body is 0.581W/kg. This device was tested for typical body-worn operations with the back of the handset kept 10 mm from the body. To maintain compliance with FCC RF exposure requirements, use accessories that maintain a 10 mm separation distance between the user's body and the back of the handset. The use of belt clips, holsters and similar accessories should not contain metallic components in its assembly. The use of accessories that does not satisfy these requirements may not comply with FCC RF exposure requirements, and should be avoided.

Body-worn Operation

Body-worn Operation
This device was tested for typical body-worn operations. To comply
with RF exposure requirements, a minimum separation distance of
1.0 cm must be maintained between the user's body and the
handset, including the antenna. Third-party belt-clips, holsters, and
similar accessories used by this device should not contain any
metallic components. Body-worn accessories that do not meet these
requirements may not comply with RF exposure requirements and

should be avoided. Use only the supplied or an approved antenna.

TECHO