Go to www.vtechphones.com to register your product for enhanced warranty support and the latest VTech product news.



VM5463 VM5463-2

Full Color Pan and Tilt Video Monitor

vtech

Nominal effective range

Transmit frequency

Channels

Quick start quide

Company-y view, Communications, inc.

Address: 9020 SW Washington Square Boad - 5te 555 Tigard, OR 97223, United States

Phone: I. (800) 595-9511 in The U.S. or I. (800) 867-1317 in Canada

initial death of the control of the

Parent unit: 3.8V Z100mAh Li-lon battery Baby unit power adapter: Output: VDC @ AL AL @ DD V2 :tuqtuO :sptees aword tinu france.

DISCLAIMER AND LIMITATION OF LIABILITY

Charlism. Lo not install the basy unit at a neight above.

This groduct is not subtilistifier adult is previolen of the infant Supervision of the infant is persent for caregiver's repossibility. The product crudic desses operating, and therefore you'd brould not assume it will confinue working model and the state of the product crudic desses operating, and therefore you'd brought on a state of the product crudic and the product crudic and the product of the product is intended to a set you in supervising your baby.

Do not use this product near water, For example, do not use it nort to a bath thus, who how, kinchen sink, Isuandry that or swimming pool, or in a wet basement or shower.

CAUTION: Use only the battery provided. There may be a risk of explosion if a vicenty the battery provided. There may be a risk of explosion if a vicenty type of battery is used for the parent intl. The battery cannot be subjected to high or low extreme temperature and low air pressure at high altitude during use, storage or transportation. Disposal of battery into fite or a hot

damage the product.

Parent unit output: 5V DC 1A

Parent unit output: 5V DC 1A

Model: VTOSEUSOSIUU

Rechargeable battery informa:
Li-ion battery, 3.87 /2100mAh
Zhongshan Ilanmao Battery Co., Ltd.
Model Number: BP1763

Model Number: 8P1763 The power adapters are intended to be correctly oriente in a vertical or floor mount position. The prongs are not designed to hold the plug in place if it is plugged into a ceiling, under-the-table or cabinet outlet.

Do not cut off the power adapters to replace them with other plugs, as this causes a hazardous situation.

Do not allow anything to rest on the power cords. Do not install this product where the cords may be walked on or

crimped.

3. This product should be operated only from the type of power source indicated on the marking label. If you are not sure of the type of power supply in your home, consult your dealer or local power company.

14. Do not overload wall outliet or use an extension cord.

15. Do not place this product on an unstable table, shelf, stand or other unstable surfaces.

IMPORTANT SAFETY INSTRUCTIONS

D. Periodically examine all components for clamage. L. There is a very low risk of privacy loss when using certain electronic devices, such as baby monitors, cordiess telephones, etc. To protect your privacy, make sure the product has never been used before purchase, reset the baby monitor periodically by powering off and then powering on the units, and power off the Baby monitor if you will not use if for some time.

Children should be supervised to ensure that they do not play with the product. play with the product.

23. The product is not intended for use by persons (including children) with reduced physical, sensory or metal capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety.

SAVE THESE INSTRUCTIONS

Use and store the product at a temperature between 32°F and 104°F. Do not expose the product to extreme cold, heat or direct sunlight. Do not put the product close to a heating

es should not be exposed to excessive heat such as sunshine or fire. Marning—Strangulation Hazard— Children have STRANGLED in cords. Keep this cord out of the reach of children (more than 3 ft (0.9m) away). Do not remove this

utions for users of implanted cardiac pacemakers


Cardiac pacemakers (applies only to digital cordless devic Wireless Technology Research, LLC (WTR), an independer research entity, led a multidisciplinary evaluation of the interference between portable wireless devices and implanted cardiac pacemakers. Supported by the U.S. Food and Drug Administration, WTR recommends to physicians that: — __ og pommetererron, WTK recommends to physicians the cemaker patients.
Should keep wireless devices at least six inches from the pacemaker.

pacemaker.

Should NOT place wireless devices directly over the pacemaker, such as in a breast pocket, when it is turned ON. Wife evaluation did not identify any risk to bystanders with pacemakers from other persons using wireless devices.

Electromagnetic fields (EMF)

WHAT'S IN THE BOX



CONNECT THE BABY MONITOR


The rechargeable battery in the parent unit is built-in Use only the power adapters supplied with this product

Make sure the baby monitor is not connected to a switch-controlled electric outlet.


Connect the power adapters in a vertical or floor mount position only. The adapters' prongs are not designed to hold the weight of baby monitor, so do not connect them to any ceiling, under-the-lable, or cabined outlets. Otherwise, the adapters may not prosperly connect to the outlets.



Power on or off the baby monitor



POSITIONING THE BABY MONITOR





() CAUTION

 The default volume of your parent unit is level 4, and the maximum volume is level 7. If you experience high-pitched screeching noise from your beby monitor while positioning: Make sure your baby unit and paren unit are more than 3 feet (1 meter) apart, OR

Lower the volume of your parent unit

4 STATUS CHECK

baby unit and parent unit, your parent unit displays image from the baby unit, and the LINK LED light turns on.

The ON LED light of baby unit turns on.



BASIC OPERATION - PARENT UNIT

Adjust speaker volume

..........

of the rest

Press ● vol. / vol. ● to adjust your parent



Press @ to zoom in or out.

Frequency control Crystal controlled PLL synthesizer

TECHNICAL SPECIFICATIONS

Talk to your baby unit

Press and hold TALK and speak to your parent unit. Your voice is transmitted to the baby unit. Release TALK when finish talking and hear your baby again



Turn off the screen Press and hold LCD ON/OFF to switch off

the screen. You can still hear sound from



Press any key on the parent unit to turn on

Use the menu

Press MENU to enter the menu, choose a menu item. or save a setting. You can use the parent unit for advanced settings or operations, such as to play or stop the baby unit lullaby, or to adjust the baby unit sound sensitivity

While in the menu:

TALK

 Press MENU to select an item or to save a setting Press ★ or ▼ to scroll among the sub-menus, or to adjust a setting.

 Press


to return to the previous menu options without changing the current setting.

Press
 (EXIT to return to live video.




14 Power jack

OVERVIEW - PARENT UNIT



LED lights LCD display Arrow keys 11 Antenna Microphone 8 OVolume O 12 RESET POWER 9 VIEW /LCD ON/OFF 13 Stand

Overview - Baby unit



Light sensor Camera lens

NEED HELP?

Microphone

Night light On/Off switch

On/Off LED light On when the baby unit is turned on and is paired to the

Flashes when the baby unit is

not being viewed; or when the link to the parent unit is lost.

For operations and guides to help you operate your video monitor, and for the latest information and support, check out our online help topics and FAQs.

Use your smartphone or mobile device to access our online help.

You can also call our Customer Support at 1 (800) 595-9511 [in US] or 1 (800) 267-7377 [in Canada] for help.

Scan the GR code on the right. Launch the camera app or GR code scanner app on your smartphone or tablet. Hold the device's camera up to the GR code and frame it. Tap the pop-up notification to be redirected to the online help page.

If the QR code is not clearly displayed, adjust your camera's focus by moving your device closer or further away until the image is clear.

Go to https://help.vtechphones.com/vm5463 or https://help.vtechphones.com/vm5463-2; OR

Speaker

Projection light on/off key 10 O Night light on/off key 11 Power jack

VM5463-2

12 Slots for wall mounting

J

Brightness



PARENT UNIT ICONS Main menu icons

(3)



Adjust the parent unit's LCD

Monitoring mode (For VM5463-2 only)

Single mode

Split mode

Patrol mode

Baby unit speaker volume

· Adjust the baby unit's





60min 45min 30min 15min Set timer to stop playing the selected



melody or soothing sound.

Night light ON / OFF Turn on/off night light \$\\ \partial 1 \\ \partial 2 \\ \partial 3 \\ \partial 4 \\ \partial 5 \\ \partial 6 \\ \partial 7



 Change to all seven colors in cycles 60min 30min 15min Set timer to turn the night light off.

AUTO

- Auto Turn on the night light when baby unit detects sound. It will turn off after 15 minutes of no sound detection. See Sound sensitivity and sound activation section to learn more.

ON/OFF DIV/OFF

Turn on/off the adaptive night light feature. When this feature is on, the baby unit detects the ambient light. If the room is bright, the night light adjusts itself to be brighter; if the room is dim, the night light adjusts itself to be less bright.

ON / OFF Turn on/off projection light 60min 45min 30min 15min Set timer to turn the projection light off.

Temperature

(D)



Projection

ON/OFF Turn on/off temperature alert tone

Set the parent unit to beeps whenever the room temperature detected by the baby unit falls outside of the set temperature range.



Alert tone setting:

· Set the maximum temperature.

Set temperature display in Fahrenheit (°F) or Celsius (°C)

Set the parent unit to beep when the battery is low. 治

 Set the parent unit to beep when the link between the parent unit and the baby unit is lost. Set the confirmation tone on or off when selecting an option in the manus \bigcirc

Set the parent unit to beep when the baby unit detects sounds while in Split mode (For VM5463-2 only).

Sound activation - screen and audio

ON/ OFF Turn on/off sound activation

 When on, once a sound is detected, the parent unit screen and speaker will automatically turn on. See Sound sensitivity and sound activation section to learn more

⊞NOTE When the parent unit screen is off

and it receives alerts, for example, link lost between parent unit and baby unit, the parent unit screen and speaker will turn on for 10 seconds.

VOX (Voice Activated Alert) Sensitivity



 You can set VOX sensitivity level to activate parent unit screen and sound when baby unit detects sounds that exceed certain levels. See Sound sensitivity and sound activation section to learn more.



PARENT UNIT ICONS (CONT'D)

Status icons Status icons 74 Connection status *

Till - Strong signal strength.

· 🚹 - Moderate signal

- strength.
- Ti Low signal strength. Weak signal strength.

Patrol modo (*For VM5463-2 only

Current view status . The haby unit number that is being viewed when in

- . Single CAM mode Patrol mode "For VM5463-2 only).
- Split mode (*For VM5463-2 only)
- Night vision On
- ⊕ Zoom - On T)

 \blacksquare

佨

Q1

<u>@</u>2

- Lullahy . On
- Color icon indicates the night light is set to auto-on, and is currently turned on by sound activation. Night light - Auto-on
- activation.

 Gray icon indicates the night light is currently off but is set to auto-on. Night light will turn on when sound is detected by



la.

.....

1. Place the wall mount bracket on a wall and then use a pencil to mark two holes in parallel. Remove the

Projection light - On

Projection light - Auto on

Real-time temperature

Color icon indicates the projection light is set to autoon, and is currently turned on by sound activation.
 Gray icon indicates the projection light is currently off but is set to auto-on. Projection

light will turn on when sound is detected by the baby unit.

Real-time temperature detected by the baby unit in Fahrenheit (°F) or Celsius (°C) (e.g. 57°F or 14°C).

Temperature alert tone - On

indicates low sound leve detected by the baby unit.

indicates moderate sound level detected by the baby unit.

Displays when the parent unit speaker volume is set to off.

Displays when the parent unit is talking to the baby unit.

. Parameter animates

Speaker volume - displays the

parent unit speaker volume leve hile adjusting.

9-level sound indicator

Mute alert

Battery status



OR



3 Insert the screws into the holes and

the screws are exposed.

tighten the screws until only 1/4 inch of



5. You can maximize your camera unit's viewing angles by tilting the wall mount bracket. Hold the camera unit, and then rotate the knob in anticlockwise direction. This will loosen the joint of the wall mount bracket. Tilt your camera unit up or down to adjust to your preferred angle. Then, rotate the knob in clockwise direction to tighten the



Alert icons

. Displays when parent unit's battony is low and people charging $\theta_{\rm M}$

. Displays when connection between parent unit and baby unit is lost · Displays when sound is detected at a baby unit when in Split view. (For VM5463-2 only)


Baby unit detects temperature reaches or exceeds the set maximum.

Raby unit detects temperature is at or is lower than the set minimum.

PROJECTION LIGHT

39

A



Sound sensitivity and sound activation

Adjust sound detection sensitivity

You can turn on **Sound activation** and adjust the VOX sensitivity to detect sounds and turn on the parent unit while its screen is switched off or dimmed

When the baby unit detects sounds that screen will turn on and the baby unit starts transmitting the sounds to the parent unit, and you can see and hear your baby. If you ave turned on the Night light Auto-on and the Projection light Auto-on feature, they vill turn on automatically to sooth your baby

If you turn off Sound activation, you will be a sounds from the baby unit all the time, even when the parent unit screen is switched off. If you have turned on sound alert, the parent

unit beeps when the baby unit detect sour while in **Split** mode ("For **VM5463-2** only).

NIGHT VISION

THE RBRC SEAL

FCC Part 15

RF radiation exposure statement



Sound activated screen and audio

When Sound activation is on, the parent unit screen stays off to save power when the baby unit detects no sound. Once the baby unit detects sounds that are louder than the chosen sound sensitivity level, the parent unit screen and speaker turn on automatically. The parent unit will then turn off again after 50 seconds of no sound detection. NOTE

If you have muted the parent unit speaker, only the parent unit





your parent unit screen as the baby unit is adapting to the dark environment. When the infrared LEDs are on, the images are in black and white. This is normal.

The program provides a convenient alternative to placing used U-ion batteries into the trash or municipal waste, which may be illegal in your area.

The RBRC seal and 1-800-8-BATTERY® are registered trademarks of California.

FCC AND IC REGULATIONS

Depending on the surroundings and othe interfering factors, like lightings, objects, colors and backgrounds, the video quality may vary. Adjust the baby unit's angle or place the baby unit at a higher level to prevent glare and blurry display









For VM5463-2 ONLY

Status check - Two baby units

If you are viewing baby unit 21 the POWER LED light of baby unit @1 turns on. As baby unit @ & is not being viewed, its POWER LED light flashes. Note





If you power on only one baby unit, you may see the parent unit displaying 🛂 and then 🛂 , and the LINK LED light flashing.

Press VIEW in Single CAM or Patrol mode to switch to the baby unit you have powered on.





Patrol mode, press VIEW to switch hotwoon the image of baby units 21 and @2





Change different views - Patrol





Select **Split** as your monitoring mode to view the images from both

baby units at once.

Change different views - Split



MOUNT THE BABY UNIT ON DRY WALL (OPTIONAL)

■Notes

- Check for reception strength and camera angle before drilling the holes
- The types of screws and anchors you need depend on the composition of the wall. You may need to purchase screws and anchors separately to moun vour camera units.

3. Align the wall mount bracket and screws with

the holes in the wall as shown. Tighten the screv

in the middle hole first, so that the wall mount

bracket position is fixed. You can tighten the

4. Place the camera unit on the wall mount bracket, and then slide it forward until it locks into place. Connect the power

adapter to the camera unit and a power

supply not controlled by a wall switch

other screw in the top hole.

wall mount bracket and drill two holes in the wall (7/32 inch drill bit).



2. If you drill the holes into a stud, go to step 3.

If you drill the holes into an object other than a stud. insert the wall anchors into the holes Tap gently on the ends with a hammer until the wall anchors are flush with the wall.



No national exposure statement.

The baby unit origines with PCC RF radiation exposure limits set forth for an uncontrolled environment. The baby unit should be installed and operated with a minimum distance of 8 in (20 cm) between the baby unit and all persons' body, Use of other accessories may not ensure compliance with PCCR Resposure quicklener. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter. This equipment complies also with Industry Canada RSS-102 with respect to Canada's Health Code for Exposure of Humans to RF Pelial Canada.

The term "IC." before the certification/registration number only signifies that the Industry Canada technical specifications were

met.
This product meets the applicable Innovation, Science and Economic Development Canada technical specifications.

This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may care

CALIFORNIA ENERGY COMMISSION BATTERY CHARGING TESTING MODE

This bady monitor meets the California Energy Commission (EEC) regulations for energy communitor. Your bady monitor is set up to comply with the energy concerving standards right out of the box Fellow the instructions to install and charge the battery. The CEC battery charging testing mode is activated while charging. Even if the parent unit is paired to baby units, the CEC battery charging reting mode is activated while it is powered of and charging.

FOR CETL COMPLIANCE ONLY

mesures de sécurité importantes La plaque signalétique appliquée est située au bas du socie de l'unité du bébé. de Tunité du bébé.
Lorque vous utilises votre appareil, vous devrier toujours suivre certaines mesures de précaulion de base afin de réduire les risques d'incende, d'électroution et de blessures corporeiles, 1. Observez toutes les instructions et mises en garde inscrites sur l'appareil.

sur rappareii. L'installation par un adulte est requise. MISE EN GARDE: N'installez pas l'unité du bébé à une

hauteur supérieure à 2 mètres. Ce produit ne remplace pas la suveillance adulte du nourrisson. La supervision du nourrisson est la responsabilité du parent ou de la personne qui s'occupe de l'enfant. Ce produit pourrait cesser de fonctionner et, par conséquent, procurs pour air cesser de fonctionner et, par conséquent, vous ne devirée pas présumer qu'il confinuera de fonction correctement péndant une période de temps donnée. De plus, il ne s'agit pas d'un instrument médical et ne devrait pa être utilisé comme tel. Ce produit est destiné à vous aider à supervisor untre hélibé.

This equipment has been tented and found to comply with the requirement for a Case 8 digital device under Part S of the Found Communication Commission (FC) under The Even expaniement are intended to provide reconsible providers on agreement of the Case 1 to the Case 1 to the Case 1 to the Case 1 to the Case 2 mply with the requirements for a Class B digital device under Part 15 of the

supervieur voire select.
N'utilisez pas cet appareil près de l'eau ni de toute autre source d'humidité, par exémple, près d'une baignoire, cuive à lessive, évier de cuisine, dans un sous-sof humide ni près d'une piscine, dans un soussof humide ou une douche.

MISE EN GARDE: Utilisez uniquement les piles fournies. Il
existe un risque d'explosion si un autre type de batterie es
utilisé pour l'unité Parents. N'incinérez pas les piles. Celles-

utilisé pour l'unité Parents. N'incinérez pàs les piles. Celle ci risqueralent d'exploser, latore les piles usées selon les renseignements sulvant le sceau du RBRC. N'utilisez que les adaptateurs inclus avec ce produit. L'utilisation d'un adaptateur dont la polarité ou la tension serait inadéquate risque d'endommager sériessement le produit et mettre votre sécurité en péril.

Informations sur les adaptateurs électriques de l'unité du parent : Sortie : SV DC 1A ommunications I tri Rdaptateur de l'unité du parens Viech felecommunications trid. Modelle : VTOSEUSSISIO Adaptateur de l'unité du bébé : Sortie : SV DC 1A Viech felecommunications trid. Modelle : VTOSEUSSISIO

Models: 'YIGSUSGIO'

Li-lon battery, J. 3V ZIO'mAn.
Li-lon battery, J. 3V ZIO'mAn.
Model Number: BP17/8

Longyll' sout branched dans use prise de courant, les
comprehenses, controlled de la plander. Les brook
comprehenses, cost als werticate ou as planders. Les brook
morting sed de courage pour supportie le podid de bloc
dans une prise au platfond, cour une table ou dans un
meuble.

meuble.

Pour les PRODUITS À BRANCHER À UNE PRISE DE COURANT, la prise de courant doit être installée pr produit, afin d'assurer une accessibilité sécuritaire à

produit, afin d'auteur une accessibile écutive à la pres Débandhez ex possibile de partie de construir à la prise Débandhez ex possibile de partie de contravant en produit au melhoyage. Il vallate par de nethroyent en les frobre, ce coe par présenter un danger potentier les les frobre, ce coe par présenter un danger potentier les les frobre, ce coe par présenter un danger potentier les frobres. Par les les parties de la présente de la pr

domicilé, consulter votre marchand ou votre compagnie locale d'électricité. Ne surchargez par les prises de courant murales ni les rallonges électriques. Ne plácez par cet appareil sur un chariot, meuble, trépied, support de montage ni table chancelants.

support de montagió in table chancelantis. Les frous et ouventures du bolines, faithe à l'arrière de impagnatio qui sous callu-ire, servent à akter ir apparent. In protecte des que ventures et riverpolicher pas l'astrainon addiquate de l'apparent en le plaçaire sur un it, d'usun, positionne par a provintiné na un debuscu d'une source de challeur ou d'un calorifère. De plus, ne plaçere pas l'apparent destu un endroir vaunt de vous astraire qu'il y ait une blonne dans un endroir vaunt de vous astraire qu'il y ait une blonne traire.

N'enfoncez jamais d'objets à travers les ouvertures d cet appareil, car ils pourraient entrer en contact avec des points de tension dangereux ou causer des courts-circuits qui peuvent dégérérer en incendies ou en risque d'électrocution. Ne renversez jamais de liquide dans ce

que confient chi apparan, a i inxempliori de l'acces ancesae à certaines portes ou ouvertures, risque de vous exposer à des points de tersion dangereux ou d'autres dangèrs. Un remontage incorrect peut par la suite présenter des risques

remontage incorrect peut par la suite présenter des risques d'électrotution.

19. Vous deuvirez tester la réception chaque fois que vous mettez l'appareil en fonction.

20. Examinez les comporantes afin de vérifier si celles-ci ne sont pas endommagées. sont pas endommiagies.

Il existe un très faible risque de perte de confidentialité avec certains appareits électroniques (autres écoute-bébés, réléphones sans fills etc.). Pour l'éviter, résurer que le produit n'a jemais été ufilisé avant l'achat, réinitailiser l'unité façon périodique, étéinder l'écoute-bébé quand il n'est

pas en cours d'utilisation.
Les enfants devraient par l'appendis afin de vous assurer Le produit n'est pas concu pour être utilisé par des personnes (incluant des enfants) aux capacités physiques, sensorielles ou mentaler rédullés ou qui manquent d'expérience et de connaissances, à môns qu'on leur ait donné suffisamment de supervision ou d'instructions relativement à trullisation de l'appareil par une personne responsable de leur sécurité.

lises en garde

Utilisez et entreposez le produit à une température entre

0° C (32° F) et 40° C (104° F).

Vego para que C (104 F).

N'exposer pas cet appareil à des froids ou des chaleurs extrémes, ainsi qu'à la lumière directe du soleil. Ne l'installe pas près d'une source de chauffage.

Le bloc-plies ne doit pas être exposé à la chaleur excessive telle que la lumière du solei ou la feu.

Avertissement - Risque de strangulation - Les enfants se sont ETRANGLES dans des cordons. Gardez ce cordon hors de portée des enfants (à plus de 0,9 m). N'enlevez pas cette étiquette.

cette étiquette. Ne jamais placer le moniteur à l'intérieur du berceau ou du parc de bébé. Ne jamais couvrir le moniteur ou l'unité (s) portative avec un article tel une serviette ou une couverture.
D'autres équipements électroniques peuvent produire des interférences sur votre moniteur vidéo et audio. Tentez interferences sur vorte moniteur video et audio. Lennes d'installer votre moniteur vidéo ou audio à l'écart des apparels électroniques tels que des routeurs sans fil, radios, téléphones cellulaires, interphones, moniteurs, féléphones, ordinateurs personnels, électroménagers et téléphones sans fil.

numériques sans fiji:
L'organisme Wilvieless Technology Research, LLC (WTR); une
Lorganisme Wilvieless Technology Research, LLC (WTR); une
puluridisciplinarche independante, a menoù une divelatation
puluridisciplinarche des interferences entre les teléphones sans
fiji portalifs el les stimulateurs cardiaques implantés dans
fil portalifs el les stimulateurs cardiaques implantés dans
fil corpanisme. Appuyée par l'Administration des aliments et
drogues (FDA) des États-Unis, la firme WTR recommande aux
médécins.

oddecini: 's aux défenteurs de stimulateurs cardiaques Vous devriez maintenir les dispositifs sans fil à au moins six pouces du simulateur cardiaque, ils ne doivent PAS place le téléphone sans fil directement sur le stimulateur cardiaque, tel que dans une poche de chemise, lossque celui-ci est en marche.

L'étude effectuée par l'organisme WRS n'a pas identifié de risque pour les défenteurs de simulateurs cardiaques causés pu les gens qui utilisent dispositifs sans fil à proximité de ceux-cl.

Champs électromagnétiques (EMF)
Ce produit de VTech est conforme à toutes les normes se rapportant aux champs électromagnétiques (EMF) standard. Si vous le manipulez correctement en suivant les instructions de ci guide, son utilisation sera sécuritaire pendant de nombreuses années, selon les meilleures évidences scientifiques dont nous

LIMITED WARRANTY

What does this limited warranty cover?

The manufacture of this VI Cach Product warrant to the holder of a valid pool of purchase ("Ocusume" or "you") that the Product and all accessories provided in the sales package ("Product") are fine from defects in material and workmantile, pursuant to the following terms and conditions, when installed and used normally and in accordance with the Product operating instructions. This limited warranty sendes only in the Consumer for Product. To obtain warranty service; To obtain warranty service in the USA, please visit our website at www.vtechphones.com or call 1 (800) 595-9511. In Canada, go to www.vtechcanada.com or call 1 (800) 267-337. minited warranty extends only to the Consumer for Produ purchased and used in the United States of America and Canada.

What will VTech do if the Product is not free from defects in materials and workmanship during the limited warranty period ("Materially Defective Product")?

representative will replace at VTech's option, without charge, at Materially Defective Product. If we choose to replace the Product, we may replace it with a new refundation of Product of the same or similar design. We will retain product of the same or similar design. We will retain the product of the same or similar design. We will retain the replacement of the Product, at VTech's option, is your exclusive remedy. VTech will return the replacement Product to you in working condition. You should expect the replacement to take approximately 30 days.

low long is the limited warranty period?

The winds is the immediately periodic. The limited warranty period for the Product extends for O (1) YEAR from the date of purchase (90 days on products of the periodic perio

What is not covered by this limited warranty? This limited warranty does not cover

1 Product that has been subjected to misure, accid

fire, water or other liquid intrusion; or 2. Product that has been diamaged due to repair, alteration or modification by anyone other than an authorized service representative of VTech; or 3. Product to the extent that the problem experienced is caused by signal conditions, network reliability, or cable or antenna systems; or

Product to the extent that the problem is caused by use with non-VTech accessories or

with non-VTech accessories; or S. Product whose warranty/quality stickers, product serial number plates or electronic serial numbers have been removed, altered or rendered illegible; or O. Product purchased, used, serviced, or shipped for repair from outside the United States of America or Canada, or

used for commercial or institutional purposes (including but not limited to Products used for rental purposes); of

Product returned without a valid proof of purchase (se item 2 below); or

Charges for installation or set up, adjustment of custome controls, and installation or repair of systems outside the

How do you get warranty service?

1,800 j.26-797.

NOTE Before calling for service, please review the user's manual - a check of the Product's controls and features may sev you a service call.

Except as provided by applicable law, you assume the risk of less or changed during famati and transportation and war less control of the productify to the service location. Virieth will return replaced Product under this limited warranty. Transportation, delivery or handling changes are prepaid. Vireth sammer on risk for damage or repealed.

What must you return with the Product to get warranty service?

service?

1. Return the entire original package and contents including the Product to the VTech service location along with a description of the malfunction or difficulty and along the analysis of the malfunction or difficulty or difficulty identifying the Product purchase (Product model) and the date of purchase or receipt; and

Provide your name, complete and correct mailing address, and telephone number. Other limitations

Other limitations.

This varranty is the complete and exclusive agreement of between you and VTech. It apperades all other written contact communications related to the Product. VTech provides and communication related to the Product. VTech provides all of VTech's responsibilities regarding the Product. These are no other express varianties. No one is authorized to make medifications to this limited warranty and you may also have other rights, which vary from state to state or you will be provided to provide the provide to provide to provide the provide to provide t

for a particular jurpose and merchantability (an unwritten warranty that the Product Is fif for cordinary use) are limited to one year from the date of purchase. Some states/ provinces do not allow limitations on how long an implied. On the cordinary of the provinces of the product of the provinces of the product of the provinces of the product of the state of the product of the product of the state of the product of the pro

Please retain your original sales receipt as proof of purchase.



