



RF EXPOSURE EVALUATION REPORT

Applicant: SHANGHAI WANWAY DIGITAL TECHNOLOGY CO.,

LTD

Address: FLOOR 23 NO. 1999 WENCHUAN ROAD BAOSHAN DISTRICT

SHANGHAI China

FCC ID: 2AWBA-H19P

Product Name: GPS Tracker

Standard(s): 47 CFR §1.1307

The above equipment has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR230740290-00C

Date Of Issue: 2023/8/3

Reviewed By: Calvin Chen

Title: RF Engineer

Reviewed By: Sun Zhong

Glinchen Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,

Guangdong, China Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

Report No.: CR230740290-00C

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol "\(^{\text{a}}\)". Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk "★".

CONTENTS

Report No.: CR230740290-00C

| TEST FACILITY | 2 |
|---------------------------|---|
| DECLARATIONS | 2 |
| DOCUMENT REVISION HISTORY | |
| 1. RF EXPOSURE EVALUATION | |
| 1.1 Applicable Standard | |
| 1.1.3 Measurement Result | 5 |

DOCUMENT REVISION HISTORY

| Revision Number | Report Number | Description of Revision | Date of Revision | |
|-----------------|-----------------|-------------------------|---------------------|--|
| 1.0 | CR230740290-00C | Original Report | 2023/8/3 | |

Report No.: CR230740290-00C

1. RF EXPOSURE EVALUATION

1.1 Applicable Standard

According to §1.1307(b)(3)(i)

(C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Report No.: CR230740290-00C

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

| RF Source frequency (MHz) | Threshold ERP (watts) | | | |
|---------------------------------|---------------------------------|--|--|--|
| 0.3-1.34 | 1,920 R ² . | | | |
| 1.34-30 | $3,450 \text{ R}^2/\text{f}^2.$ | | | |
| 30-300 | $3.83 R^2$. | | | |
| 300-1,500 | $0.0128 \text{ R}^2\text{f}.$ | | | |
| 1,500-100,000 | 19.2R ² . | | | |

1.1.3 Measurement Result

| | 1:1:0 Wedgarement Result | | | | | | | | | |
|---|--------------------------|-----------|----------------|----------|----------------------|---------|-------------------|---------|---------|-----------|
| | | | | | Exemption ERP | | Maximum | | | |
| I | Operation F | Frequency | $\lambda/2\pi$ | Distance | | | Conducted Power | Antenna | ERP | MPE- |
| | Modes | (MHz) | (mm) | (mm) | (mW) | (dBm) | including Tune-up | Gain | (dBm) | Based |
| | Modes | (141112) | (11111) | (11111) | (111 **) | (uDiii) | Tolerance | (dBi) | (ubiii) | Exemption |
| | | | | | | | (dBm) | | | |
| | GSM850 | 824-849 | 57.94 | 250 | 659 | 28.19 | 33.5 | -3.50 | 27.85 | Compliant |
| | GSM1900 | 1850-1910 | 25.81 | 250 | 1200 | 30.79 | 30 | -2.00 | 25.85 | Compliant |

Note:

The Maximum Conducted Power including Tune-up Tolerance was declared by manufacturer.

Result: The device compliant the MPE-Based Exemption at 25cm distances.

==== END OF REPORT **=====**