

# TEST REPORT

FCC/ISED MPE Test for VT2600TAN  
Certification

**APPLICANT**  
HYUNDAI MOBIS CO., LTD.

**REPORT NO.**  
HCT-RF-2105-FI009-R1

**DATE OF ISSUE**  
June 10, 2021

**Tested by**  
Chang Hee Hwang



**Technical Manager**  
Jong Seok Lee



**HCT CO., LTD.**  
*BongJai Huh*  
BongJai Huh / CEO



**HCT Co., Ltd.**

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA  
Tel. +82 31 634 6300 Fax. +82 31 645 6401

# TEST REPORT

FCC MPE Test for  
VT2600TAN

**REPORT NO.**

HCT-RF-2105-FI009-R1

**DATE OF ISSUE**

June 10, 2021

**Additional Model**

VT2620TAN, VT2610TAN, VT260TOAN, VT2500TAN, VT2520TAN, VT2510TAN,  
VT250TOAN, VT2530TAN, VT2630TAN, VT251TOAN, VT261TOAN

**Applicant**

**HYUNDAI MOBIS CO., LTD.**

203, Teheran-ro, Gangnam-gu, Seoul, 135-977, South Korea

**Eut Type  
Model Name**

CAR AUDIO SYSTEM  
VT2600TAN

**FCC ID**

TQ8-VT2600TAN

**Frequency range**

2 402 MHz ~ 2 480 MHz (Bluetooth)  
2 412 MHz ~ 2 462 MHz (WLAN)  
5 180 MHz ~ 5 825 MHz (UNII)

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test results were applied only to the test methods required by the standard.

## REVISION HISTORY

The revision history for this test report is shown in table.

| Revision No. | Date of Issue | Description                          |
|--------------|---------------|--------------------------------------|
| 0            | June 01, 2021 | Initial Release                      |
| 1            | June 10, 2021 | Added the Additional Model on Page 2 |

### Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

\* The report shall not be reproduced except in full(only partly) without approval of the laboratory.

## RF Exposure Statement

### 1. Limit

According to § 1.1310, § 2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

| Frequency range<br>(MHz) | Electric field<br>Strength (V/m) | Magnetic field<br>Strength (A/m) | Power density<br>(mW/cm <sup>2</sup> ) | Averaging time<br>(minutes) |
|--------------------------|----------------------------------|----------------------------------|----------------------------------------|-----------------------------|
| 0.3 -<br>1.34.....       | 614                              | 1.63                             | *(100)                                 | 30                          |
| 1.34 - 30.....           | 824/f                            | 2.19/f                           | *(180/ f <sup>2</sup> )                | 30                          |
| 30 - 300.....            | 27.5                             | 0.073                            | 0.2                                    | 30                          |
| 300 - 1500.....          | .....                            | .....                            | f/1500                                 | 30                          |
| 1500 -<br>100.000.....   | .....                            | .....                            | 1.0                                    | 30                          |

F = frequency in MHz

\* = Plane-wave equivalent power density

### 2. Maximum Permissible Exposure Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = Power input to antenna

G = Power gain to the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

### 3. RESULTS

#### 3-1. Bluetooth

|                                                             |             |                    |
|-------------------------------------------------------------|-------------|--------------------|
| Average output Power at antenna input terminal              | 4.000       | dBm                |
| Average output Power at antenna input terminal              | 2.512       | mW                 |
| Prediction distance                                         | 20.00       | cm                 |
| Prediction frequency                                        | 2402 – 2480 | MHz                |
| Antenna Gain(typical)                                       | -0.38       | dBi                |
| Antenna Gain(numeric)                                       | 0.916       | -                  |
| Power density at prediction frequency( S)                   | 0.0005      | mW/cm <sup>2</sup> |
| MPE limit for uncontrolled exposure at prediction frequency | 1.0000      | mW/cm <sup>2</sup> |

#### 2.1091

|           |       |       |
|-----------|-------|-------|
| EIRP      | 3.62  | (dBm) |
| ERP       | 1.47  | (dBm) |
| ERP       | 0.001 | (W)   |
| ERP Limit | 3.00  | (W)   |
| MARGIN    | 33.30 | (dB)  |

### 3-2. DTS

|                                                             |             |                    |
|-------------------------------------------------------------|-------------|--------------------|
| Average output Power at antenna input terminal              | 10.00       | dBm                |
| Average output Power at antenna input terminal              | 10.000      | mW                 |
| Prediction distance                                         | 20.00       | cm                 |
| Prediction frequency                                        | 2412 – 2462 | MHz                |
| Antenna Gain(typical)                                       | -1.19       | dBi                |
| Antenna Gain(numeric)                                       | 0.760       | -                  |
| Power density at prediction frequency( S)                   | 0.0015      | mW/cm <sup>2</sup> |
| MPE limit for uncontrolled exposure at prediction frequency | 1.0000      | mW/cm <sup>2</sup> |

### 2.1091

|           |       |       |
|-----------|-------|-------|
| EIRP      | 8.81  | (dBm) |
| ERP       | 6.66  | (dBm) |
| ERP       | 0.005 | (W)   |
| ERP Limit | 3.00  | (W)   |
| MARGIN    | 28.11 | (dB)  |

### 3-3. UNII

|                                                             |             |                    |
|-------------------------------------------------------------|-------------|--------------------|
| Average output Power at antenna input terminal              | 10.00       | dBm                |
| Average output Power at antenna input terminal              | 10.000      | mW                 |
| Prediction distance                                         | 20.00       | cm                 |
| Prediction frequency                                        | 5180 - 5825 | MHz                |
| Antenna Gain(typical)                                       | 4.58        | dBi                |
| Antenna Gain(numeric)                                       | 2.871       | -                  |
| Power density at prediction frequency( S)                   | 0.0057      | mW/cm <sup>2</sup> |
| MPE limit for uncontrolled exposure at prediction frequency | 1.0000      | mW/cm <sup>2</sup> |

### 2.1091

|           |       |       |
|-----------|-------|-------|
| EIRP      | 14.58 | (dBm) |
| ERP       | 12.43 | (dBm) |
| ERP       | 0.017 | (W)   |
| ERP Limit | 3.00  | (W)   |
| MARGIN    | 22.34 | (dB)  |

### 3-4. CDMA BC0

|                                                             |         |                    |
|-------------------------------------------------------------|---------|--------------------|
| Average output Power at antenna input terminal              | 25.70   | dBm                |
| Average output Power at antenna input terminal              | 371.54  | mW                 |
| Prediction distance                                         | 20.000  | cm                 |
| Prediction frequency                                        | 824-849 | MHz                |
| Cable Loss                                                  | -0.50   | dB                 |
| Antenna Gain(typical)                                       | 4.17    | dBi                |
| Antenna Gain(numeric)                                       | 2.612   | -                  |
| Power density at prediction frequency( S)                   | 0.1931  | mW/cm <sup>2</sup> |
| MPE limit for uncontrolled exposure at prediction frequency | 0.5493  | mW/cm <sup>2</sup> |

#### 2.1091

|           |       |       |
|-----------|-------|-------|
| EIRP      | 29.37 | (dBm) |
| ERP       | 27.22 | (dBm) |
| ERP       | 0.53  | (W)   |
| ERP Limit | 1.50  | (W)   |
| MARGIN    | 4.54  | (dB)  |

### 3-5. CDMA BC1

|                                                             |           |                    |
|-------------------------------------------------------------|-----------|--------------------|
| Average output Power at antenna input terminal              | 25.70     | dBm                |
| Average output Power at antenna input terminal              | 371.54    | mW                 |
| Prediction distance                                         | 20.000    | cm                 |
| Prediction frequency                                        | 1850-1910 | MHz                |
| Cable Loss                                                  | -0.82     | dB                 |
| Antenna Gain(typical)                                       | 2.02      | dBi                |
| Antenna Gain(numeric)                                       | 1.592     | -                  |
| Power density at prediction frequency( S)                   | 0.1177    | mW/cm <sup>2</sup> |
| MPE limit for uncontrolled exposure at prediction frequency | 1.0000    | mW/cm <sup>2</sup> |

#### 2.1091

|           |       |       |
|-----------|-------|-------|
| EIRP      | 26.90 | (dBm) |
| ERP       | 24.75 | (dBm) |
| ERP       | 0.299 | (W)   |
| ERP Limit | 3.00  | (W)   |
| MARGIN    | 10.02 | (dB)  |

### 3-6. LTE B4

|                                                             |           |                    |
|-------------------------------------------------------------|-----------|--------------------|
| Average output Power at antenna input terminal              | 25.70     | dBm                |
| Average output Power at antenna input terminal              | 371.54    | mW                 |
| Prediction distance                                         | 20.000    | cm                 |
| Prediction frequency                                        | 1710-1755 | MHz                |
| Cable Loss                                                  | -0.76     | dB                 |
| Antenna Gain(typical)                                       | 2.98      | dBi                |
| Antenna Gain(numeric)                                       | 1.986     | -                  |
| Power density at prediction frequency( S)                   | 0.1468    | mW/cm <sup>2</sup> |
| MPE limit for uncontrolled exposure at prediction frequency | 1.0000    | mW/cm <sup>2</sup> |

#### 2.1091

|           |       |       |
|-----------|-------|-------|
| EIRP      | 27.92 | (dBm) |
| ERP       | 25.77 | (dBm) |
| ERP       | 0.378 | (W)   |
| ERP Limit | 3.00  | (W)   |
| MARGIN    | 9.00  | (dB)  |

### 3-7. LTE B13

|                                                             |         |                    |
|-------------------------------------------------------------|---------|--------------------|
| Average output Power at antenna input terminal              | 25.70   | dBm                |
| Average output Power at antenna input terminal              | 371.54  | mW                 |
| Prediction distance                                         | 20.000  | cm                 |
| Prediction frequency                                        | 777-787 | MHz                |
| Cable Loss                                                  | -0.47   | dB                 |
| Antenna Gain(typical)                                       | 2.87    | dBi                |
| Antenna Gain(numeric)                                       | 1.936   | -                  |
| Power density at prediction frequency( S)                   | 0.1431  | mW/cm <sup>2</sup> |
| MPE limit for uncontrolled exposure at prediction frequency | 0.5180  | mW/cm <sup>2</sup> |

#### 2.1091

|           |       |       |
|-----------|-------|-------|
| EIRP      | 28.10 | (dBm) |
| ERP       | 25.95 | (dBm) |
| ERP       | 0.39  | (W)   |
| ERP Limit | 1.50  | (W)   |
| MARGIN    | 5.81  | (dB)  |

### 3-8. LTE B5

|                                                             |         |                    |
|-------------------------------------------------------------|---------|--------------------|
| Average output Power at antenna input terminal              | 25.70   | dBm                |
| Average output Power at antenna input terminal              | 371.54  | mW                 |
| Prediction distance                                         | 20.000  | cm                 |
| Prediction frequency                                        | 824-849 | MHz                |
| Cable Loss                                                  | -0.50   | dB                 |
| Antenna Gain(typical)                                       | 4.17    | dBi                |
| Antenna Gain(numeric)                                       | 2.612   | -                  |
| Power density at prediction frequency( S)                   | 0.1931  | mW/cm <sup>2</sup> |
| MPE limit for uncontrolled exposure at prediction frequency | 0.5493  | mW/cm <sup>2</sup> |

#### 2.1091

|           |       |       |
|-----------|-------|-------|
| EIRP      | 29.37 | (dBm) |
| ERP       | 27.22 | (dBm) |
| ERP       | 0.53  | (W)   |
| ERP Limit | 1.50  | (W)   |
| MARGIN    | 4.54  | (dB)  |

### 3-9. LTE B2

|                                                             |           |                    |
|-------------------------------------------------------------|-----------|--------------------|
| Average output Power at antenna input terminal              | 25.70     | dBm                |
| Average output Power at antenna input terminal              | 371.54    | mW                 |
| Prediction distance                                         | 20.000    | cm                 |
| Prediction frequency                                        | 1850-1910 | MHz                |
| Cable Loss                                                  | -0.82     | dB                 |
| Antenna Gain(typical)                                       | 2.02      | dBi                |
| Antenna Gain(numeric)                                       | 1.592     | -                  |
| Power density at prediction frequency( S)                   | 0.1177    | mW/cm <sup>2</sup> |
| MPE limit for uncontrolled exposure at prediction frequency | 1.0000    | mW/cm <sup>2</sup> |

#### 2.1091

|           |       |       |
|-----------|-------|-------|
| EIRP      | 26.90 | (dBm) |
| ERP       | 24.75 | (dBm) |
| ERP       | 0.299 | (W)   |
| ERP Limit | 3.00  | (W)   |
| MARGIN    | 10.02 | (dB)  |

#### Worst Case: Simultaneous MPE 20cm is

5G WLAN (0.0057) + BT (0.0005) + CDMA BC0 (0.1931/0.549) + LTE B5 (0.1931/0.549) = 0.6564 < 1