



中认信通

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: Shenzhen Youmi Intelligent Technology Co., Ltd.

Address: 406-407 Jinqi Zhigu Building, 4/F, 1 Tangling Road, Nanshan District, Shenzhen City, China

FCC ID: 2ATZ4-A15P5G

Product Name: Smart phone

Standard(s): 47 CFR Part 15, Subpart E(15.407)
ANSI C63.10-2013
KDB 789033 D02 General U-NII Test Procedures New
Rules v02r01

The above device has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR230745209-00D

Date Of Issue: 2023/12/29

Reviewed By: Calvin Chen

Title: RF Engineer

Approved By: Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,
Guangdong, China
Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

DOCUMENT REVISION HISTORY	5
1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	6
1.2 DESCRIPTION OF TEST CONFIGURATION.....	8
1.2.1 EUT Operation Condition:.....	8
1.2.2 Support Equipment List and Details	8
1.2.3 Support Cable List and Details	8
1.2.4 Block Diagram of Test Setup.....	9
1.3 MEASUREMENT UNCERTAINTY	10
2. SUMMARY OF TEST RESULTS	11
3. REQUIREMENTS AND TEST PROCEDURES	12
3.1 AC LINE CONDUCTED EMISSIONS.....	12
3.1.1 Applicable Standard.....	12
3.1.2 EUT Setup.....	13
3.1.3 EMI Test Receiver Setup	13
3.1.4 Test Procedure	14
3.1.5 Corrected Amplitude & Margin Calculation.....	14
3.2 RADIATION SPURIOUS EMISSIONS.....	15
3.2.1 Applicable Standard.....	15
3.2.2 EUT Setup.....	16
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup	17
3.2.4 Test Procedure	17
3.2.5 Corrected Amplitude & Margin Calculation.....	18
3.3 EMISSION BANDWIDTH.....	19
3.3.1 Applicable Standard.....	19
3.3.2 EUT Setup.....	19
3.3.3 Test Procedure	19
3.4 MAXIMUM CONDUCTED OUTPUT POWER.....	21
3.4.1 Applicable Standard.....	21
3.4.2 EUT Setup.....	21
3.4.3 Test Procedure	21
3.5 MAXIMUM POWER SPECTRAL DENSITY	22
3.5.1 Applicable Standard.....	22
3.5.2 EUT Setup.....	22
3.5.3 Test Procedure	23
3.6 DUTY CYCLE	24
3.6.1 EUT Setup.....	24
3.6.2 Test Procedure	24
3.7 ANTENNA REQUIREMENT.....	25
3.7.1 Applicable Standard.....	25
3.7.2 Judgment.....	25

4. Test DATA AND RESULTS.....	26
4.1 AC LINE CONDUCTED EMISSIONS.....	26
4.2 RADIATION SPURIOUS EMISSIONS.....	29
4.3 EMISSION BANDWIDTH:	70
4.4 MAXIMUM CONDUCTED OUTPUT POWER:	84
4.5 MAXIMUM POWER SPECTRAL DENSITY:	86
4.6 DUTY CYCLE:.....	100
5. EUT PHOTOGRAPHS	102
6. TEST SETUP PHOTOGRAPHS	103

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR230745209-00D	Original Report	2023/12/29

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Smart phone
Trade Name:	UMIDIGI
EUT Model:	MP36
Operation Frequency:	5180-5240 MHz (802.11a/n ht20/ac vht20) 5190-5230 MHz(802.11n ht40/ac vht40) 5210MHz (802.11ac vht80) 5745-5825 MHz (802.11a/n ht20/ac vht20) 5755-5795 MHz(802.11n ht40/ac vht40) 5775MHz(802.11ac vht80)
Maximum Average Output Power (Conducted):	13.55dBm (5150-5250 MHz) 14.02dBm (5725-5850 MHz)
Modulation Type:	802.11a/n/ac: OFDM-BPSK, QPSK, 16QAM, 64QAM, 256QAM
Rated Input Voltage:	DC 3.87V from battery or DC 5/9/12/15/20/11V from adapter
Serial Number:	CE&RE: 2BCU-2 RF: 2BCU-1
EUT Received Date:	2023/9/18
EUT Received Status:	Good

1.1.2 Operation Frequency Detail: For 802.11a/n ht20/ac vht20:

5150-5250MHz Band		5725-5850MHz Band	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	149	5745
40	5200	153	5765
44	5220	157	5785
48	5240	161	5805
/	/	165	5825
Per section 15.31(m), the below frequencies were performed the test as below:			
36	5180	149	5745
40	5200	157	5785
48	5240	165	5825

For 802.11n ht40/ac vht40:

5150-5250MHz Band		5725-5850MHz Band	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	151	5755
46	5230	159	5795
Per section 15.31(m), the below frequencies were performed the test as below:			
38	5190	151	5755
46	5230	159	5795

For 802.11ac vht80:

5150-5250MHz Band		5725-5850MHz Band	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	5210	155	5775
Per section 15.31(m), the below frequencies were performed the test as below:			
42	5210	155	5775

1.1.3 Antenna Information Detail▲:

Antenna Manufacturer	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
ANWEI commnuication Equipment Co.,Ltd	FPC	50	5150~5250MHz	-1.74 dBi
			5725~5850MHz	-1.74 dBi

The Method of §15.203 Compliance:

- ☒ Antenna was permanently attached to the unit.
☐ Antenna use a unique type of connector to attach to the EUT.
☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

1.1.4 Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
Adapter	UMIDIGI	HJ-PD66W-US	Input: AC 100-240V, 50/60Hz, 1.5A Output: DC 5.0V, 3.0A, 15.0W or 9.0V, 3.0A, 27.0W or 12.0V, 3.0A, 36.0W or 15.0V, 3.0A, 45.0W or 20.0V, 3.25A, 65.0W or 11.0V, 6.0A, 66.0W MAX

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

EUT Operation Mode:		The system was configured for testing in Engineering Mode, which was provided by the manufacturer.		
Equipment Modifications:		No		
EUT Exercise Software:		Engineer mode		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer ▲ :				
5150-5250 MHz Band:				
Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting
802.11a	Lowest	5180	6Mbps	20
	Middle	5200	6Mbps	20
	Highest	5240	6Mbps	20
802.11ac vht20	Lowest	5180	MCS8	20
	Middle	5200	MCS8	20
	Highest	5240	MCS8	20
802.11ac vht40	Lowest	5190	MCS8	20
	Highest	5230	MCS8	20
802.11ac vht80	Middle	5210	MCS8	20
5725-5850 MHz Band:				
Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting
802.11a	Lowest	5745	6Mbps	20
	Middle	5785	6Mbps	20
	Highest	5825	6Mbps	20
802.11ac vht20	Lowest	5745	MCS8	20
	Middle	5785	MCS8	20
	Highest	5825	MCS8	20
802.11ac vht40	Lowest	5755	MCS8	20
	Highest	5795	MCS8	20
802.11ac vht80	Middle	5775	MCS8	20
Note: The system support 802.11a/n ht20/n ht40/ac vht20/ac vht40/ac vht80, the n ht20/ht40 were reduced since the identical parameters with 802.11ac vht20 and ac vht40. The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations. The two antenna chain has same power level setting. The device supports SISO/MIMO in all modes, per pretest, MIMO mode was the worst mode and reported for all modes.				

1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

1.2.3 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	No	No	1.0	Adapter	EUT

1.2.4 Block Diagram of Test Setup

AC line conducted emissions:



Radiated Spurious Emissions:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9k~30MHz:4.12dB 30M~200MHz: 4.15 dB,200M~1GHz: 5.61 dB,1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1℃
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a)	AC line conducted emissions	Compliant
FCC§15.205& §15.209 &§15.407(b)	Radiated Spurious Emissions	Compliant
FCC§15.407(a) (e)	Emission Bandwidth	Compliant
FCC§15.407(a)	Maximum Conducted Output Power	Compliant
FCC§15.407 (a)	Power Spectral Density	Compliant
§15.203	Antenna Requirement	Compliant

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiation Spurious Emissions

3.2.1 Applicable Standard

FCC §15.407 (b);

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of - 27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of - 27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of - 27 dBm/MHz.

(4) For transmitters operating solely in the 5.725-5.850 GHz band:

(i) All emissions shall be limited to a level of - 27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.

(8) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.

(9) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in § 15.207.


(10) The provisions of § 15.205 apply to intentional radiators operating under this section.

(11) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.


(c) The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization a description of how this requirement is met.

3.2.2 EUT Setup


9 kHz-30MHz:



30MHz-1GHz:



1-40 GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was FCC 15.209, FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9 kHz-1000MHz:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	/	/	200 Hz	QP
	300 Hz	1 kHz	/	PK
150 kHz – 30 MHz	/	/	9 kHz	QP
	10 kHz	30 kHz	/	PK
30 MHz – 1000 MHz	/	/	120 kHz	QP
	100 kHz	300 kHz	/	PK

1GHz- 40GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	$\geq 1/T$

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

3.2.4 Test Procedure

During the radiated emission test, the adapter was connected to the first AC floor outlet.

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz-1GHz, peak and Average detection modes for frequencies above 1GHz.

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, emission shall be computed as: $E [dB\mu V/m] = EIRP[dBm] + 95.2$, for $d = 3$ meters.

According to C63.10, the above 1G test result shall be extrapolated to the specified distance using an extrapolation Factor of 20dB/decade from 3m to 1.5m

Distance extrapolation Factor = $20 \log (\text{specific distance } [3m] / \text{test distance } [1.5m])$ dB = 6.02 dB

All emissions under the average limit and under the noise floor have not recorded in the report.

3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Factor = Antenna Factor + Cable Loss- Amplifier Gain

For 30MHz-1GHz:

Result = Reading + Factor

For 1GHz-40GHz

Result = Reading + Factor- Distance extrapolation Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.3 Emission Bandwidth

3.3.1 Applicable Standard


FCC §15.407 (a),(h)

(h)(2) Radar Detection Function of Dynamic Frequency Selection (DFS). U-NII devices operating with any part of its 26 dB emission bandwidth in the 5.25-5.35 GHz and 5.47-5.725 GHz bands shall employ a DFS radar detection mechanism to detect the presence of radar systems and to avoid co-channel operation with radar systems.

FCC §15.407 (e)

Within the 5.725-5.850 GHz and 5.850-5.895 GHz bands, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

3.3.2 EUT Setup



3.3.3 Test Procedure

26dB Emission Bandwidth:

According to ANSI C63.10-2013 Section 12.4.1

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = peak.
- d) Trace mode = max hold
- e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

6 dB emission bandwidth:

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

- a) Set RBW = 100 kHz.
 - b) Set the video bandwidth (VBW) ≥ 3 RBW.
 - c) Detector = Peak.
 - d) Trace mode = max hold.
 - e) Sweep = auto couple.
 - f) Allow the trace to stabilize.
 - g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
- Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described in this section. For devices that use channel aggregation refer to III.A and III.C for determining emission bandwidth.

99% Occupied Bandwidth:

According to ANSI C63.10-2013 Section 12.4.2&6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

3.4 Maximum Conducted Output Power

3.4.1 Applicable Standard

FCC §15.407(a) (1)(iv)

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


FCC §15.407(a) (2)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

3.4.2 EUT Setup



3.4.3 Test Procedure

According to ANSI C63.10-2013 Section 12.3.3.2

Method PM-G is measurement using a gated RF average power meter. Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

3.5 Maximum Power Spectral Density

3.5.1 Applicable Standard

FCC §15.407(a) (1)(iv)

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


FCC §15.407(a) (2)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

3.5.2 EUT Setup



3.5.3 Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

Duty cycle $\geq 98\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-1 should be applied.

Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$


KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-2 should be applied.

Duty cycle $< 98\%$, duty cycle variations exceed $\pm 2\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-3 should be applied.

3.6 Duty Cycle

3.6.1 EUT Setup



3.6.2 Test Procedure

According to ANSI C63.10-2013 Section 12.2

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

3.7 Antenna Requirement

3.7.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.7.2 Judgment

Result: Compliant. Please refer to the Antenna Information detail in Section 1.

4. Test DATA AND RESULTS

4.1 AC Line Conducted Emissions

Serial Number:	2BCU-2	Test Date:	2023/09/23
Test Site:	CE	Test Mode:	Transmitting maximum output power mode 802.11 a 5200MHz
Tester:	David Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.3	Relative Humidity: (%)	57	ATM Pressure: (kPa)	99.9
----------------------	------	------------------------------	----	------------------------	------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101134	2023/03/31	2024/03/30
R&S	EMI Test Receiver	ESR3	102726	2023/03/31	2024/03/30
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2023/08/06	2024/08/05
Audix	Test Software	E3	190306 (V9)	N/A	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:


Please refer to the below table and plots.

Project No.: CR230745209-RF

Tester: David Huang

Port: Line

Note:




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.153	7.26	9.61	16.87	55.86	38.99	Average
2	0.153	21.26	9.61	30.87	65.86	34.99	QP
3	0.171	4.90	9.61	14.51	54.91	40.40	Average
4	0.171	18.58	9.61	28.19	64.91	36.72	QP
5	0.735	7.56	9.62	17.18	46.00	28.82	Average
6	0.735	17.35	9.62	26.97	56.00	29.03	QP
7	1.132	17.67	9.62	27.29	46.00	18.71	Average
8	1.132	25.49	9.62	35.11	56.00	20.89	QP
9	1.577	11.78	9.63	21.41	46.00	24.59	Average
10	1.577	24.31	9.63	33.94	56.00	22.06	QP
11	24.447	31.02	9.81	40.83	50.00	9.17	Average
12	24.447	33.33	9.81	43.14	60.00	16.86	QP

Project No.: CR230745209-RF

Tester: David Huang

Port: neutral

Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
<hr/>							
1	0.156	6.44	9.61	16.05	55.69	39.64	Average
2	0.156	22.89	9.61	32.50	65.69	33.19	QP
3	0.164	9.16	9.61	18.77	55.26	36.49	Average
4	0.164	22.08	9.61	31.69	65.26	33.57	QP
5	0.698	6.62	9.62	16.24	46.00	29.76	Average
6	0.698	18.53	9.62	28.15	56.00	27.85	QP
7	1.145	16.75	9.62	26.37	46.00	19.63	Average
8	1.145	24.64	9.62	34.26	56.00	21.74	QP
9	1.589	13.45	9.63	23.08	46.00	22.92	Average
10	1.589	26.54	9.63	36.17	56.00	19.83	QP
11	28.902	5.07	9.81	14.88	50.00	35.12	Average
12	28.902	13.40	9.81	23.21	60.00	36.79	QP

4.2 Radiation Spurious Emissions

Serial Number:	2BCU-2	Test Date:	Below 1GHz: 2023/11/28 Above 1GHz: 2023/9/25
Test Site:	966-2, 966-1	Test Mode:	Transmitting
Tester:	Tao Zhu, Carl Xue, Jeff Luo	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.7~26.2	Relative Humidity: (%)	47~62	ATM Pressure: (kPa)	100.3~101.3
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Below 1GHz					
Sunol Sciences	Antenna	JB6	A082520-6	2023/9/18	2026/9/17
BACL	Loop Antenna	1313-1P	3092721	2023/11/9	2026/11/8
R&S	EMI Test Receiver	ESR3	102724	2023/3/31	2024/3/30
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2023/7/16	2024/7/15
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2023/7/16	2024/7/15
Sonoma	Amplifier	310N	186165	2023/7/16	2024/7/15
Audix	Test Software	E3	201021 (V9)	N/A	N/A
Above 1GHz					
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020/10/13	2023/10/12
R&S	Spectrum Analyzer	FSV40	101591	2023/3/31	2024/3/30
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2023/8/6	2024/8/5
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2023/8/6	2024/8/5
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2022/11/9	2023/11/8
Audix	Test Software	E3	201021 (V9)	N/A	N/A
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021/2/5	2024/2/4
Quinstar	Preamplifier	QLW-18405536-JO	15964001005	2023/9/15	2024/9/14
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2023/8/6	2024/8/5
E-Microwave	Band Rejection Filter	5150-5850MHz	OE01902423	2023/8/6	2024/8/5
Mini Circuits	High Pass Filter	VHF-6010+	31119	2023/8/6	2024/8/5
PASTERNAK	Horn Antenna	PE9850/2F-20	072001	2021/2/5	2024/2/4

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

After pre-scan in the X, Y and Z axes of orientation, the worst case is refer to plots.

For 9kHz-30MHz, The amplitude of spurious emissions attenuated more than 20 dB below the limit was not be recorded.


1) 30MHz-1GHz:**5150-5250 MHz Band:** (Maximum Conducted Output Power 802.11a)**Low Channel**

Project No.: CR230745209-RF
Tester: Carl Xue
Polarization: horizontal
Note: 5G WIFI(5150-5250 MHz)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.638	28.43	-4.28	24.15	40.00	15.85	Peak
2	73.103	31.32	-16.82	14.50	40.00	25.50	Peak
3	102.719	37.11	-13.79	23.32	43.50	20.18	Peak
4	213.763	36.01	-12.61	23.40	43.50	20.10	Peak
5	333.687	31.01	-10.18	20.83	46.00	25.17	Peak
6	699.305	28.46	-3.61	24.85	46.00	21.15	Peak


Project No.: CR230745209-RF
Tester: Carl Xue
Polarization: vertical
Note: 5G WIFI(5150-5250 MHz)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.962	28.94	-4.53	24.41	40.00	15.59	Peak
2	37.285	35.93	-9.35	26.58	40.00	13.42	Peak
3	42.900	35.63	-13.05	22.58	40.00	17.42	Peak
4	66.266	38.19	-16.86	21.33	40.00	18.67	Peak
5	99.878	32.64	-14.35	18.29	43.50	25.21	Peak
6	206.398	31.28	-12.40	18.88	43.50	24.62	Peak


Middle Channel

Project No.: CR230745209-RF
Tester: Carl Xue
Polarization: horizontal
Note: 5G WIFI(5150-5250 MHz)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.853	28.41	-4.45	23.96	40.00	16.04	Peak
2	72.592	31.19	-16.78	14.41	40.00	25.59	Peak
3	103.080	35.90	-13.70	22.20	43.50	21.30	Peak
4	218.309	36.47	-12.79	23.68	46.00	22.32	Peak
5	331.355	31.14	-10.20	20.94	46.00	25.06	Peak
6	658.836	28.64	-4.23	24.41	46.00	21.59	Peak


Project No.: CR230745209-RF
Tester: Carl Xue
Polarization: vertical
Note: 5G WIFI(5150-5250 MHz)



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.531	28.58	-4.20	24.38	40.00	15.62	Peak
2	36.127	35.35	-8.48	26.87	40.00	13.13	Peak
3	42.900	36.30	-13.05	23.25	40.00	16.75	Peak
4	66.266	37.40	-16.86	20.54	40.00	19.46	Peak
5	71.581	37.70	-16.72	20.98	40.00	19.02	Peak
6	210.786	31.03	-12.52	18.51	43.50	24.99	Peak


High Channel

Project No.: CR230745209-RF
Tester: Carl Xue
Polarization: horizontal
Note: 5G WIFI(5150-5250 MHz)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	31.071	28.80	-4.61	24.19	40.00	15.81	Peak
2	73.103	31.53	-16.82	14.71	40.00	25.29	Peak
3	102.719	36.00	-13.79	22.21	43.50	21.29	Peak
4	164.908	31.83	-12.40	19.43	43.50	24.07	Peak
5	218.309	35.64	-12.79	22.85	46.00	23.15	Peak
6	331.355	31.76	-10.20	21.56	46.00	24.44	Peak


Project No.: CR230745209-RF
Tester: Carl Xue
Polarization: vertical
Note: 5G WIFI(5150-5250 MHz)



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.638	29.63	-4.28	25.35	40.00	14.65	Peak
2	37.155	34.72	-9.25	25.47	40.00	14.53	Peak
3	42.451	36.54	-12.78	23.76	40.00	16.24	Peak
4	70.584	37.54	-16.62	20.92	40.00	19.08	Peak
5	210.786	33.03	-12.52	20.51	43.50	22.99	Peak
6	737.071	28.19	-3.01	25.18	46.00	20.82	Peak


**5725-5850 MHz Band: (Maximum Conducted Output Power 802.11ac vht20 mode)
802.11ac vht20 Mode, Low Channel**

Project No.: CR230745209-RF
Tester: Carl Xue
Polarization: horizontal
Note: 5G WIFI(5725-5850 MHz)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.638	28.98	-4.28	24.70	40.00	15.30	Peak
2	35.624	28.45	-8.10	20.35	40.00	19.65	Peak
3	99.180	37.00	-14.51	22.49	43.50	21.01	Peak
4	214.514	35.17	-12.63	22.54	43.50	20.96	Peak
5	316.589	31.28	-10.58	20.70	46.00	25.30	Peak
6	677.580	29.14	-3.95	25.19	46.00	20.81	Peak


Project No.: CR230745209-RF
Tester: Carl Xue
Polarization: vertical
Note: 5G WIFI(5725-5850 MHz)



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.531	28.25	-4.20	24.05	40.00	15.95	Peak
2	38.888	35.90	-10.54	25.36	40.00	14.64	Peak
3	42.451	36.44	-12.78	23.66	40.00	16.34	Peak
4	66.266	39.30	-16.86	22.44	40.00	17.56	Peak
5	70.832	38.15	-16.64	21.51	40.00	18.49	Peak
6	210.048	30.56	-12.49	18.07	43.50	25.43	Peak


Middle Channel

Project No.: CR230745209-RF
Tester: Carl Xue
Polarization: horizontal
Note: 5G WIFI(5725-5850 MHz)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
<hr/>							
1	30.000	27.36	-3.80	23.56	40.00	16.44	Peak
2	37.025	29.89	-9.16	20.73	40.00	19.27	Peak
3	102.001	36.40	-13.97	22.43	43.50	21.07	Peak
4	218.309	36.28	-12.79	23.49	46.00	22.51	Peak
5	331.355	32.52	-10.20	22.32	46.00	23.68	Peak
6	706.700	29.80	-3.59	26.21	46.00	19.79	Peak


Project No.: CR230745209-RF
Tester: Carl Xue
Polarization: vertical
Note: 5G WIFI(5725-5850 MHz)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.853	29.02	-4.45	24.57	40.00	15.43	Peak
2	36.895	34.56	-9.06	25.50	40.00	14.50	Peak
3	42.900	36.61	-13.05	23.56	40.00	16.44	Peak
4	66.266	38.06	-16.86	21.20	40.00	18.80	Peak
5	71.581	37.74	-16.72	21.02	40.00	18.98	Peak
6	210.048	31.43	-12.49	18.94	43.50	24.56	Peak


High Channel

Project No.: CR230745209-RF
Tester: Carl Xue
Polarization: horizontal
Note: 5G WIFI(5725-5850 MHz)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
<hr/>							
1	31.510	29.01	-4.93	24.08	40.00	15.92	Peak
2	73.103	31.92	-16.82	15.10	40.00	24.90	Peak
3	98.833	37.25	-14.59	22.66	43.50	20.84	Peak
4	161.474	31.65	-12.11	19.54	43.50	23.96	Peak
5	213.763	35.43	-12.61	22.82	43.50	20.68	Peak
6	330.195	30.91	-10.23	20.68	46.00	25.32	Peak

Project No.: CR230745209-RF
Tester: Carl Xue
Polarization: vertical
Note: 5G WIFI(5725-5850 MHz)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.000	28.58	-3.80	24.78	40.00	15.22	Peak
2	37.416	35.58	-9.44	26.14	40.00	13.86	Peak
3	43.353	35.54	-13.32	22.22	40.00	17.78	Peak
4	66.266	37.39	-16.86	20.53	40.00	19.47	Peak
5	70.337	37.57	-16.60	20.97	40.00	19.03	Peak
6	207.123	31.35	-12.41	18.94	43.50	24.56	Peak

2) 1GHz-40GHz:**5150-5250MHz:****802.11a:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				5180	MHz		
5150.000	45.32	PK	H	11.46	56.78	74.00	17.22
5150.000	30.12	AV	H	11.46	41.58	54.00	12.42
10360.000	33.65	PK	H	19.18	52.83	68.20	15.37
15540.000	36.45	PK	H	22.44	58.89	74.00	15.11
15540.000	23.48	AV	H	22.44	45.92	54.00	8.08
Middle Channel:				5200	MHz		
10400.000	34.90	PK	H	19.16	54.06	68.20	14.14
15600.000	36.55	PK	H	22.41	58.96	74.00	15.04
15600.000	23.18	AV	H	22.41	45.59	54.00	8.41
High Channel:				5240	MHz		
5350.000	44.21	PK	H	12.25	50.44	74.00	23.56
5350.000	30.07	AV	H	12.25	36.30	54.00	17.70
10480.000	33.65	PK	H	18.86	46.49	68.20	21.71
15720.000	38.17	PK	H	22.28	54.43	74.00	19.57
15720.000	25.34	AV	H	22.28	41.60	54.00	12.40

802.11ac vht20:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 5180 MHz							
5150.000	44.78	PK	H	11.46	56.24	74.00	17.76
5150.000	30.15	AV	H	11.46	41.61	54.00	12.39
10360.000	33.86	PK	H	19.18	53.04	68.20	15.16
15540.000	33.83	PK	H	22.44	56.27	74.00	17.73
15540.000	20.39	AV	H	22.44	42.83	54.00	11.17
Middle Channel: 5200 MHz							
10400.000	33.97	PK	H	19.16	53.13	68.20	15.07
15600.000	36.10	PK	H	22.41	58.51	74.00	15.49
15600.000	23.41	AV	H	22.41	45.82	54.00	8.18
High Channel: 5240 MHz							
5350.000	44.25	PK	H	12.25	56.50	74.00	17.50
5350.000	31.18	AV	H	12.25	43.43	54.00	10.57
10480.000	33.29	PK	H	18.86	52.15	68.20	16.05
15720.000	38.27	PK	H	22.28	60.55	74.00	13.45
15720.000	25.39	AV	H	22.28	47.67	54.00	6.33

802.11ac vht40:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 5190 MHz							
5150.000	48.64	PK	H	11.46	60.10	74.00	13.90
5150.000	33.23	AV	H	11.46	44.69	54.00	9.31
10380.000	33.26	PK	H	19.17	52.43	68.20	15.77
15570.000	34.25	PK	H	22.43	56.68	74.00	17.32
15570.000	21.24	AV	H	22.43	43.67	54.00	10.33
High Channel: 5230 MHz							
5350.000	44.35	PK	H	12.25	56.60	74.00	17.40
5350.000	30.17	AV	H	12.25	42.42	54.00	11.58
10460.000	33.46	PK	H	18.94	52.40	68.20	15.80
15690.000	38.44	PK	H	22.29	60.73	74.00	13.27
15690.000	25.32	AV	H	22.29	47.61	54.00	6.39

802.11ac vht80:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Middle Channel:				5210	MHz		
5150.000	44.97	PK	H	11.46	56.43	74.00	17.57
5150.000	30.23	AV	H	11.46	41.69	54.00	12.31
5350.000	44.25	PK	H	12.25	56.50	74.00	17.50
5350.000	30.07	AV	H	12.25	42.32	54.00	11.68
10420.000	33.54	PK	H	19.09	52.63	68.20	15.57
15630.000	37.26	PK	H	22.37	59.63	74.00	14.37
15630.000	24.36	AV	H	22.37	46.73	54.00	7.27

Note:

Result = Reading + Factor- Distance extrapolation Factor

For 1-40GHz:

Distance extrapolation Factor = $20 \log (\text{specific distance [3m]}/\text{test distance [1.5m]})$ dB= 6.02 dB

5725-5850MHz:**802.11a:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				5745	MHz		
11490.000	40.32	PK	H	20.67	60.99	74.00	13.01
11490.000	27.69	AV	H	20.67	48.36	54.00	5.64
17235.000	34.19	PK	H	26.76	60.95	68.20	7.25
Middle Channel:				5785	MHz		
11570.000	39.66	PK	H	20.83	60.49	74.00	13.51
11570.000	26.48	AV	H	20.83	47.31	54.00	6.69
17355.000	33.42	PK	H	27.74	61.16	68.20	7.04
High Channel:				5825	MHz		
11650.000	39.65	PK	H	21.06	60.71	74.00	13.29
11650.000	26.38	AV	H	21.06	47.44	54.00	6.56
17475.000	34.85	PK	H	28.62	63.47	68.20	4.73

802.11ac vht20:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				5745	MHz		
11490.000	38.36	PK	H	20.67	59.03	74.00	14.97
11490.000	25.47	AV	H	20.67	46.14	54.00	7.86
17235.000	33.09	PK	H	26.76	59.85	68.20	8.35
Middle Channel:				5785	MHz		
11570.000	38.36	PK	H	20.83	59.19	74.00	14.81
11570.000	25.47	AV	H	20.83	46.30	54.00	7.70
17355.000	33.93	PK	H	27.74	61.67	68.20	6.53
High Channel:				5825	MHz		
11650.000	37.68	PK	H	21.07	58.75	74.00	15.25
11650.000	24.64	AV	H	21.07	45.71	54.00	8.29
17475.000	33.89	PK	H	28.61	62.50	68.20	5.70

802.11ac vht40:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel:				5755	MHz		
11510.000	37.69	PK	H	20.67	58.36	74.00	15.64
11510.000	24.66	AV	H	20.67	45.33	54.00	8.67
17265.000	33.21	PK	H	26.94	60.15	68.20	8.05
High Channel:				5795	MHz		
11590.000	38.44	PK	H	20.88	59.32	74.00	14.68
11590.000	25.69	AV	H	20.88	46.57	54.00	7.43
17385.000	33.28	PK	H	28.07	61.35	68.20	6.85

802.11ac80 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Middle Channel:				5775	MHz		
11550.000	36.33	PK	H	20.78	57.11	74.00	16.89
11550.000	23.59	AV	H	20.78	44.37	54.00	9.63
17325.000	33.58	PK	H	27.41	60.99	68.20	7.21


Note:

Result = Reading + Factor- Distance extrapolation Factor

For 1-40GHz:


Distance extrapolation Factor = 20 log (specific distance [3m]/test distance [1.5m]) dB= 6.02 dB

Worst Harmonic Margin Test plots: (802.11a 5825MHz)



Horizontal

Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: horizontal
Note:




6-18GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	11650.000	26.38	21.06	47.44	54.00	6.56	Average
2	11650.000	39.65	21.06	60.71	74.00	13.29	Peak
3	17475.000	34.85	28.62	63.47	68.20	4.73	Peak
4	17853.570	16.46	31.22	47.68	54.00	6.32	Average
5	17853.570	29.75	31.22	60.97	74.00	13.03	Peak

Horizontal

Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: Horizontal
Note:




18-26.5GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	26306.160	36.74	6.91	43.65	-----	-----	Average
2	26306.160	49.39	6.91	56.30	68.20	11.90	Peak

Horizontal

Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: Horizontal
Note:




26.5-40GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	39211.440	37.41	10.23	47.64	54.00	6.36	Average
2	39211.440	50.70	10.23	60.93	74.00	13.07	Peak

Vertical

Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: vertical
Note:




1-6GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5741.948	35.41	13.00	48.41	68.20	19.79	Peak

Vertical

Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: vertical
Note:




6-18GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	11650.000	25.22	21.06	46.28	54.00	7.72	Average
2	11650.000	38.11	21.06	59.17	74.00	14.83	Peak
3	17475.000	32.07	28.62	60.69	68.20	7.51	Peak
4	17774.360	16.91	30.71	47.62	54.00	6.38	Average
5	17774.360	30.14	30.71	60.85	74.00	13.15	Peak

Vertical

Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: vertical
Note:




18-26.5GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	26323.160	36.51	6.86	43.37	-----	-----	Average
2	26323.160	49.21	6.86	56.07	68.20	12.13	Peak

Vertical

Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: vertical
Note:




26.5-40GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	39324.860	37.46	10.18	47.64	54.00	6.36	Average
2	39324.860	50.68	10.18	60.86	74.00	13.14	Peak

Band edge Test plots

802.11a 5745MHz

Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: Horizontal
Note:




Horizontal

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5636.495	33.82	12.78	46.60	68.20	21.60	Peak
2	5695.757	39.59	13.00	52.59	102.07	49.48	Peak
3	5718.982	52.02	13.01	65.03	110.52	45.49	Peak
4	5723.753	58.74	13.00	71.74	119.36	47.62	Peak

802.11a 5745MHz

Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: vertical
Note:




Vertical

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5645.047	34.11	12.82	46.93	68.20	21.27	Peak
2	5698.188	41.18	13.00	54.18	103.86	49.68	Peak
3	5718.382	49.90	13.01	62.91	110.35	47.44	Peak
4	5723.813	56.71	13.00	69.71	119.49	49.78	Peak

802.11a 5825 MHz

Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: Horizontal
Note:




Horizontal

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5850.366	51.45	13.05	64.50	121.36	56.86	Peak
2	5857.235	46.69	13.08	59.77	110.17	50.40	Peak
3	5882.876	37.69	13.17	50.86	99.35	48.49	Peak
4	5965.513	34.12	13.24	47.36	68.20	20.84	Peak

802.11a 5825 MHz

Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: vertical
Note:

Date: 2023-09-25




Vertical

No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector
1	5853.665	50.56	13.06	63.62	113.84	50.22	Peak
2	5856.487	48.59	13.08	61.67	110.38	48.71	Peak
3	5878.558	39.48	13.15	52.63	102.56	49.93	Peak
4	5976.361	34.46	13.27	47.73	68.20	20.47	Peak

802.11ac20 5745 MHz

Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: Horizontal
Note:




Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5636.795	33.78	12.78	46.56	68.20	21.64	Peak
2	5698.428	40.82	13.01	53.83	104.04	50.21	Peak
3	5717.332	52.17	13.01	65.18	110.05	44.87	Peak
4	5723.843	59.42	13.00	72.42	119.56	47.14	Peak

802.11ac20 5745 MHz

Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: vertical
Note:




Vertical

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5640.336	34.19	12.81	47.00	68.20	21.20	Peak
2	5695.037	40.58	13.00	53.58	101.54	47.96	Peak
3	5719.522	52.20	13.01	65.21	110.67	45.46	Peak
4	5723.783	61.31	13.00	74.31	119.43	45.12	Peak

802.11ac20 5825 MHz

Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: Horizontal
Note:




Horizontal

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5850.672	50.69	13.05	63.74	120.67	56.93	Peak
2	5856.589	48.09	13.08	61.17	110.35	49.18	Peak
3	5877.266	37.80	13.15	50.95	103.52	52.57	Peak
4	5952.216	34.49	13.20	47.69	68.20	20.51	Peak

802.11ac20 5825 MHz

Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: vertical
Note:

Date: 2023-09-25




Vertical

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5851.420	53.45	13.06	66.51	118.96	52.45	Peak
2	5858.018	50.12	13.08	63.20	109.95	46.75	Peak
3	5876.823	40.58	13.15	53.73	103.85	50.12	Peak
4	5945.823	34.91	13.20	48.11	68.20	20.09	Peak

802.11ac40 5755 MHz

Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: Horizontal
Note:




Horizontal

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5648.632	37.82	12.84	50.66	68.20	17.54	Peak
2	5698.010	48.34	13.00	61.34	103.73	42.39	Peak
3	5717.802	61.01	13.01	74.02	110.19	36.17	Peak
4	5721.950	62.14	13.00	75.14	115.25	40.11	Peak

802.11ac40 5755 MHz

Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: vertical
Note:

Date: 2023-09-25




Vertical

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5644.687	36.09	12.82	48.91	68.20	19.29	Peak
2	5693.113	45.35	12.99	58.34	100.12	41.78	Peak
3	5717.257	57.86	13.01	70.87	110.03	39.16	Peak
4	5722.358	59.52	13.00	72.52	116.18	43.66	Peak

802.11ac40 5795MHz

Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: Horizontal
Note:




Horizontal

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5852.714	46.52	13.06	59.58	116.01	56.43	Peak
2	5855.277	47.02	13.07	60.09	110.72	50.63	Peak
3	5881.364	41.79	13.17	54.96	100.47	45.51	Peak
4	5948.494	35.06	13.19	48.25	68.20	19.95	Peak

802.11ac40 5795MHz

Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: vertical
Note:

Date: 2023-09-25




Vertical

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5850.992	43.34	13.05	56.39	119.94	63.55	Peak
2	5857.042	42.82	13.08	55.90	110.23	54.33	Peak
3	5881.280	40.40	13.17	53.57	100.54	46.97	Peak
4	5956.896	34.46	13.21	47.67	68.20	20.53	Peak

802.11ac80 5775 MHz


Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: Horizontal
Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5646.045	40.95	12.83	53.78	68.20	14.42	Peak
2	5695.561	52.10	13.00	65.10	101.93	36.83	Peak
3	5714.953	55.25	13.01	68.26	109.39	41.13	Peak
4	5720.800	56.13	13.01	69.14	112.63	43.49	Peak
5	5850.696	47.75	13.05	60.80	120.61	59.81	Peak
6	5857.432	46.38	13.08	59.46	110.12	50.66	Peak
7	5877.120	43.00	13.15	56.15	103.63	47.48	Peak
8	5927.894	35.76	13.21	48.97	68.20	19.23	Peak

802.11ac80 5775 MHz

Project No.: CR230745209-RF
Tester: Tao Zhu
Polarization: vertical
Note:



Vertical

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5644.343	39.02	12.82	51.84	68.20	16.36	Peak
2	5697.855	49.23	13.00	62.23	103.62	41.39	Peak
3	5712.807	51.07	13.01	64.08	108.79	44.71	Peak
4	5724.057	51.28	13.00	64.28	120.05	55.77	Peak
5	5850.992	47.68	13.05	60.73	119.94	59.21	Peak
6	5858.246	46.42	13.08	59.50	109.89	50.39	Peak
7	5877.268	42.74	13.15	55.89	103.52	47.63	Peak
8	5949.284	36.35	13.19	49.54	68.20	18.66	Peak

4.3 Emission Bandwidth:

Serial Number:	2BCU-1	Test Date:	2023-09-29
Test Site:	RF	Test Mode:	Transmitting
Tester:	Ken Tang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.9	Relative Humidity: (%)	60	ATM Pressure: (kPa)	100.2
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101943	2023-03-31	2024-03-30
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK- 18G	21060301	Each time	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:


5150-5250 MHz:

Test Modes	Test Frequency (MHz)	26 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
802.11a	5180	21.36	16.74
	5200	23.24	16.74
	5240	22.40	16.74
802.11ac vht20	5180	22.08	17.66
	5200	25.88	17.70
	5240	23.84	17.70
802.11ac vht40	5190	41.92	36.28
	5230	41.20	36.28
802.11ac vht80	5210	113.28	76.08
Note: Test only was performed at Chain 0. The 99% Occupied Bandwidth have not fall into the band 5250-5350MHz, please refer to the test plots of 99% Occupied Bandwidth.			




5725-5850 MHz:




Test Modes	Test Frequency (MHz)	6 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
802.11a	5745	15.16	16.70
	5785	15.16	16.70
	5825	15.16	16.58
802.11ac vht20	5745	15.16	17.62
	5785	15.16	17.66
	5825	15.16	17.66
802.11ac vht40	5755	35.20	36.20
	5795	35.20	36.20
802.11ac vht80	5775	75.84	75.76
Note: 6dB Emission Bandwidth Limit: ≥ 0.5 MHz Test only was performed at Chain 0. The 99% Occupied Bandwidth have not fall into the band 5470-5725MHz, please refer to the test plots of 99% Occupied Bandwidth.			

5150-5250MHz:









26dB Emission Bandwidth

802.11ac vht20
Lowest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 29.SEP.2023 18:01:38802.11ac vht20
Middle ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 29.SEP.2023 18:10:32802.11ac vht20
Highest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 29.SEP.2023 18:07:37




26dB Emission Bandwidth802.11ac vht40
Lowest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 29.SEP.2023 18:24:47802.11ac vht40
Highest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 29.SEP.2023 18:27:06802.11ac80
Middle ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 29.SEP.2023 18:36:06

99% Emission Bandwidth


802.11a
Lowest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 29.SEP.2023 16:59:19802.11a
Middle ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 29.SEP.2023 17:02:04802.11a
Highest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 29.SEP.2023 17:04:48


99% Emission Bandwidth802.11ac vht20
Lowest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 29.SEP.2023 18:00:44802.11ac vht20
Middle ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 29.SEP.2023 18:09:45802.11ac vht20
Highest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 29.SEP.2023 18:07:02

99% Emission Bandwidth




802.11ac vht40
Lowest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 29.SEP.2023 18:24:26802.11ac vht40
Highest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 29.SEP.2023 18:26:45802.11ac80
Middle ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 29.SEP.2023 18:35:45

5725-5850MHz:











99% Emission Bandwidth

802.11a
Lowest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 29.SEP.2023 17:08:54802.11a
Middle ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 29.SEP.2023 17:16:51802.11a
Highest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 29.SEP.2023 17:54:03

99% Emission Bandwidth

802.11ac vht20
Lowest Channel802.11ac vht20
Middle Channel802.11ac vht20
Highest Channel

99% Emission Bandwidth

802.11ac vht40
Lowest Channel802.11ac vht40
Highest Channel802.11ac80
Middle Channel

4.4 Maximum Conducted Output Power:

Serial Number:	2BCU-1	Test Date:	2023/11/15
Test Site:	RF	Test Mode:	Transmitting
Tester:	Ken Tang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.1	Relative Humidity: (%)	54	ATM Pressure: (kPa)	101
----------------------	------	------------------------------	----	------------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Anritsu	Power Meter	ML2495A	1106009	2023/8/4	2024/8/3
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Anritsu	Pulse Power Sensor	MA2411A	10780	2023/8/4	2024/8/3

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

5150-5250 MHz:

Test Modes	Test Frequency (MHz)	Max. Conducted Average Output Power (dBm)			
		Chain 0	Chain 1	Total	Limit
802.11a	5180	10.46	10.24	13.36	24
	5200	10.63	10.44	13.55	24
	5240	9.87	10.59	13.26	24
802.11ac vht20	5180	10.50	9.58	13.07	24
	5200	10.54	9.90	13.24	24
	5240	9.97	10.61	13.31	24
802.11ac vht40	5190	9.83	10.15	13.00	24
	5230	10.19	10.41	13.31	24
802.11ac vht80	5210	9.98	9.44	12.73	24

Note:

The device can operate as a client device.

The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices:

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$

Antenna Gain:	-1.74	dB	Directional gain:	-1.74	dB
---------------	-------	----	-------------------	-------	----

5725-5850 MHz:

Test Modes	Test Frequency(MHz)	Max. Conducted Average Output Power(dBm)			
		Chain 0	Chain 1	Total	Limit
802.11a	5745	10.31	10.4	13.37	30
	5785	10.58	10.57	13.59	30
	5825	10.94	10.63	13.80	30
802.11ac vht20	5745	9.87	10.33	13.12	30
	5785	10.45	10.63	13.55	30
	5825	10.81	11.21	14.02	30
802.11ac vht40	5755	10.26	11.28	13.81	30
	5795	10.69	10.44	13.58	30
802.11ac vht80	5775	10.12	9.82	12.98	30
Note: The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices: Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$					
Antenna Gain:	-1.74	dB	Directional gain:	-1.74	dB

4.5 Maximum power spectral density:

Serial Number:	2BCU-1	Test Date:	2023/11/15
Test Site:	RF	Test Mode:	Transmitting
Tester:	Ken Tang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.1	Relative Humidity: (%)	54	ATM Pressure: (kPa)	101
----------------------	------	------------------------------	----	---------------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101943	2023-03-31	2024-03-30
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

5150-5250 MHz:

Test Modes	Test Frequency (MHz)	Maximum Power Spectral Density (dBm/MHz)			
		Chain 0	Chain 1	Total	Limit
802.11a	5180	0.75	-0.18	3.32	11
	5200	0.38	0.46	3.43	11
	5240	-0.49	0.82	3.22	11
802.11ac vht20	5180	0.51	-0.55	3.02	11
	5200	0.79	0.22	3.52	11
	5240	-0.23	0.28	3.04	11
802.11ac vht40	5190	-3.25	-2.9	-0.06	11
	5230	-2.91	-2.59	0.26	11
802.11ac vht80	5210	-7.38	-8.34	-4.82	11

Note:
 The device can operate as a client device.
 Method SA-1 in KDB 789033 D02 General UNII Test Procedures New Rules v02r01 was used for PSD test.
 The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices:
 Array Gain = $10 \log(N_{\text{ANT}}/N_{\text{SS}})$ dB

Antenna Gain:	-1.74	dBi	Directional gain:	1.26	dBi
---------------	-------	-----	-------------------	------	-----

5725-5850 MHz:




Test Modes	Test Frequency (MHz)	Maximum Power Spectral Density (dBm/500kHz)			
		Chain 0	Chain 1	Total	Limit
802.11a	5745	-2.78	-2.37	0.44	30
	5785	-2.3	-2.11	0.81	30
	5825	-2.04	-1.75	1.12	30
802.11ac vht20	5745	-2.75	-2.54	0.37	30
	5785	-2.53	-2.41	0.54	30
	5825	-2.3	-1.68	1.03	30
802.11ac vht40	5755	-5.4	-4.85	-2.11	30
	5795	-5.01	-5.53	-2.25	30
802.11ac vht80	5775	-10.58	-10.42	-7.49	30

Note:
 Method SA-1 in KDB 789033 D02 General UNII Test Procedures New Rules v02r01 was used for PSD test.
 The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices:
 Array Gain = $10 \log(N_{\text{ANT}}/N_{\text{SS}})$ dB




Antenna Gain:	-1.74	dBi	Directional gain:	1.26	dBi
---------------	-------	-----	-------------------	------	-----

5150-5250MHz (Chain 0):




Maximum power spectral density

802.11a
Lowest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 19:37:36802.11a
Middle ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:05:20802.11a
Highest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:08:05

Maximum power spectral density




802.11ac vht20
Lowest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:11:05802.11ac vht20
Middle ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:12:23802.11ac vht20
Highest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:13:23

Maximum power spectral density




802.11ac vht40
Lowest Channel802.11ac vht40
Highest Channel802.11ac80
Middle Channel

5150-5250MHz (Chain 1):




Maximum power spectral density

802.11a
Lowest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:41:36802.11a
Middle ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:42:36802.11a
Highest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:44:12

Maximum power spectral density



802.11ac vht20
Lowest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:57:09802.11ac vht20
Middle ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:59:05802.11ac vht20
Highest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:59:59

Maximum power spectral density




802.11ac vht40
Lowest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 21:11:28802.11ac vht40
Highest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 21:13:03802.11ac80
Middle ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 21:29:15

5725-5850MHz (Chain 0)




Maximum power spectral density

802.11a
Lowest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:20:57802.11a
Middle ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:27:55802.11a
Highest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:28:53

Maximum power spectral density




802.11ac vht20
Lowest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:30:14802.11ac vht20
Middle ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:31:10802.11ac vht20
Highest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:32:04

Maximum power spectral density




802.11ac vht40
Lowest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:35:20802.11ac vht40
Highest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:36:20802.11ac80
Middle ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:37:54

5725-5850MHz (Chain 1)




Maximum power spectral density

802.11a
Lowest Channel802.11a
Middle Channel802.11a
Highest Channel

Maximum power spectral density

802.11ac vht20
Lowest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 21:01:35802.11ac vht20
Middle ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 21:03:44802.11ac vht20
Highest ChannelProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 21:08:09

Maximum power spectral density

802.11ac vht40
Lowest Channel802.11ac vht40
Highest Channel802.11ac80
Middle Channel

4.6 Duty Cycle:

Serial Number:	2BCU-1	Test Date:	2023/11/15
Test Site:	RF	Test Mode:	Transmitting
Tester:	Ken Tang	Test Result:	N/A

Environmental Conditions:

Temperature: (°C)	25.9	Relative Humidity: (%)	60	ATM Pressure: (kPa)	100.2
----------------------	------	------------------------------	----	------------------------	-------


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101943	2023-03-31	2024-03-30
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Test Modes	Ton (ms)	Ton+off (ms)	Duty cycle (%)	1/T (Hz)	Duty Factor (dB)	VBW Setting (kHz)
802.11a	100	100	100.00	/	/	10
802.11ac vht20	100	100	100.00	/	/	10
802.11ac vht40	100	100	100.00	/	/	10
802.11ac vht80	100	100	100.00	/	/	10




Duty Cycle

802.11ac vht20




ProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:10:25

802.11ac vht40



ProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 21:35:36

802.11ac80



ProjectNo.:CR230745209 Tester:Ken Tang
Date: 15.NOV.2023 20:17:20

5. EUT PHOTOGRAPHS

Please refer to the attachment CR230745209-EXP EUT EXTERNAL PHOTOGRAPHS and
CR230745209-INP EUT INTERNAL PHOTOGRAPHS

6. TEST SETUP PHOTOGRAPHS

Please refer to the attachment CR230745209-00D-TSP TEST SETUP PHOTOGRAPHS.

===== END OF REPORT =====