



TESTING LABORATORY
CERTIFICATE #4820.01



FCC PART 22H, PART 24E MEASUREMENT AND TEST REPORT

For

HONG KONG IPRO TECHNOLOGY CO., LIMITED

FLAT/RM A3, 9/F SILVERCORP INT TOWER 707-713 NATHAN RD MONGKOK,
HONGKONG

FCC ID:PQ4IPROAMBER7S

Report Type: Original Report	Product Type: Smart Phone
Report Number: RDG190725003-00D	
Report Date: 2019-08-24	
Reviewed By:	Jerry Zhang EMC Manager
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
JUSTIFICATION	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
CONFIGURATION OF TEST SETUP	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
FCC §1.1310 & §2.1093- RF EXPOSURE	9
APPLICABLE STANDARD	9
TEST RESULT	9
FCC §2.1047 - MODULATION CHARACTERISTIC	10
FCC § 2.1046, § 22.913 (A) & § 24.232 (C) - RF OUTPUT POWER.....	11
APPLICABLE STANDARD	11
TEST PROCEDURE	11
TEST EQUIPMENT LIST AND DETAILS.....	14
TEST DATA	14
FCC §2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH	17
APPLICABLE STANDARD	17
TEST PROCEDURE	17
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST DATA	18
FCC §2.1051, §22.917(A) & §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	23
APPLICABLE STANDARD	23
TEST PROCEDURE	23
TEST EQUIPMENT LIST AND DETAILS.....	23
TEST DATA	23
FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS	29
APPLICABLE STANDARD	29
TEST PROCEDURE	29
TEST EQUIPMENT LIST AND DETAILS.....	30
TEST DATA	30
FCC §22.917(A) & §24.238(A)- BAND EDGES.....	33
APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST EQUIPMENT LIST AND DETAILS.....	33
TEST DATA	34

FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY43

 APPLICABLE STANDARD43

 TEST PROCEDURE43

 TEST EQUIPMENT LIST AND DETAILS.....44

 TEST DATA44

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:		Smart Phone
EUT Model:		Amber7S
Operation modes:		GSM Voice, GPRS Data, WCDMA(R99 (Voice+Data), HSDPA/HSUPA/HSPA+)
Operation Frequency:		GSM 850: 824-849 MHz(TX); 869-894 MHz(RX) PCS 1900: 1850-1910 MHz(TX); 1930-1990 MHz(RX) WCDMA Band 2: 1850-1910 MHz(TX); 1930-1990 MHz(RX) WCDMA Band 5: 824-849 MHz(TX); 869-894 MHz(RX)
Maximum Output Power: (Conducted)		GSM 850 : 30.20dBm; PCS 1900: 29.50 dBm WCDMA Band 2: 22.26 dBm; WCDMA Band 5: 22.43 dBm
Modulation Type:		GMSK, BPSK, QPSK, 16QAM
Rated Input Voltage:		3.8VDC from battery and 5VDC from adapter
Adapter Information	Model:	NTR-S01
	Input:	AC 100V-240V 50/60Hz 0.2A
	Output:	DC 5.0V 1.0A
External Dimension:		150mm(L)*71mm(W)*9mm(H)
Serial Number:		190725003
EUT Received Date:		2019-07-25

Objective

This report is prepared on behalf of **HONG KONG IPRO TECHNOLOGY CO.,LIMITED** in accordance with: Part 2-Subpart J, Part 22-Subpart H, and Part 24-Subpart E of the Federal Communications Commission's rules.

The objective is to determine compliance with FCC Rules for output power, modulation characteristic, occupied bandwidth, spurious emissions at antenna terminal, spurious radiated emission, frequency stability and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: PQ4IPROAMBER7S
FCC Part 15C DSS submissions with FCC ID: PQ4IPROAMBER7S
FCC Part 15C DTS submissions with FCC ID: PQ4IPROAMBER7S

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services
Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-D-2010.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp.(Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Unwanted Emissions, radiated	30MHz ~ 1GHz: 5.85 dB 1G~26.5GHz: 5.23 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

SYSTEM TEST CONFIGURATION

Justification

The EUT was configured for testing according to TIA/EIA-603-D 2010.


Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
R&S	Universal Radio Communication Tester	CMU200	106 891
Un-Known	ANTENNA	Un-Known	Un-Known

Configuration of Test Setup



Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310, §2.1093	RF Exposure	Compliance
§2.1046; § 22.913 (a); § 24.232 (c);	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905 § 22.917; § 24.238	Occupied Bandwidth	Compliance
§ 2.1051, § 22.917 (a); § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053 § 22.917 (a); § 24.238 (a)	Spurious Radiation Emissions	Compliance
§ 22.917 (a); § 24.238 (a)	Out of band emission, Band Edge	Compliance
§ 2.1055 § 22.355; § 24.235	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

FCC §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliance, please refer to the SAR report: RDG190725003-20.

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FCC § 2.1046, § 22.913 (a) & § 24.232 (c) - RF OUTPUT POWER

Applicable Standard

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

According to §24.232 (d) Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

Test Procedure

GSM/GPRS/EGPRS

Function: Menu select > GSM Mobile Station > GSM 850/1900

Press Connection control to choose the different menus

Press RESET > choose all the reset all settings

Connection Press Signal Off to turn off the signal and change settings

Network Support > GSM + GPRS or GSM + EGSM

Main Service > Packet Data

Service selection > Test Mode A – Auto Slot Config. off

MS Signal Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting

> Slot configuration > Uplink/Gamma

> 33 dBm for GPRS 850

> 30 dBm for GPRS 1900

> 27 dBm for EGPRS 850

> 26 dBm for EGPRS 1900

BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel

Frequency Offset > + 0 Hz

Mode > BCCH and TCH

BCCH Level > -85 dBm (May need to adjust if link is not stable)

BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]

Channel Type > Off

P0 > 4 dB

Slot Config > Unchanged (if already set under MS signal)

TCH > choose desired test channel

Hopping > Off

Main Timeslot > 3

Network Coding Scheme > CS4 (GPRS) and MCS5 (EGPRS)

Bit Stream > 2E9-1 PSR Bit Stream

AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input

Connection Press Signal on to turn on the signal and change settings

WCDMA-Release 99

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification. The EUT has a nominal maximum output power of 24dBm (+1.7/-3.7).

WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c / β_d	8/15

WCDMA HSDPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subset	1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	β_d (SF)	64			
	β_c / β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
	MPR(dB)	0	0	0.5	0.5
HSDPA Specific Settings	DACK	8			
	DNAK	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback	4ms			
	CQI Repetition Factor	2			
	$A_{hs} = \beta_{hs} / \beta_c$	30/15			

WCDMA HSUPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subset	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30/15	2/15	5/15
	β_c/β_d	11/15	6/15	15/9	2/15	-
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	CM(dB)	1.0	3.0	2.0	3.0	1.0
	MPR(dB)	0	2	1	2	0
HSDPA Specific Settings	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback	4ms				
	CQI Repetition Factor	2				
	$A_{hs}=\beta_{hs}/\beta_c$	30/15				
HSUPA Specific Settings	DE-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E_FCI	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E-TFCI PO4 E-TFCI 92 E-TFCI PO 18	E-TFCI 11 E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESR3	102453	2019-06-26	2020-06-26
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2019-05-06	2020-05-06
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-02	2018-09-05	2019-09-05
R&S	Universal Radio Communication Tester	CMU200	106 891	2018-12-14	2019-12-14
Agilent	Signal Generator	E8247C	MY43321350	2018-12-10	2019-12-10
Agilent	Spectrum Analyzer	E4440A	SG43360054	2019-05-09	2020-05-09
TDK RF	Horn Antenna	HRN-0118	130 084	2018-10-12	2021-10-12
ETS-Lindgren	Horn Antenna	3115	000 527 35	2018-10-12	2021-10-12
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-02	2018-09-05	2019-09-05

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	27.9°C
Relative Humidity:	63%
ATM Pressure:	100.2kPa
Tester:	Lucy Lu
Test Date:	2019-08-08

Test Result: Compliance

Conducted Output Power**Cellular Band & PCS Band**

Band	Channel No.	Conducted Peak Output Power (dBm)				
		GSM	GPRS 1 TX Slot	GPRS 2 TX Slot	GPRS 3 TX Slot	GPRS 4 TX Slot
Cellular	128	30.10	30.01	29.35	27.8	26.71
	190	30.20	30.08	29.42	27.83	26.72
	251	30.20	30.08	29.41	27.71	26.68
PCS	512	29.50	29.35	28.84	27.32	26.71
	661	29.40	29.25	28.84	27.51	26.63
	810	29.30	29.13	28.79	27.57	26.29

WCDMA Band 2

Mode	3GPP Sub Test	Low Channel		Middle Channel		High Channel	
		Ave. Power (dBm)	PAR (dB)	Ave. Power (dBm)	PAR (dB)	Ave. Power (dBm)	PAR (dB)
Rel 99	1	22.16	2.80	22.26	2.92	22.15	2.92
HSDPA	1	20.23	3.80	20.34	4.28	20.17	3.80
	2	20.18	3.80	20.21	4.25	20.07	3.75
	3	20.11	3.70	20.2	4.24	20.04	3.60
	4	20.07	3.80	20.07	4.21	20.02	3.45
HSUPA	1	20.18	6.52	20.33	4.84	20.25	4.60
	2	20.14	5.88	20.22	4.87	20.12	4.20
	3	20.13	5.20	20.12	4.78	20.13	4.21
	4	20.14	5.40	20.12	4.70	20.10	4.50
	5	20.10	5.60	20.14	4.67	20.01	4.21
HSPA+ (16QAM)	1	21.10	5.10	21.4	4.54	21.21	4.40

WCDMA Band 5

Mode	3GPP Sub Test	Low Channel		Middle Channel		High Channel	
		Ave. Power (dBm)	PAR (dB)	Ave. Power (dBm)	PAR (dB)	Ave. Power (dBm)	PAR (dB)
Rel 99	1	22.28	3.28	22.43	3.16	22.39	3.12
HSDPA	1	21.22	4.08	21.34	4.00	21.24	3.88
	2	21.14	4.10	21.22	3.80	21.15	3.64
	3	21.12	4.03	21.3	4.30	21.16	3.14
	4	21.01	4.04	21.12	4.30	21.31	3.20
HSUPA	1	21.42	5.08	21.42	6.64	21.41	6.52
	2	21.41	4.80	21.38	6.23	20.17	6.54
	3	21.39	4.21	21.36	6.30	20.14	6.94
	4	21.35	4.25	21.24	6.40	20.18	6.45
	5	21.32	4.30	21.21	6.52	20.12	6.31
HSPA+ (16QAM)	1	21.25	4.24	21.32	6.34	21.35	6.32

ERP & EIRP

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM 850 Middle Channel								
836.60	H	92.39	17.47	0.00	0.97	16.50	38.45	21.95
836.60	V	101.08	29.29	0.00	0.97	28.32	38.45	10.13
WCDMA Band V Middle Channel								
836.60	H	78.71	3.79	0.00	0.97	2.82	38.45	35.63
836.60	V	91.36	19.57	0.00	0.97	18.60	38.45	19.85
PCS 1900 Middle Channel								
1880.00	H	92.51	19.90	11.66	2.66	28.90	33.00	4.10
1880.00	V	86.85	14.38	11.66	2.66	23.38	33.00	9.62
WCDMA Band II Middle Channel								
1880.00	H	86.24	13.63	11.66	2.66	22.63	33.00	10.37
1880.00	V	80.86	8.39	11.66	2.66	17.39	33.00	15.61

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = Substituted Level - Cable loss + Antenna Gain
- 3) Margin = Limit-Absolute Level


FCC §2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH**Applicable Standard**

FCC §2.1049, §22.917, §22.905, §24.238

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The 26 dB & 99% bandwidth was recorded.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
R&S	Spectrum Analyzer	FSP 38	100478	2018-12-10	2019-12-10
Unknown	Coaxial Cable	C-SJ00-0010	C0010/02	Each time	/
Unknown	Coaxial Cable	C-SJ00-0010	C0010/05	Each time	/
E-Microwave	Two-way Splitter	ODP-1-6-2S	OE0120142	Each time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Temperature:	27.3°C
Relative Humidity:	65%
ATM Pressure:	100.3kPa
Tester:	Chris Mo
Test Date:	2019-08-12

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table and plots.


Band	Test Channel	Mode	99% Occupied Bandwidth (MHz)	26 dB Occupied Bandwidth (MHz)
Cellular	Middle	GSM	0.245	0.321
PCS		GSM	0.246	0.320
WCDMA Band 2		Rel 99	4.160	4.740
		HSDPA	4.160	4.720
		HSUPA	4.168	4.720
WCDMA Band 5		Rel 99	4.180	4.740
		HSDPA	4.160	4.740
		HSUPA	4.160	4.740

GSM Cellular 850




Date: 12.AUG.2019 21:45:18

GSM PCS1900




Date: 12.AUG.2019 21:17:13

WCDMA Band2 Rel 99




Date: 12.AUG.2019 15:37:23

WCDMA Band2 HSDPA




Date: 12.AUG.2019 15:44:33

WCDMA Band 2 HSUPA




Date: 12.AUG.2019 15:44:33

WCDMA Band 5 Rel 99




Date: 12.AUG.2019 17:05:36

WCDMA Band5 HSDPA



Date: 12.AUG.2019 16:53:34

WCDMA Band5 HSUPA



Date: 12.AUG.2019 17:40:32

FCC §2.1051, §22.917(a) & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standard

FCC §2.1051, §22.917(a), §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/02	Each time	/
Unknown	Coaxial Cable	C-SJ00-0010	C0010/05	Each time	/
E-Microwave	Two-way Splitter	ODP-1-6-2S	OE0120142	Each time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).



Test Data

Environmental Conditions


Temperature:	27.3°C
Relative Humidity:	65%
ATM Pressure:	100.3kPa
Tester:	Chris Mo
Test Date:	2019-08-12

Test Result: Compliance. Please refer to the following plots.

GSM 850 Middle Channel




PCS 1900 Middle Channel




Date: 12.AUG.2019 21:27:21


Fundamental





Date: 12.AUG.2019 21:30:55




WCDMA Band2 Rel 99 Middle Channel






WCDMA Band5 Rel 99 Middle Channel



Date: 12.AUG.2019 23:20:59



Date: 12.AUG.2019 23:20:15

FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS

Applicable Standard

FCC § 2.1053, §22.917, § 24.238

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg (\text{TXpwr in Watts}/0.001)$ – the absolute level

Spurious attenuation limit in dB = $43 + 10 \text{Log}_{10} (\text{power out in Watts})$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESR3	102453	2019-06-26	2020-06-26
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2019-05-06	2020-05-06
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-02	2018-09-05	2019-09-05
HP	Amplifier	8447D	2727A05902	2018-09-05	2019-09-05
Agilent	Signal Generator	E8247C	MY43321350	2018-12-10	2019-12-10
Agilent	Spectrum Analyzer	E4440A	SG43360054	2019-05-09	2020-05-09
TDK RF	Horn Antenna	HRN-0118	130 084	2018-10-12	2021-10-12
ETS-Lindgren	Horn Antenna	3115	000 527 35	2018-10-12	2021-10-12
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-02	2018-09-05	2019-09-05
MITEQ	Amplifier	AFS42-00101800-25-S-42	2001271	2018-09-05	2019-09-05
Sinoscite	Band-stop filter	BSF824-862MS-1438-001	1438001	2019-06-16	2020-06-16
Sinoscite	Band-stop filter	BSF1850-1910MS-0935V2	0935V2	2019-06-16	2020-06-16
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2016-11-18	2019-11-18
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2016-11-18	2019-11-18
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2019-06-27	2020-06-27

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Test Items	Radiation Below 1GHz	Radiation Above 1GHz
Temperature:	27.7°C	26.4 °C
Relative Humidity:	50%	63 %
ATM Pressure:	100.2 kPa	100.2 kPa
Tester:	Tyler Pan	Lucy Lu
Test Date:	2019-08-08	2019-08-08

Test Result: Compliance.

EUT Operation Mode: Transmitting

Cellular Band (PART 22H)**30 MHz-10 GHz:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM850 Middle Channel, Frequency:836.600 MHz								
1673.200	H	66.82	-47.39	10.6	0.73	-37.5	-13.0	24.5
1673.200	V	65.03	-49.78	10.6	0.73	-39.9	-13.0	26.9
2509.800	H	56.07	-56.95	13.1	1.25	-45.1	-13.0	32.1
2509.800	V	55.42	-57.63	13.1	1.25	-45.8	-13.0	32.8
3346.400	H	46.79	-63.87	13.8	1.61	-51.7	-13.0	38.7
3346.400	V	46.32	-64.39	13.8	1.61	-52.2	-13.0	39.2
2900.000	H	53.46	-58.34	13.9	1.35	-45.8	-13.0	32.8
2900.000	V	51.33	-60.77	13.9	1.35	-48.2	-13.0	35.2
70.260	H	64.54	-48.48	-4.9	0.24	-53.6	-13.0	40.6
290.920	V	71.42	-39.05	0.0	0.52	-39.6	-13.0	26.6
WCDMA Band 5 Middle Channel: 836.6 MHz								
1673.200	H	59.51	-54.7	10.6	0.73	-44.8	-13.0	31.8
1673.200	V	57.94	-56.87	10.6	0.73	-47.0	-13.0	34.0
2509.800	H	48.35	-64.67	13.1	1.25	-52.8	-13.0	39.8
2509.800	V	46.77	-66.28	13.1	1.25	-54.4	-13.0	41.4
3346.400	H	47.21	-63.45	13.8	1.61	-51.2	-13.0	38.2
3346.400	V	46.36	-64.35	13.8	1.61	-52.1	-13.0	39.1
2909.000	H	52.63	-59.06	13.9	1.36	-46.5	-13.0	33.5
2909.000	V	50.72	-61.26	13.9	1.36	-48.7	-13.0	35.7
93.600	H	77.28	-31.76	0.0	0.32	-32.1	-13.0	19.1
172.500	V	71.29	-40.95	0.0	0.43	-41.4	-13.0	28.4

PCS Band (PART 24E)**30 MHz-20 GHz:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
PCS1900 Middle Channel, Frequency:1880 MHz								
3760.000	H	48.64	-60.16	13.8	1.63	-48.0	-13.0	35.0
3760.000	V	47.25	-61.42	13.8	1.63	-49.3	-13.0	36.3
5640.000	H	46.34	-59.69	14.0	1.31	-47.0	-13.0	34.0
5640.000	V	46.05	-59.86	14.0	1.31	-47.2	-13.0	34.2
388.700	H	47.24	-58	0.0	0.6	-58.6	-13.0	45.6
165.500	V	49.37	-62.93	0.0	0.41	-63.3	-13.0	50.3
WCDMA Band 2 Middle Channel: 1880 MHz								
3760.000	H	47.65	-61.15	13.8	1.63	-49.0	-13.0	36.0
3760.000	V	47.21	-61.46	13.8	1.63	-49.3	-13.0	36.3
5640.000	H	46.39	-59.64	14.0	1.31	-46.9	-13.0	33.9
5640.000	V	45.87	-60.04	14.0	1.31	-47.3	-13.0	34.3
89.810	H	52.36	-58.28	0.0	0.36	-58.6	-13.0	45.6
176.400	V	48.24	-63.97	0.0	0.44	-64.4	-13.0	51.4

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = Substituted Level - Cable loss + Antenna Gain
- 3) Margin = Limit-Absolute Level


FCC §22.917(a) & §24.238(a)- BAND EDGES**Applicable Standard**

FCC § 2.1053, §22.917, § 24.238.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/02	Each time	/
Unknown	Coaxial Cable	C-SJ00-0010	C0010/05	Each time	/
E-Microwave	Two-way Splitter	ODP-1-6-2S	OE0120142	Each time	/


* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data
Environmental Conditions


Temperature:	27.3°C
Relative Humidity:	65%
ATM Pressure:	100.3kPa
Tester:	Chris Mo
Test Date:	2019-08-12

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following plots.


GSM 850, Left Band Edge

GSM 850, Right Band Edge




Date: 12.AUG.2019 22:03:48

GSM 1900, Left Band Edge




Date: 12.AUG.2019 21:24:34

GSM 1900, Right Band Edge




Date: 12.AUG.2019 21:25:40

WCDMA Band 2 Rel 99, Left Band Edge




Date: 12.AUG.2019 23:07:24

WCDMA Band 2 Rel 99, Right Band Edge




Date: 12.AUG.2019 23:08:10

WCDMA Band 2 HSDPA, Left Band Edge




Date: 12.AUG.2019 23:09:46


WCDMA Band 2 HSDPA, Right Band Edge



WCDMA Band 2 HSUPA, Left Band Edge




WCDMA Band 2 HSUPA, Right Band Edge




Date: 12.AUG.2019 23:11:20

WCDMA Band 5 Rel 99, Left Band Edge




Date: 12.AUG.2019 23:02:06

WCDMA Band 5 Rel 99, Right Band Edge




Date: 12.AUG.2019 23:02:45

WCDMA Band 5 HSDPA, Left Band Edge




Date: 12.AUG.2019 22:57:35

WCDMA Band 5 HSDPA, Right Band Edge




Date: 12.AUG.2019 22:59:11

WCDMA Band 5 HSUPA, Left Band Edge



Date: 12.AUG.2019 23:01:00

WCDMA Band 5 HSUPA, Right Band Edge



Date: 12.AUG.2019 23:00:08

FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY**Applicable Standard**

FCC § 2.1055 (a), § 2.1055 (d), §22.355, §24.235

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile > 3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: An external variable DC power supply was connected to the battery terminals of the equipment under test. The voltage was set from 85% to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the battery end point. The output frequency was recorded for each battery voltage.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Universal Radio Communication Tester	CMU200	106 891	2018-12-14	2019-12-14
ESPEC	Constant temperature and humidity Tester	ESX-4CA	018 463	2019-03-26	2020-03-26
UNI-T	Multimeter	UT39A	M130199938	2019-07-24	2020-07-24
Pro instrument	DC Power Supply	pps3300	3300012	Not Required	/
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	27.3°C
Relative Humidity:	65%
ATM Pressure:	100.3kPa
Tester:	Chris Mo
Test Date:	2019-08-12

Test Result: Compliance.

Cellular Band

GMSK, Middle Channel, $f_c = 836.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Limit
°C	V _{DC}	Hz	ppm	ppm
-30	3.8	3	0.00359	2.5
-20		-2	-0.00239	
-10		-16	-0.01913	
0		39	0.04662	
10		0	0.00000	
20		11	0.01315	
30		48	0.05738	
40		-37	-0.04423	
50		-16	-0.01913	
20	4.35	-20	-0.02391	
20	3.6	15	0.01793	

PCS Band

PCS1900, Middle Channel, $f_c = 1880.0$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Results
°C	V _{DC}	Hz	ppm	
-30	3.8	25	0.01330	Pass
-20		24	0.01277	
-10		28	0.01489	
0		27	0.01436	
10		24	0.01277	
20		27	0.01436	
30		25	0.01330	
40		24	0.01277	
50		25	0.01330	
20	4.35	14	0.00745	
20	3.6	16	0.00851	

WCDMA Band2

WCDMA Band 2 Rel 99, Middle Channel, $f_c = 1880.0$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Results
°C	V_{DC}	Hz	ppm	
-30	3.8	-7	-0.00372	Pass
-20		2	0.00106	
-10		-2	-0.00106	
0		-5	-0.00266	
10		7	0.00372	
20		8	0.00426	
30		7	0.00372	
40		-4	-0.00213	
50		-3	-0.00160	
20	4.35	-7	-0.00372	
20	3.6	-7	-0.00372	

WCDMA Band 5

WCDMA Band 5 Rel 99, Middle Channel, $f_c = 836.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Results
°C	V_{DC}	Hz	ppm	
-30	3.8	0	0.00000	2.5
-20		-4	-0.00478	
-10		-4	-0.00478	
0		0	0.00000	
10		-2	-0.00239	
20		-5	-0.00598	
30		-4	-0.00478	
40		0	0.00000	
50		-4	-0.00478	
20	4.35	-2	-0.00239	
20	3.6	-2	-0.00239	

***** END OF REPORT *****