



Test Report - RF Exposure Evaluation Report for SAR Exclusion

Applicant: Acuity Brands Lighting, Inc.

Approved for Release By:

Signature: Bruno Clavier

Name & Title: Bruno Clavier, General Manager

Date of Signature
(YYYY-MM-DD): 08/26/2022

This test report shall not be reproduced except in full without the written and signed permission of Timco Engineering Inc. (IIA). This test report relates only to the items tested as identified and is not valid for any subsequent changes or modifications made to the equipment under test.



Table of Contents

| | |
|--|---|
| CUSTOMER INFORMATION | 3 |
| LOCATION OF TESTING | 3 |
| 1.1 TEST LABORATORY | 3 |
| 1.2 TESTING WAS PERFORMED, REVIEWED BY | 4 |
| TEST SAMPLE(S) (EUT/DUT) | 5 |
| 1.3 DESCRIPTION OF THE EUT..... | 5 |
| HISTORY OF TEST REPORT CHANGES | 8 |



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

Customer Information

Applicant: Acuity Brands Lighting, Inc.
Address: One Lithonia Way
Conyers Georgia, 30012, United States

Location of Testing

1.1 Test Laboratory

Timco Engineering Inc. is a subsidiary of Industrial Inspection & Analysis, Inc. ("IIA"). Testing was performed at Timco's permanent laboratory located at 849 NW State Road 45, Newberry, Florida 32669

FCC test firm # 578780

FCC Designation # US1070

FCC site registration is under A2LA certificate # 0955.01

ISED Canada test site registration # 2056A

EU Notified Body # 1177

For all designations see A2LA scope # 0955.01



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

1.2 Testing was performed, reviewed by

Dates of Testing: 6/27/2022 – 7/11/2022

Signature:

Sr. EMC Engineer
EMC-003838-NE



Name & Title:

Tim Royer, EMC Engineer

Date of Signature

08/26/2022

Signature:

Name & Title:

Terri Allen, Lab Assistant

Date of Signature

08/26/2022



Test Sample(s) (EUT/DUT)

The test sample was received: 06/22/2022

1.3 Description of the EUT

A description as well as unambiguous identification of the EUT(s) tested. Where more than one sample is required for technical reasons (such as the use of connected units for the purpose of conducted output power testing where the product units will have integral antennas), each specific test shall identify which unit was tested.

| Identification | |
|-------------------|------------------------------|
| FCC ID: | 2ADCB-RPODU |
| Brief Description | Light Switch with 2.4 GHz BT |
| Type of Modular | N/A |
| Model(s) # | RPODU |
| Firmware version | N/A |
| Software version | N/A |
| Serial Number | 501-01661-001 |

| Technical Characteristics | |
|------------------------------|--------------------------------|
| Technology | Light Switch |
| Frequency Range | 2400-2480.5 MHz |
| RF O/P Power (Max.) | 6.94 dBm/ 4.943 mW – 0.00494 W |
| Modulation | N/A |
| Bandwidth & Emission Class | N/A |
| Number of Channels | N/A |
| Duty Cycle | 33% |
| Antenna Connector | SMA |
| Voltage Rating (AC or Batt.) | 3.7 V |



SAR EXCLUSION CALCULATION:

Section 4.3.1 General SAR test exclusion guidance

Equation:

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR,³⁰ where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation³¹
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as *numeric thresholds* in step b) below

RSS 102 Section 2.5 Exemption Limits for Routine Evaluation

Equation:

- below 20 MHz⁶ and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).



Conclusion: SAR testing is not required.

MPE

| Frequency Band | Separation Distance (mm) | Max Power + Tolerance (dBm) | Max Power + Tolerance (mW) | SAR Exclusion Value | Limit for 1-g SAR | Limit for 10-g SAR (Extremities) | SAR Exclusion |
|-----------------|--------------------------|-----------------------------|----------------------------|---------------------|-------------------|----------------------------------|---------------|
| 2400-2480.5 MHz | 5 | 6.94 | 4.94 | 1.56 | 3.0 | 7.5 | SAR EXEMPT |



History of Test Report Changes

| Test Report # | Revision # | Description | Date of Issue |
|----------------------------------|------------|-----------------|---------------|
| TR_2878-22_RF Exp SAR Exclusion_ | 1 | Initial release | 07/21/2022 |
| | | | |
| | | | |



Timco Engineering, Inc., an IIA Company
849 NW State Road 45, Newberry, Florida 32669
(352) 472-5500 / testing@timcoengr.com

END OF TEST REPORT
