

# ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

**Test Report No.** : OT-185-RWD-005  
**AGR No.** : A183A-202  
**Applicant** : LG Innotek Co., Ltd.  
**Address** : 26, Hanamsandan 5beon-ro Gwangsan-gu, 506-731, Gwangju, South Korea  
**Manufacturer** : LG Innotek Co., Ltd.  
**Address** : 26, Hanamsandan 5beon-ro Gwangsan-gu, 506-731, Gwangju, South Korea  
**Type of Equipment** : Everest Zigbee Module  
**FCC ID.** : YZP-TWZTT009DH  
**Model Name** : TWZT-T009D-H  
**Multiple Model Name** : N/A  
**Serial number** : N/A  
**Total page of Report** : 7 pages (including this page)  
**Date of Incoming** : April 08, 2018  
**Date of issue** : May 02, 2018


## SUMMARY

The equipment complies with the regulation; **FCC PART 15 SUBPART C Section 15.247**

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by:   
 Ki-Hong, Nam / Chief Engineer  
 ONETECH Corp.

Approved by:   
 Keun-Young, Choi / Vice President  
 ONETECH Corp.

## CONTENTS

### PAGE

<b>1. VERIFICATION OF COMPLIANCE .....</b>	<b>4</b>
<b>2. GENERAL INFORMATION .....</b>	<b>5</b>
<b>2.1 PRODUCT DESCRIPTION.....</b>	<b>5</b>
<b>2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....</b>	<b>5</b>
<b>3. EUT MODIFICATIONS.....</b>	<b>5</b>
<b>4. MAXIMUM PERMISSIBLE EXPOSURE .....</b>	<b>6</b>
<b>4.1 RF EXPOSURE CALCULATION .....</b>	<b>6</b>
<b>4.2 EUT DESCRIPTION.....</b>	<b>6</b>
<b>4.3 CALCULATED MPE SAFE DISTANCE.....</b>	<b>7</b>

**Revision History**

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-185-RWD-005	2018.05.02	Initial Release	All

## 1. VERIFICATION OF COMPLIANCE

Applicant : LG Innotek Co., Ltd.  
Address : 26, Hanamsandan 5beon-ro Gwangsan-gu, 506-731, Gwangju, South Korea  
Contact Person : Jeong, Inchang / Director  
Telephone No. : +86-62-950-0332  
FCC ID : YZP-TWZTT009DH  
Model Name : TWZT-T009D-H  
Serial Number : N/A  
Date : May 02, 2018

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM
E.U.T. DESCRIPTION	Everest Zigbee Module
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

## 2. GENERAL INFORMATION

### 2.1 Product Description

The LG Innotek Co., Ltd., Model TWZT-T009D-H (referred to as the EUT in this report) is a Everest Zigbee Module. The product specification described herein was obtained from product data sheet or user's manual.

Device Type	Everest Zigbee Module
Temperature Range	-20 °C ~ +85 °C
Operating Frequency	2 405 MHz ~ 2 480 MHz
RF Output Power	7.72 dBm
Number of Channel	16 Channel
Modulation Type	O-QPSK
Antenna Type	PCB Pattern Antenna
Antenna Gain	2.53 dBi
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	24 MHz
RATED SUPPLY VOLTAGE	DC 3.0 V

### 2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

## 3. EUT MODIFICATIONS

-. None

## 4. MAXIMUM PERMISSIBLE EXPOSURE

### 4.1 RF Exposure Calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are  $f/1500 \text{ mW/cm}^2$  for the frequency range between 300 MHz and 1 500 MHz and  $1.0 \text{ mW/cm}^2$  for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a  $1 \text{ mW/cm}^2$  exposure is calculated as follows:

$$E = \sqrt{(30 * P * G) / d}, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

$S$  = Power density in  $\text{mW/cm}^2$ ,  $Z$  = Impedance of free space,  $377 \Omega$

$E$  = Electric field strength in  $\text{V/m}$ ,  $G$  = Numeric antenna gain, and  $d$  = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of  $\text{mW}$  and  $\text{cm}$ , using  $P (\text{mW}) = P (\text{W}) / 1 000$ ,  $d (\text{cm}) = 0.01 * d (\text{m})$

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

$d$  = distance in  $\text{cm}$ ,  $P$  = Power in  $\text{mW}$ ,  $G$  = Numeric antenna gain, and  $S$  = Power density in  $\text{mW/cm}^2$

### 4.2 EUT Description

Kind of EUT	Everest Zigbee Module
Operating Frequency Band	<input type="checkbox"/> Wireless Microphone: 494.000 MHz ~ 501.000 MHz and 498.200 MHz ~ 505.200 MHz <input type="checkbox"/> WLAN: 2 412 MHz ~ 2 462 MHz <input type="checkbox"/> WLAN: 5 180 MHz ~ 5 320 MHz / 5 500 MHz ~ 5 700 MHz <input type="checkbox"/> WLAN: 5 745 MHz ~ 5 825 MHz <input type="checkbox"/> Bluetooth: 2 402 MHz ~ 2 480 MHz <input checked="" type="checkbox"/> Zigbee: 2 405 MHz ~ 2 480 MHz
Device Category	<input type="checkbox"/> Portable (< 20 cm separation) <input type="checkbox"/> Mobile (> 20 cm separation) <input checked="" type="checkbox"/> Others
Max. Output Power	7.72 dBm
Used Antenna	PCB Pattern Antenna
Used Antenna Gain	2.53 dBi
Exposure Evaluation Applied	<input checked="" type="checkbox"/> MPE <input type="checkbox"/> SAR <input type="checkbox"/> N/A

### 4.3 Calculated MPE Safe Distance

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Limit (mW/ cm <sup>2</sup> )
		(dBm)	(dBm)	(mW)	Log	Linear			
2 405 ~ 2 480	Zigbee	7.50 ± 0.5	8.00	6.31	2.53	1.79	0.95	0.002 2	1.00

According to above table, for 2 405 MHz ~ 2 480 MHz Band, safe distance,

$$D = 0.282 * \sqrt{(6.31 * 1.79)/1.00} = 0.95 \text{ cm}$$

For getting power density at 20 cm separation in above table, following formula was used.


$$S = P * G / (4\pi * R^2) = 6.31 * 1.79 / (4 * 3.14 * 20^2) = 0.002 2$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna

  
 Tested by: Tae-Ho, Kim / Senior Manager