

RF Exposure Report

Report No.: SABGMK-WTW-P21030811-1

FCC ID: K7SAUF001V2

Test Model: AUF001 V2

Received Date: Mar. 23, 2021

Test Date: Apr. 20 to May 8, 2021

Issued Date: May 25, 2021

Applicant: Belkin International., Inc.

Address: 12045 East Waterfront Drive, Playa Vista, CA 90094, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

FCC Registration /

Designation Number: 198487 / TW2021





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertai measurement nty of has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Report No.: SABGMK-WTW-P21030811-1 Page No. 1 / 6 Report Format Version: 6.1.1



Table of Contents

Relea	ase Control Record	3
1	Certificate of Conformity	4
	RF Exposure	
2.1	Limits For Maximum Permissible Exposure (MPE)	5
2.2	2 MPE Calculation Formula	5
2.3	3 Classification	5
2.4	4 Calculation Result Of Maximum Conducted Power	6



Report Issue History Record

Issue No.	Description	Date Issued
SABGMK-WTW-P21030811-1	Original release.	May 25, 2021

Release Control Record

Issue No.	Description	Date Issued
SABGMK-WTW-P21030811-1	Original release.	May 25, 2021

Report No.: SABGMK-WTW-P21030811-1 Page No. 3 / 6 Report Format Version: 6.1.1



1 Certificate of Conformity

Product: SOUNDFORM™ Charge Bluetooth Speaker + Wireless Charger

Brand: belkin

Test Model: AUF001 V2

Sample Status: Engineering sample

Applicant: Belkin International., Inc

Test Date: Apr. 20 to May 8, 2021

Standards: FCC Part 2 (Section 2.1091)

References Test Guidance: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by: ______, Date: ______, May 25, 2021

Annie Chang / Senior Specialist

Approved by: , Date: May 25, 2021

Rex Lai / Associate Technical Manager



2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	ange Electric Field Magnetic Field Power Density Strength (V/m) Strength (A/m) (mW/cm²)		Average Time (minutes)		
Limits For General Population / Uncontrolled Exposure					
0.3-1.34	614	1.63	(100)*	30	
1.34-30	824/f	24/f 2.19/f (180/f²)*		30	
30-300	27.5	0.073	0.2	30	
300-1500			f/1500	30	
1500-100,000			1.0	30	

f = Frequency in MHz; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



2.4 Calculation Result Of Maximum Conducted Power

Function	Frequency Band (MHz)	Max AV Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm ²)
BT EDR	2402-2480	0.85	4.98	20	0.0008	1

Note:

- 1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
- 2. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.
- 3. The worst MPE result of Qi function, refer to BV CPS report no.: SABGMK-WTW-P21030811.

Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

BT + Qi = 0.0008 / 1.00 + 0.6928 / 1.63 = 0.4258

Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---