



TUV SUD BABT TCB  
Octagon House,  
Segensworth Road,  
Fareham,  
Hampshire,  
PO15 5RL

### ***RF exposure information***

Date: **Jan. 11, 2016**

FCC ID: **KR5TIS-02**; IC: **7812D-TIS02**

#### **1. Introduction:**

The device with FCC ID: KR5TIS-02; IC: 7812D-TIS02 is designed to be used in portable exposure conditions.

This product integrates a transmitter operated in 315 MHz frequency band.

#### **2. Output power considerations:**

Worst case output power transmitter:  $71,99 \text{ dB}\mu\text{V/m}@3\text{m} = 0,004740715 \text{ mW eirp}$

#### **3. Compliance criteria:**

Transmitter is deemed to comply with FCC § 2.1093 requirements and IC RSS-102 Issue 5 as the output power of the device meets the conditions specified in section 4.3.1 (SAR test exclusion) considerations of the document "KDB 447498 D01 General RF Exposure Guidance v06" and in section 2.5.1 (Exemption from Routine Evaluation Limits – SAR Evaluation) of RSS-102 Issue 5.

FCC:

$$\left[ \frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot [\sqrt{f(\text{GHz})}] \leq 3$$

$$[0,004740715/5] \cdot [\sqrt{0,315}] = 0,000532 \leq 3$$

IC:

Max output power (mW)  $\leq 69.1 \text{ mW}$  (limit at 315 MHz resulting of the linear interpolation of the limits at 300 MHz and 450 MHz specified in table 1 of section 2.5.1 of RSS-102 Issue 5)

$0,004740715 \text{ mW} \leq 69,1 \text{ mW}$

Sincerely,

p.a.  
Name: Dagmar Kolar  
Position: Manager RF Homologation  
Company: Continental Automotive GmbH  
Phone: +49 941 790-6699  
e-mail: dagmar.kolar@continental-corporation.com