

Annex Products (Quad Lock)

Como Centre, Level 3, Suite 6A,
299 Toorak Rd, South Yarra
VIC 3141, Australia
Phone: +61 3 9069 9698
info@quadlock.com.au

Cover Letter-Wireless Charger Approval

Date: 20th Dec, 2023

Gentlemen:

There's a 12V-18V Wireless Charger that would like to have your authorization as an Inductive wireless power transfer applications approval.

The specific product as below, 12V-18V Wireless Charger, with its designed features and specified description, meets special requirements for KDB 680106 D01 section 5.2 requirements.

Company:	Annex Products Pty Ltd
Product Name:	OEM WCM 2.0 – 12V-18V
Model Number:	QL-6585 QL-6416
FCC ID:	2AOU9-QLO2

KDB 680106 D01 Section 5.2 Requirements	Product Technical Specification	Result
1) Power transfer frequency is less than 1 MHz	116– 159.36kHz	Complied
2) Output power from each primary coil is less than or equal to 15 watts.	QL-6585: 5W / 7.5W / 10W / 15W QL-6416: 5W / 7.5W	Complied
3) A client device providing the maximum permitted load is placed in physical contact with the transmitter (i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact)		Complied
4) Only § 2.1091-Mobile exposure conditions apply	For inductive applications where the primary does not physically attach to the client, and it is intended for desktop use, the desktop guidance in KDB 680106 D01 may be applied	Complied
5) The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1. These measurements shall be taken along the principal axes of the device, with one axis oriented along the direction of the estimated maximum field strength, and for three points per axis or until a 1/d (inverse distance from the emitter structure) field strength decay is observed. Symmetry considerations may be used for test reduction purposes. The device shall be operated in documented worst-case compliance scenarios (i.e., the ones that lead to the maximum field components), and while all the radiating structures (e.g., coils or antennas) that by design can simultaneously transmit are energized at their nominal maximum power.	Please refer to RF exposure report	Complied

Annex Products (Quad Lock)

Como Centre, Level 3, Suite 6A,
299 Toorak Rd, South Yarra
VIC 3141, Australia
Phone: +61 3 9069 9698
info@quadlock.com.au

6) For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions. If the design allows one or more radiating structures to be powered at a higher level while other radiating structures are not powered, then those cases must be tested as well. For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested.	Please refer to RF exposure report	Complied
---	---	-----------------

Sincerely,

Print Name: Chris Peters

Title: Co-founder & CIO

Signature:



On behalf of Company: Annex Products Pty Ltd

Telephone: +61 3 9069 9698

E-mail: compliance@quadlock.com.au