

SAR Evaluation Report

in accordance with the requirements of FCC Report and Order: ET Docket 93-62, and OET Bulletin 65 Supplement C

for

2.4 GHZ DIRECT SEQUENCE SPREAD SPECTRUM

CORDLESS PHONE

MODEL: UX-CL220

FCC ID: APYHRO00023

DECEMBER 03, 2001

REPORT NO: 01U1067-1

Prepared for SHARP CORPORATION 492 MINOSHO-CHO YAMATOKORIYAMA-SHI, NARA 639-1186, JAPAN

Prepared by COMPLIANCE CERTIFICATION SERVICES 561F MONTEREY ROAD, MORGAN HILL, CA 95037, USA TEL: (408) 463-0885

CERTIFICATE OF COMPLIANCE (SAR EVALUATION)

Dates of Tests: November 29-30, 2001 Report No: 01U1005-1

	APPLICANT:	SHARP CORPORATION 492 MINOSHO-CHO YAMATOKORIYAMA-SHI, NARA 639-1186, JAPAN	
	TRADE NAME:	SHARP CORPORATION	
	MODEL:	UX-CL220	
	SERIAL NUMBER:	N/A (PRODUCTION)	
	FCC ID:	APYHRO00023	
I	CATEGORY	PORTABLE DSSS DEVICE	
I	UNILOUNT.		
	est Sample is a:	Production Unit	
	est Sample is a: x Frequency:	Production Unit 2404.8 – 2475MHz	
 T F	est Sample is a: x Frequency: x Frequency:	Production Unit 2404.8 – 2475MHz 2404.8 – 2475MHz	
	est Sample is a: x Frequency: x Frequency: Max. RF Output Power:	Production Unit 2404.8 – 2475MHz 2404.8 – 2475MHz 10.74dBm (Low Channel), 10.73dBm (Middle Channel), and 11.23dBm	n
	Test Sample is a: Test Sample is a: Tx Frequency: Rx Frequency: Max. RF Output Power:	Production Unit 2404.8 – 2475MHz 2404.8 – 2475MHz 10.74dBm (Low Channel), 10.73dBm (Middle Channel), and 11.23dBm (High Channel), all based on Conducted Output Power Measurements	n :s
	Fest Sample is a: Test Sample is a: Tx Frequency: Ax Frequency: Max. RF Output Power:	Production Unit 2404.8 – 2475MHz 2404.8 – 2475MHz 10.74dBm (Low Channel), 10.73dBm (Middle Channel), and 11.23dBm (High Channel), all based on Conducted Output Power Measurements Unlicensed Intentional Radiator	n :s
	Fest Sample is a: Tx Frequency: Ax Frequency: Max. RF Output Power: FCC Classification: RF Exposure environment	Production Unit 2404.8 – 2475MHz 2404.8 – 2475MHz 10.74dBm (Low Channel), 10.73dBm (Middle Channel), and 11.23dBm (High Channel), all based on Conducted Output Power Measurements Unlicensed Intentional Radiator nt: General Population/Uncontrolled	n :s
	Test Sample is a: Tx Frequency: Ax Frequency: Max. RF Output Power: TCC Classification: RF Exposure environment Application Type:	Production Unit 2404.8 – 2475MHz 2404.8 – 2475MHz 10.74dBm (Low Channel), 10.73dBm (Middle Channel), and 11.23dBm (High Channel), all based on Conducted Output Power Measurements Unlicensed Intentional Radiator nt: General Population/Uncontrolled Certification	n :s

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE Std. C95.1-1992 and had been tested in accordance with the measurement procedures specified in FCC OET 65 Supplement C (released on 6/29/2001 see Test Report).

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



- Ch

Steve Cheng EMC Engineering Manager

TABLE OF CONTENT

1. E	UT DESCRIPTION	4
2.	REQUIREMENTS FOR COMPLIANCE TESTING DEFINED BY THE FCC	C 5
3.	DOSIMETRIC ASSESSMENT SETUP	6
3.1.	MEASUREMENT SYSTEM DIAGRAM	7
3.2.	SYSTEM COMPONENTS	8
3.3.	EUT ARRANGEMENT	12
4.	EUT TUNE-UP PROCEDURE	
5.	EVALUATION PROCEDURE	
5.1.	SIMULATED TISSUE LIQUID PARAMETER CONFIRMATION	19
5.2.	SYSTEM ACCURACY VERIFICATION	19
5.3.	SAR EVALUATION PROCEDURE	21
5.4.	EXPOSURE LIMIT	22
6.	RESULTS	
7.	REFERENCES	36
8.	APPENDIX	37
8.1.	EUT PHOTOS	37
8.2	EQUIPMENTS LIST & CALIBRATION INFO	39
8.3	IEEE SCC-34/SC-2 P1528 RECOMMENDED TISSUE DIELECTRIC PARAMETERS	40
8.4	EQUIPMENTS CALIBRATION CERTIFICATE	41

1. EUT DESCRIPTION

APPLICANT:	SHARP CORPORATION 492 MINOSHO-CHO	
	YAMATOKORIYAMA-SHI, NARA	639-1186, JAPAN
TRADE NAME:	SHARP CORPORATION	
MODEL:	UX-CL220	
SERIAL NUMBER:	N/A (PRODUCTION)	
FCC ID:	APYHRO00023	
CATEGORY:	PORTABLE DSSS DEVICE	

Test Sample is a:	Production Unit	
EUT Type:	Portable 2.4GHz Direct Sequence Spread Spectrum	Cordless Phone
Trade Name:	Sharp	
Model(s):	UX-CL220	
FCC IDENTIFIER:	APYHRO00023	
S/N:	N/A (Production)	
Tx Frequency:	2404.8 - 2475 MHz	· SHAIP
Rx Frequency:	2404.8 - 2475 MHz	The second se
Application Type:	Certification	1411 5 150
FCC Classification:	Unlicensed Intentional Radiator	
Modulation(s):	DSSS	
FCC Rule Part(s):	§ 15.247	
Max. RF Output Power:	10.74dBm (Low Channel), 10.73dBm (Middle	670
	Channel), and 11.23dBm (High Channel), all	
	based on Conducted Output Power Measurements	
Antenna Type:	Stub Type	
Antenna Dimensions:	Length 17mm, Diameter (Bottom 11mm - Top 7mm)	
Dates of Tests:	November 29 - 30, 2001	
Report Project No.:	01U1067-1	

¹ Specific Absorption Rate (SAR) is a measure of the rate of energy absorption due to exposure to an RF transmitting source (wireless portable device).

2 IEEE/ANSI Std. C95.1-1992 limits are used to determine compliance with FCC ET Docket 93-62.

2. REQUIREMENTS FOR COMPLIANCE TESTING DEFINED BY THE FCC

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996 [1]. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g as recommended by the ANSI/IEEE standard C95.1-1992 [6] for an uncontrolled environment (Paragraph 65). According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

3. DOSIMETRIC ASSESSMENT SETUP

These measurements were performed with the automated near-field scanning system DASY3 from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot (working range greater than 0.9 m) which positions the probes with a positional repeatability of better than \pm 0.02 mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit. The system is described in detail in [3].

The SAR measurements were conducted with the dosimetric probe ET3DV6 SN: 1577 (manufactured by SPEAG), designed in the classical triangular configuration [3] and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure described in [7] with accuracy of better than $\pm 10\%$. The spherical isotropy was evaluated with the procedure described in [8] and found to be better than ± 0.25 dB.

The phantom used was the \Generic Twin Phantom" described in [4]. The ear was simulated as a spacer of 4 mm thickness between the earpiece of the phone and the tissue simulating liquid. The Tissue simulation liquid used for each test is in according with the FCC OET65 supplement C as listed below.

Ingredients	Frequency (MHz)									
(% by weight)	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

3.1. MEASUREMENT SYSTEM DIAGRAM



The DASY3 system for performing compliance tests consist of the following items:

- 1. A standard high precision 6-axis robot (Stäubli RX family) with controller and software.
- 2. An arm extension for accommodating the data acquisition electronics (DAE).
- 3. A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- 4. A data acquisition electronic (DAE), which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- 5. A unit to operate the optical surface detector, which is connected to the EOC. The Electro-optical coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the PC plug-in card. The functions of the PC plug-in card based on a DSP is to perform the time critical task such as signal filtering, surveillance of the robot operation fast movement interrupts.
- 6. A computer operating Windows 95 or larger
- 7. DASY3 software
- 8. Remote control with teaches pendant and additional circuitry for robot safety such as warning lamps, etc.
- 9. The generic twin phantom enabling testing left-hand and right-hand usage.
- 10. The device holder for handheld EUT.
- 11. Tissue simulating liquid mixed according to the given recipes (see Application Note).
- 12. System validation dipoles to validate the proper functioning of the system.

3.2. SYSTEM COMPONENTS

ET3DV5 Probe Specification

Construction Symmetrical design with triangular core Built-in optical fiber for surface detection System Built-in shielding against static charges Calibration In air from 10 MHz to 2.5 GHz In brain and muscle simulating tissue at Frequencies of 450 MHz, 900 MHz and 1.8 GHz (accuracy \pm 8%) Frequency 10 MHz to > 6 GHz; Linearity: ± 0.2 dB (30 MHz to 3 GHz) Directivity ± 0.2 dB in brain tissue (rotation around probe axis) \pm 0.4 dB in brain tissue (rotation normal probe axis) Dynamic 5 mW/g to > 100 mW/g; Range Linearity: ± 0.2 dB Surface \pm 0.2 mm repeatability in air and clear liquids Detection over diffuse reflecting surfaces. Dimensions Overall length: 330 mm Tip length: 16 mm Body diameter: 12 mm Tip diameter: 6.8 mm Distance from probe tip to dipole centers: 2.7 mm Application General dosimetric up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms





Photograph of the probe



Inside view of ET3DV6 E-field Probe

E-Field Probe Calibration Process

Each probe is calibrated according to a dosimetric assessment procedure described in [6] with accuracy better than +/- 10%. The spherical isotropy was evaluated with the procedure described in [7] and found to be better than +/-0.25dB. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies bellow 1 GHz, and in a waveguide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

Data Evaluation

The DASY3 software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Norm _i , a _{i0} , a _{i1} , a _{i2}
-	- Conversion factor	ConvFi
	- Diode compression point	Dcpi
Device parameters:	- Frequency	f
	- Crest factor	cf
Media parameters:	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can either be found in the component documents or be imported into the software from the configuration files issued for the DASY3 components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with	V_i	= compensated signal of channel i	(i = x, y, z)
	Ui	= input signal of channel i	(i = x, y, z)
	cf	= crest factor of exciting field	(DASY parameter)
	dcpi	= diode compression point	(DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:

$$E_{i} = \sqrt{\frac{V_{i}}{Norm_{i} \cdot ConvF}}$$
$$H_{i} = \sqrt{Vi} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^{2}}{f}$$

H-field probes:

- $\begin{array}{lll} \text{with} & V_i &= \text{compensated signal of channel } i & (i=x,\,y,\,z) \\ \text{Norm}_i &= \text{sensor sensitivity of channel } i & (i=x,\,y,\,z) \\ & \mu V/(V/m)^2 \text{ for E-field Probes} \\ \text{ConvF} &= \text{sensitivity enhancement in solution} \\ a_{ij} &= \text{sensor sensitivity factors for H-field probes} \\ f &= \text{carrier frequency [GHz]} \\ E_i &= \text{electric field strength of channel } i \text{ in V/m} \\ \end{array}$
 - H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with SAR = local specific absorption rate in mW/g E_{tot} = total field strength in V/m σ = conductivity in [mho/m] or [Siemens/m] ρ = equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{3770}$$
 or $P_{pwe} = H_{tot}^2 \cdot 37.7$

with P_{pwe} = equivalent power density of a plane wave in mW/cm²

 E_{tot} = total electric field strength in V/m

H_{tot} = total magnetic field strength in A/m

REPORT NO: 01U1067-1 DATE: DECEMBER 03, 2001 FCC ID: APYHRO00023 EUT: 2.4GHZ DIRECT SEQUENCE SPREAD SPECTRUM CORDLESS PHONE

Generic Twin Phantom

The Generic Twin Phantom is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users [9][10]. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allows the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. Shell Thickness 2 ± 0.1 mm Filling Volume Approx. 20 liters Dimensions 810 x 1000 x 500 mm (H x L x W)



Generic Twin Phantom

Device Holder for Transmitters

In combination with the Generic Twin Phantom V3.0, the Mounting Device enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear opening. The devices can be easily, accurately, and repeatedly positioned according to the FCC and CENELEC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).

* Note: A simulating human hand is not used due to the complex anatomical and geometrical structure of the hand that may produced infinite number of configurations [10]. To produce the worst-case condition (the hand absorbs antenna output power), the hand is omitted during the tests.



Device Holder

3.3. EUT ARRANGEMENT

HANDSET TEST POSITION

- HEAD POSTION -

The device was placed in a normal operating position with the Point A on the device, as illustrated in following drawing, aligned with the location of the RE(ERP) on the phantom. With the ear-piece pressed against the head, the vertical center line of the body of the handset was aligned with an imaginary plane consisting of the RE, LE and M. While maintaining these alignments, the body of the handset was gradually moved towards the cheek until any point on the mouth-piece or keypad contacted the cheek. This is a cheek/touch position. For ear/tilt position, while maintain the device aligned with the BM and FN lines, the device was pivot against ERP back for 15° or until the device antenna touch the phantom. Please refer to IEEE SC-2 P1528 illustration Below.













Left Cheek



<u>Left Tilt</u>