

RF Exposure Report

Report No.: SA180503C11B

FCC ID: UCC-CX200

Test Model: CX200

Received Date: May 03, 2018

Test Date: Jun. 06, 2018 and Nov. 23, 2018

Issued Date: Dec. 10, 2018

Applicant: Altai technologies limited

Address: Unit 209, 2/F, Lakeside 2, 10 Science Park West Avenue, HK Science Park,

Shatin, Hong Kong

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

(R.O.C.)

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, TAIWAN (R.O.C.)

FCC Registration / 788550 / TW0003

Designation Number:





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth ourfindings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: SA180503C11B Page No. 1 / 6 Report Format Version: 6.1.1 Reference No.: 181106C37



Table of Contents

Re	ease Control Record	3
1	Certificate of Conformity	4
2	RF Exposure	5
	1 Limits for Maximum Permissible Exposure (MPE)	5 5
	3 Classification	5
3	Calculation Result of Maximum Conducted Power	6



Release Control Record

Issue No.	Description	Date Issued
SA180503C11B	Original release	Dec. 10, 2018

Report No.: SA180503C11B Page No. 3 / 6 Report Format Version: 6.1.1

Report No.: SA180503C11B Reference No.: 181106C37



1 Certificate of Conformity

Product: CX200 Outdoor 2x2 802.11ac Wave 2 AP

Brand: Altai

Test Model: CX200

Sample Status: Engineering sample

Applicant: Altai technologies limited

Test Date: Jun. 06, 2018 and Nov. 23, 2018

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by: Olive Dec. 10, 2018

Celine Chou / Senior Specialist

Approved by: , Date: Dec. 10, 2018

Bruce Chen / Project Engineer



2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (minutes)		
	Limits For General Population / Uncontrolled Exposure					
300-1500			F/1500	30		
1500-100,000			1.0	30		

F = Frequency in MHz

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

Report No.: SA180503C11B Page No. 5 / 6 Report Format Version: 6.1.1

Reference No.: 181106C37



3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm²)			
CDD Mode								
2412-2462	23.72	8.18	20	0.308	1			
5180-5240	16.20	8.18	20	0.055	1			
5745-5825	23.18	8.18	20	0.272	1			
Beamforming Mode								
2412-2462	20.11	8.18	20	0.134	1			
5180-5240	13.19	8.18	20	0.027	1			
5745-5825	20.17	8.18	20	0.136	1			

Note: Directional gain = 5.17dBi + 10log(2) = 8.18dBi

Conclusion:

Both of the WLAN 2.4G & WLAN 5G can transmit simultaneously, the formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

$$2.4G + 5G = 0.308 / 1 + 0.272 / 1 = 0.580$$

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---