
EMC Test Report For RM-58



T183 (EN ISO/IEC 17025)

CONTENTS


1	CUSTOMER INFORMATION	3
2	EUT AND ACCESSORY INFORMATION	4
2.1	EUT description	4
2.2	EUT and accessories	4
3	STANDARDS AND MEASUREMENT METHODS	5
4	TEST RESULTS	6
4.1	AC powerline conducted emissions	6
4.1.1	Limit	6
4.1.2	EUT operation mode.....	6
4.1.3	Emission measurement data	7
4.2	Radiated emissions	8
4.2.1	Test method and level, 30 MHz – 8500 MHz	8
4.2.2	EUT operation mode.....	9
4.2.3	Emission measurement data, 30 MHz – 8500 MHz	9

1 CUSTOMER INFORMATION

Test laboratory:	TCC Tampere Nokia Oyj Sinitaival 5 FIN-33720 TAMPERE Tel. +358 7180 08000 Fax. +358 7180 46800
FCC registration number IC file number:	94436 (June 14, 2002) IC 3608 (March 5, 2003)
Client:	Nokia Corporation P.O. Box 300 Yrtyipellontie 6 FIN-90230 OULU, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 58300
Contact person:	Jorma Hanni
Receipt of EUT:	30.12.2004
Date of testing:	5-10.1.2005
Date of report:	18.1.2005

The tests listed in this report have been done to demonstrate compliance with the applicable requirements in FCC rules Part 15 and IC standard ICES-003.

Contents approved:


Jari Jantunen EMC test engineer

2 EUT AND ACCESSORY INFORMATION

2.1 EUT description

The EUT is a mobile phone EUT is a dual triple band (GSM 850/1800/1900 EGPRS) mobile phone.

The highest internal frequency of the EUT is 3759.6 MHz.

2.2 EUT and accessories

The table below lists all EUTs and accessories used in the tests. Later in this test report, only numbers in the last column are used to refer to the devices in each test.

	Name	Type	S/N	Number
EUT	Mobile phone	RM-58	004400521659605	40150
Accessories	Battery	BL-5C	-	40123
	Charger	ACP-12	-	40121
	USB cable	DKU-2	-	40144
	Digital camera	DS-7	7102516	40076
	Printer	HP deskjet 1600CC3540A	USB8302546	40077
	Laptop PC	LATITUDE CP M233XT	0009321C-12800-8A5- 2913	40078
	Laptop charger	PA-2	00085391	40080
	Laptop PC	LATITUDE D600	0009321C-12800-8A5- 2913	40085
	Laptop charger	AA22850	00085391	40086
	Parallel cable for printer	-	-	40087
	Serial cable for camera	-	-	40088

Note! Phone HW ID is 0721

SUMMARY OF TEST RESULTS

Section in CFR 47	Section in ICES-003		Result
15.107,a	5.3	AC powerline conducted emissions	PASS
15.109,a	5.5	Radiated emissions	PASS

3 STANDARDS AND MEASUREMENT METHODS

The tests were performed in guidance of CFR 47 Part 15 Subpart B, ANSI C63.4 (2001), ICES-003 and CISPR 22. Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method".

4 TEST RESULTS

4.1 AC powerline conducted emissions

EUT	40150
Accessories	40121, 40123, 40144, 40076, 40077, 40078, 40080, 40085, 40086, 40087, 40088
Temp, Humidity, Air Pressure	19°C 49 % RH 986 mbar
Date of measurement	5.1.2005
FCC rule part	§15.107
ICES-003 section	5.3
Measured by	Jari Jantunen
Result	PASS

4.1.1 Limit


CISPR 22 Class B limit

Frequency band (MHz)	Quasi-peak limit (dBμV)	Average limit (dBμV)
0.15 – 0.5	66 – 56	56 – 46
0.5 – 5	56	46
5 – 30	60	50

4.1.2 EUT operation mode

EUT operation mode	GSM 1900, idle mode, BlueTooth standby
EUT operation voltage	115V/60Hz

4.1.3 Emission measurement data



Picture 1 Emission measurement data

Table 1 Emission measurement data, average detector

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin	Detector dB	Line	PE
0.879000	18.80	10.20	46.00	27.20	AV	N	GND
1.045500	19.30	10.30	46.00	26.70	AV	N	GND
23.275500	27.10	12.20	50.00	22.90	AV	L1	GND
23.568000	27.00	12.30	50.00	23.00	AV	L1	GND
23.860500	23.40	12.30	50.00	26.60	AV	N	GND
24.733500	24.40	12.30	50.00	25.60	AV	L1	GND

Table 2 Emission measurement data, quasi peak detector

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin	Detector dB	Line	PE
1.536000	24.10	10.40	56.00	31.90	QP	N	GND
22.983000	32.50	12.20	60.00	27.50	QP	L1	GND

4.2 Radiated emissions

EUT	40150
Accessories	40121, 40123, 40144, 40076, 40077, 40078, 40080, 40085, 40086, 40087, 40088
Temp, Humidity, Air Pressure	20°C 49 %RH 1002 mbar
Date of measurement	10.1.2005
FCC rule part	§15.109
ICES-003 section	5.5
Measured by	Jari Jantunen
Result	PASS

4.2.1 Test method and level, 30 MHz – 8500 MHz

The test was made according to ANSI C63.4 (2001) with following exceptions and additions:

- 1) The measurement was made in semi-anechoic chamber at measurement distance of 3m. The chamber had ferrite and absorber lining in all walls and ceiling, the floor was metal covered.
- 2) The measurement was divided in two parts; prescan and final measurement.

4.2.1.1 Prescan

- a) The EUT was set on the turntable and measuring antenna in horizontal polarization at 1m.
- b) The turntable was set to 0 degrees.
- c) The receiver was set to record the maximum level using peak detector.
- d) The antenna was raised from 1m to 4m in 1 meter steps.
- e) For each antenna height the table was rotated full turn in 30 degree steps.
- f) Antenna polarization was changed to vertical and phases b - e repeated.
- g) All suspect frequencies were recorded in a file.
- h) At every suspect frequency the turntable was rotated around, antenna scanned and the polarization changed to find the maximum levels.

4.2.1.2 Final measurement

- a) The final measurement was run at suspect frequencies only using peak, quasipeak and average detector.
- b) The turntable was rotated full turn to find out the worst azimuth.
- c) On those azimuths obtained in b, the antenna was scanned from 1m to 4m to find out the worst elevation.
- d) Phases b and c were repeated with another antenna polarization.
- e) Obtained values were reported

CISPR 22 Class B limit (3m measuring distance)

Frequency band (MHz)	Quasi-peak limit (dBμV/m)
30 – 230	40
230 – 1000	47

Class B limit (3m measuring distance)

Frequency band (MHz)	Limit (µV/m)	Limit (dBµV/m)	Detector
1000-8500	500 / 5000	54 / 74	AV / PK

4.2.2 EUT operation mode

EUT operation mode	GSM 1900, idle mode, BlueTooth standby
EUT operation voltage	115V/60Hz

4.2.3 Emission measurement data, 30 MHz – 8500 MHz

The measurement results were obtained as described below.

$$E[uV / m] = U_{RX} + A_{CABLE} + AF - G_{PREAMP}$$

Where

U_{RX} receiver reading

A_{CABLE} Attenuation of the cable

AF Antenna factor

G_{PREAMP} Gain of the preamplifier

Table 3 GSM 1900, low channel, peak detector

Frequency MHz	Level dBµV/m	Margin dB	Polarisation
3860.000000	41.30	32.70	HORIZONTAL
7720.000000	45.20	28.80	HORIZONTAL

Table 4 GSM 1900, low channel, average detector

Frequency MHz	Level dBµV/m	Margin dB	Polarisation
3860.000000	27.90	26.10	VERTICAL
7720.000000	32.50	21.50	VERTICAL

Table 5 GSM 1900, mid channel, quasi-peak detector

Frequency MHz	Level dBµV/m	Margin dB	Polarisation
31.664329	30.60	9.40	VERTICAL
42.426453	29.50	10.50	VERTICAL
388.174749	40.00	6.00	VERTICAL
419.339679	37.30	8.70	VERTICAL
481.263126	42.50	3.50	VERTICAL

Table 6 GSM 1900, mid channel, peak detector

Frequency MHz	Level dBµV/m	Margin dB	Polarisation
3920.339679	41.10	32.90	VERTICAL
7840.179359	47.70	26.30	VERTICAL

Table 7 GSM 1900, mid channel, average detector

Frequency MHz	Level dBµV/m	Margin dB	Polarisation
3919.839679	28.50	25.50	VERTICAL
7839.679359	34.00	20.00	VERTICAL

Table 8 GSM 1900, high channel, peak detector

Frequency MHz	Level dBµV/m	Margin dB	Polarisation
3980.000000	44.00	30.00	VERTICAL
7960.000000	45.80	28.20	HORIZONTAL

Table 9 GSM 1900, high channel, average detector

Frequency MHz	Level dBµV/m	Margin dB	Polarisation
3980.000000	28.40	25.60	VERTICAL
7960.000000	32.90	21.10	VERTICAL