



Test & Certification Center (TCC) - Dallas

FCC ID: GMLRH-21

Test Report #: 03-SA-0058/0122



Accredited Laboratory
Certificate Number: 1819-01

SAR Compliance Test Report

Test report no.:	03-SA-0058/0122	Date of report:	17 September, 2003
Number of pages:	40	Contact person:	Nerina Walton
		Responsible test engineer:	Nerina Walton
Testing laboratory:	Test & Certification Center (TCC) Dallas Nokia Mobile Phones 6021 Connection Drive Irving TX 75039, USA Tel. +1 972 894 5000 Fax. +1 972 894 4988	Client:	Nokia Mobile Phones 6021 Connection Drive Irving TX 75039, USA Tel. +1 972 894 5000 Fax. +1 972 894 4988
Tested devices:	GMLRH-21, Model 3520		
Testing has been carried out in accordance with:	IEEE Std 1528-200X, Draft CBD 1.0 - April 4, 2002 Draft Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques <u>FCC Supplement C Edition, 01-01</u> Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields		
Documentation:	The documentation of the testing performed on the tested devices is archived for 15 years at Test & Certification Center (TCC) Dallas		
Test results:	The tested device complies with the requirements in respect of all parameters subject to the test. The test results and statements relate only to the items tested. The test report shall not be reproduced except in full, without written approval of the laboratory.		
Date and signatures:	17 September, 2003		
For the contents:			


Alan C. Ewing
TCC Line Manager


Nerina Walton
Test Engineer

CONTENTS

1. QUALITY SYSTEM	3
2. SUMMARY FOR SAR TEST REPORT	4
2.1 MAXIMUM RESULTS FOUND DURING SAR EVALUATION.....	4
3. DESCRIPTION OF TESTED DEVICE.....	5
3.1 PICTURE OF PHONE.....	5
3.2 DESCRIPTION OF THE ANTENNA.....	5
3.3 BATTERY OPTIONS	5
3.4 BODY WORN OPERATION.....	5
4. TEST CONDITIONS.....	6
4.1 AMBIENT CONDITIONS	6
4.2 RF CHARACTERISTICS OF THE TEST SITE	6
4.3 TEST SIGNAL, FREQUENCIES, AND OUTPUT POWER	6
5. DESCRIPTION OF THE TEST EQUIPMENT.....	7
5.1 SYSTEM ACCURACY VERIFICATION	8
5.2 TISSUE SIMULANTS.....	10
5.3 PHANTOMS.....	11
5.4 ISOTROPIC E-FIELD PROBE ET3DV6	11
6. DESCRIPTION OF THE TEST PROCEDURE	12
6.1 TEST POSITIONS	12
6.2 SCAN PROCEDURES.....	14
6.3 SAR AVERAGING METHODS	14
7. MEASUREMENT UNCERTAINTY	15
7.1 DESCRIPTION OF INDIVIDUAL MEASUREMENT UNCERTAINTY	15
8. RESULTS.....	17
8.1 HEAD CONFIGURATION.....	17
8.2 BODY WORN CONFIGURATION.....	18

APPENDIX A: SCOPE OF ACCREDITATION FOR A2LA

APPENDIX B: VALIDATION TEST PRINTOUTS

APPENDIX C: SAR DISTRIBUTION PRINTOUTS

APPENDIX D: CALIBRATION CERTIFICATE (S)



1. QUALITY SYSTEM

The quality system in place for TCC-Dallas conforms to ISO/IEC 17025 and has been audited to the standard by A2LA (American Association of Laboratory Accreditation). Appendix D of this report contains the scope of accreditation for A2LA. TCC – Dallas has also been audited using the ISO 9000 Quality System, as part of Nokia Mobile Phones, Inc., by ABS (American Bureau of Shipping) Quality Evaluations Inc.

TCC-Dallas is a recognized laboratory with the Federal Communications Commission in filing applications for Certification under Parts 15 and 18, Registration Number 100060, and Industry Canada, Registration Number IC 661.

2. SUMMARY FOR SAR TEST REPORT

Date of test	23-April to 04-September-03
Contact person	Nerina Walton
Test plan referred to	-
FCC ID	GMLRH-21
Type, SN, HW and SW numbers of tested device	Type: RH-21 ESN: 2355316509, HW: 420f, SW: 2.07.03 ESN: 23553165322, HW: 425f, SW: 2.07.03 ESN: 07201941611, HW: 1151f, SW: 2.6a ESN: 07201941766, HW: 1152f, SW: 2.6a
Accessories used in testing	EL 'A' Cover, Star Wars 'A' Cover, BLC-2 Battery, BLC-1 Battery, HDE-2 Headset
Notes	-
Document code	03-SA-0058/0122
Responsible test engineer	N. Walton
Measurement performed by	E.Parish / J. Love / C. Bertz

2.1 Maximum Results Found during SAR Evaluation

The equipment is deemed to fulfill the requirements if the measured values are less than or equal to the limit.

Note: this device also operates in TDMA 800 mode however, since these were 'spot-check' measurements and AMPS was considered worst-case, it was determined that testing in the TDMA 800 mode would be unnecessary.

2.1.1 Head Configuration

Mode	Ch / f (MHz)	Power (dBm)	Position	Limit (mW/g)	Measured (mW/g)	Result
AMPS	384 / 836.52	24.73	Left Touch	1.6	1.26	PASSED

2.1.2 Body Worn Configuration

Mode	Ch / f (MHz)	Power (dBm)	Position	Limit (mW/g)	Measured (mW/g)	Result
AMPS	384 / 836.52	24.73	Flat - Back of Phone with 22mm Measurement Distance	1.6	0.70	PASSED

2.1.3 Measurement Uncertainty

Combined Standard Uncertainty	± 14.5%
Expanded Standard Uncertainty (k=2)	± 29.1%

3. DESCRIPTION OF TESTED DEVICE

Device category	Portable device	
Exposure environment	Uncontrolled exposure	
Unit type	Prototype unit	
Case type	Fixed case	
Mode of Operation	AMPS	TDMA 800
Maximum Device Rating	Power Class III	Power Class III
Modulation Mode	Frequency Modulation	Quadrature Phase Shift Keying
Duty Cycle	1	1/3
Transmitter Frequency Range (MHz)	824.04 - 848.97	824.04 - 848.97

3.1 Picture of Phone

The tested device, GMLRH-21 is shown below with the EL and Star Wars 'A' Covers: -



3.2 Description of the Antenna

Type	Internal integrated antenna
Location	Inside the back cover, near the top of the device

3.3 Battery Options

There are two battery options available for the tested device, a BLC-2 and a BLC-1. Both batteries are rechargeable Li-ion.

3.4 Body Worn Operation

Body SAR was evaluated with a separation distance of 22mm and with the HDE-2 headset connected.

4. TEST CONDITIONS

4.1 Ambient Conditions

Ambient temperature (°C)	22±2
Tissue simulating liquid temperature (°C)	20±2
Humidity (%)	43

4.2 RF characteristics of the test site

Tests were performed in a fully enclosed RF shielded environment.

4.3 Test Signal, Frequencies, and Output Power

The device was controlled by using a radio tester. Communication between the device and the tester was established by air link.

Measurements were performed on the lowest, middle and highest channels of the operating band as considered appropriate.

The phone was set to maximum power level during all tests and at the beginning of each test the battery was fully charged.

The DASY3 system measures power drift during SAR testing by comparing e-field in the same location at the beginning and at the end of measurement. These records were used to monitor stability of power output.

5. DESCRIPTION OF THE TEST EQUIPMENT

The measurements were performed with an automated near-field scanning system, DASY3, manufactured by Schmid & Partner Engineering AG (SPEAG) in Switzerland.

Test Equipment	Model	NMP #	Serial Number	Due Date
DASY3, Data Acquisition	DAE V1	2292	389	07/03
DASY3, Data Acquisition	DAE V1	2108	377	11/03
E-field Probe	ET3DV6	2954	1504	07/03
E-field Probe	ET3DV6	2956	1505	09/03
Dipole Validation Kit	D835V2	3746	487	05/04
Dipole Validation Kit	D900V2	3670	025	10/03
Dipole Validation Kit	D835V2	3453	455	07/04

E-field probe and dipole validation kit calibration records are presented in Appendix D.

Additional equipment (required for validation).

Test Equipment	Model	NMP #	Serial Number	Due Date
Signal Generator	HP 8648C	2667	3847U02985	11/03
Amplifier	AR 5S1G4	0188	25583	-
Coupler	AR DC7144	2057	25304	-
Power Meter	Boonton 4232A	0147	26001	07/03
Power Sensor	Boonton 51015	0163	31143	07/03
Power Sensor	Boonton 51015	0164	31144	07/03
Thermometer	Omega CL27	3392	T-228448	07/03
Power Meter	Boonton 4232A	2996	64701	07/04
Power Sensor	Boonton 51015	2997	32187	07/04
Power Sensor	Boonton 51015	2998	32188	07/04
Thermometer	Omega CL27	3391	T-228450	06/04
Network Analyzer	Agilent 8753ES	2605	US39174932	01/04
Dielectric Probe Kit	Agilent 85070C	3089	US99360172	-

The calibration interval on all items listed above can be obtained from the Engineering Services Group within NMP, Product Creation - Dallas. Where relevant, measuring equipment is subjected to in-service checks between testing. TCC - Dallas shall notify clients promptly, in writing, of identification of defective measuring equipment that casts doubt on the validity of results given in this report.

5.1 System Accuracy Verification

The manufacturer calibrates the probes annually. Dielectric parameters of the simulating liquids are measured using an Agilent 85070C dielectric probe kit and an HP 8720D network analyzer.

SAR measurements of the tested device were performed within 24 hours of system accuracy verification, which was done using the dipole validation kit.

The dipole antenna's, which are manufactured by Schmid & Partner Engineering AG, are matched to be used near a flat phantom filled with tissue simulating solution. Length of the 835 MHz dipole is 161mm with an overall height of 330mm; length of the 900MHz dipole is 149mm with an overall height of 300mm. A specific distance holder is used in the positioning to ensure correct spacing between the phantom and the dipole.

A power level of 250 mW was supplied to the dipole antenna placed under the flat section of the SAM phantom. Validation results are in the table below and a print out of the validation tests are presented in Appendix B. All the measured parameters were within specification.

5.1.1 Head Tissue

Tissue	f (MHz)	Description (Date Measured)	SAR (W/kg), 1g	Dielectric Parameters		Temp (°C)
				ϵ_r	σ (S/m)	
Head	900	23-April-03	12.04	39.7	1.00	20.5
		24-April-03	12.12	39.5	1.00	20.6
		25-April-03	11.92	39.8	1.00	20.5
		Reference Result	11.36	41.5	0.97	N/A
	835	5-August-03	9.76	41.5	0.92	21.4
		12-August-03	9.84	41.2	0.90	21.5
		2-September-03	9.80	41.3	0.90	21.5
		3-September-03	9.88	40.9	0.92	21.5
		4-September-03	9.76	40.9	0.91	21.2
		Reference Result	9.80	42.8	0.89	N/A

5.1.2 Muscle Tissue

Tissue	f (MHz)	Description (Date Measured)	SAR (W/kg), 1g	Dielectric Parameters		Temp (°C)
				ϵ_r	σ (S/m)	
Muscle	835	25-April-03	10.80	54.9	0.95	20.5
		Reference Result	10.10	55.3	0.95	N/A
		29-August-03	10.32	53.9	0.96	21.8
		4-September-03	10.08	53.7	0.96	21.8
		Reference Result	10.10	54.03	0.96	N/A

5.2 Tissue Simulants

All dielectric parameters of tissue simulants were measured within 24 hours of SAR measurements. The depth of the tissue simulant in the ear reference point of the phantom was $15\text{cm} \pm 5\text{mm}$ during all tests. Volume for each tissue simulant was 27 litres.

5.2.1 Head Tissue Simulant

The composition of the brain tissue simulating liquid for 835 MHz is: -

51.07%	De-Ionized Water
47.31%	Sugar
1.15%	Salt
0.23%	HEC
0.24%	Bactericide

f (MHz)	Description (Date Measured)	Dielectric Parameters		Temp (°C)
		ϵ_r	σ (S/m)	
836.52	23-April-03	40.5	0.94	20.5
	24-April-03	40.2	0.94	20.6
	25-April-03	40.5	0.95	20.5
	5-August-03	41.5	0.92	21.4
	12-August-03	41.2	0.90	21.5
	2-September-03	41.3	0.91	21.5
	3-September-03	40.9	0.92	21.5
	4-September-03	40.8	0.91	21.2
	Recommended Values	41.5	0.90	N/A

Recommended values are adopted from OET Bulletin 65 (97-01) Supplement C (01-01).

5.2.2 Muscle Tissue Simulant

The composition of the muscle tissue simulating liquid for 835 MHz is: -

65.45%	De-Ionized Water
34.31%	Sugar
0.62%	Salt
0.10%	Bactericide

f (MHz)	Description (Date Measured)	Dielectric Parameters		Temp (°C)
		ϵ_r	σ (S/m)	
836.52	25-April-03	54.9	0.95	20.5
	29-August-03	53.9	0.96	21.8
	4-September-03	53.7	0.96	21.8
	Recommended Values	55.2	0.97	N/A

Recommended values are adopted from OET Bulletin 65 (97-01) Supplement C (01-01).

5.3 Phantoms

"SAM v4.0" phantom", manufactured by SPEAG, was used during the measurement. It has a fiberglass shell integrated into a wooden table. The shape of the shell corresponds to the phantom defined by SCC34-SC2. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. Reference markings on the phantom allow the complete set-up of all predefined phantom positions and measurement grids by manually teaching three points in the robot.



The thickness of phantom shell is 2 mm except for the ear, where an integrated ear spacer provides a 6 mm spacing from the tissue boundary. Manufacturer reports tolerance in shell thickness to be ± 0.1 mm.

5.4 Isotropic E-Field Probe ET3DV6

Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., glycol ether)
Calibration	Calibration certificate in Appendix D
Frequency	10 MHz to 3 GHz (dosimetry); Linearity: ± 0.2 dB (30 MHz to 3 GHz)
Optical Surface Detection	± 0.2 mm repeatability in air and clear liquids over diffuse reflecting surfaces
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.4 dB in HSL (rotation normal to probe axis)
Dynamic Range	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB
Dimensions	Overall length: 330 mm Tip length: 16 mm Body diameter: 12 mm Tip diameter: 6.8 mm Distance from probe tip to dipole centers: 2.7 mm
Application	General dosimetry up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms



6. DESCRIPTION OF THE TEST PROCEDURE

6.1 Test Positions

The device was placed into a holder using a special positioning tool, which aligns the bottom of the device with the holder and ensures that holder contacts only to the sides of the device. After positioning is done, the tool is removed. This method provides standard positioning and separation, and also ensures free space for antenna.

Device holder was provided by SPEAG together with the DASY3.



6.1.1 Against Phantom Head

Measurements were made on both the "left hand" and "right hand" side of the phantom.

Device was positioned against the phantom according to IEEE P1528/D1.2, April 21, 2003; Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques

6.1.1.1 Initial Ear Position

The device was initially positioned with the earpiece region pressed against the ear spacer of a head phantom parallel to the "Neck-Front" line defined along the base of the ear spacer that contains the "ear reference point". The "test device reference point" is aligned to the "ear reference point" on the head phantom and the "vertical centerline" is aligned to the "phantom reference plane".

6.1.1.2 Touch Position

"Initial ear position" alignments are maintained and the device is brought toward the mouth of the head phantom by pivoting along the "Neck-Front" line until any point on the display, keypad or mouthpiece portions of the handset is in contact with the phantom or when any portion of a foldout, sliding or similar keypad cover opened to its intended self-adjusting normal use position is in contact with the cheek or mouth of the phantom.

The following picture shows the tested device in the left touch position:



Tilt Position

In the "Touch Position", if the earpiece of the device is not in full contact with the phantom's ear spacer and the peak SAR location for the "touch position" is located at the ear spacer region or corresponds to the earpiece region of the handset, the device is returned to the "initial ear position" by rotating it away from the mouth until the earpiece is in full contact with the ear spacer. Otherwise, the device is moved away from the cheek perpendicular to the line passes through both "ear reference points" for approximate 2-3 cm. While it is in this position, the device is tilted away from the mouth with respect to the "test device reference point" by 15°. After the tilt, it is then moved back toward the head perpendicular to the line passes through both "ear reference points" until the device touches the phantom or the ear spacer. If the antenna touches the head first, the positioning process is repeated with a tilt angle less than 15° so that the device and its antenna would touch the phantom simultaneously.


The following picture shows the tested device in the left tilt position:



6.1.2 Body Worn Configuration

Body SAR measurements were performed with the antenna facing towards the flat part of the phantom with a separation distance of 22mm and with the HDE-2 headset connected.

The following picture shows the tested device in the body test position: -



Note: the 22mm spacer was removed before the SAR measurement.

6.2 Scan Procedures

First coarse scans are used for quick determination of the field distribution. Next a cube scan, 5x5x7 points; spacing between each point 8x8x5 mm, is performed around the highest E-field value to determine the averaged SAR-distribution over 1g.

6.3 SAR Averaging Methods

The maximum SAR value is averaged over its volume using interpolation and extrapolation.

The interpolation of the points is done with a 3d-Spline. The 3d-Spline is composed of three one-dimensional splines with the "Not a knot" -condition [W. Gander, Computermathematik, p. 141-150] (x, y and z -directions) [Numerical Recipes in C, Second Edition, p 123].

The extrapolation is based on least square algorithm [W. Gander, Computermathematik, p.168-180]. Through the points in the first 30 mm in all z-axis, polynomials of order four are calculated. This polynomial is then used to evaluate the points between the surface and the probe tip. The points, calculated from the surface, have a distance of 1mm from one another.

7. MEASUREMENT UNCERTAINTY

7.1 Description of Individual Measurement Uncertainty

7.1.1 Assessment Uncertainty

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	$e = f(d,k)$	<i>F</i>	$h = c \times f / e$	<i>k</i>
Uncertainty Component	Section in P1528.	Tol. (%)	Prob. Dist.	Div.	c_i	u_i (%)	v_i
Measurement System							
Probe Calibration	E2.1	±4.8	N	1	1	±4.8	∞
Axial Isotropy	E2.2	±4.7	R	√3	$(1-c_p)^{1/2}$	±1.9	∞
Hemispherical Isotropy	E2.2	±9.6	R	√3	√ c_p	±3.9	∞
Boundary Effect	E2.3	±8.3	R	√3	1	±4.8	∞
Linearity	E2.4	±4.7	R	√3	1	±2.7	∞
System Detection Limits	E2.5	±1.0	R	√3	1	±0.6	∞
Readout Electronics	E2.6	±1.0	N	1	1	±1.0	∞
Response Time	E2.7	±0.8	R	√3	1	±0.5	∞
Integration Time	E2.8	±2.6	R	√3	1	±1.5	∞
RF Ambient Conditions – Noise	E6.1	±3.0	R	√3	1	±1.7	∞
RF Ambient Conditions – Reflections	E6.1	±3.0	R	√3	1	±1.7	∞
Probe Positioner Mechanical Tolerance	E6.2	±0.4	R	√3	1	±0.2	∞
Probe Positioning with respect to Phantom Shell	E6.3	±2.9	R	√3	1	±1.7	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E5.2	±3.9	R	√3	1	±2.3	∞
Test sample Related							
Test Sample Positioning	E4.2.1	±6.0	N	1	1	±6.0	11
Device Holder Uncertainty	E4.1.1	±5.0	N	1	1	±5.0	7
Output Power Variation – SAR drift measurement	6.6.3	±10.0	R	√3	1	±5.8	∞
Phantom and Tissue Parameters							
Phantom Uncertainty (shape and thickness tolerances)	E3.1	±4.0	R	√3	1	±2.3	∞
Liquid Conductivity Target – tolerance	E3.2	±5.0	R	√3	0.64	±1.8	∞
Liquid Conductivity – measurement uncertainty	E3.3	±5.5	N	1	0.64	±3.5	5

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e = f(d,k)</i>	<i>F</i>	<i>h = c x f / e</i>	<i>k</i>
Uncertainty Component	Section in P1528.	Tol. (%)	Prob. Dist.	Div.	<i>c_i</i>	<i>u_i</i> (%)	<i>v_i</i>
Measurement System							
Liquid Permittivity Target tolerance	E3.2	±5.0	R	√3	0.6	±1.7	∞
Liquid Permittivity - measurement uncertainty	E3.3	±2.9	N	1	0.6	±1.7	5
Combined Standard Uncertainty			RSS			±14.5	208
Expanded Uncertainty (95% CONFIDENCE INTERVAL)						±29.1	

8. RESULTS

Corresponding SAR distribution print outs of maximum results in every operating mode and position are shown in Appendix C; z-axis plots of the maximum measurement results in head and body worn configurations are also included. The SAR distributions are substantially similar or equivalent to the plots submitted, regardless of used channel in each mode and position unless otherwise presented.

Note: the results recorded in the following tables for head and body are the highest values measured from the four HWID's and the two 'A' covers that were tested.

8.1 Head Configuration

BLC-2 Battery

Mode	Channel/ f(MHz)	Power (dBm)	SAR, averaged over 1g (mW/g)			
			Left-hand		Right-hand	
			Touch	Tilt	Touch	Tilt
AMPS	991 / 824.04	24.93	0.91	-	0.80	-
	384 / 836.52	24.73	1.26	0.74	1.16	0.70
	799 / 848.97	24.56	1.17	-	1.22	-

BLC-1 Battery Check

Mode	Channel/ f(MHz)	Power (dBm)	SAR, averaged over 1g (mW/g)			
			Left-hand		Right-hand	
			Touch	Tilt	Touch	Tilt
AMPS	991 / 824.04	24.93	0.70	-	0.72	-
	384 / 836.52	24.73	1.00	0.72	1.04	0.69
	799 / 848.97	24.56	1.10	-	1.05	-

8.2 Body Worn Configuration

Body SAR measurements were performed with the HDE-2 headset connected.

BLC-2 Battery

Mode	Channel/ <i>f</i> (MHz)	Power (dBm)	SAR, averaged over 1g (mW/g)
			HDE-2
AMPS	384 / 836.52	24.73	0.69


BLC-1 Battery Check

Mode	Channel/ <i>f</i> (MHz)	Power (dBm)	SAR, averaged over 1g (mW/g)
			HDE-2
AMPS	384 / 836.52	24.73	0.70

APPENDIX A: SCOPE OF ACCREDITATION FOR A2LA

TCC-Dallas is accredited by the American Association for Laboratory Accreditation (A2LA) as shown in the scope below:



 American Association for Laboratory Accreditation

SCOPE OF ACCREDITATION TO ISO/IEC 17025:1999

NOKIA MOBILE PHONES
TEST & CERTIFICATION CENTER - DALLAS
6021 Connection Drive
Irving, TX 75039
Alan Ewing Phone: 972.894.4744

ELECTRICAL

Valid to: November 30, 2003 Certificate Number: 1819-01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following Electromagnetic Compatibility (EMC), Specific Absorption Rate (SAR), and tests on wireless communications devices:

Tests	Test Method
<i>Emissions</i>	
Conducted and Radiated	CFR 47 Part 2, 15, 22, 24 CISPR 22; EN 55022 ICES-003; RSS-128, 132 and 133 3GPP TS 51.010-1 Section 12.2 ETSI EN 301.489-1; EN 301.489-7 (using ANSI C63.4 and RSS-212)
Specific Absorption Rate	IEEE 1528 EN 50360; EN 50361 CFR 47 Parts 2 and 24 OET Bulletin 65 and Supplement C RSS-102
<i>Immunity</i>	
Vehicular Immunity	ISO 7637-1; ETSI EN 301.489-1; EN 301.489-7
Electrostatic Discharge (ESD)	EN 61000-4-2; ETSI EN 301.489-1; EN 301.489-7
RF Radiated	EN 61000-4-3; ETSI EN 301.489-1; EN 301.489-7
Electrical Fast Transient/Burst	EN 61000-4-4; ETSI EN 301.489-1; EN 301.489-7
Surge	EN 61000-4-5; ETSI EN 301.489-1; EN 301.489-7
Conducted	EN 61000-4-6; ETSI EN 301.489-1; EN 301.489-7
Voltage Dips, Short Interruptions and Voltage Variations	EN 61000-4-11; ETSI EN 301.489-1; EN 301.489-7

(A2LA Cert. No. 1819.01) Revised 09/18/02 Page 1 of 2
5301 Buckeystown Pike, Suite 350 • Frederick, MD 21704-8373 • Phone: 301-644-3248 • Fax: 301-662-2974

Tests	Test Method
<i>Wireless</i>	
GSM (850/900/1800/1900 MHz)	3GPP TS 51.010-1, -2, -3 3GPP TS 11.10-4 ETSI EN 301.489-1
TDMA	CTIA TDMA/AMPS Test Plan (excluding Sections 7.3.3 & 7.3.4) TIA-EIA-136-270

(A2LA Cert. No. 1819.01) Revised 09/18/02 Page 2 of 2

"This laboratory is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this report have been determined to be in accordance with the laboratory's terms of accreditation unless stated otherwise in the report."

Should this report contain any data for tests for which we are not accredited, such data would not be covered by this laboratory's A2LA accreditation

APPENDIX B: VALIDATION TEST PRINTOUTS

Dipole 900 MHz, Head Validation

SAM 1 (Cellular - Brain Tissue)

Frequency: 900 MHz; Crest factor: 1.0

Validation 900MHz - Brain Tissue: $\sigma = 1.00$ mho/m $\epsilon_r = 39.7$ $\rho = 1.00$ g/cm³


Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50)

Cubes (2): Peak: 4.93 mW/g ± 0.06 dB, SAR (1g): 3.01 mW/g ± 0.06 dB, SAR (10g): 1.87 mW/g ± 0.06 dB, (Worst-case extrapolation)

Penetration depth: 11.0 (9.9, 12.5) [mm]

Powerdrift: -0.20 dB

Liquid Temperature (°C): 20.5



Dipole 900 MHz, Head Validation

SAM 1 (Cellular - Brain Tissue) Phantom

Frequency: 900 MHz; Crest factor: 1.0

Validation 900MHz - Brain Tissue: $\sigma = 1.00$ mho/m $\epsilon_r = 39.5$ $\rho = 1.00$ g/cm³


Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50)

Cubes (2): SAR (1g): 3.03 mW/g ± 0.06 dB, SAR (10g): 1.88 mW/g ± 0.06 dB, (Worst-case extrapolation)

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Powerdrift: -0.18 dB

Liquid Temperature (°C): 20.6



Dipole 900 MHz, Head Validation

SAM 1 (Cellular - Brain Tissue)

Frequency: 900 MHz; Crest factor: 1.0

Validation 900MHz - Brain Tissue: $\sigma = 1.00$ mho/m $\epsilon_r = 39.8$ $\rho = 1.00$ g/cm³


Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50)

Cubes (2): Peak: 4.87 mW/g ± 0.08 dB, SAR (1g): 2.98 mW/g ± 0.08 dB, SAR (10g): 1.85 mW/g ± 0.07 dB, (Worst-case extrapolation)

Penetration depth: 11.0 (9.9, 12.5) [mm]

Powerdrift: -0.20 dB

Liquid Temperature (°C): 20.5



Dipole 835 MHz, Head Validation

SAM 1 (Cellular - Brain Tissue)

Frequency: 835 MHz; Crest factor: 1.0

Validation 835MHz - Brain Tissue: $\sigma = 0.92$ mho/m $\epsilon_r = 41.5$ $\rho = 1.00$ g/cm³


Probe: ET3DV6 - SN1505; ConvF(7.00,7.00,7.00)

Cubes (2): Peak: 3.66 mW/g ± 0.06 dB, SAR (1g): 2.44 mW/g ± 0.06 dB, SAR (10g): 1.59 mW/g ± 0.06 dB, (Advanced extrapolation)

Penetration depth: 12.9 (12.3, 13.7) [mm]

Powerdrift: 0.00 dB

Liquid Temperature (°C): 21.4



Dipole 835 MHz, Head Validation

SAM 1 (Cellular - Brain Tissue)

Frequency: 835 MHz; Crest factor: 1.0

Validation 835MHz - Brain Tissue: $\sigma = 0.90$ mho/m $\epsilon_r = 41.2$ $\rho = 1.00$ g/cm³


Probe: ET3DV6 - SN1505; ConvF(7.00,7.00,7.00)

Cubes (2): Peak: 3.68 mW/g ± 0.03 dB, SAR (1g): 2.46 mW/g ± 0.04 dB, SAR (10g): 1.61 mW/g ± 0.04 dB, (Advanced extrapolation)

Penetration depth: 13.0 (12.5, 13.7) [mm]

Powerdrift: -0.03 dB

Liquid Temperature (°C): 21.5



Dipole 835 MHz, Head Validation

SAM 1 (Cellular - Brain Tissue)

Frequency: 835 MHz; Crest factor: 1.0

Validation 835MHz - Brain Tissue: $\sigma = 0.90$ mho/m $\epsilon_r = 41.3$ $\rho = 1.00$ g/cm³


Probe: ET3DV6 - SN1505; ConvF(7.00,7.00,7.00)

Cubes (2): Peak: 3.67 mW/g ± 0.04 dB, SAR (1g): 2.45 mW/g ± 0.04 dB, SAR (10g): 1.60 mW/g ± 0.05 dB, (Advanced extrapolation)

Penetration depth: 13.0 (12.4, 13.7) [mm]

Powerdrift: 0.00 dB

Liquid Temperature (°C): 21.5



Dipole 835 MHz, Head Validation

SAM 1 (Cellular - Brain Tissue)

Frequency: 835 MHz; Crest factor: 1.0

Validation 835MHz - Brain Tissue: $\sigma = 0.92$ mho/m $\epsilon_r = 40.9$ $\rho = 1.00$ g/cm³


Probe: ET3DV6 - SN1505; ConvF(7.00,7.00,7.00)

Cubes (2): Peak: 3.69 mW/g ± 0.03 dB, SAR (1g): 2.47 mW/g ± 0.04 dB, SAR (10g): 1.62 mW/g ± 0.04 dB, (Advanced extrapolation)

Penetration depth: 13.0 (12.5, 13.7) [mm]

Powerdrift: -0.01 dB

Liquid Temperature (°C): 21.5



Dipole 835 MHz, Head Validation

SAM 1 (Cellular - Brain Tissue)

Frequency: 835 MHz; Crest factor: 1.0

Validation 835MHz - Brain Tissue: $\sigma = 0.91$ mho/m $\epsilon_r = 40.9$ $\rho = 1.00$ g/cm³


Probe: ET3DV6 - SN1505; ConvF(7.00,7.00,7.00)

Cubes (2): Peak: 3.67 mW/g ± 0.02 dB, SAR (1g): 2.44 mW/g ± 0.03 dB, SAR (10g): 1.60 mW/g ± 0.04 dB, (Advanced extrapolation)

Penetration depth: 12.9 (12.3, 13.7) [mm]

Powerdrift: -0.04 dB

Liquid Temperature (°C): 21.2



Dipole 835 MHz, Body Validation

SAM 2 (Cellular - Muscle Tissue) Phantom

Frequency: 835 MHz; Crest factor: 1.0

Validation 835MHz - Muscle Tissue: $\sigma = 0.95$ mho/m $\epsilon_r = 54.9$ $\rho = 1.00$ g/cm³


Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50)

Cubes (2): SAR (1g): 2.70 mW/g ± 0.06 dB, SAR (10g): 1.75 mW/g ± 0.06 dB, (Worst-case extrapolation)

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Powerdrift: -0.17 dB

Liquid Temperature (°C): 20.5



Dipole 835 MHz, Body Validation

SAM 2 (Cellular - Muscle Tissue)

Frequency: 835 MHz; Crest factor: 1.0

Validation 835MHz - Muscle Tissue: $\sigma = 0.96$ mho/m $\epsilon_r = 53.9$ $\rho = 1.00$ g/cm³


Probe: ET3DV6 - SN1505; ConvF(6.70,6.70,6.70)

Cubes (2): Peak: 3.77 mW/g ± 0.06 dB, SAR (1g): 2.58 mW/g ± 0.06 dB, SAR (10g): 1.71 mW/g ± 0.06 dB, (Advanced extrapolation)

Penetration depth: 13.8 (13.3, 14.4) [mm]

Powerdrift: -0.04 dB

Liquid Temperature (°C): 21.8



Dipole 835 MHz, Body Validation

SAM 2 (Cellular - Muscle Tissue)

Frequency: 835 MHz; Crest factor: 1.0

Validation 835MHz - Muscle Tissue: $\sigma = 0.96$ mho/m $\epsilon_r = 53.7$ $\rho = 1.00$ g/cm³


Probe: ET3DV6 - SN1505; ConvF(6.70,6.70,6.70)

Cubes (2): Peak: 3.66 mW/g ± 0.05 dB, SAR (1g): 2.52 mW/g ± 0.05 dB, SAR (10g): 1.68 mW/g ± 0.04 dB, (Advanced extrapolation)

Penetration depth: 13.8 (13.4, 14.4) [mm]

Powerdrift: 0.04 dB

Liquid Temperature (°C): 21.8



APPENDIX C: SAR DISTRIBUTION PRINTOUTS

GMLRH-21, AMPS, Channel 384, Left Touch Position with BLC-2 Battery

SAM 1 (Cellular - Brain Tissue) Phantom

Frequency: 837 MHz; Crest factor: 1.0

Cellular Band - Brain Tissue: $\sigma = 0.94$ mho/m $\epsilon_r = 40.5$ $\rho = 1.00$ g/cm³


Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50)

Cube 5x5x7: SAR (1g): 1.26 mW/g, SAR (10g): 0.858 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: 0.09 dB

Liquid Temperature (°C): 20.5



GMLRH-21, AMPS, Channel 384, Left Tilt Position with BLC-2 Battery

SAM 1 (Cellular - Brain Tissue) Phantom

Frequency: 837 MHz; Crest factor: 1.0

Cellular Band - Brain Tissue: $\sigma = 0.94$ mho/m $\epsilon_r = 40.5$ $\rho = 1.00$ g/cm³


Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50)

Cube 5x5x7: SAR (1g): 0.737 mW/g, SAR (10g): 0.441 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: 0.03 dB

Liquid Temperature (°C): 20.5



GMLRH-21, AMPS, Channel 799, Right Touch Position with BLC-2 Battery

SAM 1 (Cellular - Brain Tissue) Phantom

Frequency: 849 MHz; Crest factor: 1.0

Cellular Band - Brain Tissue: $\sigma = 0.92$ mho/m $\epsilon_r = 40.9$ $\rho = 1.00$ g/cm³


Probe: ET3DV6 - SN1505; ConvF(7.00,7.00,7.00)

Cube 5x5x7: SAR (1g): 1.22 mW/g, SAR (10g): 0.845 mW/g, (Worst-case extrapolation)

Coarse: Dx = 19.0, Dy = 14.0, Dz = 10.0

Powerdrift: -0.39 dB

Liquid Temperature (°C): 21.5



GMLRH-21, AMPS, Channel 384, Right Tilt Position with BLC-2 Battery

SAM 1 (Cellular - Brain Tissue) Phantom

Frequency: 837 MHz; Crest factor: 1.0

Cellular Band - Brain Tissue: $\sigma = 0.94$ mho/m $\epsilon_r = 40.2$ $\rho = 1.00$ g/cm³


Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50)

Cube 5x5x7: SAR (1g): 0.696 mW/g, SAR (10g): 0.431 mW/g, (Worst-case extrapolation)

Coarse: Dx = 19.0, Dy = 14.0, Dz = 10.0

Powerdrift: -0.14 dB

Liquid Temperature (°C): 20.6



GMLRH-21, AMPS, Channel 384, Flat Position - Back of Phone with 22mm Spacer, HDE-2 Headset and BLC-1 Battery

SAM 2 (Cellular - Muscle Tissue) Phantom

Frequency: 837 MHz; Crest factor: 1.0

Cellular Band - Muscle Tissue: $\sigma = 0.95$ mho/m $\epsilon_r = 54.9$ $\rho = 1.00$ g/cm³


Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50)

Cube 5x5x7: SAR (1g): 0.698 mW/g, SAR (10g): 0.494 mW/g, (Worst-case extrapolation)

Coarse: Dx = 15.0, Dy = 15.0, Dz = 12.0

Powerdrift: 0.04 dB

Liquid Temperature (°C): 20.5



GMLRH-21, AMPS, Channel 384, Left Touch Position with BLC-2 Battery

SAM 1 (Cellular - Brain Tissue) Phantom

Frequency: 837 MHz; Crest factor: 1.0


Cellular Band - Brain Tissue: $\sigma = 0.94$ mho/m $\epsilon_r = 40.5$ $\rho = 1.00$ g/cm³

Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50)

Cube 5x5x7: SAR (1g): 1.26 mW/g, SAR (10g): 0.858 mW/g, (Worst-case extrapolation)

Cube 5x5x7: Dx = 8.0, Dy = 8.0, Dz = 5.0

Liquid Temperature (°C): 20.5



GMLRH-21, AMPS, Channel 384, Flat Position - Back of Phone with 22mm Spacer, HDE-2 Headset and BLC-1 Battery

SAM 2 (Cellular - Muscle Tissue) Phantom

Frequency: 837 MHz; Crest factor: 1.0

Cellular Band - Muscle Tissue: $\sigma = 0.95$ mho/m $\epsilon_r = 54.9$ $\rho = 1.00$ g/cm³

Probe: ET3DV6 - SN1504; ConvF(6.50,6.50,6.50)

Cube 5x5x7: SAR (1g): 0.698 mW/g, SAR (10g): 0.494 mW/g, (Worst-case extrapolation)

Cube 5x5x7: Dx = 8.0, Dy = 8.0, Dz = 5.0

Liquid Temperature (°C): 20.5

