

CFR 47 FCC PART 15 SUBPART C ISED RSS-247 ISSUE 2

CERTIFICATION TEST REPORT

For

WiseCube

MODEL NUMBER: CHB63

FCC ID: 2AB7X-WISECUBE2

IC: 24228-WISECUBE2

REPORT NUMBER: 4789585111.1-10

ISSUE DATE: September 11, 2020

Prepared for

BBPOS International Limited Suite 1903-04, Tower 2, Nina Tower, 8 Yeung Uk Road, Tsuen Wan, NT, Hong Kong

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

> Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products. This report does not imply that the product(s) has met the criteria for certification.



Revision History

Rev.	Issue Date	Revisions	Revised By
V0	09/11/2020	Initial Issue	



Summary of Test Results				
Clause	Test Items	FCC/ISED Rules	Test Results	
1	20dB Bandwidth and 99% Occupied Bandwidth	FCC 15.247 (a) (1) RSS-247 Clause 5.1 (a) RSS-Gen Clause 6.7	Pass	
2	Conducted Output Power	FCC 15.247 (b) (1) RSS-247 Clause 5.1 (b)	Pass	
3	Carrier Hopping Channel Separation	FCC 15.247 (a) (1) RSS-247 Clause 5.1 (b)	Pass	
4	Number of Hopping Frequency	15.247 (a) (1) III RSS-247 Clause 5.1 (d)	Pass	
5	Time of Occupancy (Dwell Time)	15.247 (a) (1) III RSS-247 Clause 5.1 (d)	Pass	
6	Conducted Bandedge	FCC 15.247 (d) RSS-247 Clause 5.5	Pass	
7	Radiated Bandedge and Spurious	FCC 15.247 (d) FCC 15.209 FCC 15.205 RSS-247 Clause 5.5 RSS-GEN Clause 8.9 RSS-GEN Clause 8.10	Pass	
8	Conducted Emission Test for AC Power Port	FCC 15.207 RSS-GEN Clause 8.8	Pass	
9	Antenna Requirement	FCC 15.203 RSS-GEN Clause 6.8	Pass	
Noto:				

Note:

1. This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

2. The measurement result for the sample received is <Pass> according to < CFR 47 FCC PART 15 SUBPART C >< ISED RSS-247 > when <Accuracy Method> decision rule is applied.



TABLE OF CONTENTS

1.	AT	TESTATION OF TEST RESULTS	. 6
2.	TES	ST METHODOLOGY	. 7
3.	FAG	CILITIES AND ACCREDITATION	. 7
4.	CA	LIBRATION AND UNCERTAINTY	. 8
4	4.1.	MEASURING INSTRUMENT CALIBRATION	. 8
4	4.2.	MEASUREMENT UNCERTAINTY	. 8
5.	EQ	UIPMENT UNDER TEST	. 9
ł	5.1.	DESCRIPTION OF EUT	. 9
ł	5.2.	MAXIMUM PEAK OUTPUT POWER	. 9
ł	5.3.	PACKET TYPE CONFIGURATION	. 9
ł	5.4.	CHANNEL LIST	10
ł	5.5.	TEST CHANNEL CONFIGURATION	10
ł	5.6.	WORST-CASE CONFIGURATIONS	10
ł	5.7.	THE WORSE CASE POWER SETTING PARAMETER	10
ł	5.8.	DESCRIPTION OF AVAILABLE ANTENNAS	11
į	5.9.	DESCRIPTION OF TEST SETUP	12
6.	ME	ASURING INSTRUMENT AND SOFTWARE USED	13
6. 7.	ME.	ASURING INSTRUMENT AND SOFTWARE USED TENNA PORT TEST RESULTS	13 15
6. 7.	ME AN ⁻ 7.1.	ASURING INSTRUMENT AND SOFTWARE USED TENNA PORT TEST RESULTS ON TIME AND DUTY CYCLE	13 15 15
6. 7.	ME AN ⁻ 7.1. 7.2.	ASURING INSTRUMENT AND SOFTWARE USED TENNA PORT TEST RESULTS ON TIME AND DUTY CYCLE 20 dB BANDWIDTH AND 99 % OCCUPIED BANDWIDTH	13 15 15 16
6. 7.	ME. AN [®] 7.1. 7.2.	ASURING INSTRUMENT AND SOFTWARE USED TENNA PORT TEST RESULTS ON TIME AND DUTY CYCLE 20 dB BANDWIDTH AND 99 % OCCUPIED BANDWIDTH CONDUCTED OUTPUT POWER	13 15 15 16 18
6. 7.	ME AN ⁻ 7.1. 7.2. 7.3. 7.4.	ASURING INSTRUMENT AND SOFTWARE USED TENNA PORT TEST RESULTS ON TIME AND DUTY CYCLE 20 dB BANDWIDTH AND 99 % OCCUPIED BANDWIDTH CONDUCTED OUTPUT POWER CARRIER FREQUENCY SEPARATION	13 15 15 16 18 19
6. 7.	ME. AN ⁷ 7.1. 7.2. 7.3. 7.4. 7.5.	ASURING INSTRUMENT AND SOFTWARE USED TENNA PORT TEST RESULTS ON TIME AND DUTY CYCLE 20 dB BANDWIDTH AND 99 % OCCUPIED BANDWIDTH CONDUCTED OUTPUT POWER CARRIER FREQUENCY SEPARATION NUMBER OF HOPPING FREQUENCIES	13 15 16 18 19 21
6. 7.	ME <i>i</i> AN ⁷ 7.1. 7.2. 7.3. 7.4. 7.5. 7.6.	ASURING INSTRUMENT AND SOFTWARE USED TENNA PORT TEST RESULTS ON TIME AND DUTY CYCLE 20 dB BANDWIDTH AND 99 % OCCUPIED BANDWIDTH CONDUCTED OUTPUT POWER CARRIER FREQUENCY SEPARATION NUMBER OF HOPPING FREQUENCIES TIME OF OCCUPANCY (DWELL TIME)	13 15 16 18 19 21 23
6. 7.	ME AN 7.1. 7.2. 7.3. 7.4. 7.5. 7.6. 7.7.	ASURING INSTRUMENT AND SOFTWARE USED TENNA PORT TEST RESULTS ON TIME AND DUTY CYCLE 20 dB BANDWIDTH AND 99 % OCCUPIED BANDWIDTH CONDUCTED OUTPUT POWER CONDUCTED OUTPUT POWER NUMBER OF HOPPING FREQUENCIES	 13 15 16 18 19 21 23 25
6. 7.	ME. AN 7.1. 7.2. 7.3. 7.4. 7.5. 7.6. 7.7. RAI	ASURING INSTRUMENT AND SOFTWARE USED TENNA PORT TEST RESULTS ON TIME AND DUTY CYCLE 20 dB BANDWIDTH AND 99 % OCCUPIED BANDWIDTH CONDUCTED OUTPUT POWER CARRIER FREQUENCY SEPARATION NUMBER OF HOPPING FREQUENCIES TIME OF OCCUPANCY (DWELL TIME) CONDUCTED BANDEDGE AND SPURIOUS EMISSION DIATED TEST RESULTS	 13 15 16 18 19 21 23 25 27
6. 7. 7. 8.	ME. AN 7.1. 7.2. 7.3. 7.3. 7.5. 7.6. 7.7. 8.1. 8.1.	ASURING INSTRUMENT AND SOFTWARE USED TENNA PORT TEST RESULTS ON TIME AND DUTY CYCLE	 13 15 16 18 19 21 23 25 27 33 33
6. 7. 7. 8. 8.	ME. AN 7.1. 7.2. 7.3. 7.4. 7.5. 7.6. 7.7. 8.1. 8.1. 8.2. 8.2.	ASURING INSTRUMENT AND SOFTWARE USED TENNA PORT TEST RESULTS. ON TIME AND DUTY CYCLE. 20 dB BANDWIDTH AND 99 % OCCUPIED BANDWIDTH	 13 15 16 19 21 23 25 27 33 33 37 37
6. 7. 7. 8. 8.	ME. AN 7.1. 7.2. 7.3. 7.4. 7.5. 7.6. 7.7. 8.1. 8.1. 8.2. 8.2. 8.3. 8.3.	ASURING INSTRUMENT AND SOFTWARE USED	13 15 16 19 21 23 25 27 33 37 37 43 43



	8.4.1.	GFSK MODE	49
	8.5. SP0 8.5.1.	URIOUS EMISSIONS (30 MHz ~ 1 GHz) GFSK MODE	51 51
	8.6. SP0 8.6.1.	URIOUS EMISSIONS BELOW 30 MHz GFSK MODE	53 53
9.		VER LINE CONDUCTED EMISSIONS	56
	9.1.1.	GFSK MODE	57
10	. ANTE	NNA REQUIREMENTS	59
	Anno	ndiv	60
1.1	. Appe		60
	11.1. A	ppendix A: Duty Cycle	60
	11.1.1.	Test Graphs	60
	11.0 A	Incondix D: 20dD Emission Bandwidth	62
	11.2. A	Test Result	02 62
	11.2.2.	Test Graphs	63
	11.3. A	ppendix C: Occupied Channel Bandwidth	65
	11.3.1.	Test Result	65
	11.3.2.	Test Graphs	66
	11.4. A	ppendix D: Maximum peak conducted output power	68
	11.4.1.	Test Result	68
	11.5. A	ppendix E: Carrier frequency separation	69
	11.5.1.	Test Result	69
	11.5.2.	Test Graphs	70
	11.6. A	ppendix F: Time of occupancy	71
	11.6.1.	Test Granhs	/1
	11.0.2. 11.7 A	Incording C: Number of bonning channels	
	11.7.1.	Test Result	74
	11.7.2.	Test Graphs	75
	11.8. A	ppendix H: Band edge measurements	76
	11.8.1.	Test Result	76
	11.8.2.	Test Graphs	77
	11.9. A	ppendix I: Conducted Spurious Emission	79
	11.9.1.	Test Result	79
	11.9.2.	rest Graphs	80



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: BBPOS International Limited				
Address:	Suite 1903-04, Tower 2, Nina Tower, 8 Yeung Uk Road, Tsuen			
	Wan, NT, Hong Kong			

Manufacturer Information

Company Name:	BBPOS International Limited
Address:	Suite 1903-04, Tower 2, Nina Tower, 8 Yeung Uk Road, Tsuen
	Wan, NT, Hong Kong

EUT Information

EUT Name:	WiseCube
Model:	CHB63
Brand:	BBPOS
Sample Received Date:	August 10, 2020
Sample Status:	Normal
Sample ID:	3241806
Date of Tested:	August 10, 2020~August 21, 2020

APPLICABLE STANDARDS				
STANDARD TEST RESULTS				
CFR 47 FCC PART 15 SUBPART C	PASS			
ISED RSS-247 Issue 2	PASS			
ISED RSS-GEN Issue 5	PASS			

Prepared By:

Kebo. zhang.

Kebo Zhang Project Engineer

Approved By:

Aephenbus

Checked By:

Sherry les

Shawn Wen Laboratory Leader

Stephen Guo Laboratory Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, CFR 47 FCC Part 15, ANSI C63.10-2013, ISED RSS-247 Issue 2 and ISED RSS-GEN Issue 5.

3. FACILITIES AND ACCREDITATION

	A2LA (Certificate No.: 4102.01)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	has been assessed and proved to be in compliance with A2LA.
	FCC (FCC Designation No.: CN1187)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	Has been recognized to perform compliance testing on equipment subject
	to the Commission's Delcaration of Conformity (DoC) and Certification rules
	ISED (Company No.: 21320)
Accreditation	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
Certificate	has been registered and fully described in a report filed with ISED.
	The Company Number is 21320.
	VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	has been assessed and proved to be in compliance with VCCI, the
	Membership No. is 3793.
	Facility Name:
	Chamber D, the VCCI registration No. is G-20019 and R-20004
	Shielding Room B, the VCCI registration No. is C-20012 and T-20011

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.



4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty		
Conduction emission	3.62 dB		
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB		
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB		
Radiated Emission	5.78 dB (1 GHz ~ 18 GHz)		
(Included Fundamental Emission) (1 GHz to 26 GHz)	5.23 dB (18 GHz ~ 26 GHz)		
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95 % confidence level using a coverage factor of k=2.			



5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	WiseCube		
Model	CHB63		
Technology	Bluetooth – BR		
Transmit Frequency Range	2402 MHz ~ 2480 MHz		
Mode	Basic Rate		
Modulation	GFSK		
Packet Type (Maximum Payload):	DH5		
Data Rate	1 Mbps		
Supply Voltage	Battery	DC 3.7V	
· · · · · · · · · ·			

Note: The EUT only support Basic Rate.

5.2. MAXIMUM PEAK OUTPUT POWER

Modulation	Frequency (MHz)	Channel Number	Maximum Peak Output Power (dBm)	Maximum EIRP (dBm)
GFSK	2402 ~ 2480	0-78[79]	0.27	-2.53

5.3. PACKET TYPE CONFIGURATION

Modulation	Packet Type	Setting (Packet Length)	
	DH1	27	
GFSK	DH3	183	
	DH5	339	



Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2422	40	2442	60	2462
01	2403	21	2423	41	2443	61	2463
02	2404	22	2424	42	2444	62	2464
03	2405	23	2425	43	2445	63	2465
04	2406	24	2426	44	2446	64	2466
05	2407	25	2427	45	2447	65	2467
06	2408	26	2428	46	2448	66	2468
07	2409	27	2429	47	2449	67	2469
08	2410	28	2430	48	2450	68	2470
09	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	/	/

5.4. CHANNEL LIST

5.5. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
GFSK-DH5	CH 0(Low Channel), CH 39(MID Channel), CH 78(High Channel)	2402 MHz, 2441 MHz, 2480 MHz
GFSK-DH5	Hopping	2402 MHz ~ 2480 MHz

5.6. WORST-CASE CONFIGURATIONS

Bluetooth Mode	Modulation Technology	Modulation Type	Data Rate	Packet Type
BR	FHSS	GFSK	1Mbit/s	DH5

5.7. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5 MHz Band						
Test Software FCC TestTool						
Modulation	Transmit Antenna	Test Software Setting Value				
	Number	CH 00	CH 39	CH 78		
GFSK	1	Default Default Default				

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.

5.8. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2402-2480	Metal Antenna	-2.8

Modulation	Transmit and Receive Mode	Description		
GFSK	⊠1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.		

Note: The value of the antenna gain was declared by customer.



5.9. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	P/N
1	Laptop	ThinkPad	T460S	SL10K24796 JS
2	UART	/	/	/

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	/	/	1.2	/

ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
/	/	/	/	/

TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.

SETUP DIAGRAM FOR TESTS



6. MEASURING INSTRUMENT AND SOFTWARE USED

	Conducted Emissions							
			Inst	rument				
Used	Equipment	Manufacturer	Mod	el No.	Serial No.		Last Cal.	Next Cal.
\checkmark	EMI Test Receiver	R&S	ES	SR3	10196	1	Dec.05,2019	Dec.05,2020
V	Two-Line V- Network	R&S	EN	V216	10198	3	Dec.05,2019	Dec.05,2020
			So	ftware				
Used	Desc	ription		Ma	nufacture	r	Name	Version
\checkmark	Test Software for Co	onducted distu	Irbanc	е	Farad		EZ-EMC	Ver. UL-3A1
		Ra	diated	l Emiss	sions			
			Inst	rument				
Used	Equipment	Manufacturer	Mod	el No.	Serial N	lo.	Last Cal.	Next Cal.
\checkmark	MXE EMI Receiver	KESIGHT	N90)38A	MY56400	0036	Dec.06,2019	Dec.06,2020
V	Hybrid Log Periodic Antenna	TDK	HLP-3003C		13096	0	Sep.17, 2018	Sep.17, 2021
\checkmark	Preamplifier	HP	84	47D	2944A09	099	Dec.05,2019	Dec.05,2020
V	EMI Measurement Receiver	R&S	ES	R26	10137	7	Dec.05,2019	Dec.05,2020
\checkmark	Horn Antenna	TDK	HRN	-0118	13093	9	Sep.17, 2018	Sep.17, 2021
V	High Gain Horn Antenna	Schwarzbeck	BBHA	\-9170	691		Aug.11, 2018	Aug.11, 2021
V	Preamplifier	TDK	PA-02	2-0118	TRS-30 0006)5- 3	Dec.05,2019	Dec.05,2020
V	Preamplifier	TDK	PA-	02-2	TRS-30 00003)7- 3	Dec.05,2019	Dec.05,2020
\checkmark	Loop antenna	Schwarzbeck	15	19B	0000	3	Jan.07, 2019	Jan.07, 2022
V	Preamplifier	TDK	PA-02 30	2-001-)00	TRS-30 0005)2-)	Dec.5, 2019	Dec.5, 2020
V	High Pass Filter	Wi	WHKX10- 2700-3000- 18000-40SS		23		Dec.05,2019	Dec.05,2020
			So	ftware				
Used	Descri	ption	P	Manufa	cturer		Name	Version
\checkmark	Test Software disturb	for Radiated ance		Fara	ad	E	Z-EMC	Ver. UL-3A1

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.



	Other instruments								
Used Equipment Manufacturer Model No. Serial No. Last Cal					Last Cal.	Next Cal.			
\checkmark	Spectrum Analyzer	Keysight	N9030A	MY55410512	Dec.06,2019	Dec.06,2020			
\checkmark	Spectrum Analyzer	Keysight	N9020A	MY49100060	Dec.06,2019	Dec.06,2020			
\checkmark	Power Meter	Keysight	N1911A	MY55416024	Dec.06,2019	Dec.06,2020			
\checkmark	Power Sensor	Keysight	U2021XA	MY5100022	Dec.06,2019	Dec.06,2020			



7. ANTENNA PORT TEST RESULTS

7.1. ON TIME AND DUTY CYCLE

LIMITS

None; for reporting purposes only.

PROCEDURE

Refer to ANSI C63.10-2013 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	25 °C	Relative Humidity	64.8 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.7 V

RESULTS

Please refer to appendix A.



7.2. 20 dB BANDWIDTH AND 99 % OCCUPIED BANDWIDTH

LIMITS

CFR 47FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2				
Section Test Item Limit Frequency Ra (MHz)				
CFR 47 FCC 15.247 (a) (1) RSS-247 Clause 5.1 (a) 20 dB Bandwidth		None; for reporting purposes only.	2400-2483.5	
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	None; for reporting purposes only.	2400-2483.5	

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 6.9.2.

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	For 20 dB Bandwidth: 1 % to 5 % of the 20 dB bandwidth For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 20 dB Bandwidth: approximately 3×RBW For 99 % Occupied Bandwidth: ≥ 3×RBW
Span	Approximately 2 to 3 times the 20dB bandwidth
Trace	Max hold
Sweep	Auto couple

Connect the EUT to the spectrum analyser and use the following settings:

a) Use the occupied bandwidth function of the instrument, allow the trace to stabilize and report the measured 99 % occupied bandwidth and 20 dB Bandwidth.

TEST SETUP





TEST ENVIRONMENT

Temperature	25 °C	Relative Humidity	64.8 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.7 V

RESULTS

Please refer to appendix B and C.



7.3. CONDUCTED OUTPUT POWER

LIMITS

CFR 47 FCC Part15 (15.247), Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247 (b) (1) ISED RSS-247 Clause 5.4 (b)	Peak Conducted Output Power	Hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel: 1 watt or 30 dBm; Hopping channel carrier frequencies that are separated by 25 kHz or two- thirds of the 20 dB bandwidth of the hopping channel: 125 mW or 21 dBm	2400-2483.5

TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

TEST SETUP



TEST ENVIRONMENT

Temperature	25 °C	Relative Humidity	64.8 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.7 V

RESULTS

Please refer to appendix D.



7.4. CARRIER FREQUENCY SEPARATION

LIMITS

CFR 47 FCC Part15 (15.247), Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247 (a) (1) ISED RSS-247 Clause 5.1 (b)	Carrier Frequency Separation	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel.	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 7.8.2.

Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Span	wide enough to capture the peaks of two adjacent channels
Detector	Peak
RBW	Start with the RBW set to approximately 30 % of the channel spacing; adjust as necessary to best identify the center of each individual channel.
VBW	≥RBW
Trace	Max hold
Sweep time	Auto couple

Allow the trace to stabilize and use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Compliance of an EUT with the appropriate regulatory limit shall be determined.

TEST SETUP





TEST ENVIRONMENT

Temperature	25 °C	Relative Humidity	64.8 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.7 V

<u>RESULTS</u>

Please refer to Appendix E.



7.5. NUMBER OF HOPPING FREQUENCIES

<u>LIMITS</u>

CFR 47 FCC Part15 (15.247), Subpart C ISED RSS-247 ISSUE 2			
Section Test Item Limit			
CFR 47 15.247 (a) (1) III ISED RSS-247 Clause 5.1 (d)	Number of Hopping Frequency	at least 15 hopping channels	

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 7.8.3.

Connect the EUT to the spectrum Analyzer and use the following settings:

Detector	Peak
RBW	To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
VBW	≥RBW
Span	The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
Trace	Max hold
Sweep time	Auto couple

Set EUT to transmit maximum output power and switch on frequency hopping function. then set enough count time (larger than 5000 times) to get all the hopping frequency channel displayed on the screen of spectrum analyzer, count the quantity of peaks to get the number of hopping channels.

TEST SETUP





TEST ENVIRONMENT

Temperature	25 °C	Relative Humidity	64.8 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.7 V

<u>RESULTS</u>

Please refer to appendix G.



7.6. TIME OF OCCUPANCY (DWELL TIME)

LIMITS

CFR 47 FCC Part15 (15.247), Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	
CFR 47 15.247 (a) (1) III ISED RSS-247 Clause 5.1 (d)	Time of Occupancy (Dwell Time)	The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds, multiplied by the number of hopping channels employed.	

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 7.8.4.

Connect the EUT to the spectrum Analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	1 MHz
VBW	≥RBW
Span	Zero span, centered on a hopping channel
Trace	Max hold
Sweep time	As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel

Use the marker-delta function to determine the transmit time per hop (Burst Width). If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

For FHSS Mode (79 Channel):

DH1 Dwell Time: Burst Width * (1600/2) * 31.6 / (channel number) DH3 Dwell Time: Burst Width * (1600/4) * 31.6 / (channel number) DH5 Dwell Time: Burst Width * (1600/6) * 31.6 / (channel number)

For AFHSS Mode (20 Channel):

DH1 Dwell Time: Burst Width * (1600/2) * 8 / (channel number) DH3 Dwell Time: Burst Width * (1600/4) * 8 / (channel number) DH5 Dwell Time: Burst Width * (1600/6) * 8 / (channel number)



TEST SETUP



TEST ENVIRONMENT

Temperature	25 °C	Relative Humidity	64.8 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.7 V

RESULTS

Please refer to appendix F.



7.7. CONDUCTED BANDEDGE AND SPURIOUS EMISSION

<u>LIMITS</u>

CFR 47 FCC Part15 (15.247), Subpart C ISED RSS-247 ISSUE 2			
Section Test Item Limit			
CFR 47 FCC §15.247 (d) ISED RSS-247 5.5	Conducted Spurious Emission	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power	

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 7.8.6 and 7.8.8.

Connect the EUT to the spectrum analyser and use the following settings for reference level measurement:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	≥3 × RBW
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	≥3 × RBW
measurement points	≥span/RBW
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements.

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.



TEST SETUP



TEST ENVIRONMENT

Temperature	25 °C	Relative Humidity	64.8 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.7 V

RESULTS

Please refer to appendix H & I.



8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Please refer to ISED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz-1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz				
Fraguenov Bongo	Field Strongth Limit	Field Strength Limit		
(MHz)	(uV/m) at 3 m	(dBuV/m) at 3 m		
(11112)	(uvini) at 5 m	Quasi-Peak		
30 - 88	100	40		
88 - 216	150	43.5		
216 - 960	200	46		
Above 960	500	54		
Above 1000	500	Peak	Average	
Above 1000	500	74	54	

FCC Emissions radiated outside of the specified frequency bands below 30 MHz				
Frequency (MHz) Field strength (microvolts/meter) Measurement distance (meters)				
0.009-0.490	2400/F(kHz)	300		
0.490-1.705	24000/F(kHz)	30		
1.705-30.0	30	30		

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz			
Frequency	Magnetic field strength (H-Field) (μA/m)	Measurement distance (m)	
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300	
490 - 1705 kHz	63.7/F (F in kHz)	30	
1.705 - 30 MHz	0.08	30	

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.



ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

Table 7 – Restricted frequency bands ^{Note 1}			
MHz	MHz	GHz	
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2	
0.495 - 0.505	158.52475 - 158.52525	9.3 - 9.5	
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7	
3.020 - 3.026	182.0125 - 187.17	13.25 - 13.4	
4.125 - 4.128	187.72 - 173.2	14.47 - 14.5	
4.17725 - 4.17775	240 - 285	15.35 - 16.2	
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4	
5.677 - 5.683	399.9 - 410	22.01 - 23.12	
6.215 - 6.218	608 - 614	23.6 - 24.0	
8.26775 - 6.26825	960 - 1427	31.2 - 31.8	
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5	
8.291 - 8.294	1845.5 - 1646.5	Above 38.6	
8.362 - 8.366	1660 - 1710		
8.37625 - 8.38675	1718.8 - 1722.2		
8.41425 - 8.41475	2200 - 2300		
12.29 - 12.293	2310 - 2390		
12.51975 - 12.52025	2483.5 - 2500		
12.57675 - 12.57725	2855 - 2900		
13.36 - 13.41	3260 - 3267		
16.42 - 16.423	3332 - 3339		
16.69475 - 16.69525	3345.8 - 3358		
16.80425 - 16.80475	3500 - 4400		
25.5 - 25.67	4500 - 5150		
37.5 - 38.25	5350 - 5460		
73 - 74.6	7250 - 7750		
74.8 - 75.2	8025 - 8500		
108 – 138			

Note 1: Certain frequency bands listed in table / and in bands above 38 to GH2 are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz. ²Above 38.6c

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch. FORM No.: 10-SL-F0086



TEST SETUP AND PROCEDURE

Below 30 MHz



The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.

2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.

3. The EUT was placed on a turntable with 80 cm above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.

5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode remeasured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.

7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.



Below 1 GHz and above 30 MHz



The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.

2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

3. The EUT was placed on a turntable with 80 cm above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.

5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.



Above 1 GHz Cabinet emi Anechoic Chamber Antenna Mount 360 Receiver 3m 1m~4m Position Controller EÜT 1.5m 1m Preamplifier 5

The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.

2. The EUT was arranged to its worst case and then tune the antenna tower (1.5 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

3. The EUT was placed on a turntable with 1.5 m above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.

5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.

6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.



X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

TEST ENVIRONMENT

Temperature	25 °C	Relative Humidity	64.8 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.7 V

RESULTS



8.1. RESTRICTED BANDEDGE

8.1.1. GFSK MODE



RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2389.580	34.21	11.96	46.17	74.00	-27.83	peak
2	2390.000	32.98	11.96	44.94	74.00	-29.06	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2388.085	32.52	11.95	44.47	74.00	-29.53	peak
2	2390.000	29.15	11.96	41.11	74.00	-32.89	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

<u>PEAK</u>



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2483.500	44.75	12.38	57.13	74.00	-16.87	peak
2	2483.600	46.05	12.38	58.43	74.00	-15.57	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



<u>AVG</u>



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2483.500	19.32	12.38	31.70	54.00	-22.30	AVG
2	2483.600	19.32	12.38	31.70	54.00	-22.30	AVG

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.

5. For the transmitting duration, please refer to clause 7.1.

6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: Both horizontal and vertical had been tested, but only the worst data was recorded in the report.


8.2. SPURIOUS EMISSIONS (1 GHz ~ 3 GHz)

8.2.1. GFSK MODE



HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.





HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	1062.000	39.15	5.14	44.29	74.00	-29.71	peak
2	1318.000	32.99	6.63	39.62	74.00	-34.38	peak
3	1664.000	32.33	8.12	40.45	74.00	-33.55	peak
4	2128.000	38.26	11.11	49.37	74.00	-24.63	peak
5	2402.000	67.36	12.03	79.39	/	/	fundamental
6	2656.000	31.62	12.74	44.36	74.00	-29.64	peak

Note: 1. Measurement = Reading Level + Correct Factor.





HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	1066.000	36.78	5.15	41.93	74.00	-32.07	peak
2	1596.000	34.58	7.93	42.51	74.00	-31.49	peak
3	2126.000	39.81	11.11	50.92	74.00	-23.08	peak
4	2441.000	76.19	12.19	88.38	/	/	fundamental
5	2658.000	31.26	12.75	44.01	74.00	-29.99	peak
6	2908.000	29.58	14.09	43.67	74.00	-30.33	peak

Note: 1. Measurement = Reading Level + Correct Factor.





HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	1060.000	38.23	5.14	43.37	74.00	-30.63	peak
2	1330.000	35.72	6.64	42.36	74.00	-31.64	peak
3	1660.000	35.22	8.11	43.33	74.00	-30.67	peak
4	2000.000	37.77	10.25	48.02	74.00	-25.98	peak
5	2134.000	39.89	11.13	51.02	74.00	-22.98	peak
6	2441.000	75.81	12.19	88.00	/	/	fundamental

Note: 1. Measurement = Reading Level + Correct Factor.







No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	1162.000	32.96	5.95	38.91	74.00	-35.09	peak
2	1512.000	31.25	7.09	38.34	74.00	-35.66	peak
3	1832.000	31.73	9.84	41.57	74.00	-32.43	peak
4	1998.000	32.75	10.24	42.99	74.00	-31.01	peak
5	2128.000	40.27	11.11	51.38	74.00	-22.62	peak
6	2480.000	77.51	12.35	89.86	/	/	fundamental

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.



1000.000

1200.000

1400.000



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	1108.000	40.09	5.30	45.39	74.00	-28.61	peak
2	1664.000	41.45	8.12	49.57	74.00	-24.43	peak
3	2126.000	40.22	11.11	51.33	74.00	-22.67	peak
4	2242.000	41.99	11.32	53.31	74.00	-20.69	peak
5	2480.000	79.38	12.35	91.73	/	/	fundamental
6	2794.000	35.31	13.71	49.02	74.00	-24.98	peak

2000.00

2200.000

2400.000

2600.000

3000.000 MHz

Note: 1. Measurement = Reading Level + Correct Factor.

1600.000

1800.000

8.3. SPURIOUS EMISSIONS (3 GHz ~ 18 GHz)

8.3.1. GFSK MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.





HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1*	3195.000	63.68	-4.42	59.26	/	/	peak
2*	3360.000	59.50	-4.33	55.17	/	/	peak
3	3990.000	57.56	-2.89	54.67	74.00	-19.33	peak
4	3990.000	49.09	-2.89	46.20	54.00	-7.80	AVG
5	5595.000	49.40	2.73	52.13	74.00	-21.87	peak
6	17025.000	32.42	20.46	52.88	74.00	-21.12	peak
7	17685.000	30.86	22.33	53.19	74.00	-20.81	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
Peak: Peak detector.

4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.

5. For the transmitting duration, please refer to clause 7.1.

6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

7. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1*	3075.000	58.67	-3.91	54.76	/	/	peak
2*	3240.000	62.89	-4.37	58.52	/	/	peak
3*	3360.000	59.88	-4.33	55.55	/	/	peak
4	5685.000	44.47	2.72	47.19	74.00	-26.81	peak
5	11520.000	35.02	13.38	48.40	74.00	-25.60	peak
6	13890.000	34.64	16.31	50.95	74.00	-23.05	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.





No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1*	3240.000	63.10	-4.37	58.73	/	/	peak
2	4065.000	55.89	-2.88	53.01	74.00	-20.99	peak
3	5685.000	50.99	2.72	53.71	74.00	-20.29	peak
4	7845.000	39.49	7.62	47.11	74.00	-26.89	peak
5	13800.000	32.56	17.10	49.66	74.00	-24.34	peak
6	17235.000	31.59	21.21	52.80	74.00	-21.20	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.





HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1*	3300.000	64.84	-4.24	60.60	/	/	peak
2	5775.000	43.45	2.99	46.44	74.00	-27.56	peak
3	11520.000	34.83	13.38	48.21	74.00	-25.79	peak
4	13905.000	34.02	16.20	50.22	74.00	-23.78	peak
5	17325.000	30.98	21.67	52.65	74.00	-21.35	peak
6	17865.000	29.91	23.33	53.24	74.00	-20.76	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1*	3300.000	62.94	-4.24	58.70	/	/	peak
2	4125.000	53.69	-2.46	51.23	74.00	-22.77	peak
3	5775.000	48.99	2.99	51.98	74.00	-22.02	peak
4	11505.000	35.27	13.42	48.69	74.00	-25.31	peak
5	16455.000	31.69	19.00	50.69	74.00	-23.31	peak
6	17835.000	29.81	23.31	53.12	74.00	-20.88	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



8.4.1. GFSK MODE





No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	19392.000	50.12	-5.57	44.55	74.00	-29.45	peak
2	21600.000	49.02	-4.54	44.48	74.00	-29.52	peak
3	22072.000	49.27	-4.41	44.86	74.00	-29.14	peak
4	23040.000	48.36	-3.43	44.93	74.00	-29.07	peak
5	23816.000	47.39	-3.08	44.31	74.00	-29.69	peak
6	25616.000	46.18	-1.24	44.94	74.00	-29.06	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. The preamplifier only effect to the above 18GHz signal and no filter added to the measurement chain.



SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	18528.000	49.61	-5.26	44.35	74.00	-29.65	peak
2	19984.000	49.71	-5.44	44.27	74.00	-29.73	peak
3	21544.000	49.76	-4.63	45.13	74.00	-28.87	peak
4	23216.000	48.51	-3.38	45.13	74.00	-28.87	peak
5	24616.000	47.30	-2.33	44.97	74.00	-29.03	peak
6	24944.000	47.05	-2.15	44.90	74.00	-29.10	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. The preamplifier only effect to the above 18GHz signal and no filter added to the measurement chain.

Note: All the modes have been tested, only the worst data was recorded in the report.



8.5. SPURIOUS EMISSIONS (30 MHz ~ 1 GHz)

8.5.1. GFSK MODE

SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



INO.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	167.7400	48.89	-17.45	31.44	43.50	-12.06	QP
2	263.7700	53.71	-18.55	35.16	46.00	-10.84	QP
3	372.4100	45.37	-14.01	31.36	46.00	-14.64	QP
4	431.5800	43.75	-12.79	30.96	46.00	-15.04	QP
5	557.6800	37.47	-10.67	26.80	46.00	-19.20	QP
6	801.1500	41.06	-7.71	33.35	46.00	-12.65	QP

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.



SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	167.7400	48.78	-17.45	31.33	43.50	-12.17	QP
2	331.6700	41.66	-14.89	26.77	46.00	-19.23	QP
3	372.4100	47.03	-14.01	33.02	46.00	-12.98	QP
4	553.8000	44.39	-10.72	33.67	46.00	-12.33	QP
5	799.2100	38.51	-7.73	30.78	46.00	-15.22	QP
6	937.9200	33.65	-5.33	28.32	46.00	-17.68	QP

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto

Note: All the modes have been tested, only the worst data was recorded in the report.



8.6. SPURIOUS EMISSIONS BELOW 30 MHz

8.6.1. GFSK MODE

(MID CHANNEL, LOOP ANTENNA FACE ON TO THE EUT, WORST-CASE CONFIGURATION)



<u>9 kHz~ 150 kHz</u>

No.	Frequency	Reading	Correct	FCC Result	FCC Limit	ISED Result	ISED Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dBuA/m)	(dBuA/m)	(dB)	
1	0.0100	73.22	-101.40	-28.18	47.60	-79.68	-3.90	-75.78	peak
2	0.0145	69.55	-101.38	-31.83	44.37	-83.33	-7.13	-76.20	peak
3	0.0200	68.18	-101.34	-33.16	41.58	-84.66	-9.92	-74.74	peak
4	0.0349	64.03	-101.41	-37.38	36.75	-88.88	-14.75	-74.13	peak
5	0.0675	59.85	-101.56	-41.71	31.02	-93.21	-20.48	-72.73	peak
6	0.1019	56.35	-101.79	-45.44	27.44	-96.94	-24.06	-72.88	peak

Note: 1. Measurement = Reading Level + Correct Factor ($dBuA/m = dBuV/m - 20Log10[120\pi] = dBuV/m - 51.5$).

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

<u>150 kHz ~ 490 kHz</u>



No.	Frequency	Reading	Correct	FCC	FCC	ISED	ISED	Margin	Remark
				Result	Limit	Result	Limit		
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dBuA/m)	(dBuA/m)	(dB)	
1	0.1647	72.26	-101.66	-29.40	23.27	-80.90	-28.23	-52.67	peak
2	0.1917	69.04	-101.70	-32.66	21.95	-84.16	-29.55	-54.61	peak
3	0.2210	66.34	-101.75	-35.41	20.71	-86.91	-30.79	-56.12	peak
4	0.2837	62.72	-101.83	-39.11	18.54	-90.61	-32.96	-57.65	peak
5	0.3392	59.90	-101.90	-42.00	16.99	-93.50	-34.51	-58.99	peak
6	0.4193	57.18	-101.98	-44.80	15.15	-96.30	-36.35	-59.95	peak

Note: 1. Measurement = Reading Level + Correct Factor ($dBuA/m = dBuV/m - 20Log10[120\pi] = dBuV/m - 51.5$).

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.



<u>490 kHz ~ 30 MHz</u>



No.	Frequency	Reading	Correct	FCC	FCC	ISED	ISED	Margin	Remark
				Result	Limit	Result	Limit		
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dBuA/m)	(dBuA/m)	(dB)	
1	0.5917	62.74	-62.08	0.66	32.16	-50.84	-19.34	-31.50	peak
2	0.8820	60.68	-62.19	-1.51	28.69	-53.01	-22.81	-30.20	peak
3	2.0939	57.39	-61.79	-4.40	29.54	-55.90	-21.96	-33.94	peak
4	4.9165	53.88	-61.48	-7.60	29.54	-59.10	-21.96	-37.14	peak
5	10.8772	53.74	-60.84	-7.10	29.54	-58.60	-21.96	-36.64	peak
6	16.3959	54.67	-60.96	-6.29	29.54	-57.79	-21.96	-35.83	peak

Note: 1. Measurement = Reading Level + Correct Factor (dBuA/m= dBuV/m- 20Log10[120 π] = dBuV/m- 51.5).

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

Note: All the modes have been tested, only the worst data was recorded in the report.



9. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

TEST SETUP AND PROCEDURE

Refer to ANSI C63.10-2013 clause 6.2.



The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013.Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST ENVIRONMENT

Temperature	25 °C	Relative Humidity	64.8 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 3.7 V

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.



9.1.1. GFSK MODE

LINE L RESULTS (LOW CHANNEL, WORST-CASE CONFIGURATION)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dB)	
1	0.1757	24.25	9.61	33.86	64.69	-30.83	QP
2	0.1757	6.40	9.61	16.01	54.69	-38.68	AVG
3	0.6096	21.99	9.60	31.59	56.00	-24.41	QP
4	0.6096	13.94	9.60	23.54	46.00	-22.46	AVG
5	1.7145	13.74	9.62	23.36	56.00	-32.64	QP
6	1.7145	6.25	9.62	15.87	46.00	-30.13	AVG
7	3.5714	13.41	9.65	23.06	56.00	-32.94	QP
8	3.5714	5.64	9.65	15.29	46.00	-30.71	AVG
9	9.3209	18.93	9.74	28.67	60.00	-31.33	QP
10	9.3209	9.77	9.74	19.51	50.00	-30.49	AVG
11	25.9223	17.27	9.93	27.20	60.00	-32.80	QP
12	25.9223	4.18	9.93	14.11	50.00	-35.89	AVG

Note: 1. Result = Reading + Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).

4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch.



LINE N RESULTS (LOW CHANNEL, WORST-CASE CONFIGURATION)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dB)	
1	0.2036	25.32	9.60	34.92	63.46	-28.54	QP
2	0.2036	8.66	9.60	18.26	53.46	-35.20	AVG
3	0.6119	25.05	9.60	34.65	56.00	-21.35	QP
4	0.6119	16.46	9.60	26.06	46.00	-19.94	AVG
5	1.2077	15.28	9.61	24.89	56.00	-31.11	QP
6	1.2077	7.89	9.61	17.50	46.00	-28.50	AVG
7	1.5976	15.92	9.62	25.54	56.00	-30.46	QP
8	1.5976	8.29	9.62	17.91	46.00	-28.09	AVG
9	9.2144	21.18	9.73	30.91	60.00	-29.09	QP
10	9.2144	12.58	9.73	22.31	50.00	-27.69	AVG
11	14.0274	18.74	9.83	28.57	60.00	-31.43	QP
12	14.0274	9.87	9.83	19.70	50.00	-30.30	AVG

Note: 1. Result = Reading + Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).

4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.



10. ANTENNA REQUIREMENTS

APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

RESULTS

Complies



11. Appendix

11.1. Appendix A: Duty Cycle 11.1.1. Test Result

Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (db)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
GFSK	2.83	2.97	0.953	95.3	0.21	0.35	0.36

Note:

Duty Cycle Correction Factor=10log(1/x). Where: x is Duty Cycle (Linear) Where: T is On Time (transmit duration) If that calculated VBW is not available on the analyzer then the next higher value should be used.



11.1.2. Test Graphs

						D	H5_/	Ant	1_24	41				
Keys	ight Spec	trum An	alyzer - Swept	t SA			actives to	æ			07.50.4		-	- 2 -
Cent	er Fr	eq 2.	441000	0000 Gł	łz	Tri	g Delay-20	0.0 µs	#Avg T	/pe: RMS	07:50:1 Ti	9 PM Aug 13, 2020 RACE 1 2 3 4 5 6	F	requency
			N	FE P	NO: Fast • Gain:Low	#A	g: video tten: 30 dB					DET P P P P P		
10 dB	/div	Ref C Ref	offset 9.79 20.00 dE	dB Bm							∆Mkr3	2.965 ms -0.10 dB		Auto Tune
10.0		_												Center Freq
0.00	6 ¹				<mark>,23∆1</mark> .	_					-		2.44	1000000 GHz
-10.0	¥	-			I	-						TRIGLM		
-20.0	-	-				-								Start Freq
-30.0		-											2.44	1000000 GHz
-40.0	i				•							1		
-60.0														Stop Freq
-70.0		_				_						_	2.44	1000000 GHz
Cent	er 2.4	4100 MH7	0000 GH	łz	#)/B	147 0 0	MLIT			Swaan	10 12 m	Span 0 Hz		CF Step
NCS I	- 44 O			Y	#VD	vi o.U	111112	EUM		Gweep	TO, TO MIS		Auto	Man
1	N 1	t	•	19	6.3 µs	, -7	.34 dBm	PONC		UNCTION WD1	Police			
3 4		t (Δ) Δ)	2.8	65 ms (2))	-0.10 dB							Freq Offset
 5												E		0 Hz
7														Scale Type
9 10													Log	Lin
11							m						–	
MSG										STAT	us			



11.2. Appendix B: 20dB Emission Bandwidth 11.2.1. Test Result

Test Mode	Antenna	Channel	20db EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5 Ant1	2402	0.798	2401.613	2402.411		PASS	
	Ant1	2441	0.792	2440.616	2441.408		PASS
		2480	0.792	2479.616	2480.408		PASS



11.2.2. Test Graphs





REPORT NO.: 4789585111.1-10 Page 64 of 84

						DH5	_Ant	t1_248	30				
***	Keysight !	Spectrum Analy:	zer - Swept SA	4									- 8 ×
Ce	_{RL} nter	Freq 2.4	50 Q DC	00 GHz		SEN	SE:INT	#Avg Type	LIGN AUTO	07:52:29 TR	PM Aug 13, 2020	F	Frequency
			NFE	PNO IFGai	:Wide ↔ in:Low	#Atten: 30) dB	Avginolu.	100/100		DET P P P P P	P	
10	dBídiv	Ref Off	set 9.79 d 0.00 dBn	B						ΔMkr3	792 kHz 1.225 dB		Auto Tune
Ĺo							,					 	
10	.0					<u>^2</u>							Center Freq
0.						X						2.4	80000000 GHz
-10						Im	m.						
~					$^{\circ}$	N ^N	~ ~,	∿ ≜3∆1			DL1 -20.42 dBm		
-21	° 📃				N			WY2					Start Freq
-30				N				1	~			2.4	78500000 GHz
-40		-	~~ r						M	m		 	
-50		- 0 m/	ww	V					~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	1-~	10.2		
-60		v vvv									A alta		Stop Freq
70												2.4	81500000 GHz
-70	° 🕅												
Ce	nter	2.480000	GHz							Span	3.000 MHz		CF Step
#F	es Bl	№ 20 kHz			#VBV	/ 62 kHz		5	weep	2.333 ms	(1001 pts)		300.000 kHz
MR	NODE	TRC SCL		x		Y	FUN	NCTION FUN	CTION WIDT	H FUNC	TION VALUE	Auto	Man
	N	1 f	2	.479 616 0	GHz	-20.508 dB	m						
	N A1	1 f	2	479 844 (-0.417 dB	lm IP						Freg Offset
4	Δ1	ι ι (Δ)		/92	KHZ (4)	-1.220 (0 Hz
6											E		
1													Scale Type
10													Lin
1												Log	Lin
< [•		
MSG									STAT	US			

11.3. Appendix C: Occupied Channel Bandwidth 11.3.1. Test Result

Test Mode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5 Ant1	2402	0.85820	2401.569	2402.427		PASS	
	Ant1	2441	0.85168	2440.575	2441.427		PASS
		2480	0.85891	2479.571	2480.430		PASS



11.3.2. Test Graphs





REPORT NO.: 4789585111.1-10 Page 67 of 84





11.4. Appendix D: Maximum peak conducted output power 11.4.1. Test Result

Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH5		2402	0.04	30	PASS
	Ant1	2441	0.24	30	PASS
		2480	0.07	30	PASS



11.5. Appendix E: Carrier frequency separation 11.5.1. Test Result

Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH5	Ant1	Нор	1.008	>=0.798	PASS



11.5.2. Test Graphs





11.6. Appendix F: Time of occupancy 11.6.1. Test Result

			FHSS Mode				
Test Made Asterna		Channel	BurstWidth	Popult[o]	Limit[a]	Vardiat	
Test Mode	Test Mode Antenna		[ms]	Results	Linin(S)	Verdici	
DH1	Ant1	Нор	0.38	0.430	<=0.4	PASS	
DH3	Ant1	Нор	1.64	1.630	<=0.4	PASS	
DH5	Ant1	Нор	2.89	2.830	<=0.4	PASS	

			AFHSS Mode			
Test Mode	Antenna	Channel	BurstWidth [ms]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Нор	0.38	0.215	<=0.4	PASS
DH3	Ant1	Нор	1.64	0.815	<=0.4	PASS
DH5	Ant1	Нор	2.89	1.415	<=0.4	PASS



11.6.2. Test Graphs




REPORT NO.: 4789585111.1-10 Page 73 of 84

		DH5 Ant	1 Hop			
Keysight Spectr	ım Analyzer - Swept SA	0110_7410			- 3 💌	
Center Fre	RF 50 Ω DC α 2 441000000 GHz	SENSE:INT Trig Delay-200.0 µs	ALIGN AUTO #Avg Type: RMS	08:02:00 PM Aug 13, 2020 TRACE 1 2 3 4 5 6	Frequency	
bonkol 110	NFE PNO: Wide ↔	Trig: Video #Atten: 30 dB	•	DET P P P P P		
	II Gam.Low		Δ	Mkr2 2.832 ms	Auto Tune	
10 dB/div	Ref 20.00 dBm			5.89 dB		
Log					Contor From	
10.0					2.441000000 GHz	
0.00					Start Fren	
10.0				TRIG LVL	2.441000000 GHz	
-10.0	2∆1					
-20.0					Stop Freg	
					2.441000000 GHz	
-30.0						
-40.0					CF Step	
					1.000000 MHz Auto Man	
-50.0						
	and the second	hite) al ederaldin	կ Արևվերով Արև	han han bar bar bar	Freq Offset	
-60.0	hittat da a	ALL HER CONTRACTOR	ilath: Ísl. In sides i Ale Island II.	a historica a historia	0 Hz	
-70.0	. a	a Hunda an ann	a la sua dudina di data	at - whet is the applied		
					Scale Type	
Center 2.44	1000000 GHz			Span 0 Hz	Log <u>Lin</u>	
Res BW 1.0	MHz #VBW :	3.0 MHz	Sweep 1	0.13 ms (8000 pts)		
MSG			STATUS			

11.7. Appendix G: Number of hopping channels 11.7.1. Test Result

Test Mode	Antenna	Channel	Result[Num]	Limit[Num]	Verdict
DH5	Ant1	Нор	79	>=15	PASS



11.7.2. Test Graphs



11.8. Appendix H: Band edge measurements 11.8.1. Test Result

Test Mode	Antenna	ChName	Channel	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
		Low	2402	-0.47	-47.07	<=-20.47	PASS
	A n+1	High	2480	-0.38	-49.55	<=-20.38	PASS
DHS	Anti	Low	Hop_2402	-0.48	-50.69	-20.48	PASS
		High	Hop_2480	-0.19	-49.86	-20.19	PASS



11.8.2. Test Graphs





REPORT NO.: 4789585111.1-10 Page 78 of 84

	DL	5_Ant1_LC	w_Hop_24	.02	
🔤 Keysight Spectrum Analyzer -	- Swept SA				- 2 ×
Center Freq 2.352	0 Ω DC	SENSE:INT	#Avg Type: RMS AvgHold: 300/300	07:54:39 PM Aug 13, 2020 TRACE 1 2 3 4 5 6 TYPE M	Frequency
	IFGain:Low	#Atten: 30 dB	Micel		Auto Tune
10 dB/div Ref 20.0	9.64 dB 0 dBm			-50.689 dBm	
10.0				1	Center Fred
0.00					2.352500000 GHz
-10.0				<u> </u>	
-20.0				DL1 -20.48 dBrf	Ctort Eron
-30.0					2 300000000 GHz
-40.0			A5	03 02	
-50.0	han production of the production of the section of	- and and a state of the state	muliabolistant		Stop From
-60.0					2.40500000 GHz
-70.0					2.40000000000112
Start 2.30000 GHz	#)(P)	W 200 kHz	Pwoon	Stop 2.40500 GHz	CF Step
WREIMODE FOR SAL	#VD	Y 300 K112	oweep		Auto Man
1 N 1 f	2.404 895 GHz	-0.481 dBm	POWCHON WIDTH	A DAVE HORE VALUE	
2 N 1 f 3 N 1 f	2.400 000 GHz 2.390 000 GHz	-51.631 dBm -51.615 dBm			Freq Offset
4 N 1 f 5 N 1 f	2.310 000 GHz 2.365 205 GHz	-53.776 dBm -50.689 dBm		E	0 Hz
6 7					
8					Scale Type
10					Log <u>Lin</u>
<		m		•	
MSG			STAT	JS	
	DH	5_Ant1_Hi	gh_Hop_24	80	
Keysight Spectrum Analyzer -	- Swept SA 0 Ω DC	SENSE:INT	ALIGN AUTO	08:04:02 PM Aug 13, 2020	- 2 💌
Center Freq 2.510	000000 GHz	Tria: Erec Bun	#Ava Type: RMS	TRACE 1 2 3 4 5 6	Frequency
	NEE DNO. East	S I IIIU. FIMP RUII	AvalHold: 300/300	TYPE M WWWWW	
	NFE PNO: Fast ← IFGain:Low	#Atten: 30 dB	Avg Hold: 300/300	DET PPPPP	
Ref Offset	NFE PNO: Fast IFGain:Low	#Atten: 30 dB	AvgiHold: 300/300	TYPE M WWWWW DET P P P P P P 40 956 d D	Auto Tune
Ref Offset 10 dB/div Ref 20.0	NFE PNO: Fast - IFGain:Low 9.79 dB 0 dBm	#Atten: 30 dB	AvgiHold: 300/300	түре Милини Det РРРРРР r4 2.489 04 GHz -49.856 dBm	Auto Tune
10 dB/div Ref Offset	NFE PNO: Fast - IFGain:Low 9.79 dB 0 dBm	#Atten: 30 dB	AvgjHold: 300/300	14 2.489 04 GHz -49.856 dBm	Auto Tune Center Freq
10 dB/div Ref Offset	NFE PNO: Fast - IFGain:Low 9.79 dB 0 dBm	#Atten: 30 dB	AvgjHold: 300/300	тиеји DET P P P P P r4 2.489 04 GHz -49.856 dBm	Auto Tune Center Freq 2.51000000 GHz
Ref Offset 10 dB/div Ref 20.0 0.00 -10.0	NFE PNO: Fast - IFGain:Low 9.79 dB 0 dBm	#Atten: 30 dB	AvgjHold: 300/300	42.489 04 GHz -49.856 dBm	Auto Tune Center Freq 2.51000000 GHz
10 dB/div Ref Offset Log 10.0 10.0 10.0 10.0 20.0	NFE PNO: Fast - IFGainLow 0 dBm	#Atten: 30 dB	Avg Hold: 300/300	DET PPPPP r4 2.489 04 GHz -49.856 dBm	Auto Tune Center Freq 2.51000000 GHz Start Freq
10 dBldiv Ref 20.0 10 dBldiv Ref 20.0 10.0 1 10.0 1	NFE PNO: Fast - IFGainLow 0 dBm	#Atten: 30 dB	AvgiHold: 300/300	21. 2019 de	Auto Tune Center Freq 2.51000000 GHz Start Freq 2.470000000 GHz
10 dBldiv Ref 015et Log 100 000 100 000 100 000 100 000 100 000 000 000	NFE PNO: Fast → IFGainLow 0 dBm	Atten: 30 dB	AvgiHold: 300/300	Det 1/2019 de la construcción de	Auto Tune Center Freq 2.51000000 GHz Start Freq 2.470000000 GHz
10 dB/div Ref Offset Log 10.0 0.00 -10.0 -10.0 -0.0 -0.0 -0.0 -0	NFE PNO: Fast - IFGainLow 0 dBm	Atten: 30 dB	AvgiHold: 300/300	EL1-2019 de	Auto Tune Center Freq 2.51000000 GHz Start Freq 2.47000000 GHz Stop Freq
10 dB/div Ref Offset 10 dB/div Ref 20.0 100 100 100 100 100 100 100	NFE PNO: Fast - IFGainLow 0 dBm	sAtten: 30 dB	AvgiHoid: 300/300	249.856 dBm	Auto Tune Center Freq 2.51000000 GHz Start Freq 2.47000000 GHz Stop Freq 2.55000000 GHz
10 dB/div Ref Offset 10 dB/div Ref 20.0 10 0 10 0	NFE PNO: Fast - IFGainLow 0 dBm	A This reaction and the second	AvgiHoid: 300/300	Ct. 2019 db	Auto Tune Center Freq 2.51000000 GHz Start Freq 2.47000000 GHz Stop Freq 2.55000000 GHz
10 dB/div Ref Offset 10 dB/div Ref 20.0 10 0 10 0	NFE PN0: Fast Frequencies 1979 dB 0 dBm 0 dBm 0 dBm 2 4 0 dBm 0 dBm	3 W 300 kHz	AvgiHoid: 300/300	Cti .2019 de GHz -49.856 dBm Cti .2019 de Stop 2.55000 GHz 3.000 ms (1001 bts)	Auto Tune Center Freq 2.51000000 GHz Start Freq 2.47000000 GHz Stop Freq 2.55000000 GHz CF Step 8.000000 MHz
OdBJdiv Ref Offset 10.0 Ref 20.0 10.0 10.0 0.00 10.0 0.00 10.0 0.00 10.0 0.00 10.0 0.00 10.0 0.00 10.0 0.00 10.0 0.00 10.0 0.00 10.0 0.00 10.0 40.0 10.0 40.0 10.0 40.0 10.0 50.0 10.0 50.0 10.0 50.0 10.0 50.0 10.0 50.0 10.0 50.0 10.0 50.0 10.0 50.0 10.0 50.0 10.0 50.0 10.0 50.0 10.0 50.0 10.0 50.0 10.0 50.0 10.0 50.0 10.0 50.0 10.0	NFE PNO: Fast - IFGainLow 979 dB 0 dBm 0 dBm	→ mg rive Kui #Atten: 30 dB	Avgiteidi: 300/300 Mk	CL1-2019-000	Auto Tune Center Freq 2.51000000 GHz Start Freq 2.47000000 GHz Stop Freq 2.55000000 GHz CF Step 8.00000 MHz Auto
Ref Offset 10 dB/div Ref 20.0 100 1 1 100 1 1 100 1 1 100 1 1 100 1 1 100 1 1 100 1 1 100 1 1 400 1 1 400 1 1 500 1 1 100 1 1 100 1 1 100 1 1	NFE PNO: Fast - IFGainLow 979 dB 0 dBm 0 dBm	→ Ing. rise Kui #Atten: 30 dB 3 3 W 300 kHz Y 80 5/1921 dBm	AvgiHold: 300/300 Mk	EL1-2019 dB CHZ 2 2000000 CHZ 3.000 ms (1001 pts)	Auto Tune Center Freq 2.51000000 GHz Start Freq 2.47000000 GHz Stop Freq 2.55000000 GHz CF Step 8.000000 MHz Auto
Ref Offset 10 B/div 10 Ref 20.0 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1 200 1 300 1 400 1 400 1 300 1 300 1 300 1 300 1 300 1 300 1 300 1 300 1 300 1 300 1	NEE PN0: Fast → IFGain1.cw 979 dB 0 0 dBm 0 2 4 2 4 2 4 2 4 2 4 2 4 2 4 2 4 2 4 2 4 2 4 2 4 2 44 2 44 2 44	→ 11 µ r r r r r km #Atten: 30 dB	AvgiHold: 300/300 Mk	CLI-2019 dBm CLI-2019 dBm CLI-2019 dBm Stop 2.55000 GHz 3.000 ms (1001 pts)	Auto Tune Center Freq 2.51000000 GHz Start Freq 2.47000000 GHz Stop Freq 2.55000000 GHz CF Step 8.00000 MHz Auto Man Freq Offset
Ref Offset 10 B/div Ref 20.0 10 0 0 0 100 0 0 0 0 100 0 0 0 0 0 200 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	NFE PNO: Fast → IFGainLow 9.79 dB 0 dBm 2	→ The rescale #Atten: 30 dB	AvgiHold: 300/300 Mk	ELI-2019 dBm ELI-2019 dBm ELI-2019 dBm Stop 2.55000 GHz 3.000 ms (1001 pts)	Auto Tune Center Freq 2.51000000 GHz Start Freq 2.47000000 GHz Stop Freq 2.55000000 GHz CF Step 8.000000 MHz Auto Man Freq Offset 0 Hz
10.dEldity Ref Offset Ref 20.0 10.0 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 1 0.00 <	NFE PNO: Fast - IFGainLow 0 dBm 2 2 2 4 3 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	→ mg.r.res.Kai sAtten: 30 dB	AvgiHold: 300/300 Mk	EL1-2019 CH2 Stop 2.55000 CH2 3.000 ms (1001 pts)	Auto Tune Center Freq 2.51000000 GHz Start Freq 2.47000000 GHz Stop Freq 2.5000000 GHz CF Step 8.00000 MHz Auto Man Freq Offset 0 Hz Scale Turo
Image: Description of the second se	NE PNO: Fast - IFGainLow 0 dBm 2 dBm	→ mg. rres Kall #Atten: 30 dB 3 W 300 kHz V 10 49.856 dBm	Avgiteid: 300/300 Mk Mk Sweep : Sweep : NCTION EUROTION MOT	EL1-2019 CH2 Stop 2.55000 CH2 3.000 ms (1001 pts)	Auto Tune Center Freq 2.51000000 GHz Start Freq 2.47000000 GHz Stop Freq 2.5000000 GHz CF Step 8.000000 MHz Auto Man Freq Offset 0 Hz Scale Type
Ball Ref Offset 10 60 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1	NE PNO: Fast - IFGainLow 0 dBm 2 dBm	→ Thigh Free Kall #Atten: 30 dB	Avgiteid: 300/300 Mk Mk Sweep : Sweep :	Stop 2.55000 CHz 3.000 ms (1001 pts)	Auto Tune Center Freq 2.51000000 GHz Start Freq 2.47000000 GHz Stop Freq 2.55000000 GHz CF Step 8.000000 MHz Auto Man Freq Offset 0 Hz Scale Type Log Lin
10 Bit Offset 100 0 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1 100 1	NE PNO: Fast - IFGainLow 0 dBm 2 dBm	→ The rise Kun #Atten: 30 dB	Avgiteid: 300/300	Ct .2019 cb . Stop 2.55000 GHz 3.000 ms (1001 pts)	Auto Tune Center Freq 2.51000000 GHz Start Freq 2.47000000 GHz Stop Freq 2.55000000 GHz CF Step 8.000000 GHz CF Step 8.000000 GHz OFF Step Scale Type Log Lin



11.9. Appendix I: Conducted Spurious Emission 11.9.1. Test Result

Test Mode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
			Reference	-0.50	-0.50		PASS
		2402	30~1000	30~1000	-38.777	<=-20.496	PASS
			1000~26500	1000~26500	-36.21	<=-20.496	PASS
			Reference	-0.23	-0.23		PASS
DH5	Ant1	2441	30~1000	30~1000	-38.801	<=-20.228	PASS
			1000~26500	1000~26500	-37.788	<=-20.228	PASS
			Reference	-0.38	-0.38		PASS
		2480	30~1000	30~1000	-38.886	<=-20.378	PASS
			1000~26500	1000~26500	-39.004	<=-20.378	PASS



11.9.2. Test Graphs





REPORT NO.: 4789585111.1-10 Page 81 of 84





REPORT NO.: 4789585111.1-10 Page 82 of 84

NE PRO: Fail - Internet Manuel 2016 Anglinde: 1010 The property and proper	RL RF Center Frea 5	50 Ω DC 15.000000 MH	Iz	SENSE:IN	#Avg Type:	IGN AUTO RMS	07:51:17 PM Aug 13, 2020 TRACE 1 2 3 4 5 6	Frequency		
Ref Offeet 373 dB Mkr1 313.86 MHz Auto Tube 100 Billow -33.801 dBm -33.801 dBm Center Freq 121		NFE	PNO: Fast ↔ FGain:Low	#Atten: 20 dB	Avg Hold: 1	10/10		Auto Tupe		
1000000000000000000000000000000000000	Ref C 10 dB/div Ref	Dffset 9.79 dB 19.79 dBm				МК	-38.801 dBm			
515.000000 MHz 515.000000 MHz 515.00000 MHz				l l				Center Free		
32 32 33 35 Start Freq 32 32 30 30000000 Hz Stop Freq 32 30 31 30000000 Hz Stop Freq 32 30 31 31 CF Step 32 30 31 CF Step 97.0000000 GHz 32 32 31 GF Step 97.0000000 GHz 32 32 31 GF Step 97.0000000 GHz 32 32 31 GF Step 97.0000000 GHz 32 32 32 32 32 32 32 32 32 32 32 33 32 32 32 32 32 33 32 32 32 32 32 32 32 32 32 32 32 32 32 32 33 35 35 35 35 33 35 35 36 37.788 dBm 37.788 dBm 32 32 31 37.788 dBm 37.788 dBm 3	9.79							515.000000 MHz		
10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2 10.2	-0.21									
302 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31 31	-10.2							30.000000 MHz		
302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 302 3							0.1.2022.000			
332 1 1 1 0.000000000 GHz 302 1 1 GF Step 97,000000 MHz GF Step 97,000000 MHz 302 1 1 GF Step 97,000000 MHz GF Step 97,000000 MHz 303 1 GF Step 97,000000 MHz Stop 1,0000 GHz GF Step 97,000000 MHz 304 1 1 GF Step 97,00000 MHz Scale Type 305 1000 MHz Stop 1,0000 GHz Scale Type 306 1000 MHz Sweep 36,00 ms (3000 pts) Scale Type 307 1000 MHz Sweep 36,00 ms (3000 pts) Freq Offset 97,90 ML 308 Mkr14,068 S5 G GHz Frequency Auto Tune 10 dB/dW Ref 19,79 dBm 37,788 dBm Start Freq 37,788 dBm 302 1 0 0 Start Freq 35,000000 GHz 303 1 0 0 Start Freq 37,788 dBm 304 1 0 0 Start Freq 37,680 dBm 302 1 0 0 Start Freq 35,0000000 GHz 303 1 0 0 Start Freq <	-20.2						001 12020 000	Stop Fred		
CF Step 97.00000 MHz 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 40.2 4	-30.2						.1	1.00000000 0112		
30.2	-40.2						<u>,</u>	CF Step		
Image: Start 0.0300 GHz Freq Offset 0.000 GHz Start 0.0300 GHz #VBW 300 KHz Start 0.0300 GHz								Auto Mar		
accord	-00.2							Erog Offed		
Scale Type Scale Type Start 0.0300 GHz #VBW 300 KHz Start Freq 1.00 GHz Start Freq	-60.2					, Inc.	us tals at the second	0 Hz		
Scale Type Start 0.0300 GHz #Res BW 100 kHz #VBW 300 kHz #VBW 300 kHz #VBW 300 kHz Sweep 36.00 ms (30001 pts) btsi DH5_Ant1_2441_1000~26500 DH5_Ant1_2441_1000~26500 Frequency Aug Mich arrow 10/5144 PMaug 13.200 Frequency Aug Mich arrow 10/5144 Start Freq 13.760000000 GHz 1.000000000 GHz Start Freq 1.000000000 GHz Start Freq 1.000000000 GHz Start Freq 1.00000000 GHz Start Freq Start Start Freq 1.00000000 GHz Start Freq Start Start Freq Start Start Freq Start Start Freq Start Start Freq Start Start Freq Start Start Fre	-70.2	habber dagalari	histophiliteen H	antige of a filler) for the second sector of the second sector second second second second second second second second second se	spreas negatives Formula Hotels	in an an the second second states and a second s			
Stop 1.0000 GHz Log Lin #Res BW 100 kHz #VBW 300 kHz Sweep 36.00 ms (30001 pts) Lin Image: Stop 1.0000 GHz Image: Stop 1.0000 GHz Image: Stop 1.0000-C26500 Image: Stop 1.0000-C26500 Image: Stop 1.0000 GHz Frequency Image: Stop 1.0000 GHz Frequency Image: Stop 1.0000 GHz Frequency Allow Auto 107513H PM aug 13.200 Image: Stop 1.00000 GHz Image: Stop 1.000000 GHz MFE PRO: Fast	displaying and	und haite a construction of the second s	for the start	alistation of the second s	and the second secon	a second	nde seda - en alte a das	Scale Type		
Internal Internal DH5_Ant1_2441_1000~26500 Internal Internal <th "<="" colspan="2" td=""><td>Start 0.0300 GH #Res BW 100 k</td><td>Hz (Hz</td><td>#VBW</td><td>300 kHz</td><td>Sw</td><td>/eep 36.0</td><td>Stop 1.0000 GHz 00 ms (30001 pts)</td><td>Log <u>Lir</u></td></th>	<td>Start 0.0300 GH #Res BW 100 k</td> <td>Hz (Hz</td> <td>#VBW</td> <td>300 kHz</td> <td>Sw</td> <td>/eep 36.0</td> <td>Stop 1.0000 GHz 00 ms (30001 pts)</td> <td>Log <u>Lir</u></td>		Start 0.0300 GH #Res BW 100 k	Hz (Hz	#VBW	300 kHz	Sw	/eep 36.0	Stop 1.0000 GHz 00 ms (30001 pts)	Log <u>Lir</u>
DH5_Ant1_2441_1000~26500 Image: colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2" NEC Frequency Aug Type: RMS Colspan="2">Colspan="2">Colspan="2">Colspan="2" Colspan="2" Auto Tune Colspan="2" Colspan="2" Auto Tune Colspan="2" Colspan="2" Auto Tune Colspan="2" Colspan="2" Auto Tune Colspan="2" Colspan="2" Colspan="2" Colspan="2" <td <="" colspan="2" t<="" td=""><td>MSG</td><td></td><td></td><td></td><td></td><td>STATUS</td><td></td><td>L</td></td>	<td>MSG</td> <td></td> <td></td> <td></td> <td></td> <td>STATUS</td> <td></td> <td>L</td>		MSG					STATUS		L
Reperting Spectrum Augurs - Sweet SA Image: Spectrum Augurs - Sweet SA Center Freq 13.750000000 GHz NFE Aug Auto Auro (0751344 PMAug 12.2000) Phot Fait - 20 dB Frequency Aug Augurs - Mark 1.000 Auro (0751344 PMAug 12.2000) The PP PP PP PP Augurs - 20 dB Frequency Aug Type: RMS Aug Hold: 1010 Trige Frequency Auto Tune 0 dBldiv Ref Offset 3.75 dB Mkr1 4.068 50 GHz -37.788 dBm Center Freq 0.0 dBldiv Ref Offset 3.75 dB Center Freq 0.0 Genter Freq 0.21 Center Freq 0.22 Center Freq 0.23 Center Freq 0.24 Center Freq 0.21 Center Freq 0.22 Center Freq 0.23 Center Freq 0.24 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>										
Center Freq 13.750000000 GHz IFGainLow Trig: Fre Run #Atter: 20 dB Avg Heid: 1010 Trig: Fre Run tel: [9 P P P P P del: [9 P P P P P del: [9 P P P P P del: [9 P P P P P P del: [9 P P P P del: [9 P P P P P del: [9 P P P P del: [9 P P P P del: [9 P P P P del: [9 P P P P P del: [9 P P P P P del: [9 P P P P del: [9 P P P P del: [9 P P P P P del: [9 P P P P P del: [9 P P P P del: [9 P P P P P P P del: [9 P P P P P P del: [9 P P P P P P P P P P P del: [9 P P P P P P P P P P P P P P P P P P			DH5_	Ant1_24	441_1000)~265	500			
Ref offset 9.79 dBm Mkr1 4.068 50 GHz Auto Tune 10 dB/div Ref offset 9.79 dBm -37.788 dBm Center Freq 979	Keysight Spectrum Ar	nalyzer - Swept SA 50 Ω DC	DH5_	Ant1_24	141_1000)~265 lign allito	07:51:44 PM Aug 13, 2020	Frequency		
10 gBd/dv Ker 19,79 dBm Creter Freq 9.73 13.75000000 GHz 10.2 14.1-02.24 deg 10.2 14.1-02.24 deg <td>Keysight Spectrum Ar RL RF Center Freq 1</td> <td>nalyzer - Swept SA 50 Ω DC 3.7500000000 NFE</td> <td>DH5_ GHz PNO: Fast →</td> <td>Ant1_24 SENSE:IN Trig: Free Run #Atten: 20 dB</td> <td>141_1000</td> <td>D~265</td> <td>07:51:44 PM Aug 13, 2020 TRACE 1 2 3 4 5 6 TYPE M</td> <td>Frequency</td>	Keysight Spectrum Ar RL RF Center Freq 1	nalyzer - Swept SA 50 Ω DC 3.7500000000 NFE	DH5_ GHz PNO: Fast →	Ant1_24 SENSE:IN Trig: Free Run #Atten: 20 dB	141_1000	D~265	07:51:44 PM Aug 13, 2020 TRACE 1 2 3 4 5 6 TYPE M	Frequency		
9.79 Center req 13.75000000 GHz 13.75000000 GHz 10.2 Start Freq 10.2 Start Start Freq 10.2 Start Start Freq	REFC	nalyzer - Swept SA 50 Ω DC 3.750000000 (NFE I I Dffset 9.79 dB	DH5_ GHz PNO: Fast ↔ FGain:Low	Ant1_24 SENSE:IN Trig: Free Run #Atten: 20 dB	141_100(T Avg Type: Avg Hold: 1	D~265	07:51:44 PMAug 13, 2020 TRACE 1, 2, 3, 4, 5, 6 TYPE M PPPPP 4.068 50 GHz	Frequency Auto Tune		
10.21 10.2 10.1 3023 dm Start Freq 10.2 10.1 3023 dm 100000000 GHz Stop Freq 30.2 1 10000000 GHz 10000000 GHz 40.2 1 10000000 GHz 10000000 GHz 40.2 1 10000000 GHz 10000000 GHz 50.2 1 100000000 GHz 10000000 GHz 50.2 1 100000000 GHz 100000000 GHz 50.2 1 100000000 GHz 10000000 GHz 60.2 1 100000000 GHz 100000000 GHz 70.2 1 100000000 GHz 100000000 GHz 5 100000000 GHz 100000000 GHz 100000000 GHz 9000 GHz 1000000000 GHz 1000000000000 GHz 1000000000000000000000000000000000000	RL RF Center Freq 1 10 dB/div Ref Log	nalyzer - Swept SA 50 Ω DC NFE UDffset 9.79 dB 19.79 dBm	DH5 GHz PNO: Fast ↔ FGain:Low	Ant1_24 SENSE:IN Trig: Free Run #Atten: 20 dB	141_100(T Avg Type: Avg Hold: 1	D~265 IGN AUTO RMS IO/10 Mkr1	07:51:44 PM Aug 13, 2020 TRACE [12:3:4:5 6 TYPE P P P P P DET P P P P P P 4.068 50 GHz -37.788 dBm	Frequency Auto Tune		
Start Freq 102 0.1.302.0000 GHz 302 0.1.302.0000 GHz 302 0.1.302.0000 GHz 302 0.1.302.0000 GHz 402 0.1.302.0000 GHz 502 0.1.302.0000 GHz 702 0.1.302.0000 GHz 500 0.1.302.00000 GHz 702 0.1.302.00000 GHz 500 0.1.302.000000 GHz 602 0.1.302.0000000 GHz 603 0.1.302.00000000000000000000000000000	Reysight Spectrum Ar RL RF Center Freq 1 10 dB/div Ref 0 g 9.79	nalyzer - Swept SA 50 Ω DC NFE UDffset 9.79 dB 19.79 dBm	DH5 GHz PNO: Fast ↔ FGain:Low	Ant1_24 SENSE:IN Trig: Free Run #Atten: 20 dB	441_1000	D~265 IGN AUTO RMS 10/10 Mkr1	07:51:44 PM Aug 13, 2020 TRACE 12 23 45 6 TYPE DEI P P P P P P 4.068 50 GHz -37.788 dBm	Frequency Auto Tune Center Frec 13.75000000 GH2		
1002 10000000 GH2 3002 110000000 GH2 3002 110000000 GH2 4002 11000000 GH2 5002 11000000 GH2 Start 1.00 GH2 #VBW 300 KH2 Starts Stop 26.50 GHz 11000 11000 KH2	RL BF Center Freq 1 0 dB/div Ref 9.79 9.79	nalyzer - Sweet SA 50 Ω DC 3.750000000 (NFE 0ffset 9.79 dB 19.79 dBm	DH5_, GHz PNO: Fast → FGain:Low	Ant1_24 sense:in Trig: Free Run #Atten: 20 dB	141_1000	D~265 Irms Ion10 Mkr1	07:51:44 PM Aug 13,2020 TRACE [1 2 3:4 5 6 TYPE MWWWW DET [P P P P P 4.068 50 GHz -37.788 dBm	Frequency Auto Tune Center Freq 13.75000000 GHz		
20.2 0 0.1.3022 des Stop Freq 30.2 1 0 1 0 2 40.2 1 0 0 1 0 2 50.2 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 <	R Kaysight Spectrum Ar R L RF Center Freq 1 10 dB/div Ref 9 79 0 21	nalyzer - Sweet SA 50 a DC S0 a DC NFE U Dffset 9.79 dB 19.79 dBm	DH5_, GHz PRO: Fast ↔ FGainLow	Ant1_24 SENSE:IN Trig: Free Run #Atten: 20 dB	141_1000	D~265 IGN AUTO RMS IOU10 Mkr1	0755144 PPRag 13,2020 TRACE 12,34 5 6 TRACE 12	Center Freq 13.75000000 GHz Start Freq		
30.2 1 26.50000000 GHz 40.2 1 26.50000000 GHz 50.2 2 2 50.2 2 2 50.2 2 2 50.2 2 2 50.2 2 2 50.2 2 2 50.2 2 2 50.2 2 2 50.2 2 2 50.2 2 2 50.2 2 2 50.2 2 2 50.2 2 2 50.2 2 2 50.2 2 2 50.2 2 2 50.2 2 2 50.2 2 2 50.2 2 2 50.2 2 2 50.2 2 2 50.2 2 2 50.2 2 2 50.2 <t< td=""><td>Center Freq 1</td><td>nalyzer - Swept SA 50 a DC NFE 1 Dffset 9.79 dB 19.79 dBm</td><td>DH5_,</td><td>Ant1_24 SENSE:IN Trig: Free Run #Atten: 20 dB</td><td>141_1000</td><td>D~265 In AUTO RMS IO/10 Mkr1</td><td>07:51:44 PM Aug 13, 2020 TRACE 13, 24, 5, 6 TRACE 14, 24, 5 TRACE 14, 24, 5 TRACE 14, 24, 5 TRACE 14, 24, 5 TRACE 14, 5 TR</td><td>Center Freq 13.76000000 GHz Start Free 1.00000000 GHz</td></t<>	Center Freq 1	nalyzer - Swept SA 50 a DC NFE 1 Dffset 9.79 dB 19.79 dBm	DH5_,	Ant1_24 SENSE:IN Trig: Free Run #Atten: 20 dB	141_1000	D~265 In AUTO RMS IO/10 Mkr1	07:51:44 PM Aug 13, 2020 TRACE 13, 24, 5, 6 TRACE 14, 24, 5 TRACE 14, 24, 5 TRACE 14, 24, 5 TRACE 14, 24, 5 TRACE 14, 5 TR	Center Freq 13.76000000 GHz Start Free 1.00000000 GHz		
40.2 1 1 CF Step 50.2 1 1 1 1 50.2 1 1 1 1 1 50.2 1 1 1 1 1 1 50.2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 <td>Ku Ref RL RF Center Freq 1 10 dB/div Ref C 9.79 9.79 -0.21 9.79 -10.2 9.79</td> <td>Nalyzer - Sweet SA S0 00 DC NFE 1 Dffset 9.79 dB 19.79 dBm</td> <td>DH5_, GHz FRN:Fast ↔ FGain:Low</td> <td>Ant1_24 SERVERN Trig: Free Run #Atten: 20 dB</td> <td>141_1000</td> <td>D~265 IGN AUTO RMS IGN10 Mkr1</td> <td>0755144 PMAug 13, 2020 TRACE 13, 23 4 5 6 TRACE 13, 24 5 6 TRACE 13, 24 5 6 TRACE 14, 23 4 5 6 TRACE 14, 23 4 5 6 TRACE 14, 25 4 5 6 TRACE</td> <td>Center Free 13.75000000 GHz Start Free 1.00000000 GHz Stop Free</td>	Ku Ref RL RF Center Freq 1 10 dB/div Ref C 9.79 9.79 -0.21 9.79 -10.2 9.79	Nalyzer - Sweet SA S0 00 DC NFE 1 Dffset 9.79 dB 19.79 dBm	DH5_, GHz FRN:Fast ↔ FGain:Low	Ant1_24 SERVERN Trig: Free Run #Atten: 20 dB	141_1000	D~265 IGN AUTO RMS IGN10 Mkr1	0755144 PMAug 13, 2020 TRACE 13, 23 4 5 6 TRACE 13, 24 5 6 TRACE 13, 24 5 6 TRACE 14, 23 4 5 6 TRACE 14, 23 4 5 6 TRACE 14, 25 4 5 6 TRACE	Center Free 13.75000000 GHz Start Free 1.00000000 GHz Stop Free		
40.2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 3 2 3 3 3 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	Ku Ref RL Ref Center Freq 1 10 dB/div Ref 9.79 9 -0.21 9 -10.2 9 -20.2 9	Nalyzer - Sweet SA S0 0 DC NFE D0000001 0 NFE D000001 0 NFE D0000001 0 NFE D0000001 0 NFE D0000001 0 NFE D0000001 0 NFE D000000000000000000000000000000000000	DH5_, GHz PR0: Fast ↔ FGain:Low	Ant1_24	141_1000	D~265 IGN AUTO RMS IOV10 Mkr1	075144 PHAug 13, 2020 TRACE 13, 24 5 6 TRACE 13, 24 5 6 TRACE 13, 24 5 6 TRACE 10, 24 5 6 TRACE 10, 24 5 6 TRACE 10, 24 5 6 TRACE 10, 20 0 0 0, 1, 30 20 den	Center Free 13.75000000 GHz Start Free 1.00000000 GHz 26.50000000 GHz		
60.2 60.2 70.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2 50.2	Keysight Spectrum A/ RL RF Center Freq 1 10 dB/div Ref 0 9 79	Nalyzer - Sweet SA Source - Sweet SA S.75500000000 NFE Dffset 9.79 dB 19.79 dBm	DH5_,	Ant1_24	141_1000	D~265	500 1751:41 MHAUG 13, 2020 TREE 1751:41 MHAUG 13, 2020 1762:17 MHAUG 13, 2020 1762:17 MHAUG 13, 2020 1771:17 MHAUG 13, 2020 1771:17 MHAUG 13, 2020 2011:2020 dbm	Center Free 13.75000000 GH2 Stop Free 26.5000000 GH2 CF Step		
50.2 Scale Type Start 1.00 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 938.0 ms (30001 pts) HISG	Keysight Spectrum A/2 RL RF Center Freq 1 10 dB/div Ref 0 979 9 -0.21	Aalyzer - Sweet SA Source - Sweet SA S.75500000000 NFE Diffset 9.79 dB 19.79 dBm	DH5_, GHz FGainLow	Ant1_24	141_1000	D~265	500 10751:44 PHAug 13,2020 TROOD 13,4 5 6 TROOD 13,4 5 6 T	Center Free 13.75000000 GH2 Stop Free 26.5000000 GH2 CF Step 2.5500000 GH2 CF Step 2.55000000 GH2 CF Step 2.5500000 GH2 CF Step 2.55000000 GH2 CF Step 2.55000000 GH2 CF Step 2.55000000 GH2 CF Step 2.55000000 GH2 CF Step 2.550000000 GH2 CF Step 2.5500000000000 GH2 CF Step 2.5500000000000000000000000000000000		
70.2	Keysight Spectrum Ar R L RF Center Freq 1 10 aB/div Ref C 979 979 -021	Aalyzer - Swept SA 50 a. DC S750000000 (NFE Dffset 9.79 dB 19.79 dBm	DH5_, GHz PRO: Fast ↔ GainLow	Ant1_24	141_1000	D~265	500 1751:44 PHAug 13, 2020 TROOD 11, 23 4 5 6 TROOD 12, 43 5 6	Center Free 13.75000000 GH2 Start Free 1.00000000 GH2 Stop Free 2.55000000 GH2 CF Step 2.55000000 GH3 Mar		
Start 1.00 GHz Stop 26.50 GHz Log Ling #Res BW 100 kHz #VBW 300 kHz Sweep 938.0 ms (30001 pts)	Kaysight Spectrum Ar R L RF Center Freq 1 0 Ref C 10 B/div -0.21	nalyzer - Swept SA So DC NFE DT5est 9.79 dB 19.79 dBm	DH5_, GHz PRO: Fast ↔ FGain:Low	Ant1_24	141_1000	0~265	500 107:51:44 PM Aug 13,2020 TRACE 13,23 4 5 6 TRACE 13,23 4 5 6 TRACE 13,24 5 6 TRACE 13,24 5 6 107:51:44 PM Aug 13,2020 001 PP PP PP 4.068 50 GHz -37.788 dBm 2.1 -0220 dBm 2.1 -0220 dBm	Center Free 13.76000000 GH2 Start Free 1.00000000 GH2 Stop Free 25.5000000 GH2 CF Step 2.55000000 GH2 CF Step 2.55000000 GH2 CF Step 2.55000000 GH2 DF2 CF Step DF2 CF Step DF2 DF2		
Start 1.00 GHz Stop 26.50 GHz Lin #Res BW 100 kHz #VBW 300 kHz Sweep 938.0 ms (30001 pts)	Keysight Spectrum Ar RL RF Center Freq 1 Image: Control of the second s	Nalyzer - Swept SA So DC NFE DT5set 9.79 dB 19.79 dBm	DH5_,	Ant1_24		D~265	500 10753144 PMAug 13,2020 TRACE 13,23 4 5 6 TRACE 13,23 4 5 6 TRACE 13,24 5 6 TRACE 13,24 5 6 TRACE 13,24 5 6 10,14 5 7 7 7 8 8 dBm 0,1 -0.023 dBm	Frequency Auto Tune Center Freq 13.75000000 GH2 Start Freq 1.00000000 GH2 25.50000000 GH2 2.550000000 GH2 Preq Offseq 0 H2		
NSG STATUS	Ku Ref RL RF Center Freq 1 10 dB/div Ref C 10 dB/div 10.2	Nalyzer - Sweet SA S0 0 DC NFE 1 DOFfset 9.79 dB 19.79 dBm	DH5_,	Ant1_24	141_1000	D~265	500 10753144 PM Aug 13, 2020 TRACE 11, 33, 45, 6 TRACE 11, 33, 45, 6 TRACE 11, 33, 45, 6 TRACE 11, 33, 45, 6 10, 15, 45, 6 10, 15, 10, 10, 10, 10, 10, 10, 10, 10, 10, 10	Center Free Auto Tune Center Free 13.75000000 GH2 Start Free 1.00000000 GH2 Stop Free 2550000000 GH2 CF Step 2.55000000 GH2 Freq Offsee 0 H2 Scale Type		
	Keyselft Spectrum Ar RL RF Center Freq 1 0 Ref C 0 Ref C <td>Nalyzer - Sweet SA S0 00 DC NFE DT5600000000 NFE DT5619.79 dB 19.79 dB</td> <td>DH5_,</td> <td>Ant1_24</td> <td>141_1000</td> <td></td> <td>500 1075134 PM Aug 13, 2020 TRACE 11, 3, 4, 5, 6 TRACE 11, 3, 4, 5, 6 TRACE 11, 3, 4, 5, 6 TRACE 11, 3, 4, 5, 6 10, 4, 5, 6, 6, 6 20, 1, 30, 20, 10, 10, 10, 10, 10, 10, 10, 10, 10, 1</td> <td>Center Free Auto Tune Center Free 13.75000000 GH2 Start Free 1.00000000 GH2 Stop Free 25.5000000 GH2 CF Step 2.55000000 GH2 CF Step 2.55000000 GH2 Treeq Offsee 0 H2 Scale Type Log Lin</td>	Nalyzer - Sweet SA S0 00 DC NFE DT5600000000 NFE DT5619.79 dB 19.79 dB	DH5_,	Ant1_24	141_1000		500 1075134 PM Aug 13, 2020 TRACE 11, 3, 4, 5, 6 TRACE 11, 3, 4, 5, 6 TRACE 11, 3, 4, 5, 6 TRACE 11, 3, 4, 5, 6 10, 4, 5, 6, 6, 6 20, 1, 30, 20, 10, 10, 10, 10, 10, 10, 10, 10, 10, 1	Center Free Auto Tune Center Free 13.75000000 GH2 Start Free 1.00000000 GH2 Stop Free 25.5000000 GH2 CF Step 2.55000000 GH2 CF Step 2.55000000 GH2 Treeq Offsee 0 H2 Scale Type Log Lin		



REPORT NO.: 4789585111.1-10 Page 83 of 84

Cert	ter Frea	F 50 Ω 2.48000	0000 GH	łz	SENSE	E:INT	#Avg Type	LIGN AUTO : RMS	07:53:06 I TRA	CE 1 2 3 4 5 6	Frequency
10 di	Re Bidiv R e	f Offset 9.7 ef 29.79 d	NFE PN IFO 9 dB BM	NO:Wide ↔ Sain:Low	≓ Trig: Free R #Atten: 30 d	Run dB	Avg Hold:	100/100 Mkr1 2.	479 84 -0.3	5 5 GHz 78 dBm	Auto Tune
19.8											Center Freq 2.480000000 GHz
9.79					1	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	N.				Start Freq 2.479250000 GHz
-10.2 -20.2		- And a start of the	m					and the second	user Van	h.	Stop Freq 2.480750000 GHz
-30.2	row									- M	CF Step 150.000 kHz <u>Auto</u> Man
-50.2											Freq Offset 0 Hz
Cen #Re:	ter 2.480 s BW 100	0000 GHz kHz		#VBW	/ 300 kHz		s	weep 1.	Span 000 ms	1.500 MHz (1001 pts)	Scale Type ^{Log <u>Lin</u>}
MSG								STATUS			
				DH	5 Ant1	248	30 30	~100	0		
Kej	/sight Spectrum	n Analyzer - Swe	pt SA	DH	5_Ant1	_248	30_30		07:53:15	PM Aug 13, 2020	- 3 ×
Cen	rsight Spectrum	Analyzer - Swe F 50 Ω 515.000	pt SA DC OOO MHz NFE PI IF(DH5 z NO: Fast → Gain:Low	5_Ant1 SENSE Trig: Free R #Atten: 20 d	_248	30_30 #Avg Type Avg Hold:		07:53:15 TRA Th C	MAug 13, 2020 CE 1 2 3 4 5 6 PE M WWWWW ET P P P P P P .86 MHz	Frequency
10 dE	ter Freq 8/div R	n Analyzer - Swe F 50 Ω 515.000 f Offset 9.7 ef 19.79 d	pt SA DC OOO MHz NFE Pt IFC 9 dB Bm	DH5 NO: Fast ↔ Gain:Low	5_Ant1 sense Trig: Free R #Atten: 20 d	_248	30_30 #Avg Type Avg Hold:		0 07:53:15 TRA T t t t t t t t t t t t t t t t t t t	MAug 13, 2020 CE[] 2 3 4 5 6 PE M MET P P P P P P 86 MHz 86 dBm	Frequency Auto Tune Center Freq 515.00000 MHz
10 dE 9.79	sight Spectrum ter Freq 8/div R(a Analyzer - Swe F 50 Ω 515.000 f Offset 9.7 ef 19.79 d	pt SA DC OOO MH2 NFE PIFC IFC 9 dB Bm	DHS NO: Fast	5_Ant1 sense Trig: Free R #Atten: 20 d	_248	AvgType	I~100 Ign auto RMS 10/10	07:53:151 TRA TT tr tr1 826 -38.8	Maug 13, 2020 CE 1 2 3 4 5 6 PP P P P P P 86 MHz 86 dBm	Frequency Auto Tune 515.00000 MHz Start Freq
	right Spectrum ter Freg Re 3/div Re	s Analyzer - Swe F 50 Ω 515.000 f Offset 9.7 ef 19.79 d	pt SA DC OOO MH2 NFE PI IFC 9 dB Bm	DHS	5_Ant1	248	80_30 #Avg Type Avg Hold:	I~100	07:53:15 TRA tr t t t t t t t t t t t t t t t t t t	MAug 13, 2020 CE 12 3 4 5 6 RE MWWWW ET P P P P P P RE O MHZ 866 MHZ 866 dBm	Frequency Auto Tune 515.00000 MHz Start Freq 30.00000 MHz
ске 10 dl 10	sight Spectrum ter Freq 8/div R	a Analyzer - Swe F [50 Ω 515.000 f Offset 9.7 f 19.79 d	pt SA DC DOO MH2 IFC 9 dB Bm	DHS NO: Fast ++ Sain:Low	5_Ant1	248	30_30 #Avg Type Avg Hold:		0 07:53:151 TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI TRAI	MANY 13, 2020 CET 21 2 4 5 6 M WANNEY ET P P P P P P 86 MHz 186 dBm D(1 - 20.38 eben	Center Frequency Center Freq 515.00000 MH2 Start Freq 30.00000 MH2 CF Step 97.000000 MH2
2002 2002 2002 2002 2002 2002 2002 200	right Spectrum	Analyzer - Swe	pt SA DC OOO MHZ NFE PI IFC 9 dB Bm	DH:	5_Ant1	248	80_30 #Avg Type Avg Hold:		0 17753:1515 1787 1 1 1 1 1 1 1 1 1 1 1 1 1	Maug 13, 2020 of [] 2 3 4 5 6 FM WWWWWENT H P P P P P P 86 d Bm D(1 -2039 dbs	Start Frequency Auto Tune Center Freq 515.000000 MHz Start Freq 30.000000 MHz Stop Freq 1.000000000 GHz 97.00000 MHz GCF Step 97.00000 MHz Freq Offset Freq Offset
10 Ke 10 R 10 di 9.79 -0.21 -10.2 -20.2 -30.2 -40.2 -50.2 -50.2 -70.2	sight Spectrum in the spectrum	Analyze - Sw ₹ 50 ± 50 ± 50 ± 50 ± 50 ± 50 ± 50 ± 50	er SA DC DO MH2 WFE PH PH BM BM	DHS 200 Feat	5_Ant1	_248	80_30 #Avg Type Avg Hold:	- 100 Lien Auto RMS Mk	0 10753:1512 TRATE 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10753:1512 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 10755 107555 107555 10755 10755 107555 10755 107555 10755	Maug 13, 2020 OF [1 2 4 5 6 FT] P P P P P 86 dBm D.1 -2030 dBe	Frequency Auto Tune Center Freq Start Freq Stop Freq 1.00000000 HHz CF Step 97.00000 MHz CF Step 97.0000 MHz CF Step 97.00000 MHz CF St
10 di 10 di	anget Spectrum and a	Anayze - Sw F 30 0 5 5 15.000 f Offset 9.7 f 19.79 d angle 1.4 solution f 2 - solution f 2 - solutio f 2 - solutio f 2 - solution f 2 - solutio f	er SA DC DC DO DC DC PC PC PC PC PC PC PC PC PC PC PC PC PC		5_Ant1	_248	80_30	~1000	0 10753:1515 TRUE 10771 8266 -38.6 1 1 1 1 1 1 1 1 1 1 1 1 1	Maug 13, 2020 CE [] 2 3 4 5 6 EM WORKWORK ET P P P P P P 86 d Bm 0.1 -0030 dbs 0.1 -0030 dbs 0.0000 GHz	Frequency Auto Tune Center Freq 515.00000 MHz Start Freq 30.00000 MHz Stop Freq 1.000000000 GHz CF Step 97.00000 MHz CF Step 97.00000 MHz CF Step 97.00000 MHz Scale Type Log Log Lin



REPORT NO.: 4789585111.1-10 Page 84 of 84

Keysight Sp R L Center F	RF 50	Swept SA IΩ DC D0000000 (NFE F	DH5_/	Ant1_ SE	_2480	D_100	D~26: LIGN AUTO : RMS 10/10	07:53:42 PI TRAD TYP DE	MAug 13, 2020 26 1 2 3 4 5 6 PE M	Frequency
10 dB/div	Ref Offset 9	9.79 dB 9 dBm					Mkr	1 4.133 -39.0	95 GHz 04 dBm	Auto Tu
9.79										Center Fr 13.75000000 Gi
-0.21										Start Fre 1.000000000 G
-20.2									DL1 -20.38 dBm	Stop Fr 26.50000000 G
-40.2	¶ 									CF Ste 2.550000000 GI <u>Auto</u> M
-60.2				n er solere geri Al destations and						Freq Offs
-70.2										Scale Ty
Start 1.00 #Res BW	.00 GHz W 100 kHz		#VBW	300 kHz		SI	veep 93	Stop 2 8.0 ms (3	6.50 GHz 0001 pts)	Log

END OF REPORT